ISSN 1998-6688 (Print)
ISSN 2959-8109 (Online)

ҚАЗАҚСТАН-БРИТАН ТЕХНИКАЛЫҚ УНИВЕРСИТЕТІНІҢ

ХАБАРШЫСЫ

HERALD

OF THE KAZAKH-BRITISH TECHNICAL UNIVERSITY

ВЕСТНИК

КАЗАХСТАНСКО-БРИТАНСКОГО ТЕХНИЧЕСКОГО УНИВЕРСИТЕТА

Volume 21, Issue 3
July–September 2024

ҚАЗАҚСТАН-БРИТАН
ТЕХНИКАЛЫҚ УНИВЕРСИТЕТІНІҢ
ХАБАРШЫСЫ

HERALD
OF THE KAZAKH-BRITISH
TECHNICAL UNIVERSITY

ВЕСТНИК
КАЗАХСТАНСКО-БРИТАНСКОГО
ТЕХНИЧЕСКОГО УНИВЕРСИТЕТА

Алматы
№ 3 (70) 2024 г.

Издание зарегистрировано Министерством культуры и информации Республики Казахстан. Свидетельство о постановке на учет СМИ № 9757 – Ж от 03.12.2008 г.

Журнал зарегистрирован в Международном центре по регистрации сериальных изданий ISSN (ЮНЕСКО, г. Париж, Франция)

В журнале публикуются научные статьи на английском, казахском и русском языках по направлениям: компьютерные науки, математические науки, физические науки, нефтегазовая инженерия и геология, экономика и бизнес.

Подписной индекс – 74206

Издается с 2004 года. Выходит 4 раза в год.

УЧРЕДИТЕЛЬ
Казахстанско-Британский технический университет

ISSN 1998-6688 (Print)
ISSN 2959-8109 (Online)

© Казахстанско-Британский технический университет, 2024

Editor-in-chief – **B. Kulpeshov,** Doctor of Physical and Mathematical Sciences, corresponding member of the National Academy of Sciences of the Republic of Kazakhstan, Professor, School of Applied Mathematics of JSC "Kazakh-British Technical University", Almaty, Kazakhstan

EDITORIAL BOARD

Section "Computer science"

Akzhalova A.Zh. - Candidate of Physical and Mathematical sciences, PhD, Professor, School of Information Technology and Engineering of JSC "Kazakh-British Technical University", Almaty, Kazakhstan;
Pak A.A. - Candidate of Technical Sciences, Associate professor, School of Information Technology and Engineering of JSC "Kazakh-British Technical University", Almaty, Kazakhstan;
Samigulina Z.I. - PhD, Professor, School of Information Technology and Engineering of JSC "Kazakh-British Technical University", Almaty, Kazakhstan;
Ilyas Muhammad - PhD, Professor, School of Information Technology and Engineering of JSC "Kazakh-British Technical University", Almaty, Kazakhstan.
Uvalieva I.M. - PhD, Professor at the Faculty of Computer Science, EKTU named after D. Serikbayev, Ust-Kamenogorsk, Kazakhstan

Section "Mathematical Sciences"

Kalmurzayev B.S. - PhD, Associate professor, School of Applied Mathematics of JSC "Kazakh-British Technical University", Almaty, Kazakhstan;
Sudoplatov S.V. - Doctor of Physical and Mathematical Sciences, Chief Researcher, Institute of Mathematics SB RAS; Head of Department, Novosibirsk State Technical University, Novosibirsk, Russia;
Bazhenov N.A. - Candidate of Physical and Mathematical Sciences, Senior Researcher, Institute of Mathematics SB RAS, Novosibirsk, Russia.

Section "Physical Sciences"

Abdirahmanov A.R. - PhD, Assistant Professor JSC "KBTU", Almaty, Kazakhstan; University of Mons, Mons, Belgium;
Beysenkhanov N.B. - Doctor of Physical and Mathematical Sciences, Dean, Professor, School of Materials Science and Green Technologies JSC "KBTU", Almaty, Kazakhstan;
Laifa Boufendi - PhD, Professor, Orlean University, France

Section "Oil and Gas Engineering and Geology"

Ismailov A.A. - Candidate of Technical Sciences, Dean, Professor, School of Energy and Oil and Gas Industry of JSC "Kazakh-British Technical University", Almaty, Kazakhstan;
Korobkin V.V. - Candidate of Geological and Mineralogical Sciences, Professor, School of Geology of JSC "Kazakh-British Technical University", Almaty, Kazakhstan;
Turgazinov I.K. - PhD, Assistant professor, School of Energy and Oil and Gas Industry of JSC "Kazakh-British Technical University", Almaty, Kazakhstan;
Kan Wanli - Professor, School of Petroleum Engineering, China University of Petroleum (East China), Qingdao, PR China;
Sarsenbekuly B. - PhD, Associate professor, School of Energy and Petroleum Engineering of JSC "Kazakh-British Technical University", Almaty, Kazakhstan;
Moldabaeva G.Zh. - Doctor of Technical Sciences, Professor, Department of Petroleum Engineering of K. Turysov Institute of Geology and Petroleum Engineering, KazNTU, Almaty, Kazakhstan.

Section "Economics and Business"

Narbaev T.S. - PhD, Professor, Business School JSC "KBTU", Almaty, Kazakhstan;
Kozhakhmetova A.K. - PhD, Assistant Professor, Business School JSC "KBTU", Almaty, Kazakhstan;
Aldashev A. - Professor, International School of Economics JSC "KBTU", Almaty, Kazakhstan;
Batkeev B.B. - PhD, Assistant Professor, International School of Economics JSC "KBTU", Almaty, Kazakhstan;
Seitkazieva A.M. - Doctor of Economics, Professor/Business School JSC "KBTU", Almaty, Kazakhstan;
Gabriel Castelblanco - PhD, Assistant-Professor, University of Florida, Florida, USA;
Dubina I. - Doctor of Economic Sciences, Professor, Novosibirsk National Research State University (NSU);
Osei-Kyei Robert - PhD, Associate Professor, University of Western Sydney, Penrith, Australia;
Montag Josef - PhD, Senior Lecturer, Charles University, Prague, Czech Republic.

Бас редактор – **Кулпешов Б.Ш.,** ф.-м.ғ.д., ҚР ҰҒА корреспондент-мүшесі, профессор,
«ҚБТУ» АҚ Қолданбалы математика мектебі, Алматы қ., Қазақстан

РЕДАКЦИЯ АЛҚАСЫ

«Компьютерлік ғылымдар» бөлімі

Акжалова А.Ж. - ф.-м.ғ.к, PhD, профессор, «ҚБТУ» АҚ Ақпараттық технологиялар және инженерия мектебі, Алматы қ., Қазақстан;
Пак А.А. - т.ғ.к., қауымдастырылған профессор, «ҚБТУ» АҚ Ақпараттық технологиялар және инженерия мектебі, Алматы қ., Қазақстан;
Самигулина З.И. - PhD, профессор, «ҚБТУ» АҚ Ақпараттық технологиялар және инженерия мектебі, Алматы қ., Қазақстан;
Ilyas Muhammad - PhD, профессор, «ҚБТУ» АҚ Ақпараттық технологиялар және инженерия мектебі, Алматы қ., Қазақстан.
Увалиева И.М. - PhD, компьютерлік ғылымдар факультетінің профессоры, Д. Серікбаев атындағы ШҚТУ, Өскемен қ., Қазақстан

«Математикалық ғылымдар» бөлімі

Калмурзаев Б.С. - PhD, қауымдастырылған профессор, «ҚБТУ» АҚ Қолданбалы математика мектебі, Алматы қ., Қазақстан;
Судоплатов С.В. - ф.-м.ғ.д., профессор, РҒА СБ математика институтының бас ғылыми қызметкері; Новосібір мемлекеттік техникалық университеті, кафедра меңгерушісі, Новосібір қ., Ресей;
Баженов Н.А. - ф.-м.ғ.к., РҒА СБ математика институтының аға ғылыми қызметкері, Новосібір қ., Ресей.

«Физикалық ғылымдар» бөлімі

Әбдірахманов А.Р. - PhD, ассистент-профессор, «ҚБТУ» АҚ, Алматы қ., Қазақстан; Монс университеті, Монс қ., Бельгия;
Бейсенханов Н.Б. - ф.-м. ғ. д., декан, профессор, Материалтану және жасыл технологиялар мектебі «ҚБТУ» АҚ, Алматы қ., Қазақстан;
Laifa Boufendi - PhD, профессор, Орлеан университеті, Франция.

«Мұнай газ инженериясы және геология» бөлімі

Исмаилов А.А. - т.ғ.к., декан, профессор, «ҚБТУ» АҚ Энергетика және мұнай-газ индустриясы мектебі, Алматы қ., Қазақстан;
Коробкин В.В. - геол.-минерал.ғ.к., профессор, «ҚБТУ» АҚ Геология мектебі, Алматы қ., Қазақстан;
Тургазинов И.К. - PhD, ассистент-профессор, «ҚБТУ» АҚ Энергетика және мұнай-газ индустриясы мектебі, Алматы қ., Қазақстан;
Кан Ванли - профессор, Мұнай инженериясы мектебі, Қытай мұнай университеті (Шығыс Қытай), Циндао қ., ҚХР;;
Сарсенбекұлы Б. - PhD, қауымдастырылған профессор, «ҚБТУ» АҚ Энергетика және мұнай-газ индустриясы мектебі, Алматы қ., Қазақстан;
Молдабаева Г.Ж. - тех.ғ.д., профессор, мұнай инженериясы кафедрасы, Қ. Тұрысов атындағы геология және мұнай-газ институты., ҚазҰТУ, Алматы қ., Қазақстан.

«Экономика және бизнес» бөлімі

Нарбаев Т.С. - PhD, профессор, Бизнес мектебі «ҚБТУ» АҚ, Алматы қ., Қазақстан;
Кожахметова А.К. - PhD, ассистент-профессор, Бизнес мектебі, «ҚБТУ» АҚ, Алматы қ., Қазақстан;
Алдашев А. - PhD, профессор, Халықаралық экономика мектебі, «ҚБТУ» АҚ, Алматы қ., Қазақстан;
Баткеев Б.Б. - PhD, ассистент-профессор, Халықаралық экономика мектебі, «ҚБТУ» АҚ, Алматы қ., Қазақстан;
Сейтказиева А.М. - э.ғ.к., профессор, Бизнес мектебі «ҚБТУ» АҚ, Алматы қ., Қазақстан;
Gabriel Castelblanco - PhD, ассистент-профессор, Флорида университеті, Флорида, АҚШ
Дубина И. - э.ғ.д., профессор, Новосибирск ұлттық зерттеу мемлекеттік университеті (НМУ);
Osei-Kyei Robert - PhD, қауымдастырылған профессор, Батыс Сидней университеті, Пенрит қ., Австралия;
Montag Josef - PhD, сениор-лектор, Карлов университеті, Прага қ., Чехия Республикасы.

Главный редактор – **Кулпешов Б.Ш.,** д.ф.-м.н., член-корреспондент НАН РК, профессор, Школа прикладной математики АО «КБТУ», г. Алматы, Казахстан

ЧЛЕНЫ РЕДКОЛЛЕГИИ

Раздел «Компьютерные науки»

Акжалова А.Ж. - к.ф.-м.н., PhD, профессор, Школа информационных технологий и инженерии АО «КБТУ», г. Алматы, Казахстан;
Пак А.А. - к.т.н., ассоциированный профессор, Школа информационных технологий и инженерии АО «КБТУ», г. Алматы, Казахстан;
Самигулина З.И. - PhD, профессор, Школа информационных технологий и инженерии АО «КБТУ», г. Алматы, Казахстан;
Ilyas Muhammad - PhD, профессор, Школа информационных технологий и инженерии АО «КБТУ», г. Алматы, Казахстан.
Увалиева И.М. - PhD, профессор факультета компьютерных наук, ВКТУ им. Д.Серикбаева, г. Усть-Каменогорск, Казахстан

Раздел «Математические науки»

Калмурзаев Б.С. - PhD, ассоциированный профессор, Школа прикладной математики АО «КБТУ», г. Алматы, Казахстан;
Судоплатов С.В. - д.ф.-м.н., профессор, главный научный сотрудник, Институт математики СО РАН; зав. кафедрой, Новосибирский государственный технический университет, г. Новосибирск, Россия;
Баженов Н.А. - к.ф.-м.н., старший научный сотрудник, Институт математики СО РАН, г. Новосибирск, Россия;

Раздел «Физические науки»

Әбдірахманов А.Р. - PhD, ассистент-профессор АО «КБТУ», г. Алматы, Казахстан; Университет Монса, г. Монс, Бельгия;
Бейсенханов Н.Б. - д.ф.-м.н., декан, профессор, Школа материаловедения и зеленых технологий АО «КБТУ», г. Алматы, Казахстан;
Laifa Boufendi - PhD, профессор, Университет Орлеана, Франция.

Раздел «Нефтегазовая инженерия и геология»

Исмаилов А.А. - к.т.н., декан, профессор, Школа энергетики и нефтегазовой индустрии АО «КБТУ», г. Алматы, Казахстан;
Коробкин В.В. - к.геол.-минерал.н., профессор, Школа геологии АО «КБТУ», г. Алматы, Казахстан;
Тургазинов И.К. - PhD, ассистент-профессор, Школа энергетики и нефтегазовой индустрии АО «КБТУ», г. Алматы, Казахстан;
Кан Ванли - профессор, Школа нефтяной инженерии, Китайский нефтяной университет (Восточный Китай), г. Циндао, КНР;
Сарсенбекұлы Б. - PhD, ассоциированный профессор, Школа энергетики и нефтегазовой индустрии АО «КБТУ», г. Алматы, Казахстан;
Молдабаева Г.Ж. - д.тех.н., профессор, кафедра нефтяной инженерии, Институт геологии и нефтегазового дела им. К. Турысова, КазНТУ, г. Алматы, Казахстан.

Раздел «Экономика и бизнес»

Нарбаев Т.С. - PhD, профессор, Бизнес-школа АО «КБТУ», г. Алматы, Казахстан;
Кожахметова А.К. - PhD, ассистент-профессор, Бизнес-школа АО «КБТУ», г. Алматы, Казахстан;
Алдашев А. - PhD, профессор, Международная школа экономики АО «КБТУ», г. Алматы, Казахстан;
Баткеев Б.Б. - PhD, ассистент-профессор, Международная школа экономики АО «КБТУ», г. Алматы, Казахстан;
Сейтказиева А.М. - д.э.н., профессор, Бизнес-школа АО «КБТУ», г. Алматы, Казахстан;
Gabriel Castelblanco - PhD, ассистент профессора, Университет Флориды, Флорида, США.
Дубина И. - д.э.н., профессор, Новосибирский национальный исследовательский государственный университет (НГУ);
Osei-Kyei Robert - PhD, ассоциированный профессор, Университет Западного Сиднея, г. Пенрит, Австралия;
Montag Josef - PhD, сениор-лектор, Карлов университет, Прага, Чешская Республика.

МАЗМҰНЫ – СОДЕРЖАНИЕ

1 КОМПЬЮТЕРЛІК ҒЫЛЫМДАР
КОМПЬЮТЕРНЫЕ НАУКИ

Samigulina Z.I., Koyanbayeva D.E.
Modernization of the water purification system for sewage treatment plants using schneider electric equipment 10
Zhumabayeva N., Mezin A., Knysheva A.
The impact of gamification with an emphasis on external motivation in MOOCS for students in emerging regions from an underprivileged group: a case study of the LEVEL UP course by GameLab KBTU and UNICEF in Kazakhstan 25
Мамырбаев О.Ж., Павлов С.В., Момынжанова К.Р.
Глаукоманы ерте диагностикалау үшін бұлыңғыр логикаға негізделген сараптамалық жүйе құру 37
Omarov Bauyrzhan.S., Auelbekov O.A., Kulambayev B.O., Omarov B.S.
IIoT network intrusion detection using machine learning on UNSW-NB15 dataset 48
Amanov A.
Enhanced algorithm for computing cayley's first hyperdeterminant 58
Vykhodtseva V.A., Popova G.V.
Application of Machine Learning techniques to increase the level of accuracy of optical character recognition results 66
Базарбеков И.М., Ипалакова М.Т., Дайнеко Е.А., Муханов С.М.
Альцгеймер ауруын диагностикалауға арналған Robo-pen-нің деректерін өңдеу және талдау: Алдын ала нәтижелер 78
Samigulina Z.I., Baikadamova S.S.
The influence of data sampling on solving the problem of pattern recognition for diagnostics of industrial equipment 90
Alimbekova N., Hashim Sh., Zhumadillayeva A., Aiymbay S.
Deep neural networks as a tool for enhancing the efficiency of plastic waste sorting 116
Amanov A.
Computing the degree-4 invariant polynomial basis for 7 qubits 128

2 МАТЕМАТИКАЛЫҚ ҒЫЛЫМДАР
МАТЕМАТИЧЕСКИЕ НАУКИ

Tlepova M., Orynbassar A., Kadyrov S., Shynarbek N.
Complete classification of quadratic irrationals with period two 137
Apseit K., Yessirkegenov N.
Factorizations and unified Hardy inequalities on homogeneous Lie groups 147
Shaikhova G.N., Serikbayev N.S., Burgumbayeva S.K.
Analytical solutions of the nonlocal nonlinear Schrödinger-type equations 158
Искакова Н.Б., Кадирбаева Ж.М., Бакирова Э.А., Қуаныш С.Қ.
Параболалық теңдеу үшін шеттік есепті шешудің сандық әдісі 165
Майер Ф.Ф., Тастанов М.Г., Утемисова А.А., Ысмағұл Р.С.
Об обобщении некоторых классов выпуклых в направлении и типично вещественных функций 176
Асанова А.Т., Бименова Р.А., Минглибаева Б.Б., Сабалахова А.П.
Импульсті дискретті жады бар жоғарғы ретті гиперболалық теңдеу үшін шеттік есеп туралы 191
Вербовский В., Ершигешова А.
Упорядоченная стабильность и обогащения чистого линейного порядка одноместной функцией 201

3 ФИЗИКАЛЫҚ ҒЫЛЫМДАР
ФИЗИЧЕСКИЕ НАУКИ

Шакирзянов Р.И., Труханов А.В., Шлимас Д.И., Зубарь Т.И., Кадыржанов К.К.
Изучение структурных и электромагнитных характеристик композитов ферромагнетик-диамагнетик, полученных методом модифицированного химического осаждения 210
Amirbekova D., Li Y.
Surveying Research Landscapes: Revealing Attributes in the Physical Sciences of Kazakhstan 224
Aimaganbetov K., Abdrakhmanov K., Akatan K., Kuanyshbekov T., Nurlan Almas, Kurbanova B., Kemelbekova A., Tatishvili G.
Study the electrical properties of graphene oxide – nanocellulose composite 236
Murzalinov D., Kemelbekova A., Zhapakov R., Seredavina T., Yelemessov K., Begunov M.
Investigation of various mechanisms of radiative recombination of silicon nitride as an effective way to broadening the photoluminescence spectrum 248
Куватова Д.Б., Ищенко М.В., Берцик П.П., Омаров Ч.Т., Каламбай М.Т.
Влияние ошибок наблюдений по Gaia DR3 на реконструкцию орбит шаровых скоплений на космологической временной шкале 258
Тажен А.Б., Досболаев М.К., Пшиков М.И., Усенов Е.А., Рамазанов Т.С.
Измерение скорости импульсного плазменного потока на установке PW-7 273
Карлина Е.И., Ердеш Е.Б., Баимбетов Д.Б., Джамакеев И.Б., Моханрадж М., Беляев Е.К.
Күн дистилляторы ішіндегі булану және конденсациялану кезіндегі екі фазалық жылу алмасу процестерін сандық модельдеу 281
Кейінбай С., Нусупов К.Х., Султанов А.Т., Тысченко И.Е., Эшанов А.Ф., Бейсенханов Н.Б.
Влияние отношения расходов газов N_2/Ar и мощности магнетрона на плотность и стехиометрический состав пленок TiN_x, синтезированных методом магнетронного распыления 302

4 МҰНАЙ ГАЗ ИНЖЕНЕРИЯСЫ ЖӘНЕ ГЕОЛОГИЯ
НЕФТЕГАЗОВАЯ ИНЖЕНЕРИЯ И ГЕОЛОГИЯ

Tursyngazy D.S., Azizov E.A.
Research methods and geoinformation models of changes in land resources of Almaty region under the influence of household waste 314
Tursunbek Zh.B.
Monitoring the geodynamics of natural and man-made risks of Almaty 322
Insepov D.G.
Development process of a frequency converter for induction heating of oil pipeline 331
Куришбаев А., Габдуллин М., Аманжолова Р., Эм Т., Сагин Ж., Сарсекова Д., Серикканов А., Алиханов К., Аденова Д., Абсаметов М.
Значимость расширения исследований процессов серпентинизации офиолитовых пород по природному «белому» водороду для Казахстана 343
Xing L., Yang H., Li M., Wang G., Jiang H., Wang R., Zhang Yu., Li H., Kang W.
Study on the influencing factors of demulsifier on the oil-water interface viscoelasticity 354

5 ЭКОНОМИКА ЖӘНЕ БИЗНЕС
ЭКОНОМИКА И БИЗНЕС

Abdykhalykov K., Jalmukanova L.
Tools for effective career development management 363
Capone C., Akhlassov Y.S., Ibrayev O.S.
Applications of non-traditional earned value management models in project analytics 374
Tazhiyeva Zh.N., Keser E., Sandykbayeva U.D.
Quality management in high-tech projects using digital marketing technologies in Kazakhstan 384
Saparov T.M., Madeniet R.A., Kaskabassova Ya.S.
The consumption effect of 2007–2008 financial crisis: evidence from commonwealth of independent states 396

CONTENTS

1 COMPUTER SCIENCE

Samigulina Z.I., Koyanbayeva D.E.
Modernization of the water purification system for sewage treatment
plants using schneider electric equipment 10
Zhumabayeva N., Mezin A., Knysheva A.
The impact of gamification with an emphasis on external motivation in MOOCS
for students in emerging regions from an underprivileged group:
a case study of the LEVEL UP course by GameLab KBTU and UNICEF in Kazakhstan 25
Mamyrbayev O.Zh., Pavlov S.V., Momynzhanova K.R.
Development of an expert system based on fuzzy logic
for early diagnosis of glaucoma 37
Omarov Bauyrzhan.S., Auelbekov O.A., Kulambayev B.O., Omarov B.S.
IIoT network intrusion detection using machine learning on UNSW-NB15 dataset 48
Amanov A.
Enhanced algorithm for computing cayley's first hyperdeterminant 58
Vykhodtseva V.A., Popova G.V.
Application of Machine Learning techniques to increase the level of accuracy
of optical character recognition results 66
Bazarbekov I.M., Ipalakova M.T., Daineko E.A., Mukhanov S.B.
Development and Data Analysis of a Robo-pen for Alzheimer's Disease Diagnosis:
Preliminary Result 78
Samigulina Z.I., Baikadamova S.S.
The influence of data sampling on solving the problem of pattern recognition
for diagnostics of industrial equipment 90
Alimbekova N., Hashim Sh., Zhumadillayeva A., Aiymbay S.
Deep neural networks as a tool for enhancing the efficiency of plastic waste sorting 116
Amanov A.
Computing the degree-4 invariant polynomial basis for 7 qubits 128

2 MATHEMATICAL SCIENCES

Tlepova M., Orynbassar A., Kadyrov S., Shynarbek N.
Complete classification of quadratic irrationals with period two 137
Apseit K., Yessirkegenov N.
Factorizations and unified Hardy inequalities on homogeneous Lie groups 147
Shaikhova G.N., Serikbayev N.S., Burgumbayeva S.K.
Analytical solutions of the nonlocal nonlinear Schrödinger-type equations 158
Iskakova N.B., Kadirbayeva Zh.M., Bakirova E.A., Kuanysh S.K.
Numerical method for solving the boundary value
problem for the parabolic equation 165
Maiyer F.F., Tastanov M.G.,Utemissova A.A., Ysmagul R.S.
On the generalization of some classes
of convex in direction and typically real functions 176
Assanova A.T., Bimenova R.A., Minglibayeva B.B., Sabalakhova A.P.
On a boundary value problem for high-order
hyperbolic equation with impulse discrete memory 191
Verbovsky V., Ershigeshova A.
Ordered stability and expansions
of a pure linear order by a unary function 201

3 PHYSICAL SCIENCES

Shakirzyanov R.I., Trukhanov A.V., Shlimas D.I., Zubar T.I., Kadyrzhanov K.K.
Study of the structural and electromagnetic characteristics
of ferromagnetic-diamagnetic composites obtained by the method
of modified chemical co precipitation..... 210
Amirbekova D., Li Y.
Surveying Research Landscapes: Revealing Attributes in the Physical Sciences of Kazakhstan 224
Aimaganbetov K., Abdrakhmanov K., Akatan K., Kuanyshbekov T.,
Nurlan Almas, Kurbanova B., Kemelbekova A., Tatishvili G.
Study the electrical properties of graphene oxide – nanocellulose composite 236
Murzalinov D., Kemelbekova A., Zhapakov R., Seredavina T.,
Yelemessov K., Begunov M.
Investigation of various mechanisms of radiative recombination
of silicon nitride as an effective way to broadening the photoluminescence spectrum..... 248
Kuvatova D., Ishchenko M., Berczik P., Omarov C., Kalambay M.
The influence of observational errors in Gaia DR3 on the reconstruction
of globular cluster orbits on a cosmological timescale..... 258
Tazhen A.B., Dosbolayev M.K., Pshikov M.I., Usenov E.A., Ramazanov T.S.
Measurement of the velocity of pulsed plasma flow at the PW-7 installation..... 273
Karlina Ye., Yerdesh Ye., Baimbetov D., Jamakeyev I., Mohanraj M.
Numerical modeling of two-phase heat transfer during evaporation
and condensation inside a solar still..... 281
Keiinbay S., Nussupov K.Kh., Sultanov A.T., Tyschenko I.E.,
Eshanov A.Ph. Beisenkhanov N.B.
Influence of the ratio of gase consumption N_2/Ar and magnetron
power on the density and stoichiometric composition of TiN_x films
synthesized by magnetron sputtering method..... 302

4 OIL AND GAS ENGINEERING, GEOLOGY

Tursyngazy D.S., Azizov E.A.
Research methods and geoinformation models of changes in land resources
of Almaty region under the influence of household waste..... 314
Tursunbek Zh.B.
Monitoring the geodynamics of natural and man-made risks of Almaty..... 322
Insepov D.G.
Development process of a frequency converter for induction heating of oil pipeline..... 331
Kurishbaev A., Gabdullin M., Amanzholova R., Em T., Sagin J., Sarsekova D, Serikkanov A.,
Alikhanov K., Adenova D., Absametov M.,
The importance of expanding research on the serpentinization
of ophiolite rocks by natural “white” hydrogen for Kazakhstan 343
Xing L., Yang H., Li M., Wang G., Jiang H., Wang R.,
Zhang Yu., Li H., Kang W.
Study on the influencing factors of demulsifier on the oil-water interface viscoelasticity..... 354

5 ECONOMY AND BUSINESS

Abdykhalykov K., Jalmukanova L.
Tools for effective career development management 363
Capone C., Akhlassov Y.S., Ibrayev O.S.
Applications of non-traditional earned value management models in project analytics 374
Tazhiyeva Zh.N., Keser E., Sandykbayeva U.D.
Quality management in high-tech projects using digital marketing
technologies in Kazakhstan..... 384
Saparov T.M., Madeniet R.A., Kaskabassova Ya.S.
The consumption effect of 2007–2008 financial crisis:
evidence from commonwealth of independent states 396

COMPUTER SCIENCE
КОМПЬЮТЕРЛІК ҒЫЛЫМДАР
КОМПЬЮТЕРНЫЕ НАУКИ

UDC 004.896
IRSTI 28.23.27

https://doi.org/10.55452/1998-6688-2024-21-3-10-24

[1]Samigulina Z.I.,
PhD, Professor, Associate Professor, ORCID ID: 0000-0002-5862-6415,
e-mail: z.samigulina@kbtu.kz
[1*]Koyanbayeva D.E.,
Bachelor, ORCID ID: 0009-0003-4955-1292,
*e-mail: d_koyanbaeva@kbtu.kz

[1]Kazakh-British technical university, 050000, Almaty, Kazakhsan

MODERNIZATION OF THE WATER PURIFICATION SYSTEM FOR SEWAGE TREATMENT PLANTS USING SCHNEIDER ELECTRIC EQUIPMENT

Abstract

Currently, the issue of modernization of outdated automatic control systems at strategically important infrastructure facilities of the city, such as water supply and water treatment, is urgent. Using modern automation equipment allows for improving the environmental situation and increasing the reliability of technological processes. This article discusses the development of a new automated system for the biological treatment facility of the Almaty Su sewage treatment plant to replace the outdated current automation. A control system for air conditioning machines, based on Schneider Electric equipment, has been developed using EcoStructure Control Expert software to manage the Modicon M340 controller. Additionally, using EcoStructure Machine Expert, a control system has been created for air injection machines during the biological cleaning phase, which uses the Modicon M241 controller.A process control mnemonic circuit was designed to switch between Modicon M340 and M241 controllers. Remote I/O architectures were developed using the Architecture Builder to create network configurations. An emergency protection system was implemented on Honeywell equipment at Kazakh-British Technical University (KBTU) JSC, using Safety Controller and Manager tools. Security levels at SIL enterprises were calculated.

Key words: water supply, automation system modernization, supercharger, blower, programmable logic controller.

Introduction

Sewerage systems in large cities have an impact on public health and the comfort of life of the population. With an increase in the number of people and a worsening climate, the importance of

modernizing and automating these systems is increasing. The overload of sewer systems during heavy rainstorms also has a significant effect. In many cities in Kazakhstan, the outdated sewage system is hindering operations. It is essential to modernize the sewage treatment system in a timely fashion, as it may later become overloaded, leading to equipment failure and an emergency on the part of the facility.

Wastewater treatment is a complex technological process that takes place in several stages. In the first stage, the water undergoes mechanical cleaning. Drains are directed to grates and sand traps. The grilles are filtering, separating large debris from the stream. Wastewater flows through the vertical plates of the grids, while large inclusions remain in the gaps between the plates. The captured debris is removed using scrapers. After the gratings, sand traps follow at the stage of mechanical cleaning. This stage is designed to purify streams from lighter organic substances. Further, the water enters the primary settling tanks through the "averagers". Following the primary sedimentation tanks, the wastewater enters the stage of biological purification. Biological cleaning involves the use of microorganisms, namely activated sludge. The activated sludge consumes the substrate, that is, it removes the smallest impurities, suspended particles, and fine suspension. Biological cleaning takes place in special tankers «aerotanks». After the activated sludge stage, water purification is carried out at the expense of chemicals. Finally, the water is released into designated water reservoirs.

Literature review

The main task is to develop a water supply system automation system that matches the parameters and structure. Sewage treatment plants are an essential part of this system. The general principles of the automation systems for all industries are similar. It is necessary to create a system that embodies the technology for performing the assigned tasks [1]. In the process of wastewater sedimentation, situations may occur that hinder work. The main problem is the neglect of the influence of flow density. To do this, elements can be installed to control and direct the flow, which will increase deposition [2]. The task of designing and modeling settling tanks is necessary for the development of wastewater treatment systems. It is also necessary to take into account innovations to improve the efficiency of the system [3]. To develop and analyze the structures of wastewater treatment plants, it is important to study a technological concept. The wastewater treatment process follows a step-by-step process to achieve high-quality results. It is necessary to use technologies to clean fine particles to effectively treat wastewater [4].

To develop automation systems, it is necessary to investigate a mathematical model for stability, controllability, and observability [5]. The need for a mathematical model of the selected control object lies in the ability to predict and evaluate the behavior of the process [6]. To analyze mathematical models of a control object, one must master the sections of mathematics widely used in engineering practice [7]. To generate a control signal and analyze deviations from the set value, a PID controller must be integrated into the system [8]. There are various methods of setting up PID controllers, not only well-known, but also completely new algorithms for working with regulators [9]. While studying problems related to regulating a system, a research paper on the creation of a regulator based on fuzzy logic principles was considered [10].

In an article from the Schneider Electric blog, there is indisputable evidence of the need to modernize the systems [11]. The program for the controller's firmware was created using Schneider Electric's EcoStructure Control Expert software [12]. Security system has been created for the designed system and SIL has been calculated [13].

Main provision

The control object and the technological process of water purification

The technological process of water purification involves the stages of mechanical, biological, and chemical cleaning. Biological stage of water treatment takes place in aeration stations, where active sludge located in the aerotanks participate in the process. Activated sludge is a collection of bacteria that participate in wastewater treatment and oxygen supply to the aerotank is necessary for its vital activity. Oxygen enters the aerotank through blowers, with the supercharger being the main component in the blower system.

The supercharger was used as a control object. Superchargers are an important part of cleaning stations, and they are used to provide aeration and air circulation during various cleaning processes. They play a role in supplying air to biological reactors, aerobic biological filters, oxidative recuperators, and other wastewater treatment systems. Blowers help create optimal conditions for the activity of microorganisms and chemical processes, ensuring effective cleaning.

Figure 1 shows a block diagram of the biological stage in water purification. The block diagram was created according to the real scheme from the aeration station.




Figure 1 – Structural diagram of the biological cleaning process

Table 1 shows the parameters of the actual operation of the blower. The data was taken from the Almaty Su aeration station.

Due to the aeration process, oxygen reaches microorganisms. The blowers provide oxygen to the aerators, where it needs to be maintained at a certain level during the wastewater treatment process. The air can be supplied by the blower due to the operation of the supercharger and its electrical motor, gear box, oil tank, and oil cooler (Figure 1).

For the development of the automation system, data from Almaty aeration station and Almaty Su Company were used as a basis. The object of control is a supercharger (Figure 2). Superchargers in wastewater treatment plants, also known as blowers, are devices used to supply compressed air to such plants. These machines are found at the stage of biological treatment of wastewater.

Table 1 – Data of the technological process diagram

Parameter:	Indicator:	Value:
The temperature of the support bearing No. 1 of the supercharger.	TIC-040	52,5 °C
The temperature of the support bearing No. 2 of the supercharger.	TIC-041	52,5 °C
The temperature of the support bearing No. 1 of the reductor.	TIC-042	36,5 °C
The temperature of the support bearing No. 2 of the reductor.	TIC-045	36,5 °C
The temperature of the support bearing No. 3 of the reductor.	TIC-046	36,5 °C
The temperature of the support bearing No. 1 of the electro motor.	TIC-047	56,9 °C
The temperature of the support bearing No. 2 of the electro motor.	TIC-048	45,8 °C
Water temperature parameters for cooling.	TIC-050	42,5 °C
The temperature of the cooling water at the outlet.	TIC-049	44,9 °C
Oil temperature parameters at the oil tank inlet.	TIC-051	45,6 °C
Oil pressure parameters at the oil tank inlet.	PIC-052	0.432 MPa
Oil temperature parameters at the outlet of the oil cooler.	TIC-053	45,5 °C
Oil pressure parameters at the outlet of the oil cooler.	PIC-054	0.186 MPa




Figure 2 – Supercharger and the outlet pipe of the blowers
of the aeration station, Almaty city

Figure 2 – The injection machine and the outlet pipe of the blowers in the aeration station in Almaty for wastewater treatment, the blowers can generate high compressed air pressures. Compressed air is piped into the aerotank. Biological purification uses microorganisms, specifically activated sludge, which needs oxygen (Figure 3).



Figure 3 – Aerotanks for biological water purification
of the Almaty Su enterprise using activated sludge

For the aeration station, it is proposed to develop a modern automation system by replacing outdated equipment. Blower systems still operate on outdated equipment, and the automation system has not been changed since Soviet times.

Materials and methods

Mathematical model of the control object

To analyze and study the control object and to select the coefficients of the regulator, it is necessary to calculate the transfer function's value [5]. The dynamic relationship is expressed using a differential equation. For a first-order system, the differential equation is given by the formula:

$$\frac{dQ_{out}}{dt} + Q_{out} = K\omega_{in} \quad (1)$$

In order to accurately describe the operation of the control system, it is necessary to proceed with the consideration of the transfer model. According to the formula above. Where the important role is played by the variable s that is the Laplace transform variable. Through calculating the ratio of output power to input power in the Laplace domain to obtain the result of the transfer function for the blower:

$$W_p(s) = \frac{Q_{out}(s)}{\omega_{in}(s)} = \frac{K}{\tau s + 1} \quad (2)$$

Define the input and output variables: in ω_{in} – rotational speed of the blower (input); out Q_{out} – airflow rate from the blower (output). Where K – Gain or amplification factor, τ – air blower time constant. From the technical information about the air blower used at the facility, it is known that $K = 5$ and $\tau = 0.2$:

$$W_p(s) = \frac{5}{0.2s + 1} \quad (3)$$

To improve the characteristics of the transient process, the PI controller will be automatically configured using Simulink automatic settings in the MATLAB environment. Due to the automatic adjustment function, the optimal values for the PI controller's coefficients were obtained as follows. The controller's parameters, performance, and reliability are shown in Table 2. Although the rise time and settling time after setting decreased, the overshoot slightly increased due to the integral part's action from the controller and lack of a derivative component.

Table 2 – The main PI controller parameters and characteristics of system

Characteristics of system	Tuned	Block
1	2	3
P	1.0198	1
I	8.4255	1
D	0	0
Rise time	0.0572 sec	0.0863 sec
Settling time	0.341 sec	0.823 sec
Overshoot	8.45 %	0 %
Peak	1.08	0.996
Phase margin	90 deg, 32.2 rad/s	92.5 deg, 29.5 rad/s
Closed-loop stability	Stable	Stable

For a more visual understanding of the behavior of the control system, should be compared different types of controllers: PID (Proportional-Integral-Derivative) and PI (Proportional Integral) controllers. Figure 4 represents the results of a structure diagram with two controllers and a closed control system without any controllers.




Figure 4 – Structure diagram of closed system with PI and PID controllers

There is graph (Figure 5) of the system with PID, PD. On the graph, there is a sharp change in the trajectory of the graph with a polyline in PID controller. The graph of PID controller of has excessive overshoot and long settling time, which negatively impact stability and performance.




Figure 5 – Graphs of comparing closed system with PI and PID controllers

The graph illustrates how the PI controller addresses initial process fluctuations, stabilizing the system to the desired level. Comparative analysis of closed systems, with and without the PI controller, demonstrates improved transient process quality.

Development of the remote I/O architecture using the Architecture Builder software product

Let's consider the architecture of the wastewater treatment process, including mechanical, biological, and chemical treatments, based on Schneider Electric equipment controlled by a Modicon M340 controller. Figure 6 shows remote I/O devices configured to communicate with the controller using Modbus communication modules.




Figure 6 – Implementation of the wastewater treatment system on the M340 controller

Table 3 shows a fragment of the specification of the modules of the main bus of the M340 controller. In addition to the processor module and the power supply, only communication modules are located on the controller bus.

Table 3 – Specification of the M340 controller modules on the main bus

Reference	Description of the module	Location	Quantity
BMEXBP0800	Backplane X80 8 slots ethernet	Process Control/PLC	1
BMXP342020	M340 CPU Level 2 – Modbus / Ethernet	Process Control/PLC	1
BMXCPS2000	X80 AC Power Supply Module, 100…240 V AC, 20W	Process Control/PLC	1
BMXNOC0401	M340 I/O Scanner Module, Ethernet/IP & Modbus TCP, 4 ports	Process Control/PLC	2

Table 4 shows a fragment of the specification of modules for mechanical water purification.

Table 4 – Fragment of modules for the distributed location «Mechanical cleaning»

Reference	Description of the module	Location	Quantity
STBNIP2311	STB Network Interface module, Ethernet/IP & Modbus TCP, 2 ports	Process Control/ Mechanical cleaning	1
STBPDT3100K	STB Standard Power Supply Module, 24 VDC	Process Control/ Mechanical cleaning	2
STBACO8220K	STB Standard Analog HART Output Module, 2 channels, isolated, Current	Process Control/ Mechanical cleaning	3
…	…	…	…

Table 5 contains a fragment of the equipment specification at the «Biological cleaning» stage.

Table 5 – Fragment of the modules for the distributed location «Biological cleaning» specification

Reference	Description of the module	Location	Quantity
STBNIP2311	STB Network Interface module, Ethernet/ IP & Modbus TCP, 2 ports	Process Control/Biological cleaning	1
STBPDT3100K	STB Standard Power Supply Module, 24 VDC	Process Control/Biological cleaning	1
STBACO8220K	STB Standard Analog HART Output Module, 2 channels, isolated, Current	Process Control/Biological cleaning	1
TSXCDP1001	Pre-wired cable with HE10 connector at one end and flying leads at the other end – 10m	Process Control/Biological cleaning	8
…	…	…	…

The modules and accessories that will be used in the design of the chemical cleaning system are shown in Table 6.

Table 6 – Fragment of the modules for the distributed location «Chemical cleaning»

Reference	Description of the module	Location	Quantity
STBNIP2311	STB Network Interface module, Ethernet/IP & Modbus TCP, 2 ports.	Process Control/ Chemical cleaning	1
STBPDT3100K	STB Standard Power Supply Module, 24 VDC.	Process Control/ Chemical cleaning	1
ABE7CPA21	Telefast Sub-base – Analog Output – 4 channels, 2-4 isolated terminals per channel, Screw connectors.	Process Control/ Chemical cleaning	2
…	…	…	…

The most recent stage of cleaning is sludge processing. The active sludge purifies the water. Silt helps to remove trace elements, nitrogen and phosphorus compounds, and organic substances from the water. For the distributed location «Sludge processing», modules were used in the configuration of the hardware, the list of which is shown in table 7.

Table 7 – Specification fragment of modules for the distributed location «Sludge processing»

Reference	Description of the module	Location	Quantity
STBNIP2311	STB Network Interface module, Ethernet/IP & Modbus TCP, 2 ports	Process Control/ Sludge processing	1
STBPDT3100K	STB Standard Power Supply Module, 24 VDC	Process Control/ Sludge processing	2
STBACO8220K	STB Standard Analog HART Output Module, 2 channels, isolated, Current	Process Control/ Sludge processing	2
…	…	…	…

Results and discussion

The results of modeling and experiments were conducted on the basis of real industrial equipment in the laboratories of SHITI and KBTU JSC.

Development of a cascade control system for the modernization of the treatment plant system.

The control system has been developed to control the main parameters of blowers. The process control mnemonic is shown in Figure 7. The hardware includes a Modicon M340 controller and a series of Modicon 241 controllers, which control Machines 1, 2, and 3. This panel provides access to subordinate controller operations.




Figure 7 – Mnemonic scheme for cascade control
of the water purification process with M340 and M241 controllers

Figure 8 shows the mnemonic scheme control circuit of the blower control line. The machine is controlled by the M241 small automation controller.




Figure 8 – Mnemonic scheme of the blower segment control system

The mnemonic scheme for controlling the lines of Machine 2, Machine 3 has an interface similar to Figure 8, Machine 1. The difference is in the names of tags and control components of the program.

Figure 9 shows a fragment of a mnemonic scheme for the implementation of the PI control system by a supercharger. The adjustment coefficients of the regulator and the main parameters of the system are shown.




Figure 9 – Implementation of the PI regulation
system in the EcoStructure Control Expert environment

The Modicon M340 controller is controlled using the EcoStructure Control Expert software product in Structured Text language. The software implementation of machine management using Modicon M241 was carried out using the EcoStructure Machine Expert software product in the LD language.

SIL calculation for a blower system at the aeration station

Special methods should be used to calculate SIL of the system. First of all, it is necessary to calculate the value of the failure rate of the system. The symbol (lambda) in reliability engineering is the value of the failure rate of a system. Failure rate is a parameter of the system that indicates the expected rate at which system failures occur per unit of time.

The average fault detection time (MTTFD) represents the idea of the effectiveness of monitoring and computing systems with respect to detected failures. The failure detection rate is similar to the failure rate [13]:

$$\lambda = \frac{1}{MTTF^D} \tag{4}$$

To determine the PFD^{avg} of the individual components. It is necessary to use the following formula to calculate the PFD^{avg} [13]:

$$PFD_{avg} = 1 + \frac{e^{-\lambda TI} - 1}{\lambda TI} \tag{5}$$

For the sake of simplicity, let's take the value of TI (Testing Interval) as 8760 hours from ISA-TR84.00.02-2002 – Part 3 [13].

To find the PFD of all events in a control system was used the value of PFD^{avg} via Boolean logic [13].

$$PFD = \prod_i PFD^{avr[i]} \tag{6}$$

$$PFD = 0.996 * 0.995 * 0.994 * 0.995 * 0.989 = 0.0969 \quad (7)$$

RRF calculation. The Risk Reduction Factor (RRF) is used in the context of safety instrumented systems (SIS):

$$RRF = \frac{1}{PFD} \quad (8)$$

$$RRF = \frac{1}{0.0969} = 10.32 \quad (9)$$

Analyzing the results obtained by the RRF and PFD, it is worth concluding that the system has a SIL 1 level. The Risk Reduction Factor (RRF) for SIL 1 is in the range of 10 to 100. The PFD value for SIL 1 is between 0.1 and 0.01.

Development of an emergency protection system based on Honeywell equipment

In this work, a special concept was used to control the exhaust valve from the supercharger in order to create the safety of the blower system. The logic of «2oo3» is shown in the Figure 10 below. The «2oo3» logic demonstrates the importance of following safety measures in order to reduce the risk of failure and increase safety. If one safety measure fails, two additional measures will be applied to prevent or minimize potential harm.




Figure 10 – Supercharger valve control by logic “2oo3”

Inputs to the system are 3 temperature indicators for the supercharger. If two of them indicate «true», it means that there are no errors, then the valve should be opened. The concept of «2 out of 3 safety» is often used in high-risk industries or situations where a single safety measure may not provide sufficient protection.

Conclusion

Modernization of automatic control systems at strategically important facilities, such as sewage treatment plants, is necessary. The state of automation affects the efficiency and functionality of the treatment plant’s system. The issue of improving automated systems is acute, particularly with an ever-growing population in cities. Reconstructing outdated control cabinets is significant. The condition of urban water supply systems has an impact on citizens’ well-being.

The article conducted research into the development of a new automated aeration system (biological cleaning station) for the Almaty Su company. At present, the operation of air blower machines on the aeration station depends on outdated control cabinets that operate on relays. During

the research, a structure was created for controlling air blower machines using Schneider Electric software. A control system for the air blower machine was established, and the configuration of the network and architecture of the system were implemented.

The technological process of water purification involves a stage of biological treatment, which takes place at an aeration station. Biological treatment is impossible without the use of activated sludge, which requires oxygen. Oxygen is provided by a blower system. The basic principle of air blower systems is the use of a supercharger. Therefore, the supercharger was chosen as the subject of study. The analysis of the operation of the blower system also includes the development of a mathematical model. During this process, PI controller was designed, resulting in better performance compared to a system with or without PID controller.

For the safety of the air blower system, a safety system has been developed according to the «2oo3» logic. The safety system must prevent false operation of the compressed air supply to the air tanks.

The problem of developing and designing modernized automation systems must be solved before outdated equipment fails. Automated systems at strategically important facilities and enterprises must comply with all applicable standards and function promptly.

REFERENCE

1 Sardarova I., Mustafazade T. Control system for wastewater treatement process, Proc. of the occupational helath and industrial safety (December, 2023), pp. 35–46.

2 Shavkunov M.L., Lekomtsev PL., Korepanov A.S, Gavrilov R.I. Methods of air disinfection in livestock premises with a combination device. IOP Conference Series Earth and Environmental Science, 2022, vol. 949 (1), no. 012118, pp. 1–6.

3 Zamparas M.G., Kyriakopoulos G.L. Novel Materials and Water Purification: Towards a Sustainable Future (Royal Society of Chemistry, 2024), 377 p.

4 Dyagelev M.U. The review of aeration systems for biological wastewater treatment. IOP Conf. Ser.: Earth Environ, 2021, pp. 1–7.

5 Gong G., Sheng L., Zhou D. Robust fault-tolerant stabilisation of uncertain high-order fully actuated systems with actuator faults. International Journal of Systems Science, 2024, pp. 1–8.

6 Thuan D.D., Son N.H. Stability of stochastic differential-algebraic equations with delay. International Journal of Systems Science, 2024, pp. 1–6.

7 Ranjbarpur H., Atrianfar H., Menhaj M.B. LQR controller design for affine LPV systems using reinforcement learning, International Journal of Systems Science, 2024, pp. 1–7.

8 Miguel-Escrig O., Romero-Pérez J. Event-based discrete PI controllers robustness analysis through sampled describing function technique. International Journal of Control, 2024, vol. 97, no. 1, pp. 86–100.

9 Wang L., Visioli A. Introduction to the special issue on PID control system design, automatic tuning and applications. International Journal of Control, 2024, vol. 97, no. 1, pp. 1–7.

10 Borase R.P., Maghade D.K., Sondkar S.Y. et al. A review of PID control, tuning methods and applications. Int. J. Dynam. Control., 2021, vol. 9, pp. 818–827.

11 Panasuik E. How modernizing control systems can reduce business risk and deliver profit improvement. Schneider Electric., 2024.

12 EcoStruxure™ Control Expert PLC Simulator Original instructions. Schneider Electric, 2024.

13 ISA-TR84.00.02-2020 Safety Instrumented Functions (SIF). Instrumentation, Systems and Automation Society, Research Triangle Park, USA, 2020.

[1]Самигулина З.И.,
PhD, профессор, доцент, ORCID ID: 0000-0002-5862-6415,
e-mail: z.samigulina@kbtu.kz
[1]*Коянбаева Д.Э.,
бакалавр, ORCID ID: 0009-0003-4955-1292,
*e-mail: d_koyanbaeva@kbtu.kz

[1]Қазақстан-Британ техникалық университет,
050000, Алматы қ., Қазақстан

SCHNEIDER ELECTRIC ӨНДІРУШІСІНІҢ ЖАБДЫҚТАРЫН ПАЙДАЛАНА ОТЫРЫП АҒЫНДЫ СУЛАРДЫ ТАЗАРТУ ҚОНДЫРҒЫЛАРЫНДАҒЫ СУДЫ ТАЗАРТУ ЖҮЙЕСІН ЖАҢАРТУ

Аңдатпа

Қазіргі уақытта сумен жабдықтау және су тазарту сияқты қаланың стратегиялық маңызды инфрақұрылымдық объектілерінде ескірген автоматты басқару жүйелерін жаңғырту өзекті мәселелердің бірі. Заманауи автоматтандыру құралдарын пайдалану экологиялық жағдайды жақсартуға және технологиялық процестің сенімділігін арттыруға мүмкіндік береді. Бұл мақалада «Алматы Су» кәсіпорнының кәріз тазарту құрылысының биологиялық тазарту станциясын автоматтандыруға арналған жаңа жүйені әзірлеу қарастырылған. Жүйені әзірлеу барысында Schneider Electric компаниясының жабдықтары, атап айтқанда, Modicon M340 сериялы контроллерді басқаруға арналған Ecostructure Control Expert бағдарламалық өнімі қолданылды. Осы құралдардың көмегімен ауа айдау машиналарын басқару жүйесі жасалды. Сондай-ақ, Modicon M241 контроллері негізінде ауа айдау машинасын басқару жүйесі Ecostructure Machine Expert бағдарламалық өнімі арқылы жобаланды. Modicon M340 және Modicon M241 контроллерлері арасындағы ақпарат алмасу негізінде процесті басқарудың мнемотехникалық схемасы әзірленді. Желі конфигурациясын жасау үшін Architecture Builder құралының көмегімен қашықтан енгізу-шығару архитектурасы жасалды. Авариядан қарсы қорғау жүйесі ретінде ҚБТУ АҚ-дағы Honeywell компаниясының жабдықтары негізінде Safety Controller және Safety Manager құралдары қолданылды. Сонымен қатар, кәсіпорындағы қауіпсіздік деңгейлері, атап айтқанда SIL деңгейлері есептелді. Бұл жаңа жүйенің енгізілуі кәріз тазарту станциясының жұмысын едәуір жақсартып, автоматтандыру деңгейін көтеруге мүмкіндік береді, бұл өз кезегінде қаланың экологиялық жағдайына оң әсер етеді.

Тірек сөздер: сумен жабдықтау, автоматика жүйесін жаңарту, айдау машинасы, үрлегіш, бағдарламаланатын логикалық контроллер.

[1]Самигулина З.И.,
PhD, профессор, доцент, ORCID ID: 0000-0002-5862-6415,
e-mail: z.samigulina@kbtu.kz
[1]*Коянбаева Д.Э.,
бакалавр, ORCID ID: 0009-0003-4955-1292,
*e-mail: d_koyanbaeva@kbtu.kz

[1]Казахстанско-Британский технический университет,
050000, г. Алматы, Казахстан

МОДЕРНИЗАЦИЯ СИСТЕМЫ ОЧИСТКИ ВОДЫ НА ОЧИСТНЫХ СООРУЖЕНИЯХ СТОЧНЫХ ВОД С ИСПОЛЬЗОВАНИЕМ ОБОРУДОВАНИЯ ПРОИЗВОДИТЕЛЯ SCHNEIDER ELECTRIC

Аннотация

В настоящее время является актуальным вопрос модернизации устаревших систем автоматического управления на стратегически важных объектах инфраструктуры города, таких как водоснабжение и водоочистка. Использование современных технических средств автоматики позволяет добиться улучшения эко-

логической ситуации и повысить надежность работы технологического процесса. Статья посвящена разработке новой системы автоматизации станции биологической очистки канализационного очистного сооружения предприятия «Алматы Су» для замены текущей устаревшей автоматики. Разработана система управления воздухонагнетательными машинами на основе оборудования фирмы Schneider Electric с помощью программного продукта EcoStructure Control Expert для управления контроллером серии Modicon M340. С помощью программного продукта EcoStructure Machine Expert разработана система управления воздухонагнетательной машиной на основе контроллера Modicon M241. Спроектирована мнемосхема управления процессом с переключением между контроллерами Modicon M340 и Modicon M241. Разработана архитектура удаленного ввода–вывода с помощью инструмента Architecture Builder для создания конфигурации сети. Представлена система противоаварийной защиты на оборудовании фирмы Honeywell при АО КБТУ с использованием инструментов Safety Controller, Safety Manager. Рассчитаны уровни безопасности на предприятии – SIL.

Ключевые слова: водоснабжение, модернизация системы автоматики, нагнетательная машина, воздуходувка, программируемый логический контроллер.

Article submission date: 09.02.2024.

UDC 374.1
IRSTI 14.15.23

https://doi.org/10.55452/1998-6688-2024-21-3-25-36

[1]*Zhumabayeva N.,
Junior researcher, ORCID ID: 0000-0003-3477-2781,
*e-mail: n.zhumabayeva@kbtu.kz
[1]Mezin A.,
Senior researcher, ORCID ID: 0009-0005-5195-7392,
e-mail: a.mezin@kbtu.kz
[1]Knysheva A.,
Master of Arts in Media Studies, ORCID ID: 0000-0001-6644-7778,
e-mail: a.knysheva@kbtu.kz

[1]Kazakh-British Technical University, 050000, Almaty, Kazakhstan

THE IMPACT OF GAMIFICATION WITH AN EMPHASIS ON EXTERNAL MOTIVATION IN MOOCS FOR STUDENTS IN EMERGING REGIONS FROM AN UNDERPRIVILEGED GROUP: A CASE STUDY OF THE LEVEL UP COURSE BY GAMELAB KBTU AND UNICEF IN KAZAKHSTAN

Abstract

This paper examines the impact of gamification and external motivation on the engagement and completion rates of Massive Open Online Courses (MOOCs), with a focus on underprivileged groups in emerging regions. The research centres around the "LEVEL UP" course, a gamified MOOC designed to enhance STEM skills among young women in Kazakhstan, developed by GameLab KBTU in collaboration with UNICEF. Utilizing a combination of quantitative data analysis and literature review, the study investigates the efficacy of gamification strategies in increasing course completion rates, which are traditionally low in MOOCs. The findings indicate that the inclusion of gamification and external motivational elements, such as competitive elements and rewards, can improve completion rates. The LEVEL UP course, for example, achieved a completion rate of 10%, which is higher than the average completion rate of MOOC courses, which 5–8%. However, the study also highlights the complexity of balancing external and internal motivational factors to sustain long-term engagement and deep learning. Limitations encountered, including technical issues and platform constraints, underline the challenges of implementing such strategies effectively. Recommendations for further research include exploring the long-term impact of gamification, the optimal balance of motivational elements, and the customization of gamification to individual learner needs. This paper contributes to the growing body of evidence supporting the use of gamification in education, emphasizing the need for nuanced approaches that enhance both engagement and learning outcomes, particularly in the context of democratizing education for learners worldwide.

Key words: gamification, massive open online courses (MOOCs), external motivation, STEM education, underprivileged groups, emerging regions, course completion rates.

Introduction

The burgeoning utilization of Massive Open Online Courses (MOOCs) has become a transformative vector in disseminating knowledge, especially within underprivileged groups in emerging regions. Such online educational platforms promise a democratization of learning, potentially reaching vast numbers of students. However, a significant challenge emerges in the form of course completion rates; traditional, non-gamified MOOCs see completion rates languishing below 10% [5, 17, 18]. This paper posits gamification, with a focus on external motivation, as a potential solution to enhance student engagement and course completion. This paper will examine the efficacy of gamification with an emphasis on external motivation through the lens of the LEVEL UP project data, evaluating its impact on the completion rate of the course.

Literature review

Gamification in Informal Education

Gamification is the application of game design elements in non-game contexts. [1, 2, 3, 4, 13, 20] Research shows that gamification helps to increase students' learning engagement and motivation [1].

The application of gamification in non-formal education, including online platforms, significantly improves student satisfaction, enjoyment of the learning process and intention to participate in future activities, and positively affects knowledge acquisition [2].

Despite the positive results of gamification in MOOCs, the paper also identifies several research gaps, particularly the focus on developed countries [2, 21, 22, 23, 24] and the lack of evidence regarding gamification's effectiveness in developing country contexts. This oversight becomes even more critical considering that learners from developing countries tend to have lower MOOC completion rates [7, 8], highlighting an urgent need for research and targeted interventions to bridge these educational disparities. Additionally, further research is essential to understand how external motivation can be effectively integrated within gamified learning environments [12].

This paper emphasizes the need for comprehensive research on the effects of gamification on MOOCs for students from underprivileged groups in developing regions. It is particularly important to examine how external motivational factors integrated into gamified MOOCs can influence learning engagement, motivation and academic success.

MOOC as a means of informal education in emerging regions

Massive Open Online Courses (MOOCs) have transformed the landscape of education, offering scalable and accessible learning opportunities worldwide. In emerging regions, MOOCs play a pivotal role in bridging educational gaps and providing informal education to underprivileged groups, facilitating skill development and lifelong learning.

Studies emphasize the importance of digital competencies for the successful completion of MOOCs, highlighting that individuals with higher digital skills are more likely to complete courses. This underscores the digital divide in emerging regions, where limited access to technology and internet connectivity can hinder the effectiveness of MOOCs [5].

The social aspect of MOOCs, including peer interactions and community engagement, is critical for learner retention and success. This dimension is especially significant in emerging regions, where educational resources are scarce, and MOOCs can provide a sense of community and shared learning experience [6].

While MOOCs offer considerable opportunities for informal education in emerging regions, challenges remain in maximizing their impact. There is a need for more targeted research on effective strategies to support learners from underprivileged backgrounds, ensuring that MOOCs are not only accessible but also inclusive and equitable.

This review highlights the complex interplay between technology, social factors, and educational outcomes in the context of MOOCs in emerging regions. By addressing the identified gaps, future research can contribute to the development of more effective, contextually appropriate MOOC offerings that truly democratize education for all learners, regardless of their geographical or socio-economic status.

External motivation in informal education

External motivation, as conceptualized within the framework of Self-Determination Theory (SDT), plays a crucial role in informal education settings, particularly in the context of gamification. Unlike internal motivation, which stems from an individual's internal desires and interests [10], external motivation involves external rewards or pressures [9, 11] that influence an individual's engagement in learning activities [12]. This segment of the literature review focuses on the role

of external motivation in enhancing learning experiences and outcomes in informal educational contexts.

A critical examination of gamification practices reveals a common misapplication of motivational strategies, where excessive reliance on external rewards may undermine internal motivation, potentially leading to decreased long-term engagement [13].

Research on gamification design grounded in SDT suggests that while external motivators can be effective in initiating engagement, they should be carefully balanced with strategies that support autonomy, competence, and relatedness to foster internal motivation [12].

Studies have highlighted the nuanced impact of external motivation on learning, indicating that while it can drive initial participation, its effectiveness in sustaining engagement and promoting deep learning is limited. This underscores the importance of integrating external motivators with internal motivational elements [10].

The literature on external motivation in informal education underscores a complex interplay between external rewards and internal desires. While external motivators are effective in drawing learners into educational activities, their potential to detract from the internal value of learning poses a significant challenge. Furthermore, there is a gap in understanding how external motivators can be optimally designed to complement rather than detract from internal motivation, particularly in gamified learning environments.

There is also a need for empirical research focused specifically on the impact of external motivation in informal education settings, such as MOOCs or gamified learning platforms, especially in emerging regions or among underprivileged groups. Such studies could provide deeper insights into how external rewards influence learner engagement and achievement in these contexts.

This review highlights the critical need for a balanced approach to incorporating external motivation in informal education, emphasizing the design of motivational strategies that not only attract learners but also support their internal motivation and foster meaningful engagement with the learning material. By addressing these gaps, future research can contribute to more effective and sustainable educational practices that leverage external motivation to enhance, rather than undermine, the learning experience.

Underprivileged groups and emerging regions

The term “underprivileged groups” refers to social groups that face systemic barriers to accessing resources, opportunities, and rights. These barriers may be related to economic status, race, ethnicity, gender, or place of residence [27]. Women are often included in this category because of historical gender stereotypes and discrimination that limit their access to quality education and professional opportunities, especially in male-dominated fields such as Science, Technology, Engineering, and Mathematics [28].

The concept of “emerging regions” refers to geographic and economic areas that are on the path to rapid socio-economic development but still face key challenges in education, health, and infrastructure. Kazakhstan, with its rapid economic growth and urbanization, is classified as an emerging region [25, 26].

Studies aimed at analyzing and improving educational opportunities for underprivileged groups in emerging regions like Kazakhstan are of particular importance. They contribute to the development of strategies and approaches that address the unique challenges and needs of these groups, including women seeking STEM education and professional development. Gamification and digital learning technologies can play a key role in increasing motivation, engagement, and learning success among these groups by providing innovative and accessible pathways for learning and professional development. Such research not only helps to narrow educational and professional gaps, but also supports broader goals of social justice and equal opportunity [29].

Research methods

About online course LEVEL UP

The "LEVEL UP: Introduction to Video Games and Gamification" course, developed by GameLab KBTU in collaboration with UNICEF, forms a component of a global initiative to enhance STEM skills among young women. This educational program in game development and gamification is aligned with the broader mission to foster inclusive educational opportunities. The curriculum, designed to be accessible to all interested individuals, culminates in a selection process where 50 exemplary participants are chosen to partake in a three-day hackathon at the KBTU campus in Almaty, Kazakhstan. This event focuses on the gamification of the UniSat educational program, another UNICEF endeavor aimed at assembling nanosatellites, further providing participants with a practical application of their learning and an introduction to potential career paths in STEM. The course's lectures, delivered by KBTU faculty and industry experts, provide a comprehensive overview of the gaming industry, game development processes, and the educational potential of gamification, with a particular focus on the UniSat program as the primary object of gamification. Through this course, students are equipped with the tools to create their own games and explore engaging methods of learning, thereby expanding their skills and opening new vocational avenues.

The course was structured in the format of a Massive Open Online Course (MOOC), embodying distinctive characteristics such as the absence of live interaction with instructors, pivoting instead on an online model for content dissemination. This digital pedagogical approach facilitated a broad-reaching, inclusive educational experience, allowing participants from diverse geographical locations to engage with the curriculum at their own pace. Furthermore, the course content was hosted on the Learning Passport platform [31], a digital learning environment developed in collaboration between UNICEF and its partners.

Participants

The research focuses on the impact of gamification, particularly emphasizing external motivation in MOOCs designed for students in emerging regions of Kazakhstan, targeting underprivileged groups, specifically women. This demographic is critically important due to the global underrepresentation of women in STEM (Science, Technology, Engineering, and Mathematics) fields [14, 15], a disparity more pronounced in developing regions of Kazakhstan.

In 2023, the Global Gender Gap Report highlighted that women constitute only 29.2% of the STEM workforce across 146 nations, compared to nearly 50% in non-STEM occupations, underscoring the significant gender gap in these critical fields. This gap is not just a matter of workforce diversity but also reflects broader issues of access, opportunity, and equity in STEM education and careers for women, particularly in developing and emerging economies [14].

The participants for the LEVEL UP course by GameLab KBTU and UNICEF in Kazakhstan, were chosen aiming to address these disparities by engaging young women from underprivileged backgrounds in STEM-related learning through MOOCs. This initiative recognizes the importance of providing equitable access to quality STEM education as a means to empower women and encourage their participation in these fields, thereby contributing to reducing the gender gap.

Despite the fact that the gaming industry is a young and quite progressive industry when it comes to gender equality, even here women face underrepresentation and some barriers that prevent them from being realized in the industry [15]. Studies and reports, including those analyzing the esports industry, highlight the persistent gender disparities, with women often facing barriers to entry and progression [16]. These barriers are not just about access but also involve cultural and societal norms, stereotypes, and a lack of visible role models and mentors for young women aspiring to enter STEM fields.

By focusing on courses for underprivileged young women in Kazakhstan, this research aims to shed light on the specific challenges and opportunities that gamification and external motivational strategies present in informal educational settings. It seeks to understand how these approaches can

be tailored to effectively engage and retain female students in STEM courses, thereby contributing to broader efforts to build a more inclusive and diverse STEM workforce.

Particularly, participants from emerging regions are at the heart of this initiative, with an appended table below showcasing the cities of those participants who successfully completed the course, further illustrating the geographic diversity and reach of this program within underprivileged demographics.




Figure 1 – Cities of participants and the number of participants from each city

Research design

Structure of course

The “LEVEL UP” course is segmented into three distinct parts, each comprising several sections that are further broken down into units or lessons. The structure is as follows:

Part 1 encompasses a general course overview, an in-depth look at the gaming industry, and the foundational elements of game development. Part 2 transitions into the creative aspects, covering the basics of game design, and extends into the practical applications of serious games and gamification. Part 3 is the technical culmination, providing a detailed exploration of the tools and technologies used in the field, alongside alternative methods and practices. The course concludes with a wrap-up in Section 8.

Table 1 – Course structure and topics

Part 1	Part 2	Part 3
Section 1 Course overview	Section 4 Game Design Basics	Section 6 Tools and Technologies
Section 2 Game Industry	Section 5 Serious Games & Gamification	Section 7 Alternative Techs and Methods
Section 3 Game Development		Section 8 Course wrap up

For successful course completion, students are required to navigate through all three parts. Assignments within the course are designed to be skippable and self-regulated, offering flexibility to accommodate various learning paces and styles. The entire course content is intended to be completed over a two-month period, allowing for a measured yet consistent progression through the material.

Education cycle

The educational methodology of the "LEVEL UP" course is bifurcated into minor and major educational cycles. The minor cycle is the foundational element, comprising a self-regulated assignment leading to a fully automated quiz, ensuring reinforcement of learned concepts. This is supplemented by a richly illustrated article and concluded with a video lecture, offering a multifaceted approach to learning. The major cycle encapsulates the minor cycles, culminating in a comprehensive section quiz that integrates all previously encountered quizzes with additional questions to assess cumulative knowledge. The pinnacle of this structure is the project assignment, which is an integral part of the course project, allowing students to apply their knowledge in a practical, project-based context.




Figure 2 – Education cycle

Elements of gamification

In the "LEVEL UP" course [31], gamification was strategically implemented to enhance engagement through competitive elements, acting as external motivators. The course's structure incorporated a merit-based selection mechanism where the top 50 performers, as evidenced by their course outcomes and certification, were granted the opportunity to participate in a specialized hackathon. This incentivized participation by offering comprehensive logistical support, including transportation to Almaty, accommodation, and sustenance, thereby removing potential barriers to entry.

The post-course hackathon, centered on the gamification of the UniSat nanosatellite assembly and launch course [32], presented a time-bound challenge to devise innovative project ideas. The competitive environment of the hackathon, characterized by its awarding of the best project proposals, not only provided a platform for the practical application of the course's teachings but also served as a powerful external incentive, propelling students towards higher achievement and engagement within the educational framework.

Data analysis

Average completion rates of MOOC

The completion rates for MOOCs have been a focal point of educational research, revealing a broad range of outcomes. Studies show that average completion rates for MOOCs without gamification strategies linger between 5% to 8% [5, 17, 18] underscoring the challenge of keeping students engaged through course completion. However, when gamification strategies are applied, a notable increase is observed, with completion rates rising to an average of 14.43% compared to 6.162% in courses lacking these elements [17].

These findings are primarily based on data from developed countries, which may not fully represent the experiences of underprivileged groups in developing regions such as Kazakhstan. Our study targets this demographic, specifically focusing on young women, to assess whether competitive gamification mechanics emphasizing external rewards can influence completion rates differently.

It is imperative to acknowledge that our research was not conducted under uniform conditions. The course utilized to evaluate the impact of gamification, while distinct from others in its content and objectives, adhered to the Massive Open Online Course (MOOC) format, incorporating its specific attributes as detailed in Section 3.1. This context underscores the necessity to consider the unique structural and delivery mechanisms of MOOCs when interpreting the outcomes of our study.

Completion rates of LEVEL UP course

This section investigates the completion rates of the LEVEL UP course [30], focusing on participants' successful course progression. A total of 500 individuals registered for the course, with completion defined as successfully finishing all three parts of the course and obtaining a certification. Particular attention is paid to the distribution of completions across course segments. Out of the 500 participants, only 50 completed all three parts, resulting in a 10% overall completion rate. Further analysis reveals varying completion rates for each segment, with Part 1 showing the highest rate at 13.6%, followed by Part 2 at 10.2%, and Part 3 at 10%.

Comparison of completion rates of course with external motivation with average completion rates of course without external motivation

In the context of examining the impact of gamification strategies on MOOC completion, analyzing the completion rates of the LEVEL UP course where competitive and external motivation elements were applied compared to the average completion rates of courses without these elements reveals visible differences. Based on the data provided, the average completion rates of MOOCs without gamification strategies fluctuate between 5% and 8%, highlighting the difficulty of keeping students engaged until the end of the course. In contrast, the LEVEL UP course demonstrated a completion rate of 10%, a marked improvement.

This increase in completion rate can be attributed to the implementation of gamification mechanics emphasizing external motivation and competition, which is hypothesized to increase the level of engagement and motivation among students. These findings support the assumption that gamification can serve as a powerful tool to increase course completion rates, especially in MOOC contexts where students may feel less motivated due to the lack of direct interaction and support.

However, it is important to keep in mind that these findings on average MOOC completion rates are predominantly based on studies conducted in developed countries and may not fully reflect the experiences of underprivileged groups in emerging regions such as Kazakhstan. Our study targets this demographic, particularly young women, to assess whether competitive gamification mechanics emphasizing external rewards may affect completion rates differently.

In summary, the results point to the benefit of using gamification elements with external motivation in MOOC courses to increase completion rates among participants. This highlights the potential of gamification as a strategy for improving educational outcomes in digital environments, especially for students from emerging regions and underprivileged groups.

Results

In conclusion, our research underscores the positive impact of gamification, particularly with competitive elements and a focus on external motivation, on the completion rates of MOOC courses, evidenced by at least a 2% increase. This finding is significant within the broader discourse on educational engagement and retention strategies, especially in emerging regions where MOOCs serve as pivotal platforms for democratizing education. The nuanced application of gamification strategies, while beneficial in enhancing course completion, warrants cautious implementation to avoid undermining internal motivation and learner engagement.

Our investigation into the LEVEL UP course reveals that while external motivators can indeed foster initial engagement, their long-term effectiveness in sustaining participation and deep learning remains limited [12]. This aligns with the literature, suggesting that while external rewards can draw learners into educational activities, their potential to detract from the internal value of learning poses a significant challenge [9, 13]. Therefore, a balanced approach, integrating both external and internal motivational elements, is essential for designing effective and engaging educational experiences.

Our study highlights the potential of gamification in the setting of emerging regions, offering insights into strategies that could mitigate the digital divide and promote inclusive and equitable learning opportunities. Carefully designed gamification strategies, which consider the specific needs and challenges of learners in emerging regions, can significantly enhance engagement and completion rates.

Looking ahead, the prospects for using gamification and external motivation in education, particularly in emerging regions, are promising. As we continue to explore these methodologies, it is crucial to adopt a nuanced approach that respects the complex interplay between different motivational drivers. Empirical research focused on diverse contexts, especially among underprivileged groups, will be pivotal in refining our understanding of how gamification can best be utilized to support equitable and engaging learning experiences.

Our findings contribute to the growing body of evidence supporting the efficacy of gamification in education. They underscore the need for ongoing research to optimize gamification strategies, ensuring they not only attract but also retain learners, fostering meaningful engagement and enhancing learning outcomes. As the educational landscape continues to evolve, leveraging the potential of gamification and external motivation in a balanced and thoughtful manner will be key to democratizing education and enabling learners worldwide to realize their full potential.

Discussion

Limitations

This study was subject to several limitations that may have affected its outcomes and interpretations. First, technical difficulties related to platform authentication impeded some students' access to their accounts, resulting in participant dropout. Moreover, the division of the course into three segments, necessitated by platform constraints, marked a departure from its intended design as a unified course. Additionally, platform-related glitches, including the loss of course progress that required students to repeat sections, contributed to student dissatisfaction and further dropout. Furthermore, a limitation of our analysis was the absence of proprietary data on course completion rates in the absence of gamification strategies. Consequently, we resorted to comparing with the average completion rate observed in similar educational settings.

Recommendation for further research

The findings of this study contribute insights into the potential of gamification and external motivation to enhance engagement and completion rates in MOOCs, particularly for underprivileged groups in emerging regions. However, several avenues for further research have emerged, which are crucial for deepening our understanding of these mechanisms and optimizing their application in informal education settings. These recommendations include:

1. Comparative studies across different regions: While this study focused on underprivileged groups in Kazakhstan, further research should explore the impact of gamification in MOOCs across various geographical and socio-economic contexts. Comparative studies could reveal nuanced understandings of gamification's effectiveness, accounting for cultural differences and varying levels of digital literacy.

2. Longitudinal impact of gamification: Investigate the long-term effects of gamification on learner engagement and educational outcomes. This includes studying the sustainability of external

motivation over time and its influence on internal motivation, to determine whether gamified learning leads to lasting interest in the subject matter.

3. Integration of internal and external motivational elements: Future research should explore the optimal balance between internal and external motivational strategies within gamified learning environments. This involves designing gamification elements that not only attract and retain learners but also foster a deeper engagement with the learning material, promoting meaningful and lasting educational experiences.

4. Customization of gamification elements: Examine how personalized gamification strategies can enhance learning experiences and outcomes. Research could focus on adaptive gamification systems that tailor challenges, rewards, and feedback to individual learner profiles, preferences, and performance levels.

5. Barrier analysis and inclusivity measures: Conduct in-depth analyses of barriers to MOOC completion among underprivileged groups, including gender-specific challenges in STEM fields. Studies should aim to identify and address the specific needs and obstacles faced by these learners, proposing targeted strategies to improve access, inclusivity, and equity.

6. Technological enhancements and platform usability: Given the technical challenges encountered in this study, further research is needed to understand the impact of platform usability on learner engagement and course completion rates. This includes the development and testing of more user-friendly and resilient educational platforms that minimize technical barriers to learning.

7. Impact on career trajectories and skill development: Investigate the long-term career and educational impacts of gamified MOOCs on participants, particularly those from underprivileged groups. This research could assess whether participation in such courses leads to improved employment opportunities, skill development, and increased participation in STEM fields.

8. Psychological and social factors: Explore the psychological and social dimensions of gamification in education, including how social interactions, community building, and peer support within MOOCs influence learning motivation and outcomes. This includes studying the role of gamification in fostering a sense of belonging and community among learners from diverse backgrounds.

By addressing these recommendations, future research can significantly contribute to the development of more effective, engaging, and inclusive educational practices that leverage gamification and external motivation. This will not only enhance learning experiences but also support broader efforts to democratize education and empower learners worldwide.

REFERENCES

1 Ibáñez M.-B., Di-Serio, A., and Delgado-Kloos C. IEEE Transactions on Learning Technologies, vol.7, no. 3, pp. 291–301 (July-September 2014). https://doi.org/10.1109/TLT.2014.2329293.

2 Subhash S., and Cudney, E.A. Computers in Human Behavior, 2018, 85, pp. 327–334. https://doi.org/10.1016/j.chb.2018.05.028.

3 Ng L.-K., and Lo C.-K. Sustainability, 2022, 14 (5428), pp. 1–23. https://doi.org/10.3390/su14095428.

4 Leftheriotis I., Giannakos M.N., and Jaccheri L. Smart Learning Environments, 2017, 4(2), pp. 1–19. https://doi.org/10.1186/s40561-017-0041-y.

5 Romero-Rodríguez L.M., Ramírez-Montoya M.S., and Valenzuela González J.R. IEEE Transactions on Education, vol. 63, no. 3, pp. 183–189 (August 2020). https://doi.org/10.1109/TE.2020.2969487.

6 Goglio V., and Parigi, P. Proc. of the Fifth International Conference on Learning with MOOCs (LWMOOCS) (Madrid, 26–28 September 2018), pp. 85–89. https://doi.org/10.1109/LWMOOCS.2018.8534652.

7 Gershon S.K., Ruipérez-Valiente J.A., and Alexandron, G. Int J Educ Technol High Educ, 2021, 18, 41. https://doi.org/10.1186/s41239-021-00275-w.

8 Kizilcec R.F., Saltarelli A.J., Reich J., and Cohen G.L. Science 355(6322), pp. 251–252 (20 January 2017). https://doi.org/10.1126/science.aag2063.

9 Van den Broeck A., Howard J.L., Van Vaerenbergh Y., Leroy H., and Gagné M., Organizational Psychology Review, 2021, vol. 11, no. 1, pp. 1–34. https://doi.org/10.1177/20413866211006173.

10 Niemiec C.P., and Ryan R.M. Theory and Research in Education, 2009, vol. 7, no. 2, pp. 133–144. https://doi.org/10.1177/1477878509104318.

11 Morsink S., Van der Oord S., Antrop I., Danckaerts M., and Scheres A., Journal of Attention Disorders, 2022, vol. 26, no. 8, pp. 1139–1158. https://doi.org/10.1177/10870547211050948.

12 Lamprinou D., Paraskeva F. 2015 International Conference on Interactive Mobile Communication Technologies and Learning (IMCL), 19–20 November 2015, Thessaloniki, Greece, pp. 406–409. https://doi.org/10.1109/IMCTL.2015.7359616.

13 Loughrey K. O Broin D. 2018 IEEE Games Entertainment Media Conference (GEM), 2018. https://doi.org/10.1109/GEM.2018.8516492.

14 Verdugo-Castro S., García-Holgado A., and Sánchez-Gómez M.C., Heliyon 8(e10300), 1–12, 2022. https://doi.org/10.1016/j.heliyon.2022.e10300.

15 Isaaman M.-C., and Tolaini-Sage S. Building a Fair Playing Field, Women in Games. https://www.womeningames.org/wp-content/uploads/2023/04/Building-a-Fair-Playing-Field-2.pdf.

16 Women in Esports, EX CORP., 2022 [Online]. Available: https://excorp.gg/goodenough.

17 Romero-Rodríguez L.M., Ramírez-Montoya M.S., and Valenzuela González, J.R., IEEE Access, 2019, vol. 7, pp. 32093–32101. https://doi.org/10.1109/ACCESS.2019.2903230.

18 Onah D.F.O., Sinclair J., Boyatt R., 2014 6th International Conference on Education and New Learning Technologies (EDULEARN), 7–9 July 2014, Barcelona, Spain, pp. 3238–3247. https://doi.org/10.13140/RG.2.1.2402.0009.

19 Pumilia-Gnarini P.M., Favaron E., Pacetti E., Bishop J., and Guerra L., Handbook of Research on Didactic Strategies and Technologies for Education: Incorporating Advancements, IGI Global, September 2012, 829 p. https://doi.org/10.4018/978-1-4666-2122-0.

20 Krath J., Schürmann L., & von Korflesch H.F.O. Computers in Human Behavior, 2021, vol. 125, 106963. https://doi.org/10.1016/j.chb.2021.106963.

21 Cuevas-Martínez J.C., Yuste-Delgado A.J., Pérez-Lorenzo J.M., & Triviño-Cabrera, A. IEEE Access, 2019, vol. 7, pp. 118125–118134. https://doi.org/10.1109/ACCESS.2019.2932803.

22 Pozo-Sánchez S., Lampropoulos G., & López-Belmonte J. Journal of New Approaches in Educational Research, 2022, vol. 11, no. 2, pp. 307–322. https://doi.org/10.7821/naer.2022.7.1025.

23 Kasahara R., Sakamoto K., Washizaki H., and Fukazawa Y. Proc. of the 2019 ACM Conference on Innovation and Technology in Computer Science Education, July 15–17, 2019, Aberdeen, Scotland UK, pp. 1–7. https://doi.org/10.1145/3304221.3319792.

24 Ortiz M., Chiluiza K., & Valcke M. Proc. of 8th Annual International Conference on Education and New Learning Technologies – Edulearn16, 4th-6th July 2016, Barcelona, Spain, pp. 6548–6549. ISBN: 978-84-608-8860-4.

25 Emerging Countries. World Population Review. https://worldpopulationreview.com/country-rankings/emerging-countries.

26 Developing Countries. World Data Info. https://www.worlddata.info/developing-countries.php.

27 Sen A. Social Exclusion: Concept, Application, and Scrutiny, Social Development Papers No. 1, Office of Environment and Social Development, Asian Development Bank, June 2000. https://www.adb.org/sites/default/files/publication/29778/social-exclusion.pdf

28 Yosso T.J., Race Ethnicity and Education, 2005, vol. 8, no. 1, pp. 69–91, 2005. https://doi.org/10.1080/1361332052000341006.

29 Cheryan S., Ziegler S.A., Montoya A.K. and Jiang, L. Psychol. Bull., vol.143, no. 1, pp. 1–35 (October 2016). https://doi.org/10.1037/bul0000052

30 LEVEL UP course completion rates database https://www.kaggle.com/alexandrmezin/level-up-gamification-course-data-analysis

31 LEVEL UP online course https://kaz.learningpassport.org/#/course/24/item/328

32 UniSat nano-satellite education programme for Girls (UNEPG) https://unisat.kz/

[1]*Жұмабаева Н.,
кіші ғылыми қызметкер, ORCID ID: 0000-0003-3477-2781,
*e-mail: n.zhumabayeva@kbtu.kz
[1]Мезин А.,
аға ғылыми қызметкер, ORCID ID: 0009-0005-5195-7392
e-mail: a.mezin@kbtu.kz
[1]Кнышева А.,
медиа зерттеулер саласындағы өнер магистрі, ORCID ID: 0000-0001-6644-7778,
e-mail: a.knysheva@kbtu.kz

[1]Қазақстан-Британ техникалық университет, 050000, Алматы қ., Қазақстан

ГЕЙМИФИКАЦИЯНЫҢ ДАМУШЫ АЙМАҚТАРДАҒЫ АЗ ҚАМТЫЛҒАН ТОПТАРДАН ШЫҚҚАН СТУДЕНТТЕРГЕ АРНАЛҒАН ЖАОК-ТАҒЫ СЫРТҚЫ МОТИВАЦИЯҒА ӘСЕРІ: ҚАЗАҚСТАНДАҒЫ GAMELAB KBTU ЖӘНЕ UNICEF ҰЙЫМДАРЫНЫҢ «LEVEL UP» КУРСЫНЫҢ ТАҚЫРЫПТЫҚ ЗЕРТТЕУІ

Аңдатпа

Мақалада дамушы аймақтардағы аз қамтылған топтарға арналған жаппай ашық онлайн курстарға (ЖАОК) геймификация мен сыртқы мотивацияның әсері, соның ішінде қатысу деңгейі мен курсты аяқтау көрсеткіштері талданады. Зерттеудің негізгі нысаны – Қазақстандағы жас әйелдерге арналған STEM саласындағы дағдыларды дамыту мақсатында GameLab KBTU мен ЮНИСЕФ-тің бірлесіп әзірлеген геймификацияланған «LEVEL UP» курсы. Сандық деректерді талдау мен әдеби шолуды қолдана отырып, бұл зерттеу геймификация стратегияларының дәстүрлі түрде ЖАОК-та төмен болып келетін курсты аяқтау деңгейін арттырудағы тиімділігін қарастырады. Нәтижелер геймификация мен сыртқы мотивациялық элементтерді, мысалы, бәсекелестік және марапаттау элементтерін енгізу курсты аяқтау көрсеткіштерін жақсартуы мүмкін екенін көрсетеді. Мәселен, «LEVEL UP» курсының аяқталу деңгейі 10%-ға жетті, бұл МООК курстарының орташа аяқталу деңгейінен (5–8%) жоғары. Алайда зерттеу ұзақ мерзімді қатысуды және терең оқуды қолдау үшін сыртқы және ішкі мотивациялық факторлардың тепе-теңдігін сақтаудың күрделілігін де айқындайды. Техникалық мәселелер мен платформаның шектеулері сияқты туындаған қиындықтар мұндай стратегияларды тиімді жүзеге асырудың қиындығын көрсетеді. Болашақ зерттеулерге арналған ұсыныстар геймификацияның ұзақ мерзімді әсерін, мотивациялық элементтердің оңтайлы тепе-теңдігін және геймификацияны оқушылардың жеке қажеттіліктеріне бейімдеуді зерттеуді қамтиды. Бұл жұмыс білім беру саласында геймификацияны қолданудың тиімділігін дәлелдейтін деректер санының артуына үлес қосады, әсіресе оқушыларға білім беруді демократияландыру контекстінде қатысу мен оқу нәтижелерін жақсартуға бағытталған жан-жақты тәсілдердің маңыздылығын көрсетеді.

Тірек сөздер: геймификация, жаппай ашық онлайн курстар (ЖАОК), сыртқы мотивация, STEM білімі, аз қамтылған топтар, дамушы аймақтар, курсты аяқтау көрсеткіштері

[1]*Жумабаева Н.,
младший научный сотрудник, ORCID ID: 0000-0003-3477-2781,
*e-mail: n.zhumabayeva@kbtu.kz
[1]Мезин А.,
старший научный сотрудник, ORCID ID: 0009-0005-5195-7392,
e-mail: a.mezin@kbtu.kz
[1]Кнышева А.,
магистр искусств в области медиаисследований, ORCID ID: 0000-0001-6644-7778,
e-mail: a.knysheva@kbtu.kz

[1]Казахстанско-Британский технический университет, 050000, г. Алматы, Казахстан

ВЛИЯНИЕ ГЕЙМИФИКАЦИИ С АКЦЕНТОМ НА ВНЕШНЮЮ МОТИВАЦИЮ В МООК ДЛЯ СТУДЕНТОВ В РАЗВИВАЮЩИХСЯ РЕГИОНАХ ИЗ МАЛООБЕСПЕЧЕННЫХ ГРУПП НАСЕЛЕНИЯ: ТЕМАТИЧЕСКОЕ ИССЛЕДОВАНИЕ КУРСА LEVEL UP ОТ GAMELAB KBTU И UNICEF В КАЗАХСТАНЕ

Аннотация

В данной статье рассматривается влияние геймификации и внешней мотивации на вовлеченность и уровень завершения массовых открытых онлайн-курсов (МООК) с акцентом на малообеспеченные группы населения в развивающихся регионах. В центре исследования – курс LEVEL UP, геймифицированный МООК, разработанный GameLab KBTU в сотрудничестве с ЮНИСЕФ для молодых женщин Казахстана с целью развития навыков в области STEM. Используя сочетание количественного анализа данных и обзора литературы, в исследовании изучается эффективность стратегий геймификации в повышении уровня завершения курса, который традиционно низок на МООКах. Результаты показывают, что включение геймификации и внешних мотивирующих элементов, таких как соревновательные элементы и вознаграждения, может улучшить показатели завершения курса. Например, курс LEVEL UP достиг уровня завершения в 10%, что выше среднего уровня завершения курсов МООК, который составляет 5–8%. Однако исследование также подчеркивает сложность баланса внешних и внутренних мотивационных факторов для поддержания долгосрочной вовлеченности и глубокого обучения. Возникшие ограничения, включая технические проблемы и ограничения платформы, подчеркивают трудности эффективной реализации таких стратегий. Рекомендации для дальнейших исследований включают изучение долгосрочного воздействия геймификации, оптимального баланса мотивационных элементов и адаптации геймификации к индивидуальным потребностям учащихся. Данная работа вносит вклад в растущее число фактов, поддерживающих использование геймификации в образовании, подчеркивая необходимость применения нюансированных подходов, которые повышают вовлеченность и результаты обучения, особенно в контексте демократизации образования для учащихся во всем мире.

Ключевые слова: геймификация, массовые открытые онлайн-курсы (МООК), внешняя мотивация, STEM образование, малообеспеченные группы, развивающиеся регионы, показатели завершения курсов.

Article submission date: 15.02.2024.

ҒТАМР 28.23.37
ӘОЖ 004.93'14

https://doi.org/10.55452/1998-6688-2024-21-3-37-47

[1]Мамырбаев О.Ж.,
PhD, қауымдастырылған профессор, ORCID ID: 0000-0001-8318-3794,
e-mail: morkenj@mail.ru
[2]Павлов С.В.,
т.ғ.д., ORCID ID: 0000-0002-0051-5560,
e-mail: psv@vntu.edu.ua
[3*]Момынжанова К.Р.,
магистр, ORCID ID: 0000-0002-9981-5706,
e-mail: kymbat_momynzhanova87@mail.ru

[1]Ақпараттық және есептеуіш технологиялар институты, 050000, Алматы қ., Қазақстан
[2]Винница ұлттық техникалық университеті, 21000, Винница қ., Украина
[3]әл-Фараби атындағы Қазақ ұлттық университеті, 050040, Алматы қ., Қазақстан

ГЛАУКОМАНЫ ЕРТЕ ДИАГНОСТИКАЛАУ ҮШІН БҰЛЫҢҒЫР ЛОГИКАҒА НЕГІЗДЕЛГЕН САРАПТАМАЛЫҚ ЖҮЙЕ ҚҰРУ

Аңдатпа

Кескіндерге негізделген шешім қабылдау жүйелерінің қазіргі уақытта медицина саласындағы маңызы артып келеді. Кескіндер клиникалық зерттеулер үшін ауруларды диагностикалаудың негізгі құралдарының біріне айналды. Бұл мақалада біз көру жүйкесінің басын зақымдайтын және көру қабілетінің қалпына келмейтіндей жоғалуына әкелетін глаукоманы емдеу туралы сөз қозғаймыз. Мақалада глаукоманы ерте диагностикалауға арналған жаңа бұлдыр сараптамалық жүйе ұсынылған. ОКТ бастапқы кескіндері алдымен кескіннің анық еместігін жою үшін тиісті сүзгілер арқылы алдын ала өңделеді. Содан кейін контурларды анықтау үшін Canny детекторы алгоритмі қолданылады. Осыдан кейін негізгі параметрлер анықталып, оптикалық диск пен ойықтың эллиптикалық формалары сәйкестендіріледі. Бұл операция Randomized Hough Transform арқылы жүзеге асырылады. Соңында, пациенттердің ауруын анықтау үшін бұлдыр логикалық тәсілдерге негізделген жіктеу алгоритмі ұсынылады. Біздің жүйе аспаптық параметрлерді де, қауіп факторларын да (жас, нәсіл, отбасы тарихы) ескереді, бұл глаукоманың болуы мүмкін деген болжамды нақтылауға маңызды үлес қосады. Ұсынылған жүйе қалыпты және глаукоматозды науқастардың офтальмологиялық кескіндерінің нақты деректер жинағында сыналған. Қолданыстағы басқа жүйелермен салыстырғанда тәжірибелік нәтижелер ұсынылған әдістердің артықшылығын көрсетеді. Бұрынғы әдістермен салыстырғанда, дұрыс болжамдардың пайызы 96%-дан асып, 1–9% жақсару көрсеткен.

Тірек сөздер: глаукома, шешім қабылдау жүйесі, офтальмологиялық суреттер, оптикалық жүйкенің басы, кескінді өңдеу, бұлыңғыр логика.

Кіріспе

Глаукома – бұл адамның көру қабілетін біртіндеп жоғалтуға әкелетін, оптикалық жүйке мен көздің басқа бөліктеріне тұрақты зақым келтіретін күрделі көз ауруы, ал бұл зақымдануларды қалпына келтіру мүмкін емес [1]. Ресми статистика деректеріне сәйкес, Қазақстан Республикасында глаукомамен алғашқы сырқаттанушылық 2010 жылы 100 мың тұрғынға шаққанда 70,8-ден 2014 жылы 96,1-ге дейін өсті. Бұл өсім Қазақстанда 2011 жылдың сәуірінен бастап глаукомаға халықты скринингтік тексеру бағдарламасын енгізумен немесе созылмалы инфекциялық емес аурулармен сырқаттанушылықтың жалпы өсуімен байланысты болуы мүмкін. Глаукома созылмалы ауру болғанымен, оның қазіргі уақытта емі жоқ. Шын мәнінде, бұл ауру «неврологиялық ауру» болып табылады, себебі жүйке клеткаларына зақым келіп, оны қалпына келтіру мүмкін болмайды [2, 3]. Сондықтан оны ерте диагностикалау

және емдеу көру қабілетін жоғалтудың алдын алуға көмектеседі [4]. Көру жүйкесінің басын офтальмоскопия немесе сканерлеуші лазерлік томография (SLT), сканерлеуші лазерлік поляриметрия (SLP) және оптикалық когерентті томография (ОСТ) сияқты сандық бейнелеу әдістері арқылы қолмен бағалау глаукоманы анықтауға арналған клиникалық құрал ретінде ұсынылады [5]. Алайда, олардың тиімділігіне қарамастан, бұл әдістердің құны жоғары болғандықтан, олар дәрігерлердің басым көпшілігіне қолжетімсіз [6].

Көз шарасының дискіге қатынасы (CDR) және «Төменгі, жоғарғы, беткі және самай» (ISNT) ережесі ОКТ-ны бағалау үшін негізгі екі көрсеткіш болып табылады. CDR оптикалық көз шарасы диаметрінің көру жүйкесі дискінің диаметріне қатынасы ретінде анықталады. Глаукома асқынған сайын көру жүйкесі талшықтары біртіндеп жоғалады. Осылайша, оптикалық көз шарасының көру жүйкесі дискінің диаметріне қатынасы үлкейіп, CDR жоғарылайды [7]. Осы зерттеудің нысаны болып табылатын Тунис сияқты дамушы елдерде CDR-ды офтальмолог әдетте қолмен өлшеу арқылы анықтайды. Дегенмен, ОКТ өзгерістерін қолмен бақылау көп уақытты қажет ететін процесс болып табылады және оның дәлдігі офтальмологтың тәжірибесіне байланысты өзгереді.

Көз шарасының дискіге қатынасын (CDR) есептеуге негізделген жүйені Чандрика және оның серіктестері ұсынды [8]. CDR > 0,3 глаукоманың бар екенін көрсетеді, ал CDR ≤ 0,3 қалыпты кескін болып саналады. Бұл әдісті Собиа Наци және басқа да зерттеушілер қолданған [9]. Алайда, CDR көздің глаукоматозды екендігінің сенімді көрсеткіші болмауы мүмкін. Шын мәнінде, диск пен көз шарасының үлкен болуынан глаукома диагнозының қате қойылған жағдайлары да кездеседі, ал керісінше, көз шарасының кішкентай болуынан глаукоманың барын байқамаған жағдайлар да бар. Осыған байланысты, егер CDR дискінің мөлшерімен сәйкес келмесе, бұл әдісті қолдану шектеулі болуы мүмкін.

Бұл мақала глаукоманы көз түбінің кескіндерін қолдана отырып, 96,15% жіктеу дәлдігін қамтамасыз ететін жаңа әдіске негізделген. Ұсынылған әдіс алдыңғы салыстырмалы зерттеулердің дәлдігінен асып түседі [7, 11–12, 14, 15]. Мақалада офтальмологиялық кескіндердің компьютерлік талдауына арналған жаңа стратегия сипатталған, оның негізінде глаукоманы диагностикалауға қажетті параметрлерді алу және оптикалық папиллярды анықтау үшін кескіндерді өңдеу алгоритмдері жасалған.

Бұл параметрлер глаукомамен ауыратын науқастың жағдайын анықтау үшін бұлыңғыр логикалық механизмдерге негізделген математикалық алгоритмдер жасалатын келесі бөлімнің бастапқы деректері болады.

Негізгі ережелер

Бұл түрлендіру келесідей көрсетілген параметрлік эллипс теңдеуіне негізделген [16]:

$$ax^2 + 2bxy + cy^2 + 2dx + 2ey + f = 0 \quad (1)$$

Үлкен эллипс осінің екі шыңы болып саналатын әрбір жұп (x_1, y_1) және (x_2, y_2) жиек пикселдері үшін эллипс центрінің координаттары (x_0, y_0), үлкен r_1 осінің ұзындығы және бағыты сәйкес теңдеулерді қолдана отырып есептеледі.

Содан кейін кіші осьтің ұзындығының жартысын анықтау үшін үшінші нүкте қажет, оны келесі теңдеумен бағалауға болады [17]:

$$r^2 = \sqrt{\frac{a^2 d^2 \sin^2 \tau}{a^2 - d^2 \cos^2 \tau}} \quad (2)$$

Мұндағы:

$$\cos \tau = \frac{a^2 + d^2 - f^2}{2ad} \quad (3)$$


Мұндағы d – (x, y) және (x_0, y_0) арасындағы қашықтық, ал f – (x, y) және (x_2, y_2) арасындағы қашықтық.

Эллипстерді анықтау үшін бұл алгоритм параметрлердің бес өлшемді кеңістігін қажет етті. Тәуелсіз дискілер эллипстің болжамды параметрлері үшін бір-біріне тәуелсіз дауыс алады. Дауыс беру немесе жинақтау процесінің соңында әрбір диск сәйкес параметр үшін бір немесе бірнеше көпшілік дауысты береді, бұл сәйкес параметрлері бар фигураның сенімді дәлелі.

Материалдар мен әдістер


Бұл жұмыс үшін барлығы 104 кескін өңделді, оның 46-сы глаукомамен ауыратын науқастардың жағдайларын, ал 58-і 25 пен 82 жас аралығындағы қалыпты жағдайды білдіреді. Кескіндер JPEG пішімінде, ажыратымдылығы 3008 × 2000 пиксель. Сарапшылар жіберген оптикалық жүйкенің теориялық бейнелерінің кейбір мысалдары 3-суретте сипатталған. Түпнұсқа кескіндердің ажыратымдылығы өте жоғары болғандықтан, өңдеу уақытын қысқарту және әртүрлі ажыратымдылықтағы кескіндердің бірдей немесе өте ұқсас хэштерге ие болуын қамтамасыз ету үшін кескіндердің өлшемін 752 × 500 пиксельге өзгертуден бастадық. Содан кейін өлшемі өзгертілген көз түбінің кескіндері сұр реңкке түрлендіру, гистограмманы теңестіру және шуды сүзу арқылы алдын ала өңделеді.

Кейінгі өңдеу: Глаукоманы диагностикалаудың негізгі параметрлерін алу үшін көлденең және тік сызбаларды есептейміз. Бұл қадам дискінің пішіндерін және генерализацияланған Hough трансформациясы арқылы ойықтарды анықтауға бағытталған, сонымен қатар оптикалық дискінің диаметрі бойынша ойық диаметрін көлденең және тік бағытта бөлуді қамтиды. Бұл мәндер глаукоманы анықтауда маңызды факторлар болып табылады. 1-суретте осы операцияның нәтижелері көрсетілген.



Сурет 1 – CDR көлденең және тік есептеу

ISNT мәндерін өлшеу, S, N және T-нейро-торлы сақинаның төменгі, жоғарғы, мұқаба және уақытша бөліктері, олар төменгі бөлігінде ең кең, одан кейін жоғарғы бөлігінде, мұқаба жағында, содан кейін уақытша жағында болуы керек. Ол қалыпты жағдайларда ең жұқа болуы керек. Бұл шаралар науқастың жағдайы туралы айтады. Егер бұл мәндер жоғарыда сипатталған ережені қанағаттандырмаса, науқас глаукомадан зардап шегеді. Нәтиже 2-суретте көрсетілген.



Сурет 2 – I, S, N және T параметрлерін шығару және есептеу.

Көздің асимметриясын есептеу сол және оң көздің кескіндері сурет қораптарына салынып, диаметрлері есептелгендіктен, бұл фазада оң және сол көздің көлденең диаметрі арасындағы айырмашылық оның 0,2-ден жоғары екенін тексеру үшін есептеледі. Барлық алынған мәндер: Көлденең ЖӘНЕ тік CDR, ISNT параметрлері, екі көздің арасындағы ассимметрия viatextbox-es пайдаланушысы үшін көрсетіледі, содан кейін қолданбаға байланыстырылған дерекқорда тіркеледі.

Бұлыңғыр логикаға негізделген шешім қабылдау алгоритмі.

Бұл бөліктің мақсаты-бұлыңғыр логикаға негізделген алгоритмді қолдана отырып шешім қабылдау үшін кескінді өңдеу бөлігінде алынған нәтижелерді өңдеу және талдау. Диагностика үшін бір параметрді қолдану бізге жалған нәтижелер береді. Шынында да, офтальмологтармен талқылаулар мен осы тақырыптағы зерттеулерден кейін біз бұл патологияның диагностикасы шешім қабылдауды қолдау жүйесінде ескеретін бірнеше параметрлерге негізделгенін түсінеміз.

Кесте 1 – «Тостағанша-диск» қатынасының мәндеріне сәйкес корпустарды жіктеу

	Қалыпты	Глаукомаға күдікті	Глаукоматозды
Тік CDR	0.541 (±0.226)	0.657 (±0.149)	0.776 (±0.250)
Көлденең CDR	0.593 (±0.187)	0.681 (±0.0715)	0.797 (±0.143)

Үш лингвистикалық айнымалы қолданылады: екі кіріс және шығыс.


Кіріс тік және көлденең CDR болып табылады, әр жазба үшін дискурстың әмбебап мәні [2] аралығы болып табылады. Нәтижелер дискурсивті ғаламның интервалы болатын шешімді білдіреді [1].

Мүшелік функциялары. Кіріс функциялары. Адамдар тобының статистикалық зерттеулері үш түрлі жағдайдың бар екенін көрсетті: біріншісі-глаукомасы жоқ адамдардың жағдайы, екіншісі-глаукомаға күдікті науқастардың жағдайы және үшіншісі-глаукомасы бар адамдар тобы [19]. 1-кестеде топтардың тік және көлденең CDR мәндері бойынша жіктелуі көрсетілген.

Осы топтарды көрсету үшін біз келесі теңдеумен сипатталған Гаусс функцияларын қолдандық:

$$f(x) = \frac{-(x-m)^2}{2\,\partial^2} \qquad (4)$$

Мұндағы ∂ - стандартты ауытқу, ал m – Гаусс функциясының орташа мәні. 2-кестеде әр тиістілік функциясының параметрлері, m_V және m_H сәйкесінше тік және көлденең CDR сипатталған.



(a) (b)

Сурет 3 – Кіріс функциялары (a) CDR-ге тиесілі тік функция.
(b) CDR-ге көлденең мүшелік функциясы.

Жабдықтың шығыс функциясы.

Шығу мүшелігі функция анық емес қозғалтқыштың кірісіне және оның шығу ережелеріне сынақтар жүргізілгеннен кейін эмпирикалық түрде таңдалады. Оның құрамында екі класс бар: қалыпты және глаукоматозды. Белгіленген бірінші класс функциясы (қалыпты класс) сызықтық функция болып табылады, ал белгіленген екінші класс функциясы (глаукоматозды класс) аффиндік болып табылады. Олар сәйкесінше теңдеулермен сипатталады. (5) және (6):

$$f_N(x) = ax;\ a = 1 \tag{5}$$

$$f_G(x) = ax + b;\ a = -1\ b = 1 \tag{6}$$

Кесте 2 – Кіріс функциясының параметрлерінің сипаттамалық кестесі

	Қалыпты	Глаукомаға күдікті	Глаукоматозды
Тік қатынасты мүшелік функциясының орташа мәні mv	0.541	0.657	0.776
Мүшелік функциясының тік қатынасты стандартты ауытқуы ∂v	0.113	0.0745	0.125
Көлденең қатынасты мүшелік функциясының орташа мәні mH	0.593	0.681	0.797
Мүшелік функциясының көлденең қатынасты стандартты ауытқуы ∂H	0.0935	0.0357	0.0715


Бұлыңғыр ережелер

«Егер болса» ережелерін офтальмологтар бекітеді. Медициналық маңызы бар олар қазірдің өзінде глаукомадан зардап шегетін және көру қабілеті нашар глаукомаға күдікті адамдарды ажыратады Бұлыңғыр қозғалтқыш алты ережені қамтиды.

Егер тік қатынас қалыпты класына жатса, ал көлденең – қалыпты класқа, содан кейін науқас қалыпты.

Егер тік қатынас қалыпты класқа, ал көлденең қатынас глаукомаға күдікті класқа жатса, науқас қалыпты деп есептеледі.

Егер тік қатынас қалыпты класқа, ал көлденең қатынас глаукомаға күдікті класқа жатса, науқас қалыпты деп есептеледі.



Сурет 4 – Жабдықтың шығыс функциясы.

Егер тік қатынас глаукомаға күдікті класқа, ал көлденең қатынас қалыпты класқа жатса, онда пациент қалыпты.

Егер тік қатынас глаукоматоз класына жатса, ал көлденең қатынас глаукоматоз класына жатса, онда науқаста глаукома болады.

Егер тік қатынас глаукоматозды класқа, ал көлденең қатынас глаукомаға күдікті класқа жатса, онда науқаста глаукома болады.

Егер тік қатынас глаукомаға күдік туғызатын класқа жатса, ал көлденең қатынас глаукоматозды класқа жатса, онда науқаста глаукома болады.

Шығару әдісі

Бірнеше кластардан кейін «MAX PROD» әдісі ең дәл нәтиже берді. Бұл әдіс үшін AND, OR операторлары сәйкесінше келесідей анықталады:

$$\mu_{A\cap B}(x) = \min(\mu_A(x), \mu_B(x)) \quad (7)$$

$$\mu_{A\cup B}(x) = \max(\mu_A(x), \mu_B(x)) \quad (8)$$

Бұл теңдеулерді бұлыңғыр жүйені жасаушы жоғарыда аталған бұлыңғыр ережелерді жазу үшін пайдаланады. Шын мәнінде, классикалық логика операторлары (and, or, they) бұлыңғыр логикада қолайсыз, сондықтан оларды математикалық операторлар (min, max және product) қайта анықтауы керек.

Ауырлық центрінің бұлыңғырлығы

Дефазификация интерфейсінің мақсаты шешім қабылдауға мүмкіндік беретін логикалық Шығыс механизмі есептеген бұлыңғыр жиынды бұлыңғыр мәнге түрлендіру болып табылады [18]. Ұсынылған қолданба аймақтың ортасында бұлыңғырлық әдісін қолданады. Ауырлық центрінің абсциссасын келесі жалпы теңдеу арқылы анықтауға болады [19]:

$$x_R^* = \frac{\int x_R \mu_R(x_R) dx_R}{\int \mu_R(x_R) dx_R} \infty \quad (9)$$

Мұнда:

$$\mu_R(x_R) = \frac{1}{n}\sum_{i=1}^{n} \mu_{C_i} * \mu_{oi}(x_R i) \quad (10)$$

$\mu_{C_i} - R_i$ ережесінің мүшелік коэффициенті, ал μ_{oi} – ережемен байланысты операцияның мүшелік функциясы.

(8) және (9) теңдеулер бұлыңғыр жиынды сипаттайтын мүшелік центроидтың абсциссасына сәйкес x_R^* деп белгіленген шығысты есептеу үшін қызмет етеді. Бұл операцияның мақсаты бұрын қорытындылау механизмімен есептелген бұлыңғыр жиынды бір бұлыңғыр мәнге түрлендіру, соған сәйкес соңғы шешім қабылданады.

Нәтижелер мен талқылау

Бұл жұмыс оптикалық жүйке басының зақымдануын азайту үшін глаукоманы ерте танудың тиімді әдісін ұсынады. Біз ұсынған әдіс көз түбінің 104 кескінінің 100-ін дұрыс жіктеуге мүмкіндік берді (58 қалыпты және 46 глаукоматозды кескін). Ұсынылған жүйенің жұмысын одан әрі тексеру үшін сезімталдықты, ерекшелікті, оң болжамдық мәнді (PPV), теріс болжамдық мәнді (NPV) және дәлдікті талдау жүргізілді, нәтижелер 3-кестеде келтірілген.

Кесте 3 – Жіктеу нәтижелері

TP	45	Сезімталдық	97.82%
TN	55	Ерекшелігі	94.82%
FP	3	Дәлдігі	93.75%
FN	1	Теріс болжамды мән	98.21%
		Дәлдігі	96.15%

– Нағыз оң нәтиже (TP): біз ұсынған классификатор бойынша глаукоматозды деп жіктелген глаукомасы бар суреттердің саны.


– Ақиқат теріс (TN): ұсынылған классификатор арқылы қалыпты деп жіктелген қалыпты кескіндер саны.

– Жалған оң нәтиже (FP): ұсынылған классификаторға сәйкес глаукоматозды деп жіктелген қалыпты кескіндердің саны.

– Жалған теріс (FN): ұсынылған классификаторға сәйкес қалыпты деп жіктелген глаукома кескіндерінің саны.

Әзірленген жүйелердің көпшілігі фундаментальды кескіндерден белгілерді алуға және әртүрлі жіктеу әдістерін қолдануға негізделген. Тірек векторлық аппараттың көмегімен глаукома 88%–95,2% дәлдікпен, 93% сезімталдықпен және 94,3%–96,7% ерекшелігімен анықталды [9, 14]. Жасанды нейрондық желі (ANN) 72%–94,7% дәлдікке қол жеткізді, 96,9% сезімталдық пен 93,3% ерекшелік. Бұл жұмыс жіктеу үшін белгілерді шығаруға және бұлыңғыр логикаға негізделген жаңа әдісті ұсынады. Бұл жүйе 96,15% дәлдікке, 97,8% сезімталдыққа және 94,8% ерекшелікке қол жеткізді. жіктеу нәтижелері 3-кестеде сипатталған.

Жіктеу тиімділігін талдау мақсатында біз жалған позитивтердің жиілігін оң нәтижелердің шынайы жиілігінің функциясы ретінде білдіретін қабылдағыштың жұмыс сипаттамаларының графигін (ROC) таңдадық. ROC қисықтары біздің алгоритмді тан және т.б. [10], Исаак және т.б. [14]. ROC қисықтарын алу үшін біз әр алгоритм үшін бірнеше шекті мәндерді таңдаймыз және оларға сәйкес жалған позитивтілік пен шынайы оң нәтиже көрсеткіштерін есептейміз. 5-сурет жоғарыда аталған алгоритмдер арасындағы ROC қисығын салыстыруды көрсетеді.



Сурет 5 – Әр түрлі глаукома-диагностикалық жүйелер
арасындағы ROC графигін салыстыру.

Мұның бәрі сандық кескінді өңдеу мен форманы танудың тиісті дамыған әдістерін қолдану және жасанды интеллекттің алгоритмдік әдістерін қолдану арқылы жүзеге асырылды.

Қорытынды

Осы зерттеу аясында глаукома ауруын анықтау алгоритмі іс жүзінде енгізілді. Бұл қауіпті ауру уақытында диагноз қойылмаса, соқырлыққа әкелуі мүмкін. Сондықтан біз осы патологияны анықтау үшін қажетті параметрлерді алуға мүмкіндік беретін кескінді өңдеу мен пішінді танудың әртүрлі әдістеріне негізделген автоматтандырылған диагностикалық жүйені әзірледік

Глаукоманы диагностикалау үшін осы жұмыста алынған сәйкестік жиілігін арттыру мақсатында авторлардың ағымдағы зерттеуі жасанды нейрондық желілерді пайдалану арқылы жасалатын шешімдерді қолдаудың келесі әдісін әзірлеуге бағытталған. Болашақта қан тамырлары желісінің конвергенциясын бақылау жұмыстары да жүргізіледі. Бұл шешімдер сыналғаннан кейін, екі әдістің әрқайсысы алған нәтижелерге сәйкес іске асыруда ең жақсы әдісіне таңдау жасалады.

Қаржыландыру туралы ақпарат: Бұл зерттеуді Қазақстан Республикасы Ғылым және жоғары білім министрлігінің Ғылым комитеті қаржыландырды (Грант № AP19675574).

ӘДЕБИЕТТЕР

1 Dahl A.A. Glaucoma Causes, Symptoms. – Treatment & Surgery. – 2018. [online]. https://www.medicinenet.com/glaucoma/article.htm. [Accessed: 10-Available at: Mar-2018].

2 Nayak J., Acharya U.R., Bhat P.S., Shetty A., Lim T.C. Automated diagnosis ofglaucoma using digital fundus images // J. Med. Syst. – 2009. – Vol. 33. – No. 5. – 7, Springer. – PP. 337–346.7.

3 Абышева Л.Д., Алдашева Н.А., Утельбаева З.Т. Сравнительная оценка методов лечения рефрактерной глаукомы // Вестник КазНМУ. – 2019. – № 3. – PP. 185–188.

4 Kourkoutas D., Karanasiou I.S., Tsekouras G.J., Moshos M., Iliakis E., Georgopoulos G. Glaucoma risk assessment using a non-linear multivariableregression method // Comput. Methods Programs Biomed. 2012. – Vol.108. – No. 3. – PP. 1149–1159.

5 Greany M.J. et al. Comparisons of optic nerve imaging methods to distinguishnormal eyes from those with glaucomaInvest // Ophthalmol. Visual Sci. – 2002. – Vol. 43. – No. 1. – PP. 140–14.

6 Lachkar Y., Sellem E. La papille glaucomateuse en pratique // LaboratoireChauvin Bausch & Lomb. – 2024. – No. 80.

7 Man Hua, Chenghao Zhub, Xiaoxing Lib, Yongli Xub. Optic Cup Segmentationfrom Fundus Images for Glaucoma Diagnosis. – Taylor & Francis, 2016. – PP. 1–8 [Online].

8 Chandrika S., Nirmala K. Analysis of CDR detection for glaucoma diagnosis // Int. J. Eng. Res. Appl. (IJERA). – 2013. ISSN: 2248-9622, NCACCT-19.

9 Sobia Nazi, Sheela N. Rao. Glaucoma detection in color fundus images usingcup to disc ratio // Int. J. Eng. Sci. (IJES). –2014. – Vol. 3. – No. 6. – PP. 51–58.

10 Kim P.Y., Iftekharuddin K.M. Novel fractal feature-Based multiclass glaucomadetection and progression prediction // IEEE J. Biomed. Health. Inf. – 2013. – Vol. 17. – No. 2.

11 Tan M.H., Sun Y., Ong S.H., Liu J., Baskaran M., Aung T., Wong T.Y. Automaticnotch detection in retinal images : IEEE 10th International Symposium onBiomedical Imaging, April, San Francisco, CA, USA, 2013.

12 Yadav D., Sarathi M.P., Dutta M.K. Classification of glaucoma based on texturefeatures using neural networks : IEEE 7th International Conference onContemporary Computing, August, Noida, India, 2014.

13 Noronha K.P., Acharya U.R., Nayaka K.P., Martis R.J., Bhandary S.V. Automatedclassification of glaucoma stages using higher order cumulant features Biomed // Signal Process. Control. – 2014. – No. 10. – PP. 174–183.

14 Raja C., Gangatharan N. A hybrid swarm algorithm for optimizing glaucomadiagnosis // Comput. Biol. Med. – 2015. – No. 63. – PP. 196–207.

15 Ashish Issac, M. Partha Sarathi, Malay Kishore Dutta. An adaptive thresholdbased image processing technique for improved glaucoma detection andclassification // Comput. Methods Programs Biomed. – 2015. – Vol. 122. – No. 2. – PP. 229–244.

16 Cosmin A. Basca, Mihai Talos, Remus Brad. Randomized hough transform forellipse detection with result clustering : IEEE International Conference onComputer as a Tool, Serbia & Montenegro, Belgrade, 2005.

17 Bennett N., Burridge R., Saito N. A method to detect and characterize ellipsesusing the Hough transform // IEEE Trans. Pattern Anal. Mach. Intell. – 1999. – Vol. 21. – No. 7. – PP. 652–657.

18 Corine Schnyder, André Mermoud, et al. Glaucome. – Atlas En Ophtalmologie. – Elsevier, 2005. – PP. 463.

19 Van Broekhoven E., De Baets B. A comparison of three methods for computingthe center of gravity defuzzification : IEEE International Conference onFuzzy Systems, Budapest, Hungary, 2004.

REFERENCES

1 Dahl A.A. Glaucoma Causes, Symptoms. Treatment & Surgery, 2018. [Online]. https://www.medicinenet.com/glaucoma/article.htm. [Accessed: 10-Available at: Mar-2018].

2 Nayak J., Acharya U.R., Bhat P.S., Shetty A., Lim T.C. (2009) Automated diagnosis ofglaucoma using digital fundus images. J. Med. Syst., vol. 33, no. 5, pp. 337–346.7.

3 Abysheva L.D., Aldasheva N.A., Utel'baeva Z.T. (2019) Sravnitel'naja ocenka metodov lechenija refrakternoj glaukomy. Vestnik KazNMU, no. 3, pp. 185–188.

4 Kourkoutas D., Karanasiou I.S., Tsekouras G.J., Moshos M., Iliakis E., Georgopoulos G. (2012) Glaucoma risk assessment using a non-linear multivariableregression method. Comput. Methods Programs Biomed, vol.108, no. 3, pp. 1149–1159.

5 Greany M.J. et al. (2002) Comparisons of optic nerve imaging methods to distinguishnormal eyes from those with glaucomaInvest. Ophthalmol. Visual Sci., vol. 43, no. 1, pp. 140–14.

6 Lachkar Y., Sellem E. (2024) La papille glaucomateuse en pratique. Laboratoire Chauvin Bausch & Lombo, no. 80.

7 Man Hua, Chenghao Zhub, Xiaoxing Lib, Yongli Xub. (2016) Optic Cup Segmentationfrom Fundus Images for Glaucoma Diagnosis, Taylor & Francis, 2016, pp. 1–8. [Online].

8 Chandrika S., Nirmala K. (2013) Analysis of CDR detection for glaucoma diagnosis. Int. J. Eng. Res. Appl. (IJERA), ISSN: 2248-9622, NCACCT-19.

9 Sobia Nazi, Sheela N. Rao. (2014) Glaucoma detection in color fundus images usingcup to disc ratio. Int. J. Eng. Sci. (IJES), vol. 3, no. 6, pp. 51–58.

10 Kim P.Y., Iftekharuddin K.M. (2013) Novel fractal feature-Based multiclass glaucomadetection and progression prediction. IEEE J. Biomed. Health. Inf., vol. 17, no. 2.

11 Tan M.H., Sun Y., Ong S.H., Liu J., Baskaran M., Aung T., Wong T.Y. (2013) Automaticnotch detection in retinal images. IEEE 10th International Symposium onBiomedical Imaging, April, San Francisco, CA, USA.

12 Yadav D., Sarathi M.P., Dutta M.K. (2014) Classification of glaucoma based on texturefeatures using neural networks. IEEE 7th International Conference onContemporary Computing, August, Noida, India.

13 Noronha K.P., Acharya U.R., Nayaka K.P., Martis R.J., Bhandary S.V. (2014) Automatedclassification of glaucoma stages using higher order cumulant features Biomed. Signal Process. Control, no. 10, pp. 174–183.

14 Raja C., Gangatharan N. (2015) A hybrid swarm algorithm for optimizing glaucomadiagnosis. Comput. Biol. Med., no. 63, pp. 196–207.

15 Ashish Issac, M. Partha Sarathi, Malay Kishore Dutta. (2015) An adaptive thresholdbased image processing technique for improved glaucoma detection andclassification. Comput. Methods Programs Biomed., vol. 122, no. 2, pp. 229–244.

16 Cosmin A. Basca, Mihai Talos, Remus Brad. (2005) Randomized hough transform forellipse detection with result clustering. IEEE International Conference onComputer as a Tool, Serbia & Montenegro, Belgrade.

17 Bennett N., Burridge R., Saito N. (1999) A method to detect and characterize ellipsesusing the Hough transform. IEEE Trans. Pattern Anal. Mach. Intell., vol. 21, no. 7, pp. 652–657.

18 Corine Schnyder, André Mermoud, et al. Glaucome (2005) Atlas En Ophtalmologie, p. 463.

19 Van Broekhoven E., De Baets B. (2004) A comparison of three methods for computingthe center of gravity defuzzification. IEEE International Conference onFuzzy Systems, Budapest, Hungary.

[1]Мамырбаев О.Ж.,
PhD, ассоциированный профессор, ORCID ID: 0000-0001-8318-3794,
e-mail: morkenj@mail.ru,
[2]Павлов С.В.,
к.т.н., ORCID ID: 0000-0002-0051-5560,
e-mail: psv@vntu.edu.ua
[3*]Момынжанова К.Р.,
магистр, ORCID ID: 0000-0002-9981-5706,
*e-mail: kymbat_momynzhanova87@mail.ru

[1]Институт информационных и вычислительных технологий, 050000, г. Алматы, Казахстан
[2]Винницкий национальный технический университет, 12000, г. Винница, Украина
[3]Казахский национальный университет имени аль-Фараби, 050040, г. Алматы, Казахстан

СОЗДАНИЕ ЭКСПЕРТНОЙ СИСТЕМЫ, ОСНОВАННОЙ НА НЕЧЕТКОЙ ЛОГИКЕ, ДЛЯ РАННЕЙ ДИАГНОСТИКИ ГЛАУКОМЫ

Аннотация

В настоящее время системы принятия решений, основанные на изображениях, приобретают все большее значение, особенно в области медицины. Изображения стали фундаментальным инструментом для клинических исследований и диагностики заболеваний. В случае глаукомы, заболевания, которое может повредить головку зрительного нерва и привести к необратимой потере зрения, для ранней диагностики была разработана новая нечеткая экспертная система. Исходные изображения ONH предварительно обрабатываются фильтрами для удаления шума, после чего используется алгоритм Canny detector для определения контуров. Затем извлекаются ключевые параметры путем идентификации эллиптических форм диска зрительного нерва и экскавации с использованием рандомизированного преобразования Хафа. Алгоритм классификации, основанный на нечеткой логике, используется для оценки состояния пациентов с учетом как инструментальных параметров, так и факторов риска, таких как возраст, раса и семейный анамнез. Система протестирована на наборе данных офтальмологических изображений, демонстрирующих значительное улучшение прогнозов по сравнению с существующими методами с точностью более 96% при выявлении случаев с подозрением на глаукому.

Ключевые слова: глаукома, система принятия решений, офтальмологические изображения, головка зрительного нерва, обработка изображений, нечеткая логика.

[1]Mamyrbayev O.Zh.,
Ph.D., associate professor, ORCID ID: 0000-0001-8318-3794,
e-mail: morkenj@mail.ru
[2]Pavlov S.V.,
prof. Dr. Techn. Sc., ORCID ID: 0000-0002-0051-5560,
e-mail: psv@vntu.edu.ua
[3*]Momynzhanova K.R.,
master, ORCID ID: 0000-0002-9981-5706,
e-mail: kymbat_momynzhanova87@mail.ru

[1]Institute of information and computational technologies, 050040, Almaty, Kazakhstan
[2]Vinnytsia National Technical University, 21000, Vinnytsa, Ukraine
[3]Al-Farabi Kazakh National University, 050040, Almaty, Kazakhstan

DEVELOPMENT OF AN EXPERT SYSTEM BASED ON FUZZY LOGIC FOR EARLY DIAGNOSIS OF GLAUCOMA

Abstract

Nowadays, decision-making systems that rely on images are becoming increasingly crucial, especially in the medical field. Images have become a fundamental tool for clinical research and diagnosing illnesses. In the case of

glaucoma, a disease that can damage the optic nerve head and result in irreversible vision loss, a new Fuzzy Expert System has been developed for early diagnosis. Original ONH images are preprocessed with filters to remove noise, followed by using the Canny detector algorithm to detect contours. Key parameters are then extracted by identifying elliptical forms of the optic disc and excavation using the Randomized Hough Transform. A classification algorithm based on fuzzy logic is used to assess patients' conditions, taking into account both instrumental parameters and risk factors such as age, race, and family history. The system is tested on a dataset of ophthalmologic images, showing a significant improvement in predictions compared to existing methods, with over 96% accuracy in identifying cases suspected to have glaucoma.

Key words: Glaucoma, decision-making system, ophthalmic images, optic nerve head, image processing, fuzzy logic.

Мақаланың редакцияға түскен күні: 05.04.2024.

UDC 004.896
IRSTI 28.23.29

https://doi.org/10.55452/1998-6688-2024-21-3-48-57

[1]Omarov Bauyrzhan.S.,
PhD student, ORCID ID: 0000-0002-9312-4429,
e-mail: bauyrzhanomarov01@gmail.com
[2]Auelbekov O.A.,
Cand. Phys.-Math. Sc., senior researcher, ORCID ID: 0000-0002-2903-9086,
e-mail: omirlan.auelbek@gmail.com
[3]*Kulambayev B.O.,
Cand. Tech. Sc., Associate Professor, ORCID ID 0009-0002-9279-6239,
*e-mail: bakhytzhan.kulambaev@gmail.com
[1]Omarov B.S.,
PhD, acting associate professor, ORCID ID: 0000-0002-8341-7113,
e-mail: batyahan@gmail.com

[1]Al-Farabi Kazakh National University, 050040, Almaty, Kazakhstan
[2]Institute Information and Computational Technologies, 050000, Almaty, Kazakhstan
[3]Turan University, 050013, Almaty, Kazakhstan

IOT NETWORK INTRUSION DETECTION USING MACHINE LEARNING ON UNSW-NB15 DATASET

Abstract

This research presents a comprehensive investigation into the application of machine learning techniques for addressing the pervasive security challenges within Internet of Things (IoT) networks. With the exponential growth of interconnected devices, ensuring the integrity and confidentiality of data transmissions has become increasingly critical. In this study, we deploy and evaluate seven distinct machine learning methods tailored to the IoT network intrusion detection problem. Leveraging the rich and diverse UNSW-NB15 dataset, encompassing real-world network traffic scenarios, our analysis encompasses a thorough examination of both traditional and state-of-the-art algorithms. Through rigorous experimentation and performance evaluation, we assess the efficacy of these methods in accurately detecting and classifying various forms of network intrusions. Our findings provide valuable insights into the strengths and limitations of different machine learning approaches for enhancing the security posture of IoT environments, thereby facilitating informed decision-making for network administrators and cybersecurity practitioners.

Key words: IoT network, intrusion detection, IoT attack, machine learning, artificial intelligence.

Introduction

The advent of the Internet of Things (IoT) has ushered in a new era of connectivity, interconnecting countless devices and systems to enhance efficiency, convenience, and productivity across various domains [1]. However, the proliferation of IoT devices and the sheer volume of data they generate have raised significant concerns regarding security and privacy [2]. As these devices become increasingly integrated into critical infrastructure, homes, and industries, they become attractive targets for malicious actors seeking unauthorized access, data breaches, or disruption of services [3].

IoT intrusion detection has emerged as a pivotal defense mechanism against these threats, aiming to detect and mitigate potential intrusions or malicious activities within IoT ecosystems [4]. Machine learning methods analyze data through computational algorithms, extracting patterns and features indicative of network intrusions, and subsequently employ decision-making processes to classify and discern between benign and malicious activities within IoT network traffic [5]. By leveraging

ML algorithms, it becomes possible to develop proactive, adaptive, and efficient security measures capable of addressing the dynamic nature of IoT networks [6].

This research paper explores the intricate landscape of IoT attack detection applying machine learning methods. It delves into the various challenges associated with securing IoT ecosystems and highlights the significance of robust intrusion detection systems in safeguarding the IoT data [7]. Moreover, this paper offers a comprehensive analysis of the existing ML techniques applied to IoT security, shedding light on their strengths and limitations [8].

The goal of this research is to contribute to the ongoing discourse on IoT security by offering insights into the efficacy of ML-based intrusion detection systems. Through rigorous experimentation and evaluation, we aim to assess the efficiency of different ML algorithms in identifying and mitigating threats within IoT environments. This research intends to provide practical recommendations for enhancing the security posture of IoT deployments, with implications for industries, governments, and individuals [9].

In the subsequent sections, we will delve deeper into the foundations of IoT intrusion detection, review pertinent literature, discuss the methodologies employed in this research, present experimental results, and offer conclusions and future directions. In this paper, we anticipate that readers will gain a comprehensive understanding of the intricate interplay between IoT, machine learning, and intrusion detection, and how these elements collectively contribute to the broader landscape of IoT security.

Main provisions

The proposed research reveals that the application of anomaly detection techniques introduces a notable challenge related to the categorization of data. The task entails segregating network traffic into two discrete categories: regular and anomalous, thus constituting a binary classification problem [10]. This delineation is pivotal for discerning between typical network behavior and potentially malicious activities within the IoT environment.

In tackling this binary classification challenge, fundamental mathematical methodologies will be utilized to detect notable deviations present within the network traffic graph. This approach aims to effectively distinguish between normal and abnormal patterns, thereby enhancing the robustness of intrusion detection systems deployed in IoT networks. These techniques will enable us to detect and isolate instances of severe fluctuations or deviations that signify potential anomalies in the IoT network traffic. Equation (1) demonstrates mathematical model of the IoT intrusion detection process using machine learning.

$$S = \int_{t_1}^{t_2} \left| x'(t) \right| dt \tag{1}$$

The aggregate manifestation of potential deviations within the temporal span from t1 to t2 is encapsulated herein. Within the framework of a discretized function, the formulation is articulated as follows:

$$S = \sum_{t=t_1}^{t_2-1} \left| x(t+1) - x(t) \right| \tag{2}$$

In the following segment, machine learning methodologies are applied to unveil discrepancies inherent within the IoT network, followed by an assessment utilizing various measurement parameters customized to the dataset at hand.

Materials and Methods

The research process can be structured into a comprehensive three-phase framework, as illustrated in Figure 1. The initial stage entails a meticulous system modeling process, aimed at

delineating three discrete categories: normal operations, malfunctions, and potential attacks. This modeling endeavor serves as a cornerstone for comprehending the varied system behaviors across these diverse scenarios.

Moving on to the second phase, an extensive range of execution scenarios is systematically conducted. The primary objective here is to generate datasets that provide a comprehensive and nuanced representation of the system's performance across the aforementioned conditions – namely, normal, defective, and under attack [11]. This step involves the deliberate manipulation of variables and conditions to capture the full spectrum of system behavior.

In the third and final stage of the research process, the amassed datasets become invaluable assets for the evaluation of numerous supervised machine learning algorithms [12]. The focus of this phase centers on assessing the efficacy of these algorithms, particularly in addressing the classification challenge inherent in distinguishing between the different system states identified earlier [13]. Through this rigorous evaluation, the research aims to contribute insights into the suitability and performance of various machine learning techniques in the context of system state classification.




Figure 1 – Flowchart of the study

Dataset

The UNSW-NB15 dataset plays a pivotal role as a primary dataset within this research endeavor [14]. This dataset comprises a diverse and representative collection of network traffic data, encompassing a multitude of network-based attacks and normal network activities [15]. It is meticulously constructed to simulate real-world network traffic scenarios, making it an invaluable resource for assessing the performance of intrusion detection algorithms and machine learning models.

One of the main characteristics of the applied dataset is its categorization into various classes, including different types of attacks (e.g., denial-of-service attacks, intrusion attempts, and exploitation),

as well as benign or normal network traffic [16]. This categorization enables researchers to train and evaluate their models on a wide spectrum of network behaviors, facilitating the development of robust intrusion detection systems.

Moreover, the dataset provides a wealth of attributes and features, ranging from basic network flow statistics to more advanced protocol-specific characteristics. These attributes offer a comprehensive view of network traffic patterns, allowing researchers to employ a variety of ML methods to uncover hidden insights and patterns.

In this research, the UNSW-NB15 dataset serves as a foundational element, enabling the evaluation and validation of the machine learning approaches employed for IoT network anomaly detection. By utilizing this dataset, the research aims to harness its diversity and complexity to develop and assess effective intrusion detection models tailored to IoT environments, ultimately contributing to the enhancement of IoT security.

Evaluation Parameters

In this section, we provide an overview of the research topic and outline the key objectives and scope of the study. We introduce the importance of the subject matter, highlight existing gaps or challenges, and offer a roadmap for the subsequent sections of the paper [17–18].

Following the classification process, the outcomes can be categorized into four distinct types: TP means True Positive values, TN means True Negative values, FP means False Positive values, and FN means False Negative values. These outcomes are encapsulated within an error matrix [19].

In the evaluation of machine learning models, several essential metrics are employed to assess their performance, each offering valuable insights into their effectiveness and capabilities.

Accuracy is a fundamental evaluation metric used in machine learning to assess the performance of classification models [20]. It represents the proportion of correctly classified instances among the total number of instances in the dataset. A higher accuracy score indicates that the model has made fewer mistakes in its predictions, reflecting its ability to effectively distinguish between different classes. However, accuracy alone may not provide a complete picture of model performance, especially in imbalanced datasets where one class significantly outnumbers the others. In such cases, it is essential to consider additional metrics such as precision, recall, and F1 score to better evaluate the model's effectiveness.

$$accuracy = \frac{TP + TN}{P + N} \tag{3}$$

Precision focuses on the model's ability to correctly identify positive instances among those it classified as positive [21]. It is a crucial metric in scenarios where false positives are costly or undesirable, such as medical diagnoses.

$$preision = \frac{TP}{TP + FP} \tag{4}$$

Recall, also known as sensitivity or true positive rate, gauges the model's capability to identify all positive instances within the dataset [22]. High recall is essential when missing a positive instance could have significant consequences.

$$recall = \frac{TP}{TP + FN} \tag{5}$$

The F-score combines precision and recall into a single metric, striking a balance between the two [23]. It's particularly valuable when there's a trade-off between precision and recall, helping find an optimal threshold for classification.

$$F1 = \frac{2 \times precision \times recall}{precision + recall} \tag{6}$$

The Receiver Operating Characteristic (ROC) curve and the Area Under the Curve (AUC) are essential evaluation metrics used to assess the performance of binary classification models. The ROC curve illustrates the trade-off between the true positive rate (sensitivity) and the false positive rate (1 – specificity) across various threshold values. A perfect classifier would have an ROC curve that reaches the top-left corner of the plot, indicating high sensitivity and low false positive rate across all thresholds.

The AUC-ROC metric quantifies the overall performance of the classifier by computing the area under the ROC curve. A higher AUC-ROC score indicates better discrimination capability of the model, with a value of 1 representing a perfect classifier and 0.5 representing random guessing. It provides a single scalar value to compare and rank different classifiers, making it a valuable tool for model selection and comparison.

The ROC-AUC metric is particularly useful in scenarios where class imbalance exists or when the costs of false positives and false negatives are not equal. It provides a comprehensive assessment of the model's ability to rank instances correctly, irrespective of the chosen threshold, making it a widely used metric in various fields, including healthcare, finance, and cybersecurity.

Results and Discussion

In the context of the burgeoning field of Internet of Things (IoT) security, the task of network intrusion detection is paramount for safeguarding interconnected devices and systems. The research presented in Table 1 delineates the efficacy of various machine learning models in identifying unauthorized access within an IoT network. This study meticulously evaluates the models based on four critical metrics: Accuracy, Precision, Recall, and F-score, which collectively offer a comprehensive view of each model's performance.

The K-Nearest Neighbours (KNN) algorithm demonstrates a commendable performance with an accuracy of 86.03%, indicating its proficiency in correctly identifying intrusion instances. Its precision and recall, closely aligned at 86.12% and 86.02% respectively, along with an F-score of 86.02%, suggest a balanced capability in both identifying true positives and minimizing false negatives.

The Naïve Bayes classifier, with an accuracy of 83.05%, showcases its potential despite being based on the assumption of feature independence. The slight elevation in precision (83.79%) over recall (83.09%) underscores its conservative nature in classifying an action as an intrusion, which is further substantiated by its F-score of 83.47%.

Decision Trees (DT) exhibit a modest performance with an 82.27% accuracy and similarly aligned precision and recall rates. This model's simplicity and interpretability do not compromise its effectiveness in the intrusion detection domain, as evidenced by an F-score of 82.31%.

Support Vector Machines (SVM) emerge as a robust contender with the highest recall of 87.80%, indicating superior sensitivity in detecting true positives. Its overall accuracy stands at 87.21%, complemented by a precision of 87.18% and an F-score mirroring its precision, which highlights its strength in managing unbalanced classes inherent to intrusion detection tasks.

Logistic Regression and AdaBoost algorithms show notable accuracies of 86.08% and 87.54%, respectively, with AdaBoost slightly edging out in precision, recall, and F-score metrics. These outcomes underscore the adaptability of ensemble methods like AdaBoost in enhancing prediction accuracy through the combination of multiple weak learners.

The Random Forest model, an ensemble of Decision Trees, registers the highest accuracy (87.82%) and F-score (87.65%) among the evaluated models. This denotes its exceptional capability in handling the complexity and variability of IoT intrusion datasets, benefiting from both the robustness of ensemble learning and the depth of decision trees.

In summary, the Random Forest algorithm stands out as the most effective model for IoT network intrusion detection, demonstrating superior performance across all evaluated metrics. This analysis underscores the critical role of machine learning in fortifying IoT networks against sophisticated intrusion attempts, advocating for the adoption of advanced models like Random Forest for enhanced security measures in IoT ecosystems.

Table 1 – Obtained results in IoT network intrusion detection problem

Machine Learning Model	Accuracy	Precision	Recall	F-score
KNN	86.03	86.12	86.02	86.02
Naïve Bayes	83.05	83.79	83.09	83.47
DT	82.27	82.34	82.19	82.31
SVM	87.21	87.18	87.80	87.18
Logistic Regression	86.08	86.54	86.85	86.48
AdaBoost	87.54	87.24	87.31	87.60
Random Forest	87.82	87.85	87.84	87.65

The graph in Figure 2 provides a comprehensive comparison of the performance of various machine learning models on the task of IoT network intrusion detection, using four key metrics: Accuracy, Precision, Recall, and F-score.




Figure 2 – Machine learning models in IoT network anomaly detection.

Random Forest stands out as the most effective model, demonstrating the highest scores across all metrics. This indicates its superior capability in correctly identifying both positive and negative instances of network intrusions, with minimal false positives and negatives. Its leading performance, particularly in Recall (87.84%) and Precision (87.85%), suggests it is highly reliable in identifying true intrusion cases without mistakenly flagging normal behavior as intrusive.

AdaBoost follows closely, with notably high scores, especially in F-score (87.60%), highlighting its effectiveness in balancing precision and recall. This suggests that AdaBoost is also highly capable of distinguishing between intrusion and non-intrusion instances, making it a strong candidate for IoT security applications.

SVM (Support Vector Machines) shows a distinct advantage in Recall (87.80%), the highest among all models, indicating its strength in identifying most true positive cases. However, its Precision and F-score, while competitive, do not outperform Random Forest or AdaBoost, suggesting that while it is excellent at detecting intrusions, it may have a slightly higher rate of false positives.

Logistic Regression and KNN (K-Nearest Neighbours) exhibit solid performance, with their metrics closely aligned. They both show a balanced trade-off between Precision and Recall, making them reliable choices for intrusion detection, albeit not as optimal as Random Forest or AdaBoost.

Naïve Bayes and DT (Decision Trees), while still effective, score lower compared to the other models. Naïve Bayes, despite its simplicity and fast computation, shows a limitation in precision and recall compared to more sophisticated models. Decision Trees present a foundational approach with decent performance but are outshined by their ensemble counterparts, such as Random Forest and AdaBoost, which leverage multiple trees for improved accuracy and generalization.

Overall, the graph illustrates the nuanced strengths and weaknesses of each model in the context of IoT network intrusion detection. Random Forest and AdaBoost emerge as the most promising models, offering a robust blend of high accuracy, precision, recall, and F-score, making them highly suitable for protecting IoT networks against intrusions.

Conclusion

In conclusion, this research endeavors to address the challenge of IoT network intrusion detection through the application of various machine learning methodologies. By employing a diverse set of classifiers including KNN, Naïve Bayes, Decision Tree, Support Vector Machine (SVM), Logistic Regression, AdaBoost, and Random Forest, we have conducted a comprehensive evaluation of their performance on the developed dataset. The results highlight the efficacy of Random Forest and AdaBoost in achieving high accuracy, precision, recall, and F-score values, signifying their suitability for intrusion detection tasks in IoT networks. Conversely, Naïve Bayes and Decision Tree models demonstrate comparatively lower performance across all evaluated metrics. These findings underscore the significance of selecting appropriate machine learning algorithms tailored to the intricacies of the dataset to enhance detection capabilities within IoT environments. Moreover, the study contributes valuable insights into the comparative analysis of machine learning techniques for intrusion detection, offering guidance for network administrators and cybersecurity practitioners in selecting optimal solutions to mitigate security threats. Future research directions may involve exploring ensemble methods or deep learning approaches to further enhance the accuracy and robustness of intrusion detection systems in IoT networks, addressing evolving cybersecurity challenges in the digital landscape.

REFERENCES

1 Ahmad M., Riaz Q., Zeeshan M., Tahir H., Haider S.A., & Khan M.S. Intrusion detection in internet of things using supervised machine learning based on application and transport layer features using UNSW-NB15 data-set. EURASIP Journal on Wireless Communications and Networking, 2021, no. 1, pp. 1–23.

2 Aleesa A., Younis M. O. H. A. M. M. E. D., Mohammed A.A., & Sahar N. Deep-intrusion detection system with enhanced UNSW-NB15 dataset based on deep learning techniques. Journal of Engineering Science and Technology, 2021, vol. 16, no.1, pp. 711–727.

3 Fuat, T. Ü. R. K. Analysis of intrusion detection systems in UNSW-NB15 and NSL-KDD datasets with machine learning algorithms. Bitlis Eren Üniversitesi Fen Bilimleri Dergisi, 2023, vol. 12, no. 2, pp. 465–477.

4 Kabir M.H., Rajib M.S., Rahman, A. S. M. T., Rahman M.M., & Dey S.K. Network Intrusion Detection Using UNSW-NB15 Dataset: Stacking Machine Learning Based Approach. In 2022 International Conference on Advancement in Electrical and Electronic Engineering (ICAEEE), 2022, February, pp. 1–6, IEEE.

5 Sahar N., Mishra R., & Kalam S. Deep learning approach-based network intrusion detection system for fog-assisted iot. In Proceedings of international conference on big data, machine learning and their applications: ICBMA 2019, 2021, pp. 39–50, Springer Singapore.

6 Fathima A., Khan A., Uddin M.F., Waris M.M., Ahmad S. Sanin C., & Szczerbicki E. Performance Evaluation and Comparative Analysis of Machine Learning Models on the UNSW-NB15 Dataset: A Contemporary Approach to Cyber Threat Detection. Cybernetics and Systems, 2023, pp. 1–17.

7 Hossain Z., Sourov M.M.R., Khan M., & Rahman P. Network Intrusion Detection using Machine Learning Approaches. In 2021 Fifth International Conference on I-SMAC (IoT in Social, Mobile, Analytics and Cloud)(I-SMAC), 2021, November, pp. 438–442. IEEE.

8 Sharma B., Sharma L., Lal C., & Roy S. (2023). Anomaly based network intrusion detection for IoT attacks using deep learning technique. Computers and Electrical Engineering, no.107, p. 108626.

9 Saheed Y.K., Abiodun A.I., Misra S., Holone M.K., & Colomo-Palacios, R. A machine learning-based intrusion detection for detecting internet of things network attacks. Alexandria Engineering Journal, 2022, vol. 61, no. 12, pp. 9395–9409.

10 Sarhan M., Layeghy S., & Portmann M. Towards a standard feature set for network intrusion detection system datasets. Mobile networks and applications, 2022, pp. 1–14.

11 Baich M., Hamim T., Sael N., & Chemlal Y. Machine Learning for IoT based networks intrusion detection: a comparative study. Procedia Computer Science, 2022, no. 215, pp. 742–751.

12 Shareena J., Ramdas A., & AP H. Intrusion detection system for iot botnet attacks using deep learning. SN Computer Science, 2021, vol. 2, no. 3, pp. 1–8.

13 Zhao R., Gui G., Xue Z., Yin J., Ohtsuki T., Adebisi B., & Gacanin H. (2021). A novel intrusion detection method based on lightweight neural network for internet of things. IEEE Internet of Things Journal, 2021, vol. 9, no. 12, pp. 9960–9972.

14 Baniasadi S., Rostami O., Martín D., & Kaveh M. A novel deep supervised learning-based approach for intrusion detection in IoT systems. Sensors, 2022, vol. 22, no. 12, p. 4459.

15 Yin Y., Jang-Jaccard J., Xu W., Singh A., Zhu J., Sabrina F., & Kwak J. IGRF-RFE: a hybrid feature selection method for MLP-based network intrusion detection on UNSW-NB15 dataset. Journal of Big Data, 2023, vol.10, no. 1, pp. 1–26.

16 Kumar S., & Pathak N.K. Evaluation Of Machine Learning Algorithms For Intrusion Detection Utilizing UNSW-NB15 Dataset. Journal of Pharmaceutical Negative Results, 2022, pp. 4819–4832.

17 Al-Ambusaidi M., Yinjun Z., Muhammad Y., & Yahya A. ML-IDS: an efficient ML-enabled intrusion detection system for securing IoT networks and applications. Soft Computing, 2024, vol. 28, no. 2, pp. 1765–1784.

18 Kumar N., & Sharma S. A Hybrid Modified Deep Learning Architecture for Intrusion Detection System with Optimal Feature Selection. Electronics, 2023, vol. 12, no. 19, p. 4050.

19 Ahmad Z., Shahid Khan A., Wai Shiang C., Abdullah J., & Ahmad F. Network intrusion detection system: A systematic study of machine learning and deep learning approaches. Transactions on Emerging Telecommunications Technologies, 2021, vol. 32, no. 1, e4150.

20 Hammad M., Hewahi N., & Elmedany W. T - SNERF: A novel high accuracy machine learning approach for Intrusion Detection Systems. IET Information Security, 2021, vol. 15, no. 2, pp. 178–190.

21 Almomani O., Almaiah M.A., Alsaaidah A., Smadi S., Mohammad A.H., & Althunibat A. Machine learning classifiers for network intrusion detection system: comparative study. In 2021 International Conference on Information Technology (ICIT), 2021, July, pp. 440–445. IEEE.

22 Rashid M., Kamruzzaman J., Imam T., Wibowo S., & Gordon S. A tree-based stacking ensemble technique with feature selection for network intrusion detection. Applied Intelligence, 2022, vol. 52, no. 9, pp. 768–9781.

23 Abdulla A.R., & Jameel N.G.M. A Review on IoT Intrusion Detection Systems Using Supervised Machine Learning: Techniques, Datasets, 2023.

[1]Омаров Бауыржан.С.,
докторант, ORCID ID: 0000-0002-9312-4429,
e-mail: bauyrzhanomarov01@gmail.com
[2]Әуелбеков Ө.А.,
ф.-м.-ғ.к., а.ғ.қ., ORCID ID: 0000-0002-2903-9086,
e-mail: omirlan.auelbek@gmail.com
[3]*Куламбаев Б.О.,
т.ғ.к., қауымдастырылған профессор, ORCID ID: 0009-0002-9279-6239,
e-mail: bakhytzhan.kulambaev@gmail.com
[1]Омаров Б.С.,
PhD, доцент м.а., ORCID ID: 0000-0002-8341-7113,
e-mail: batyahan@gmail.com

[1]Әл-Фараби атындағы Қазақ ұлттық университеті,
050040, Алматы қ., Қазақтан
[2]Ақпараттық және Есептеу технологиялары институты,
050000, Алматы қ., Қазақстан
[3]«Тұран» университеті, 050013, Алматы қ., Қазақстан

UNSW-NB15 ДЕРЕКТЕР ЖИЫНТЫҒЫНДА МАШИНАЛЫҚ ОҚЫТУДЫ ҚОЛДАНА ОТЫРЫП ИНТЕРНЕТ ЗАТТАР ЖЕЛІСІНЕ ЕНУДІ АНЫҚТАУ

Аңдатпа

Бұл зерттеу жұмысы интернет заттар (IoT) мәнмәтінінде желілік ауытқуларды анықтау мәселесін шешу үшін әртүрлі машиналық оқыту әдістерінің тиімділігін зерттейді. Бағалау параметрлерінің кең жиынтығын, соның ішінде дәлдік, прецизиондылық, қайтарымдылық, F1 бағасы, оқыту уақыты және қабылдаушының жұмыс сипаттамаларының (ROC) талдауын пайдалана отырып, алты түрлі машиналық оқыту әдісін жүйелі түрде салыстырылады. Алынған нәтижелер логистикалық регрессияның тәжірибелік қолданылу мүмкіндігін ерекше айқындайды, бұл оның теңдестірілген жұмыс сипаттамаларына байланысты сенімді таңдау екенін көрсетеді. Логистикалық регрессия желілік ауытқуларды анықтауда жоғары дәлдікті ғана емес, сонымен қатар оқыту уақытының айтарлықтай қысқарғанын да көрсетеді, бұл оны әсіресе ауытқуларға уақытылы жауап беретін шешуші нақты қолданбалар үшін қолайлы етеді. Бұл зерттеу Интернет заттары желілерінің қауіпсіздігі мен тұтастығын жақсарту, желілік ауытқуларды анықтаумен байланысты күрделі мәселелерді шешу және Интернет заттарының киберқауіпсіздігінің дамып келе жатқан ландшафтында осы әдістемелердің практикалық өзектілігін көрсету үшін машиналық оқыту әдістерін қолдану туралы құнды ақпарат береді.

Тірек сөздер: Интернет заттар, басқыншылық, шабуылды анықтау, машиналық оқыту, жіктеу.

[1]Омаров Бауыржан С.,
докторант, ORCID ID: 0000-0002-9312-4429,
e-mail: bauyrzhanomarov01@gmail.com
[2]Әуелбеков Ө.А.,
к.ф.-м.н., с.н.с., ORCID ID: 0000-0002-2903-9086,
e-mail: omirlan.auelbek@gmail.com
[3]*Куламбаев Б.О.,
к.т.н., ассоциированный профессор, ORCID ID: 0009-0002-9279-6239,
e-mail: bakhytzhan.kulambaev@gmail.com
[1]Омаров Б.С.,
PhD, и.о. доцента, ORCID ID: 0000-0002-8341-7113,
e-mail: batyahan@gmail.com

[1]Казахский национальный университет имени аль-Фараби,
050040, г. Алматы
[2]Институт информационных и вычислительных технологий,
05000, г. Алматы
[3]Университет «Туран», 050013, г. Алматы

ОБНАРУЖЕНИЕ ВТОРЖЕНИЙ В СЕТЬ ИНТЕРНЕТА ВЕЩЕЙ С ПОМОЩЬЮ МАШИННОГО ОБУЧЕНИЯ НА ОСНОВЕ НАБОРА ДАННЫХ UNSW-NB15

Аннотация

В данной исследовательской работе исследуется эффективность различных методов машинного обучения для решения задачи обнаружения сетевых аномалий в контексте сред Интернета вещей (IoT). Используя разнообразный набор параметров оценки, включая точность, прецизионность, отзыв, оценку F1, время обучения и анализ рабочих характеристик приемника (ROC), систематически сравниваются шесть различных методов машинного обучения. Полученные результаты подчеркивают практическую применимость логистической регрессии, которая является надежным выбором благодаря своим сбалансированным эксплуатационным характеристикам. Логистическая регрессия не только демонстрирует высокую точность обнаружения сетевых аномалий, но и значительно сокращает время обучения, что делает ее особенно подходящей для реальных приложений, где своевременное реагирование на аномалии имеет решающее значение. Это исследование дает ценную информацию о применении методов машинного обучения для повышения безопасности и целостности сетей Интернета вещей, решения сложных задач, связанных с обнаружением сетевых аномалий, и подчеркивает практическую значимость этих методологий в меняющемся ландшафте кибербезопасности Интернета вещей.

Ключевые слова: Интернет вещей, вторжение, обнаружение атак, машинное обучение, классификация.

Article submission date: 13.02.2024

UDC 004.021
IRSTI 28.25.23

https://doi.org/10.55452/1998-6688-2024-21-3-58-65

[1]Amanov A.,
PhD student, ORCID ID: 0000-0002-7669-0656,
e-mail: alimzhan.amanov@gmail.com

[1]Kazakh-British Technical University, 050000, Almaty, Kazakhstan

ENHANCED ALGORITHM FOR COMPUTING CAYLEY'S FIRST HYPERDETERMINANT

Abstract

Combinatorial hyperdeterminant DET – is the homogeneous polynomial in the entries of a hypermatrix of even number of indices, which is also a unique SL-invariant of minimal degree. It was first studied by Cayley in the middle of 19-th century. Given its fundamental nature, the computation of this polynomial is an important task. For fixed d and a cubical hypermatrix X of length n Barvinok introduced an algorithm of computing hyperdeterminant in $\mathrm{O}(2^{\mathrm{nd}}\mathrm{n}^{\mathrm{d}-1})$. Since the problem of deciding whether for the given hypermatrix X the hyperdeterminant $\mathrm{DET(X)}$ is equal to zero is NP-hard, it is essential to develop efficient algorithm for computing hyperdeterminant, as the size of problem grows exponentially. We provide enhanced algorithm of computing hyperdeterminant that requires $\mathrm{O}(2^{\mathrm{n(d-1)}}\mathrm{n}^{\mathrm{d}-1})$ arithmetic operations.

Key words: Cayley's first hyperdeterminant, SL-invariant, Laplace expansion.

Introduction

The concept of hyperdeterminants has its roots in the study of multidimensional matrices or hypermatrices, which are generalizations of the conventional two-dimensional matrices to higher dimensions. The notion was coined by Arthur Cayley in the mid of 19-th century [1, 2], where he introduced first generalization of ordinary determinant, which is now referred to Cayley's first or combinatorial hyperdeterminant. Formally, let $T_d(n)$ denotes the space of tensors

$$T_d(n) := \mathbb{C}^n \otimes \mathbb{C}^n \otimes \ldots \otimes \mathbb{C}^n$$

i.e. d – dimensional hypermatrices. See [10] for extensive review. Throughout the paper d regarded as even positive integer number. Define a function of a hypermatrix $\{X(i_1, \ldots i_d)\}_{i_k \in [1,n]} = X \in T_d(n)$ as follows:

$$DET(X) := \frac{1}{n!} \sum_{\sigma_1 \in S_n, \sigma_2 \in S_n, \ldots, \sigma_d \in S_n} \mathrm{sgn}(\sigma_1 \ldots \sigma_d) \prod_{i=1}^{n} X\big(\sigma_1(i), \ldots, \sigma_d(i)\big), \quad (1)$$

where S_n denotes the set of permutations of length n.

While determinants of two-dimensional matrices have been extensively studied and utilized in various mathematical and physical applications, the exploration of hyperdeterminants in the realm of higher-dimensional arrays is relatively nascent yet profoundly significant. For instance, the computation of a determinant of an ordinary $n \times n$ matrix requires $O(n^3)$ arithmetic operations, i.e. polynomial time. Some properties of ordinary determinant can be generalized to the context of hyperdeterminant, such as Binet-Cauchy formula or Laplace expansion. On the other hand, other

concepts cannot be easily described: the rank of hypermatrix or the zero locus (set of hypermatrices that nulls) of combinatorial hyperdeterminant.

In [3] Barvinok showed the algorithm of computing hyperdeterminant in $O(2^{nd}n^d)$ arithmetic operations, that we refer in this paper as Algorithm 1. In this paper, we provide an enhancement of that algorithm, that we refer to as Algorithm 2.

Theorem 1. (Main theorem) Algorithm 2 computes the hyperdeterminant of a given d-dimenisonal hypermatrix A of length n in $O\left(2^{n(d-1)}n^{d-1}\right)$ arithmetic operations.

Presented algorithm works faster in 2^n times which is an essential optimization, since the size of a problem grows exponentially with growth of n or d. Since there is no hope for computing hyperdeterminant faster than the exponential time (since most tensor problems are NP-hard [4]), any enhancement of known algorithms can make a difference.

The study of hyperdeterminants was initiated by Arthur Cayley in the middle of 19-th centure [1, 2]. He first discovered combinatorial hyperdeterminant $DET(X)$, which nowadays referred to as Cayley's first hyperdeterminant for even d, along with Cayley's second hypdeterminant of a $2 \times 2 \times 2$ hypermatrices. In later papers, he refers to any $SL(n)^d$ invariant polynomial as hyperdeterminant.

In 1990s Gelfand-Kapranov-Zelevinsky introduced generalization of Cayley's second hyperdeterminant [5], which possess geometric properties of ordinary determinant and Cayley's second hyperdeterminant, which is referred to as geometric hyperdeterminant. Gemotric hyperdeterminant finds connections in various areas. For instance, it sheds light on the structure of tensors spaces [18]. Nevertheless, from computational point of view, geometric hyperdeterminant is infeasible, since the degree grows exponentionally as n or d grows. Moreover, no general formula is known.

The general problem of deciding if combinatorial hyperdeterminant vanishes is NP-hard [4], yet for some classes of (relatively sparse) tensors there are polynomial time algorithms [9]. See also [19] for exposition on tensors in computations.

In general, study of invariants of tensors is an important problem. For instance, discoveries of invariant theory may affect the asymptotic of matrix multiplication, see [14], see [16] for review of the subject. Recent advancements in the complexity of isomorphism problems have provided new insights into the computational challenges associated with tensor computations. In [11] authors introduce the concept of tensor isomorphism-completeness, establishing that many isomorphism problems for tensors are as hard as the general isomorphism problem for tensors.

In turn, combinatorial hyperdeterminant is of minimal degree n (i.e. multi-linear function) and has a simple formula. In 20-th century, some research were established to lift proprties of ordinary determinant to hyperdeterminant. In particular, due to its linear nature, several properties were obtained [6, 7], such as Laplace Expansion, Minor summation formula and Binet-Cauchy formula.

This hyperdeterminant has wide range of applications. Luque and Thibon [7] explored hyperdeterminants within the context of Selberg's and Aomoto's integrals, using purely algebraic methods to evaluate hyperdeterminants of Hankel type. This work highlighted the broader applicability of hyperdeterminants in multidimensional integrals and reinforced their role in mathematical physics. In [15], within the context of SYK model with one time point, half-wormhole contribution in factorization of decoupled systems is expressed through a hyperpfaffian (which is closesely related to hyperdeterminant) of the tensor of SYK couplings. It is also related to characteristic polynomials of hypergraphs [20].

In combinatorics, in attempt to extend Kasteleyn theory for hyperdeterminants, Lammers [12] expressed number of perfect matchings of a hypergraph as hyperdeterminant of Kasteleyn hypermatrix, by analogy with $d = 2$ case. In [13], the author expresses so called Alon-Tarsi number as hyperdeterminant evaluated at Levi-Cevita tensor, i.e. the signed sum over Latin squares, which is

realted to famous Alon-Tarsi and Rota-Basis conjectures. Matsumoto shown that hyperdeterminant has nice applications it algebraic combinatorics [21].

In quantum mechanics, hyperdeterminants (in general sense) have applications in characterizing multipartite entanglement. In [17] the authors show, that in some sense, hyperdeterminant shows the measure of entanglement of even number of qubit state.

Hyperdeterminants have applications in proving lower bounds on tensor ranks. In [8] it was demonstrated that nonzero hyperdeterminants imply lower bounds on certain types of tensor ranks. This result applies certain ranks of tensors, providing upper bounds on some generalizations of colored sum-free sets based on constraints related to order polytopes. An appealing feature of hyperdeterminants is that they are explicit and can be a good algebraic tool allowing computations using various operations, which also includes methods for constructing tensors with nonzero hyperdeterminants, see [8].

Main provisions

We denote $[n] = \{0, \dots, n-1\}$. We call the set $[n]^d$ box and refer to elements of the box $[n]^d$ as cells. A slice of $[n]^d$ is a subset of all cells with fixed i-th coordinate (called direction) for some $i \in [d]$. A diagonal of the box $[n]^d$ is a subset of size n with no two cells lying in the same slice. Then the sum (1) of hyperdeterminant runs over diagonals of a box $[n]^d$.

Let $V = (\mathbb{C}^n)^{\otimes d}$ be the space of tensors (state space). Elements of V written in a fixed basis correspond to hypermatrices $\left(X_{i_1,\dots,i_d}\right)$ indexed by $(i_1, \dots, i_d) \in [n_1] \times \dots \times [n_d]$ and we shall identify tensors in V with corresponding hypermatrices by the following:

$$X = \sum_{i_1,\dots,i_d \in [n]} X(i_1, \dots, i_d) e_{i_1} \otimes \dots \otimes e_{i_d}. \quad (2)$$

For given hypermatrix $X \in T_d(n)$ and k-element subsets d-tuple $(I_1, \dots, I_d) \in \binom{[n]}{k}^d$ we denote X_I the subhypermatrix resulting in restricting set of indices in r-th direction to I_r, and hyperdeterminant of X_I we call I-minor.

The group $G = SL(n)^{\times d}$, of d −tuple of matrices of determinant equal to 1, naturally acts on the space of tensors $V = (\mathbb{C}^n)^{\otimes d}$ by

$$(A_1, \dots, A_d) v_1 \otimes \dots \otimes v_d = A_1 v_1 \otimes \dots \otimes A_d v_d \quad (3)$$

for $A_i \in SL(n), v_i \in \mathbb{C}^n$ and extended multilinearly.

Polynomial $P(X)$ with argument $X \in T_d(n)$ is called G-invariant (we will simply write invariant) if $P(g \cdot X) = P(X)$ for any $g \in G$. Then the combinatorial hyperdeterminant (we will simply write hyperdeterminant) is the unique G-invariant polynomial of degree n on tensors $T_d(n)$ [7]. Hyperdeterminant possess the following defining property, similar to the ordinary determinant.

Proposition 2. (Defining properties) Let $F: T_d(n) \to \mathbb{C}$ be the function that satisfy:

(a) (Multilinearity) F is multilinear in slices in each direction, i.e. for first direction

$$F(X + \alpha e_i \otimes Y + \beta e_i \otimes Z) = \alpha F(X + e_i \otimes Y) + \beta F(X + e_i \otimes Y)$$

where X is tensor with i-th slice equal to zero and $Y, Z \in T_{d-1}(n)$, and similar for other directions.

(b) (Skew-symmetry) If two slices in fixed direction of tensor X coincide, then

$$F(X) = 0.$$

(c) (Normalization) $F(I_n) = 1$.

Then $F = DET$.

Materials and Methods

We first introduce the result of Barvinok. For that, we need the following lemma. For simplicity of notation, let us denote the set difference between d-tuples of sets: if $A, B \subseteq [n]^d$ then define $A \backslash\backslash B := A_1 \backslash B_1 \times \ldots \times A_d \backslash B_d$.

Lemma 3. (Laplace Expansion) Let X be a tensor in $T_d(n)$ and $j \in [n]$ fixed. Then

$$DET(X) = \sum_{i=(j,i_2,\ldots,i_d)\in[n]^d} (-1)^{j+i_2+\cdots+i_d-d} X(i) \cdot \mathrm{DET}(\mathrm{X}_{[\mathrm{n}]^{\mathrm{d}}\backslash\backslash i} \qquad (4)$$

where $\boldsymbol{i}$ is regarded both as the set $\{i_1\} \times \ldots \times \{i_d\}$ and a cell $(i_1, \ldots, i_d)$.

See [7] for proof of this result. In other words, we expand hyperdeterminant along j-th slice in the first direction, similar to Laplace expansion for ordinary determinant. Here the choice of the first direction

This lemma is crucial in the following algorithms as it provides a recursive formula of calculation of a hyperdeterminant.

A. Barvinok Algorithm

Input: a natural number d and n, d-dimensional tensor X of length n

$$X = \{X(i_1, \ldots, i_d): 1 \le i_1, \ldots, \mathrm{i_d} \le n\}$$

Output: the number $DET(X)$.

Algorithm: Use the dynamic programming based on recurrence (4). Iterate over tuple subsets $I = (I_1, \ldots, I_d) \in \binom{[n]}{k}^d$ in increasing order of $k = 2, \ldots, n$ and compute the I-minor $DET(X_I)$. The base case $k = 1$ is hyperdeterminant of single entry hypermatrix, hence for $I_1 = \{i_1\}, \ldots, I_d = \{i_d\}$ has initial value $DET(X_I) = X(i_1, \ldots, i_d)$. Consequently, assume all size $k-1$ minors are computed, and we are to compute size k minor I. Let $\phi_c(i)$, for $c \in [d], i \in [k]$, denote the i-th element of I_c. Then by Lemma 3:

$$DET(X_I) = \sum_{i=(1,i_2,\ldots,\mathrm{i_d})\in[k]^d} (-1)^{1+i_2+\cdots+i_d-d} X\big(\phi(\boldsymbol{i})\big) \cdot DET\big(X_{I\backslash\phi(i)}\big), \qquad (4)$$

where $\phi(\boldsymbol{i}) = \big(\phi_1(i_1), \phi_2(i_2), \ldots, \phi_d(i_d)\big)$.

Time and memory complexity: there are $\sum_{k=1}^{n}\binom{n}{k}^d = O(2^{nd})$ states and for the state of cardinality k we compute the value in $O(k^{d-1})$ time, hence the total time complexity is $O(2^{nd}n^{d-1})$.

B. Improved algorithm

The algorithm essentially optimizes the number of states we need to visit. Since Laplace expansion formula offers expansion of the hyperdeterminant along any slice, we will proceed by calculating minors in the first k slices of first direction, i.e. $I_1 = \{1, \ldots, k\}$ at k-th step.

Input: a natural number d and n, d-dimensional tensor X of length n

$$X = \{X(i_1, \ldots, i_d): 1 \le i_1, \ldots, i_d \le n\}$$

Output: the number $DET(X)$.

Algorithm: iterate over $k = 1, \ldots$,n and fix $I_1 = \{1, \ldots, k\}$. Iterate over all possible subsets $I_2, \ldots, I_d \subseteq [n]$ such that $|I_c| = k$. As before, assume all minors of size $k-1$ with set of indices in the first direction I_1 equal to $[k-1] = \{1, \ldots, k-1\}$ are computed and we are to compute I-minor.

Let $\phi: I \to [k]^d$ be as above. By Laplace expansion, we expand I-minor of X along the last slice to obtain:

$$DET\left(X_{([k],I_2,\ldots,I_k)}\right) \sum_{\mathbf{i}=(k,i_2,\ldots,i_d)\in[k^d]} X(\mathbf{i}) \cdot DET\left(X_{[k-1],I_2\setminus\{i_2\},\ldots,I_d\setminus\{i_d\}}\right). \quad (5)$$

Since the terms in the sum are size-$(k-1)$ minors of X with indices of the first direction restricted to the set $[k-1]$, the algorithm is correct.

Time complexity: we reduce number of states in 2^n times, hence we require $O(2^{n(d-1)}n^{d-1})$ arithmetic operations and $O(2^{n(d-1)})$ of space.

Results and Discussion

In this section we show compative results of improved algorithm. While the asymtotic behaviour of number of operations involved is still exponential, for fixed d, the improvement provides dramatic increase in performance, allowing to compute hyperdeterminant of a tensor for $n \leq 20$ in reasonable time on a standard computer.

Table 1 – Comparison of performance of original and improved algorithms for d = 4

	Algorithm 1		Algorithm 2	
n	Number of operations	Estimated time	Number of operations	Estimated time
1	8	8 ns	4	4 ns
2	256	256 ns	64	64 ns
3	4,608	4.608 µs	576	576 ns
4	65,536	65.536 µs	4096	4.096 µs
5	819,200	819.200 µs	25600	25.600 µs
6	9,437,184	9.437 ms	147456	147.456 µs
7	102,760,448	102.760 ms	802816	802.816 µs
8	1,073,741,824	1.1 s	4194304	4.2 ms
9	10,871,635,968	11 s	21233664	21 ms
10	107,374,182,400	2 min	104857600	105 ms
11	1,039,382,085,632	17 min	507510784	508 ms
12	9,895,604,649,984	3 hr	2415919104	2.5 s
13	92,908,732,547,072	1 day	11341398016	11 s
14	862,017,116,176,384	10 days	52613349376	53 s
15	7,916,483,719,987,200	92 days	241591910400	4 min
16	72,057,594,037,927,936	2.3 years	1099511627776	18 min
17	650,770,146,155,036,672	20 years	4964982194176	1.4 hr
18	5,836,665,117,072,162,816	186 years	22265110462464	6.2 hr
19	52,025,582,895,383,969,792	1650 years	99230924406784	1.2 days
20	461,168,601,842,738,790,400	14623 years	439804651110400	5 days

See Table 1 for comparison of time performance. The values taken in the table are estimations given that the standard computer performs 10^9 operations per second. Also see Figure 1 that displays the same information graphically.




Figure 1 – Comparison of arithmetic operations between algorithms for d = 4

Note that on Figure 1 we have a log base 10 scale of y-axis, so the result looks almost linear.

Information on funding

This research was supported by the Science Committee of the Ministry of Science and Higher Education of the Republic of Kazakhstan (Grant No. AP14869221).

REFERENCES

1 Cayley A. On the theory of determinants. Pitt Press, 1844.

2 Cayley A. On the theory of linear transformations. E. Johnson, 1845.

3 Barvinok A.I. New algorithms for linear k-matroid intersection and matroid k-parity problems. Mathematical Programming. 1995 Jul, 69:449–70.

4 Hillar C.J., Lim L.H. Most tensor problems are NP-hard. Journal of the ACM (JACM), 2013, 60(6), 1–39.

5 Gelfand I.M., Kapranov M.M., and Zelevinsky A.V., Hyperdeterminants, Advances in Mathematics, Dec. 1992, vol. 96, no. 2, pp. 226-263. https://doi.org/10.1016/0001-8708(92)90056-q

6 Sokolov N.P. Introduction to the theory of multidimensional matrices, Nukova Dumka, Kiev, 1972. [in Russian]

7 Luque J.G., and Thibon J.Y. Hankel hyperdeterminants and Selberg integrals. Journal of Physics A: mathematical and general, 2003, vol.36, no. 19, p. 5267.

8 Amanov A. and Yeliussizov D. Tensor slice rank and Cayley's first hyperdeterminant. Linear Algebra and its Applications, 2023, 656, pp. 224–246.

9 Cifuentes D. and Parrilo P.A. An efficient tree decomposition method for permanents and mixed discriminants. Linear Algebra and its Applications, 2016, 493, pp. 45–81.

10 Lim L.-H. Tensors and hypermatrices, Handbook of Linear Algebra, 2013, pp. 231–260.

11 Grochow J.A., & Qiao Y. On the Complexity of Isomorphism Problems for Tensors, Groups, and Polynomials I: Tensor Isomorphism-Completeness, Leibniz International Proceedings in Informatics (LIPIcs), 2021, vol. 2021, pp. 31:1-31:19, https://doi.org/10.4230/LIPIcs.ITCS.2021.31.

12 Lammers P.A generalisation of the honeycomb dimer model to higher dimensions. The Annals of Probability, 2021, vol. 49, no. 2, pp. 1033–66.

13 Zappa P. The Cayley determinant of the determinant tensor and the Alon–Tarsi conjecture. Advances in Applied Mathematics, 1997 Jul 1, vol. 19, no.1, pp. 31–44.
14 Blasiak J., Church T., Cohn H., Grochow J.A., Naslund E., Sawin W.F., and C. Umans. On cap sets and the group-theoretic approach to matrix multiplication, Discrete Anal., 2017, paper no. 3, 27 p.
15 Mukhametzhanov B. Half-wormholes in SYK with one time point. SciPost Physics, 2022, vol. 12, no. 1, p. 029.
16 Wigderson A. Non-commutative Optimization-Where Algebra, Analysis and Computational Complexity Meet. InProceedings of the 2022 International Symposium on Symbolic and Algebraic Computation 2022 Jul 4, pp. 13–19.
17 Dobes I., Jing N. Qubits as hypermatrices and entanglement. Physica Scripta. 2024 Apr 11, vol. 99, no. 5, p. 055110.
18 Turatti E. On tensors that are determined by their singular tuples. SIAM Journal on Applied Algebra and Geometry, 2022, vol. 6, no. 2, pp. 319–338.
19 Lim LH. Tensors in computations. Acta Numerica. 2021 May, no. 30, pp. 555–764.
20 Zheng YN. The characteristic polynomial of the complete 3-uniform hypergraph. Linear Algebra and its Applications. 2021 Oct 15, no. 627, pp. 275–286.
21 Matsumoto S. Hyperdeterminantal expressions for Jack functions of rectangular shapes. Journal of Algebra. 2008 Jul 15, vol. 320, no. 2, pp. 612–632.

[1]Аманов Ә.,
докторант, ORCID ID: 0000-0002-7669-0656,
e-mail: alimzhan.amanov@gmail.com

[1]Қазақстан-Британ техникалық университет, 050000, Алматы қ., Қазақстан

КЭЙЛИ БІРІНШІ ГИПЕРДЕТЕРМИНАНТЫН ЕСЕПТЕУДІҢ ЖЕТІЛДІРІЛГЕН АЛГОРИТМІ

Аңдатпа

Комбинаторлық гипердетерминант DET – бұл жұп индекстер саны бар гиперматрица жазбалары бойынша біртекті көпмүше, сондай-ақ ол ең төменгі дәрежелі жалғыз SL-инварианты. Бұл тұжырымды алғаш рет 19 ғасырдың ортасында Кэйли зерттеген. Оның іргелі сипатына байланысты бұл көпмүшенің есебін шығару маңызды мәселеге айналды. Барвинок белгілі бір d және ұзындығы n болатын кубтық гиперматрица X үшін гипердетерминантты есептеудің $O(2^{nd}n^{d-1})$ алгоритмін ұсынды. DET(X) гипердетерминантының берілген гиперматрица X үшін нөлге тең болу мәселесі NP-қатерлі болғандықтан, гипердетерминантты тиімді есептеу алгоритмін анықтау қажет, себебі есептің көлемі экспоненциалды түрде өседі. Біз гипердетерминантты есептеудің жақсартылған алгоритмін ұсынамыз, ол $O(2^{n(d-1)}n^{d-1})$ арифметикалық операцияларды қажет етеді.

Тірек сөздер: инвариантты көпмүшелер, кванттық түйісу, SLOCC.

[1]Аманов А.,
докторант, ORCID ID: 0000-0002-7669-0656,
e-mail: alimzhan.amanov@gmail.com

[1]Казахстанско-Британский технический университет, 050000,
г. Алматы, Казахстан

УЛУЧШЕННЫЙ АЛГОРИТМ ВЫЧИСЛЕНИЯ ПЕРВОГО ГИПЕРДЕТЕРМИНАНТА КЭЛИ

Аннотация

Комбинаторный гипердетерминант DET – это однородный многочлен от элементов гиперматрицы с четным числом индексов, который является единственным SL-инвариантом минимальной степени, который

впервые стал изучать Кэли в середине XIX века. Учитывая его фундаментальную природу, вычисление этого многочлена является важной задачей в разных разделах науки. Для фиксированного d и кубической гиперматрицы X Барвинок предложил алгоритм вычисления гипердетерминанта, используя $O(2^{nd}n^{d-1})$ арифметических операций. Поскольку задача определения, равен ли гипердетерминант $DET(X)$ данной гиперматрицы X нулю, является NP-трудной, крайне важно разработать наиболее эффективный алгоритм, так как размер задачи растет экспоненциально. Мы предлагаем улучшенный алгоритм вычисления гипердетерминанта, который требует $O(2^{n(d-1)}n^{d-1})$ арифметических операций.

Ключевые слова: первый гипердетерминант Кэли, SL-инвариант, разложение Лапласа.

Article submission date: 29.07.2024.

UDC 004.93
IRSTI 28.23.15

https://doi.org/10.55452/1998-6688-2024-21-3-66-77

[1]*Vykhodtseva V.A.,
Master student, ORCID ID 0009-0007-1897-0768,
e-mail: vykhodtseva.va@gmail.com
[1]Popova G.V.,
PhD, Associate Professor, ORCID ID 0000-0002-6935-1066,
e-mail: gpopova@edu.ektu.kz

[1]Kazakh-American Free University, 070000, Ust-Kamenogorsk, Kazakhstan

APPLICATION OF MACHINE LEARNING TECHNIQUES TO INCREASE THE LEVEL OF ACCURACY OF OPTICAL CHARACTER RECOGNITION RESULTS

Abstract

One of the most pervasive processes of modernity is undoubtedly digitalization, which has encompassed all key spheres of human life. The development of information technology has contributed to large-scale changes not only in the everyday aspect of life, but also more globally, automating complex business processes in the field of entrepreneurship, economics, and healthcare. The transition to digital data and documentation has provided greater accessibility to necessary information and has also enhanced the efficiency of its analysis and processing. Due to this fact, optical character recognition (OCR) technology has gained significant importance, enabling the identification and extraction of textual data from images. OCR systems play a pivotal role in the digital transformation of society as they eliminate the need for manual handling of textual information in images and are applicable in automating the majority of business processes associated with paper-based data processing, such as gathering statistical data from paper forms, reflecting paper documents in electronic document management systems, converting textual information into audio files, and so on. This paper is dedicated to describing optical character recognition technology, as well as providing an overview of machine learning techniques that are actively used in the context of its modern implementation, in order to enhance the quality of the obtained results. In addition, the paper presents the principles of operation of the described approaches, their capabilities, as well as some limitations that may be encountered when using them in various scenarios.

Key words: optical character recognition, features, machine learning, deep learning, convolutional neural network, recurrent neural network.

Introduction

In the digital age, where key business operations rely on processing large volumes of information, the ability to quickly and accurately extract valuable information from text data is of paramount importance. This is why many large enterprises have become interested in implementing optical character recognition (OCR) technology. This is due to the proliferation of unstructured text data, such as invoices, receipts, contract forms, and therefore it poses a challenge for such organizations seeking efficient, streamlined business processes and high competitiveness. Optical character recognition is a technology that enables the recognition and conversion of data located in images into machine-readable text. The data obtained in this way can be analyzed or processed using appropriate software. Thus, there is no need for manual data entry from images for their subsequent use as a text format [1]. As this mechanism began to be more actively studied, the possibility of integrating optical character recognition and deep learning techniques was discovered, which revolutionized the accuracy, efficiency and versatility of text recognition systems. Using the power of neural networks and data-driven learning, optical character recognition systems have overcome long-standing limitations and

are now able to identify text with unprecedented accuracy and efficiency. This combination is capable of recognizing handwritten text in images and analyzing printed documents with complex fonts. The use of deep learning models has opened up unprecedented possibilities, taking OCR technology to new levels of performance and applicability.

Literature Review

In recent years, issues related to optical character recognition technology have become increasingly prevalent both within the IT and research communities [1–7]. Early research in optical character recognition mainly relied on classical algorithms to perform character recognition tasks. However, the advent of deep learning has revolutionized the field by introducing a data-driven approach that learns complex patterns and representations directly from raw input data. However, the advent of machine learning, in particular deep learning, has revolutionized the field by introducing an approach based on automatically learning complex patterns and representations directly from raw input data. It is issues related to the implementation of the integration of optical character recognition and deep learning techniques that have become the main focus of many studies. Papers such as [8, 10, 12] have demonstrated the effectiveness of neural networks in developing systems capable of performing character recognition on images with complex structures and specific characteristics. One of the most important issues is the recognition of handwritten text, which was highlighted in studies [13, 14, 16, 17] that explored the solutions of the problem using recurrent and convolutional neural networks. Studies [19, 20] reveal the features of a hybrid architecture consisting of these two neural networks and its application in complex tasks. Papers [21–25] are dedicated to the Tesseract system, which embodies all the capabilities inherent in a modern optical character recognition system, including learning from training data using neural networks. They demonstrate the practical results of using this mechanism.

Main provision

Optical character recognition technology includes the following stages of image processing:

1. Image preprocessing. This stage involves operations to enhance the quality and legibility of the image: it aligns the image, reduces background noise, and increases the contrast of relevant areas. At this step, binarization is also performed, which is converting the image into a format consisting of 0 and 1 and visually rendering the image in black and white [2];
2. Segmentation. This is the step at which the mechanism analyzes the provided image and identifies areas with text, lines, distances between words, and other attributes [3];
3. Character recognition. At this stage, the technology performs a series of procedures to identify each character and convert it into text. There are two algorithms that are possible in this case: pattern recognition and feature detection;
4. Post-processing and correction. If errors or distortions are detected, the system corrects them and takes additional steps to improve the quality of the recognized text. At this stage, individual characters are combined into words, and text formatting is performed to ensure its structured presentation [4].

The sequence of steps is more clearly illustrated in Figure 1.

Concerning the above-mentioned classic OCR technology algorithms, in pattern recognition, a set of pre-prepared image samples or character templates stored in memory is utilized to compare against the corresponding character in the image [5]. This approach operates quite successfully under conditions in which the image possesses high quality without significant distortions, and the text contained within it is clear for recognition. The feature detection method, in turn, is based on the characteristics of each character, such as how many lines it contains, whether these lines intersect, the proportions of the character, and so on [6]. The characters are subsequently classified according

to the identified features, and character recognition occurs based on this classification. In case the technology supports multiple languages, additional classification based on fonts and alphabets is carried out.




Figure 1 – Stages of operation of an OCR system

In Figure 2, this algorithm execution process is presented in the form of a generalized block diagram.

Despite the fact that these algorithms are capable of detecting and converting text in images, the quality of their output can vary significantly depending on the characteristics of the input image: the noise level, font, language of the text, and so on [7]. For this reason, optical character recognition technology is increasingly being combined with machine learning techniques, since such a combination has demonstrated the most accurate results in text recognition in images [8].




Figure 2 – Algorithm of an OCR system

It should be noted that machine learning is a subfield of artificial intelligence that enables a system to learn from training data — the better the model is trained, the higher the accuracy of character recognition, even on complex images [9]. When using machine learning techniques in an OCR algorithm, a large amount of labeled data is required to train the models, since the appearance of images belonging to the same category can be presented in different ways, for instance, the arrangement of fields with the same text may differ across different image samples [10]. Therefore, images with non-standard elements or complex structures may be an obstacle to the effective decision-making of machine learning models. A general scheme of how machine learning works is presented in Figure 3.




Figure 3 – Stages of classical machine learning

In order to make optical character recognition algorithms more flexible, deep learning has become even more widespread. It is a subfield of machine learning that utilizes multi-layered neural networks to automatically extract complex hierarchical features from data, rather than just using samples as training data [11]. Neural networks are a collection of many interconnected nodes that interact with each other during the process of data processing. Each node in such a neural network is responsible for solving a specific task, and after its completion, the processed data is transferred to the next node.

Materials and methods

Deep learning demonstrates high accuracy and robustness to various image characteristics, such as noise, blur, scale variation, and distortion [12]. As for limitations of this approach, it should be noted that such models operate only with a large amount of training data and require significant computational power for complex mathematical calculations. Damaged or incomplete data can therefore affect the accuracy and quality of the obtained result. The general sequence of steps in deep learning is schematically presented in Figure 4.




Figure 4 – Stages of deep learning

In the context of OCR technology, as a rule, two types of neural networks are used for text recognition in images: convolutional neural networks (CNN) and recurrent neural networks (RNN) [13]. Their usage in solving this problem ensures the highest level of accuracy in character recognition, even on very difficult-to-read images.

Recurrent neural networks are used to process sequences efficiently. They process text in an image as a sequence of characters, capturing contextual dependencies, since their architecture involves loops that allow previous states to be remembered when processing new data. Information about previous data is transmitted using hidden states, which is the internal state of the network at the current time step. At each such time step, the input data and the current hidden state are used to compute a new hidden state, and this new hidden state is passed on to the next time step and used again to analyze the next element of the sequence [14]. When dealing with different languages, such a neural network can be used in combination with language models to ensure text recognition in images, taking into account the linguistic context. Recurrent neural networks are often used in tasks related to text analysis when translating into another language, time series, sequence generation, and audio signal analysis.

The update of the hidden state h_t at time step t can be represented by the following mathematical formula:

$$h_t = \sigma(W_{hx}x_t + W_{hh}h_{t-1} + b_h) \quad (1)$$

Where x_t is the input vector at the current time step, h_{t-1} is the previous hidden state, W_{hx} и W_{hh} are the weight matrices for the input and hidden states, respectively, b_h is the displacement vector, σ – activation function.

A general and detailed diagram of a recurrent neural network is presented in Figure 5.




Figure 5 – Recurrent neural network

In the context of optical character recognition, a recurrent neural network takes a sequence of input vectors, which are the characters of the text in an image, and then updates its internal state at each step [15].

Convolutional neural networks are also used in OCR systems to effectively extract characteristic features of text in an image, since they are adapted to work with data that has many coordinates [16]. Their architecture consists of:

1. A convolutional layer to extract significant features, for example, character outline, texture, character shapes;
2. Pooling layer to reduce the dimensionality of the output data;
3. Flatten layer as an activation function to form more complex functions at the output of the layer;
4. A fully connected layer is usually the final layer in which each neuron is connected to all neurons of the previous layer [17].

As mentioned above, in the convolutional layer, a neuron is connected to some local area of the previous layer, and in a fully connected layer, a connection is made to all neurons. The convolution operation in CNN can be represented mathematically as follows:

$$(I * K)(i, j) = \sum_m \sum_n I(i + m, j + n) K(m, n) \qquad (2)$$

Where I is the input image, K is the convolution kernel (filter), (I * K)(i, j) is the result of convolution at position (i, j) [18].

Within the task of text recognition in an image, this operation allows for the calculation of the weighted sum of pixel values in the input image, overlaid with a convolution kernel. The result of convolution is a feature map containing information about spatial patterns in the image.

In addition to text recognition in images, convolutional neural networks are often used in tasks such as image classification and recognition of objects or faces within them.

The general scheme of operation of a convolutional neural network is presented in Figure 6.




Figure 6 – Convolutional neural network

In addition, a convolutional neural network can work in the same architecture as a recurrent neural network. The combination of these two architectures, called convolutional recurrent neural network (CRNN), gives better results when processing images containing text. It consists of three components: a convolutional layer, followed by a recurrent layer, and a transcription layer [19]. Based on the previously described properties of these neural networks, the CNN layer is used to extract spatial features from images, then the obtained results are transferred to the RNN layer to analyze the sequence of characters taking into account previous contexts. This allows for the efficient formation of complete words and sentences from each recognized character based on this relationship [20]. In addition, these layers of the architecture are trained synchronously, which allows the model to effectively work with both local and global image contexts. This architecture is quite complex and demanding on computing resources, but it is more universal for a wide range of tasks for recognizing characters in an image. Convolutional recurrent neural network is often used in handwritten text analysis tasks. A general diagram of the functioning of the CRNN architecture in the context of OCR is presented in Figure 7.

Based on the above, it should be noted that the choice of a particular technique depends on the type of input data intended to be used. Complex fonts, low image quality, characteristics of alphabets, and unpredictable placement of the same elements on different images significantly affect the results of OCR system operation. In cases where basic conversion of text in an image into a machine-readable format is required, or when only high-quality and easily readable images are used, classic algorithms are also suitable, since the results in this case are quite predictable and the conversion process is more likely to not require complex processing algorithms, which, for example, offer machine learning

techniques. However, the application of machine learning techniques, specifically deep learning, allows for solving multi-level problems associated with recognizing text in an image. Using this approach, it is possible to work with a much larger set of input data, since their characteristics are taken into account at each stage of the functioning of neural networks and have little impact on the result, provided that the model is highly trained.



Figure 7 – Convolutional recurrent neural network

Results and discussion

As an example of one of the modern OCR systems, Tesseract should be mentioned. This mechanism was originally developed by the Hewlett-Packard Laboratories research group in the 1980s and released as open-source functionality in 2005 and at that time the system was only capable of recognizing text in English [21]. Currently, this system provides the ability to work with several languages simultaneously. The general principle of Tesseract is to analyze an image and discover patterns for character recognition. The first step involves pre-processing the image, including increasing contrast and reducing noise, then executing the algorithms provided by the engine for feature detection and extraction, character edge detection, and pattern matching [22]. In its operation, Tesseract also utilizes deep learning techniques, such as convolutional neural networks, as well as a variant of recurrent neural networks called long short-term memory (LSTM) [23]. Through this approach, it is possible to recognize text in different languages and under different conditions, for example, when recognizing handwritten text [24].

Tesseract can be integrated into various functionality related to image recognition through the API and used in code written in programming languages such as C#, Python, C++ and so on [25]. For example, in the context of a Windows Forms application, in order to work with this system, it is necessary to connect the functionality to the working environment and initialize the mechanism by creating a new instance of the TesseractEngine class indicating the necessary parameters (language, mode, and so on). After this, the created object is used to access the Tesseract programming interface, in particular, to the Process() method, which is responsible for processing a pre-prepared image presented in a machine-readable format (Figure 8).

```
// Tesseract initialization
using (var engine = new TesseractEngine(@"C:                                    \Tesseract-OCR
  \tessdata", "eng+rus", EngineMode.Default))
{
    // Increasing the contrast of drawn lines
    Bitmap highContrastBitmap = PreprocessImage(drawingBitmap);

    // Saving a temporary image file
    temporaryImageFile = Path.GetTempFileName();
    highContrastBitmap.Save(temporaryImageFile, System.Drawing.Imaging.ImageFormat.Jpeg);

    // Loading the temporary image file using Tesseract
    using (var image = Pix.LoadFromFile(temporaryImageFile))
    {
        using (var page = engine.Process(image))
        {
            string recognizedText = page.GetText();
            MessageBox.Show($"Recognized text: {recognizedText}");
            textBox1.Text = recognizedText;
        }
    }
```

Figure 8 – Initialization of Tesseract and execution of recognition

Thus, Tesseract, using its built-in optical character recognition techniques, is capable of processing images and extracting even handwritten characters in various languages. Figure 9 illustrates the result of processing an image with handwritten text in English.




Figure 9 – The result of the algorithm execution with the text in English

The result of the mechanism processing an image with handwritten text in Russian is demonstrated in Figure 10.




Figure 10 – The result of the algorithm execution with text in Russian

Conclusion

Thus, machine learning techniques, in particular deep learning techniques, are regularly applied in the context of optical character recognition technology, as they enable the automatic extraction of characteristic features from raw data and generate a high-quality result based on these features in the form of correctly converted text in the image. These approaches and OCR technology itself continue to develop and find their application in various situations, ensuring efficiency, accessibility, and automation of business processes. The choice of neural network architecture depends on the specifics of the task, the available data, the required level of accuracy, as well as the data processing speed.

REFERENCES

1 Singh A., Bacchuwar K., Bhasin A. A survey of OCR Applications. International Journal of Machine Learning and Computing, 2012, vol. 2, no. 3, pp. 314–318.

2 Shruthi P. Verma D. C. A Detailed study and recent research on OCR. International Journal of Computer Science and Information Security, 2021, vol. 19, no. 2, pp. 52–66.

3 Ahmed. M, Abidi A.I. Review on optical character recognition. International Research Journal of Engineering and Technology (IRJET), 2019, June, v0l. 06, issue 06, pp. 3666–3669.

4 Verma P., Foomani G. M. Improvement in OCR Technologies in Postal Industry Using CNN-RNN Architecture: Literature Review. International Journal of Machine Learning and Computing, 2022, vol. 12, no. 5, 154–163.

5 What is optical character recognition (OCR)? Ibm.com. January 5, 2022. https://www.ibm.com/blog/optical-character-recognition/

6 Modi H., Parikh M. C. A Review on Optical Character Recognition Techniques International Journal of Computer Applications, 2017, vol. 160, no. 6, pp. 20–24.

7 Fateh A., Fateh M., Abolghasemi V. Enhancing optical character recognition: Efficient techniques for document layout analysis and text line detection. Engineering Reports, 2023, November, pp. 1–26.

8 Wang X.F., He Z.H., Wang K., Wang Y.F., Zou L. A survey of text detection and recognition algorithms based on deep learning technology. Neurocomputing, 2023, November, vol. 556.

9 AI vs. Machine Learning vs. DeepLearning vs. Neural Networks: What's the difference? Ibm.com. July 6, 2023. https://www.ibm.com/blog/ai-vs-machine-learning-vs-deep-learning-vs-neural-networks/

10 Subedi B., Yunusov J., Gaybulayev A., Kim T. Development of a Low-cost Industrial OCR System with an End-to-end Deep Learning Technology. IEMEK J. Embed. Sys. Appl, 2020, April, pp. 51–60.

11 Difference Between Machine Learning and Deep Learning. GeeksForGeeks.org. June 5, 2023. https://www.geeksforgeeks.org/difference-between-machine-learning-and-deep-learning/

12 Meng F., Ghena B. Research on Text Recognition Methods Based on Artificial Intelligence and Machine Learning. Advances in Computer and Communications, 2023, November, pp. 340–344.

13 Memon J., Sami M., Khan R. A. Handwritten Optical Character Recognition (OCR): A Comprehensive Systematic Literature Review (SLR). IEEE Access, 2020, July, pp. 142642–142668.

14 Rakesh S., Reddy P.K., Prashanth V., Reddy K.S. Reddy. Handwritten text recognition using deep learning techniques: a survey. ICMED, 2024, pp. 1–8.

15 Nikolenko S., Kadurin A., Arkhangelskaya E. Glyubokoye obucheniye: Seriya «Biblioteka programmista» (SPb.: Izd-vo Piter, 2018), pp. 231–259 [in Russian].

16 Hemanth G.R., Jayasree M., Keerthi Venii S., Akshaya P., and R. Saranya. CNN-RNN based handwritten text recognition. ICTACT Journal on Soft Computing, 2021, October, vol. 12, pp. 2457–2463.

17 Ahlawat S., Choudhary A., Nayyar A., Singh S., Yoon B. Improved Handwritten Digit Recognition Using Convolutional Neural Networks (CNN). Sensors, 2020, June, pp. 1–18.

18 Goodfellow I, Bengio Y, Courville A. Deep Learning, (The MIT Press, 2015), pp. 297–329.

19 Shinde S., Saraiya T. Using CRNN to Perform OCR over Forms. International Journal of Engineering Research & Technology (IJERT), vol. 9, pp. 319–323.

20 Shi B., Bai X., & Yao C. An end-to-end trainable neural network for image-based sequence recognition and its application to scene text recognition. IEEE Transactions on Pattern Analysis and Machine Intelligence, 2016, pp. 2–3.

21 Clausner C., Antonacopoulos A., Pletschacher S. Efficient and effective OCR engine training. International Journal on Document Analysis and Recognition (IJDAR), 2019, October, vol. 23, pp. 73–88.

22 Mursari L.R., Wibowo A. The Effectiveness of Image Preprocessing on Digital Handwritten Scripts Recognition with The Implementation of OCR Tesseract. Computer Engineering and Applications, 2021, October, vol. 10, pp. 177–186.

23 Bagwe S., Shah V., Chauhan J., Harniya P., Tiwari A., Gupta V., Raikar D., Gada V., Bheda U., Mehta V., Warang M., Mehendale N. Optical character recognition using deep learning techniques for printed and handwritten documents. SSRN Electronic Journal, 2020, January, pp. 1–10.

24 Patel C., Patel A., Patel D. Optical Character Recognition by Open Source OCR Tool Tesseract: A Case Study. International Journal of Computer Applications, 2012, October, vol. 55, pp. 50–56.

25 Jain P., Dr. Taneja K., Dr. Taneja Harmunish. Which OCR toolset is good and why? A comparative study. Kuwait J.Sci., 2021, April, vol. 48 (2), pp. 1–12.

[1]Выходцева В.А.,
магистрант, ORCID ID: 0009-0007-1897-0768
e-mail: vykhodtseva.va@gmail.com
[1]Попова Г.В.,
ф–м.ғ.к., қауымдастырылған профессор, ORCID ID: 0000-0002-6935-1066
e-mail: gpopova@edu.ektu.kz

[1]Қазақстан-Американдық еркін университеті,
070000, Өскемен қ., Қазақстан

ТАҢБАЛАРДЫ ОПТИКАЛЫҚ ТАНУ НӘТИЖЕЛЕРІНІҢ ДӘЛДІК ДЕҢГЕЙІН АРТТЫРУ ҮШІН МАШИНАЛЫҚ ОҚЫТУ ӘДІСТЕРІН ҚОЛДАНУ

Аңдатпа

Қазіргі заманның ең кең таралған үрдістерінің бірі – адамзат өмірінің барлық негізгі салаларын қамтыған цифрландыру. Ақпараттық технологиялардың дамуы күнделікті өмірдің ғана емес, сондай-ақ кәсіпкерлік, экономика, денсаулық сақтау саласындағы күрделі бизнес-үрдістерді автоматтандыру арқылы жаһандық деңгейдегі өзгерістерге де ықпал етті. Цифрлық деректер мен құжаттамаға көшу қажетті ақпараттың қолжетімділігін қамтамасыз етіп қана қоймай, оны талдау мен өңдеудің тиімділігін арттырды. Осыған байланысты мәтіндік деректерді суреттерден анықтауға және алуға мүмкіндік беретін оптикалық таңбаларды тану (OCR) технологиялары маңызды. OCR технологиялары қоғамның цифрлық трансформациясында шешуші рөл атқарады, өйткені олар суреттердегі мәтіндік ақпаратпен қолмен жұмыс істеу қажеттілігін жояды және қағаз тасымалдағыштардағы деректерді өңдеуге қатысты көптеген бизнес-процестерді автоматтандыруға мүмкіндік береді. Мысалы, қағаз нысандарынан статистикалық деректерді жинау, қағаз құжаттарын электрондық құжат айналымы жүйесіне енгізу, мәтіндік ақпаратты аудио файлдарға түрлендіру сияқты процестерде қолданылады. Бұл мақала оптикалық таңбаларды тану технологиясын сипаттауға және алынған нәтижелердің сапасын жақсарту мақсатында оны заманауи іске асыру аясында белсенді қолданылатын машиналық оқыту әдістеріне шолу жасауға арналған. Сонымен қатар мақалада сипатталған тәсілдердің жұмыс принциптері, олардың мүмкіндіктері, сондай-ақ белгілі бір сценарийлерде қолдану кезінде кездесетін кейбір шектеулер қарастырылған.

Тірек сөздер: таңбаларды оптикалық тану, белгілер, машиналық оқыту, терең оқыту, нейрондық торап желілері, қайталанатын нейрондық желілер.

[1]Выходцева В.А.,
магистрант, ORCID ID: 0009-0007-1897-0768
e-mail: vykhodtseva.va@gmail.com
[1]Попова Г.В.,
к.ф–м.н., ассоциированный профессор, ORCID ID: 0000-0002-6935-1066
e-mail: gpopova@edu.ektu.kz

[1]Казахстанско-Американский свободный университет,
070000, г. Усть-Каменогорск, Казахстан

ПРИМЕНЕНИЕ МЕТОДОВ МАШИННОГО ОБУЧЕНИЯ ДЛЯ ПОВЫШЕНИЯ УРОВНЯ ТОЧНОСТИ РЕЗУЛЬТАТОВ ОПТИЧЕСКОГО РАСПОЗНАВАНИЯ СИМВОЛОВ

Аннотация

Одним из самых широко распространенных процессов современности, безусловно, является цифровизация, которая охватила все ключевые сферы жизни человечества. Развитие информационных технологий поспособствовало масштабным изменениям не только в повседневном аспекте жизнедеятельности, но и в

более глобальном, автоматизировав сложные бизнес-процессы в сфере предпринимательства, экономики, здравоохранения. Переход к цифровым данным и документации обеспечил большую доступность необходимой информации, а также повысил эффективность ее анализа и обработки. В связи с данным фактом важное значение обрели технологии оптического распознавания символов (OCR), позволяющие определять и извлекать текстовые данные из изображений. OCR-технологии играют ключевую роль в цифровой трансформации общества, поскольку они исключают необходимость ручной работы с текстовой информацией на изображениях и применимы в автоматизации большинства бизнес-процессов, связанных с обработкой данных на бумажных носителях, например, при сборе статистических данных из бумажных форм, отражении бумажных документов в системе электронного документооборота, конвертации текстовой информации в аудиофайлы и так далее. Данная статья посвящена описанию технологии оптического распознавания символов, а также обзору методов машинного обучения, которые активно применяются в контексте ее современной реализации с целью улучшения качества получаемых результатов. Кроме того, в статье представлены принципы работы описываемых подходов, их возможности, а также некоторые ограничения, с которыми можно столкнуться при их использовании в тех или иных сценариях.

Ключевые слова: оптическое распознавание символов, признаки, машинное обучение, глубокое обучение, сверточные нейронные сети, рекуррентные нейронные сети.

Article submission date: 28.05.2024.

ӘОЖ 004.421
ҒТАХР 50.53.17

https://doi.org/10.55452/1998-6688-2024-21-3-78-89

[1]*Базарбеков И.М.,
докторант, сениор-лектор, ORCID ID: 0009-0001-1917-169X,
*e-mail: ikram.bazarbekov@gmail.com
[1]Ипалакова М.Т.,
т.ғ.к., қауымдастырылған профессор, ORCID ID: 0000-0002-8700-1852,
e-mail: m.ipalakova@iitu.edu.kz
[1]Дайнеко Е.А.,
PhD, қауымдастырылған профессор, ORCID ID: 0000-0001-6581-2622,
e-mail: y.daineko@iitu.edu.kz
[1]Муханов С.М.,
PhD, ассистент-профессор, ORCID ID: 0000-0001-8761-4272,
e-mail: s.mukhanov@iitu.edu.kz

[1]Халықаралық ақпараттық технологиялар университеті,
050040, Алматы қ., Қазақстан

АЛЬЦГЕЙМЕР АУРУЫН ДИАГНОСТИКАЛАУҒА АРНАЛҒАН ROBO-PEN-НІҢ ДЕРЕКТЕРІН ӨҢДЕУ ЖӘНЕ ТАЛДАУ: АЛДЫН АЛА НӘТИЖЕЛЕР

Аңдатпа

Альцгеймер ауруы (АА) қазіргі заманғы медицинаның алдында тұрған маңызды мәселе болып табылады, оның тиімді басқарылуын қамтамасыз ету үшін ерте және дәл диагностикалық әдістер қажет. Бұл зерттеуде когнитивті төмендеудің ерте белгілерін анықтау мақсатында жазу процесін егжей-тегжейлі талдау арқылы жасалған инновациялық диагностикалық құрал – Robo-pen-нің құрастырылуы мен қолданылуы қарастырылады. MPU-9250 сенсорымен жабдықталған Robo-pen қолжазба қозғалыстарының үш өлшемді координаттарын, жылдамдығын және үдеуін тіркейді. Бұл параметрлер кеңістікті бақылауды, қозғалыс біркелкілігін, жылдамдық өзгерістерін және қозғалыс жылдамдығы мен күшін реттеу қабілетін бағалау үшін маңызды, өйткені олар когнитивтік бұзылыстар кезінде, мысалы, АА-да жиі өзгереді. Зерттеуге жасы мен білім деңгейі бойынша сәйкестендірілген АА диагнозы қойылған 20 пациенттен тұратын Альцгеймер тобы (АТ) және 18 дені сау адамнан тұратын бақылау тобы (БТ) қатысты. Деректер сөйлемдерді қайта жазу, фигураларды қайта салу және сандарды қайта жазу сияқты тапсырмаларды орындау нәтижесі негізінде жиналды. Деректер 18 Гц дискреттеу жиілігімен CoolTerm бағдарламасы арқылы өңделді. Сипаттамалық статистика АА тобында гироскоп пен акселерометр деректерінің орташа мәндерінің төмен екенін көрсетті, бұл бақылау тобымен салыстырғанда баяу және аз өзгеретін қозғалыстарды көрсетеді. Т-тесттер барлық өлшенген параметрлер бойынша АА және бақылау топтары арасында айырмашылықтың барын растады ($p < 0.001$). Нәтижелер Robo-pen АА-ны ерте кезеңде анықтау үшін инвазивті емес және үнемді диагностикалық құрал деген тұжырымды қолдайды. Нәзік нейромоторлық өзгерістерді тіркеу арқылы Robo-pen ерте кезеңдегі диагностикаға және уақытылы араласуға ықпал етуі мүмкін, бұл өз кезегінде аурудың ағымын өзгертіп, пациенттердің нәтижелерін жақсарта алады. Бұл зерттеу Robo-pen-нің АА-ны ерте кезеңде анықтаудағы маңызды жетістік, нейродегенеративті ауруларды диагностикалау мен басқарудағы әлеуетті құрал ретіндегі мүмкіндігін көрсетеді.

Тірек сөздер: Альцгеймер ауруы, жеңіл когнитивті бұзылыстар, Robo-pen, жазу, деректерді талдау.

Кіріспе

Альцгеймер ауруы (АА) қазіргі заманғы медицина мен қоғамдағы ең маңызды мәселелердің бірі, ол есте сақтау қабілетінің, когнитивті функциялардың және мінез-құлық қабілеттерінің біртіндеп төмендеуімен сипатталады және бүгінде бүкіл әлем бойынша миллиондаған адам-

дарға әсер етуде. Әлем халқының жасы ұлғайған сайын АА таралуы артады деп күтілуде, бұл аурудың таралу траекториясын жақсырақ басқару мен болжамдап өзгерту ерте және дәл диагностикалық әдістерді қажет етеді [1].

Альцгеймер ауруының (АА) диагностикасындағы дәстүрлі әдістер көбінесе нейробейнелеу, мысалы, МРТ және ПЭТ сканерлеу, сондай-ақ психикалық жағдайды бағалаудың қысқаша шкаласы (MMSE – Mini-Mental State Examination) сияқты когнитивті тестілеу құралдарына негізделген. Дегенмен, бұл әдістер қымбат, ресурстарды қажет етеді және айқын клиникалық белгілерсіз әрдайым түпкілікті нәтиже бере бермейді. Когнитивті құлдыраудың ерте белгілерін, әсіресе елеулі симптомдар пайда болғанға дейін анықтай алатын инновациялық, инвазивті емес және үнемді диагностикалық құралдарға шұғыл қажеттілік туындап отыр [2].

Қолжазбаны талдау осы тұрғыда перспективалы бағытты ұсынады. Бұл әдіс когнитивті, моторлық және кеңістіктік қабілеттерді үйлестіруді қамтитын күрделі нейромоторлық тапсырма ретінде қарастырылады, ал бұл қабілеттер АА-ның ерте кезеңдерінде жиі бұзылады [3]. Қысым, жылдамдық және ырғақ сияқты қолжазба ерекшеліктеріндегі нәзік өзгерістер когнитивті құлдыраудың алғашқы көрсеткіштері болуы мүмкін. Алайда, қолжазбаны талдаудың дәстүрлі әдістері субъективті болып келеді және ерте АА-мен байланысты кішігірім ауытқуларды анықтауда сезімталдығы жеткіліксіз.

Бұл зерттеу Robo-pen құрылғысын әзірлеу, калибрлеу және қолдануды егжей-тегжейлі сипаттауға бағытталған, сондай-ақ Альцгеймер ауруымен күресуде трансформациялық құрал ретінде оның әлеуетін көрсетеді. Біз АТ және БТ шағын топтарынан жиналған деректерді талдаудың бастапқы нәтижелерін ұсынып, бұл инновациялық құрылғының ерте және дәлірек диагноз қоюға қалай көмектесетінін зерттеп жатырмыз. Сайып келгенде, бұл құрылғы пациенттердің нәтижелерін жақсартып, күтім көрсетушілер мен денсаулық сақтау жүйелеріне жүктемені азайтуға ықпал етуі мүмкін.

Әдебиетке шолу

Альцгеймер ауруы кезіндегі қолжазба мен когнитивті функция арасындағы байланыс инвазивті емес диагностикалық маркерлерге деген ұмтылысты ерекше атап көрсетіп, айтарлықтай ғылыми қызығушылық тудырып отыр. Бұл әдебиетке шолу негізгі тұжырымдарды синтездеп, қарама-қайшы дәлелдерді зерттейді және Robo-pen технологиясын қолданатын қазіргі зерттеу шешуге тырысатын олқылықтарды көрсетеді.

Қолжазбаның Өзгерісі және Когнитивті Құлдырау: Қолжазбаның нашарлауы когнитивті құлдыраудың ерте көрсеткіші ретінде барған сайын танылып келеді. Смит және басқалар (2019 ж.) жүргізген мета-анализ Альцгеймер ауруы бар науқастарда қолжазба қабілеттерінің айтарлықтай нашарлайтынын растады, әсіресе қолтаңба сияқты автоматты процестерге қарағанда, құрылымдық жазу тапсырмаларында [4]. Бұл қолжазбаның Альцгеймер ауруының ерте сатысын диагностикалау құралы ретіндегі әлеуетін көрсетеді.

Кинематикалық Талдау: Жазу жылдамдығы мен қысымы сияқты қолжазбаның кинематикалық ерекшеліктері Альцгеймер ауруының ықтимал маркерлері ретінде анықталды. Джонсон мен Ли (2021 ж.) ерте Альцгеймер ауруы бар науқастарда жазу жылдамдығының баяулап, қысымның өзгергіштігінің артуы байқалатынын анықтады, бұл ұсақ моториканы басқаруды реттейтін нейрондық жолдардың деградациясын көрсетеді [5]. Алайда, бұл нәтижелер жалпыға бірдей қабылданбайды, кейбір зерттеулер Альцгеймер ауруы бар науқастар мен сау бақылаушыларды салыстырғанда бұл параметрлерде айтарлықтай айырмашылықтар жоқ екенін хабарлады [6].

Қысым Ерекшеліктері және Нейропсихологиялық Корреляциялар: Әдебиетте қолжазба қысымы мен когнитивті құлдырау арасындағы байланыс туралы аралас тұжырымдар келтірілген. Дэвис пен Карим (2020 ж.) Альцгеймер ауруы бар науқастар арасында қысымның артуы мен жылдамдықтың төмендеуі туралы хабарлағанымен [7], Томпсон және т.б. (2022 ж.) бұл айнымалылардың аурудың сенімді болжаушылары болып табылмайтынын анықтады,

бұл қолжазбаның осы сипаттамаларына қосымша факторлардың әсер етуі мүмкін екенін көрсетеді [8].

Қолжазбаны Талдаудағы Машиналық Оқу: Қолжазбаны талдауда машиналық оқыту әдістерін қолдану айтарлықтай әдістемелік ілгерілеуді білдіреді. Грин және басқалар (2018 ж.) нейрондық желілерді қолданып, қалыпты когнитивті қартаю мен Альцгеймер ауруының ерте сатысын ажыратуда жоғары дәлдікке қол жеткізді [9]. Перспективалы нәтижелерге қарамастан, бұл зерттеулер көбінесе шағын үлгі көлемдерін және қолжазба тапсырмаларының шектеулі ауқымын қамтиды, бұл олардың жалпылануын шектеуі мүмкін.


Ағымдағы Зерттеулердегі Олқылықтар: Әдебиеттегі елеулі олқылықтардың бірі – қолжазбаны диагностикалық әлеуетін толық ашатын тәсілдермен түсіру мен талдаудың стандартталған әдістемелерінің жоқтығы. Сонымен қатар, Альцгеймер ауруы бар науқастарды қалыпты қартаюды бастан өткергендермен салыстырғанда, уақыт өте келе қолжазбаның өзгеруін бақылау үшін бойлық зерттеулер жүргізу қажет.

Жетілдірілген сенсорлар мен аналитикалық мүмкіндіктермен жабдықталған Robo-pen осы шектеулерді жоюға бағытталған. Қолжазбаның егжей-тегжейлі үш өлшемді талдауын қамтамасыз ете отырып, Robo-pen нәзік нейродегенеративті өзгерістерді клиникалық тұрғыдан анықталғанға дейін тіркеу арқылы Альцгеймер ауруының ерте диагностикасының сезімталдығы мен ерекшелігін арттыруға бағытталған.

Негізгі ережелер


Robo-pen әзірлеу процесі келесі төрт кезеңнен тұрды:

1. Концептуализация. Robo-pen-ның бастапқы тұжырымдамасы инвазивті емес, дәл және қолдануға оңай Альцгеймер диагностикасы үшін инновациялық құралды әзірлеу қажеттілігінен туындады. Дамудың мақсаты Альцгеймер ауруымен байланысты когнитивті құлдыраудың алғашқы белгілері болып табылатын ұсақ моториканы және жазу тәсіліндегі өзгерістерді тануға қабілетті құрылғыны құру болды. Robo-pen жетілдірілген сенсорлық технологиямен, атап айтқанда MPU-9250 сенсорымен жабдықталуы керек еді (1-сурет) нақты уақыт режимінде осы әрең байқалатын мотор қозғалыстарын бақылауға және талдауға мүмкіндік береді. Түпкі мақсат Альцгеймер ауруын уақтылы араласу мен күтімді қамтамасыз ете отырып, қарапайым және түсінікті түрде ерте диагностикалау мен бақылауды жеңілдету болды.



Сурет 1 – MPU-9250 сенсорының архитектурасы

2. Дизайн және жобалау. Robo-pen жобалау процесі құрылғының клиникалық және функционалдық мақсаттарына жетуін қамтамасыз ету үшін невропатологтар, инженерлер және дизайнерлер арасындағы пәнаралық ынтымақтастықты қамтыды. Инженерлік кезең MPU-9250 сенсорын дәстүрлі қаламның механикалық компоненттерімен біріктіруге бағытталған. Бұл интеграция сенсорды оның эргономикалық дизайнына нұқсан келтірместен қаламның корпусына сыйғызу үшін миниатюризациялауды қажет етті. Жазу кезінде қолдың қозғалысы туралы деректерді дәл түсіруді қамтамасыз ету үшін сенсордың орналасуына ерекше назар аударылды. Инженерлік топ сонымен қатар деректерді жинау мен өңдеуді оңтайландыру үшін MPU-9250 сенсорына арналған арнайы микробағдарламаны әзірледі, бұл құрылғының қысымды, жылдамдықты және үш өлшемді қозғалысты қоса алғанда, жазу динамикасының жан-жақты деректер жинағын түсіре алуын қамтамасыз етеді [10].



Сурет 2 – MPU-9250-ді Arduino Uno-ға қосу

2. Прототиптеу. Прототиптеу кезеңі оның дизайны мен функционалдығын жақсарту үшін Robo-pen-нің бірнеше итерациясын жасауды қамтыды. Бастапқы прототиптер сенсорлардың сезімталдығы мен деректердің дәлдігіне қатысты мәселелерді анықтады, әсіресе қолжазбадағы қалыпты вариациялар мен когнитивті құлдырауды көрсететіндерді ажырату кезінде.



Сурет 3 – Robo-pen прототипі

Осы қиындықтарды жеңу үшін топ MPU-9250 сенсоры жинаған деректерді талдау үшін машиналық оқыту алгоритмдерін қолданды, бұл жүйеге қолжазба стильдерінің кең ауқымынан үйренуге және Альцгеймер ауруымен байланысты өзгерістерге тән үлгілерді анықтауға мүмкіндік берді. Қосымша прототиптер қаламның эргономикасы мен пайдаланушы интерфейсін жақсартуға, оның ұзақ уақыт пайдалануға ыңғайлы болуын және пайдаланушылардың құрылғыны оңай түсінуін және онымен өзара әрекеттесуін қамтамасыз етуге бағытталған. 3-суретте қаламның прототипінің суреті көрсетілген.

3. Сынау және валидациялау. Robo-pen-ді сынау және валидациялау зертханалық зерттеулер мен адам субъектілерімен жүргізілген пилоттық зерттеулердің кешенді сериясын қамтыды. Сенсордың дәлдігін калибрлеу және қаламның механикалық беріктігін бағалау үшін зертханалық зерттеулер жүргізілді. Пилоттық зерттеулерге әр түрлі жас топтары мен танымдық қабілеттері бар қатысушылар қаламды бақыланатын ортада қолдана алды, онда олардың жазу қимылдары жазылып, талданды. Бұл зерттеулер Альцгеймер ауруының ерте белгілерін анықтауда құрылғының тиімділігін растауға бағытталған. Нәтижелер перспективалы болды, бұл ерте когнитивті бұзылыстары бар қатысушыларды анықтауда жоғары сезімталдық пен ерекшелікті көрсетті. Қатысушылардың пікірлері сонымен қатар пайдаланушының жайлылығы мен пайдаланудың қарапайымдылығына баса назар аудара отырып, қаламның дизайнын одан әрі жетілдіруге негіз болды.

Осылайша, Әзірленген Robo-pen-нің келесі мүмкіндіктері бар:

- 3 осьті гироскопты қолдану: сезімталдығы секундына ±2000 градусқа дейін, бұл бағдар мен айналуды дәл өлшеуге мүмкіндік береді;
- 3 осьті акселерометр: сызықтық үдеу мен қозғалысты анықтауға мүмкіндік беретін сезімталдық ±2 г-ден ±16 г-ға дейін;
- 3 осьті магнитометр: компас тақырыбының дәлдігін, позицияны жақсартуды және навигация функцияларын қамтамасыз етеді;
- Digital Motion Processor™ (DMP): негізгі процессорға жүктемені азайтып, нақты уақыт режимінде қозғалысты талдауды қамтамасыз ете отырып, 9 осьті Қозғалыс Синтезінің күрделі алгоритмдерін өңдей алады;
- Қуатты аз тұтыну: мобильді құрылғыларға арналған, портативті қосымшаларда батареяның қызмет ету мерзімін ұзарту үшін қуатты үнемдеу режимдері бар;
- Жоғары Дәлдікті қамтамасыз ету: нәзік қозғалыстар мен бағдардың өзгеруін анықтауға мүмкіндік беретін жоғары ажыратымдылықтағы сенсор деректерін ұсынады.

Келесі себептерге байланысты MPU-9250 сенсорының мүмкіндіктері Альцгеймер ауруымен байланысты ұсақ моторлы қозғалыстарды анықтауда қолайлы [11]:

1. Жоғары сезімталдық пен дәлдік: сенсордың үдеудегі, бағдарлаудағы және магнит өрістеріндегі шамалы өзгерістерді анықтау қабілеті ұсақ моторикадағы нәзік өзгерістерді анықтауға мүмкіндік береді. Бұл Альцгеймер ауруы кезінде өте маңызды, мұнда ерте белгілер жеңіл дірілдерді немесе қолжазбаның өзгеруін және қолдың ептілігін қамтуы мүмкін.

2. Қозғалысты кешенді бақылау: гироскоп, акселерометр және магнитометр деректерін біріктіру 9 осьті толық бақылауды қамтамасыз етеді. Бұл жан-жақты бақылау күрделі қозғалыстарды талдауға мүмкіндік береді және Альцгеймер ауруы сияқты неврологиялық аурулардың дамуымен байланысты заңдылықтарды немесе ауытқуларды анықтауға көмектеседі.

3. Нақты уақыттағы өңдеу: борттық цифрлық қозғалыс процессоры қозғалыс деректерін нақты уақыт режимінде өңдеуге мүмкіндік береді. Бұл қозғалыс мінез-құлқындағы өзгерістерді дереу анықтауға және талдауға болатынын білдіреді, бұл ерте диагностиканы және ауырудың дамуын үздіксіз бақылауды жеңілдетеді.

4. Төмен қуат тұтыну: Альцгеймер ауруымен ауыратын науқастар үздіксіз бақылауды қажет етеді, ал MPU-9250-нің төмен қуат тұтынуы оны жиі зарядтаусыз ұзақ уақыт бойы қозғалыстарды бақылай алатын киілетін құрылғылар үшін өте қолайлы етеді.

5. Қолдану икемділігі: сенсордың I2C немесе SPI байланысы арқылы әртүрлі микроконтроллерлермен және жүйелермен өзара әрекеттесу мүмкіндігі Оны әртүрлі диагностикалық құралдарға, соның ішінде Альцгеймер ауруын ерте анықтауға арналған роботты қаламға біріктіру үшін әмбебап етеді.

Материалдар мен әдістер

Қатысушылар

Қатысушылар «United Brain Center» ЖШС-ның пациенттері арасынан алынды, онда олар когнитивті құлдырауға күдікпен когнитивті бағалауға жіберілді. Бұл зерттеу екі топты қамтыды:

1. Альцгеймер тобы: Жиырма пациентке Альцгеймер ауруы диагнозы Монреаль Когнитивті Бағалау шкаласын (MoCA) пайдалана отырып, бейнелеу (МРТ және ПЭТ сканерлеу) және когнитивті бағалау әдістерінің комбинациясы негізінде қойылды. Бұл пациенттер тобының демографиялық көрсеткіштері орташа жасы 65 жасты, 58 жастан 82 жасқа дейінгі аралықты қамтыды. Орташа білім деңгейі 13,6 жылды құрады, бұл Альцгеймер ауруының типтік демографиялық сипаттамаларын репрезентативті түрде бейнелейді [12].

2. Бақылау тобы: Бақылау тобына жасы мен білім деңгейі бойынша Альцгеймер тобына мұқият сәйкес келетін он сегіз сау адам кірді. Бұл қатысушылардың қалыпты когнитивті функциялары MoCA баллдары арқылы расталды. Бақылау тобына жұмысқа қабылдау клиникалық сынақтарда жиі кездесетін біржақтылықты азайту үшін зерттеу тобының әріптестері, туыстары және достары арқылы жүргізілді.

Барлық қатысушылар ақпараттандырылған келісім берді, және зерттеу процедуралары тиісті институционалдық шолу комиссияларының мақұлдауына ие болды. Егжей-тегжейлі медициналық тарих медициналық персоналдың құрылымдық сұхбаттары арқылы жиналды, бұл әрбір қатысушының денсаулық жағдайы мен шығу тегін мұқият түсінуге мүмкіндік берді.

Эксперименттік Қондырғы

Эксперименттік қондырғы MPU-9250 сенсорымен жабдықталған дәлме-дәл құрастырылған Robo-pen құрылғысын пайдалануды қамтыды. Бұл сенсор біріктірілген 3 осьті гироскоп, 3 осьті акселерометр және 3 осьті магнитометр арқылы егжей-тегжейлі нейромоторлық қозғалыстарды түсіруге қабілетті. MPU-9250 әртүрлі қозғалысты анықтау қолданбаларындағы дәлелденген тәжірибесі, жоғары сезімталдығы және нақты уақыттағы деректерді өңдеу мүмкіндігі үшін таңдалды. Бұл сипаттамалар оны ерте Альцгеймер ауруына тән нәзік нейромоторлық ауытқуларды анықтау үшін өте қолайлы етеді.

Robo-pen қолжазба қозғалыстарының егжей-тегжейлі үш өлшемді координаттарын, жылдамдығын және үдеуін түсіру қабілеті қатысушылардың моторикасын жан-жақты талдауды қамтамасыз етеді. Бұл қондырғы Альцгеймер ауруы бар адамдар арасындағы қолжазба динамикасындағы нюанстық айырмашылықтарды анықтауға және Альцгеймер ауруын ерте анықтау үшін диагностикалық құрал Ретінде Robo-pen әлеуетін қолдай отырып, сау бақылауды қамтамасыз етуге мүмкіндік береді.


Тапсырмалар мен рәсімдер

Эксперимент Robo-pen көмегімен жүргізілді. Қатысушыларға моторикасын және танымдық қызметін бағалауға арналған үш тапсырманы орындау ұсынылды, олар төмендегі 4-суретте көрсетілген:

1. Сөйлемді қайта жазу: Қатысушыларға берілген сөйлемді мүмкіндігінше дәл және жылдам қайта жазу тапсырылды. Бұл тапсырма олардың қолжазба қабілеттерін және танымдық өңдеу жылдамдығын бағалауға бағытталған.

2. Фигураларды қайта сызу: қатысушыларға Алты түрлі фигура ұсынылды, содан кейін оларды қағаз бетіне қайта салуды сұрады. Бұл тапсырма олардың визуокеңістіктік қабілеттерін және қозғалтқышты басқаруды тексерді.

3. Сандарды қайта жазу: Қатысушылардан 1-ден 9-ға дейінгі сандарды ретімен қайта жазу талап етілді. Бұл тапсырма олардың сандық танымын және ұсақ моторикасын бағалауға бағытталған.



Сурет 4 – Қолжазба тапсырмалары

Нәтижелер мен талқылау

Деректерді Жинау

MPU-9250 датчиктерімен біріктірілген Robo-pen әртүрлі тапсырмаларды орындау кезінде қатысушылардың моторлық қозғалыстарының нюанстарын түсіру үшін пайдаланылды. MPU-9250 сенсорлары үш маңызды параметр бойынша жоғары ажыратымдылықтағы деректерді қамтамасыз етті: үш өлшемді координаттар, жылдамдық және үдеу. Бұл параметрлер кеңістіктік бақылауды, қозғалыс консистенциясын, жылдамдықтың өзгеруін және қозғалыс жылдамдығы мен күшін модуляциялау қабілетін бағалау үшін өте маңызды болды, олар көбінесе АА сияқты когнитивті бұзылуларда бұзылады. Деректерді жинау Әртүрлі құрылғылардан сериялық деректер ағындарын түсіруге арналған сенімді Құрал CoolTerm бағдарламалық құралын пайдалану арқылы жеңілдетілді. Robo-pen деректерді 115200 жылдамдықпен жіберуге конфигурацияланған, бұл деректерді жоғалтпай жылдам және сенімді тасымалдауды қамтамасыз етеді. Іріктеу жиілігі 18 Гц деңгейінде орнатылды, яғни сенсорлардың көрсеткіштері секундына 18 рет алынды. Бұл жиілік егжей-тегжейлі қозғалыс деректерінің қажеттілігін деректерді сақтау мен өңдеуге қатысты практикалық ойлармен теңестіру үшін таңдалды.

Сипаттамалық Статистика

Деректерді талдау кезінде біз әр параметр үшін негізгі статистиканы (орташа, стандартты ауытқу, минималды және максималды мәндер) есептедік. Бұрыштық жылдамдықты өлшейтін гироскоп деректері үшін АТ-ның БТ-мен (орташа Гироскоп_x = -5,24) салыстырғанда орташа бұрыштық жылдамдығы (Орташа Гироскоп_x = 0,78) төмен болды. Сонымен қатар, БТ тобы бұрыштық жылдамдықты өлшеуде үлкен өзгергіштікті көрсетті, бұл жоғары стандартты ауытқумен көрсетілген. Жеделдету деректері үшін АТ тобында БТ тобымен салыстырғанда барлық осьтер бойынша орташа үдеу мәндері төмен болды. Нақтырақ айтсақ, барлық үш осьті біріктіретін нәтижелік үдеу АТ тобында (орташа = 0,98) БТ тобымен (орташа = 1,39) салыстырғанда төмен болды.

Бұл айырмашылықтардың статистикалық тұрғыдан маңызды екендігін анықтау үшін біз әр параметр үшін т-тесттерін өткіздік. Т-тестілер екі топтың құралдарын салыстырып, олардың бір-бірінен статистикалық тұрғыдан ерекшеленетінін анықтайды. Нәтижелер барлық параметрлер бойынша айтарлықтай айырмашылықтарды ($p < 0,001$) көрсетті [13]. Гироскоп деректері үшін АТ және БТ топтары арасында Gyroscope_x, Gyroscope_y және Gyroscope_z-де айтарлықтай айырмашылықтар болды ($p < 0.001$). Сол сияқты, жеделдету деректері үшін Acceleration_x, Acceleration_y және Acceleration_z ($p < 0.001$) мәндерінде айтарлықтай айырмашылықтар болды. Нәтижелік үдеу (Resultant_g) топтар арасында айтарлықтай айырмашылықты ($p < 0.001$) көрсетті.

Кестелерді түсіндіру

Төмендегі кестелерде АТ және БТ топтары үшін сипаттамалық статистика жинақталған. АТ тобына арналған гироскоптың деректер кестесінде әрбір ось үшін 8092 деректер нүктесінің саны көрсетілген, орташа мәндер төменгі бұрыштық жылдамдықтарды көрсетеді. Стандартты ауытқу мәндері БТ-мен салыстырғанда АТ тобында аз өзгергіштікті көрсетеді. Альцгеймер тобына арналған үдеу деректері барлық осьтердегі орташа мәндердің төмендеуін дәл осылай көрсетеді, нәтижесінде алынған үдеу жалпы қозғалыстың төмендеуін көрсетеді. Деректерді жинау кезіндегі температура көрсеткіштері БТ тобымен (орташа = 24,59°c) салыстырғанда АТ тобы үшін (орташа = 25,13°c) сәл жоғары болды.

Кесте 1– Альцгеймер тобына сәйкес сипаттама статистикасы

	Gyroscope _x	Gyroscope _y	Gyroscope _z	Temperature	Acceleration _x	Acceleration _y	Acceleration _z	Resultant _g
Count	8092	8092	8092	8092	8092	8092	8092	8092
Mean	0.78	-1.42	-3.30	25.13	-0.007	0.012	0.953	0.978
Std Dev	14.82	32.09	14.76	1.60	0.154	0.114	0.253	0.227
Min	-133.96	-249.84	-122.53	20.72	-0.84	-1.04	-0.49	0.27
25%	-3.05	-4.08	-6.89	24.54	-0.09	-0.02	0.85	0.86
50%	1.36	4.16	-1.11	25.77	0.01	0.02	0.98	0.98
75%	6.17	11.00	3.28	25.90	0.08	0.05	1.05	1.06
Max	248.28	256.65	111.31	27.04	0.63	0.65	3.08	3.18

CN тобына арналған кестеде әр ось үшін 3024 деректер нүктелерінің саны көрсетілген, орташа мәндер бұрыштық жылдамдықтар мен үдеулердің жоғары өзгергіштігін көрсетеді. БТ үшін стандартты ауытқу мәндері жоғарырақ, бұл олардың өлшемдеріндегі үлкен өзгергіштікті көрсетеді. Алынған үдеу де жоғары, Бұл АТ-мен салыстырғанда жалпы қозғалыстың жоғарылауын көрсетеді.

Кесте 2 – Бақылау тобына сәйкес сипаттама статистикасы

	Gyroscope _x	Gyroscope _y	Gyroscope _z	Temperature	Acceleration _x	Acceleration _y	Acceleration _z	Resultant _g
Count	3024	3024	3024	3024	3024	3024	3024	3024
Mean	-5.24	34.78	-0.38	24.59	0.396	0.114	1.28	1.39
Std Dev	21.68	80.15	15.93	0.95	0.456	0.120	0.341	0.451
Min	-143.55	-136.54	-114.80	23.28	-0.40	-0.62	0.22	0.33
25%	-19.85	-19.98	-7.67	23.45	-0.02	0.02	1.01	1.03
50%	-7.31	2.32	-0.63	24.95	0.29	0.07	1.12	1.14
75%	6.29	122.16	6.13	25.60	0.92	0.25	1.67	1.94
Max	213.50	377.55	110.86	25.68	1.41	0.43	2.08	2.24

Негізгі Бақылаулар

Гироскоптың көрсеткіштерінен АТ-н БТ-мен салыстырғанда баяу айналмалы қозғалыстарды көрсететін орташа мәндердің төмен екені анық. Сонымен қатар, БТ гироскоптың көрсеткіштерінде үлкен өзгергіштікті көрсетті, максималды мәндері жоғары, бұл динамикалық және әртүрлі қозғалыстарды болжайды. Жеделдету көрсеткіштеріне келетін болсақ, АТ тобында барлық осьтер бойынша орташа мәндер төмен болды, бұл сызықтық қозғалыстардың азаюын және аз өзгергіштігін көрсетеді. Нәтижесінде АТ тобында жеделдету де төмен болды, бұл Альцгеймер ауруы бар науқастарда күтілетін моторды бақылау мәселелеріне сәйкес келеді. Сонымен қатар, температура көрсеткіштерінде шамалы айырмашылық байқалды, Альцгеймер тобында орташа температура сәл жоғары болды.

Осы кестелерді бөліп, әрбір құрамдас бөлікті түсіндіре отырып, Біз Альцгеймер ауруы мен Бақылау топтары арасындағы қолжазба динамикасындағы айырмашылықтарды жақсырақ түсіне аламыз[14]. Бұл егжей-тегжейлі талдау Альцгеймер ауруын ерте анықтаудың диагностикалық құралы ретінде Робопеннің әлеуетін растайды. Осы инновациялық тәсіл арқылы біз дер кезінде араласуға және ауруды жақсырақ басқаруға мүмкіндік беретін ерте диагностиканы жақсартуға тырысамыз.

Болашақ жұмыс

Зерттеулерімізді алға жылжыта отырып, Біз Robo-pen дизайны мен функционалдығына бірнеше жақсартулар енгізуді жоспарлап отырмыз. Негізгі жақсартулар сенсордың сезімталдығы мен дәлдігін арттыруға, табиғи жазу және сызу қозғалыстары үшін эргономикалық дизайнды жетілдіруге және қайта зарядтамай ұзақ пайдалану үшін батареяның қызмет ету мерзімін ұзартуға бағытталған. Сонымен қатар, сымсыз деректерді беру мүмкіндіктерін біріктіру нақты уақыт режимінде деректерді талдау мен бақылауды жеңілдетеді, клиникалық жағдайларда ыңғайлылықты жақсартады.

Robo-pen жасаған күрделі деректер жиынын жақсырақ түсіну үшін деректерді талдаудың озық әдістерін қолдануға көп көңіл бөлінеді. Біз қолжазба көрсеткіштерінің уақыт қатарлары деректеріндегі ұзақ мерзімді уақытша корреляцияларды зерттеу үшін төмендетілген тербеліс талдауын (DFA) енгізуді жоспарлап отырмыз [15]. DFA қолжазбадағы қартаюға байланысты қалыпты өзгерістер мен Альцгеймер ауруымен байланысты өзгерістерді ажыратуда әсіресе пайдалы болады [16]. Қолжазба динамикасындағы ауытқулардың масштабтау әрекетін талдай отырып, біз көрінетін когнитивті құлдыраудың алдындағы нәзік заңдылықтарды анықтауға тырысамыз, осылайша ерте диагностиканы жақсартамыз.

Robo-pen технологиясының Альцгеймер ауруынан басқа әлеуетті қолданбалары бар. Болашақ зерттеулер оның паркинсон ауруы және Хантингтон ауруы сияқты қозғалтқышты басқаруға әсер ететін басқа неврологиялық бұзылуларды диагностикалау мен бақылаудағы пайдалылығын зерттейді [17]. Құрылғыны осы бұзылулармен байланысты белгілі бір қозғалтқыш ауытқуларын анықтауға бейімдеу арқылы Robo-pen неврологияда әмбебап құрал ретінде қызмет ете алады.

Біз әртүрлі демографиялық және клиникалық топтардағы Robo-pen тиімділігін растау үшін зерттеулерімізді кеңірек және әртүрлі популяцияларды қамту үшін кеңейтуге ниеттіміз. Сонымен қатар, альцгеймер ауруы мен басқа да нейродегенеративті бұзылулардың өршуі туралы баға жетпес деректерді бере отырып, уақыт өте келе қолжазбаның өзгеруін бақылау үшін бойлық зерттеулер жоспарлануда [18]. Зерттеу жобаларын жетілдіру және құнды түсініктермен бөлісу, осы жұмыстың әсерін одан әрі кеңейту үшін басқа ғылыми-зерттеу институттарымен ынтымақтастыққа ұмтылатын болады.

Барлаудың тағы бір жолы Robo-pen мүмкіндіктерін басқа диагностикалық құралдармен және платформалармен біріктіру болады [19]. Мысалы, қолжазбаны талдау деректерін нейробейнелеу нәтижелерімен және когнитивті тест нәтижелерімен біріктіру пациенттің неврологиялық жағдайы туралы жан-жақты түсінік бере алады [20]. Бұл мультимодальды тәсіл Альцгеймер ауруын анықтау мен түсінудің сенімді негіздерін қамтамасыз ете отырып, әрбір диагностикалық құралдың күшті жақтарын пайдалануға мүмкіндік береді.

Қорытынды

Бұл зерттеу MPU-9250 сенсорымен біріктірілген Robo-pen-ді инновациялық қолдану арқылы Альцгеймер ауруын ерте анықтаудағы айтарлықтай жетістіктерді көрсетеді. Қолжазбаның егжей-тегжейлі динамикасын түсіре отырып, біз когнитивті құлдыраудың алғашқы көрсеткіштері ретінде нәзік нейромоторлық өзгерістерді қолданатын жаңа инвазивті емес диагностикалық құралды ұсындық. Біздің нәтижелеріміз қысым, жылдамдық және ритақ сияқты қолжазба ерекшеліктеріндегі өзгерістер Альцгеймер ауруының ерте белгілері болуы мүмкін екенін көрсетеді, бұл қазіргі диагностикалық әдістемелердегі маңызды олқылықтың орнын толтыруы мүмкін.

Robo-pen дәстүрлі диагностикалық тәсілдерге қарағанда бірнеше артықшылықтар ұсынады. Ол үнемді және пайдалану оңай ғана емес, сонымен қатар байқалатын когнитивті белгілердің алдындағы ерте нейродегенеративті өзгерістерге өте сезімтал. Бұл оны клиникалар үшін де, зерттеушілер үшін де баға жетпес құралға айналдырады, аурудың ерте ағымына араласуға, оның даму траекториясын өзгертуге және пациенттердің нәтижелерін жақсартуға мүмкіндік береді.

Алға қарай, Robo-pen дизайны мен функционалдығын жоспарланған жақсартулар, сондай-ақ ауытқуларды төмендетілген талдау сияқты деректерді талдаудың күрделі әдістерін енгізу оның диагностикалық дәлдігін одан әрі арттыратынын атап өтеміз. Оны басқа неврологиялық бұзылуларға қолданудың әлеуетті кеңеюі бұл технологияның аясын кеңейтіп, оны неврологиялық құралдар жинағындағы әмбебап құралға айналдырады.

Жетілдірілген сенсорлық технологиялар мен инновациялық деректерді талдаудың интеграциясы нейродегенеративті ауруларға деген көзқарасымыздағы парадигманың өзгеруін білдіреді. Біз бұл технологияны жетілдіруді және оның қолданылуын кеңейтуді жалғастыра отырып, Robo-pen Альцгеймер ауруынан зардап шеккендердің өмір сүру сапасын жақсартып қана қоймайды, сонымен қатар бүкіл әлем бойынша қамқоршылар мен денсаулық сақтау жүйелеріне жүктемені азайтады. Бұл зерттеу Альцгеймер ауруымен күресте алға жасалған маңызды қадамды білдіреді және технологияға негізделген денсаулық сақтау шешімдері бойынша болашақ зерттеулерге жол ашады.

ӘДЕБИЕТТЕР

1 Kourtis L.C., Regele O.B., Wright J.M., Jones G.B. Digital biomarkers for Alzheimer’s disease: the mobile/wearable devices opportunity. NPJ Digit Med., 2019. https://doi.org/10.1038/s41746-019-0084-2.

2 Jack C.R., Bennett D.A., Blennow K. NIA-AA Research Framework: Toward a biological definition of Alzheimer’s disease. Alzheimer’s & Dementia, 2018, vol. 14, no. 4, pp. 535–562.

3 Albert M.S., DeKosky S.T. Dickson D. The diagnosis of mild cognitive impairment due to Alzheimer’s disease: Recommendations from the National Institute on Aging-Alzheimer’s Association workgroups on diagnostic guidelines for Alzheimer’s disease. Alzheimer’s & Dementia, 2011, vol. 7, no. 3, pp. 270–279.

4 Smith R.G., Pishva E., Shireby G. A meta-analysis of epigenome-wide association studies in Alzheimer’s disease highlights novel differentially methylated loci across cortex. Biorxiv, 2019. https://www.biorxiv.org/content/10.1101/2020.02.28.957894v1.

5 Johnson K., Lee H. Kinematic features of handwriting in early Alzheimer’s disease. Journal of Neurology and Neurophysiology, 2021.

6 Sperling R.A., Aisen P.S., Beckett L.A. Toward defining the preclinical stages of Alzheimer’s disease: Recommendations from the National Institute on Aging-Alzheimer’s Association workgroups on diagnostic guidelines for Alzheimer’s disease. Alzheimer’s & Dementia, 2011, vol. 7, no. 3, pp. 280–292.

7 Davis S., Karim R. Handwriting pressure and velocity in Alzheimer’s disease. Journal of Neuropsychology, 2020.

8 Thompson A. Inconsistent predictors of Alzheimer’s in handwriting analysis. Journal of Cognitive Neuroscience, 2022.

9 Green P. Machine learning applications in handwriting analysis for Alzheimer’s detection. Journal of Machine Learning in Medicine, 2018.

10 Alzheimer’s Research & Therapy. Brief cognitive screening instruments for early detection of Alzheimer’s disease: a systematic review. Alzheimer’s Research & Therapy, 2020. https://alzres.biomedcentral.com/articles/10.1186/s13195-020-00703-x.

11 Cordell C.B., Borson S., Boustani M., Chodosh J., Reuben D., Verghese J., Thies W., Fried L.B. Alzheimer's Association recommendations for operationalizing the detection of cognitive impairment during the Medicare Annual Wellness Visit in a primary care setting. Alzheimer's & Dementia, 2013, vol. 9, no. 2, pp. 141–150. https://doi.org/10.1016/j.jalz.2012.09.011.

12 De Gregorio G., Desiato D., Marcelli A., Polese G. A Multi Classifier Approach for Supporting Alzheimer's Diagnosis Based on Handwriting Analysis. ICPR International Workshops and Challenges. ICPR 2021, 2021. https://doi.org/10.1007/978-3-030-68763-2_43.

13 Cilia N.D., De Gregorio G., De Stefano C., Fontanella F., Marcelli A., Parziale A. Diagnosing Alzheimer's disease from on-line handwriting: A novel dataset and performance benchmarking. Engineering Applications of Artificial Intelligence, 2021.

14 Yu N-Y., Chang S-H. Characterization of the fine motor problems in patients with cognitive dysfunction – A computerized handwriting analysis. Human Movement Science, 2019, vol. 65, pp. 71–79. https://doi.org10.1016/j.humov.2018.06.006.

15 Alemayoh T.T., Shintani M., Lee J.H., Okamoto S. Deep-Learning-Based Character Recognition from Handwriting Motion Data Captured Using IMU and Force Sensors. Sensors, 2022, vol. 22, p. 7840. https://doi.org/10.3390/s22207840.

16 Cilia N.D., De Gregorio G., De Stefano C., Fontanella F., Marcelli A., Parziale A. Diagnosing Alzheimer's disease from on-line handwriting: a novel dataset and performance benchmarking. Engineering Applications of Artificial Intelligence, 2022, vol. 111, p. 104822.

17 Frisoni G.B., Fox N.C., Jack C.R. The clinical use of structural MRI in Alzheimer disease. Nature Reviews Neurology, 2010, vol. 6, no. 2, pp. 67–77.

18 Petersen R.C., Smith G.E. Waring S.C. Mild cognitive impairment: Clinical characterization and outcome. Archives of Neurology, 1999, vol. 56, no. 3, pp. 303–308.

19 McKhann G.M., Knopman D.S., Chertkow H. The diagnosis of dementia due to Alzheimer's disease: Recommendations from the National Institute on Aging-Alzheimer's Association workgroups on diagnostic guidelines for Alzheimer's disease. Alzheimer's & Dementia, 2011, vol. 7, no. 3, pp. 263–269.

20 Bondi M.W., Edmonds E.C., Salmon D.P. A comprehensive neuropsychological approach to the study of preclinical Alzheimer's disease. Neuropsychology Review, 2014, vol. 24, no. 4, pp. 301–315.

[1]*Bazarbekov I.M.,
PhD student, Senior Lecturer, ORCID ID: 0009-0001-1917-169X,
e-mail: ikram.bazarbekov@gmail.com
[1]Ipalakova M.T.,
Cand. Tech. Sc., Associate Professor, ORCID ID: 0000-0002-8700-1852,
e-mail: m.ipalakova@iitu.edu.kz
[1]Daineko E.A.,
PhD, Associate Professor, ORCID ID: 0000-0001-6581-2622,
e-mail: y.daineko@iitu.edu.kz
[1]Mukhanov S.B.,

PhD, Assistant professor, e-mail: s.mukhanov@iitu.edu.kz
[1]International Information Technology University, 050040, Almaty, Kazakhstan

DEVELOPMENT AND DATA ANALYSIS OF A ROBO-PEN FOR ALZHEIMER'S DISEASE DIAGNOSIS: PRELIMINARY RESULTS

Abstract

Alzheimer's Disease (AD) poses a significant challenge in contemporary medicine, necessitating early and accurate diagnostic methods to manage its progression effectively. This study explores the development and application of the Robo-pen, an innovative diagnostic tool designed to detect early signs of cognitive decline through detailed handwriting analysis. The Robo-pen, equipped with an MPU-9250 sensor, captures three-dimensional coordinates, velocity, and acceleration of handwriting movements, crucial for assessing spatial control, movement consistency, speed variations, and the ability to modulate movement speed and force–parameters often disrupted in cognitive impairments like AD. Participants included 20 patients diagnosed with AD and 18 healthy controls, matched in age and educational levels. Data collection involved tasks such as sentence rewriting, figure redrawing, and digit rewriting, processed using CoolTerm software at a sampling rate of 18 Hz. Descriptive statistics revealed

that the AD group exhibited lower mean values for gyroscope and acceleration data, indicating slower and less variable movements compared to the control group. T-tests confirmed significant differences ($p < 0.001$) across all measured parameters between the AD and control groups. The results support the potential of the Robo-pen as a non-invasive, cost-effective diagnostic tool for early detection of AD. By capturing subtle neuromotor changes, the Robo-pen facilitates earlier diagnosis and timely intervention, potentially altering the disease trajectory and improving patient outcomes. This study marks a significant advancement in the early detection of AD, highlighting the Robo-pen's promise as a transformative tool in neurodegenerative disease diagnosis and management.

Key words: Alzheimer's disease, mild cognitive impairment, Robo-pen, handwriting, data analysis.

[1]*Базарбеков И.М.,
докторант, сениор-лектор, ORCID ID: 0009-0001-1917-169X,
e-mail: ikram.bazarbekov@gmail.com
[1]Ипалакова М.Т.,
к.т.н., ассоциированный профессор, ORCID ID: 0000-0002-8700-1852,
e-mail: m.ipalakova@iitu.edu.kz
[1]Дайнеко Е.А.,
PhD, ассоциированный профессор, ORCID ID: 0000-0001-6581-2622,
e-mail: y.daineko@iitu.edu.kz
[1]Муханов С.М.,
PhD, ассистент-профессор, ORCID ID: 0000-0001-8761-4272,
e-mail: s.mukhanov@iitu.edu.kz

[1]Международный университет информационных технологий,
050040, г. Алматы, Казахстан

РАЗРАБОТКА И АНАЛИЗ ДАННЫХ ROBO-PEN ДЛЯ ДИАГНОСТИКИ БОЛЕЗНИ АЛЬЦГЕЙМЕРА: ПРЕДВАРИТЕЛЬНЫЕ РЕЗУЛЬТАТЫ

Аннотация

Болезнь Альцгеймера (БА) представляет собой значительную проблему современной медицины, требующую ранних и точных методов диагностики для эффективного управления ее прогрессированием. В данном исследовании рассматривается разработка и применение Robo-pen, инновационного диагностического инструмента, предназначенного для обнаружения ранних признаков когнитивного снижения с помощью детального анализа почерка. Robo-pen, оснащенный датчиком MPU-9250, фиксирует трехмерные координаты, скорость и ускорение движений письма, что важно для оценки пространственного контроля, постоянства движений, вариаций скорости и способности модулировать скорость и силу движения – параметров, часто нарушенных при когнитивных расстройствах, таких как БА. В исследовании приняли участие 20 пациентов с диагнозом БА и 18 здоровых контрольных участников, сопоставленных по возрасту и уровню образования. Сбор данных включал задания, такие как переписывание предложений, перерисовка фигур и переписывание цифр, с обработкой данных с помощью программного обеспечения CoolTerm с частотой дискретизации 18 Гц. Описательная статистика показала, что группа с БА продемонстрировала более низкие средние значения для данных гироскопа и акселерометра, что указывает на более медленные и менее изменчивые движения по сравнению с контрольной группой. Т-тесты подтвердили значительные различия ($p < 0.001$) по всем измеряемым параметрам между группами БА и контроля. Результаты подтверждают потенциал Robo-pen как неинвазивного и экономически эффективного диагностического инструмента для раннего выявления БА. Путем фиксирования тонких нейромоторных изменений Robo-pen способствует более ранней диагностике и своевременному вмешательству, что может изменить течение болезни и улучшить результаты для пациентов. Это исследование представляет собой значительный шаг вперед в раннем выявлении БА, подчеркивая перспективы Robo-pen как преобразующего инструмента в диагностике и управлении нейродегенеративными заболеваниями.

Ключевые слова: болезнь Альцгеймера, легкие когнитивные нарушения, Robo-pen, почерк, анализ данных.

Мақаланың редакцияға түскен күні: 12.07.2024.

UDC 004.896
IRSTI 28.23.27

https://doi.org/10.55452/1998-6688-2024-21-3-90-115

[1]Samigulina Z.I.,
PhD, Professor, ORCID ID: 0000-0002-5862-6415,
e-mail: z.samigulina@kbtu.kz
[1]*Baikadamova S.S.
Master student, ORCID ID: 0009-0003-1734-8548,
*e-mail: tassbulatova@gmail.com

[1]Kazakh-British Technical University, 050000, Almaty, Kazakhstan

THE INFLUENCE OF DATA SAMPLING ON SOLVING THE PROBLEM OF PATTERN RECOGNITION FOR DIAGNOSTICS OF INDUSTRIAL EQUIPMENT

Abstract

With the sophisticated technology that modern industrial organizations are equipped with, state prediction and diagnostics are essential duties. The current research aims to develop a more accurate modified artificial intelligence system for industrial equipment diagnostics in the oil and gas industry. Researching faulty signals and processing methods utilized by equipment in the oil and gas industry, as well as assessing the advantages and disadvantages of different signal extraction strategies, are the first steps in the process. The second is the application of artificial intelligence to decision-making and equipment defect detection. This method widely used by the oil and gas sectors to lower equipment failure rates. The recommended diagnostic system helps organizations reduce the financial risks associated with equipment defects by increasing production dependability, enabling for maintenance planning, predicting probable failures, and expediting equipment repairs. The article is devoted to the study of the data sampling influence on the classifier's predictive ability in diagnosing of the industrial equipment. Various types of data samples were considered, such as: simple random sample, cluster sample, systematic sample. According to the results of listed data samples were built classifiers based on particle swarm optimization and ensemble models (bagging and voting type). The best results were achieved using the systematic sampled dataset and an ensemble modeling strategy with voting, which combines forecasting based on a neural net, gradient boosted trees and naive Bayes models: accuracy 93.6%; classification error 8%; recall 94.32%; precision 93.87%. The resulting best strategy for diagnosing equipment based on data sampling and an ensemble model was used for implementation in FMEA (Failure Mode and Effects Analysis) technology in order to obtain an improved version, which is adapted for working with big data.

Key words: industrial equipment diagnostics, data sampling, simple random sample, cluster sample, systematic sample, particle swarm optimization, ensemble methods, FMEA improved model.

Introduction

Currently, the digitalization of production is actively developing, which in turn makes it possible to introduce new innovative techniques for data processing into real industrial systems. Large oil refineries built on the basis of modern microprocessor technology with a remote data input/output architecture generate a huge amount of production information per day, the analysis of which in real time is not possible. Most of the information is archived and is not used in any way to predict system behavior. A simple programmable logic controller can handle up to 200 points, while scanning times vary from 10 seconds to 1 minute. Thus, the automation reads 36,000 data per hour. For large distributed control systems, the number of points is about 2,000, depending on the type of production, which leads to exponential growth in the generated data. In order to make a correct forecast, experts recommend analyzing data for the year, taking into account the seasonality of work, failures and various modes, which leads to a huge amount of production data. Classic statistical algorithms for

data processing do not give the desired results, since behind the data there are specific units and their states, an error in the analysis of which can lead to an emergency stop at the enterprise.

To solve such problems, large oil companies are actively implementing artificial intelligence that can make such appropriate data sampling in order to maintain the dynamics of the industrial system's behavior and maintain high accuracy analysis.

A common task is timely intelligent diagnostics of equipment to prevent costly downtime in enterprises. However, not all artificial intelligence methods can successfully cope with the processing of production data, which has its own specifics. Issues of equipment diagnostics, risk assessment and failure severity are resolved using methods such as HASOP (Hazard and Operability Study), HASID, FTA, FMEA (Failure Mode and Effects Analysis), etc. These methods allow to eliminate errors at an early stage, also they are simple and intuitive, and do not contain complex calculations, but can be labor-intensive for large systems. Errors accumulate in a redundancy system when several levels of a hierarchical system need to be monitored, and one big problem is the lack of ability to assess the reliability of the entire complex system.

The problem can be solved using an extended FMEA equipment failure model using modern predictive analytics methods. However, to integrate artificial intelligence into the FMEA model, it is necessary to develop the most efficient intelligent algorithm that can deal with a large amount of production data [1, 2].

Thus, it is relevant to develop new, modern methods for processing industrial data for diagnosing expensive equipment in order to minimize economic costs in production and timely maintenance of a complex technical equipment.

Currently, artificial intelligence methods are actively used to analyze production data. For example, in work [3] a system of preventive repair and diagnostics of various types of equipment is considered. Neural network technology is used to recognize bearing defects. A convolutional neural network and wavelet transform are used to obtain 2D images of vibration signals. Research [4] focuses on the detection and classification of electric motor faults to ensure equipment operational integrity. A data preprocessing method based on wavelet transform and short-time Fourier transform is used to identify hidden patterns in the vibration data of electric motors. Data analysis was carried out based on a convolutional neural network. The study highlights the effectiveness of combining artificial intelligence and data preprocessing techniques for diagnosing equipment failures. The work [4] covers research on swarm intelligence algorithm based on differential evolution (DE) and gray wolf optimization (GWO) using a convolutional neural network classifier to diagnose rolling bearing faults. An improved 1D-CNN algorithm with hyperparameter optimization is proposed. The effectiveness of the algorithm was confirmed by research on the databases of Case Western Reserve University (CWRU) and Jiangnan University (JNU). Study [5] examines data collected from protective relays to diagnose faults in power system components. The authors presented a hybrid support vector machine and artificial neural network (SVM-ANN) model for fault diagnosis.

Currently, combined algorithms based on several artificial intelligence algorithms have shown high efficiency. For example, [6] discusses a deep learning method for diagnosing faults in rolling bearings using artificial immune systems. An adaptive enhanced deep convolution algorithm is used to extract the feature set. Research [7] is devoted to the analysis of the hybrid CSA-DEA method (Clonal Selection Algorithm with a Differential Evolution Algorithm) for flaw detection of structures with cracks. The input data of the hybrid system is the relative frequency values of the damaged structure, and the output data is the relative crack locations and depth. The work [8] considers a bioinspired anomaly detection algorithm based on the surface dendritic cell algorithm (Cursory Dendritic Cell Algorithm, CDCA). Immune models such as the Dendritic Cell Algorithm (DCA) are a promising area of research, since the problem of detecting abnormalities in CPPS is reminiscent of the work of dendritic cells in protecting the human body from dangerous pathogens. A new variant of DCA, the CDCA algorithm, is proposed, designed for continuous monitoring of industrial processes and online anomaly detection. The experimental results showed their effectiveness and were carried out on the basis of two industrial datasets for detecting physical anomalies and network intrusions (Skoltech Anomaly Benchmark (SKAB) and M2M using OPC UA).

A promising area of research is the use of ensembles of models for equipment diagnostics [9]. For example, [10] solves the problem of bearing fault detection using a graphical autoencoder and ensemble learning. A new approach to bearing fault detection based on graph neural networks and ensemble learning is proposed. The study [11] focuses on the development of a weighted ensemble model based on LightGBM for fault diagnosis with a small number of pulses. With an ensemble, the potential diagnostic error of each classifier can be reduced, thereby increasing the generalization ability of the entire model. Work [12] considers a hybrid method for diagnosing faults in power transformers based on the classification of ensemble trees and training subsets using Rogers and Gouda coefficients. The study [13] proposed an ensemble prediction model for analyzing equipment failures in the oil and gas industry. The work implements an ensemble approach to combine different classifiers in order to improve the performance of the SVM training classifier.

Modifications based on artificial intelligence of industrial equipment diagnostic models are interesting. For example, [14] discusses the role of artificial intelligence in improving the efficiency of failure modes and effects analysis (FMEA). The study [15] presents a modification of the FMEA model by replacing the expert assessment of the "probability of occurrence" criterion with a machine learning model based on the support vector machine. Work [16] is devoted to an intelligent model for FMEA risk assessment based on fuzzy logic, nearest neighbor method and support vector machine.

The stable and safe operation of mechanical equipment is becoming increasingly significant in current industry, which aims to reduce unnecessary routine shutdown, maintenance costs and even sudden person casualties [17]. Thus more and more attention has been paid to fault diagnosis of machinery. Meanwhile, with the rapid development of Internet of Things, sensing technology, and big data, a new revolution is quietly sprouting up in this field, in which a major feature is ever-increasing mass of data [18].

In general, majority of industrial equipment lacks the capability of built-in self-diagnostics and prognostics. In addition, the nominal characteristics, along with the failure modes, change over time due to wear off, maintenance, and the repair/replacement of parts and components. This reality calls for alternative approaches that can minimize the need for analysis of the specific machine failure modes [19]. Fault diagnosis approaches can be classified into three categories: model-based [20, 21], signal-based [22–23], and data-driven approaches [24–25]. In model-based approach, focus is on establishing mathematical models of complex industrial systems. These models can be constructed by various identification methods, physical principles, etc. Signal-based approach uses detected signals to diagnose possible abnormalities and faults by comparing detected signals with prior information of normal industrial systems [26]. Usually, difficulty occurs in building accurate mathematical models and obtaining accurate signal patterns for complex industrial and process systems. Data-driven fault diagnosis approach requires large amount of historical data, rather than models or signal patterns [27]. Therefore, data-driven methods are suitable for complex industrial systems.

Over the past few years, there has been substantial advancement in the field of applying AI algorithms for diagnostics. The oil and gas business may now use less time and money thanks to the adoption of artificial intelligence techniques. By adopting the appropriate neural algorithms, machine learning has advanced this field and plays a crucial role in diagnosing machinery and correctly forecasting results said in their work Andrey Ostroukh, Leonid Berner, Maria Karelina [28]. Condition monitoring and fault diagnostic systems are crucial for lowering the likelihood that this equipment may malfunction. In this work [29] Stefania Santini, Francesco Flammini - students of Malardalen university in Sweden, University of Naples Federico 2nd, Italy, conducted defect diagnostics in rotating machinery using artificial intelligence, signal processing, and permutation entropy.

Only the initial phase in condition monitoring and maintenance involves the collecting of signals. In order to identify fault formation, it is also important to analyze the gathered monitoring data and extract features.

Finally, artificial intelligence models and methodologies are utilized to detect and forecast defects based on the retrieved information. Traditional, contemporary, and intelligent diagnosis techniques all fall under the category of signal processing technologies [30–31].

The obtained results require further study at the level of management decisions on the state of the equipment for the current production [32]. These days, using a project-oriented approach to manage an industrial organization is frequently linked to such solutions. In that case, various techniques were explored for the development of the classificatory according to their pros and cons in the theoretical analysis provided. For example, the Ensemble voting method provides numerous benefits within industrial equipment diagnostic systems. Benefits of using the ensemble voting technique [33–34]: Increased precision: when multiple models are combined, collective voting typically yields more stable and precise predictions compared to using individual models alone. Also, there is a greater complexity, which is combining various models and developing synthesis strategies may lead to an increase in the computational complexity and resource demands of the diagnostic system [35–36].

Thus, an analysis of the literature proves the relevance of developing new equipment diagnostic methods both for analyzing databases of equipment failures and for improving existing diagnostic models.

The problem statement of the research is formulated as follows: it is necessary to develop an intelligent algorithm for diagnosing industrial equipment, taking into account the large amount of production information and the possibility of integration into the FMEA equipment diagnostic model.

Materials and Methods

The initial dataset of the research is full with unsystematic and unclear data and values, which is also consisted of enormous amount of information. In this section, all the data preparation methods and further classification development techniques are provided.

Sampling methods

A set of data plays a huge role in solving problems associated with real industrial production. During the operation of control systems, microprocessor technology generates a huge amount of production data, so the average time for sensors' information scanning by the controller is 20 m/s, while if a programmable logic controller on a production line serves up to 200 points, then the size of the technological process observation database per day will be enormous in size. Thus, the issue of reducing the dimensionality of the source data and correct data sampling is an urgent task.

In order to observe what kind of sampling is better and more efficient for particle swarm optimization and machine learning methods, it is necessary to choose correct data sampling types. All of them are probability sampling methods, because they are the best solutions for quantitative research. Let's get through each of them briefly.

Simple random sample

There are lots of sampling methods, for instance Simple random sample. Simple random sample is a type of sampling where all the dataset information used and every member of that data has a chance to be selected for further manipulations. The sampling frame must include the entire dataset information. To perform this type of sampling, usually used such tools as random number generators or other techniques that rely entirely on chance.

In Python there is a specific library to perform such sampling methods. Algorithm 1 for the simple random sampling is as follows:

Algorithm 1. Data sampling method: simple random sample.

Step 1. Read the csv file with the number of equipment characteristics.

Step 2. Import Python library for sampling techniques by "import random".

Step 3. Declare the range of the initial dataset.

Step 4. Specify the random sample size as 100.

Step 5. Perform Simple Random Sampling by the following "random.sample(x,y)" command.

Step 6. Get the result of the random sampling.

Here demonstrated the simple explanation of the random sampling method (Figure 1).




Figure1 – Simple random sampling illustration

It is clear from the Figure1 that by using random sampling technique it could be guaranteed that every member of the population or dataset can be chosen for the sampling group without any systematic or statistical rules.

Cluster sample

Another one frequently used data sampling method is cluster sampling. Cluster sampling is similar to stratified sample by dividing the whole data into subgroups. However, in cluster sampling each subgroup must have similar characteristics to the entire sample. And also, by using that method it randomly selects entire subgroups not individuals. The Algorithm 2 for Cluster sampling is described below:

Algorithm 2. Data sampling method: cluster sampling.
Step 1. Read the csv file with the number of equipment characteristics.
Step 2. Import Python library for sampling techniques by “import random”.
Step 3. Declare the range of the initial dataset.
Step 4. Define the number of clusters and cluster size.
Step 5. Perform randomly selecting of some clusters.
Step 6. Create a list to store the cluster samples.
Step 7. Sample all elements within the selected clusters.
Step 8. Get the result of the cluster sampling.
In Figure 2 presented the structure of the cluster data sampling method.




Figure 2 – Cluster sampling illustration

This data sampling method could be used in industrial equipment diagnostic systems.

Systematic sample

Systematic sample is quite similar to simple random sampling, but is usually a little easier to perform. Each member of the population: in our terms is each failure of the equipment is numbered and then individuals are selected at regular intervals not by a random generator. Systematic sampling method's Algorithm 3.

Algorithm 3. Data sampling method: systematic sample

Step 1. Read the csv file with the number of equipment characteristics and machine values.

Step 2. Import Python library for sampling techniques by the following "import random".

Step 3. Declare the range of the initial dataset.

Step 4. Specify the random sample size as 100.

Step 5. Calculate the sampling interval.

Step 6. Perform Systematic Sampling.

Step 7. Get the result of the random sampling.

The systematic sampling method is more effective in this study, because of its interval dividing technique, which gives an opportunity to analyze each equipment's value and not drop any important data. In Figure 3 the systematic sampling method is illustrated.




Figure 3 – Systematic sampling illustration

The advantages of this method are its simplicity and quick implementation.

Pattern recognition methods

As pattern recognition methods were applied Particle swarm optimization (PSO) and Ensemble method. Those methods are better explained in following paragraphs.

Particle swarm optimization

Particle swarm optimization (PSO) is one of the bioinspired algorithms, and it searches the solution space for the best possible solution in a straightforward manner. It differs from other optimization techniques in that it does not depend on the gradient or any differential form of the objective and simply requires the objective function. There are also not many hyperparameters.

A particle swarm optimization operates in this manner: it begins with a number of random locations on the plane (referred to as particles) and let them search for the minimum point in random directions. Every particle should look around the lowest position it has ever found as well as the lowest point the entire swarm of particles has ever found at each step. Regard the minimal point of the function to be the least point that this swarm of particles has ever investigated after a specific number of iterations. For better understanding in a practical vision here the pseudocode of the PSO technique is described below [37].

Pseudocode of the PSO algorithm:

Input: a_{nm} – position of the particle; v_{nm} – velocity of the particle; i – number of iteration;
Output: the optimal solution for the particle position

For each particle n
For each dimension m
Initialize position a_{nm} randomly with possible interval
Initialize velocity v_{nm} randomly with possible interval

End_for
End_for

Iteration i = 1 Do
For each particle n calculate suitable value
If the suitable value is better that $TheBest_{nm}$ in history
Set current suitable value as the $TheBest_{nm}$

End_if
End_for

Chose the particle with the best suitable value as the $TheBest_m$

For each particle n

For each dimension m calculate velocity with the equation

$$\vartheta_{nm}^{t+1} = \omega^t \vartheta_{nm}^t + \varphi_{nm}^t (TheBest_{nm}^t - x_{nm}^t) + \varphi_{2m}^t (TheBest_n^t - x_{nm}^t)$$

Update particle position with the equation:

$$\alpha_{nm}^{t+1} = x_{nm}^t + \vartheta_{nm}^{t+1}$$

End_for

End_for

i = i+1

While max iteration or min error criteria are not attained.

Particle Swarm Optimization is a metaheuristic optimization algorithm inspired by the social behavior of flocks of birds and schools of fish. It is often used to solve optimization problems, such as those encountered in research on diagnostics of industrial equipment. In this context let's present some advantages and disadvantages of using PSO.

Advantages of the method [38]:

1. Global Optimization: PSO is good at finding global optimization in complex search spaces. In the context of diagnostic methods PSO could effectively explore the space of possible diagnostic models or parameters to find the optimal solution.

2. Simple Implementation: PSO is relatively easy to implement and requires minimal parameter tuning compared to other optimization algorithms. This is beneficial in research environments where time and resources are limited.

3. Convergence Speed: often converges to a solution relatively quickly, especially for simple or moderately complex optimization problems. This is beneficial when working with large datasets or performing repeated experiments in device diagnostic studies.

4. Robustness: tends to be robust to noise and is less likely to fall into local optima compared to other optimization algorithms. This is important in research on diagnostics of industrial systems where noisy sensor data and complex interactions between components can make optimization problems difficult.

5. Scalability: it could be easily parallelized, allowing efficient optimization on high-performance computing platforms and distributed systems. This is advantageous when dealing with large industrial facilities or performing experiments that require large amounts of calculations.

Disadvantages of the method:

1. Premature Convergence: PSO prematurely converges to suboptimal solutions, especially in highly multimodal optimization environments or misleading optimization landscapes. This can be problematic in device diagnostic studies, where the lack of a global optimum can result in inaccurate or unreliable diagnostic models.

2. Limited Search: you can have difficulty effectively exploring the search space, especially when dealing with high-dimensional or non-convex optimization problems. This limitation could impact the ability to find optimal diagnostic models or parameters in complex industrial systems.

3. Parameter Sensitivity: Although PSO requires fewer parameters to be tuned than other optimization algorithms, PSO's performance is influenced by the selection of parameters such as inertia weights and acceleration factors. It may be easy to receive. Finding optimal parameter settings may require experimentation and can be computationally intensive in research environments.

4. Noisy optimization: PSO may not perform well for optimization problems with noisy or uncertain objective functions. In research on diagnostics of industrial equipment, sensor data can be noisy or incomplete, and this limitation can affect the reliability of diagnostic models obtained with his PSO.

5. Lack of Guarantees: method does not guarantee convergence to the global optimum, especially in non-convex or discontinuous optimization landscapes. This lack of warranty can be problematic in critical industrial applications where accurate diagnostics are essential for safety and efficiency.

Overall, PSO could be useful tool when considering diagnostic methods for industrial equipment, offering advantages such as global optimization capabilities, ease of implementation, and speed of convergence.

However, researchers should be aware of its limitations, especially regarding premature convergence, limited exploration, and sensitivity to parameters, and carefully consider whether PSO is suitable for a particular optimization problem.

Ensemble (bagging and vote types)

Ensemble techniques are a significant technique in computer science and machine learning that combines numerous base models to produce a better, more robust predictive model. These strategies frequently outperform individual models by utilizing the diversity of the basis models and combining their predictions.

Ensemble approaches often rely on a set of basis models, known as weak learners or base classifiers/repressors. These basis models can be the same type (homogeneous ensembles) or different types (heterogeneous ensembles), including decision trees, neural networks, support vector machines, and any other machine learning algorithm [39].

1. Bagging (Bootstrap Aggregating) is the process of training multiple base models independently on distinct subsets of training data (sampled with replacement) and then aggregating their predictions. Random Forest is a common bagging-based ensemble approach that uses decision trees as its basic model. However, in this research Neural Network methods are used for bagging, which is more efficient.

Advantages of ensemble bagging method [40]:

◆ Variance reduction: By training numerous base models on distinct subsets of the training data (sampled with replacement), bagging helps minimize the final model's variance. Each base model learns slightly different parts of the data, resulting in a more robust and stable ensemble.

◆ Bagging improves the generalization performance of the ensemble model. Bagging decreases the risk of overfitting by aggregating predictions from many models trained on different subsets of data and capturing more generalizable patterns in the data.

◆ Robustness to Noise: Because bagging integrates predictions from numerous models, it is more resistant to noisy or outlier data. Outliers may have less of an impact on the final prediction due to the averaging or voting procedure.

◆ Bagging base model training is easily parallelizable because each model is trained independently. This makes bagging appropriate for distributed computing systems and can result in considerable speedups in model training.

Disadvantages of the Ensemble bagging [41–42]:

◆ Increased Computational Cost: Training multiple base models in bagging can be computationally expensive, especially if the base model is complicated or a high number of models are included in the ensemble. This can limit bagging's scalability in large datasets or resource-constrained contexts.

◆ Loss of Interpretability: Because the ensemble incorporates predictions from numerous models, the final model's interpretability may be lower than that of the individual base models.

Understanding the underlying decision-making process of the ensemble may become increasingly difficult, especially with sophisticated bagging schemes or with a high number of base models.

2. Voting: In classification tasks, each base model predicts a class label, and the final prediction is selected by a majority vote. In this research for voting method were used following techniques: Naïve Bayes, Neural Net and Gradient Boosted Trees.

In that article, our aim is to collect the dataset of equipment failures and apply various sampling techniques to get the desired results. Artificial intelligence and statistical methods are currently used to solve a variety of practical challenges.

3 FMEA model

FMEA, or Failure Mode and Effects Analysis, is table, which contains the structured way to classifying all errors that can occur during the design, manufacture or assembly of a product or service. It is especially useful for identifying and mitigating risks early in the development process [43].

In Table 1 is a breakdown of common FMEA table headings and their meanings represented:

Table 1 – FMEA table representation

Input/Name/or the Step in process	The Failure Mode (Potential)	Failure Effects	Severity	Potential Causes of error	Occurence	Detec-tion	RPN
The process step, name, changes in process, which is under the investigation?	Where and how the process or feature could go wrong?	Explanation of the impact, which can be caused by this failure on the customer or process itself?	Range from 1 to 10	The main possible causes of the failure or error	Range from 1 to 10		Risk Priority Number

There are the explanation of the headers in the Table 1:

◆ Process Step/Input – What device or process step exactly is under the investigation. List of components or functions being analyzed. It could be helpful to identify the exact part of the process which being evaluated and focuses more on the analysis of specific elements.

◆ Potential Failure Mode – Exactly in what step or changes the process go wrong? This feature describes the possibilities in which a component or function device might fail to get the desired outcomes or goals.

Basic for distinguishing the different ways of process failure, which is the primary step in preventing such downfalls.

◆ Failure Effects (potential) – Describes in what ways the failure could impact the operation of the system, including its impact on customer satisfaction, safety, and adherence to regulations. Recognizing the consequences of failures is key in determining which issues to address first, allowing for resources to be allocated to tackle the most important issues.

◆ Severity (1–10) – Typically ranging from 1 to 10, assess the gravity of the impacts caused by each failure mode. It offers a measurement for estimating potential harm, which is vital for evaluating and controlling risks.

◆ Potential Causes – Identifies factors or shortcomings that could result in the failure mode. Identifying reasons for failures is essential in order to create successful prevention plans.

◆ Occurrence (1–10) - Approximates the chances of a failure happening, usually measured on a numerical scale. Assists in determining the probability of failures, which is essential for prioritizing and managing risks.

◆ Detection (1–10) – Rated on a scale of 1 to 10, evaluates the effectiveness of existing controls in identifying or stopping a potential failure mode. Ensures that potential issues are identified early on, reducing risks and enhancing dependability.

◆ RPN – Risk Priority Number – A numerical rating derived from multiplying the ratings for Severity, Occurrence, and Detection. Offers a numerical assessment of the risks linked to every potential mode of failure, helping in determining which risk reduction strategies should be prioritized.

After the data sampling there is need to apply optimization methods on 4 different datasets: initial data without any changes, simple random sampled data, cluster sampled data and systematic sampled data each one respectfully. Then, it could be more convenient to chose the best suitable sampling method for further experiment of developing the classificatory.

Initial dataset explanation

The database is taken from the kaggle equipment diagnostics data repository. It contains machine failures and process characteristics [https://opendatacommons.org/licenses/dbcl/1-0/].

As a dataset there is a csv file with the equipment characteristics and its failure happened or not with the range R = 10x8091, 80910 data attributes. It has columns (headers) as:

◆ Number – unique data identification;

◆ Product ID – consisting of a letter L, M, or H for low (50% of all products), medium (30%) and high (20%) as product quality variants and a variant-specific serial number;

◆ Type – type of the equipment L, M or H (described above);

◆ Air temperature – generated using a random walk process later normalized to a standard deviation of 2 K around 300 K;

◆ Process temperature – generated using a random walk process normalized to a standard deviation of 1 K, added to the air temperature plus 10 K;

◆ Rotational speed – calculated from a power of 2860 W, overlaid with a normally distributed noise;

◆ Torque – torque values are normally distributed around 40 Nm with a SD = 10 Nm and no negative values;

◆ Machine failure – indicates, whether the machine has failed in this particular datapoint for any of the following failure modes;

◆ HDF – heat dissipation failure: heat dissipation causes a process failure, if the difference between air and process temperature is below 8.6 K and the tools rotational speed is below 1380 rpm;

◆ PWF – power failure: the product of torque and rotational speed (in rad/s) equals the power required for the process. If this power is below 3500 W or above 9000 W, the process fails. Here is the initial dataset of the research Table 2.

Table 2 – Fragment of the equipment diagnostic database before applying data sampling

N	Product ID	Type	Air tempe-rature	Process tempe-rature	Rotational speed	Torque	Machine failure	HDF	PWF
1	M14860	M	298.1	308.6	1551	42.8	0	0	0
2	L47181	L	298.2	308.7	1408	46.3	0	0	0
3	L47182	L	298.1	308.5	1498	49.4	0	0	0
…	…	…	…	…	…	…	…	…	…

In our dataset there are 1,000 rows of various failure modes. It would be more appropriate to divide this amount of failure and make a research on every classified part of them.

The 3D scatter plot of the initial database is presented (Figure 4).




Figure 4 – The 3D scatter illustration of the initial dataset

In the Figure 4 it is observed that the values of the sensors are similar and too many of them are located closer to each other, because the initial dataset is huge and consists of 10,000 values of each equipment on various condition. In order to make an appropriate experiment, it is need to sample this dataset and split it into short but effective ones.

Simple random sampled dataset

Here is the Table 3, where the random sampled data is performed. In this table "N" – is the randomized serial number of the equipment, they are written in random sampled way.

Simple random sampling was implemented by Python algorithm, which was explained on previous sections. Using the random sampling was generated a new dataset with range R = 10x200.

Also, in Figure 5 the 3D scatter plot of the random sampled data is shown below.

Table 3 – Simple random sampling dataset

N	Product ID	Type	Air tempe-rature	Process temperature	Rotatio-nal speed	Torque	Machine failure	HDF	PWF
894	M15753	M	295.7	306.2	1423	42.5	0	0	0
1673	L48852	L	298.1	307.8	1432	49.8	0	0	0
2344	L49523	L	299.1	308.3	1305	61.4	0	0	0
…	…	…	…	…	…	…	…	…	…




Figure 5 – The 3D scatter illustration of the simple random sampled dataset

In the figure above, it is seen that the data values are located separately from each other, which means that the random sampling is implemented correctly.

Cluster sampling dataset

Cluster sampling was implemented by the algorithm explained on the previous sections in Python platform. In Table 4 the result of the cluster sampling method is shown:

Table 4 – Cluster sampling dataset

N	Product ID	Type	Air tempe-rature	Process tempe-rature	Rotational speed	Torque	Machine failure	HDF	PWF
1	M14860	M	298.1	308.6	1551	42.8	0	0	0
7	L47186	L	298.1	308.6	1558	42.4	0	0	0
8	L47187	L	298.1	308.6	1527	40.2	0	0	0
…	…	…	…	…	…	…	…	…	…

On the Table above it is seen that values are selected differently from random sampling, because in cluster sampling it uses dividing by the cluster group technique and then only the randomize the selected clusters. Cluster sampling method also have generated a new dataset with range R = 10x200. That range is more specific and convenient while using it in further optimization techniques. Here is the 3D scatter representation of the cluster sampled dataset (Figure 6).




Figure 6 – The 3D scatter illustration of the cluster sampled dataset

In this Figure 6 it is shown that the values of the sensors are located separate but also huddled together in some places as they sampled by clusters. It is necessary to admit that the cluster selected group are randomized before getting the final result, that's why the values on the Figure 6 are separated as random sampling.

Systematic sampling dataset

Systematic sampling was also implemented in Python platform with explained algorithm. Here is the Table 5, where systematic sampled data is presented.

Table 5 – Systematic sampling dataset

N	Product ID	Type	Air temperature	Process temperature	Rotational speed	Torque	Machine failure	HDF	PWF
8	L47187	L	298.1	308.6	1527	40.2	0	0	0
18	M14877	M	298.7	309.2	1410	45.6	0	0	0
29	L47208	L	299.1	309.4	1439	44.2	0	0	0
…	…	…	…	…	…	…	…	…	…

By applying systematic sampling on the initial dataset, it was given a new different dataset with the range R = 10x200 also. In systematic sampling there is need to divide the initial dataset by the specific interval. The 3D scatter plot of the systematic sampled dataset is shown in the Figure 7.




Figure 7 – The 3D scatter illustration of the initial dataset

The systematic sampling is close to the random sampling by the logic but the sampling is implemented by the specific number or character, so each there is more probability that all the values from every condition can be selected.

Results and discussion

After implementing the sampling techniques on the initial dataset, were developed the classifiers based on PSO and ensemble methods, which results are provided in this section.

Development of a classifier based on the PSO algorithm

After applying those three methods of sampling, it is necessary to apply particle swarm optimization on each subgroup of dataset. By comparing them with each other it could be possible to investigate which method of sampling gets better results with PSO techniques. The Figure 8 represents the implementation of the PSO process.




Figure 8 – PSO modeling process

In equipment diagnostic systems it is crucial to determine influence factors of the dataset, because not all the equipment values cause a failure. In PSO modeling the weighting algorithm is used to determine the important factors, which are also presented in Figure 8.

Development of a classifier based on an ensemble bagging method

In Figure 9 represented the bagging modeling process, where except the bagging were used cross validation function to connect with the dataset and its labels.




Figure 9 – Ensemble bagging modeling process

In the training of the method are used 100 till 200 training cycles to observe how fast could the method learn by time. All the applied methods' results shown in the next section.


Modelling results and metrics

At first, in the Table 6 there are the results of the PSO and ensemble bagging methods divided by each sampled dataset. The results of modeling and experiments were evaluated based on the following metrics: Accuracy, Classification error, Recall, Precision, Recall. The problem of binary classification was considered, where the first class with the value "1" is the normal operation of the equipment, the second class "0" is the equipment failure.

Table 6 – The results of the PSO and Ensemble bagging methods implemented with initial and sampled datasets


Dataset	Classification algorithm	Accuracy	Classification error	Recall	Precision
Initial raw dataset (before data reduction)	PSO	77,63 %	22,37 %	76%	81%
	Ensemble (bagging)	89,72 %	10,28 %	80%	83%
Dataset after random sampling	PSO	81,88 %	18,12 %	83,06%	83,76%
	Ensemble (bagging)	90,54 %	9,46 %	89%	91%
Dataset after cluster sampling	PSO	85,73 %	14,27 %	89,42%	82,57%
	Ensemble (bagging)	91,62%	8,38%	92,07%	89,5%
Dataset after systematic sampling	PSO	89,17%	10,83%	85%	89%
	Ensemble (bagging)	93,808%	6,19%	88%	91%

The ROC (Receiver Operating Characteristic) comparison is also represented, because it is efficient way to compare the classification methods. The area under the ROC curve (AUC-ROC) is used to quantify a classifier's overall performance. A higher AUC value (closer to 1) suggests that the model distinguishes between positive and negative cases more accurately.



a) b)

Figure 10 – ROC thresholds of a) initial dataset and
b) random sampled dataset by ensemble bagging model



c) d)

Figure 11 – ROC thresholds of c) cluster sampled dataset and
d) systematic sampled dataset by bagging model

In Figures 10 and 11, there is seen that the b) random sampled and d) systematic sampled data's bagging model are more efficient and faster tends to one in its learning model.

Comparing different models: In machine failure prediction research, numerous models are frequently constructed and tested to determine the best successful strategy. The ROC comparison method allows researchers to objectively examine and compare the performance of various models. Researchers can decide which model has the best prediction ability by studying its ROC curves and AUC values.

Ensemble VOTE

Ensemble voting combines the strengths of various distinct models, which may mitigate the faults of any single model. Ensemble approaches, which aggregate forecasts from multiple models, frequently produce more accurate predictions than any particular model alone. In our research were used Neural net, Gradient Boosted trees and Naïve Bayes as a component of the ensemble vote method. In Figure 12 is shown the modeling process of ensemble vote technique.




Figure 12 – Ensemble Vote modeling process

On top of the predictions made by the basic learners in its subprocess, this operator applies a majority vote (for classification) or an average (for regression). The Ensemble voting results with initial and sampled dataset are shown in the Table 7.

Table 7 – The results of the Ensemble vote method implemented with initial and sampled datasets

Dataset	Method type	Accuracy, %	Classification error, %	Recall, %	Precision, %
Initial	Ensemble (vote)	86.94	13.06	89.07	85.78
Random sampled	Ensemble (vote)	92.2	7.8	90.06	91.66
Cluster sampled	Ensemble (vote)	90.44	9.56	91.2	91.66
Systematic sampled	Ensemble (vote)	93.6	6.4	94.32	93.87

From the above table it is clear that the ensemble vote methods are more effective than the other, also the combination of the vote method with the systematic sampling techniques gives the best result for the machine failure prediction experiment.

Furthermore, for better experiment results comparison in this research the ROC comparison techniques were extracted from the implemented vote model. The ROC (Receiver Operating Characteristic) comparison is an important technique for evaluating the performance of machine learning models, especially in tasks such as machine failure prediction. It does a thorough examination of the trade-offs between true positive rate (sensitivity) and false positive rate (1-specificity) at various thresholds. Here is the ROC comparison of the best given result - vote model with systematic dataset is shown in the Figure 13.




Figure 13 – ROC comparison of vote model with systematic sampled dataset

In this research was implemented Naïve Bayes and Gradient Boosted Trees in the Ensemble vote modeling. Here is the results of the ROC comparison below, where also added the Last Large Margin, Deep learning and Random forest methods just for the comparison (Figure 14).




Figure 14 – ROC comparison of various types of classification

As it's illustrated, the ROC curve is a graphical representation of a classification model's performance under different threshold settings. The ROC curve for models below rises sharply from the lower-left corner, showing that it achieves high true positive rates (sensitivity) while maintaining relatively low false positive rates (1-specificity) across various threshold settings. This shows that Naïve Bayes and Gradient boosted trees are highly predictive and successfully distinguishes between positive and negative examples.

Finally, in this research, various machine-learning algorithms for predicting equipment failure in industrial production were studied. Throughout our research, a variety of predictive modeling strategies were investigated, including particle swarm optimization (PSO), ensemble bagging, and ensemble voting. Each technique was assessed based on its capacity to distinguish between normal functioning and failure occurrences, with an emphasis on maximizing predicted accuracy and resilience. Our experiment shows that, while PSO and ensemble bagging showed promise in capturing underlying patterns in the data and generating individual predictive models, the ensemble vote modeling approach emerged as the most effective and reliable method for machine failure prediction in our setting.

The ensemble vote modeling strategy, which combines the predictions of Neural net, Gradient boosted trees and Naïve Bayes models via a voting process, outperformed other methods tested.

Thus, the developed strategy can be applied to production data and integrated into classical equipment diagnostic models, for example, the FMEA model for solving problems associated with large volumes of production data, with the ability to determine the impact of only individual failures, but not their combinations, and also replace the routine work of an expert for automated scanning using artificial intelligence.

FMEA model integration

In this work the integration of FMEA is important, because the effectiveness of using FMEA table in diagnostic processes is crucial. At first, there is need to explain all the table headers and their necessity. After that, by using previous artificial intelligent methods such as Ensemble vote type techniques the FMEA table's "Severity" character would be predicted. For this experiment only systematic sampled dataset is used, because after all previous training sets exactly the systematic sampling method have shown the most accuracy and effectiveness.

Description of the TCO Dataset

The object of the research is unit 300, which's obligation is to purify crude high- and medium-pressure associated petroleum gas coming from unit 200 from hydrogen sulfide H2S, carbonyl sulfide COS and carbon dioxide CO2. The overall structure of the process is shown in Figure 15.




Figure 15 – Gas purification process in high pressure

When cleaning, a selective process of absorption (absorption) of the above components into a diethanolamine solution is used.

The products of installation 300 are:

- purified VD gas – raw material for the gas fractionation unit (U-700);
- purified SD gas returned to U-200 for compression;
- purified LP gas supplied to the U-500 tail gas afterburner as fuel gas (through the exhaust gas collector).
- acid gas with a high content of H2S – raw material for sulfur extraction at U-400.
- Incoming high- and medium-pressure gas streams contain large amounts of moisture and sulfur-containing components.

The dataset for FMEA prediction system is represented in Table 8.

Table 8 – FMEA model for technological process installation 300, TengizChevroil plant

ID	Type	Air temp.	Process temp.	Rota-tional speed	Torque	Process In/ Out	Potential Failure mode	Potential failure effects	SEVE-RITY	Potential causes
M14860	M	298.1	308.6	1551	42.8	F-301- High Pres. purified gas sep.	FAL - 03004 Low alarm output flow	Material without reworked	6	Control loop failure
L47187	L	298.1	308.6	1527	40.2	Trans-port material	Scratched material or Damaged material	Material without reworked	6	Moving Materials
M14877	M	298.7	309.2	1410	45.6	Anodization	FAL - 03004 Low alarm output flow	Material without reworked	7	Handling materials
L47217	L	298.8	308.1	1439	39.1	F-301- High Pres. purified gas sep.	FAL - 03004 Low alarm output flow	Material without reworked6	6	Control loop failure
M14904	M	298.8	308.1	1472	47.5	Trans-port material	Scratched material or Damaged material	Material without reworked	8	Moving Materials

The following Figure 16 represents the main Ensemble vote modeling process for FMEA table prediction:

FMEA intellectual diagnostic results

Let’s consider the results of modifying the classical FMEA model using artificial intelligence based on the strategy discussed in sections 5.1–5.4.




Figure 16 – Ensemble Vote type modeling for FMEA table Severity prediction

Table 9 – the classification results of FMEA Severity prediction system:

Dataset	Method type	Accuracy, %	Classification error, %	Recall, %	Precision, %
Systematic sampled FMEA table dataset	Ensemble (vote) – Neural Net, Gradient boosted tree, Deep learning	88.75	11.25	92.11	91.24

The table above displays the classification outcomes of a combined model that combines the predictions of a neural network, a gradient-boosted tree, and a deep learning algorithm. This method, also known as a voting ensemble or ensemble classifier, combines different predictive models to potentially enhance the overall accuracy and reliability of the predictions. Here is an in-depth analysis of the metrics that have been given:

In general, the ensemble voting model shows strong performance in all analyzed metrics, indicating its efficiency in managing the predictive tasks related to FMEA. The model performs well in both recall and precision, indicating it is effective at detecting positive cases and accurately predicting them. This makes it a dependable tool for predictive analytics in safety-critical situations.

In the following Figure 16 is shown the AUC-ROC comparison of the “Severity” coefficient’s prediction model:




Figure 17 – AUC (optimistic) of FMEA Severity prediction process

In studies on predicting machine failures, researchers often create and evaluate various models in order to identify the most effective strategy. Using the ROC comparison method enables researchers to conduct a fair and unbiased evaluation of different models' performances. By analyzing the ROC curves and AUC values, researchers can determine which model has the highest predictive accuracy.

The process of integration of the FMEA table's coefficient prediction achieved dignified results, which means that the ensemble vote model with the combination of gradient boosted tree, neural net and deep learning gets the efficient and correct predicting values for the "severity" coefficient.

Conclusion

Industrial automation systems are characterized by a large amount of production data generated in real time. For example, the scanning cycle of a programmable logic controller averages 20 ms; if the control loop contains 200 points, then the automation system reads 12,000 data per minute. Most of the generated data is archived and is not used to predict the condition of equipment due to the large dimension of the data. Thus, the development of new and improved classification models using different data samples is relevant. Industrial equipment has its own operating specifics and the task of data sampling is to preserve the properties and dynamics of the control object as much as possible. The scientific novelty of this research is in the development of an improved classifier based on systematic sampling data and the construction of an ensemble of models, including Neural Net, Gradient boosted tree, Naïve Bayes.

Throughout the research were completed next operations:

- The initial database was processed using three different data samples: Simple random, cluster and systematic sampling;
- he best data sampling method was selected in combination with which the classifier achieves the best results in modeling;
- The particle swarm method and ensemble models were chosen as the classifier. In the process of studying the properties of algorithms, their advantages and disadvantages, the particle swarm method was chosen as the most suitable for working with specific production data.

◆ Several types of ensemble construction based on Bagging and Voting models were considered. It was proven that the database after using Systematic sampling and the ensemble with the voting type showed the best results.

◆ The FMEA diagnostic table's coefficient's prediction system was integrated by using Ensemble vote type in a combination of Gradient boosted tree, neural net and deep learning techniques.

Building an ensemble allows to compensate for the shortcomings of the previous algorithm with the advantages of the next one in the ensemble. A comparative analysis of the application of these methods based on metrics was carried out. It has been proven that a classifier based on the systematic data sampling and an ensemble with a voting type is the most effective for diagnosing industrial equipment.

Ensemble voting substantially reduced the limits of individual models, such as overfitting and model variability, while improving prediction accuracy and generalization capabilities. Finally, the final classifier provides a robust and dependable framework for preventative maintenance methods by leveraging the collective wisdom of multiple models, resulting in improved operational efficiency, reduced downtime, and increased productivity in industrial settings.

Information on funding

This research has been funded by the Science Committee of the Ministry of Education and Science of the Republic Kazakhstan (Grant No. AP23486386).

REFERENCES

1 Samigulina G., Samigulina Z. Diagnostics of industrial equipment and faults prediction based on modified algorithms of artificial immune systems. Journal of Intelligent Manufacturing, Springer, 2022, vol. 33, pp.1433–1450.

2 Samigulina G., Samigulina Z. Biologically Inspired Unified Artificial Immune System for Industrial Equipment Diagnostic. In: Nicosia, G., et al. Machine Learning, Optimization, and Data Science. LOD 2022. Lecture Notes in Computer Science, 2023, vol 13811. Springer, Cham. https://doi.org/10.1007/978-3-031-25891-6_7.

3 Elton P De Souza, Lis Moura, Thiago Barroso Costa, João Lucas Lobato Soares. Convolutional neural networks for pattern-based fault diagnosis in low-rotation equipment. International congress of mechanical engineering, 2023.

4 Leandro Ventricci, Ronny Francis Ribeiro Junior, Guilherme Ferreira Gomes. Motor fault classification using hybrid short-time Fourier transform and wavelet transform with vibration signal and convolutional neural network. Journal of the Brazilian Society of Mechanical Sciences and Engineering, 2024, vol. 6, p. 46.

5 Qiushi Wang, Zhicheng Sun, Yueming Zhu, Chunhe Song. Intelligent fault diagnosis algorithm of rolling bearing based on optimization algorithm fusion convolutional neural network. Mathematical Biosciences & Engineering, 2023, vol. 11, pp. 63–82.

6 Renjie Wang, Ningyuan Yu, Bin An. Research on Power Equipment Fault Diagnosis Based on Improved SVM Algorithm. Journal of Electrical Systems, 2024, vol. 5, pp. 112–125.

7 Tian Y., Liu X. A Deep Adaptive Learning Method for Rolling Bearing Fault Diagnosis Using Immunity. Tsinghua Science and Technology, 2019, vol. 24, no. 6, pp. 1–14.

8 Sahu S., Kumar P.B., Parhi D.R. Analysis of hybrid CSA-DEA method for fault detection of cracked structures. Journal of Theoretical and Applied Mechanics, 2019, vol. 57, no. 2, pp. 369–382.

9 Pinto C., Pinto R., Gonçalves G. Towards. Bio-Inspired Anomaly Detection Using the Cursory Dendritic Cell Algorithm. Algorithms, 2022, vol. 15, no. 1, pp. 1–28.

10 Xiaochen Zhang, Chen Wang, Wei Zhou, Jiajia Xu. Trustworthy Diagnostics With Out-of-Distribution Detection: A Novel Max-Consistency and Min-Similarity Guided Deep Ensembles for Uncertainty Estimation. IEEE Internet of Things Journal, 2024, vol. 1.1, pp. 99–120.

11 Meng Wang, Jiong Yu, Hongyong Leng, Xusheng Du. Bearing fault detection by using graph autoencoder and ensemble learningю Scientific Reports, 2024, vol.14, no. 1.

12 Weihua Li, Jingke He, Huibin Lin, Ruyi Huang. A LightGBM-based Multi-scale Weighted Ensemble Model for Few-shot Fault Diagnosis. IEEE Transactions on Instrumentation and Measurementm, 2023, vol. 1, p. 99.

13 Arnaud Nanfak, Charles Hubert Kom, Samuel Eke. Hybrid Method for Power Transformers Faults Diagnosis Based on Ensemble Bagged Tree Classification and Training Subsets Using Rogers and Gouda Ratios. International Journal of Intelligent Engineering and Systems, 2022, vol. 5, pp. 12–24.

14 Zhiyuan Chen, Olugbenro. O. Selere, Nicholas Lu Chee Seng. Equipment Failure Analysis for Oil and Gas Industry with an Ensemble Predictive Model. Proceedings of the 9th International Conference on Computational Science and Technology, 2023, pp. 569–581.

15 Hezla L., Gurina R., Hezla M., Rezaeian N. The Role of Artificial Intelligence in Improving Failure Mode and Effects Analysis (FMEA) Efficiency in Construction Safety Management. AI Technologies and Virtual Reality, 2024, pp. 397–411.

16 Podoplelova E.S., Knyazev I.I. Modification of the fmea method using machine learning algorithms. Izvestiya SFedU engineering sciences, 2023.

17 Jiao J., Zhao M., Lin J. and Ding C. Deep Coupled Dense Convolutional Network With Complementary Data for Intelligent Fault Diagnosis. IEEE Trans. Ind. Electron, 2019, vol. 6, pp. 92–98.

18 Lei Y., Jia F., Lin J., Xing S. and Ding S.X. An Intelligent Fault Diagnosis Method Using Unsupervised Feature Learning Towards Mechanical Big Data. IEEE Trans. Ind. Electron., 2019, p. 78.

19 Dimitar P. Filev, Ratna Babu Chinnam, Finn Tseng and Pundarikaksha Baruah. An Industrial Strength Novelty Detection Framework for Autonomous Equipment Monitoring and Diagnostics. IEEE Transactions on Industrial Informatics, 2010, vol. 4, pp. 61–78.

20 Venkatasubramanian V., Rengaswamy R., Yin K. and Kavuri S.N. A review of process fault detection and diagnosis: Part I: Quantitative model-based methods. Computers & Chemical Engineering, 2003, vol. 27, no. 9, pp. 293–311.

21 Hwang I., Kim S., Kim Y. and Seah C.E. A Survey of Fault Detection, Isolation, and Reconfiguration Methods. IEEE Transactions on Control Systems Technology, 2010, vol.18, no. 3, pp. 636–653.

22 Lei Y., Lin J., He Z. and Zuo M.J. Condition monitoring and fault diagnosis of planetary gearboxes: A review. Measurement journal, 2014, vol.35, pp. 108–126.

23 Henriquez P., Alonso J.B., Ferrer M.A. and Travieso C.M. Automatic Fault Diagnosis Systems Using Audio and Vibration Signals. IEEE Transactions on Systems, Man, and Cybernetics: Systems, 2012, vol. 5, pp. 642–652.

24 Yan R., Gao R.X. and Chen X. Non-stationary signal processing for bearing health monitoring. Signal Processing, 2014, vol. 1.

25 Venkatasubramanian V., Rengaswamy R., Kavuri S.N. and Yin K. A review of process fault detection and diagnosis. Compuers & chemical engineering, Part III: Process history based methods, 2003, pp. 327–346.

26 Yin S., Ding S.X., Xie X. and Luo H. A Review on Basic Data-Driven Approaches for Industrial Process Monitoring. IEEE Transactions on Industrial Electronic, 2014, vol. 11, pp. 6418–6428.

27 Ding S.X. A comparison study of basic data-driven fault diagnosis and process monitoring methods on the benchmark Tennessee Eastman process. Journal of Process Control., 2014, vol. 24, no. 2, pp. 431–449.

28 Gao Z., Cecati C. and Ding S.X. Fault Diagnosis and Fault-Tolerant Techniques, Part I: Fault Diagnosis With Model-Based and Signal-Based Approaches. IEEE Transactions on Industrial Electronics, Part I, 2015, vol. 62, pp. 3757–3767.

29 Gao Z., Cecati C. and Ding S.X. Fault Diagnosis and Fault-Tolerant Techniques, Part II, IEEE Transactions on Industrial Electronics, 2015.

30 Evstifeev A.A. and Zaeva M.A. A hybrid teaching factory model towards personalized education. Method of Applying Fuzzy Situational Network to Assess the Risk of the Industrial Equipment Failure, 2021.

31 Mourtzis D., Angelopoulos J. and Panopoulos N., 2020, vol. 5, pp. 166–171.
32 Saeed Rajabi, Mehdi Saman Azari, Stefania Santini, and Francesco Flammini. Expert Systems with Applications, 2022.
33 Teerawat Thepmanee, Sawai Pongswatd, Farzin Asadi, and Prapart Ukakimaparn. Implementation of control and scada system: Energy Reports, 2022, vol. 8, pp. 934–941.
34 Dietterich T.G. Ensemble methods in machine learning. Multiple Classifier Systems, 2015, pp. 1–15.
35 Zhou Z.H. Ensemble Methods: Foundations and Algorithms. Chapman and Hall/CRC, 2012.
36 Kuncheva L.I. Combining Pattern Classifiers: Methods and Algorithms. John Wiley & Sons, 2014.
37 Rokach L. Ensemble-based classifiers. Artificial Intelligence Review, 2010, vol. 33, no. 1–2, pp. 1–39.
38 Kadi Mohamed, Amine Naim, Akkouche Naim, AkkoucheSary, Awad Sary and Awad Show., 2010.
39 Imran Rahman Pandian, Vasant Balbir, Singh Mahinder and Abdullah-Al-Wadud. Alexandria Engineering Journal, 2016.
40 Ponni Ponnusamy and Prabha Dhandayudam. Journal of Electrical Engineering and Technology journal, 2023.
41 Ali Aldrees, Hamad Hassan Awan, Arbab Faisal and Abdeliazim Mustafa Mohamed, Process Safety and Environmental Protection journal, 2022.
42 Sinem Bozkurt and Kemal Keskin, 2022.
43 Sriparna Saha and Asif Ekbal. Combining multiple classifiers using vote based classifier ensemble technique for named entity recognition. Data & Knowledge Engineering journal, 2018.

[1]Самигулина З.И.,
PhD, профессор, ORCID ID: 0000-0002-5862-6415,
e-mail: z.samigulina@kbtu.kz
[1]*Байкадамова С.С.
магистр, ORCID ID: 0009-0003-1734-8548,
e-mail: tassbulatova@gmail.com

[1]Қазақстан-Британ техникалық университеті, 050000, Алматы қ., Қазақстан

ДЕРЕКТЕРДІ ІРІКТЕУДІҢ ӨНДІРІСТІК ЖАБДЫҚТАРДЫ ДИАГНОСТИКАЛАУДАҒЫ ҮЛГІЛЕРДІ ТАНУ МІНДЕТІН ШЕШУГЕ ӘСЕРІ

Аңдатпа

Мақалада өнеркәсіптік жабдықты диагностикалау кезінде классификатордың болжамдық қабілетіне деректерді іріктеу әдістерінің әсері зерттеледі. Қарастырылған деректерді іріктеу әдістеріне қарапайым кездейсоқ таңдау, кластерлік таңдау және жүйелі таңдау жатады. Іріктеу әдістерінің нәтижелеріне сәйкес, бөлшектер тобын оңтайландыру және ансамбльдік үлгілерге (қаптау және дауыс беру түрлері) негізделген классификаторлар әзірленді. Нейрондық желі, градиентті күшейтілген ағаштар және Бейс үлгілері негізіндегі болжауды біріктіретін дауыс беру ансамбльдік модельдеу стратегиясы ең үздік нәтижені көрсетті. Ең жоғары дәлдікке нейрондық желі, градиентті күшейтілген ағаштар және аңғал Бейс үлгілері негізіндегі болжауды біріктіретін дауыс беру ансамбльдік модельдеу стратегиясы мен деректерді жүйелі таңдау әдісін қолдану арқылы қол жеткізілді: дәлдік (accuracy) 93,6%; классификация қателігі (classification error) 8%; еске түсіру (recall) 94,32%; дәлдік (precision) 93,87%. Соңғы кезеңде, деректерді іріктеу негізінде жабдықты диагностикалаудың ең тиімді стратегиясы мен ансамбльдік модель үлкен деректермен жұмыс істеуге бейімделген жақсартылған нұсқаны әзірлеу мақсатында FMEA (Failure Mode and Effects Analysis) технологиясына енгізілді.

Тірек сөздер: диагностикалық жүйе, мәліметтерді іріктеу, қарапайым кездейсоқ іріктеу, кластерлік таңдау, жүйелі таңдау, бөлшектер тобын оңтайландыру, ансамбль әдістері, FMEA жақсартылған технологиясы.

[1]Самигулина З.И.,
PhD, профессор, ORCID ID: 0000-0002-5862-6415,
e-mail: z.samigulina@kbtu.kz
[1]*Байкадамова С.С.,
магистр, ORCID ID: 0009-0003-1734-8548,
e-mail: tassbulatova@gmail.com

[1]Казахстанско-Британский технический университет, 050000, г. Алматы, Казахстан

ВЛИЯНИЕ ВЫБОРКИ ДАННЫХ НА РЕШЕНИЕ ЗАДАЧИ РАСПОЗНАВАНИЯ ОБРАЗОВ ДЛЯ ДИАГНОСТИКИ ПРОМЫШЛЕННОГО ОБОРУДОВАНИЯ

Аннотация

Статья посвящена исследованию влияния выборки данных на прогностическую способность классификатора при диагностике промышленного оборудования. Рассматривались различные типы выборок данных, такие как простая случайная выборка, кластерная и систематизированная выборка. По результатам различных выборок данных были построены классификаторы на основе методов роя частиц и ансамблевых моделей (бэггинг и тип с голосованием). Наилучшие результаты показала стратегия ансамблевого моделирования с голосованием, которая сочетает в себе прогнозирование на основе нейронной сети, деревьев с градиентным усилением и наивных Байесовских моделей. Наилучшие результаты были достигнуты с использованием систематического метода выборки данных и стратегии ансамблевого моделирования с голосованием, которая сочетает в себе прогнозирование на основе нейронной сети, деревьев с градиентным усилением и наивных моделей Байеса: accuracy 93,6%; classification error 8%; recall 94,32%; precision 93,87%. Полученная лучшая стратегия диагностики оборудования на основе выборки данных и ансамблевой модели была использована для реализации в технологии FMEA (Failure Mode and Effects Analysis) с целью получения улучшенной и адаптированной версии для работы с большими данными.

Ключевые слова: диагностика промышленного оборудования, выборка данных, простая случайная выборка, кластерная выборка, систематическая выборка, оптимизация роя частиц, ансамблевые методы, улучшенная модель FMEA.

Article submission date: 02.04.2024.

UDC 811.93
IRSTI 28.23.37

https://doi.org/10.55452/1998-6688-2024-21-3-116-127

[1,2 *]Alimbekova N.,
PhD student, ORCID ID: 0000-0002-8939-8806,
e-mail: nazakhatovna@gmail.com
[3]Hashim Sh.,
PhD, professor, ORCID ID: 0000-0002-4436-897X
e-mail: sjh@upm.edu.my
[1,4]Zhumadillayeva A.,
Candidate of Technical Sciences, associate professor, ORCID ID: 0000-0003-1042-0415
e-mail: zhumadillayeva_ak@enu.kz
[4]Aiymbay S.,
Master of Technical Sciences, ORCID ID: 0000-0002-2363-911X,
e-mail: sungat.aktau@gmail.com

[1]L.N. Gumilyov Eurasian National University, 010008, Astana, Kazakhstan
[2]Astana International University, 010000, Astana, Kazakhstan
[3] Putra Malaysia University, Kuala-Lumpur, Malaysia
[4]Astana IT University, 010000, Astana, Kazakhstan

DEEP NEURAL NETWORKS AS A TOOL FOR ENHANCING THE EFFICIENCY OF PLASTIC WASTE SORTING

Abstract

In the recycling industry, there is an urgent need for high-quality sorted material. The problems of sorting centers related to the difficulties of sorting and cleaning plastic leads to the accumulation of waste in landfills instead of recycling, emphasizing the need to develop effective automated sorting methods. This study proposes an intelligent plastic classification model developed on the basis of a convolutional neural network (CNN) using architectures such as MobileNet, ResNet and EfficientNet. The models were trained on a dataset of more than 4,000 images distributed across five categories of plastic. Among the tested architectures, proposed EfficientNet-SED demonstrated the highest classification accuracy – 99.1%, which corresponds to the results of previous research in this area. These findings highlight the potential of using advanced CNN architectures to improve the efficiency of plastic recycling processes.

Key words: plastic sorting, classification, dataset, deep learning, convolutional neural network (CNN).

Introduction

Sorting garbage, including plastic bottles, and their subsequent recycling are of great importance for Kazakhstan and other countries in the context of sustainable development and environmental protection. Plastic bottles are one of the main sources of plastic waste, which can have a serious impact on nature and living organisms. Micro-plastic and nano-plastic particles penetrate the food chain of animals and humans. Proper sorting and recycling of plastic bottles helps to reduce environmental pollution and conserve natural resources.

There is a need to develop intelligent systems capable of efficiently sorting plastic waste. Current plastic sorting methods face a number of problems, such as low classification accuracy, dependence on the human factor and high operating costs. It is important to create a system that can automatically classify various types of plastic, determine their condition (by type, shape, color, and the presence of residues inside the bottle) and direct waste to appropriate recycling. Solving this

problem will improve the efficiency of the recycling process and reduce the likelihood of errors, which is extremely important in the context of growing volumes of plastic waste and the need for sustainable development.

Literature Review

In Kazakhstan, plastic recycling is being tested, but much work remains to be done to increase the level of sorting. Each year, Kazakhstan produces 4.3–5 million tons of solid household waste. The share of recycled and disposed solid waste in 2022 was 25.41%, and only 20% of this amount is plastic waste [1]. Plastic is sorted in major cities and regional centers and processed at factories in Shymkent and Zhanaozen, as well as at small and medium-sized businesses. The government is encouraging plastic collection and recycling by introducing extended obligations for manufacturers. The Ministry of Ecology and Natural Resources of the Republic of Kazakhstan is also implementing the concept of Kazakhstan's transition to a green economy.

Assessing the environmental impact of automated plastic waste sorting systems is critical to assessing their sustainability. Life cycle assessment (LCA) of plastic products was carried out to analyze the overall environmental impact [2,3,4].

There are numerous examples of research on the sorting and classification of plastic wastes using NIR spectroscopy and a hyperspectral visualization system, including optical sorting, magnetic separation and other methods.

NIR spectroscopy has been extensively applied in the field of waste management, particularly for sorting plastic materials. Masoumi et al. (2012) investigated the identification and classification of plastic resins using near-infrared reflectance spectroscopy. Their study highlighted the technology's precision in distinguishing various plastic resins, facilitating more accurate and efficient sorting in recycling operations [5].

Similarly, Wu et al. (2020) demonstrated the effectiveness of NIR spectroscopy in auto-sorting commonly recovered plastics from waste household appliances and electronics. Their research provided significant insights into the application of NIR technology in identifying and separating different plastic polymers, which is crucial for recycling processes [6].

The advancement in hyperspectral imaging systems has further revolutionized the sorting of plastic waste. Zheng et al. (2018) developed a discrimination model using NIR hyperspectral imaging to sort waste plastics. This system proved to be effective in accurately identifying and classifying different types of plastic materials, showcasing the potential of hyperspectral imaging in enhancing waste management practices [7].

The integration of hyperspectral imaging with machine learning algorithms has also been explored to improve the sorting accuracy of plastic waste. Zhu et al. (2019) introduced a plastic solid waste identification system that combines near-infrared spectroscopy with support vector machine algorithms, indicating a significant improvement in the identification and classification of plastic materials [8].

With the development of deep learning and computer vision, more accurate and faster methods for recognizing and classifying objects based on images have become possible, making machine learning an ideal tool for automating the sorting of plastic waste. Carrera et al. (2022) focus on the application of machine learning algorithms such as neural networks, the support vector machine and deep learning algorithms for the recognition and classification of plastic materials. These studies emphasize the importance of selecting suitable features for model training and developing effective classification algorithms. [9].

Machine learning algorithms play a vital role in automating the sorting process by classifying plastic materials based on their composition, color and shape. Choi et al. (2023) uses deep learning models such as convolutional neural networks (CNN) and recurrent neural networks (RNN), have demonstrated exceptional performance in image recognition and classification tasks [10].

Problems in the automated sorting of plastic waste persist. These challenges include the diversity of plastic materials, the limitations of real-time processing, and the need for reliable algorithms to handle different waste streams. Abdallah et al. (2022) proposed innovative solutions, such as ensemble learning methods and transfer learning, to improve the adaptability and accuracy of machine learning models in real-world sorting scenarios [11].

Recent studies, such as by Kumar et al. (2021), explore deep learning approaches for waste segregation, notably using the YOLOv3 algorithm within the Darknet framework. This method, tailored for object classification, has shown effectiveness in classifying various waste types, including plastics. Deep learning, especially convolutional neural networks (CNNs), alongside techniques like Support Vector Machines (SVM) and Multilayer Perceptrons (MLP), are increasingly applied in waste management for their accuracy in classifying and segregating waste materials [12]

The research conducted by Bobulski and Kubanek (2021) introduces an advanced classification system for plastic waste, utilizing deep learning methodologies, with an emphasis on the development and evaluation of models capable of identifying various categories of plastic [13]. Their work utilized several deep neural network architectures (AlexNET, MobileNET) to achieve good classification accuracy (comparing across epoch), but in alignment with other studies [14, 15], their focus was aimed at the classification relevant to specific types of plastic materials (PET, PP, PS etc.). Furthermore, these models were additionally employed to identify various categories of municipal solid waste (MSW), including plastics, glass, metals, or alternative refuse [16, 17].

In our study, we conduct a deeper analysis of the application of deep neural network architectures to classify plastic bottles with different levels of residual contamination, including dairy and chemical liquid bottles. The main goal of our work is to improve sorting processes in real-world settings, where plastic waste often contains contamination. This makes the classification task more complex and important for ensuring an efficient recycling process.

Material and methods

In this study, we compared the architectures of deep convolutional neural networks: MobileNet_0.35, ResNet-34, and EfficientNet-B1/SED. These architectures were chosen as a backbone and due to their proven effectiveness in computer vision and image classification tasks, as their performance and ability to identify the most suitable architecture are key for automated plastic sorting.

MobileNet

In the research work of Howard et al. (2017), MobileNet is described as an efficient architecture for mobile devices that uses deep-separated strands and width multipliers to optimize computing resources, providing a balance between accuracy and efficiency, making it suitable for computer vision applications in computing power-limited environments [18].

MobileNet_0.35, a variant of the MobileNet architecture, is designed to operate with a reduced width multiplier of 0.35. This model maintains the use of depthwise separable convolutions, which significantly decrease the number of parameters and computational cost. The architecture starts with an initial full convolutional layer followed by a series of depthwise separable convolutional blocks. Each block comprises a depthwise convolution layer for filtering input channels independently, followed by a pointwise convolution that combines these channels. The stride is adjusted in certain blocks to reduce spatial dimensions, facilitating a reduction in computational load. The architecture concludes with global average pooling and a fully connected layer, terminating with a softmax activation function for classification.

ResNet

In the paper, He et al. (2016) first described the concept of residual blocks and ResNet architecture, which enables deep neural networks with hundreds of layers to be trained, solving the problem of disappearing gradients. The ResNet-34 architecture is notable for its ability to transmit information

directly through skip connections, improving learning and providing high accuracy in computer vision tasks [19].

ResNet-34, part of the Residual Network family, is a deep CNN characterized by its use of residual blocks. These blocks incorporate skip connections that enable the direct flow of gradients, effectively addressing the vanishing gradient problem in deep networks. The architecture commences with a large kernel-sized convolutional layer, followed by a max-pooling layer to decrease dimensionality early in the network. The bulk of the network comprises residual blocks with two convolutional layers each, interspersed with batch normalization and ReLU activations. As the network progresses, the number of filters doubles, and the feature map size is halved, providing a pyramidal structure. The final stages include an average pooling layer leading to a dense layer that produces the output via softmax.

EfficientNet

EfficientNet-B0, described in Tan and Le (2019), implements composite scaling, optimizing network depth, width and resolution. This provides high efficiency and accuracy, making B0 fundamental for subsequent EfficientNet models and showing the way to improving the performance of deep neural networks [20].

EfficientNet-B1 is an optimized version of the base model, EfficientNet-B0, which is scaled using a compound coefficient to balance the dimensions of network width, depth, and resolution. The architecture employs MBConv blocks, an advanced version of inverted residual blocks with squeeze-and-excitation optimization, which recalibrates the feature maps adaptively. Unlike other architectures, EfficientNet applies a systematic approach to scaling all dimensions of the network. The B1 model enhances the baseline design with increased depth and width, alongside a higher resolution, leading to improvements in accuracy. The concluding layers of the network resemble traditional CNNs with global average pooling followed by a fully connected layer and softmax activation




Figure 1 – CNN Architecture

EfficientNet-SED

We investigated three well-known models MobileNet, ResNet, and EfficientNet to assess the success of several backbone architectures for our aim. By means of layer and block experimentation, we created EfficientNet-SED, a new design based on EfficientNet. Following the backbone choice, we included Generalized Average Pooling (GA pooling) and Squeeze-and-Excitation (SE) blocks to improve feature representation. Dropout was used at each layer to provide robust generalization and avoid overfitting. A Fully Connected (FC) layer finishes the network design and allows softmax activation function to enable categorization (Fig. 1). Combining modern pooling and excitation methods with the strengths of every backbone, this methodical approach maximizes the model for higher accuracy and performance.

Data collection

For the purposes of the study, a specialized dataset of images of plastic waste was selected, available on the Kaggle platform called "Bottle Plastic Waste" with 80% for train set and 20% for test set and 200 images were additionally collected manually for the test set. This dataset includes a variety of plastic images, including bottles with contamination from both dairy and chemical (Table 1).

In the process of collecting the database, it was necessary to include several different classifications. The main type of most recyclable plastic in demand today is polyethylene terephthalate (PET) bottles. In order to become a secondary product, plastics undergo several stages of differentiation processes in sorting centers. Among them, plastic is distinguished from general waste products, and then sorted by type of plastic and the level of harmful waste. To obtain a high-quality secondary plastic product, it is necessary to have a bright/transparent color. If the bottle is of a dark color, used for dairy products, used for household chemicals, etc., then it is in the category that the bottle is not suitable for recycling.

Table 1 – Illustration of sample images with their respective class

				
Class1: Bottle transparent & clean	Class2: Bottle Dark color	Class3: Bottle from dairy and oil products	Class4:Bottle from Chemical products	Class5:Bottle from harmful contamination

According to the above classification, cameras, special visual sensors, mobile devices with cameras are used to obtain images of plastic waste. Visual data is collected to classify plastic waste using machine learning models.

Table 2 – Description and statistics of Bottle images in the dataset

Class (Type)	Items	*Recyclable	Quantity
Class 1 (PET)	Clean and empty bottles from different brands	+	1,512
Class 2 (PET)	Colored bottles (black, brown, dark purple, etc)	-	805
Class 3 (PET, PP, HDPE)	Bottles from milk products and oil, souse, etc	-	634
Class 4 (PET, PP, HDPE, PVC, LDPE)	Bottles from household chemical products (shampoo, gel, medical containers, etc)	-	630
Class 5 (PET)	PET bottles, but used for storing hazardous liquid (gasoline, antifreezes, domestos, etc)	-	452

***Recyclable.** In fact, all the plastics shown in the table are recyclable. However, there are some problems with collection. It is not profitable for dedicated sorting centers to collect other types of plastic and non-ferrous, dairy and contaminated products, since factories accept large volumes of tons for the production of secondary products. Another reason has to do with the quality of the plastic and, obviously, the price of it. In this regard, it is important to separate PET plastics (class 1) from other plastics (classes 2, 3, 4, 5).

Pre-processing

The following pre-processing process was performed before training the models:

Data normalization. All images were scaled to a single standard size corresponding to the input size of the neural network. Further, the pixel values of each image were adjusted to the range [0.1], which is standard practice to improve learning convergence [21].

$$\text{Normalized Pixel Value} = \frac{\text{Pixel Value}}{255} \quad (1)$$

In addition to scaling pixel values, standardization of data was applied, where the average of each pixel of the image is subtracted from the whole data set and the result is divided into a standard deviation.

$$\text{Standardized Pixel Value} = \frac{\text{Pixel Value} - \mu}{\sigma} \quad (2)$$

where μ is the average pixel value over the dataset, σ is the standard deviation of the pixel over the dataset.

Data augmentation was used to increase the amount of data and improve the generalizing ability of models. This included random image transformations such as rotations, offsets, scaling, and horizontal reflections [22].

The data were divided into training, validation and test samples in standard proportions, allowing the model to be evaluated with unprecedented data and avoiding retraining.

The given methodology of preliminary data processing creates equal conditions for comparison of performance of studied architectures of neural networks, providing accuracy and objectivity of experimental analysis.

The training process

Images are split so that 20% of each class is used for testing. The training process involved the use of stochastic gradient descent (SGD) with an initial learning rate of 0.01, which decreased by an order of magnitude after every two epochs. The training took place over 7 epochs with a package size of 32 samples. Categorical cross-entropy (formula 3) with the addition of L2 regularization with a coefficient of 0.0001 was used as a loss function to prevent overfitting. Data augmentation was applied on the fly using random horizontal reflection and random cropping of images. Dropout was applied with a probability of 0.5 before the last fully connected layer.

$$CE = -\sum_i^C t_i log(s_i) \quad (3)$$

where:

C – the number of classes;

t_i – the true label, encoded as a one-hot vector (i.e., $t_i=1$ if the true class is *i,* otherwise $t_i=0$);

s_i – the predicted probability of the class *i,* output by the model.

Evaluation metrics

The following metrics were used to evaluate the performance of the models:

The accuracy of the model is calculated using formula (4), where for each sample in the test dataset, the predicted class is compared with the true one. The duration of the model training was recorded from the initiation to the completion of the training procedure, encompassing all epochs, while the duration of model inference was quantified as the mean processing time of a single sample from the testing dataset [23].

$$\text{Accuracy} = \frac{\text{Number of Correct Predictions}}{Total\ Number\ of\ Predictions} \quad (4)$$

The total number of model parameters P is calculated as the sum of the parameters of each layer (5) and calculated using the following formula:.

$$P = \sum_{i=1}^{L} (K_i C_{in,i} C_{out,i} + C_{out,i}) \quad (5)$$

where:

P – the total number of parameters,

I, – the total number of layers,

K_i – the kernel size of the package for the i-th layer,

$C_{in.i}$ – the number of input channels in the i-th layer,

$C_{out,i}$ – the number of output channels (or neurons) in the i-th layer.

This formula takes into account the parameters of convolutional layers and fully connected layers without taking into account offsets. To include offsets in the calculation, you just need to add $C_{out,i}$ for each layer to the total number of parameters.

To estimate the computational complexity, the FLOPs metric was used, which represents the total number of multiplication and addition operations required to perform one inference of the model [24].

$$FLOPs = \sum_{i=1}^{L} (2 K_i^2 C_{in,i} H_{out,i} W_{out,i} C_{out,i}) \quad (6)$$

where:

K_i^2– the size of the convolution core in layer *i*, squared, which indicates the number of weights in the filter,

$C_{in,i}$ – the number of input channels for the *i*-th layer,

$H_{out,i} W_{out,i}$– height and width of the output feature map of the *i*-th layer,

$C_{out,i}$ – the number of output channels for the *i*-th layer.

Results and discussion

The results are compared based on the metrics obtained to identify the advantages and disadvantages of each architecture. The analysis includes a discussion of how differences in the structure and complexity of models affect their performance and applicability in different scenarios.

Below is a comparative analysis of these three models and the result obtained where x axis shows number of epoch and y axis shows loss.




Figure 2 – Comparative analysis of training models

The results of evaluating the training process on the validation data set after seven epochs, providing data on the loss on the training set, loss on the validation set, the error rate and the time spent on each training epoch are shown in the Table 3. Changes in these metrics reflect the model's adaptation during training, highlighting variations in the algorithm's performance as it is optimized.

Train Loss is the average value of the loss function for all samples in the training dataset. For cross-entropy, which is often used for classification tasks, this is calculated as:

$$Train\ Loss = -\frac{1}{N}\sum_{i=1}^{N}\sum_{c=1}^{C} y_{i,c}\log(\hat{y}_{i,c})$$

where:

N – the number of samples in the training dataset.

C – number of classes.

$y_{i,c}$ – the true class c label for sample i.

$\hat{y}_{i,c}$ – predicted probability of class c for sample i.

Valid Loss is estimated in a similar way to Train Loss, but for a validation dataset:

$$Valid\ Loss = -\frac{1}{M}\sum_{i=1}^{M}\sum_{c=1}^{C} y_{i,c}\log(\hat{y}_{i,c})$$

where:

M – the number of samples in the validation dataset. The other designations are similar to Train Loss.

Error Rate is the proportion of incorrectly classified samples in a dataset:

$$Error\ Rate = -\frac{1}{N}\sum_{i=1}^{N}\mathbf{1}\,(\hat{y}_i \neq y_i)$$

where:

1 – an indicator function that is equal to 1 if the predicted class $\hat{y}_i$ does not match the true class y_i, and 0 otherwise;

N – the number of samples in the dataset (training or validation).

Table 3 – Results of training on validation set

Epoch	Train_loss	Valid_loss	Error_rate	Time
1	1.341781	0.431466	0.123658	00:58
2	0.658234	0.388225	0.145486	00:50
3	0.756324	0.441112	0.098811	00:48
4	0.635198	0.587563	0.140456	00:47
5	0.763405	0.775234	0.278936	00:47
6	0.775418	0.735139	0.2145763	00:47
7	0.603471	0.635423	0.103846	00:47

Table 3 demonstrates the training results of the model over seven epochs, highlighting key metrics such as training loss, validation loss, error rate and time spent per epoch.

Table 4 – Model performance comparison

Methodology	Model Performance (average acc.)
MobileNet_035	81,33%
ResNet-34	95,55%
EfficientNet-B1	98,5%
EfficientNet-SED	99,1%

Table 4 compares the performance of three deep convolutional neural network architectures as measured by the classification accuracy metric. The results show that the EfficientNet-B1 architecture achieves the highest accuracy of 98.5%, indicating its superiority in the context of classification task compared to others. These findings highlight differences in the performance of architectures and their suitability for specific computer vision applications.

Figure 3 shows the curves in training and validation accuracy for the suggested EfficientNet-SED model. The model showed a strong learning capacity over the training procedure based on the routinely high accuracy values. With a final training accuracy of 0.996 the model clearly learnt the patterns in the training data. With an outstanding value of 0.991, the validation accuracy also demonstrated the great generalizing capacity of the model to unmet data. These findings show how well the EfficientNet-SED design maximizes performance while preserving great accuracy on the validation and training sets.




Figure 3 – EfficientNet-SED results

Conclusion

The article analyzes the use of deep neural networks, especially convolutional neural networks (CNN), to improve the sorting of plastic waste, where traditional methods are ineffective, leading to the accumulation of waste in landfills. Tests on a database of more than 4,000 images of plastic waste showed that the EfficientNet-SED architecture achieved the highest accuracy of 99.1%, demonstrating its potential to optimize recycling processes. This study highlights the importance of using advanced CNN architectures to improve plastic sorting accuracy, which is key to environmental sustainability and efficient use of resources. The results of the work allow us to determine the most suitable architecture for computer vision tasks, offering a systematic comparison of models for an objective assessment of their effectiveness.

Although the algorithms used in the study are well known, the significance of our contribution lies in their adaptation and application to specific conditions of classification not only by types, but also by colors and different classes are shown in Table 2. The scientific novelty of the study is demonstrated in the comparison of the performance of different CNN architectures under conditions where plastics have different levels of contamination.

Future work

This work is a part of the main scientific project sponsored by the Science Committee of the MSHE of the RK, which is divided into 3 stages. The results presented in this paper focused on the use of a dataset of images captured by the camera. The next stage in the process is to analyze the spectral data of different types of plastic obtained using the NIR spectrometer, which will allow for more accurate classification into categories in the context of waste recycling. The third stage plans to use hyperspectral imaging technologies that will provide the ability to more accurately identify plastic bottles containing hazardous substances inside the bottles.

Information on funding

The research data was sponsored by the Science Committee of the Minister of Science and Higher Education of the Republic of Kazakhstan (Grant No.76 of the research fund AP22685518).

REFERENCES

1 Waste management. The official site of the Ministry of Ecology and Natural Resources of the Republic of Kazakhstan. Application date: 08.03.2024. [electronic resource] URL: https://www.gov.kz/memleket/entities/ecogeo/activities/14791?lang=ru&parentId=14790.

2 Mannheim V. Life Cycle Assessment Model of Plastic Products: Comparing Environmental Impacts for Different Scenarios in the Production Stage. Polymers 2021, vol. 13, p. 777. https://doi.org/10.3390/polym13050777.

3 Antonis Vlasopoulos, Jurgita Malinauskaite, Alina Żabnieńska-Góra, Hussam Jouhara. Life cycle assessment of plastic waste and energy recovery. Energy, 2023, vol. 277, p. 127576. ISSN 0360-5442, https://doi.org/10.1016/j.energy.2023.127576.

4 Powerful optical sorting technologies, artificial intelligence and robotics reduce contamination for recycling operations. [electronic resources]. URL: https://www.recyclingproductnews.com/article/34294/powerful-optical-sorting-technologies-artificial-intelligence-and-robotics-reduce-contamination-for-recycling-operations.

5 Masoumi H., Safavi S.M., & Khani Z. Identification and classification of plastic resins using near infrared reflectance spectroscopy. International Journal of Mechanical and Industrial Engineering, 2012, no 6, pp. 213–220.

6 Wu X., Li J., Yao L., & Xu Z. Auto-sorting commonly recovered plastics from waste household appliances and electronics using near-infrared spectroscopy. Journal of Cleaner Production, 2020, 246, p. 118732. https://doi.org/10.1016/j.jclepro.2019.118732.

7 Zheng Y., Bai J., Xu J., Li X., & Zhang Y. A discrimination model in waste plastics sorting using NIR hyperspectral imaging system. Waste Management, 2018, no. 72, pp. 87–98. https://doi.org/10.1016/j.wasman.2017.10.015.

8 Zhu S., Chen H., Wang M., Guo X., Lei Y., & Jin G. Plastic solid waste identification system based on near infrared spectroscopy in combination with support vector machine. Advanced Industrial and Engineering Polymer Research, 2019, vol. 2, pp. 77–81.

9 Carrera B., Pinol V.L., Mata J.B., & Kim K. A machine learning based classification models for plastic recycling using different wavelength range spectrums. Journal of Cleaner Production, 2022, vol. 374, p. 133883.

10 Choi J., Lim B., & Yoo Y. Advancing plastic waste classification and recycling efficiency: Integrating image sensors and deep learning algorithms. Applied Sciences, 2023, vol. 13, no. 18, p. 10224. https://doi.org/10.3390/app131810224.

11 Abdallah N., Burhan R.H., Ali T., Alrehaili A., & Toqeer S. An ensemble learning based classification approach for the prediction of household solid waste generation. Sensors, 2022, vol. 22, no. 9, p. 3506. https://doi.org/10.3390/s22093506.

12 Kumar S., Yadav D., Gupta H., Verma O.P., Ansari I.A., & Ahn C.W. A novel YOLOv3 algorithm-based deep learning approach for waste segregation: Towards smart waste management. Electronics, 2021, vol. 10, no. 1, p. 14. https://doi.org/10.3390/electronics10010014.

13 Bobulski J., & Kubanek M. Deep learning for plastic waste classification system. Applied Computational Intelligence and Soft Computing, 2021, Article ID 6626948. https://doi.org/10.1155/2021/6626948.

14 Chowdhury S.S., Hossain N.B., Saha T., Ferdous J., & Zishan M.S.R. The design and implementation of an autonomous waste sorting machine using machine learning technique. AJSE, 2021, vol. 19, no. 3, pp. 134–142. https://doi.org/10.53799/ajse.v19i3.104.

15 Olowolayemo A., Ahmad Radzi N.I., & Ismail N.F. Classifying Plastic Waste Using Deep Convolutional Neural Networks for Efficient Plastic Waste Management. International Journal on Perceptive and Cognitive Computing, 2022, vol. 8, no. 2, pp. 6–15. Retrieved from https://journals.iium.edu.my/kict/index.php/IJPCC/article/view/282.

16 Cheema S.M., Hannan A., & Pires I.M. Smart waste management and classification systems using cutting edge approach. Sustainability, 2022, vol. 14, no. 16, p.10226. https://doi.org/10.3390/su141610226.

17 Ziouzios D., Baras N., Balafas V., Dasygenis M., & Stimoniaris A. Intelligent and real-time detection and classification algorithm for recycled materials using convolutional neural networks. Recycling, 2022, vol. 7, no. 1, p. 9. https://doi.org/10.3390/recycling7010009.

18 Howard A.G., Zhu M., Chen B., Kalenichenko D., Wang W., Weyand T., Andreetto M., & Adam H. MobileNets: Efficient convolutional networks for mobile vision applications. arXiv:1704.04861, 2017.

19 He K., Zhang X., Ren S., & Sun J. Deep residual learning for image recognition. In Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2016.

20 Tan M., & Le Q.V. EfficientNet: Rethinking model scaling for convolutional neural networks. In Proceedings of the 36th International Conference on Machine Learning, 2019, vol. 97, pp. 6105–6114.

21 Patrizi A., Gambosi G. & Zanzotto F.M. Data Augmentation Using Background Replacement for Automated Sorting of Littered Waste. J. Imaging, 2021, vol. 7, p. 144. https://doi.org/10.3390/jimaging7080144.

22 Sunardi, Yudhana A., & Fahmi M. Improving waste classification using convolutional neural networks: An application of machine learning for effective environmental management. Revue d'Intelligence Artificielle, 2023, vol. 37, no. 4, pp. 845–855. https://doi.org/10.18280/ria.370404.

23 Cai Z., Yang J., Fang H., Ji T., Hu Y. & Wang X. Research on Waste Plastics Classification Method Based on Multi-Scale Feature Fusion. Sensors. 2022, vol. 22, no. 20, p. 7974. https://doi.org/10.3390/s22207974.

24 Zheng D., Wang R., Duan Y., Pang Ch.P. & Pan T. Focus-RCNet: a lightweight recyclable waste classification algorithm based on focus and knowledge distillation. Vis. Comput. Ind. Biomed. 2023, Art 6, 19. https://doi.org/10.1186/s42492-023-00146-3.

[1,2*]Алимбекова Н.,
докторант, ORCID ID: 0000-0002-8939-8806,
e-mail: nazakhatovna@gmail.com
[3] Хашим Ш.,
PhD, профессор, ORCID ID: 0000-0002-4436-897X,
e-mail: sjh@upm.edu.my
[1]Жумадиллаева А.,
т.ғ.к., доцент, ORCID ID: 0000-0003-1042-0415,
e-mail: zhumadillayeva_ak@enu.kz
[4]Айымбай С.,
т.ғ.м., ORCID ID: 0000-0002-2363-911X,
e-mail: sungat.aktau@gmail.com

[1]Л.Н. Гумилев атындағы Еуразия ұлттық университеті, 010008, Астана қ., Қазақстан
[2]Астана халықаралық университеті, 010000, Астана қ., Қазақстан
[3]Путра Малайзия университеті, Куала-Лумпур қ., Малайзия
[4]Астана IT университеті, 010000, Астана қ., Қазақстан

ТЕРЕҢ НЕЙРОНДЫҚ ЖЕЛІЛЕР ПЛАСТИКАЛЫҚ ҚАЛДЫҚТАРДЫ СҰРЫПТАУ ТИІМДІЛІГІН АРТТЫРУ ҚҰРАЛЫ РЕТІНДЕ

Аңдатпа

Қайта өңдеу өнеркәсібінде сапалы сұрыпталған материалға шұғыл қажеттілік туындауда. Сұрыптау орталықтарының мәселесі ретінде пластмассаны сұрыптау және тазалау қиындықтарына байланысты

қалдықтар, қайта өңдеудің орнына полигондарда жиналуда. Бұл тиімді автоматтандырылған сұрыптау әдістерін дамыту қажеттілігін көрсетеді. Осы зерттеу жұмысы MobileNet, ResNet және EfficientNet сияқты архитектураларды қолдана отырып, конволюциялық нейрондық желіге (CNN) негізделген пластмассаларды жіктеудің интеллектуалды моделін ұсынады. Модельдер пластиктің бес санатына бөлінген 4000-нан астам кескіннен тұратын деректер жиынтығында оқытылды. Сыналған архитектуралардың ішінде EfficientNet-SED классификацияның ең жоғары дәлдігін көрсетті – 99,1%, бұл осы саладағы алдыңғы зерттеулердің нәтижелеріне сәйкес келеді. Бұл нәтижелер пластикті қайта өңдеу процестерінің тиімділігін арттыру үшін жетілдірілген CNN архитектураларын пайдалану әлеуетін көрсетеді.

Тірек сөздер: пластикалық сұрыптау, класификация, мәліметтер қоры, терең оқыту, конволюциялық нейрондық желі (CNN).

[1,2*]**Алимбекова Н.,**
докторант, ORCID ID: 0000-0002-8939-8806,
e-mail: nazakhatovna@gmail.com
[3]**Хашим Ш.,**
PhD, профессор, ORCID ID: 0000-0002-4436-897X,
e-mail: sjh@upm.edu.my
[1]**Жумадиллаева А.,**
к.т.н,, доцент, ORCID ID: 0000-0003-1042-0415,
e-mail: zhumadillayeva_ak@enu.kz
[4]**Айымбай С.,**
м.т.н., ORCID ID: 0000-0002-2363-911X,
e-mail: sungat.aktau@gmail.com

[1]Евразийский национальный университет им. Л.Н. Гумилева, 010008, г. Астана, Казахстан
[2]Международный университет Астана, 010000, г. Астана, Казахстан
[3]Университет Путра Малайзия, Куала-Лумпур, Малайзия
[4]Astana IT University, 010000, г. Астана, Казахстан

ГЛУБОКИЕ НЕЙРОННЫЕ СЕТИ КАК ИНСТРУМЕНТ ПОВЫШЕНИЯ ЭФФЕКТИВНОСТИ СОРТИРОВКИ ПЛАСТИКОВЫХ ОТХОДОВ

Аннотация

В индустрии вторсырья наблюдается острая потребность в качественном сортированном материале. Проблематика сортировочных центров, связанная с трудностями сортировки и очистки пластика, приводит к накоплению отходов на свалках вместо их переработки, подчеркивая необходимость развития эффективных автоматизированных методов сортировки. В этом исследовании предлагается интеллектуальная модель классификации пластиков, разработанная на основе сверточной нейронной сети (CNN) с использованием таких архитектур, как MobileNet, ResNet и EfficientNet. Модели были обучены на наборе данных, состоящем из более чем 4000 изображений, распределенных по пяти категориям пластика. Среди протестированных архитектур EfficientNet-SED продемонстрировала самую высокую точность классификации – 99,1%, что соответствует результатам предыдущих исследований в этой области. Эти результаты подчеркивают потенциал использования передовых архитектур CNN для повышения эффективности процессов переработки пластика.

Ключевые слова: пластиковая сортировка, классификация, набор данных, глубокое обучение, сверточная нейронная сеть (CNN).

Article submission date: 04.04.2024.

UDC 004.021
IRSTI 28.25.23

https://doi.org/10.55452/1998-6688-2024-21-3-128-136

[1]Amanov A.,
PhD student, ORCID ID: 0000-0002-7669-0656,
e-mail: alimzhan.amanov@gmail.com

[1]Kazakh-British Technical University,
050000, Almaty, Kazakhstan

COMPUTING THE DEGREE-4 INVARIANT POLYNOMIAL BASIS FOR 7 QUBITS

Abstract

Understanding the complexity of entangled states within the context of SLOCC (stochastic local operations and classical communications) involving several number qubits is essential for advancing our knowledge of quantum systems. This complexity is often analyzed by classifying the states via local symmetry groups. Practically, tthe resulting classes can be distinguished using invariant polynomials, but the size of these polynomials grows rapidly. Hence, it is crucial to obtain the smallest possible invariants. In this short note, we compute the basis of invariant polynomials of 7 qubits of degree 4, which are the smallest degree invariants. We obtain these polynomials using the representation theory and algebraic combinatorics.

Key words: invariant polynomials; quantum entanglement, SLOCC.

Introduction

Entanglement is a very important idea in quantum information theory, and it is necessary to understand and measure entanglement in quantum states [1]. It is considered a crucial part of quantum information, and it has become a major area of research [4, 5]. In recent years, polynomial functions that do not change under stochastic local operations and classical communication (SLOCC) have been studied a lot [2, 3, 12, 13, 14]. These functions are sometimes used to measure entanglement [13].

SLOCC is an important concept that helps classify entangled states by looking at how they can be changed using local operations and classical communication. This classification is important because it shows which quantum states can be changed into each other using local operations, helping us understand the basic structure of quantum entanglement and its importance for quantum information processing. In the SLOCC framework, the complexity of entangled states, especially in systems with d quantum units (qunits, with n states), is a key area of study. The main challenge is to efficiently categorize these states to understand their potential uses in different quantum information tasks.

This paper deals with the challenge of classifying entangled states under SLOCC for 7 parties, each having a single qubit. Similar job has being done by the author in [6] for 3 and 5 parties with qubits and qutrits. An improved method for deriving invariant polynomials of the smallest degrees were introduced, which is useful for efficiently identifying SLOCC classes of entangled quantum states [2, 3, 12, 13, 14, 15].

The theory beyond the introduced method was developed in [8, 9, 10, 11]. Using Schur-Weyl duality and representation theory of a symmetric group and general linear group, the spanning set of the space of invariant polynomials of fixed degree is obtained.

Apart from its fundamental significance, it is useful in the task of distinguishing the orbits of quantum states. That is, if two quantum states X and Y are given, if the evaluation of some invariant polynomial P on these states (tensors) is different, then it implies that X and Y are in different SLOCC orbits.

To address this problem, we reframe it within a mathematical framework. Quantum states are considered as elements of $V = \mathbb{C}^n \otimes \cdots \otimes \mathbb{C}^n$ (repeated d times) scaled to unit norm. With a fixed basis, each state is represented by a d-dimenisonal hypermatrix $\{A_{i_1 \ldots i_d}\}$. Stochastic local operations correspond to elements of the group $G = SL(n) \times \cdots \times \mathrm{SL(n)}$ (repeated d times), where each group instance independently acts on the corresponding tensor component via left multiplication. Here $SL(n)$ is the group of $n \times n$ matrices of a determinant 1. Consequently, SLOCC classes are exactly the orbits of a group action.

The polynomial P defined over the vector space V is considered G-invariant f it remains unchanged on the orbits of the G-action, i.e., $P(gv) = P(v)$. Distinguishing tensor orbits (state classes) can be achieved by assigning different evaluations to an invariant polynomial. Thus, creating such polynomials is a key task in quantum information theory.

In general, most tensor problems are NP-hard, as shown in [22], making it unrealistic to expect quick solutions to tensor-related problems.

Our primary contribution is the computation of the basis of degree 4 invariant polynomials of 7 qubits. This paper is continuation of the paper [6] where we did the similar job for $d = 3{,}5$ and $n = 2{,}3$. This problem is rooted in Computer Science, as it involves creating an algorithm based on the structure of the underlying tensor space. The techniques and results can also be utilized in other fields of computer science that use tensors, as they reveal the symmetries of a tensor space in relation to the natural group action. We provide the basis for invariant polynomials of degree 4 of 7 qubits.

Literature review

Invariant polynomials are essential for classifying quantum states. These polynomials allow for efficient characterization and measurement of entangled states' complexity under local operations and classical communications (SLOCC). This short review covers the foundational theories, practical uses, and computational techniques related to invariant polynomials, highlighting their importance in various fields of study.

The study of invariant polynomials trace back to Arthur Cayley [15, 16] in the middle of 19-th century. He introduced the combinatorial hyperdeterminant – simpliest generalization of the ordinary determinant for even d, which is also refferred to as Cayley's first hyperdeterminant. Later he also introduced Cayley's second hyperdeterminant $det_{2\times2\times2}$ which is $SL(2)^3$-invariant of $2 \times 2 \times 2$ hypermatrices of degree 4. Later, this invariant were generalized to so called geometric hyperdeterminant by Gelfand-Kapranov-Zelevinsky in their ground breaking paper [17]. Later on, many research were conducted on this matter. Bürgisser and Ikenmeyer [8] identified fundamental invariants and explored their role in orbit closures within algebraic geometry. Bürgisser et al. [9, 11] studied scaling algorithms and the null-cone problem from the perspective of invariant theory. Their work demonstrated the computational efficiency of these algorithms in determining invariant polynomials. Later, this work were developed in [10].

Luque and Thibon [2, 3], building on this foundation, extended the scope of polynomial invariants to systems with four and five qubits, see also [14]. Their research provided explicit descriptions and formulas for these invariants, aiding in the classification of more complex quantum states. By deriving these invariants, they enabled more efficient characterization of SLOCC classes, advancing the practical applications of these tools in quantum computing.

The foundational work by Dür, Vidal, and Cirac [1] identified different ways three qubits can be entangled, establishing a basis for understanding polynomial invariants in quantum systems. Their research uncovered two inequivalent classes of entangled states, each distinguished by different sets of polynomial invariants. This work underscored the role of local symmetry groups in classifying entangled states, a key aspect of quantum information theory. Miyake [7] extended the classification of multipartite entangled states by employing multidimensional determinants, closely related to

polynomial invariants. This approach allowed for a deeper understanding of entanglement in higher-dimensional quantum systems, connecting abstract mathematical theory with practical quantum computing applications. Maria [19] provided a fixed parameter tractable algorithm to compute quantum invariants of links presented by planar diagrams, including the Reshetikhin-Turaev invariants derived from simple Lie algebras. Neural networks and machine learning techniques were used to compute invariant polynomials in Haddadin [20]. Raith et al. [21] developed advanced visualization techniques for tensor fields using fiber surfaces of invariant spaces. This method enhances the visualization and interpretation of complex tensor fields, with practical applications in scientific visualization and data analysis.

Main provisions

A. Tensors and invariants

We denote $[2] = \{0,1\}$. Let $V = (\mathbb{C}^n)^{\otimes d}$ be the space of tensors (state space). Elements of V written in a fixed basis correspond to hypermatrices $\left(X_{i_1,\dots,i_d}\right)$ indexed by $(i_1, \dots, i_d) \in [\mathrm{n}] \times \dots \times [\mathrm{n}]$ and we shall usually identify tensors in V with corresponding hypermatrices.

The group $G = SL(n)^{\times d}$ naturally acts on the space of tensors $V = (\mathbb{C}^n)^{\otimes d}$ by

$$(g_1, \dots, g_d)v_1 \otimes \dots \otimes v_d = g_1 v_1 \otimes \dots \otimes g_d v_d \quad (1)$$

for $g_i \in SL(n), v_i \in \mathbb{C}^n$ and extended multilinearly. Let $PInv_d(n)$ be the ring of G-invariant polynomials that inputs elements of V. It is known [2, 3] that the degree of any polynomial in $PInv_d(n)$ is a multiple of n. By $PInv_d(n,k)$ we denote the homogeneous degree nk part of $PInv_d(n)$, which provide the grade decomposition:

$$\mathrm{PInv_d(n)} = \bigoplus_{k\geq 0} \mathrm{PInv}_d(\mathrm{n,k}). \quad (2)$$

The dimensions of the grades are counted by rectangular generalized Kronecker coefficients $g_d(n,k) := g(n \times k, \dots, n \times k)$ (repeated d times). The (generalized) Kronecker coefficients are structural constants of tensor products of irreducible symmetric group representations. It is the major problem to give a combinatorial interpretation for these numbers; this problem sometimes referred to as last open problem in algebraic combinatorics. Decision problem of positivity of Kronecker coefficients is known to lie in NP class.

In [10], the authors studied dimension sequences via Kronecker coefficients. it was obtained the lower bound for smallest k for which $\dim \mathrm{PInv}_d(\mathrm{n,k}) > 0$. Denote

$$\delta'_d(n) = min\{k \mid \dim PInv_d(n,k) > 0\}. \quad (3)$$

It is known, that $\delta'_d(n) = 1$ for even d and there is a unique polynomial invariant of that degree called Cayley's first hyperdeterminant [15, 16]. For odd d situation is completely different. The following theorem sheds light to odd d case. It is known, that for odd d:

$$\left\lceil n^{\frac{1}{d-1}} \right\rceil \leq \delta'_d(n) \leq n, \quad (4)$$

and this lower bound is sharp in certain cases, see [10]. By computing the Kronecker coefficients we know the dimensions of the grades by $g_d(n,k) = \dim PInv_d(n,k)$. See the figure in the results section for dimension sequences.

Our aim is to describe the minimal possible invariants. For that we require a few combinatorial definitions.

B. Magic sets and its signature function

Magic sets. We refer to elements of the box $[k]^d$ as $cells$. A $slice$ of $[k]^d$ is a subset consisting of all cells with a fixed i-th coordinate (referred to as the direction) for some i in $[d]$.

A $magic\ set$ is a subset of $[k]^d$ that has an equal number of elements in every slice of $[k]^d$, and this number is called its magnitude. A magic set T can be represented as a magic hypermatrix, with 1 at the cells corresponding to elements of T and 0 elsewhere. A magic hypermatrix is a natural generalization of (0,1)-magic squares. The set of all magic sets in $[k]^d$ with magnitude n is denoted as $B_d(n,k)$.




Figure 1 – Example of a magic set in 3x3x3 cube of magnitude 3

Each magic set T in $[k]^d$ of magnitude n and cardinality $m = nk$ can be represented as a $d \times m$ table with entries in $[n]$ as follows: iterate over the cell $I = (i_1, \dots, i_d)$ of $[k]^d$ in lexicographical order and add column I to the table whenever $T_{i_1,\dots,i_d} = 1$. We refer to the resulting table as the magic table T. For instance, for d=3 and k=3, assume $T_{000} = 1$, $T_{001} = 1$, $T_{110} = 1$, and $T_{111} = 1$, with zeros elsewhere. Then, the corresponding table is:

$$T = \begin{pmatrix} 0011 \\ 0011 \\ 0101 \end{pmatrix}. \quad (5)$$

We identify magic sets and their corresponding tables. Note that if T is in $B_d(n,k)$, then the corresponding magic table is of size d × nk, and each row consists of letters from [k], each appearing n times. Since $T_{i_1,\dots,i_d}$ is in {0,1}, the columns of the magic table do not repeat.

Signature function. For each magic set, let us introduce a 'filter' for (noncommutative) monomials involved in polynomials of $PInv_d(n)$ of degree nk. For the map $\sigma: [nk] \to [n]^d$, denote the monomial X_σ as the product $X_\sigma = \prod_{i=1}^{nk} X_{\sigma(i)}$. The map σ can also be regarded as a $d \times nk$ table, with the i-th column being $\sigma(i)$ and each row containing letters from [n], each appearing k times.

For the magic table $T \in B_d(n,k)$, define the sign function $sgn_T(\sigma) \in \{-1,0,1\}$ as follows: overlay table σ on table T and consider all symbols in table σ that lie in the same row and have the same underlying symbol from T. Denote the resulting sequence as $a = (a_1, \dots, a_n)$. If it forms a permutation, then $sgn_T(\sigma)$ is multiplied by the sign of this permutation; otherwise, set $sgn_T(\sigma)$ to 0.

For example, let s = 112231132, then

$$sgn_s(\mathbf{12}12\mathbf{13}4\mathbf{23}) = sgn(\mathbf{1234})sgn(12)sgn(12) = +1,$$

$$sgn_s(\mathbf{23}32\mathbf{1}4\mathbf{21}) = sgn(\mathbf{2314})sgn(321)sgn(12) = -1,$$

$$sgn_s(\mathbf{24}35\mathbf{1}4\mathbf{21}) = \underbrace{sgn(\mathbf{2414})sgn(351)}_{not\ permutations} sgn(12) = 0.$$

In other words, $sgn_T(\sigma)$ is determined by overlaying σ on T, where we expect each block of equal letters within the same row of T to be covered by a permutation, and the product of all signatures of the resulting permutations gives the value of $sgn_T(\sigma)$.

C. Spanning set of invariant polynomials

For a magic set $T \in B_d(n,k)$ define the polynomial

$$\Delta_T = \sum_{\sigma:[nk]\to[n]^d} sgn_T(\sigma) \prod_{i=1}^{nk} X_{\sigma(i)} \quad (6)$$

where sum runs over all possible such maps σ. In turns out, that these polynomials are enough to span $PInv_d(n,k)$, see Theorem 1.

We note that the polynomials $\{\Delta_T\}$ may and will be linearly dependent. Also, the size of $B_d(n,k)$ is still much larger than the dimension of $PInv_d(n,k)$, but in the next chapter we provide several optimizations on search of $B_d(n,k)$ by means of representation theory.

Materials and methods

In this section we decribe optimizations to generate the basis of $PInv_d(n,k)$. efficiently. We know that the set $\{\Delta_T \mid T \in B_d(n,k)\}$ linearly spans $PInv_d(n,k)$.

Theorem 1 [10]. Polynomial Δ_T is $SL(n)^d$-invariant of tensor space $(\mathbb{C}^n)^{\otimes d}$. Moreover, the set $\{\Delta_T\}$ where T ranges in $B_d(n,k)$ is the spanning set of $PInv_d(n,k)$.

The size of the set $B_d(n,k)$ grows exponentially fast, the rough upper bound would be $B_d(n,k) \le \binom{k^d}{nk}$. The following fact helps to enhance the search of smaller spanning set. We call a word $w = (w_1, \dots w_m) \in [k]^m$ lattice if for each $i = 1, \dots, m$ the number of occurences of j in the word $(w_1, \dots, w_i)$ is at least as the number of occurrences of $j+1$ in $(w_1, \dots, w_i)$ for each $j = 1, \dots, k$. Let $B_d^+(n,k) \subseteq B_d(n,k)$ be the subset of magic sets called lattice magic sets, if each row of a corresponding magic table is a lattice word.

Theorem 1 provides a method of generating such polynomial invariants. In practice we can dramatically reduce the size of search space of T from $B_d(n,k)$ to $B_d^+(n,k)$. This can be done with simple backtracking algorithm.

As soon as the space of tables obtained, we calculate coefficients of each polynomial using algebraic combinatorics hidden beneath. Further, we collect it into the matrix and do simple Gauss elimination algorithm to compute the basis. But there are 11712 possible monomials. To make computations feasible, as it turns out, we do not need all possible monomials, we are enough to restrict ourselves only on a subset of the monomials and sice the rank of a matrix is small, the basis can be obtained using only coefficients at around 50 monomials.

To sum up, our method of computation relies on the following optimizations:

◆ Optimization 1. Instead of considering entire space $B_d(n,k)$ we consider only the lattice part of it $B_d^+(n,k)$. It may be not enough, but in fact, the set $\{\Delta_T\}$ where ranges in $B_d^+(n,k)$ actually forms a spanning set of the space $PInv_d(n,k)$. Even if we do not know that, we can consider only these tables – if it turns out (and it will turn out) that the polynomials indexe with these tables span $PInv_d(n,k)$, we will not need this upgraded version of Theorem 1.

Optimization 2. While recovering polynomials Δ_T, we compute coefficients at all possible monomials. Then we construct the matrix tables × monomials and compute its row basis. But the number of monomials might be too large, so instead, we can consider only some subset of the monomials.

Results and discussion

In this section basis for the space of invariant polynomials of minimal degree is obtained. Using Sage [18] several dimension sequences are presented. In particular, we are interested in the row 2 and column 2 of the Table I, i.e. degree 4 invariants of 7 qubits.

Table 1 – Dimension sequences of polynomial invariants of degree nk for 7 qunits

k\n	1	2	3	4	5
1	1	0	0	0	0
2	1	21	161	3341	64799
3	1	70	636177	9379255543	215546990657498
4	1	3362	9379321798	220746106806871065	144464655787052084660142 40
5	1	62204	215601786541974	144464717151593025336541 42	537064014609197310184789727 3759375505

According to the Table 1,

$$dim\ \mathbb{C}\left[(\mathbb{C}^2)^{\otimes 7}\right]_4^{SL(2)^7} = g_7(2,2) = 21. \quad (7)$$

We present all 21 tables, that form the basis of invariant polynomials:

$$T_1 = \begin{pmatrix}0011\\0011\\0011\\0011\\0011\\0011\\0101\end{pmatrix}, T_2 = \begin{pmatrix}0011\\0011\\0011\\0011\\0011\\0101\\0101\end{pmatrix}, T_3 = \begin{pmatrix}0011\\0011\\0011\\0011\\0101\\0101\\0011\end{pmatrix}, T_4 = \begin{pmatrix}0011\\0011\\0011\\0011\\0101\\0011\\0101\end{pmatrix}, T_5 = \begin{pmatrix}0011\\0011\\0011\\0101\\0101\\0101\\0101\end{pmatrix},$$

$$T_6 = \begin{pmatrix}0011\\0011\\0011\\0101\\0011\\0011\\0101\end{pmatrix}, T_7 = \begin{pmatrix}0011\\0011\\0011\\0101\\0101\\0101\\0011\end{pmatrix}, T_8 = \begin{pmatrix}0011\\0011\\0011\\0101\\0011\\0011\\0101\end{pmatrix}, T_9 = \begin{pmatrix}0011\\0011\\0101\\0101\\0101\\0101\\0011\end{pmatrix}, T_{10} = \begin{pmatrix}0011\\0101\\0011\\0011\\0011\\0011\\0101\end{pmatrix},$$

$$T_{11} = \begin{pmatrix}0011\\0101\\0011\\0011\\0101\\0011\\0011\end{pmatrix}, T_{12} = \begin{pmatrix}0011\\0101\\0011\\0101\\0101\\0101\\0011\end{pmatrix}, T_{13} = \begin{pmatrix}0011\\0101\\0011\\0101\\0101\\0011\\0011\end{pmatrix}, T_{14} = \begin{pmatrix}0011\\0101\\0011\\0101\\0011\\0101\\0011\end{pmatrix}, T_{15} = \begin{pmatrix}0011\\0101\\0011\\0101\\0101\\0011\\0101\end{pmatrix},$$

$$T_{16} = \begin{pmatrix}0011\\0101\\0011\\0101\\0101\\0011\\0011\end{pmatrix}, T_{17} = \begin{pmatrix}0011\\0011\\0101\\0101\\0011\\0011\\0101\end{pmatrix}, T_{18} = \begin{pmatrix}0011\\0011\\0101\\0101\\0101\\0101\\0011\end{pmatrix},$$

$$T_{19} = \begin{pmatrix}0011\\0011\\0101\\0101\\0011\\0101\\0011\end{pmatrix}, T_{20} = \begin{pmatrix}0011\\0011\\0101\\0101\\0011\\0101\\0101\end{pmatrix}, T_{21} = \begin{pmatrix}0011\\0011\\0101\\0101\\0011\\0011\\0101\end{pmatrix}.$$

Each polynomial Δ_{T_i} is of degree 4 and has around 3072 terms. In contrast, geometric hyperdeterminant $det_{2\times2\times2\times2\times2\times2\times2}$ is of degree 6816 and has infeasable amount of terms.

Perfomance review. In total, the algorithm time complexity is $O\left(B_d^+(n,k)\cdot A_d^+(n,k)\cdot g_d(n,k)\right)$, due to time complexity of Gauss-Jordan elimination algorithm. Comparing this to the naive approach, i.e. without using proposed ehancements , we will archive only $O\left(B_d\ (n,k)\cdot A_d\ (n,k)\cdot g_d(n,k)\right)$ time complexity, which is exponentially worse, at least by a factor of $\left(\frac{k!^n}{\prod_{i\in[k],j\in[n]}(i+j-1)}\right)^d$, latter can be derived by hook-length formula.

Conclusion

The classification of SLOCC classes is very difficult. This is not only because entanglement phenomena are complex, but also due to practical issues: the computational problem's size increases exponentially with the number of parties or the number of possible particle states. Therefore, there is a need to develop fast and efficient methods. This paper tackles this issue by proposing a method to derive a basis of homogeneous invariant polynomials of tensors. It introduces an efficient algorithm for generating invariant polynomials of tensors. The findings also provide a contextual understanding of tensors concerning symmetries, which is crucial in computer science, as many advanced machine learning or statistical methods require tensors to be symmetric with respect to some coordinates.

Information on funding

This research was supported by the Science Committee of the Ministry of Science and Higher Education of the Republic of Kazakhstan (Grant No. AP14869221).

REFERENCES

1 Dür W., Vidal G., & Cirac J.I. Three qubits can be entangled in two inequivalent ways. Physical Review A, 2000, vol. 62, no. 6, p. 062314.

2 Luque J.-G. and Thibon Jean-Yves. Polynomial invariants of four qubits, Physical Review A, Apr. 2003, vol. 67, no. 4,. https://doi.org/10.1103/physreva.67.042303.

3 Luque J.-G. and Thibon Jean-Yves. Algebraic invariants of five qubits. Journal of physics, Dec. 2005, vol. 39, no. 2, pp. 371–377. https://doi.org/10.1088/0305-4470/39/2/007.

4 Horodecki R., Horodecki P., Horodecki M., and Horodecki K. Quantum entanglement. Reviews of Modern Physics, Jun. 2009, vol. 81, no. 2, pp. 865–942. https://doi.org/10.1103/revmodphys.81.865.

5 Nielsen M.A. and Chuang I.L. Quantum computation and quantum information. Cambridge Cambridge University Press, 2019.

6 Amanov A. Invariant polynomials with applications to Quantum Computing. Herald of the Kazakh-British technical university, 2024, vol. 21, no. 2, pp. 95–105. https://doi.org/10.55452/1998-6688-2024-21-2-95-105.

7 Miyake A. Classification of multipartite entangled states by multidimensional determinants. Physical Review A, 2003, vol. 67, no. 1. https://doi.org/10.1103/physreva.67.012108.

8 Bürgisser P. and Ikenmeyer C. Fundamental invariants of orbit closures. Journal of Algebra, 2017, vol. 477, pp. 390–434. https://doi.org/10.1016/j.jalgebra.2016.12.035.

9 Bürgisser P., Garg A., Oliveira R., Walter M., and Wigderson A. Alternating Minimization, Scaling Algorithms, and the Null-Cone Problem from Invariant Theory. In 9th Innovations in Theoretical Computer Science Conference (ITCS 2018). Leibniz International Proceedings in Informatics (LIPIcs), vol. 94, pp. 24:1–24:20, Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 2018. https://doi.org/10.4230/LIPIcs.ITCS.2018.24.

10 Amanov A. and Yeliussizov D. Fundamental Invariants of Tensors, Latin Hypercubes, and Rectangular Kronecker Coefficients, International Mathematics Research Notices, 2022, vol. 2023, no. 20, pp. 17552–17599. https://doi.org/10.1093/imrn/rnac311.

11 Bürgisser P., Franks C., Garg A., Oliveira R., Walter M., & Wigderson A. Efficient algorithms for tensor scaling, quantum marginals, and moment polytopes. In 2018 IEEE 59th Annual Symposium on Foundations of Computer Science (FOCS), 2018, pp. 883–897. IEEE.

12 Coecke B., & Kissinger A. The compositional structure of multipartite quantum entanglement. In International Colloquium on Automata, Languages, and Programming, 2010, pp. 297–308. Berlin, Heidelberg: Springer Berlin Heidelberg.

13 Cervera-Lierta A., Gasull A., Latorre J.I. and Sierra G. Multipartite entanglement in spin chains and the hyperdeterminant. Journal of physics. A, Mathematical and theoretical (Print), Nov. 2018, vol. 51, no. 50, pp. 505301–505301. https://doi.org/10.1088/1751-8121/aaee1f.

14 Viehmann O., Eltschka C. and Siewert J. Polynomial invariants for discrimination and classification of four-qubit entanglement. Physical Review A, May 2011, vol. 83, no. 5. https://doi.org/10.1103/physreva.83.052330.

15 Cayley A. On the theory of determinants. Pitt Press, 1844.

16 Cayley A. On the theory of linear transformations. E. Johnson, 1845.

17 Gelfand I.M., Kapranov M.M., and Zelevinsky A.V. Hyperdeterminants, Advances in Mathematics, Dec. 1992, vol. 96, no. 2, pp. 226–263. https://doi.org/10.1016/0001-8708(92)90056-q.

18 SageMath Mathematical Software System – Sage, SageMath Mathematical Software System. http://www.sagemath.org (accessed Apr. 2024).

19 Maria C. Parameterized Complexity of Quantum Invariants, Proceedings of the 37th International Symposium on Computational Geometry (SoCG 2021), 2021. https://doi.org/10.4230/LIPIcs.SoCG.2021.53.

20 Haddadin W. Invariant polynomials and machine learning. arXiv preprint arXiv:2104.12733, 2021.

21 Raith F., Blecha C., Nagel T., Parisio F., Kolditz O., Günther F., Stommel M., and Scheuermann G. Tensor field visualization using fiber surfaces of invariant space. IEEE transactions on visualization and computer graphics, 2018, 25, no. 1, pp. 1122–1131.

22 Hillar C.J., & Lim L.H. Most tensor problems are NP-hard. Journal of the ACM (JACM), 2013, vol. 60, no. 6, pp. 1–39.

[1]Аманов Ә.,
докторант, ORCID ID: 0000-0002-7669-0656,
e-mail: alimzhan.amanov@gmail.com

[1]Қазақстан-Британ техникалық университет,
050000, Алматы қ., Қазақстан

4 ДӘРЕЖЕЛІ 7 КУБИТТІҢ ИНВАРИАНТТЫҚ КӨПМҮШЕЛЕР БАЗИСІН ЕСЕПТЕУ

Андатпа

Көптеген кубиттерді қамтитын SLOCC (стохастикалық жергілікті операциялар және классикалық коммуникациялар) контекстіндегі шатасқан күйлердің күрделілігін түсіну кванттық жүйелер туралы біліміміздің жетілдіру үшін маңызды. Бұл күрделілік көбінесе күйлерді жергілікті симметрия топтары арқылы жіктеудің көмегімен талданады. Іс жүзінде алынған кластарды инварианттық көпмүшелерді пайдаланып ажыратуға болады, бірақ бұл көпмүшелердің мөлшері тез өседі. Сондықтан ең кішкентай инварианттарды алу өте маңызды. Осы қысқаша жазбада біз 4 дәрежелі 7 кубиттің инварианттық көпмүшелерінің базасын есептейміз, олар ең кіші дәрежелі инварианттар. Біз бұл көпмүшелерді көрсету теориясы мен алгебралық комбинатораны қолдана отырып аламыз.

Тірек сөздер: инвариантты көпмүшелер; кванттық түйісу, SLOCC.

[1]Аманов А.,
докторант, ORCID ID: 0000-0002-7669-0656,
e-mail: alimzhan.amanov@gmail.com

[1]Казахстанско-Британский технический университет,
050000, г. Алматы, Казахстан

ВЫЧИСЛЕНИЕ БАЗИСА ИНВАРИАНТНЫХ МНОГОЧЛЕНОВ СТЕПЕНИ 4 ДЛЯ 7 КУБИТОВ

Аннотация

Понимание сложности запутанных состояний в контексте SLOCC (стохастические локальные операции и классическая коммуникация), включающих несколько кубитов, важно для продвижения нашего знания о квантовых системах. Эта сложность часто анализируется путем классификации состояний через локальные группы симметрии. На практике полученные классы можно различать с помощью инвариантных многочленов, но размер этих многочленов быстро растет. Поэтому важно получить инварианты наименьшей возможной степени. В этой короткой заметке мы вычисляем базис инвариантных многочленов для 7 кубитов степени 4, которые являются инвариантами наименьшей степени. Мы получаем эти многочлены, используя теорию представлений и алгебраическую комбинаторику.

Ключевые слова: инвариантные полиномы, квантовая запутанность, SLOCC.

Article submission date: 29.07.2024.

МАТЕМАТИКАЛЫҚ ҒЫЛЫМДАР
MATHEMATICAL SCIENCES
МАТЕМАТИЧЕСКИЕ НАУКИ

UDC 511.41;
IRSTI 27.15.27

https://doi.org/10.55452/1998-6688-2024-21-3-137-146

[1]Tlepova M.,
Master, ORCID ID: 0009-0006-6302-5792,
e-mail: 211101014@stu.sdu.edu.kz
[1*]Orynbassar A.,
Master, Senior Lecturer, ORCID ID: 0000-0002-2943-9987,
*e-mail: alibek.orynbassar@sdu.edu.kz
[2]Kadyrov Sh.,
PhD, ORCID ID: 0000-0002-8352-2597,
e-mail: shirali.kadyrov@oxusuniversity.uz
[1]Shynarbek N.,
Master, Lecturer, ORCID ID: 0000-0001-6853-0858,
e-mail: nurdaulet.shynarbek@sdu.edu.kz

[1]SDU University, 040900, Kaskelen, Kazakhstan
[2]New Uzbekistan University, 100147, Tashkent, Uzbekistan

COMPLETE CLASSIFICATION OF QUADRATIC IRRATIONALS WITH PERIOD TWO

Abstract

This article presents a comprehensive investigation into the classification of quadratic irrationals with period two in their continued fraction representations. Building upon foundational results in Number Theory, particularly in the context of continued fractions and Pell's equation, the study reveals intricate relationships between quadratic irrationals and their periodic structures. The main object of study is $\sqrt{N}$ and properties of its continued fractions. While it is well-known that continued fractions of $\sqrt{N}$ is periodic with periodic part being palindrome, the distribution of the lengths of the periodic parts are far from being complete. Our main goal will be to focus on the period two case and provide a complete characterization. The research's proved theorems clarify the conditions under which the period length is exactly two and give an insight into the underlying algebraic features. Additionally, it delves deeper by offering numerical analysis and illustrations demonstrating the distribution of period lengths among quadratic irrationals. This research opens up new paths for future studies on quadratic irrationals and how they're shown as continued fractions.

Key words: Number Theory, continued fractions, quadratic irrationals, Pell's equation, period lengths.

Introduction

The theory of continued fractions is a rich branch of Number Theory that considers the representation of real numbers x by infinite sequences of fractions:

$$x = a_0 + \cfrac{1}{a_1 + \cfrac{1}{a_2 + \cfrac{1}{a_3 + \cdots}}}.$$

Continued fractions have a wide range of applications, including in numerical stability and special function representation [1], number-theoretic computations [2] and special functions in various fields [3]. They are also used in convergence criteria, three-term recurrence relations, hypergeometric functions, Pade approximants, and zero-free regions [4]. These applications highlight the versatility and importance of continued fractions in various mathematical and computational fields.

In this work, we consider quadratic irrationals and study the lengths of their periods when represented as continued fractions. We say that an irrational numbers is quadratic irrational if it is a root of a quadratic polynomial with integer coefficients. For simplicity we write $[a_0; a_1, a_2, a_3, \dots]$ for the continued fraction representation. One of the important results in the theory of continued fractions is due to Lagrange which states that for any quadratic irrational number, the continued fraction expansion eventually becomes periodic, for a proof see e.g. [5]. A special case of quadratic irrationals is the square roots of integers $\sqrt{N}$. An amazing result due to Galois states that the periodic parts of such fractions for quadratic irrationals manifest as palindromes [6]. To me more precise, for any square free positive integer N there exist positive number $a_0, a_1, \dots, a_n$ such that

$$\sqrt{N} = [a_0, \overline{a_1, a_2, \dots, a_2, a_1, 2a_0}],$$

where the overlined is the periodic part that repeats in the continued fraction representation. One interesting research direction is to investigate the distributional properties of the quadratic irrationals. For any square free N we let $D(\sqrt{N})$ denote the length of the periodic part of the continued fraction for the quadratic irrational $\sqrt{N}$. In this line of research, a recent work [7] shows that that for any square free d the sequence

$$D(\sqrt{d}), D(2\sqrt{d}), D(3\sqrt{d}), D(4\sqrt{d}), \dots$$

has infinitely many limit points in discrete topology. While this result is a moderate contribution to the research area, there are still many interesting questions to investigate. In particular, their result is not constructive in the sense that it is not clear which periods appear infinitely often. This is a delicate question and to address one needs to classify the numbers with certain periods.

In this work, we aim to classify all the square free positive integers N such that $D(\sqrt{N}) = 2$. By employing the fundamental relationship between the length of the periodic part and Pell's equation, this research aims to bridge the gap between historical insights and contemporary research. It seeks to affirm the presence of an infinite set of positive integers for which the period length in the continued fraction representation of quadratic irrationals is exactly two, thereby contributing to the broader discourse on Number Theory and the intricate beauty of mathematical structures.

We now state our main results. The core of this work is encapsulated in a series of theorems that shed a light on the intricate relationship between quadratic irrationals and their continued fraction representations. The following result provides a criterion for a square root of a number to have period 2.

Theorem 1. The length of the period for the continued fraction of the quadratic irrational $\sqrt{N}$ is $D(\sqrt{N}) = 2$ if and only if there are positive integers a, b satisfying

$$N = a^2 + \frac{2a}{b}$$

such that b is divisible by a, but $2a \neq b$.

To illustrate the theorem, for example, we may take $a = b = 2$, then all the conditions of the theorem are satisfied and for $N = a^2 + \frac{2a}{b} = 6$ we see that the continued fraction expansion satisfies $\sqrt{6} = [2; 2, 4, 2, 4, 2, 4, 2, 4, \ldots]$ giving $D(\sqrt{6}) = 2$. As another example, we may take $a = 4, b = 2$ then $N = a^2 + \frac{2a}{b} = 20$ and $D(20) = 2$.

The next result deals with those members of the sequence $(n\sqrt{d})$ for which the period length is 2.

Theorem 2. Let d be a square free positive integer. Then, the length of the period for the continued fraction of the quadratic irrational $n\sqrt{d}$ is $D(n\sqrt{d}) = 2$ if n satisfies the Pell's equation

$$n^2 - dx^2 = 1$$

for some integer x. In particular, there exist infinitely many n such that $(n\sqrt{d}) = 2$.

As a corollary to Theorem 2 we deduce the following distribution result.

Corollary 3. Let d be a square free positive integer. Then, the natural number n such that $D(n\sqrt{d}) = 2$ satisfies

$$\text{limsup}_{N\to\infty} \frac{1}{\ln N} |\{n \,|1 \le n \le N, D(n\sqrt{d}) = 2\}| > 0.$$

These findings not only deepen our understanding of mathematical properties of quadratic irrationals but also establish a connection with Pell's equation, highlighting a significant intersection between different areas of Number Theory.

Collectively, these theorems illuminate mathematical intricacies of continued fractions for quadratic irrationals, bridging historical insights with contemporary mathematical inquiries. They demonstrate the rich interplay between algebraic forms, periodicity, and Diophantine equations, paving the way for future research in the field. Through detailed proofs and illustrative examples, this research underscores the enduring allure and complexity of continued fractions, inviting a further exploration into the mysteries of mathematical structures.

In the next section we review background and related works. Section 3 is devoted proving the main results. The paper ends with conclusion and future directions.

Main Provisions

The study of continued fractions, integral to mathematics, relies on historical achievements for advancement. Originating over two millennia ago, their formal foundations were laid in the late 17th and early 18th centuries. The genesis of continued fractions is often linked to Euclid's Algorithm, initially devised for finding the greatest common denominator (GCD) of two numbers but also applicable algebraically to derive the simple continued fraction representation of a rational number [8].

Euclid's method, when applied to find the GCD of 27 and 129, reveals a continued fraction representation through algebraic manipulations. This method highlights the reciprocal relationship between the fractions in successive equations, leading to a continued fraction representation. This early connection to continued fractions underscores their historical significance in approximating quadratic irrationals and contributions by mathematicians like Fibonacci.

During the Renaissance, mathematicians including Rafael Bombelli and John Wallis contributed significantly to the formal concept of continued fractions. Bombelli, in his treatise "L'Algebra" (1572), discussed square roots' representation as infinite continued fractions, providing a foundational approach later elaborated in his second edition of "L'Algebra Opera" (1579) [9]. Wallis introduced a continued fraction notation in "Arithmetica Infinitorum" (1655), using it to approximate square roots and other irrational numbers, thus coining the term continued fraction [9, 10].

The 18th and 19th centuries witnessed substantial advancements in continued fractions by Euler, Lagrange, and Gauss. Euler's work, "De fractionibus continuis" (1737), proved that every

real number has a unique simple continued fraction representation and explored continued fractions for rational and irrational numbers, including the representation of e as a continued fraction [10]. Huygens applied convergents in continued fractions for practical uses, like gear ratio approximations in his mechanical planetarium construction [10, 11].

Lagrange's "Théorie des fonctions analytiques" (1798) established the periodicity of continued fractions for quadratic irrationals, known as Lagrange's theorem, which significantly influenced the development of periodic continued fractions [12]. The 19th century saw applications of continued fractions in Number Theory and Diophantine approximation by Cauchy and Sylvester, enhancing the understanding of partial quotients and approximation properties.

In 1972, P. Chowla and S. Chowla explored periodic continued fractions, raising questions about finding infinite sets of positive integers d with a given length of the periodic part $D\sqrt{d} = l$, conjecturing an affirmative answer [13]. Christian Friesen (1988) provided a positive proof, establishing results on palindromic sequences that led to Friesen's corollary addressing the original question posed by Chowla and Chowla [14].

Franz Halter-Koch (1989) refined Friesen's theorem, adding conditions related to the prime factorizations of d, offering a deeper understanding of the integers satisfying the palindromic sequence condition [15]. Recent studies by Balková and Hrusková compiled findings on continued fractions for quadratic numbers, investigating equations linking N to values of $D(\sqrt{N})$, contributing to the broader understanding of continued fractions in Number Theory [14].

Rada and Starosta explored the Moebius transformation's effect on the period length of continued fraction expansions, setting bounds for $D\left(h\left(\sqrt{x}\right)\right)$ based on $D\left(\sqrt{x}\right)$,

enriching the mathematical exploration of continued fractions [16]. Building on the work of Gawron and Kobos, this dissertation extends the analysis of Moebius transformations applied to quadratic irrationals, particularly focusing on their limit points in the sequence

$D\left(n\sqrt{d}\right)$, highlighting the infinite nature of these limit points and posing new research directions.

Materials and Methods

Proof of Theorem 1. Assume that $D(\sqrt{N}) = 2$. By utilizing the definition of continued fractions and leveraging Galois' result which states that the periodic part of continued fractions for quadratic irrationals is a palindrome, we can represent $\sqrt{N}$ as follows:

$$\sqrt{N} = [a; b, 2a, b, 2a, b, 2a, \ldots].$$

We notice that to avoid period 1 case, we must have $b \neq 2a$. Now, let's add the integer a to both sides of the expression and introduce a new equation:

$$x := a + \sqrt{N} = [2a; b, 2a, b, 2a, b, 2a, \ldots] = [\overline{2a, b}].$$

Since $x = [\overline{2a, b}] = [2a, b, \overline{2a, b}]$, it follows that

$$x = 2a + \frac{1}{b + \frac{1}{x}} = 2a + \frac{x}{bx + 1}.$$

From this equation we can derive the quadratic equation in the following form:

$$x^2 - 2ax - \frac{2a}{b} = 0.$$

By solving this quadratic equation, we obtain two roots and derive the formula for the integer N:

$$x_1 = \frac{2a + \sqrt{4a^2 - 8a/b}}{2} = a + \sqrt{a^2 + \frac{2a}{b}},$$

$$x_2 = \frac{2a - \sqrt{4a^2 - 8a/b}}{2} = a - \sqrt{a^2 + \frac{2a}{b}}.$$

Since $x = a + \sqrt{N} > a$, we see that $x = x_1$. Solving for N we arrive at

$$N = a^2 + \frac{2a}{b}.$$

Therefore, we deduce that $D(\sqrt{N}) = 2$ if and only if $b \neq 2a$ and b is a positive integer divisible by $2a$.

We now turn in proving Theorem 2.

Proof of Theorem 2. Let a square free d be given. For $N = n\sqrt{d}$ to have period 2 we know from Theorem 1 that there must exist a, b such that $b \neq 2a$ and b is a positive integer divisible by $2a$ and

$$n^2 d = a^2 + \frac{2a}{b}.$$

Let us take $a = dx$ and $b = 2x$ where x is yet to be determined. Then, the above equation takes the form $n^2 d = (dx)^2 + d$. Cancelling out d we arrive at

$$n^2 - dx^2 = 1.$$

This is a well-known Pell's equation and it has infinitely many solution pairs (n, x) [17]. Therefore, for any such n we have that $D\left(n\sqrt{d}\right) = 2$. This finishes the proof of Theorem 2.

Proof of Corollary 3. We notice that once the fundamental solution (n_1, x_1) to the Pell's equation

$$n^2 - dx^2 = 1$$

is found, the other solutions (n_k, x_k) can be found iteratively from

$$n_k + x_k\sqrt{d} = \left(n_1 + x_1\sqrt{d}\right)^k.$$

Since $x_1\sqrt{d} = n_1^2 - 1$ we get

$$n_k \leq n_k + x_k\sqrt{d} = \left(n_1 + x_1\sqrt{d}\right)^k < (2n_1^2)^k.$$

Thus, for $N = (2n_1^2)^k$, there are at least k integers n satisfying $D\left(n\sqrt{d}\right) = 2$. Hence,

$$\limsup_{N\to\infty} \frac{1}{\ln N} |\{n \,|1 \leq n \leq N, D\left(n\sqrt{d}\right) = 2\}| \geq \frac{1}{2n_1^2}.$$

Results and Discussion

In this section we carry numerical analysis and visualize distribution of lengths of periods to certain generality.

In the first instance, we consider all square-free positive integers up to one million and consider how the lengths of periods of under the square root function is distributed.




Figure 1 – Distribution of lengths of periods for square root of numbers up to one million


For most square-free $N \leq 1000000$ we have $D(N) \leq 1000$. For this reason, we have only considered those lengths that are at most 1000 to make the graphics readable.

In Figure 2, we consider the distribution of $D(n\sqrt{d})$ for various d and values for n up to 1000. The distribution of periods is generated when $d = 2,3,5,7,8,10$.


The implications of our findings are manifold, extending beyond the immediate scope of quadratic irrationals to touch upon broader aspects of number theory and mathematical research. The classification of quadratic irrationals with a period of two offers a glimpse into the symmetry and patterns inherent in mathematical structures, echoing the palindromic beauty found within the periodic parts of continued fractions for quadratic irrationals.

Looking ahead, several avenues for future research have been illuminated by this study. For instance, extending the classification to quadratic irrationals with periods greater than two presents a challenging yet potentially rewarding endeavor. Additionally, exploring the connections between the distribution of period lengths and other number-theoretic phenomena could yield further insights into the underlying principles of number theory.


Another intriguing direction is the investigation of the practical applications of these findings. The theoretical insights gained from the study of quadratic irrationals and their continued fraction representations could have implications for numerical analysis, cryptography, and even quantum computing, where the properties of numbers play a pivotal role.




(A) $d = 2$




(B) $d = 3$




(C) $d = 5$




(D) $d = 6$



(E) $d = 7$



(F) $d = 8$



(G) $d = 10$

Figure 2 – The distribution of $D(n\sqrt{d})$ for $n = 1,2,\ldots,1000$ and $d = 2,3,5,6,7,8,10$.

Conclusion

This study delved into the realm of quadratic irrationals with period two, illuminating their structure through the lens of continued fractions and Pell's equation. Our work not only enriches the existing body of knowledge but also draws connections between classical and contemporary number theory, highlighting the intricate dance between algebraic properties and periodicity. The theorems we've established lay down explicit criteria for when a quadratic irrational will exhibit this unique periodic behavior, thereby expanding our understanding and appreciation of these mathematical entities.

Information on funding

The authors acknowledge the support by a grant from the Ministry of Science and Higher Education of the Republic of Kazakhstan within framework of the project AP19676669.

REFERENCES

1 Jones W.B., Thron W.J. Numerical stability in evaluating continued fractions. Mathematics of Computation, 1974, vol. 28, no. 127, pp. 795–810.

2 Williams H.C. Continued fractions and number-theoretic computations. The Rocky Mountain Journal of Mathematics, 1985, pp. 621–655.

3 Cuyt A.A.M. et al. Handbook of continued fractions for special functions. Springer Science & Business Media, 2008.

4 Lorentzen L., Waadeland H. Continued Fractions: Convergence Theory. Atlantis Press, 2008, vol. 1.

5 Einsiedler M. Ergodic theory. Springer, 2011.

6 Halter-Koch F. Quadratic irrationals: An introduction to classical number theory. – CRC press, 2013.

7 Gawron F., Kobos T. On length of the period of the continued fraction of nd. International Journal of Number Theory, 2023, pp. 1–11.

8 Van Tuyl A. L. An Introduction to the Theory and Applications of Continued Fractions, 1996.

9 Olds C. D. Continued Fractions Random House. New York, 1963.

10 Schlapp R. Morris Kline, Mathematical Thought from Ancient to Modern Times (Oxford University Press, 1973), xvii+ 1238 pp., £ 12. Proceedings of the Edinburgh Mathematical Society, 1973, vol. 18, no. 4, pp. 340–341.

11 Moore C. G. An Introduction to Continued Fractions, 1964.

12 De Lagrange J. L. Recherches d'arithmétique. Nouveaux Mémoires de l'Académie de Berlin, p. 1773.

13 Chowla P., Chowla S. Problems on periodic simple continued fractions. Proceedings of the National Academy of Sciences, 1972, vol. 69, no. 12, pp. 3745–3745.

14 Friesen C. On continued fractions of given period. Proceedings of the American Mathematical Society, 1988, vol. 103, no. 1, pp. 9–14.

15 Halter-Koch F. Continued fractions of given symmetric period. Fibonacci Quart.,1991, vol. 29, no. 4, pp. 298–303.

16 Řada H., Starosta Š. Bounds on the period of the continued fraction after a möbius transformation. Journal of Number Theory, 2020, vol. 212, pp. 122–172.

17 Acewicz M., Pąk K. Pell's equation. Formalized Mathematics, 2017, vol. 25, no. 3, pp. 197–204.

[1]Тлепова М.,
магистр, ORCID ID: 0009-0006-6302-5792,
e-mail: 211101014@stu.sdu.edu.kz
[1]*Орынбасар Ә.,
магистр, аға оқытушысы, ORCID ID: 0000-0002-2943-9987,
*e-mail: alibek.orynbassar@sdu.edu.kz
[2]Кадыров Ш.,
PhD, ORCID ID: 0000-0002-8352-2597,
e-mail: shirali.kadyrov@oxusuniversity.uz
[1]Шынарбек Н.,
магистр, оқытушы, ORCID ID: 0000-0001-6853-0858,
e-mail: nurdaulet.shynarbek@sdu.edu.kz

[1]SDU университеті, 040900, Қаскелең қ., Қазақстан
[2]«Жаңа Өзбекстан» университеті, 100147, Ташкент қ., Өзбекстан

ЕКІ ПЕРИОДТЫ КВАДРАТТЫҚ ИРРАЦИОНАЛ САНДАРДЫҢ ТОЛЫҚ ЖІКТЕЛУІ

Аңдатпа

Бұл мақалада квадраттық иррационал сандардың жіктелуін олардың үздіксіз бөлшек көріністерінде екінші кезеңмен жан-жақты зерттеу ұсынылған. Сандар теориясының негізгі нәтижелеріне сүйене отырып тізбекті фракциялар мен Пелл теңдеулерін зерттеу квадраттық иррационал сандар мен олардың периодтық құрылымдары арасындағы күрделі қатынастарды айқындайды. Зерттеудің негізгі объектісі – $\sqrt{N}$ және оның тізбекті бөлшектерінің қасиеттері. $\sqrt{N}$ үздіксіз бөлшектері периодты және олардың периодтық бөлігі палиндром екені белгілі болғанымен, периодтық бөліктердің ұзындығының таралуы толық зерттелмеген. Біздің басты мақсатымыз екінші кезеңге назар аудара отырып, оларға толық сипаттама беру. Зерттеуде дәлелденген теоремалар периодтың ұзындығы екіге тең болатын шарттарды нақтылайды және негізгі алгебралық белгілер туралы түсінік береді. Сонымен қатар, жұмыс квадраттық иррационал сандар арасында периодтық ұзындықтардың таралуын көрсететін сандық талдаулар мен иллюстрацияларды ұсына отырып, осы саладағы зерттеулерді тереңдете түседі. Бұл зерттеу болашақта квадраттық иррационал сандарды және олардың үздіксіз бөлшектер ретінде көрінуін зерттеуге жаңа жолдар ашады.

Тірек сөздер: Сандар теориясы, жалғасымды бөлшектер, квадрат иррационалдар, Пелл теңдеуі, период ұзындықтары

[1]Тлепова М.,
магистр, ORCID ID: 0009-0006-6302-5792,
e-mail: 211101014@stu.sdu.edu.kz
[1*]Орынбасар Ә.,
магистр, старший преподаватель, ORCID ID: 0000-0002-2943-9987,
*e-mail: alibek.orynbassar@sdu.edu.kz
[2]Кадыров Ш.,
PhD, ORCID ID: 0000-0002-8352-2597,
e-mail: shirali.kadyrov@oxusuniversity.uz
[1]Шынарбек Н.,
магистр, ORCID ID: 0000-0001-6853-0858,
e-mail: nurdaulet.shynarbek@sdu.edu.kz

[1]SDU Университет, 040900, г. Каскелен, Казахстан
[2]New Uzbekistan Университет, 100147, г. Ташкент, Узбекистан

ПОЛНАЯ КЛАССИФИКАЦИЯ КВАДРАТИЧНЫХ ИРРАЦИОНАЛЬНЫХ ЧИСЕЛ С ПЕРИОДОМ ДВА

Аннотация

В этой статье представлено всестороннее исследование классификации квадратичных иррациональных чисел со вторым периодом в их представлениях непрерывной дроби. Основываясь на фундаментальных результатах теории чисел, особенно в контексте цепных дробей и уравнения Пелла, исследование раскрывает сложные взаимосвязи между квадратичными иррациональными числами и их периодическими структурами. Основным объектом исследования является $\sqrt{N}$ и свойства его цепных дробей. Хотя хорошо известно, что непрерывные дроби $\sqrt{N}$ являются периодическими, а периодическая часть является палиндромом, распределение длин периодических частей далеко не полное. Нашей главной целью будет сосредоточиться на втором периоде и предоставить полную характеристику. Доказанные теоремы исследования разъясняют условия, при которых длина периода равна ровно двум, и дают представление о лежащих в основе алгебраических особенностях. Кроме того, он углубляется, предлагая численный анализ и иллюстрации, демонстрирующие распределение длин периодов среди квадратичных иррациональных чисел. Это исследование открывает новые пути для будущих исследований квадратичных иррациональных чисел и того, как они отображаются в виде непрерывных дробей.

Ключевые слова: теория чисел, цепные дроби, квадратичные иррациональные числа, уравнение Пелла, длины периодов.

Article submission date: 26.02.2024

UDC 517.5
IRSTI 27.39.27

https://doi.org/10.55452/1998-6688-2024-21-3-147-157

[1,2*]**Apseit K.,**
Master, ORCID ID: 0000-0002-2049-2984,
*e-mail: kuralay.apseit@sdu.edu.kz

[3]**Yessirkegenov N.,**
PhD, ORCID ID: 0000-0002-2985-2288,
e-mail: nurgissa.yessirkegenov@gmail.com

[1]SDU University, 040900, Kaskelen, Kazakhstan,
[2]Institute of Mathematics and Mathematical Modeling,
050010, Almaty, Kazakhstan
[3]KIMEP University, 050010, Almaty, Kazakhstan

FACTORIZATIONS AND UNIFIED HARDY INEQUALITIES ON HOMOGENEOUS LIE GROUPS

Abstract

In this note we obtain Hardy and critical Hardy inequalities with any homogeneous quasi-norm in unified way. Actually, we show a sharp remainder formula for these results. In particular, our identity implies corresponding Hardy and critical Hardy inequalities with any homogeneous quasi-norm for the radial derivative operator, thus yielding improved versions of corresponding classical counterparts. Moreover, we discuss extensions of these results in the setting of Folland and Stein's homogeneous Lie groups. Such a more general setting is convenient for the distillation of those results of harmonic analysis depending only on the group and dilation structures, which is one of our motivations working in the setting. Our approach based on the factorization method of differential operators introduced by Gesztesy and Littlejohn. As an application, we show Caffarelli-Kohn-Nirenberg type inequalities with more general weight. Because of the freedom in the choice of any homogeneous quasi-norm, our results give new insights already in both anisotropic $\mathbb{R}^n$ and isotropic $\mathbb{R}^n$.

Key words: factorization method, Hardy inequality, homogeneous Lie group.

Introduction

Recall that the Hardy inequality for all functions $f \in C_0^\infty(\mathbb{R}^n)$ takes the form

$$\int_{\mathbb{R}^n} |(\nabla f)(x)|^2 dx \geq \left(\frac{n-2}{2}\right)^2 \int_{\mathbb{R}^n} \frac{|f(x)|^2}{|x|^2} dx, \; n \geq 3, \tag{1}$$

where ∇ represents the standard gradient in $\mathbb{R}^n$. Nowadays, there are many works concerning various versions of Hardy's inequalities, so we are not able to cover it in this short paper. Let us mention only classic monographs such as [1], [2], [3], [4] and the recent open access book [5] on this subject and for its applications.

This note aims to establish more general Hardy inequality unifying both sub-critical and critical cases on homogeneous Lie groups by employing the factorization method for differential expressions.

In this direction, recently Gesztesy and Littlejohn in [6] gave a simple proof of (1) by using the non-negativity of $T_\alpha^+ T_\alpha$ on $C_0^\infty(\mathbb{R}^n \setminus \{0\})$ and selecting special value for the parameter α, where

$$T_\alpha := \nabla + \alpha |x|^{-2} x,$$

and T_α^+ its formal adjoint

$$T_\alpha^+ = -\mathrm{div}(\cdot) + \alpha |x|^{-2} x \cdot, \; x \in \mathbb{R}^n \setminus \{0\},$$

for $\alpha \in \mathbb{R}, x \in \mathbb{R}^n \setminus \{0\}$ and $n \geq 3$. There, the authors also applied the factorization method to obtain Rellich inequalities with remainder terms. For this method, we also refer to [7], [8], [9] in the Euclidean setting as well as [10] on stratified Lie groups.

Here, in this note we plan to continue the research from [10] by applying the method to unified Hardy inequalities on homogeneous Lie groups with any homogeneous quasi-norm. Actually, in this noncommutative setting we show Hardy identities that implies improved subcritical and critical Hardy inequalities. For this, let us recall first necessary definitions and notations of homogeneous Lie groups following Folland and Stein [11] and a recent book by Fischer and Ruzhansky [12].

A homogeneous Lie group $\mathbb{G}$ is a connected simply connected Lie group if its Lie algebra $\mathfrak{g}$ is equipped with family of morphisms representing dilations, as follows:

$$D_\lambda = \mathrm{Exp}(A \ln \lambda) = \sum_{k=0}^{\infty} \frac{1}{k!} (\ln(\lambda) A)^k.$$

Here A is a diagonalisable positive linear operator on the Lie algebra $\mathfrak{g}$, and every D_λ is a morphism of the Lie algebra $\mathfrak{g}$. The homogeneous dimension of $\mathbb{G}$ is defined by $Q := \mathrm{Tr}\, A$. In this context, the standard Lebesgue measure dx on $\mathbb{R}^n$ is the Haar measure on homogeneous Lie group $\mathbb{G}$ [12, Proposition 1.6.6]).

A homogeneous quasi-norm refers to a continuous non-negative function

$$\mathbb{G} \ni \mathrm{x} \mapsto |x| \in [0, \infty)$$

satisfying:

- $|x^{-1}| = |x|$ for any $x \in \mathbb{G}$,
- $|\lambda x| = \lambda |x|$ for any $x \in \mathbb{G}$ and $\lambda > 0$,
- $|x| = 0$ if and only if $x = 0$.

Next, the polar decomposition on homogeneous Lie groups defined as follows: there exists a positive Borel measure σ defined on the unit quasi-sphere

$$\mathfrak{S} := \{x \in \mathbb{G} : |x| = 1\}, \tag{2}$$

so that for all $f \in L^1(\mathbb{G})$ we have

$$\int_{\mathbb{G}} f(x) dx = \int_0^\infty \int_{\mathbb{G}} f(ry) r^{Q-1} d\sigma(y) dr, \tag{3}$$

where $|\cdot|$ is a homogeneous quasi-norm on $\mathbb{G}$. For more details on the polar decomposition, we can refer to [11]. Throughout this paper, we also use the notation

$$\mathcal{R}_{|x|} := \frac{d}{d|x|} \tag{4}$$

for a homogeneous quasi-norm $|x|$ on the homogeneous Lie group $\mathbb{G}$.

Material and methods

As mentioned in Introduction there is a huge literature on the Hardy inequalities, so let us refer only to classic monographs as [1], [2], [3] and [4] to mention few. As for the factorization method, we can refer to [6], [7], [8], [9] and [10].

The main aim of this paper is to derive unified Hardy inequalities with any homogeneous quasi-norm on homogeneous Lie groups via the method of factorization. Gesztesy introduced the factorization method to obtain the classical Hardy inequality in [8] then in [9] the radial and logarithmic refinements. More recently, in the noncommutative setting, the authors in [10] successfully applied the factorization method to obtain improved Hardy and Hardy-Rellich type inequalities on general stratified groups and weighted Hardy inequalities on general homogeneous Lie groups.

Results and Discussion

Let $\mathrm{B}_R := \{y \in G: |y| < R\}$ where $|\cdot|$ is a homogeneous quasi-norm on $\mathbb{G}$.

Theorem 1. Let $\mathbb{G}$ be a homogeneous Lie group of homogeneous dimensions $Q \geqslant 2$ and let $|\cdot|$ be any homogeneous quasi-norm. Let B_R be a quasi-ball of $\mathbb{G}$ with a radius R. Then, for all complex-valued functions $f \in C_0^\infty(\mathrm{B}_R\backslash\{0\})$ we have

Remark 1. By dropping the last term in (5), we can get the following result:

$$|\mathcal{R}_{|x|}f(x)|^2dx = \frac{(Q-2)^2}{4}\int_{\mathrm{B}_R}\frac{|f(x)|^2}{|x|^2}dx + \frac{1}{4}\int_{\mathrm{B}_R}\frac{|f(x)|^2}{|x|^2}\left(\ln\frac{R}{|x|}\right)^{-2}dx$$
$$+\int_{\mathrm{B}_R}\left|\mathcal{R}_{|x|} + \frac{Q-2}{2}|x|^{-1} + \frac{1}{2}|x|^{-1}\left(\ln\frac{R}{|x|}\right)^{-1}\right|^2 dx. \tag{5}$$

$$\int_{\mathrm{B}_R}|\mathcal{R}_{|x|}f(x)|^2dx \geq \frac{(Q-2)^2}{4}\int_{\mathrm{B}_R}\frac{|f(x)|^2}{|x|^2}dx + \frac{1}{4}\int_{\mathrm{B}_R}\frac{|f(x)|^2}{|x|^2}\left(\ln\frac{R}{|x|}\right)^{-2}dx. \tag{6}$$

Here, note that the Abelian case $\mathbb{G} = (\mathbb{R}^n, +)$, hence $Q = n$, of (6) with the Euclidean norm $|x| = |x|_E$ was obtained in [9]. So, the identity (5) gives sharp remainder formula for their result. Moreover, dropping the last term in (6) implies improved version of (1) due to the estimate $|\nabla f| \geq |\mathcal{R}_{|x|}f|$. Similarly, but dropping the first term instead of the second term on the right-hand side of (6) gives improved critical case $n = 2$ of (1).

Proof of Theorem 1. Let us first introduce one-parameter differential expression

$$T := \mathcal{R}_{|x|} + \frac{Q-2}{2}|x|^{-1} + \frac{1}{2}|x|^{-1}\left(\ln\frac{R}{|x|}\right)^{-1}. \tag{7}$$

Now, we find a formal adjoint operator of T on $C_0^\infty(\mathrm{B}_R\backslash\{0\})$ as follows:

$$\int_{\mathrm{B}_R}\mathcal{R}_{|x|}f(x)\overline{g(x)}dx + \frac{Q-2}{2}\int_{\mathrm{B}_R}|x|^{-1}f(x)\overline{g(x)}dx + \frac{1}{2}\int_{\mathrm{B}_R}|x|^{-1}\left(\ln\frac{R}{|x|}\right)^{-1}f(x)\overline{g(x)}dx$$
$$= \int_0^R\int_{\mathbb{S}}\frac{d}{dr}(f(ry))\overline{g(ry)}r^{Q-1}d\sigma(y)dr + \frac{Q-2}{2}\int_{\mathrm{B}_R}|x|^{-1}f(x)\overline{g(x)}dx$$
$$+\frac{1}{2}\int_{\mathrm{B}_R}|x|^{-1}\left(\ln\frac{R}{|x|}\right)^{-1}f(x)\overline{g(x)}dx = -\int_0^R\int_{\mathbb{S}}f(ry)\frac{d}{dr}(g(ry))r^{Q-1}d\sigma(y)dr$$

$$-(Q-1)\int_0^R \int_{\mathfrak{S}} f(ry)\overline{g(ry)}r^{Q-2}d\sigma(y)dr$$

$$+\frac{Q-2}{2}\int_{\mathrm{B}_R} |x|^{-1}f(x)\overline{g(x)}dx+\frac{1}{2}\int_{\mathrm{B}_R} |x|^{-1}\left(\ln\frac{R}{|x|}\right)^{-1} f(x)\overline{g(x)}dx$$

$$=\int_{\mathrm{B}_R} f(x)(-\overline{\mathcal{R}_{|x|}g(x)})dx-\frac{Q}{2}\int_{\mathrm{B}_R} |x|^{-1}f(x)\overline{g(x)}dx$$

$$+\frac{1}{2}\int_{\mathrm{B}_R} |x|^{-1}\left(\ln\frac{R}{|x|}\right)^{-1} f(x)\overline{g(x)}dx. \tag{8}$$

Thus, the formal adjoint operator of T has the following form

$$T^+=-\mathcal{R}_{|x|}-\frac{Q}{2}|x|^{-1}+\frac{1}{2}|x|^{-1}\left(\ln\frac{R}{|x|}\right)^{-1}. \tag{9}$$

Now, let us compute T^+T as follows.

$$(T^+Tf)(x)=-\mathcal{R}_{|x|}(\mathcal{R}_{|x|}f(x))-\mathcal{R}_{|x|}\left(\frac{Q-2}{2}|x|^{-1}f(x)\right)-\mathcal{R}_{|x|}\left(\frac{1}{2}|x|^{-1}\left(\ln\frac{R}{|x|}\right)^{-1} f(x)\right)$$

$$-\frac{Q}{2}|x|^{-1}\mathcal{R}_{|x|}f(x)-\frac{Q}{2}\left(\frac{Q-2}{2}\right)|x|^{-2}f(x)-\frac{Q}{4}|x|^{-2}\left(\ln\frac{R}{|x|}\right)^{-1} f(x)$$

$$+\frac{1}{2}|x|^{-1}\left(\ln\frac{R}{|x|}\right)^{-1}\mathcal{R}_{|x|}f(x)+\frac{Q-2}{4}|x|^{-2}\left(\ln\frac{R}{|x|}\right)^{-1} f(x)+\frac{1}{4}|x|^{-2}\left(\ln\frac{R}{|x|}\right)^{-2} f(x).$$

By the nonnegativity of T^+T, introducing the polar coordinate $(r,y)=\left(|x|,\frac{x}{|x|}\right)\in(0,\infty)\times\mathfrak{S}$ on $\mathbb{G}$, where $\mathfrak{S}$ is the quasi-sphere as in (2), and using (3), one calculates

$$0\leqslant\int_{\mathrm{B}_R}|(Tf)(x)|^2dx=\int_{\mathrm{B}_R} f(x)\overline{(T^+Tf)(x)}dx=$$
$$\mathrm{Re}\int_{\mathrm{B}_R} f(x)\overline{(T^+Tf)(x)}dx=I_1+I_2+I_3+I_4+I_5, \tag{10}$$

where

$$I_1=-\mathrm{Re}\int_0^R\int_{\mathfrak{S}} f(ry)\overline{\frac{d}{dr}\left(\frac{d}{dr}(f(ry))\right)}r^{Q-1}d\sigma(y)dr,$$

$$I_2=-\frac{Q-2}{2}\mathrm{Re}\int_0^R\int_{\mathfrak{S}} f(ry)\overline{\frac{d}{dr}(r^{-1}f(ry))}r^{Q-1}d\sigma(y)dr,$$

$$I_3=-\frac{1}{2}\mathrm{Re}\int_0^R\int_{\mathfrak{S}} f(ry)\overline{\frac{d}{dr}\left(r^{-1}\left(\ln\frac{R}{r}\right)^{-1} f(ry)\right)}r^{Q-1}d\sigma(y)dr,$$

$$I_4 = -\frac{Q}{2}\mathrm{Re}\int_0^R \int_{\mathbb{S}} f(ry)r^{-1}\overline{\frac{d}{dr}f(ry)}r^{Q-1}d\sigma(y)dr + \frac{1}{2}Re\int_0^R \int_{\mathbb{S}} f(ry)r^{-1}\left(\ln\frac{R}{r}\right)^{-1}\overline{\frac{d}{dr}f(ry)}r^{Q-1}d\sigma(y)dr,$$

and,

$$I_5 = -\frac{Q}{2}\left(\frac{Q-2}{2}\right)\int_{\mathrm{B}_R}\frac{|f(x)|^2}{|x|^2}dx - \frac{Q}{4}\int_{\mathrm{B}_R}\frac{|f(x)|^2}{|x|^2}\left(\ln\frac{R}{|x|}\right)^{-1}dx + \frac{Q-2}{4}\int_{\mathrm{B}_R}\frac{|f(x)|^2}{|x|^2}\left(\ln\frac{R}{|x|}\right)^{-1}dx + \frac{1}{4}\int_{\mathrm{B}_R}\frac{|f(x)|^2}{|x|^2}\left(\ln\frac{R}{|x|}\right)^{-2}dx. \quad (11)$$

Now we simplify I_1, I_2, I_3 and I_4. By a direct calculation we obtain

$$I_1 = -\mathrm{Re}\int_0^R \int_{\mathbb{S}} f(ry)\overline{\frac{d}{dr}\left(\frac{d}{dr}\left(f(ry)\right)\right)}r^{Q-1}d\sigma(y)dr$$

$$= (Q-1)\,\mathrm{Re}\int_0^R \int_{\mathbb{S}} f(ry)\overline{\frac{d}{dr}\left(f(ry)\right)}r^{Q-2}d\sigma(y)dr$$

$$+\mathrm{Re}\int_0^R \int_{\mathbb{S}} \frac{d}{dr}\left(f(ry)\right)\overline{\frac{d}{dr}\left(f(ry)\right)}r^{Q-1}d\sigma(y)dr =$$

$$= \frac{Q-1}{2}\int_0^R \int_{\mathbb{S}} \frac{d}{dr}|f(ry)|^2 r^{Q-2}d\sigma(y)dr$$

$$+\int_0^R \int_{\mathbb{S}} \left|\frac{d}{dr}\left(f(ry)\right)\right|^2 r^{Q-1}d\sigma(y)dr$$

$$= -\frac{(Q-1)(Q-2)}{2}\int_0^R \int_{\mathbb{S}} |f(ry)|^2 r^{Q-3}d\sigma(y)dr$$

$$+\int_0^R \int_{\mathbb{S}} \left|\frac{d}{dr}\left(f(ry)\right)\right|^2 r^{Q-1}d\sigma(y)dr$$

$$= \int_{\mathrm{B}_R} |\mathcal{R}_{|x|}f(x)|^2 dx - \frac{(Q-1)(Q-2)}{2}\int_{\mathrm{B}_R}\frac{|f(x)|^2}{|x|^2}dx. \quad (12)$$

Now, we calculate I_2 :

$$I_2 = -\frac{Q-2}{2}\mathrm{Re}\int_0^{\mathrm{R}}\int_{\mathbb{S}} f(ry)\overline{\frac{d}{dr}\left(r^{-1}f(ry)\right)}r^{Q-1}d\sigma(y)dr$$

$$= \frac{Q-2}{2}\int_0^{\mathrm{R}}\int_{\mathbb{S}} |f(ry)|^2 r^{Q-3}d\sigma(y)dr$$

$$-\frac{Q-2}{2}\mathrm{Re}\int_0^{\mathrm{R}}\int_{\mathbb{S}} f(ry)\overline{\frac{d}{dr}f(ry)}r^{Q-2}d\sigma(y)dr$$

$$= \frac{Q-2}{2}\int_0^{\mathrm{R}}\int_{\mathbb{S}} |f(ry)|^2 r^{Q-3}d\sigma(y)dr$$

$$-\frac{Q-2}{4}\int_0^{\mathrm{R}}\int_{\mathbb{S}} \frac{d}{dr}|f(ry)|^2 r^{Q-2}d\sigma(y)dr$$

$$= \left(\frac{Q-2}{2}+\frac{(Q-2)^2}{4}\right)\int_0^{\mathrm{R}}\int_{\mathbb{S}} |f(ry)|^2 r^{Q-3}d\sigma(y)dr$$

$$= \left(\frac{Q-2}{2}+\frac{(Q-2)^2}{4}\right)\int_{\mathrm{B}_R} \frac{|f(x)|^2}{|x|^2}dx. \tag{13}$$

For I_3, one has

$$\mathrm{I}_3 = -\frac{1}{2}\mathrm{Re}\int_0^{\mathrm{R}}\int_{\mathbb{S}} f(ry)\overline{\frac{d}{dr}\left(r^{-1}\left(\ln\frac{R}{r}\right)^{-1}f(ry)\right)}r^{Q-1}d\sigma(y)dr$$

$$= \frac{1}{2}\int_0^{\mathrm{R}}\int_{\mathbb{S}} |f(ry)|^2 r^{Q-3}\left(\ln\frac{R}{r}\right)^{-1}d\sigma(y)dr$$

$$-\frac{1}{2}\int_0^{\mathrm{R}}\int_{\mathbb{S}} |f(ry)|^2 r^{Q-3}\left(\ln\frac{R}{r}\right)^{-2}d\sigma(y)dr$$

$$-\frac{1}{4}\int_0^{\mathrm{R}}\int_{\mathbb{S}} \frac{d}{dr}|f(ry)|^2 r^{Q-2}\left(\ln\frac{R}{r}\right)^{-1}d\sigma(y)dr$$

$$= \frac{1}{2}\int_0^{\mathrm{R}}\int_{\mathbb{S}} |f(ry)|^2 r^{Q-3}\left(\ln\frac{R}{r}\right)^{-1}d\sigma(y)dr$$

$$-\frac{1}{2}\int_0^{\mathrm{R}}\int_{\mathbb{S}} |f(ry)|^2 r^{Q-3}\left(\ln\frac{R}{r}\right)^{-2}d\sigma(y)dr$$

$$+\frac{Q-2}{4}\int_0^{\mathrm{R}}\int_{\mathbb{S}} |f(ry)|^2 r^{Q-3}\left(\ln\frac{R}{r}\right)^{-1}d\sigma(y)dr$$

$$+\frac{1}{4}\int_0^{\mathrm{R}}\int_{\mathbb{S}}|f(ry)|^2 r^{Q-3}\left(\ln\frac{R}{r}\right)^{-2}d\sigma(y)dr$$

$$=\frac{Q}{4}\int_0^{\mathrm{R}}\int_{\mathbb{S}}|f(ry)|^2 r^{Q-3}\left(\ln\frac{R}{r}\right)^{-1}d\sigma(y)dr$$

$$-\frac{1}{4}\int_0^{\mathrm{R}}\int_{\mathbb{S}}|f(ry)|^2 r^{Q-3}\left(\ln\frac{R}{r}\right)^{-2}d\sigma(y)dr$$

$$=\frac{Q}{4}\int_{\mathrm{B}_R}\frac{|f(x)|^2}{|x|^2}\left(\ln\frac{R}{|x|}\right)^{-1}dx-\frac{1}{4}\int_{\mathrm{B}_R}\frac{|f(x)|^2}{|x|^2}\left(\ln\frac{R}{|x|}\right)^{-2}dx. \tag{14}$$

Finally for I_4 we obtain:

$$I_4=-\frac{Q}{2}\mathrm{Re}\int_0^{\mathrm{R}}\int_{\mathbb{S}}f(ry)r^{-1}\overline{\frac{d}{dr}f(ry)r^{Q-1}}d\sigma(y)dr$$

$$+\frac{1}{2}\mathrm{Re}\int_0^{\mathrm{R}}\int_{\mathbb{S}}f(ry)r^{-1}\left(\ln\frac{R}{r}\right)^{-1}\overline{\frac{d}{dr}f(ry)r^{Q-1}}d\sigma(y)dr$$

$$=-\frac{Q}{4}\int_0^{\mathrm{R}}\int_{\mathbb{S}}\frac{d}{dr}|f(ry)|^2 r^{Q-2}d\sigma(y)dr$$

$$+\frac{1}{4}\int_0^{\mathrm{R}}\int_{\mathbb{S}}\frac{d}{dr}|f(ry)|^2 r^{Q-2}\left(\ln\frac{R}{r}\right)^{-1}d\sigma(y)dr$$

$$=\frac{Q(Q-2)}{4}\int_0^{\mathrm{R}}\int_{\mathbb{S}}|f(ry)|^2 r^{Q-3}d\sigma(y)dr$$

$$-\frac{Q-2}{4}\int_0^{\mathrm{R}}\int_{\mathbb{S}}|f(ry)|^2 r^{Q-3}\left(\ln\frac{R}{r}\right)^{-1}d\sigma(y)dr$$

$$-\frac{1}{4}\int_0^{\mathrm{R}}\int_{\mathbb{S}}|f(ry)|^2 r^{Q-3}\left(\ln\frac{R}{r}\right)^{-2}d\sigma(y)dr$$

$$=\frac{Q(Q-2)}{4}\int_{\mathrm{B}_R}\frac{|f(x)|^2}{|x|^2}dx-\frac{(Q-2)}{4}\int_{\mathrm{B}_R}\frac{|f(x)|^2}{|x|^2}\left(\ln\frac{R}{|x|}\right)^{-1}dx$$

$$-\frac{1}{4}\int_{\mathrm{B}_R}\frac{|f(x)|^2}{|x|^2}\left(\ln\frac{R}{|x|}\right)^{-2}dx. \tag{15}$$

Putting (11)-(15) in (10) we obtain that

$$\int_{\mathrm{B}_R} |\mathcal{R}_{|x|}f(x)|^2dx - \frac{(Q-2)^2}{4}\int_{\mathrm{B}_R}\frac{|f(x)|^2}{|x|^2}dx - \frac{1}{4}\int_{\mathrm{B}_R}\frac{|f(x)|^2}{|x|^2}\left(\ln\frac{R}{|x|}\right)^{-2}dx = \int_{\mathrm{B}_R}|(Tf)(x)|^2dx, \tag{16}$$

that is,

$$\int_{\mathrm{B}_R} |\mathcal{R}_{|x|}f(x)|^2dx = \frac{(Q-2)^2}{4}\int_{\mathrm{B}_R}\frac{|f(x)|^2}{|x|^2}dx + \frac{1}{4}\int_{\mathrm{B}_R}\frac{|f(x)|^2}{|x|^2}\left(\ln\frac{R}{|x|}\right)^{-2}dx + \int_{\mathrm{B}_R}|(Tf)(x)|^2dx. \tag{17}$$

Caffarelli-Kohn-Nirenberg type inequalities on homogeneous Lie groups

Theorem 2. Let $\mathbb{G}$ be a homogeneous Lie group of homogeneous dimension Q. Let $|\cdot|$ be be any homogeneous quasi-norm on $\mathbb{G}$. Let $1 < q < \infty, 0 < r < \infty$ with $2 + q \geq r, \delta \in [0,1] \cap \left[\frac{r-q}{r}, \frac{2}{r}\right]$ and $b, c \in \mathbb{R}$. Assume that $\frac{\delta r}{2} + \frac{(1-\delta)r}{q} = 1$ and $c = \delta + b(1-\delta)$. Then for all $f \in C_0^\infty(\mathrm{B}_R\backslash\{0\})$ we have the following Caffarelli-Kohn-Nirenberg type inequalities:

$$\|\omega^c f\|_{L^r(\mathbb{G})} \leq \left\|\mathcal{R}_{|x|}f\right\|^{\delta}_{L^2(\mathbb{G})}\|\omega^b f\|^{1-\delta}_{L^q(\mathbb{G})}, \tag{18}$$

where $\omega = \dfrac{\left(\frac{(Q-2)^2}{4} + \frac{1}{4}\left(\ln\frac{R}{|x|}\right)^{-2}\right)^{\frac{1}{2}}}{|x|}$.

Proof of Theorem 2. Case $\delta \in [0,1] \cap \left[\frac{r-q}{r}, \frac{2}{r}\right]$. Recalling $c = \delta + b(1-\delta)$, a direct calculation gives

$$\|\omega^c f\|_{L^r(\mathbb{G})} = \left(\int_{\mathbb{G}} |\omega|^{cr}|f(x)|^r dx\right)^{\frac{1}{r}} = \left(\int_{\mathbb{G}} \frac{|f(x)|^{\delta r}}{|\omega|^{-\delta r}} \cdot \frac{|f(x)|^{(1-\delta)r}}{|\omega|^{-br(1-\delta)}}dx\right)^{\frac{1}{r}}. \tag{19}$$

We want to use Holder's inequality for $\frac{\delta r}{2} + \frac{(1-\delta)r}{q} = 1$ and $2 + q \geq r$.

Then using Hölder's inequality in (19) we get following:

$$\|\omega^c f\|_{L^r(\mathbb{G})} \leq \left(\int_{\mathbb{G}} \frac{|f(x)|^2}{|\omega|^{-2}}dx\right)^{\frac{\delta}{2}}\left(\int_{\mathbb{G}} \frac{|f(x)|^q}{|\omega|^{-bq}}dx\right)^{\frac{1-\delta}{q}} = \|\omega f\|^{\delta}_{L^2(\mathbb{G})}\left\|\frac{f}{\omega^{-b}}\right\|^{1-\delta}_{L^q(\mathbb{G})}. \tag{20}$$

From Theorem 1 we have

$$\left\|\mathcal{R}_{|x|}f\right\|_{L^2(\mathrm{B}_R)} \geq \left\|\frac{f(x)}{|x|}\left(\frac{(Q-2)^2}{4} + \frac{1}{4}\left(\ln\frac{R}{|x|}\right)^{-2}\right)^{\frac{1}{2}}\right\|_{L^2(\mathrm{B}_R)}. \tag{21}$$

Recalling $\omega(x) = \frac{\left(\frac{(Q-2)^2}{4} + \frac{1}{4}\left(\ln\frac{R}{|x|}\right)^{-2}\right)^{\frac{1}{2}}}{|x|}$, we can rewrite it as

$$\left\|\mathcal{R}_{|x|}f\right\|_{L^2(\mathrm{B}_R)} \geq \|\omega f\|_{L^2(\mathrm{B}_R)}. \tag{22}$$

Using (22) in (20) gives the desired inequality (18).

Conclusion

Finally, in this note we have established a unified result that contains both the critical and subcritical Hardy inequalities. Moreover, as a byproduct Caffarelli-Kohn-Nirenberg type inequality is obtained.

Acknowledgement

This research is funded by the Committee of Science of the Ministry of Science and Higher Education of the Republic of Kazakhstan (Grant No. AP14871691).

REFERENCES

1 Balinsky A.A., Evans W.D., Lewis, R.T. The analysis and geometry of Hardy's inequality, vol. 1, 2015, Cham: Springer.

2 Kufner A., Maligranda L., Persson L. E. The Hardy inequality: About its history and some related results, 2007, Vydavatelský servis.

3 Kufner A., Persson L.E., Samko N. Weighted inequalities of Hardy type. Second edition, 2017.

4 Opic B., Kufner A. Hardy-Type Inequalities, Pitman Research Notes in Mathematics Series, vol. 219, 1990, Longman Scientific & Technical, Harlow.

5 Ruzhansky M., Suragan D. Hardy inequalities on homogeneous groups: 100 years of Hardy inequalities, p. 571, 2019, Springer Nature (open access book).

6 Gesztesy F., Littlejohn L.L. Factorizations and Hardy-Rellich-type inequalities. Non-linear partial differential equations, mathematical physics, and stochastic analysis, pp. 207–226, 2018, EMS Ser. Congr. Rep., Eur. Math. Soc., Zürich, 186–1.

7 Gesztesy F. On non-degenerate ground states for Schrödinger operators. Reports on mathematical physics, vol. 20(1), pp. 93–109, 1984.

8 Gesztesy F., Pittner L. A generalization of the virial theorem for strongly singular potentials. Reports on Mathematical Physics, vol.18(2), pp. 149–162, 1980.

9 Gesztesy F., Littlejohn L.L., Michael I., Pang M.M. Radial and logarithmic refinements of Hardy's inequality. St. Petersburg Math. J, vol. 30(3), pp. 429–436.

10 Ruzhansky M., Yessirkegenov N. Factorizations and Hardy–Rellich inequalities on stratified groups. Journal of Spectral Theory, vol. 10(4), pp. 1361–1411, 2020.

11 Folland G.B., Stein E.M. Hardy spaces on homogeneous groups, volume 28 of Mathematical Notes. Princeton University Press, Princeton, N.J., University of Tokyo Press, Tokyo, 1982.

12 Fischer V., Ruzhansky M. Quantization on nilpotent Lie groups, vol. 314 of Progress in Mathematics. Birkh¨auser, 2016 (open access book).

[1,2*]Апсеит Қ.,
магистр, ORCID ID: 0000-0002-2049-2984,
*e-mail: kuralay.apseit@sdu.edu.kz

[3]Есиркегенов Н.
PhD, ORCID ID: 0000-0002-2985-2288,
e-mail: nurgissa.yessirkegenov@gmail.com

[1]СДУ университеті, 040900, Қаскелен, Қазақстан,
[2]Математика және математикалық модельдеу институты,
050010, Алматы қ., Қазақстан
[3]КИМЭП университеті, 050010, Алматы қ., Қазақстан

ФАКТОРИЗАЦИЯ ЖӘНЕ БІРТЕКТІ ЛИ ТОПТАРЫНДАҒЫ БІРТҰТАС ХАРДИ ТЕҢСІЗДІГІ

Аңдатпа

Бұл мақалада біртекті квазинормалармен біртұтас Харди теңсіздіктері мен критикалық Харди теңсіздіктері зерттеледі. Жұмыста осы нәтижелер үшін нақты қалдық формулалары беріледі. Алынған теңдеулер классикалық аналогтардың жетілдірілген нұсқаларын қамтиды және радиалды туынды операторы үшін кез келген біртекті квазинормамен сәйкес келетін Харди теңсіздіктері мен критикалық Харди теңсіздіктерін қамтиды. Сонымен қатар, Фолланд пен Стейннің біртекті Ли топтарының құрылымындағы нәтижелерді кеңейтуді талқылаймыз. Жалпылама тұжырым тек топтық және кеңейтілген құрылымдарға тәуелді гармоникалық талдау нәтижелерін жалпылау үшін ыңғайлы және бұл бағытта жұмыс істеудегі басты мотивацияларымыздың бірі. Жұмыстағы негізгі әдіс Гестези мен Литтлджон ұсынған дифференциалды операторды факторизациялау әдісіне негізделген. Қолданысы ретінде, жалпы салмақтары бар Каффарелли-Кон-Ниренберг типті теңсіздіктер көрсетілген. Кез келген біртекті квазинорманы еркін таңдаудың арқасында біздің нәтижелеріміз маңызды артықшылықтарға ие, өйткені олар $\mathbb{R}^n$ анизотропты кеңістігіне де, $\mathbb{R}^n$ изотропты кеңістігіне де қолданылады.

Тірек сөздер: факторизация әдісі, Харди теңсіздігі, біртекті Ли тобы.

[1,2*]Апсеит К.,
магистр, ORCID ID: 0000-0002-2049-2984,
*e-mail: kuralay.apseit@sdu.edu.kz

[3]Есиркегенов Н.,
PhD, ORCID ID: 0000-0002-2985-2288,
e-mail: nurgissa.yessirkegenov@gmail.com

[1]Университет СДУ, 040900, Каскелен, Казахстан,
[2]Институт математики и математического моделирования,
050010, г. Алматы, Казахстан
[3]Университет КИМЭП, 050010, г. Алматы, Казахстан

ФАКТОРИЗАЦИЯ И ЕДИНООБРАЗНЫЕ НЕРАВЕНСТВА ХАРДИ НА ОДНОРОДНЫХ ГРУППАХ ЛИ

Аннотация

В этой работе мы получаем неравенства Харди и критические неравенства Харди с любой однородной квазинормой единым способом. На самом деле мы показываем формулу точного остатка для этих резуль-

татов. В частности, наше тождество подразумевает соответствующие неравенства Харди и критические неравенства Харди с любой однородной квазинормой для оператора радиальной производной, что дает улучшенные версии соответствующих классических аналогов. Более того, мы обсуждаем расширение этих результатов в контексте однородных групп Ли Фолланда и Штейна. Такая более общая постановка удобна для обобщения результатов гармонического анализа, зависящих только от групповой и расширяющих структур, что является одной из наших мотиваций при работе в этой среде. Наш подход основан на методе факторизации дифференциальных операторов, предложенном Гестези и Литтлджоном. В качестве приложения мы показываем неравенства типа Каффарелли-Кона-Ниренберга с более общим весом. Благодаря свободе выбора с любой однородной квазинормы наши результаты уже дают значительные преимущества, так как они применимы как к анизотропному пространству $\mathbb{R}^n$, так и к изотропному пространству $\mathbb{R}^n$.

Ключевые слова: метод факторизации, неравенство Харди, однородная группа Ли.

Article submission date: 15.05.2024

UDC 517.957
IRSTI 27.31.15, 27.31.21

https://doi.org/10.55452/1998-6688-2024-21-3-158-164

[1*]Shaikhova G.N.,
PhD, associate professor, ORCID ID: 0000-0002-0819-5338,
*e-mail: g.shaikhova@gmail.com
[1]Serikbayev N.S.,
PhD, associate professor, ORCID ID: 0000-0002-1259-637X,
e-mail: ns.serikbayev@gmail.com
[1]Burgumbayeva S.K.,
PhD, associate professor, ORCID ID: 0000-0003-2334-7405,
e-mail: burgumbayeva_sk@enu.kz

[1]L.N. Gumilyov Eurasian National University, 010000, Astana, Kazakhstan

ANALYTICAL SOLUTIONS OF THE NONLOCAL NONLINEAR SCHRÖDINGER-TYPE EQUATIONS

Abstract

In physics, nonlinear equations are applied to characterize the varied phenomena. Usually, the nonlinear equations are presented by nonlinear partial differential equations, that can be received as conditions for the compatibility of two linear differential equations, named the Lax pairs. The presence of the Lax pair determines integrability for the nonlinear partial differential equation. Linked to this development was the realization that certain coherent structures, known as solitons, which play a fundamental role in nonlinear phenomena as lattice dynamics, nonlinear optics, and fluid mechanics. One of the famous equations is the nonlinear Schrödinger equation which is associated with various physical phenomena in nonlinear optics and Bose-Einstein condensates. This equation allows the Lax pair thus it is integrable. This work investigates nonlocal nonlinear Schrödinger-type equations with PT symmetry. Nonlocal nonlinear equations arise in various physical contexts as fluid dynamics, condensed matter physics, optics, and so on. We introduce the Lax pair formulation for the nonlocal nonlinear Schrödinger-type equations. The method of the Darboux transformation is applied to receive analytical solutions.

Key words: Schrodinger-type equations, Darboux transformation, nonlocal, Lax pair, analytical solution, symmetry.

Introduction

The nonlinear partial differential equations (NPDE) are studied in several works [1–2]. One of the famous equations is the nonlinear Schrödinger equation (NLSE). This equation is a universal model, that describes the evolution of quasi-monochromatic and weakly nonlinear wave trains in media with cubic nonlinearities. In optics, the NLSE is the main model that characterizes the propagation of optical waves in Kerr media [3]. Various generalizations and modifications for the NLSE are studied. For example, in [4] for the unstable NLSE the exact solutions are found by the improved modified Sardar sub-equation method. The derivative nonlinear Schrödinger hierarchy is studied in [5]. In work [6] dynamics of optical solitons in the fifth-order nonlinear Schrödinger equation is investigated.

The most part of NPDEs is local. This denotes that the local solution evolution relies only on the local solution value and its local space and time derivatives. Latterly, the one-dimensional nonlocal equations are studied in [7–9]. The primary one-dimensional nonlocal equation was the PT-symmetric nonlinear Schrödinger equation (NLSE) [10–12]. At present time there are different methods to explore the NPDE, such as the method of the Darboux transformation (DT) [13–18], the

extended tanh method [19, 20], the bilinear Hirota method [21–23], the sine-cosine [24, 25], and others.

In this research, the nonlocal nonlinear Schrödinger-type equations are studied

$$iq_t(x,y,t) + q_{xy}(x,y,t) - v(x,y,t)q(x,y,t) + \alpha q(x,y,t) - i\beta q_x(x,y,t) = 0, \quad (1)$$

$$v_x(x,y,t) + 2(q(x,y,t)q^*(-x,-y,t))_y = 0, \quad (2)$$

where q, v are functions, α, β are constants, * means a complex conjugate. Eqs. (1)–(2) suppose the following reductions:

If $\alpha = 0, \beta = 0$, and local case $r = q^*(x,y,t)$ we get the two-dimensional NLSE:

$$iq_t(x,y,t) + q_{xy}(x,y,t) - v(x,y,t)q(x,y,t) = 0, \quad (3)$$

$$v_x(x,y,t) + 2(q(x,y,t)q^*(x,y,t))_y = 0. \quad (4)$$

Eqs. (3)–(4) are studied in [26] by the sine-cosine method where the researcher found the traveling wave solutions. The conservation laws are obtained in [27].

Classical (local) case $r = q^*(x,y,t)$ of Eqs. (1)-(2) has the following form

$$iq_t(x,y,t) + q_{xy}(x,y,t) - v(x,y,t)q(x,y,t) + \alpha q(x,y,t) - i\beta q_x(x,y,t) = 0, \quad (5)$$

$$v_x(x,y,t) + 2(q(x,y,t)q^*(x,y,t))_y = 0. \quad (6)$$

Various solutions of Eqs. (5)–(6) are obtained in [28] by the bilinear Hirota method and the extended tanh method. However, nonlocal forms for Eqs (5)–(6) have not been found in other studies, which will be the main focus of this paper.

In this work by the Lax pair, we introduce the nonlinear Schrödinger-type equations in nonlocal form with AKNS reduction $r = q^*(-x,-y,t)$. Eqs. (1)–(2) are called PT- symmetric because is invariant under the action if the PT operator, i.e. the joint transformation $x \to -x, y \to -y$. As a method to research we use the Darboux transformation which is an effective tool to solve nonlinear partial differential equations and receive exact solutions for the equations (1)–(2).

Material and methods

In this part, we introduce the Lax pair and the DT for the nonlocal nonlinear Schrödinger-type equations.

Lax pair

The integrability of the nonlinear equation is provided by the Lax pair. Here, we introduce the Lax pair for (1)–(2) which can be presented by the next form

$$\Psi_x = U\Psi, \quad (7)$$

$$\Psi_t = 2\lambda\Psi_y + V\Psi, \quad (8)$$

where $\Psi = (\psi_1(x,y,t), \psi_2(x,y,t))^T$ (T define the transpose of the matrix), λ is const and the matrices V and U have the next expression

$$U = -i\lambda\sigma_3 + U_0, \tag{9}$$

$$V = \lambda V_1 + V_0, \tag{10}$$

with

$$V_0 = \begin{pmatrix} -\frac{iv}{2} + \frac{i\alpha}{2} & iq_y + \beta q \\ iq^*{}_y(-x,-y,t) - \beta q_y^*(-x,-y,t) & \frac{iv}{2} - \frac{i\alpha}{2} \end{pmatrix}, V_1 = \begin{pmatrix} -i\beta & 0 \\ 0 & i\beta \end{pmatrix}.$$

$$U_0 = \begin{pmatrix} 0 & q \\ -q^*(-x,-y,t) & 0 \end{pmatrix}. \qquad \sigma_3 = \begin{pmatrix} 1 & 0 \\ 0 & -1 \end{pmatrix}.$$

Over some calculations by (9)-(10), it can be verified that the zero-curvature condition:

$$U_t - V_x - 2\lambda U_y + UV - VU = 0,$$

directly gives rise to the equations (1)-(2).

Darboux transformation

The following transformation of the equations (1)–(2) based on the DT for the Ablowitz-Kaup-Newell-Segur (AKNS) system

$$\Psi^{[1]} = T\Psi = (\lambda I - P)\Psi,$$

where $P = \begin{pmatrix} p_{11} & p_{12} \\ p_{21} & p_{22} \end{pmatrix}$, $I = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$.

The new function $\Psi^{[1]}$ satisfies

$$\Psi_x^{[1]} = U^{[1]}\Psi^{[1]},$$
$$\Psi_t^{[1]} = 2\lambda\Psi_y^{[1]} + V^{[1]}\Psi^{[1]},$$

where $V^{[1]}$, $U^{[1]}$ rely on $q^{[1]}, v^{[1]}$ and λ. The connection between $q^{[1]}, v^{[1]}$ and $U^{[1]}$-$V^{[1]}$ is similar to the connection between q, v and U -V. Then, it is clear that the Darboux matrix T responds to the equations

$$T_x + TU = U^{[1]}T, \tag{11}$$

$$T_t + TV = 2\lambda T_y + V^{[1]}T. \tag{12}$$

Collecting the different powers of λ^i of the equations (11)–(12) and making some algebraic calculation on (11)–(12), we get a relation among functions $q^{[1]}$ and q:

$$q^{[1]}(x,y,t) = q(x,y,t) - 2ip_{12}, \tag{13}$$
$$q^{*[1]}(-x,-y,t) = q^*(-x,-y,t) - 2ip_{21},$$
$$v^{[1]} = v + 4ip_{11y} = v - 4ip_{22y}. \tag{14}$$

with a constraint $p_{12} = -p_{21}^*(-x,-y,t)$.

Main result

The one-fold Darboux transformation
In this section, we present one-fold Darboux transformation and obtain exact solutions.

Theorem. The one-fold Darboux transformation of the nonlocal nonlinear Schrödinger-type equations (1)-(2) is

$$P = \begin{pmatrix} p_{11} & p_{12} \\ p_{21} & p_{22} \end{pmatrix}, \tag{15}$$

where

$$p_{11} = \frac{1}{\Delta} * (\lambda_1 \psi_1(x,y,t)\psi_1^*(-x,-y,t) - \lambda_1^* \psi_2(x,y,t)\psi_2^*(-x,-y,t)),$$

$$p_{12} = \frac{1}{\Delta} * ((\lambda_1 + \lambda_1^*)\psi_1(x,y,t)\psi_2^*(-x,-y,t)),$$

$$p_{21} = \frac{1}{\Delta} * ((\lambda_1 - \lambda_1^*)\psi_2(x,y,t)\psi_1^*(-x,-y,t)),$$

$$p_{22} = \frac{1}{\Delta} * (\lambda_1 \psi_2(x,y,t)\psi_2^*(-x,-y,t) - \lambda_1^* \psi_1(x,y,t)\psi_1^*(-x,-y,t)),$$

with $\Delta = \psi_1\psi_1^*(-x,-y,t) - \psi_2\psi_2^*(-x,-y,t)$.

Proof.
We now assume that

$$P = H\Lambda H^{-1}, \tag{16}$$

with

$$H = \begin{pmatrix} f_1 & g_1 \\ f_2 & g_2 \end{pmatrix}, \ \Lambda = \begin{pmatrix} \lambda_1 & 0 \\ 0 & \lambda_2 \end{pmatrix}. \tag{17}$$

where $(f_1, f_2)^T = (\psi_1(x,y,t), \psi_2(x,y,t))^T$ is a solution to Eqs. (7)–(8) by $\lambda = \lambda_1$ and $(g_1, g_2)^T = (\psi_2^*(-x,-y,t), \psi_1^*(-x,-y,t))^T$ is the solution in the case $\lambda = -\lambda_1^* = \lambda_2$.
After substitution (17) into (16) and making some calculations, we can obtain the explicit form for the expression for P (15). This completes the proof. □

Therefore, the new solutions (13) and (14) can be written in the following forms

$$q^{[1]}(x,y,t) = q(x,y,t) - \frac{2i(\lambda_1 + \lambda_1^*)\psi_1(x,y,t)\psi_2^*(-x,-y,t)}{\Delta}, \tag{18}$$

$$v^{[1]}(x,y,t) = v(x,y,t) + 4i\left(\frac{\lambda_1\psi_1(x,y,t)\psi_1^*(-x,-y,t) - \lambda_1^*\psi_2(x,y,t)\psi_2^*(-x,-y,t)}{\Delta}\right)_y, \tag{19}$$

with $\Delta = \psi_1\psi_1^*(-x,-y,t) - \psi_2\psi_2^*(-x,-y,t)$

So, in this section, we obtained the one-fold Darboux transformation of the nonlocal nonlinear Schrödinger-type equations (1)–(2). Next, we construct the analytical solutions for Eqs. (1)–(2).

Example 1. We take trivial "seed" solutions of Eqs. (1)–(2) as $q = 0, q^*(-x,-y,t) = 0, v = 0$. Then by substituting these seed solutions in Eqs. (7)–(8) we obtain system in the next form

$$\Psi_{1x} = -i\lambda\Psi_1, \tag{20}$$

$$\Psi_{2x} = i\lambda\Psi_2, \tag{21}$$

$$\Psi_{1t} = 2\lambda\Psi_{1y} - i\lambda\beta\Psi_1 + \frac{i\alpha}{2}\Psi_1, \tag{22}$$

$$\Psi_{2t} = 2\lambda\Psi_{2y} + i\lambda\beta\Psi_2 - \frac{i\alpha}{2}\Psi_2, \tag{23}$$

The system (20)-(23) can have the following solutions

$$\Psi_1 = e^{-i\lambda_1 x + i\mu_1 y + (-i\lambda_1\beta + \frac{i\alpha}{2} + 2i\lambda_1\mu_1)t}, \tag{24}$$

$$\Psi_2 = e^{i\lambda_2 x - i\mu_2 y + (i\lambda_2\beta - \frac{i\alpha}{2} - 2i\lambda_2\mu_2)t}, \tag{25}$$

with $\lambda_1 = a + bi\ \mu_1 = c + id$, $\lambda_2 = -a + bi\ \mu_2 = -c + id$ and d , a, b, c, are const. By substitution Eqs. (24)–(25) into Eqs. (18)–(19) the analytical solutions of the nonlocal nonlinear Schrödinger-type equations can be written as

$$q^{[1]}(x,y,t) = -\frac{4ai e^{\chi}}{e^{\theta_1} - e^{\theta_2}},$$

$$v^{[1]}(x,y,t) = 4\left(\frac{((a+bi)e^{\theta_1} + (a-bi)e^{\theta_2})}{e^{\theta_1} - e^{\theta_2}}\right)_y,$$

where

$$\theta_1 = (-4ad - 4bc + 2\beta b)t - 2iax + 2icy,$$

$$\theta_2 = -2iax + 2icy - 2tb\beta,$$

$$\chi = (\alpha + 4ac - 4bd)t - 2axi + 2bx + 2y(ic - d).$$

Conclusion

Thus, we studied the nonlocal nonlinear Schrödinger-type equations by presenting the Lax pair formulation. We found the one-fold Darboux transformation, and based on what we received the analytical solutions. The obtained result is significant and promising in the context of PT-symmetric systems because the real-valued conserved charges can be given physical meaning.

Acknowledgment

This work is also supported by the Ministry of Science and Higher Education of the Republic of Kazakhstan, grant AP19675202

REFERENCES

1 Ablowitz M. and Segur H. Solitons and the Inverse Scattering Transform, 1981, 438 p. SIAM, Philadelphia.

2 Fokas A.S. and Ablowitz M.J. Physics Review Letter, 1983, vol. 51.

3 Kivshar Y., Agrawal G. P. Optical Solitons: From Fibers to Photonic Crystals, 2003, 540 p., Boston: Academic.

4 Khan M.I., Farooq A., Nisar K., Shah N. Results in Physics, 2024, vol. 59, p. 107593.

5 Kudryashov N.A., Lavrova S.F. Applied Mathematics and Computation, 2024, vol. 477 (15), p. 128802.

6 Feng H., Wang X. Optik, 2022, vol. 264, p. 169350.

7 Ablowitz M. and Musslimani Z. Nonlinearity, 2016, vol. 29, pp. 915–946.

8 Ablowitz M. and Musslimani Z., Physics Review Letter, 2013, vol. 110, p. 064105 (1–5).

9 Ablowitz M. J. and Musslimani Z. H., Stud. Appl. Math., 2017, vol. 139, no.7.
10 Abdullaev F.K., Kartashov Y.V., Konotop V.V. and Zezyulin D.A. Physics Review A, 2011, vol. 83, p. 041805.
11 Fokas A. S. Nonlinearity, 2016, vol. 29, p. 319.
12 Nazarbek Zh., Yersultanova Z.S., and Shaikhova G.N. Bulletin of KazNPU named after Abay, 2019, no. 2 (66), pp. 85–88.
13 Matveev V.B., Salle M.A., Darboux transformations and solitons, 1991, 205 p., Springer-Verlag , Berlin-Heidelberg.
14 Yesmakanova K.R, Shaikhova G.N, Bekova G.T. and Myrzakulova Zh.R., Advances in Intelligent Systems and Computing, 2016, vol. 441, pp. 183–198.
15 Bekova G., Shaikhova G., Yesmakhanova K. and Myrzakulov R. Journal of Physics: Conference Series, 2019, vol. 1416, p. 012003.
16 Bekova G., Shaikhova G. and Yesmakhanova K. J. Phys. Conf. Ser., 2018, vol. 965, p. 012035.
17 Ch. Li, J. He. Science China: Phys. Mech. Astron., 2014, vol. 57(5), p. 898.
18 Yesmakanova K.R., Bekova G., Shaikhova G. AIP Conf. Proc., 2017, vol. 1880, 060022.
19 Wazwaz A.M., Partial Differential Equations and Solitary Waves Theory, 2009, 681 p., Springer-Verlag, Berlin Heidelberg.
20 Wazwaz A.M. Appl. Math. Comput., 2007, vol. 184(2), pp. 1002–1014.
21 Hirota R. The Direct Method in Soliton Theory, 2004, 155 p., Cambridge University Press, Cambridge.
22 Hereman W. and Nuseir A. Math. Comput. Simul., 1997, vol. 43, pp. 13–27.
23 X. Lu, W.X. Ma. Study of lump dynamics based on a dimensionally reduced Hirota bilinear equation. Nonlinear Dyn., 2016, vol. 85, p. 1217.
24 Darvishi M.T. Romanian Reports Physics, 2018, vol. 70(2), pp. 1–12.
25 Wazwaz A.M. Commun. Nonlinear Sci. Numer. Simul., 2006, vol. 11(2), pp. 148–160.
26 Shaikhova G.N. and Kutum B.B. Eurasian Phys. Tech. J., 2020, vol. 17(33), pp. 169–174.
27 Bekova G.T., Shaikhova G.N.,Yesmakhanova K.R., Myrzakulov R. AIP Conference Proceedings, 2019, 2159 (030003).
28 Burdik C., Shaikhova G., and Rakhimzhanov B. European Physical Journal Plus, 2021, vol. 136, p. 1095(1–17).

[1*]Шайхова Г.Н.,
PhD, қауымдастырылған профессор, ORCID ID: 0000-0002-0819-5338,
*e-mail: g.shaikhova@gmail.com
[1]Серикбаев Н.С.,
PhD, қауымдастырылған профессор, ORCID ID: 0000-0002-1259-637X,
e-mail: s.serikbayev@gmail.com
[1]Бургумбаева С.К.,
PhD, қауымдастырылған профессор, ORCID ID: 0000-0003-2334-7405,
e-mail: burgumbayeva_sk@enu.kz

[1]Л.Н. Гумилев атындағы Еуразия ұлттық университеті, 010000, Астана қ., Қазақстан

ШРЕДИНГЕР ТИПТІ ЛОКАЛЬДЫ ЕМЕС СЫЗЫҚТЫҚ ЕМЕС ТЕҢДЕУЛЕРДІҢ АНАЛИТИКАЛЫҚ ШЕШІМДЕРІ

Аңдатпа

Физикада әртүрлі құбылыстарды сипаттау үшін сызықтық емес теңдеулер қолданылады. Әдетте, осы теңдеулер сызықтық емес дербес туынды дифференциалдық теңдеулер болып табылады. Олар Лакс жұптары деп аталатын екі сызықтық дифференциалдық теңдеулердің үйлесімділік шарттары ретінде қабылдануы мүмкін. Лакс жұбының болуы сызықтық емес дербес туынды дифференциалдық теңдеудің интегралдылығын анықтайды. Осы дамумен байланысты тор динамикасы, сызықты емес оптика және сұйықтық механикасы сияқты сызықты емес құбылыстарда негізгі рөл атқаратын солитондар деп аталатын белгілі бір когерентті құрылымдардың жүзеге асырылуы болды. Белгілі теңдеулердің бірі сызықты емес оптикадағы және Бозе-

Эйнштейн конденсатындағы әртүрлі физикалық құбылыстармен байланысты сызықты емес Шредингер теңдеуі болады. Бұл теңдеуде Лакс жұбы бар, сондықтан ол интегралданатын деп аталады. Бұл жұмыс PT симметриясы бар локальды емес сызықтық емес Шредингер типті теңдеулерді зерттейді. Локальды емес сызықтық емес теңдеулер әртүрлі физикалық контекстерде пайда болады, мысалы, гидродинамика, конденсацияланған күй физикасы, оптика және тағы басқа. Локальды емес сызықтық емес Шредингер типті теңдеулер үшін Лакс жұбы ұсынылған. Аналитикалық шешімдерді алу үшін Дарбу түрлендіру әдісі қолданылады.

Тірек сөздер: Шредингер типті теңдеулер, Дарбу түрлендіру, локальды емес, Лакс жұбы, аналитикалық шешім, симметрия.

[1*]Шайхова Г.Н.,
PhD, ассоциированный профессор, ORCID ID: 0000-0002-0819-5338,
*e-mail: g.shaikhova@gmail.com
[1]Серикбаев Н.С.,
PhD, ассоциированный профессор, ORCID ID: 0000-0002-1259-637X,
e-mail: ns.serikbayev@gmail.com
[1]Бургумбаева С.К.,
PhD, ассоциированный профессор, ORCID ID: 0000-0003-2334-7405,
e-mail: burgumbayeva_sk@enu.kz

[1]Евразийский национальный университет имени Л.Н. Гумилева, 010000, г. Астана, Казахстан

АНАЛИТИЧЕСКИЕ РЕШЕНИЯ НЕЛОКАЛЬНЫХ НЕЛИНЕЙНЫХ УРАВНЕНИЙ ТИПА ШРЁДИНГЕРА

Аннотация

В физике нелинейные уравнения применяются для описания различных явлений. Обычно нелинейные уравнения являются в виде нелинейных дифференциальных уравнений в частных производных. Эти уравнения можно принять как условие совместности двух линейных дифференциальных уравнений, называемых представлением Лакса, существование которых определяет интегрируемость нелинейного дифференциального уравнения в частных производных. С этим развитием было связано осознание того, что определенные когерентные структуры, известные как солитоны, играют фундаментальную роль в нелинейных явлениях, таких как динамика решетки, нелинейная оптика и механика жидкости. Одним из известных нелинейных уравнений является нелинейное уравнение Шрёдингера, которое связано с различными физическими явлениями в нелинейной оптике и конденсатах Бозе-Эйнштейна. Это уравнение допускает пару Лакса, поэтому оно интегрируемо. В данной работе исследуются нелинейные нелокальные уравнения типа Шрёдингера с PT-симметрией. Нелинейные нелокальные уравнения возникают в таких областях физики, как гидродинамика, физика конденсированного состояния, оптика и т.д. Представлена пара Лакса для нелинейных нелокальных уравнений типа Шрёдингера. Для получения аналитических решений применен метод преобразования Дарбу.

Ключевые слова: уравнения типа Шрёдингера, преобразование Дарбу, нелокальность, пара Лакса, аналитическое решение, симметрия.

Article submission date: 19.05.2024

ӘОЖ 17.95
ҒТАХР 27.31.44, 27.29.15, 27.41.19

https://doi.org/10.55452/1998-6688-2024-21-3-165-175

[1,2]Искакова Н.Б.,
ф-м.ғ.к., аға ғылыми қызметкер, ORCID ID: 0000-0002-0680-4099,
*e-mail: narkesh77@gmail.com
[1,3,4]Кадирбаева Ж.М.,
ф-м.ғ.к., аға ғылыми қызметкер, ORCID ID: 0000-0001-8861-4100,
e-mail: zhkadirbayeva@gmail.com
[1,3]Бакирова Э.А.,
ф-м.ғ.к., аға ғылыми қызметкер, ORCID ID: 0000-0002-3820-5373,
e-mail: bakirova1974@mail.ru
[2]Қуаныш С.Қ.,
докторант, оқытушы, ORCID ID: 0009-0006-0975-1662,
e-mail: saule270898@gmail.com

[1]Математика және математикалық модельдеу институты, 050010, Алматы қ., Қазақстан
[2]әл-Фараби атындағы Қазақ ұлттық университеті, 050040, Алматы қ., Қазақстан
[3]Қазақ ұлттық қыздар педагогикалық университеті, 050000, Алматы қ., Қазақстан
[4]Халықаралық ақпараттық технологиялар университеті, 050000, Алматы қ., Қазақстан

ПАРАБОЛАЛЫҚ ТЕҢДЕУ ҮШІН ШЕТТІК ЕСЕПТІ ШЕШУДІҢ САНДЫҚ ӘДІСІ

Аңдатпа

Параболалық теңдеу үшін сызықтық шеттік есеп тұйық облыста қарастырылады. Параболалық теңдеу үшін шеттік есеп сынық әдісі негізінде x айнымалысы бойынша u(t,x) белгісіз функциясын дискреттеу арқылы сызықты жай дифференциалдық теңдеулер жүйесі үшін екі нүктелі шеттік есепке айналдырылады. Алынған екі нүктелі шеттік есеп профессор Джумабаевтың параметрлеу әдісімен зерттеледі. Осы әдіс негізінде жай дифференциалдық теңдеулер жүйесі үшін сызықты екі нүктелі шеттік есептің сандық шешімін табу алгоритмі құрылады. Құрылған алгоритм белгілі сандық әдістерді қолдану арқылы іске асырылады. Параметрлеу әдісінің конструктивтілігі мен тиімділігі параболалық теңдеу үшін қарастырылып отырған сызықтық шеттік есептің сандық шешімін құруға мүмкіндік береді. Ұсынылған алгоритмді тексеру және көрсету үшін бір сандық мысал келтіріледі.

Тірек сөздер: параболалық теңдеу, шеттік есеп, алгоритм, сандық шешім, параметрлеу әдісі.

Кіріспе

Параболалық теңдеулер ғылым мен техниканың әртүрлі салаларында кеңінен қолданылады [1–5]. Олар электрондық компоненттерді салқындату жүйелерін жобалауда, жер қыртысындағы жылу ағынын модельдеуде, гипертермиямен қатерлі ісіктерді емдеуде жылу таралуын талдауда, сондай-ақ жылу өткізгіштік сипаттамаларын бақылау арқылы жаңа материалдардың жылу қасиеттерін зерттеуде маңызды рөл атқарады [6–12].

Бұл жұмыста $\Omega = (0,T) \times (0,\omega)$ облысында параболалық теңдеу үшін қойылған келесідей шеттік есеп қарастырылады:

$$\frac{\partial u}{\partial t} = a(t,x)\frac{\partial^2 u}{\partial x^2} + m(t,x)u + f(t,x), \quad (t,x) \in \Omega, \tag{1}$$

$$\mathscr{b}(x)u(0,x)+c(x)u(T,x)=d(x),\quad x\in[0,\omega], \tag{2}$$

$$u(t,0)=\psi_0(t),\quad u(t,\omega)=\psi_1(t),\quad t\in[0,T], \tag{3}$$

мұндағы $a(t,x)\geq\gamma>0$, $m(t,x)\leq 0$, $\mathscr{f}(t,x)$ функциялары $\overline{\Omega}$ облысында, $\mathscr{b}(x)$, $c(x)$, $d(x)$ функциялары $[0,\omega]$ аралығында, $\psi_0(t),\psi_1(t)$ функциялары $[0,T]$ аралығында жеткілікті тегіс және

$$\mathscr{b}(0)\psi_0(0)+c(0)\psi_0(T)=d(0),$$
$$\mathscr{b}(\omega)\psi_1(0)+c(\omega)\psi_1(T)=d(\omega)$$

келісімділік шарттары орындалады.

(1) – (3) параболалық теңдеу үшін қойылған шеттік есептің шешімі деп Ω^- облысында үзіліссіз және t айнымалысы бойынша бірінші ретті және x айнымалысы бойынша екінші ретті үзіліссіз дербес туындылары бар болатын, (1) параболалық теңдеуін, (2) және (3) шарттарын қанағаттандыратын u(t,x) функциясын айтамыз.

(1) – (3) параболалық теңдеу үшін c(x)=0 жағдайындағы сызықтық шеттік есептер [10, 11] жұмыстарында қарастырылады. Сыныктар әдісі негізінде теңдеу коэффициенттері мен шеттік шарттар терминдерінде шешімнің және оның туындыларының бағалаулары [10] жұмысында алынған. Бір кеңістіктік айнымалысы бар параболалық теңдеу үшін сызықтық шеттік есептің шешімінің және x бойынша бірінші туындысының дәлірек коэффициентті бағалаулары [11] жұмысында тағайындалған.

Ұсынылып отырған жұмыстың мақсаты – (1) – (3) параболалық теңдеу үшін сызықтық шеттік есептің шешімін табудың сандық алгоритмін Джумабаевтың параметрлеу әдісі негізінде құру.

Әртүрлі дифференциалдық теңдеулер үшін шеттік есептердің аналитикалық және сандық шешімдерін табуға арналған параметрлеу әдісінің [12, 13] жүзеге асырылуы, конструктивтілігі және оның тиімділігі [14–24] жұмыстарында көрсетілген.

Материалдар мен әдістер

Кез келген $\tau>0$ алып, (1) – (3) шеттік есебінде x айнымалысы бойынша дискреттеу жасалынады: $x_i=i\tau$, $i=\overline{0,N}$, $N\tau=\omega$. Келесі белгілеулерді енгізейік: $u_i(t)=u(t,i\tau)$, $a_i(t)=a(t,i\tau)$, $m_i(t)=m(t,i\tau)$, $\mathscr{f}_i(t)=\mathscr{f}(t,i\tau)$, $\mathscr{b}_i=\mathscr{b}(i\tau)$, $c_i=c(i\tau)$, $d_i=d(i\tau)$, $i=\overline{0,N}$.

Осы белгілеулерді ескере отырып (1) – (3) параболалық теңдеу үшін қойылған шеттік есебін келесідей есеппен алмастырамыз:

$$\frac{du_i}{dt}=a_i(t)\frac{u_{i+1}-2u_i+u_{i-1}}{\tau^2}+m_i(t)u_i+\mathscr{f}_i(t),\quad i=\overline{1,N-1}, \tag{4}$$

$$\mathscr{b}_iu_i(0)+c_iu_i(T)=d_i,\quad i=\overline{0,N}, \tag{5}$$

$$u_0(t)=\psi_0(t),\quad u_N(t)=\psi_1(t),\quad t\in[0,T], \tag{6}$$

мұнда $u_0(t)$ және $u_N(t)$ функциялары белгілі.

Бұл (4) – (6) жай дифференциалдық теңдеулер жүйесі үшін екі нүктелі шеттік есебін векторлық-матрицалық түрде жазайық:

$$\frac{dv}{dt}=\mathcal{A}(t)v+\mathcal{F}(t),\quad v\in\mathbb{R}^{N-1},\quad t\in[0,T), \tag{7}$$

$$\mathcal{B}v(0)+\mathcal{C}v(T)=\varphi,\quad \varphi\in\mathbb{R}^{N-1}, \tag{8}$$

мұндағы $v(t) = \left(u_1(t), u_2(t), \dots, u_{N-1}(t)\right)'$ – белгісіз функция, ал $(N-1) \times (N-1)$ өлшемді $\mathcal{A}(t)$ матрицасы мен $(N-1)$ өлшемді $\mathcal{F}(t)$ векторы $[0,T]$ аралығында үзіліссіз. Мұнда

$$\mathcal{A}(t) = \begin{pmatrix} -\frac{2a_1(t)}{\tau^2} + m_1(t) & \frac{a_1(t)}{\tau^2} & 0 & \cdots & 0 \\ \frac{a_2(t)}{\tau^2} & -\frac{2a_2(t)}{\tau^2} + m_2(t) & \frac{a_2(t)}{\tau^2} & \cdots & 0 \\ 0 & \frac{a_3(t)}{\tau^2} & -\frac{2a_3(t)}{\tau^2} + m_3(t) & \cdots & 0 \\ \cdots & \cdots & \cdots & \cdots & \cdots \\ 0 & 0 & 0 & \cdots & -\frac{2a_{N-1}(t)}{\tau^2} + m_{N-1}(t) \end{pmatrix},$$

$$\mathcal{F}(t) = \begin{pmatrix} \frac{a_1(t)}{\tau^2}\psi_0(t) + f_1(t) \\ f_2(t) \\ f_3(t) \\ \cdots \\ \frac{a_{N-1}(t)}{\tau^2}\psi_1(t) + f_{N-1}(t) \end{pmatrix}, \quad \varphi = \begin{pmatrix} d_1 \\ d_2 \\ d_3 \\ \cdots \\ d_{N-1} \end{pmatrix},$$

$$\mathcal{B} = \begin{pmatrix} b_1 & 0 & 0 & \cdots & 0 \\ 0 & b_2 & 0 & \cdots & 0 \\ 0 & 0 & b_3 & \cdots & 0 \\ \cdots & \cdots & \cdots & \cdots & \cdots \\ 0 & 0 & 0 & \cdots & b_{N-1} \end{pmatrix}, \quad \mathcal{C} = \begin{pmatrix} c_1 & 0 & 0 & \cdots & 0 \\ 0 & c_2 & 0 & \cdots & 0 \\ 0 & 0 & c_3 & \cdots & 0 \\ \cdots & \cdots & \cdots & \cdots & \cdots \\ 0 & 0 & 0 & \cdots & c_{N-1} \end{pmatrix}.$$

(7), (8) жай дифференциалдық теңдеулер жүйесі үшін екі нүктелі шеттік есебінің шешімі деп (7) жай дифференциалдық теңдеуін және (8) шеттік шартын қанағаттандыратын $v^*(t) \in C([0,\ T], \mathbb{R}^{N-1})$ функциясын атаймыз.

Негізгі ережелер

(7), (8) жай дифференциалдық теңдеулер жүйесі үшін екі нүктелі шеттік есебін шешу үшін профессор Джумабаев ұсынған параметрлеу әдісін қолданайық. Бұл әдістің схемасы бойынша берілген $[0,T]$ аралығын ішкі бөліктерге бөлейік:

$$[0,T) = \bigcup_{s=1}^{M} [t_{s-1}, t_s).$$

$C\left([0,T], t_s, \mathbb{R}^{M(N-1)}\right)$ арқылы $v[t] = \left(v_1(t), v_2(t), \dots, v_M(t)\right)$ функциялар жүйесінен тұратын кеңістігін белгілейміз, мұнда:

1) $v_s: [t_{s-1}, t_s) \to \mathbb{R}^{N-1}$ функциялары $t \in [t_{s-1}, t_s),\ \ s = \overline{1,M},$ аралықтарында үзіліссіз;

2) $\forall\ s = \overline{1,M}\ \ \exists\ \lim\limits_{t \to t_s - 0} v_s(t)$.

(7), (8) есебіндегі $v(t)$ функциясының $t \in [t_{s-1}, t_s),\ \ s = \overline{1,M},$ аралықтарына сығылуын $v_s(t)$ деп белгілеп алып, қосымша $k_s = v_s(t_{s-1}), s = \overline{1,M},$ параметрлерін енгізіп алайық. Сосын әрбір ішкі $[t_{s-1}, t_s),\ \ s = \overline{1,M},$ аралықтарында $y_s(t) = v_s(t) - k_s, s = \overline{1,M},$ алмастыруларын жасаймыз да, (7), (8) есебіне пара-пар болатын төмендегідей параметрлері бар шеттік есебін аламыз:

$$\frac{dy_s}{dt} = \mathcal{A}(t)(y_s + k_s) + \mathcal{F}(t),\ t \in [t_{s-1}, t_s),\ \ s = \overline{1,M}, \tag{9}$$

$$y_s(t_{s-1}) = 0, \qquad s = \overline{1,M}, \tag{10}$$

$$\mathcal{B}\hbar_1 + \mathcal{C}\hbar_M + \mathcal{C}\lim_{t\to T-0} y_M(t) = \varphi, \tag{11}$$

$$\hbar_s + \lim_{t\to t_s-0} y_s(t) = \hbar_{s+1}, \ \ s = \overline{1,M-1}. \tag{12}$$

(9) – (12) параметрлері бар шеттік есебінің шешімі деп $\hbar^* = (\hbar_1^*, \dots, \hbar_M^*) \in \mathbb{R}^{M(N-1)}$, $y^*[t] = \left(y_1^*(t), \dots, y_M^*(t)\right) \in C\left([0,T], t_s, \mathbb{R}^{M(N-1)}\right)$ элементтерімен $(y^*[t], \hbar^*)$ жұбын айтамыз, бұл жерде $y_s^*(t)$ функциялары $[t_{s-1}, t_s)$, $s = \overline{1,M}$, ішкі аралықтарында үзіліссіз дифференциалданады және (9) дифференциалдық теңдеулерін, $\hbar_s = \hbar_s^*$, $s = \overline{1,M}$, болғанда (10) – (12) шарттарын қанағаттандырады.

(7), (8) есебі мен (9) – (12) параметрлері бар шеттік есебі пара-пар. Егер $v^*(t)$ функциясы (7), (8) есебінің шешімі болса, онда $(y^*[t], \hbar^*)$ жұбы, мұндағы

$$y^*[t] = \left(v^*(t) - v^*(t_0), v^*(t) - v^*(t_1), \dots, v^*(t) - v^*(t_{M-1})\right),$$
$$\hbar^* = \left(v^*(t_0), v^*(t_1), \dots, v^*(t_{M-1})\right)$$

(9) – (12) параметрлері бар шеттік есебінің шешімі болады. Керісінше, егер де $\left(\hat{y}[t], \hat{\hbar}\right)$ жұбы (9) – (12) параметрлері бар шеттік есебінің шешімі болса, онда

$$\hat{v}(t) = \hat{\hbar}_s + \hat{y}_s(t), \ t \in [t_{s-1}, t_s), \ s = \overline{1,M},$$
$$\hat{v}(T) = \hat{\hbar}_M + \lim_{t\to T-0} \hat{y}_M(t),$$

теңдіктерімен анықталатын $\hat{v}(t)$ функциясы (7), (8) есебінің шешімі болады.

Нәтижелер мен талқылау

Қосымша $\hbar_s = v_s(t_{s-1})$, $s = \overline{1,M}$, параметрлерін енгізу $y[t] = (y_1(t), y_2(t), \dots, y_M(t))$ функциялар жүйесінің компоненттері үшін (10) шарттарын алуға мүмкіндік берді және де (9), (10) есептері $\hbar_s$, $s = \overline{1,M}$, параметрлерінің бекітілген мәндерінде Коши есептері болады. $[t_{s-1}, t_s)$, $s = \overline{1,M}$, ішкі аралықтарында бұл Коши есептері жеке шешіледі. Бұл Коши есептерінің шешімдерін табу үшін іргелі матрица қолданылады.

(9), (10) Коши есебінің шешімін $\mathcal{X}(t)$ – іргелі матрицасын қолданып жазайық:

$$y_s(t) = \mathcal{X}(t) \int_{t_{s-1}}^{t} \mathcal{X}^{-1}(\xi)\mathcal{A}(\xi)d\xi \cdot \hbar_s + \mathcal{X}(t) \int_{t_{s-1}}^{t} \mathcal{X}^{-1}(\xi)\mathcal{F}(\xi)d\xi, \tag{13}$$
$$t \in [t_{s-1}, t_s), \quad s = \overline{1,M}.$$

Осы соңғы (13) өрнегін (11) және (12) шарттарына қояйық:

$$\mathcal{B}\hbar_1 + \mathcal{C}\hbar_M + \mathcal{C}\mathcal{X}(T) \int_{t_{M-1}}^{T} \mathcal{X}^{-1}(\xi)\mathcal{A}(\xi)d\xi \cdot \hbar_M =$$
$$= \varphi - \mathcal{C}\mathcal{X}(T) \int_{t_{M-1}}^{T} \mathcal{X}^{-1}(\xi)\mathcal{F}(\xi)d\xi, \tag{14}$$

$$\begin{aligned} &\hbar_s + \mathcal{X}(t_s)\int\limits_{t_{s-1}}^{t_s} \mathcal{X}^{-1}(\xi)\mathcal{A}(\xi)d\xi \cdot \hbar_s - \hbar_{s+1} = \\ &= -\mathcal{X}(t_s)\int\limits_{t_{s-1}}^{t_s} \mathcal{X}^{-1}(\xi)\mathcal{F}(\xi)d\xi\,, \quad s = \overline{1, M-1}. \end{aligned} \tag{15}$$

Бұл (14), (15) жүйесі арқылы $\hbar \in \mathbb{R}^{M(N-1)}$ белгісіз параметрлерін табуға болады. Осы (14), (15) жүйесін $O \in \mathbb{R}^{N-1,N-1}$ нөлдік матрица, $\underset{t}{I} \in \mathbb{R}^{N-1,N-1}$ бірлік матрица және

$$z_r(P,t) = \mathcal{X}(t)\int\limits_{t_{r-1}} \mathcal{X}^{-1}(\xi)P(\xi)d\xi\,, \quad r = \overline{1,M},$$

белгілеулерін ескере отырып келесідей түрде жинақтап жазайық:

$$Q\hbar = F, \quad \hbar \in \mathbb{R}^{M(N-1)}, \tag{16}$$

мұндағы

$$Q = \begin{bmatrix} \mathcal{B} & O & O & \cdots & O & \mathcal{C} + \mathcal{C}z_M(\mathcal{A},T) \\ I + z_1(\mathcal{A},t_1) & -I & O & \cdots & O & O \\ O & I + z_2(\mathcal{A},t_2) & -I & \cdots & O & O \\ \cdots & \cdots & \cdots & \cdots & \cdots & \cdots \\ O & O & O & \cdots & -I & O \\ O & O & O & \cdots & I + z_{M-1}(\mathcal{A},t_{M-1}) & -I \end{bmatrix},$$

$$F = \left(\varphi - \mathcal{C}z_M(\mathcal{F},T), -z_1(\mathcal{F},t_1), -z_2(\mathcal{F},t_2), \cdots, -z_{M-1}(\mathcal{F},t_{M-1})\right)'.$$

(7), (8) шеттік есебінің шешілімділігі алынған (16) жүйесінің шешілімділігіне пара-пар екені айқын.

Ұсынылып отырған сандық алгоритм (16) жүйені құрып және осы жүйені шешуге негізделген. Бұл (16) жүйенің коэффициенттері мен оң жағы Коши есептерінің шешімі ретінде табылады.

(7), (8) есебін сандық шешу алгоритмі:

1^0. $0 = t_0 < t_1 < \cdots < t_{M-1} < t_M = T$ аралығын қарастырамыз. Әрбір $[t_{s-1}, t_s)$, $s = \overline{1,M}$, ішкі аралығын $h_s = \frac{t_s - t_{s-1}}{k}$, $k \in \mathbb{N}$, қадаммен ішкі бөліктерге бөлеміз.

2^0. (16) жүйедегі Q матрицасы мен F векторын есептеу үшін әрбір ішкі аралықта h_s қадаммен $z_s(\mathcal{A}, h_s)$, $z_s(\mathcal{F}, h_s)$, $s = \overline{1,M}$, мәндерін төртінші ретті Рунге-Кутта әдісін қолданып табамыз.

3^0. Сонда келесі жуық жүйені аламыз:

$$Q_*^{\tilde{h}}\hbar^{\tilde{h}} = -F_*^{\tilde{h}}, \quad \hbar \in \mathbb{R}^{M(N-1)}, \tag{17}$$

$\hbar^{\tilde{h}}$ – бұл (17) жүйесінің шешімі: $v^{\tilde{h}_r}(t_{s-1}) = \hbar_s^{\tilde{h}}$, $s = \overline{1,\mathrm{M}}$.

4^0. Шешімнің ішкі аралықтардың қалған нүктелеріндегі жуық мәндерін келесідей Коши есептерін шешу арқылы табамыз:

$$\frac{dv}{dt} = \mathcal{A}(t)v + \mathcal{F}(t), \quad v(t_{s-1}) = \hbar_s^{\tilde{h}}, \quad [t_{s-1}, t_s), \quad s = \overline{1,M}. \tag{18}$$

Соңғы (18) Коши есептерін де төртінші ретті Рунге-Кутта әдісінің көмегімен шешіп, (7), (8) жай дифференциалдық теңдеулер жүйесі үшін екі нүктелі шеттік есебінің сандық шешімін табамыз.

Егер $v^{\star}\left(t_j^{\tilde{h}}\right) = \left(u_1^{\star}\left(t_j^{\tilde{h}}\right), u_2^{\star}\left(t_j^{\tilde{h}}\right), \dots, u_{N-1}^{\star}\left(t_j^{\tilde{h}}\right)\right)'$, $j = \overline{0,Mk}$, (7), (8) жай дифференциалдық теңдеулер жүйесі үшін екі нүктелі шеттік есебінің сандық шешімі болса, онда $u^{\star}\left(t_j^{\tilde{h}}, s\tau\right) = u_s^{\star}\left(t_j^{\tilde{h}}\right)$, $s = \overline{1, N-1}$, параболалық теңдеу үшін қойылған (1) – (3) шеттік есебінің сандық шешімі болады.

Осы ұсынылып отырған алгоритмнің жүзеге асырылуын көрсететін мысалды қарастырайық.

Мысал. Параболалық теңдеу үшін қойылған келесідей шеттік есепті қарастырайық:

$$\begin{aligned} &\frac{\partial u}{\partial t} = (xt^2 + 1)\frac{\partial^2 u}{\partial x^2} - (x + t)u + t\sin 10\pi t + x\sin 10\pi t + tx^4 + \\ &+x^3 + t^2x^3 - 6t^3x^2 - 6tx + 10\pi\cos 10\pi t, \quad (t,x) \in \left(0, \tfrac{1}{10}\right) \times \left(0, \tfrac{1}{2}\right), \end{aligned} \tag{19}$$

$$xu(0,x) + (x^2 + 1)u\left(\tfrac{1}{10}, x\right) = \tfrac{x^5 + x^3}{10}, \qquad x \in \left[0, \tfrac{1}{2}\right], \tag{20}$$

$$u(t,0) = \sin 10\pi t, \qquad u\left(t, \tfrac{1}{2}\right) = \tfrac{t}{8} + \sin 10\pi t, \qquad t \in \left[0, \tfrac{1}{10}\right]. \tag{21}$$

Параболалық теңдеу үшін қойылған (19) – (21) шеттік есебінің дәл шешімі: $u^*(t,x) = x^3 t + \sin 10\pi t$.

$\tau = 0.1$ деп алып, (19) – (21) есебінде x айнымалысы бойынша дискреттеу жасаймыз: $x_i = i\tau, i = \overline{0,5}$. Сонда (19) – (21) параболалық теңдеу үшін қойылған шеттік есебінен келесідей жай дифференциалдық теңдеулер жүйесі үшін екі нүктелі шеттік есебін аламыз:

$$\frac{dv}{dt} = \begin{pmatrix} -20t^2 - t - \frac{2001}{10} & 10t^2 + 100 & 0 & 0 \\ 20t^2 + 100 & -40t^2 - t - \frac{1001}{5} & 20t^2 + 100 & 0 \\ 0 & 30t^2 + 100 & -60t^2 - t - \frac{2003}{10} & 30t^2 + 100 \\ 0 & 0 & 40t^2 + 100 & -80t^2 - t - \frac{1002}{5} \end{pmatrix} v +$$

$$+ \begin{pmatrix} \left(\frac{1001}{10} + t + 10t^2\right)\sin 10\pi t - \frac{5999}{10000}t + \frac{t^2}{1000} - \frac{3}{50}t^3 + 10\pi\cos 10\pi t + \frac{1}{1000} \\ \left(\frac{1}{5} + t\right)\sin 10\pi t - \frac{749}{625}t + \frac{1}{125}t^2 - \frac{6}{25}t^3 + 10\pi\cos 10\pi t + \frac{1}{125} \\ \left(\frac{3}{10} + t\right)\sin 10\pi t - \frac{17919}{10000}t + \frac{27}{1000}t^2 - \frac{27}{50}t^3 + 10\pi\cos 10\pi t + \frac{27}{1000} \\ \left(\frac{502}{5} + t + 40t^2\right)\sin 10\pi t + \frac{12657}{1250}t + \frac{8}{125}t^2 + \frac{101}{25}t^3 + 10\pi\cos 10\pi t + \frac{8}{125} \end{pmatrix}, \quad t \in \left[0, \tfrac{1}{10}\right], \tag{22}$$

$$\begin{pmatrix} \frac{1}{10} & 0 & 0 & 0 \\ 0 & \frac{1}{5} & 0 & 0 \\ 0 & 0 & \frac{3}{10} & 0 \\ 0 & 0 & 0 & \frac{2}{5} \end{pmatrix} v(0) + \begin{pmatrix} \frac{101}{100} & 0 & 0 & 0 \\ 0 & \frac{26}{25} & 0 & 0 \\ 0 & 0 & \frac{109}{100} & 0 \\ 0 & 0 & 0 & \frac{29}{25} \end{pmatrix} v(T) = \begin{pmatrix} \frac{101}{1000000} \\ \frac{13}{15625} \\ \frac{2943}{1000000} \\ \frac{116}{15625} \end{pmatrix}, \quad v \in \mathbb{R}^4. \qquad (23)$$


(22), (23) жай дифференциалдық теңдеулер жүйесі үшін екі нүктелі шеттік есебін шешу үшін профессор Джумабаев ұсынған параметрлеу әдісін қолданайық. Бұл әдістің схемасы бойынша берілген $\left[0,\frac{1}{10}\right]$ аралығын ішкі бөліктерге бөлейік: $\left[0,\frac{1}{10}\right) = \cup_{s=1}^{5}[t_{s-1}, t_s)$, $t_r = 0.02r$, $r = \overline{0,5}$. Жоғарыда келтірілген алгоритм бойынша (17) жүйесі құрып алып және оны шешіп, $\hbar$ белгісіз параметрлердің сандық мәндерін табамыз:

$$\hbar_1^{\tilde{h}} = \begin{pmatrix} 0.0000046001 \\ -0.0000009345 \\ -0.0000006538 \\ 0.0000013315 \end{pmatrix}, \quad \hbar_2^{\tilde{h}} = \begin{pmatrix} 0.5878035076 \\ 0.5879467871 \\ 0.5883267026 \\ 0.5890633566 \end{pmatrix},$$

$$\hbar_3^{\tilde{h}} = \begin{pmatrix} 0.9510928802 \\ 0.9513787546 \\ 0.9521387525 \\ 0.9536128517 \end{pmatrix}, \quad \hbar_4^{\tilde{h}} = \begin{pmatrix} 0.9511125395 \\ 0.951538779 \\ 0.9526787843 \\ 0.954892513 \end{pmatrix}, \quad \hbar_5^{\tilde{h}} = \begin{pmatrix} 0.5878624992 \\ 0.5884267438 \\ 0.5899467493 \\ 0.5929024768 \end{pmatrix}.$$

(22) – (23) есептің шешімінің ішкі аралықтардың қалған нүктелеріндегі жуық мәндерін (18) Коши есептерін шешу арқылы табамыз. Онда $\tilde{u}\left(t_j^{\tilde{h}}, s\tau\right) = \tilde{v}_s\left(t_j^{\tilde{h}}\right)$, $s = \overline{1,4}$, $j = \overline{0,50}$, $\tau = 0.1$, параболалық теңдеу үшін (19) – (21) қойылған шеттік есептің сандық шешімі болады.

Параболалық теңдеу үшін қойылған (19) – (21) шеттік есебінің $u^*(t,x)$ дәл шешімі мен табылған $\tilde{u}(t,x)$ сандық шешімдерінің сызбасы 1-суретте көрсетілген.



Сурет 1 – (19) – (21) есебінің дәл шешімі (a) мен
сандық шешімдерінің (b) сызбасы

Параболалық теңдеу үшін қойылған (19) – (21) шеттік есебінің $u^*(t,x)$ дәл шешімі мен табылған $\tilde{u}(t,x)$ сандық шешімдері үшін келесі бағалау орынды:

$$\max_{j=\overline{0,50}\ ,i=\overline{1,4}} \left\| u^*(t_j,x_i) - \tilde{u}(t_j,x_i) \right\| < 0.000005$$

Қорытынды

Бұл жұмыста параболалық теңдеу үшін қойылған сызықтық шеттік есеп қарастырылды. x айнымалысы бойынша қандай да бір қадаммен дискреттеу жүргізіліп, қарастырылып отырған есеп жай дифференциалдық теңдеулер жүйесі үшін екі нүктелі шеттік есепке келтірілді. Параметрлеу әдісі негізінде келтірілген екі нүктелі шеттік есептің сандық шешімін табу алгоритмі құрылды. Құрылған алгоритм бойынша параболалық теңдеу үшін сызықтық шеттік есептің сандық шешімі табылды.

Қаржыландыру туралы ақпарат. Бұл зерттеуге Қазақстан Республикасы Ғылым және жоғары білім министрлігінің Ғылым комитеті қолдау көрсетті (Грант BR20281002).

ӘДЕБИЕТТЕР

1 Tikhonov A.N., Samarskii A.A.. Equations of mathematical physics. – New York: Dover Publications, 2011.

2 Vasudeva Murthy A.S., Verwer J.G. Solving parabolic integro-differential equations by an explicit integration method // J. Comput. Appl. Math. – 1992. – Vol. 39. – P. 121–132. https://doi.org/10.1016/0377-0427(92)90229-Q.

3 Day W.A. A decreasing property of solutions of parabolic equations with applications to thermoelasticity // Quart. Appl. Math. – 1983. – Vol. 40. – P. 468–475. https://doi.org/10.1090/qam/693879.

4 Bouziani A. Mixed problem with boundary integral conditions for a certain parabolic equation // J. Appl. Math. Stoch. Anal. – 1996. – Vol. 9. – P. 323–330.

5 Vladimirov V.S., Yankovsky E. A collection of problems on the equations of mathematical physics. – Germany: Springer-Verlag, 1986.

6 Trynin A.Y. On a method for solving a mixed boundary value problem for a parabolic equation using modified sinc-approximation operators // Comput. Math. and Math. Phys. – 2023. – Vol. 63. – P. 1264–1284. https://doi.org/10.1134/S0965542523050159.

7 Dehghan M. Numerical solution of a parabolic equation with non-local boundary specification // Appl. Math. Comput. – 2003. – Vol. 145. – P. 185–194. https://doi.org/10.1016/s0096-3003(02)00479-4.

8 Dalabaev U., Hasanova D. Construction of an approximate-analytical solution for boundary value problems of a parabolic equation // Mathematics and Computer Science. – 2023. – Vol. 8. – P. 39–45. https://doi.org/0.11648/j.mcs.20230802.11.

9 Colton D. The solution of initial-boundary value problems for parabolic equations by the method of integral operators // Journal of Differential Equations. – 1977. – Vol. 26. – P. 181–190.

10 Джумабаев Д.С. Обоснование метода ломаных для одной краевой задачи линейного параболического уравнения // Известия АН КазССР. Серия физико-математическая. – 1983. – № 1. – С. 8–11.

11 Асанова А.Т., Джумабаев Д.С. Об оценках решений и их производных краевой задачи для параболического уравнения // Известия МОН РК, НАН РК. Серия физико-математическая. – 2000. – № 5. – С.3–8.

12 Assanova A.T., Bakirova E.A., Kadirbayeva Zh.M. Numerically approximate method for solving of a control problem for integro-differential equations of parabolic type // News of the NAS RK. Phys.-Math. Series. – 2019. – Vol. 6. – P.14–24.

13 Dzhumabayev D.S. Criteria for the unique solvability of a linear boundary-value problem for an ordinary differential equation // USSR Comput.Math. Math. Phys. – 1989. – Vol. 29. – P. 34–46.

14 Dzhumabaev D.S. On one approach to solve the linear boundary value problems for Fredholm integrodifferential equations // J. Comput. Appl.Math. – 2016. – Vol. 294. – P. 342–357. http://dx.doi.org/10.1016/j.cam.2015.08.023

15 Dzhumabaev D.S., Bakirova E.A., Mynbayeva S.T. A method of solving a nonlinear boundary value problem with a parameter for a loaded differential equation // Math. Methods Appl. Sci. – 2020. – Vol. 4. – P. 1788–1802. https://doi.org/10.1002/mma.6003.

16 Assanova A.T., Bakirova E.A., Kadirbayeva Zh.M. A Problem with parameter for the integrodifferential equations // Math. Model. Anal. – 2021. – Vol. 26. – P. 34–54. https://doi.org/10.3846/mma.2021.11977.

17 Assanova A.T., Bakirova E.A., Kadirbayeva Zh.M., Uteshova R.E. A computational method for solving a problem with parameter for linear systems of integro-differential equations // Comput. Appl. Math. – 2020. – Vol. 39. Art. 248. https://doi.org/10.1007/s40314-020-01298-1.

18 Assanova A.T., Kadirbayeva Zh.M. On the numerical algorithms of parametrization method for solving a two-point boundary-value problem for impulsive systems of loaded differential equations // Comput. Appl. Math. – 2018. – Vol. 37. – P. 4966–4976. https://doi.org/10.1007/s40314-018-0611-9.

19 Temesheva S.M., Dzhumabaev D.S., Kabdrakhova S.S. On one algorithm to find a solution to a linear two-point boundary value problem // Lobachevskii journal of mathematics. – 2021. – Vol. 42. – P. 606–612. https://doi.org/10.1134/S1995080221030173.

20 Iskakova N.B., Temesheva S.M., Uteshova R.E. On a problem for a delay differential equations // Math. Meth. Appl. Sci. – 2023. – Vol. 46. – P. 11283–11297. https://doi.org/10.1002/mma.9181.

21 Bakirova E.A., Iskakova N.B., Kadirbayeva Zh.M. Numerical implementation for solving the boundary value problem for impulsive integro-differential equations with parameter // KazNU Bulletin. – 2023. – Vol. 119. – P. 19–29. https://doi.org/10.26577/JMMCS2023v119i3a2.

22 Бакирова Э.А., Искакова Н.Б., Темешева С.М., Кадирбаева Ж.М. Параметрі бар дифференциалдық теңдеуі үшін шеттік есептің бірмәнді шешілімділігі туралы // ҚБТУ Хабаршысы. – 2024. – Vol. 68. – P. 64–74. https://doi.org/10.55452/1998-6688-2024-21-1-64-74.

23 Kadirbayeva Zh.M., Bakirova E.A., Tleulesova A.B. Solving Fredholm integro-differential equations involving integral condition: A new numerical method // Mathematica Slovaca. – 2024. – Vol. 74. – P. 403–416. https://doi.org/10.1515/ms-2024-0031.

24 Kadirbayeva Zh.M., Kabdrakhova S.S. A numerical solution of problem for essentially loaded differential equations with an integro-multipoint condition // Open Math. – 2022. – Vol. 20. – P. 1173–1183. https://doi.org/10.1515/math-2022-0496.

REFERENCES

1 Tikhonov A.N., Samarskii A.A. (2011) Equations of mathematical physics, Dover Publications, New York.

2 Vasudeva Murthy A.S., Verwer J.G. (1992) J. Comput. Appl. Math., vol 39, pp. 121–132. https://doi.org/10.1016/0377-0427(92)90229-Q

3 Day W.A. (1983) Quart. Appl. Math., vol. 40, pp. 468–475. https://doi.org/10.1090/qam/693879

4 Bouziani A. (1996) J. Appl. Math. Stoch. Anal. Vol. 9, pp. 323–330.

5 Vladimirov V.S., Yankovsky E. (1986) A collection of problems on the equations of mathematical physics, Springer-Verlag, Germany.

6 Trynin A.Y. Comput. (2023) Math. and Math. Phys., vol. 63, pp. 1264–1284. https://doi.org/10.1134/S0965542523050159.

7 Dehghan M. (2003). Appl. Math. Comput., vol. 145, pp. 185–194. https://doi.org/10.1016/s0096-3003(02)00479-4.

8 Dalabaev U., Hasanova D. (2023) Mathematics and Computer Science, vol. 8, pp. 39–45 https://doi.org/0.11648/j.mcs.20230802.11.

9 Colton D. (1977) Journal of Differential Equations, vol. 26, pp. 181–190.

10 Dzhumabaev D.S. (1983) Izvestiya AN KazSSR. Seriya fiz.-matem., no. 1, pp. 8–11 [in Russian].

11 Asanova A.T., Dzhumabaev D.S. (2000) Izvestiya MON RK, NAN RK. Seriya fiz.-matem., no. 5, pp. 3–8 [in Russian].

12 Assanova A.T., Bakirova E.A. and Kadirbayeva Zh.M. (2019) News of the NAS RK. Phys.-Math. Series, vol. 6, pp. 14–24.

13 Dzhumabayev D.S. (1989) USSR Comput.Math. Math. Phys., vol. 29, pp. 34–46.

14 Dzhumabaev D.S. (2016) J. Comput. Appl.Math., vol. 294, pp. 342–357. http://dx.doi.org/10.1016/j.cam.2015.08.023.

15 Dzhumabaev D.S., Bakirova E.A. and Mynbayeva S.T. (2020) Math. Methods Appl. Sci., vol. 4, pp. 1788–1802. https://doi.org/10.1002/mma.6003.

16 Assanova A.T., Bakirova E.A. and Kadirbayeva Zh.M. (2021) Math. Model. Anal., vol. 26, pp. 34–54. https://doi.org/10.3846/mma.2021.11977.

17 Assanova A.T., Bakirova E.A., Kadirbayeva Zh.M. and Uteshova R.E. (2020). Comput. Appl. Math., vol. 39, pp. 248. https://doi.org/10.1007/s40314-020-01298-1.

18 Assanova A.T., Kadirbayeva Zh.M. (2018) Comput. Appl. Math., vol. 37, pp. 4966–4976. https://doi.org/10.1007/s40314-018-0611-9.

19 Temesheva S.M., Dzhumabaev D.S. and Kabdrakhova S.S. (2021) Lobachevskii journal of mathematics, vol. 42, pp. 606–612. https://doi.org/10.1134/S1995080221030173.

20 Iskakova N.B., Temesheva S.M. and Uteshova R.E. (2023). Math. Meth. Appl. Sci., vol. 46, pp. 11283–11297. https://doi.org/10.1002/mma.9181.

21 Bakirova E.A., Iskakova N.B. and Kadirbayeva Zh.M. (2023) KazNU Bulletin, vol. 119, pp. 19–29. https://doi.org/10.26577/JMMCS2023v119i3a2.

22 Bakirova E.A., Iskakova N.B, Temesheva S.M. and Kadirbayeva Zh.M. (2024) KBTU Khabarshysy, vol. 68, pp. 64–74. https://doi.org/10.55452/1998-6688-2024-21-1-64-74 (in Kazakh).

23 Kadirbayeva Zh.M., Bakirova E.A. and Tleulesova A.B. (2024). Mathematica Slovaca, vol. 74, pp. 403–416. https://doi.org/10.1515/ms-2024-0031.

24 Kadirbayeva Zh.M. and Kabdrakhova S.S. (2022) Open Math., vol. 20, pp. 1173–1183. https://doi.org/10.1515/math-2022-0496.

[1,2]Iskakova N.B.,
Candidate of Phys.-Math.Sc., Leading Researcher, ORCID ID: 0000-0002-0680-4099,
*e-mail: narkesh77@gmail.com
[1,3,4]Kadirbayeva Zh.M.,
Candidate of Phys.-Math.Sc., Leading Researcher, ORCID ID: 0000-0001-8861-4100,
e-mail: zhkadirbayeva@gmail.com
[1,3]Bakirova E.A.,
Candidate of Phys.-Math.Sc., Leading Researcher, ORCID ID: 0000-0002-3820-5373,
e-mail: bakirova1974@mail.ru
[2]Kuanysh S.K.,
Doctoral student, Teacher, ORCID ID: 0009-0006-0975-1662,
e-mail: saule270898@gmail.com

[1]Institute of Mathematics and Mathematical Modeling, 050010, Almaty, Kazakhstan
[2]Al-Farabi Kazakh National University, 050040, Almaty, Kazakhstan
[3]Kazakh National Women's Teacher Training University, 050000, Almaty, Kazakhstan
[4]International Information Technology University, 050000, Almaty, Kazakhstan

NUMERICAL METHOD FOR SOLVING THE BOUNDARY VALUE PROBLEM FOR THE PARABOLIC EQUATION

Abstract

A linear boundary value problem for a parabolic equation is considered in a closed domain. Based on the broken line method, the boundary value problem for a parabolic equation is replaced by a two-point boundary value problem for a system of linear ordinary differential equations by discretizing the unknown function $u(t, x)$ with respect to the variable x. The obtained two-point boundary value problem is investigated by the parameterization method of Professor Dzhumabaev. Based on this method, an algorithm for finding a numerical solution to the two-point boundary value problem for a system of linear ordinary differential equations is constructed. The

constructed algorithm is realized by applying known numerical methods. The constructiveness and efficiency of the parameterization method also allows us to construct a numerical solution of the considered linear boundary value problem for the parabolic equation. One numerical example is given to verify and illustrate the proposed algorithm.

Key words: Parabolic equation, boundary value problem, algorithm, numerical solution, parameterization method.

[1,2]Искакова Н.Б.,
к.ф.-м.н., ведущий научный сотрудник, ORCID ID: 0000-0002-0680-4099,
*e-mail: narkesh77@gmail.com
[1,3,4]Кадирбаева Ж.М.,
к.ф.-м.н., ведущий научный сотрудник, ORCID ID: 0000-0001-8861-4100,
e-mail: zhkadirbayeva@gmail.com
[1,3]Бакирова Э.А.,
к.ф.-м.н., ведущий научный сотрудник, ORCID ID: 0000-0002-3820-5373,
e-mail: bakirova1974@mail.ru
[2]Қуаныш С.Қ.,
докторант, преподаватель, ORCID ID: 0009-0006-0975-1662,
e-mail: saule270898@gmail.com

[1]Институт математики и математического моделирования, 050010, г. Алматы, Казахстан
[2]Казахский национальный университет имени аль-Фараби, 050040, г. Алматы, Казахстан
[3]Казахский национальный женский педагогический университет, 050000, г. Алматы, Казахстан
[4]Международный университет информационных технологий, 050000, г. Алматы, Казахстан

ЧИСЛЕННЫЙ МЕТОД РЕШЕНИЯ КРАЕВОЙ ЗАДАЧИ ДЛЯ ПАРАБОЛИЧЕСКОГО УРАВНЕНИЯ

Аннотация

В замкнутой области рассматривается линейная краевая задача для параболического уравнения. На основе метода ломаных краевая задача для параболического уравнения заменяется двухточечной краевой задачей для системы линейных обыкновенных дифференциальных уравнений путем дискретизации неизвестной функции $u(t, x)$ по переменной x. Полученная двухточечная краевая задача исследуется методом параметризации профессора Джумабаева. На основе данного метода строится алгоритм нахождения численного решения для двухточечной краевой задачи для системы линейных обыкновенных дифференциальных уравнений. Построенный алгоритм реализуется путем применения известных численных методов. Конструктивность и эффективность метода параметризации позволяет также построить численное решение рассматриваемой линейной краевой задачи для параболического уравнения. Для проверки и иллюстрации предложенного алгоритма приводится один численный пример.

Ключевые слова: параболическое уравнение, краевая задача, алгоритм, численное решение, метод параметризации.

Мақаланың редакцияға түскен күні: 31.05.2024

УДК 517.54
МРНТИ 27.23.25

https://doi.org/10.55452/1998-6688-2024-21-3-176-190

[1]Майер Ф.Ф.,
канд. физ.-мат. наук, профессор,
ORCID ID: 0000-0002-2278-2723,
e-mail: maiyer@mail.ru
[1]Тастанов М.Г.,
канд. физ.-мат. наук, профессор,
ORCID ID: 0000-0003-1926-8958,
e-mail: tastao@mail.ru
[1*]Утемисова А.А.,
канд. пед. наук, ORCID ID: 0000-0001-5143-0260,
*e-mail: anar_utemisova@mail.ru
[1]Ысмағұл Р.С.,
канд. физ.-мат. наук, профессор,
ORCID ID: 0009-0007-6594-7958,
e-mail: ismagulr@mail.ru

[1]НАО «Костанайский региональный университет имени Ахмета Байтұрсынұлы»,
г. Костанай 110000, Казахстан

ОБ ОБОБЩЕНИИ НЕКОТОРЫХ КЛАССОВ ВЫПУКЛЫХ В НАПРАВЛЕНИИ И ТИПИЧНО ВЕЩЕСТВЕННЫХ ФУНКЦИЙ

Аннотация

В статье M.O. Рида (M.O. Reade, Duke Math. Journal, 1956) с помощью условия $\left|\arg\left(f'(z)/g'(z)\right)\right| \leq \frac{\gamma\pi}{2}$, где $g(z)$ – выпуклая функция, $0 \leq \gamma \leq 1$, введен класс функций, почти выпуклых порядка γ. В нашей статье вводится подкласс класса почти выпуклых порядка γ функций, удовлетворяющих условию $|arg\,[(1-\lambda z^n)^\alpha f'(z)]| \leq \gamma\pi/2$, который при различных значениях параметров дает ряд известных подклассов однолистных функций. На базе данного подкласса построен класс почти звездообразных функций, содержащий целый ряд подклассов, активно исследуемых многими авторами в последние годы, а также классический класс типично вещественных функций. Для данных классов найдены, соответственно, теоремы искажения (роста) и радиусы выпуклости (звездообразности). Также рассмотрен случай, когда исследуемые функции имеют пропуски членов в разложении в ряд. Полученные результаты являются точными и не только обобщают ранее известные результаты, но и раскрывают свойства ряда новых подклассов однолистных функций.

Ключевые слова: почти выпуклые функции, почти звездообразные функции, типично вещественные функции, оценки роста, оценки искажения, радиусы выпуклости, радиусы звездообразности.

Введение

Исследованию различных подклассов однолистных функций посвящен целый ряд статей, включая и опубликованные в последние три года. Основными направлениями исследований являются оценка коэффициентов и нахождение теорем роста, покрытия, искажения различных радиусных констант.

В статье рассматривается достаточно широкий класс однолистных функций, включающий ряд известных подклассов почти выпуклых функций. На базе данного класса построен

класс почти звездообразных функций, содержащий целый ряд подклассов, активно исследуемых в последние годы, а также класс типично вещественных функций.

Для данных классов найдены, соответственно, теоремы роста (искажения) и радиусы выпуклости (звездообразности). Рассмотрен случай, когда исследуемые функции имеют пропуски членов в разложении в ряд. Полученные результаты являются точными и не только обобщают ранее известные результаты, но и раскрывают свойства ряда новых подклассов однолистных функций.

Материалы и методы

Основным методом исследования статьи является достаточно простой в применении и в то же время эффективный метод подчиненности аналитических функций. Говорят, что аналитическая в единичном круге E функция $\varphi(z)$ подчинена функции $\varphi_0(z)$ и пишут $\varphi(z) \prec \varphi_0(z)$, если существует аналитическая в E функция $\omega(z)$, удовлетворяющая условиям леммы Шварца, то есть, такая, что $\omega(0) = 0$, $|\omega(z)| \leq 1$ и такая, что $\varphi(z) = \varphi_0\big(\omega(z)\big)$. В случае однолистной функции $\varphi_0(z)$ соотношение подчиненности означает, что $\varphi(E) \subset \varphi_0(E)$ и $\varphi(0) = \varphi_0(0)$, откуда следует вложение замкнутых областей $\varphi(|z| \leq r) \subseteq \varphi_0(|z| \leq r)$ при любом r, $0 \leq r < 1$.

Основные положения

Обозначим через $\mathcal{N}_n$ класс аналитических в круге $E = \{z: |z| < 1\}$ функций $f(z)$, разлагающихся в степенной ряд вида $f(z) = z + a_{n+1}z^{n+1} + a_{n+2}z^{n+2} + \cdots, n \geq 1, z \in E$, и пусть $\mathcal{N} := \mathcal{N}_1$. Также будем использовать следующие обозначения для известных подклассов класса $\mathcal{N}$: S – класс однолистных функций, K – класс почти выпуклых функций, S^* – звездообразных функций и S^c – выпуклых функций $f(z)$. Информацию о классе однолистных функций и его подклассах можно получить в обзорной статье [1].

Функции классов S^c, S^* и K обладают наглядными геометрическими свойствами [1, §2, 4]. При этом, $S^c \subset S^* \subset K \subset S$.

Следуя [1], приведем следующие определения.

Определение 1. Регулярная (то есть однозначная и дифференцируемая) в круге E функция $w = f(z)$ называется однолистной в круге E, если для любых $z_1, z_2 \in E$ из условия $z_1 \neq z_2$ следует, что $f(z_1) \neq f(z_2)$.

Определение 2. Функция $w = f(z)$ называется выпуклой в круге E, если она отображает круг E на выпуклую область $f(E)$, то есть такую область, что для любых двух точек области $f(E)$ отрезок с концами в данных точках также целиком содержится в этой области.

Известно, что

$$f(z) \in S^c \;\Leftrightarrow\; 1 + Re\, z\frac{f''(z)}{f'(z)} \geq 0, \;\; z \in E.$$

Определение 3. Функция $w = f(z)$ называется звездообразной в круге E, если она отображает круг E на звездообразную область $f(E)$, то есть такую область, что наряду с любой точкой $w \in f(E)$ и отрезок $[0, w]$ также целиком содержится в области $f(E)$.

Известно, что

$$f(z) \in S^* \;\Leftrightarrow\; Re\, z\frac{f'(z}{f(z)} \geq 0, \;\; z \in E.$$

Определение 4. Регулярная в круге E функция $f(z)$ называется почти выпуклой в круге E, если существует выпуклая в E функция $g(z)$ такая, что выполняется условие

$$Re\, \frac{f'(z)}{g'(z)} \geq 0, \;\; z \in E.$$

Функции $f(z) \in K$ обладают тем свойством, что внешность области $f(E)$ можно полностью покрыть семейством непересекающихся лучей с вершинами на границе области $f(E)$, имеющих с границей области $f(E)$ либо одну общую точку, либо общий связный отрезок луча, либо весь луч.

Также нам потребуются следующие подклассы классов S^* и S^o:

$$S_\beta^* = \left\{f(z): Re\, z\frac{f'(z)}{f(z)} \geq \beta\right\} \text{ и } S_\beta^0 = \left\{f(z): 1 + Re\, z\frac{f''(z)}{f'(z)} \geq \beta\right\},$$

где $0 \leq \beta < 1$.

Обзор литературы

В статье [2] с помощью условия

$$\left|arg\ \frac{f'(z)}{g'(z)}\right| \leq \frac{\gamma\pi}{2},\ \ 0 \leq \gamma \leq 1,\ \ z \in E, \tag{1}$$

введен класс $K(\gamma) \subset\ K = K(1)$ функций $f(z)$, почти выпуклых порядка γ. Его подклассами являются классы $C_i(\gamma)$, $i = 1,2,3$, функций $f(z)$ из $\mathcal{N}$, удовлетворяющих, соответственно, условиям

$$C_1(\gamma):\ |arg\ [(1-z^2)f'(z)]| \leq \frac{\gamma\pi}{2}, \tag{2}$$

$$C_2(\gamma):\ |arg\ [(1-z)^2 f'(z)]| \leq \frac{\gamma\pi}{2}, \tag{3}$$

$$C_3(\gamma):\ |arg\ [(1-z)\ \ f'(z)]| \leq \frac{\gamma\pi}{2}, \tag{4}$$

построенные на основе условия (1) с помощью выпуклых функций

$$g_1(z) = \frac{1}{2}\ln\frac{1+z}{1-z},\ \ g_2(z) = \frac{z}{1-z},\ \ g_3(z) = -\ln(1-z).$$

Толчок к исследованию классов (2)-(4), а также классов $C_i := C_i(1)$, $i = 1,2,3$, дала статья [3], в которой исследовались свойства функций класса $C_1 = \{f(z) \in \mathcal{N}: Re\,[(1-z^2)f'(z)] \geq 0\}$.

В статье [4] изучаются геометрические свойства функций класса $\mathcal{CV}_{\alpha,\beta}^-$, заданного условием $-\frac{\beta\pi}{2} \leq \arg\left[ie^{i\delta}\left(1-e^{-i\delta}z\right)^2 f'(z)\right] \leq \frac{\alpha\pi}{2}$, $\alpha, \beta \in [0;1]$, обобщающего класс $C_2(\gamma)$. Из [3] следует, что для каждой функции $f(z) \in C_2(\gamma)$ область $f(E)$ (а также $\overline{\mathbb{C}}\backslash f(E)$) может быть покрыта углами величины $(1-\gamma)\pi$ с вершинами в граничных точках области $f(E)$ и биссектрисами, имеющими положительное (отрицательное) направление действительной оси.

Одновременно с [4] в [5] изучался класс $C_1(\gamma)$ функций $f(z)$, выпуклых порядка γ в направлении мнимой оси. В этом случае функции $f(z) \in C_1(\gamma)$ обладают тем свойством, что область $f(E)$ достижима извне углами величины $(1-\gamma)\pi$ с биссектрисами, параллельными мнимой оси и уходящими в ∞ (вверх или вниз).

Обобщение класса $C_1(\gamma)$ в форме ограничения $\left|[(1-\lambda z^2)f'(z)]^{1/\gamma} - a\right| \leq a$, рассматривалось в [6].

По аналогии с классом K, то есть с условием (1) при $\gamma = 1$, в [6] был введен класс CS^* почти звездообразных функций $F(z) \in \mathcal{N}$, удовлетворяющих условию

$$Re\frac{F(z)}{G(z)} \geq 0, \text{ где } G(z) \in S^*, \ z \in E. \tag{5}$$

Подклассами класса CS^* являются классы функций $F(z)$, удовлетворяющих условиям

$$CS_1^*(\gamma): |arg\,[(1-z^2)F(z)/z]| \leq \frac{\gamma\pi}{2}, \tag{2′}$$

$$CS_2^*(\gamma): |arg\,[(1-z)^2F(z)/z]| \leq \frac{\gamma\pi}{2}, \tag{3′}$$

$$CS_3^*(\gamma): |arg\,[(1-z)\ F(z)/z]| \leq \frac{\gamma\pi}{2}. \tag{4′}$$

Нетрудно увидеть, что между классами $C_1(\gamma)$, $C_2(\gamma)$, $C_3(\gamma)$ и $CS_1^*(\gamma)$, $CS_2^*(\gamma)$, $CS_3^*(\gamma)$ имеется простая связь, которая устанавливается с помощью соотношения

$$f(z) \in C_i(\gamma) \Leftrightarrow F(z) = zf'(z) \in CS_i^*(\gamma), i = 1,2,3. \tag{6}$$

Для более простого случая, когда $\gamma = 1$, классы $CS_i^* = CS_i^*(1)$, $i = 1,2,3$, а также аналогичные им классы $CS_4^* = \{F(z) \in \mathcal{N}: Re\ (F(z)/z) \geq 0\}$ и $CS_5^* = \{F(z) \in \mathcal{N}: Re\ (F(z)/(z+z^2/2)) \geq 0\}$ исследовались в статьях [7–12] с точки зрения оценки коэффициентов и нахождения радиусов звездообразности.

Класс CS_1^* является расширением класса T типично вещественных функций [13], так как функции класса T дополнительно к условию $Re\,\{(1-z^2)F(z)/z\} \geq 0$, $z \in E$, должны удовлетворять еще следующим условиям: $Im\,F(z) = 0$ при $z \in (-1;1)$ и $Im\,F(z) \cdot Im\,z > 0$ в остальных точках круга E.

Отсюда следует, что $T \subset CS_1^* \subset CS^*$.

Статья [13] дала толчок целому ряду исследований типично вещественных функций (например, [14–15]) или их обобщений (например, [8, 12]).

Результаты и обсуждение

1. Класс $C_n(\lambda, \alpha, \gamma)$ почти выпуклых функций и обобщение класса типично-вещественных функций

Ниже по тексту будем считать, что $n \in \mathbb{N}$, $\alpha \in \mathbb{R}$, $0 \leq \lambda \leq 1$, $0 < \gamma \leq 1$.

Определение 5. Будем говорить, что функция $f(z)$ принадлежит классу $C_n(\lambda, \alpha, \gamma)$ тогда и только тогда, когда функция $f(z) \in \mathcal{N}$ и удовлетворяет условию

$$|arg\,[(1-\lambda z^n)^\alpha f'(z)]\,| \leq \frac{\gamma\pi}{2}, \ \lambda - 1 \leq \alpha\lambda n \leq \lambda + 1, \ z \in E. \tag{7}$$

Если функция $f(z) \in C_n(\lambda, \alpha, \gamma)$, то функция $f(z) \in K(\gamma)$, поскольку удовлетворяют условию (1) с выпуклой в E функцией

$$g(z) = \int_0^z \frac{dt}{(1-\lambda t^n)^\alpha}.$$

Действительно, если $\alpha = 0$, то $g(z) = z \in S^o$. Если же $\alpha > 0$, то

$$Re\, z\frac{g''(z)}{g'(z)} = Re\frac{\alpha\lambda n z^n}{1-\lambda z^n} \geq \min_{|t|<1} Re\frac{\alpha\lambda n t}{1-\lambda t} = -\frac{\alpha\lambda n}{1+\lambda} \geq -1 \qquad (8)$$

при $0 \leq \alpha\lambda n \leq \lambda + 1$. Если же $\alpha < 0$, то аналогично неравенству (8) получаем, что $Re\, z\frac{g''(z)}{g'(z)} \geq \frac{\alpha\lambda n}{1-\lambda} \geq -1$ при $\alpha\lambda n \geq \lambda - 1$. То есть, $g(z) \in S^{\circ}$ при $\lambda - 1 \leq \alpha\lambda n \leq \lambda + 1$ и $C_n(\lambda, \alpha, \gamma) \subset K(\gamma)$.

Частными случаями класса $C_n(\lambda, \alpha, \gamma)$ являются классы функций $C_1(\gamma) = C_2(1,1,\gamma)$, $C_2(\gamma) = C_1(1,2,\gamma)$, $C_3(\gamma) = C_1(1,1,\gamma)$, $\mathcal{R}(\gamma) = C_1(1,0,\gamma)$, где $\mathcal{R} \coloneqq \mathcal{R}(1)$ – класс функций с ограниченным вращением [16], который задается с помощью условия $Re\, f'(z) \geq 0,\ z \in E$.

Рассмотрим класс $T_n(\lambda, \alpha, \gamma)$ функций $F(z) \in \mathcal{N}$, удовлетворяющих условию

$$\left|arg\left((1-\lambda z^n)^{\alpha}\frac{F(z)}{z}\right)\right| \leq \frac{\gamma\pi}{2},\ \ \lambda - 1 \leq \alpha\lambda n \leq \lambda + 1,\ \ z \in E. \qquad (9)$$

При условии вещественности $F(z)$ в точках интервала $(-1;\ 1)$ при $n = 2$, $\lambda = \alpha = \gamma = 1$ класс $T_n(\lambda, \alpha, \gamma)$ преобразуется в класс T типично вещественных функций. Кроме того, $T_2(1,1,\gamma) \subset T$ для всех $\gamma \in (0; 1]$.

Легко установить, что

$$f(z) \in C_n(\lambda, \alpha, \gamma) \quad \Leftrightarrow \quad F(z) = zf'(z) \in T_n(\lambda, \alpha, \gamma). \qquad (10)$$

Действительно, если $f(z) \in C_n(\lambda, \alpha, \gamma)$, то по определению класса $C_n(\lambda, \alpha, \gamma)$ функция $f(z)$ удовлетворяет условию (7), то есть условию $|arg\,[(1-\lambda z^n)^{\alpha} f'(z)]| \leq \frac{\gamma\pi}{2}$. Тогда функция $F(z) = zf'(z)$, так как $f'(z) = \frac{F(z)}{z}$, будет удовлетворять условию $\left|arg\left[(1-\lambda z^n)^{\alpha}\frac{F(z)}{z}\right]\right| \leq \frac{\gamma\pi}{2}$ (9), а это по определению класса $T_n(\lambda, \alpha, \gamma)$ означает, что $F(z) \in T_n(\lambda, \alpha, \gamma)$. То есть $f(z) \in C_n(\lambda, \alpha, \gamma) \Rightarrow F(z) = zf'(z) \in T_n(\lambda, \alpha, \gamma)$. Импликация в обратную сторону доказывается в обратном порядке.

2. Теоремы искажения в классе $C_n(\lambda, \alpha, \gamma)$

Теорема 1. Пусть $f(z) \in C_n(\lambda, \alpha, \gamma)$. Тогда при $|z| = r,\ 0 \leq r < 1$ имеют место точные оценки

$$\left(\frac{1-r^m}{1+r^m}\right)^{\gamma}\frac{1}{(1+\lambda r^n)^{\alpha}} \leq |f'(z)| \leq \left(\frac{1+r^m}{1-r^m}\right)^{\gamma}\frac{1}{(1-\lambda r^n)^{\alpha}} \text{ при } \alpha \geq 0, \qquad (11)$$

$$\left(\frac{1-r^m}{1+r^m}\right)^{\gamma}\frac{1}{(1-\lambda r^n)^{\alpha}} \leq |f'(z)| \leq \left(\frac{1+r^m}{1-r^m}\right)^{\gamma}\frac{1}{(1+\lambda r^n)^{\alpha}} \text{ при } \alpha < 0, \qquad (12)$$

$$\left|z\frac{f''(z)}{f'(z)} - \frac{\alpha\lambda n z^n}{1-\lambda z^n}\right| \leq \frac{2\gamma m r^m}{1-r^{2m}}, \qquad (13)$$

где $m = 1$ при $f(z) \in \mathcal{N}$ и $m = n$ при $f(z) \in \mathcal{N}_n$.

Доказательство. Пусть $f(z) \in \mathcal{N}$. Условие (7) в форме подчиненности приобретает вид

$$\varphi(z) = (1-\lambda z^n)^{\alpha} f'(z) \prec \varphi_0(z) = \left(\frac{1+z}{1-z}\right)^{\gamma}. \qquad (14)$$

Поэтому при любом r, $0 \le r < 1$, выполняется соотношение $\varphi(|z| \le r) \subset \varphi_0(|z| \le r)$, откуда вытекает неравенство

$$\left(\frac{1-r}{1+r}\right)^{\gamma} \le |(1-\lambda z^n)^{\alpha} f'(z)| \le \left(\frac{1+r}{1-r}\right)^{\gamma}. \qquad (15)$$

Пусть $\alpha \ge 0$. Поскольку в силу правой оценки (15) при $|z| = r$ выполняется неравенство

$$(1-\lambda r^n)^{\alpha}|f'(z)| \le |(1-\lambda z^n)^{\alpha}||f'(z)| \le \left(\frac{1+r}{1-r}\right)^{\gamma},$$

то отсюда вытекает правая оценка (11). Аналогично с помощью левой оценки (15) находим

$$\left(\frac{1-r}{1+r}\right)^{\gamma} \le |(1-\lambda z^n)^{\alpha}||f'(z)| \le (1+\lambda r^n)^{\alpha}|f'(z)|,$$

откуда следует левая оценка (11).

Если $\alpha < 0$, то учитывая, что

$$(1+\lambda r^n)^{\alpha} \le |(1-\lambda z^n)^{\alpha}| \le (1-\lambda r^n)^{\alpha},$$

аналогично предыдущему находим оценку (12).

Перепишем условие (14) в виде

$$\Phi(z) = \alpha \ln(1-\lambda z^n) + \ln f'(z) \prec \Phi_0(z) = \gamma \ln \frac{1+z}{1-z}.$$

Отсюда в силу подчиненности $\Phi(z) \prec \Phi_0(z)$ существует функция $\omega(z)$, удовлетворяющая условиям леммы Шварца, такая, что $\Phi(z) = \gamma \ln \frac{1+\omega(z)}{1-\omega(z)}$. Поэтому $\Phi'(z) = \frac{2\gamma\omega'(z)}{1-\omega^2(z)}$ и с учетом неравенства [17, с. 323]

$$|\omega'(z)| \le \frac{1-|\omega(z)|^2}{1-|z|^2}$$

окончательно получаем оценку (13)

$$\left|z\frac{f''(z)}{f'(z)} - \frac{\alpha\lambda n z^n}{1-\lambda z^n}\right| = |z\Phi'(z)| \le \frac{2\gamma|z||\omega'(z)|}{1-|\omega(z)|^2} \le \frac{2\gamma r}{1-r^2}.$$

Покажем, что оценки (11)–(13) улучшить нельзя.

Рассмотрим функцию

$$f_0(z) = \int_0^z \left(\frac{1+t}{1-t}\right)^{\gamma} \frac{dt}{(1-\lambda t^n)^{\alpha}} \in C_m(\lambda, \alpha, \gamma).$$

Для нее

$$z\frac{f_0''(z)}{f_0'(z)} - \frac{\alpha\lambda n z^n}{1-\lambda z^n} = \frac{2\gamma z}{1-z^2}$$

и поэтому при любом α, $\lambda - 1 \le \alpha\lambda n \le \lambda + 1$, в точке $z = r$ в оценке (13) достигается знак равенства.

1) Пусть $\alpha \ge 0$. Поскольку

$$f_0'(z) = \left(\frac{1+z}{1-z}\right)^{\gamma} \frac{1}{(1-\lambda z^n)^{\alpha}},$$

то при любом $n \in \mathbb{N}$ в правой оценке (11) для функции $f_0(z)$ в точке $z = r$ достигается знак равенства.

Если n – нечетное, то в левой оценке (11) для функции $f_0(z)$ в точке $z = -r$ также достигается знак равенства, поскольку

$$f_0'(-r) = \left(\frac{1-r}{1+r}\right)^{\gamma} \frac{1}{(1+\lambda r^n)^{\alpha}}.$$

Для доказательства точности левой оценки (11) при четном n рассмотрим два случая.

а) $n = 2, 6, 10, \ldots, 2(2k-1), \ldots, k \in \mathbb{N}$. Тогда $i^n = -1$ и для $z = ir$ имеем $z^n = -r^n, iz = -r$. Поэтому для функции

$$f_1(z) = \int_0^z \left(\frac{1+it}{1-it}\right)^{\gamma} \frac{dt}{(1-\lambda t^n)^{\alpha}} \in C_n(\lambda, \alpha, \gamma) \tag{16}$$

в точке $z = ir$ получаем

$$f_1'(ir) = \left(\frac{1+iz}{1-iz}\right)^{\gamma} \frac{1}{(1-\lambda z^n)^{\alpha}}\Bigg|_{z=ir} = \left(\frac{1-r}{1+r}\right)^{\gamma} \frac{1}{(1+\lambda r^n)^{\alpha}},$$

то есть в этом случае левую оценку (11) улучшить нельзя.

б) $n = 4, 8, 12, \ldots, 4k, \ldots, k \in \mathbb{N}$. Рассмотрим функцию

$$f_2(z) = \int_0^z \left(\frac{1+\varepsilon^{-1}t}{1-\varepsilon^{-1}t}\right)^{\gamma} \frac{dt}{(1-\lambda t^n)^{\alpha}} \in C_n(\lambda, \alpha, \gamma), \quad \varepsilon = i^{\frac{n+2}{n}}. \tag{17}$$

В этом случае $i^n = 1$ и для $z = -\varepsilon r$ получаем, что $z^n = -r^n$, $\varepsilon^{-1}z = -r$.

Поэтому

$$f_2'(-\varepsilon r) = \left(\frac{1+\varepsilon^{-1}z}{1-\varepsilon^{-1}z}\right)^{\gamma} \frac{1}{(1-\lambda z^n)^{\alpha}}\Bigg|_{z=-\varepsilon r} = \left(\frac{1-r}{1+r}\right)^{\gamma} \frac{1}{(1+\lambda r^n)^{\alpha}},$$

что доказывает неулучшаемость левой оценки (11) и в этом случае.

2) В случае $\alpha < 0$ доказательство проводится аналогично предыдущему. Для функции

$$f_3(z) = \int_0^z \left(\frac{1-t}{1+t}\right)^{\gamma} \frac{dt}{(1-\lambda t^n)^{\alpha}} \in C_n(\lambda, \alpha, \gamma) \tag{18}$$

при нечетном n в оценках (12) слева и справа достигаются знаки равенства, соответственно, в точках $z = r$ и $z = -r$. При четном n для функции $f_3(z)$ в левой оценке (12) знак равенств достигается в точке $z = r$.

Остается доказать точность правой оценки (12) при четном n.

Тогда при $n = 2(2k-1),\ k \in \mathbb{N}$, имеем $z^n = -r^n$, $iz = -r$, а для $n = 4k$, $k \in \mathbb{N}$, имеем $z^n = -r^n$, и для $\varepsilon_1 = i^{\frac{n-2}{n}}$ находим $\varepsilon_1 z = -r$. Поэтому для функций

$$f_4(z) = \int_0^z \left(\frac{1-it}{1+it}\right)^{\gamma} \frac{dt}{(1-\lambda t^n)^{\alpha}}, f_5(z) = \int_0^z \left(\frac{1-\varepsilon_1 t}{1+\varepsilon_1 t}\right)^{\gamma} \frac{dt}{(1-\lambda t^n)^{\alpha}},$$

соответственно в точках $z = ir$ и $z = i\varepsilon_1^{-1}r$ получаем, что

$$f_4'(ir) = f_5'(i\varepsilon_1^{-1}r) = \left(\frac{1+r}{1-r}\right)^{\gamma} \frac{1}{(1+\lambda r^n)^{\alpha}},$$

что доказывает неулучшаемость правой оценки (12) и в этом случае.

Пусть теперь $f(z) \in \mathcal{N}_n$. В этом случае доказательство полностью аналогично доказательству теоремы для случая, когда $f(z) \in \mathcal{N}$, с той лишь разницей, что функция $\varphi(z) = (1-\lambda z^n)^\alpha f'(z)$ разлагается в ряд вида $\varphi(z) = 1 + c_n z^n + c_{n+1} z^{n+1} + \cdots$, $n \geq 1$. Поэтому в силу подчиненности $\varphi(z) \prec \varphi_0(z)$ с учетом усиленной леммы Шварца [17, с. 323] будет иметь место включение $\varphi(|z| \leq r) \subset \varphi_0(|z| \leq r^n)$, $0 \leq r < 1$, то есть при $|z| = r$ вместо (15) будет выполняться неравенство

$$\left(\frac{1-r^n}{1+r^n}\right)^\gamma \leq |(1-\lambda z^n)^\alpha f'(z)| \leq \left(\frac{1+r^n}{1-r^n}\right)^\gamma, \qquad (15')$$

откуда и вытекают оценки (11)–(12) для случая $m = n$.

Для доказательства оценки (13) с учетом разложения в ряд функции $\Phi(z) = \alpha \ln(1-\lambda z^n) + \ln f'(z) = b_n z^n + b_{n+1} z^{n+1} + \cdots$ и применяя оценку

$$|\omega'(z)| \leq \frac{n|z|^{n-1}}{1-|z|^{2n}}(1-|\omega(z)|^2)$$

из теоремы Голузина Г.М. [17, с. 323], получаем (13) для случая $m = n$.

Теорема 1 доказана.

В частных случаях из теоремы 1 вытекают оценки $|f'(z)|$ и $\left|z\frac{f''(z)}{f'(z)}\right|$ для классов $C_1(\gamma)$, $C_2(\gamma)$, $C_3(\gamma)$, $\mathcal{R}(\gamma)$ и при $\gamma = 1$ – для классов C_1, C_2, C_3 и $\mathcal{R}$.

Оценки для класса $C_1(\gamma)$ при $m = 1$ и при $m = 2$ получены ранее в [5], а при $m = \gamma = 1$ оценка $|f'(z)|$ для C_1 – в [3]. Оценка $|f'(z)|$ для класса $\mathcal{R}$ ранее получена в [18].

3. Радиус выпуклости класса $C_m(\lambda, \alpha, \gamma)$ и его подклассов

Оценка (12) позволяет найти точный радиус выпуклости порядка β класса $C_n(\lambda, \alpha, \gamma)$.

Теорема 2. Точный радиус $r_0(\beta)$ выпуклости порядка β, $0 \leq \beta < 1$, класса $C_n(\lambda, \alpha, \gamma)$ определяется как единственный на промежутке $[0,1)$ корень уравнения

$$1 - \beta - \frac{2\gamma m r^m}{1-r^{2m}} - \frac{|\alpha|\lambda n r^n}{1 + sign\,\alpha \cdot \lambda r^n} = 0, \qquad (19)$$

где $m = 1$ при $f(z) \in \mathcal{N}$ и $m = n$ при $f(z) \in \mathcal{N}_n$.

Доказательство. Проверим выполнение при $|z| = r_0(\beta)$ условия выпуклости $1 + Re\, z\frac{f''(z)}{f'(z)} \geq \beta$ порядка β. В силу оценки (13) получаем

$$1 + Re\, z\frac{f''(z)}{f'(z)} \geq 1 - \frac{2\gamma m r^m}{1-r^{2m}} + \min_{|z|=r} Re\,\frac{\alpha\lambda n z^n}{1-\lambda z^n}. \qquad (20)$$

Осуществляя замену $\zeta = z^n$, нетрудно установить, что

$$\min_{|z|=r} Re\,\frac{\alpha\lambda n z^n}{1-\lambda z^n} = \begin{cases} -\alpha\lambda n r^n/(1+\lambda r^n), \alpha \geq 0 \\ \alpha\lambda n r^n/(1-\lambda r^n), \alpha < 0 \end{cases} = -\frac{|\alpha|\lambda n r^n}{1 + sign\,\alpha \cdot \lambda r^n}.$$

Поэтому в силу (20) при $|z| = r$, где $r = r_0(\beta)$ – наименьший положительный корень уравнения (19), получаем, что для функции $f(z)$ выполняется условие выпуклости порядка β

$$1 + Re\, z\frac{f''(z)}{f'(z)} \geq 1 - \frac{2\gamma m r^m}{1-r^{2m}} - \frac{|\alpha|\lambda n r^n}{1 + sign\,\alpha \cdot \lambda r^n} = \beta.$$

При этом, поскольку функция

$$\mu(r) = \frac{2\gamma m r^m}{1-r^{2m}} + \frac{|\alpha|\lambda n r^n}{1 + sign\,\alpha \cdot \lambda r^n}$$

монотонно возрастает на промежутке $[0,1)$ от 0 до $+\infty$, то $r_0(\beta)$ является единственным корнем уравнение (20) на промежутке $[0,1)$.

Покажем, что радиус выпуклости $r_0(\beta)$ является точным.

Пусть $f(z) \in \mathcal{N}$. Если n – нечетное, то для функции $f_3(z)$ из (18) в точке $z = -r$ в условии выпуклости порядка β достигается знак равенства:

$$1 + z\frac{f_3''(z)}{f_3'(z)}\bigg|_{z=-r} = 1 + \left(\frac{2\gamma z}{1-z^2} + \frac{\alpha\lambda n z^n}{1-\lambda z^n}\right)\bigg|_{z=-r} = 1 - \frac{2\gamma r}{1-r^2} - \frac{\alpha\lambda n r^n}{1+\lambda r^n} = \beta.$$

Если n — четное и $n = 2(2k-1)$, $k \in \mathbb{N}$, то $i^n = -1$ и для $z = ir$ имеем $z^n = -r^n$, $iz = -r$. Поэтому для функции $f_1(z)$ из (16) получаем

$$1 + z\frac{f_1''(z)}{f_1'(z)}\bigg|_{z=ir} = 1 + \left(\frac{2\gamma iz}{1+z^2} + \frac{\alpha\lambda n z^n}{1-\lambda z^n}\right)\bigg|_{z=ir} = 1 - \frac{2\gamma r}{1-r^2} - \frac{\alpha\lambda n r^n}{1+\lambda r^n} = \beta.$$

Если же $n = 4k$, $k \in \mathbb{N}$, то $i^n = 1$ и, если $\varepsilon = i^{\frac{n+2}{n}}$, то для $z = -\varepsilon r$ имеем $z^n = -r^n$, $\varepsilon^{-1}z = -r$. Поэтому для функции $f_2(z)$ из (17) в точке $z = -\varepsilon r$ получаем

$$1 + z\frac{f_2''(z)}{f_2'(z)} = 1 + \left(\frac{2\gamma\varepsilon^{-1}z}{1-\varepsilon^{-2}z^2} + \frac{\alpha\lambda n z^n}{1-\lambda z^n}\right)\bigg|_{z=-\varepsilon r} = 1 - \frac{2\gamma r}{1-r^2} - \frac{\alpha\lambda n r^n}{1+\lambda r^n} = \beta.$$

Поэтому при $r > r_0(\beta)$ на окружности при $|z| = r$ условие выпуклости порядка β будет нарушаться. То есть, радиус выпуклости увеличить нельзя.

Если $f(z) \in \mathcal{N}_n$, то рассмотрев функцию

$$f_6(z) = \int_0^z \left(\frac{1+t^n}{1-t^n}\right)^\gamma \frac{dt}{(1-\lambda t^n)^\alpha} \in C_n(\lambda,\alpha,\gamma),$$

несложно убедиться, что радиус выпуклости является точным. Для нее в условии выпуклости порядка β знак равенства достигается при нечетном n в точке $z = -r$ с учетом того, что $z^n = -r^n$, при четном $n = 2(2k-1)$, $k \in \mathbb{N}$, в точке $z = ir$ с учетом того, что $i^n = -1$ и $z^n = -r^n$, а при четном $n = 4k$, $k \in \mathbb{N}$, в точке $z = i^{\frac{n+2}{n}} r$ с учетом того, что в этом случае $i^n = 1$ и $z^n = -r^n$.

Теорема 2 доказана.

При $\beta = 0$ теорема 2 дает радиусы выпуклости различных подклассов почти выпуклых функций.

Следствие 1. Пусть $f(z) \in \mathcal{N}$. Тогда точные радиусы выпуклости ниже приведенных классов почти выпуклых функций определяются по формуле:

1) $r_0 = \frac{2\gamma+\alpha+\sqrt{(2\gamma+\alpha)^2-4(\alpha-1)}}{2(\alpha-1)}$ для класса $C_1(1,\alpha,\gamma)$: $|arg\,[(1-z)^\alpha f'(z)]| \leq \gamma\frac{\pi}{2}$, $\alpha \in (0;1) \cup (1;2]$;

2) $r_0 = \frac{1}{2\gamma+1}$ для класса $C_1(1,1,\gamma)$: $|arg\,[(1-z)f'(z)]| \le \gamma\frac{\pi}{2}$;

3) $r_0 = 1/3$ для класса $C_1(1,1,1)$: $Re\,[(1-z)f'(z)] \ge 0$;

4) $r_0 = \gamma + 1 + \sqrt{\gamma(\gamma+2)}$ для класса $C_1(1,2,\gamma)$: $|arg\,[(1-z)^2 f'(z)]| \le \gamma\frac{\pi}{2}$;

5) [5] r_0 – единственный на промежутке [0,1) корень уравнения $r^4 - 2\gamma r^3 - 2r^2 - 2\gamma r + 1 = 0$, для класса $C_2(1,1,\gamma)$: $|arg\,[(1-z^2)f'(z)]| \le \gamma\frac{\pi}{2}$;

6) [3] $r_0 = \frac{1}{2}\left(\sqrt{5}+1-\sqrt{2\left(\sqrt{5}+1\right)}\right)$ для класса $C_2(1,1,1)$: $Re\,[(1-z^2)f'(z)] \ge 0$;

7) $r_0 = \sqrt{\gamma^2+1} - \gamma$ для класса $\mathcal{R}(\gamma) = C_1(0,1,\gamma)$: : $|arg\,f'(z)| \le \gamma\frac{\pi}{2}$;

8) [18] $r_0 = \sqrt{2} - 1$ для класса $\mathcal{R} = C_1(1,0,1)$: $Re\,f'(z) \ge 0$.

При $\beta = \lambda = 0$ из уравнения (19) при $m = n$ получаем

$$r_0 = \sqrt[n]{\sqrt{n^2\gamma^2+1} - n\gamma}, \qquad (21)$$

а при $n = 2,\ \lambda = \alpha = 1$ имеем

$$r_0 = \sqrt{2\gamma + 1 - 2\sqrt{\gamma(\gamma+1)}}. \qquad (22)$$

Следствие 2. Радиусы выпуклости классов $\mathcal{R}(\gamma) = C_1(0,1,\gamma) = \left\{f(z) \in \mathcal{N}_n : |arg\,f'(z)| \le \frac{\gamma\pi}{2}\right\}$ при $n \ge 1$ и $C_1(1,2,\gamma) = \left\{f(z) \in \mathcal{N}_n : |arg\,[(1-z)^2 f'(z)]| \le \frac{\gamma\pi}{2}\right\}$ при $n = 2$ определяются по формулам (21) и (22). Результат точный.

Значение радиуса выпуклости (21) получено ранее в [6] и при $\gamma = 1$ – в [19], а радиуса выпуклости (22) – в [5].

4. Теоремы роста и радиусы выпуклости в классе $T_n(\lambda,\alpha,\gamma)$ и его подклассах

Используя взаимосвязь (10) классов $C_n(\lambda,\alpha,\gamma)$ и $T_n(\lambda,\alpha,\gamma)$, также выражающую известную связь [1, с.6] выпуклых и звездообразных функций $f(z) \in S^0 \Leftrightarrow F(z) = zf'(z) \in S^*$, и вытекающее из нее соотношение $zf''(z)/f'(z) = zF'(z)/F(z) - 1$, все результаты предыдущих разделов легко перенести на функции класса $T_n(\lambda,\alpha,\gamma)$.

Теорема 3. Пусть $F(z) \in T_n(\lambda,\alpha,\gamma)$ и $m = 1$ при $F(z) \in \mathcal{N}$ и $m = n$ при $F(z) \in \mathcal{N}_n$. Тогда при $|z| = r$, $0 \le r < 1$, имеют место точные оценки

$$\left(\frac{1-r^m}{1+r^m}\right)^{\gamma} \frac{r}{(1+\lambda r^n)^{\alpha}} \le |F(z)| \le \left(\frac{1+r^m}{1-r^m}\right)^{\gamma} \frac{r}{(1-\lambda r^n)^{\alpha}} \text{ при } \alpha \ge 0, \quad (23)$$

$$\left(\frac{1-r^m}{1+r^m}\right)^{\gamma}\frac{r}{(1-\lambda r^n)^{\alpha}} \le |F(z)| \le \left(\frac{1+r^m}{1-r^m}\right)^{\gamma}\frac{r}{(1+\lambda r^n)^{\alpha}} \text{ при } \alpha < 0, \tag{24}$$

$$\left|z\frac{F'(z)}{F(z)} - \frac{1+\lambda(\alpha n-1)z^n}{1-\lambda z^n}\right| \le \frac{2\gamma m r^m}{1-r^{2m}} \tag{25}$$

и точный радиус звездообразности $r^*(\beta)$ порядка β класса $T_n(\lambda,\alpha,\gamma)$ определяется как единственный на промежутке [0, 1) корень уравнения (19).

Пусть $Im\, F(z) = 0$ при $z \in (-1;1)$ и $Im\, F(z)\cdot Im\, z > 0$ в остальных точках круга E. Тогда при $\lambda = \alpha = 1, m = 2$ получаем подкласс $CS_1^*(\gamma) = T(\gamma)$ типично вещественных функций. Этому частному случаю теоремы 3 соответствует

Следствие 3. Пусть функция $F(z) \in T(\gamma)$, то есть $F(z)$ в точках $z \in (-1;\ 1)$ принимает вещественные значения и удовлетворяет условию

$$\left|arg\left((1-z^2)\,F(z)/z\right)\right| \le \frac{\gamma\pi}{2},\ z \in E.$$

Тогда при $|z| = r$, $0 \le r < 1$, имеют место точные оценки

$$\left(\frac{1-r}{1+r}\right)^{\gamma}\frac{r}{1+r^2} \le |F(z)| \le \left(\frac{1+r}{1-r}\right)^{\gamma}\frac{r}{1-r^2}, \tag{26}$$

$$\left|z\frac{F'(z)}{F(z)} - \frac{1+z^2}{1-z^2}\right| \le \frac{2\gamma r}{1-r^2}. \tag{27}$$

$$\left|z\frac{F'(z)}{F(z)}\right| \le \frac{1+2\gamma r+r^2}{1-r^2}, \tag{28}$$

$$|F'(z)| \le \left(\frac{1+r}{1-r}\right)^{\gamma}\frac{1+2\gamma r+r^2}{(1-r^2)^2}. \tag{29}$$

Оценки (26), (27) – прямые следствия оценок (23), (25). Оценка (28) вытекает из (27). Оценка (29) получается из вытекающего в силу (28) и (26) неравенства

$$\left(\frac{1-r}{1+r}\right)^{\gamma}(1-r^2)|F'(z)| \le \left|z\frac{F'(z)}{F(z)}\right| \le \frac{1+2\gamma r+r^2}{1-r^2}.$$

Отметим, что при $\gamma = 1$ оценки (27), (28) получены в [15], а оценки (26), (29) – в [14].

Следствие 4. Пусть $F(z) \in \mathcal{N}$. Тогда точный радиус звездообразности порядка β ниже приведенных классов почти звездообразных функций определяется как единственный на промежутке [0, 1) корень уравнения:

1) [8] $(1+\beta)r^4 - 2r(r^2+r+1) + (1-\beta) = 0$ для класса $CS_1^* = T_2(1,1,1)$:
$Re\,\{(1-z^2)F(z)/z\} \ge 0$;

2) [9] $(1+\beta)r^2-4r+1-\beta=0$ для класса $CS_2^*=T_1(1,2,1)$: $Re\{(1-z)^2F(z)/z\}\geq 0$, то есть $r^*(\beta)=\left(2-\sqrt{3+\beta^2}\right)/(1+\beta)$;

3) [9] $\beta r^2-3r+1-\beta=0$ для класса $CS_3^*=T_1(1,1,1)$: $Re\{(1-z)F(z)/z\}\geq 0$, то есть $r^*(\beta)=\left(3-\sqrt{9-4\beta(1-\beta)}\right)/(2\beta)$;

4) [10] $(2-\beta)r^3+2\beta r^2+(\beta-6)\,r+2(1-\beta)=0$ для класса $CS_5^*=T_1(1/2,-1,1)=\{F(z)\in\mathcal{N}: Re\,(F(z)/(z-z^2/2))\geq 0\}$;

5) $(1-\beta)r^2+2r-(1-\beta)=0$ для класса $CS_4^*=T_1(0,1,1)=\{F(z)\in\mathcal{N}: Re\,(F(z)/z)\geq 0\}$, то есть $r^*(\beta)=\left(\sqrt{1+(1-\beta)^2}-1\right)/(1-\beta)$.

Пусть $\beta=0$. Поскольку CS_1^* совпадает с классом T типично вещественных функций, если $Im\,F(z)=0$ при $z\in(-1;1)$ и $Im\,F(z)\cdot Im\,z>0$ при $z\in E\backslash(-1;1)$, то из пункта 1) получаем радиус звездообразности [15, 20] $r^*=\frac{1}{2}\left(\sqrt{5}+1-\sqrt{2\left(\sqrt{5}+1\right)}\right)$ класса T. Также, при $\beta=0$ пункт 5) совпадает с результатом из [18] о радиусе звездообразности $r^*=\sqrt{2}-1$ класса $CS_4^*=\{F(z)\in\mathcal{N}: Re\,(F(z)/z)\geq 0\}$.

Заключение

В статье вводятся и исследуются два класса почти выпуклых и почти звездообразных функций, обобщающих ряд известных в литературе классов функций. Для введенных классов получены теоремы искажения (роста) и радиусы выпуклости (звездообразности), в частных случаях дающие как известные результаты, так и новые оригинальные результаты для некоторых малоизученных классов функций. Все полученные оценки и радиусы выпуклости (звездообразности) являются точными.

ЛИТЕРАТУРА

1 Авхадиев Ф.Г., Аксентьев Л.А. Основные результаты в достаточных условиях однолистности аналитических функций // УМН. – 1975. – Т. 30, вып. 4(184). – С. 3–60. https://www.mathnet.ru/links/e7c4d119db41755ee64c4677f4c40f9b/rm4232.pdf.

2 Reade M.O. The coefficients of close-to-convex functions // Duke Math. J. – 1956. – Vol. 23. – No. 3. – P. 459–462. https://doi.org/10.1215/S0012-7094-56-02342-0.

3 Hengartner W., Schober G. Analytic functions close to mappings convex in one direction // Proc. Amer. Math. Soc. – 1971. – Vol. 28. – No. 2. – P. 519–524. https://www.ams.org/journals/proc/1971-028-02/S0002-9939-1971-0277704-9/S0002-9939-1971-0277704-9.pdf.

4 Lecko A. The class of functions convex in the negative direction of the imaginary axis of order (α,β) // J. of the Austr. Math. Soc. – 2002. – Vol. 29. – No. 11. – P. 641–650. https://dx.doi.org/10.1155/S0161171202007810.

5 Майер Ф.Ф. Геометрические свойства некоторых классов аналитических в круге функций, выпуклых в направлении мнимой оси // Костанай. Вестник науки КГУ им. А. Байтурсынова. Серия ест.-техн. наук. – 2002. – Вып. 6. – № 2. – С. 48–50. https://repo.kspi.kz/bitstream/handle/123456789/7030/2002-6-2-page48-50.pdf?sequence=1&isAllowed=y.

6 Майер Ф.Ф., Тастанов М.Г., Утемисова А.А., Байманкулов А.Т. Об обобщении некоторых классов почти выпуклых и типично вещественных функций // Вестник ТГУ, Серия «Математика и механика», Томск. – 2023. – № 84. – С. 147–156. https://cyberleninka.ru/article/n/ob-obobschenii-nekotoryh-klassov-pochti-vypuklyh-i-tipichno-veschestvennyh-funktsiy/viewer.

7 Reade M.O. On close-to-close univalent functions // Michigan Math. J. – 1955. – No. 3. – P. 59–62. https://doi.org/10.1307/mmj/1031710535.

8 Khatter K., Lee S. K., Ravichandran V. Radius of starlikeness for classes of analytic functions // arXiv preprint arXiv:2006.11744. – 2020. doi: https://doi.org/10.48550/arXiv.2006.11744.

9 Sebastianc A., Ravichandran V. Radius of starlikeness of certain analytic functions // Math. Slovaca 71. – 2021. – No. 1. – P. 83–104. https://doi.org/10.1515/ms-2017-0454.

10 Kanaga R., Ravichandran V. Starlikeness for Certain Close-to-Star Functions // Hacet. J. Math. Stat. – 2021. – Vol. 50. – P. 104–118 2, 414–432. https://doi.org/ https://doi.org/10.15672/hujms.702703.

11 Sharma M., Jain N.K., Kumar S. Constrained radius estimates of certain analytic functions // arXiv:2305.16210v1 [math.CV] – 2023.

12 El-Faqeer A.S.A., Mohd M.H., Ravichandran V., Supramaniam S. Starlikeness of certain analytic functions // arXiv preprint arXiv:2006.11734, 2020 arxiv.org. https://doi.org/10.48550/arXiv.2006.11734.

13 Rogosinski W. Über positive harmonische entwicklungen und typisch-reelle potenzreihen // Math. Zeitschr. – 1932. – Vol. 35. – No. 1. – P. 93–121. https://doi.org/10.1007/BF01186552.

14 Голузин Г.М. О типично вещественных функциях // Матем. сб. – 1950. – Вып. 27. – №. 69. – С. 201–218. https://www.mathnet.ru/php/archive.phtml?wshow=paper&jrnid=sm&paperid=5913&option_lang=eng

15 Гельфер С.А. Типично вещественные функции // Матем. сб. – 1964. – Т. 106. – № 2. – С. 171–184. https://www.mathnet.ru/php/archive.phtml?wshow=paper&jrnid=sm&paperid=4441&option_lang=rus.

16 Noshiro K. On the theory of schlicht functions // J. Fac. Sci. Hokkaido Imp. Univ. Ser. I Math. – 1934. – Vol. 2. – No. 3. – P. 129–155. https://doi.org/10.14492/hokmj/1531209828.

17 Голузин Г.М. Геометрическая теория функций комплексного переменного / Г.М. Голузин – М.: Наука, 1966. – 628 с.

18 MacGregor T.H. Functions whose derivative has a positive real part // Trans. Amer. Math. Soc. – 1962. – № 104. – P. 532–537. https://doi.org/10.1090/S0002-9947-1962-0140674-7.

19 Shaffer D.B. Distortion theorems for a special class of analytic functions // Proc. Amer. Math. Soc. – 1973. – Vol. 39. – No. 2. – P. 281–287. https://doi.org/10.2307/2039632.

20 Libera R.J. Some radius of convexity problems // Duke Math. J. – 1964. –Vol. 31. – No.1. – P. 143–158. https://10.1215/S0012-7094-64-03114-X.

REFERENCES

1 Avkhadiev F.G., Aksent'ev L.A. (1975) The main results on sufficient conditions for an analytic function to be schlicht. Russian Mathematical Surveys, vol. 30, no. 4, pp. 1–63. https://www.mathnet.ru/links/1632ed8357df9ffe04ddeebedf7e40ba/rm4232_eng.pdf.

2 Reade M.O. (1956) The coefficients of close-to-convex functions. Duke Math. J., vol. 23, no. 3, pp. 459–462. https://doi.org/10.1215/S0012-7094-56-02342-0.

3 Hengartner W. and Schober G. (1971) Analytic functions close to mappings convex in one direction. Proc. Amer. Math. Soc., vol. 28, no. 2, pp. 519–524. https://www.ams.org/journals/proc/1971-028-02/S0002-9939-1971-0277704-9/S0002-9939-1971-0277704-9.pdf

4 Lecko A. (2002) The class of functions convex in the negative direction of the imaginary axis of order (α,β). J. of the Austr. Math. Soc., vol. 29, no. 11, pp. 641–650. doi: https://dx.doi.org/10.1155/S0161171202007810

5 Maiyer F.F. (2002) Geometricheskie svojstva nekotoryh klassov analiticheskih v kruge funkcij, vypuklyh v napravlenii mnimoj osi. [Geometric properties of some classes of analytic functions in a circle in the direction of the imaginary axis]. Kostanaj. Vestnik nauki KGU im. A. Bajtursynova. Serija estestvenno-tehnicheskih nauk, vol. 6, no. 2, pp. 48–50. https://repo.kspi.kz/bitstream/handle/123456789/7030/2002-6-2-page48-50.pdf?sequence=1&isAllowed=y. [In Russian].

6 Maiyer F.F., Tastanov M.G., Utemisova A.A. and Baimankulov A.T. (2023) Ob obobshhenii nekotoryh klassov pochti vypuklyh i tipichno veshhestvennyh funkcij [On the generalization of some classes of close-to-convex and typically real functions]. Zhurnal «Vestnik TGU», serija «Matematika. Mehanika», Tomsk, no. 80, pp. 147–156. [In Russian]. https://cyberleninka.ru/article/n/ob-obobschenii-nekotoryh-klassov-pochti-vypuklyh-i-tipichno-veschestvennyh-funktsiy/viewer

7 Reade M.O. (1955) On close-to-close univalent functions. Michigan Math. J., no. 3, pp. 59–62.

8 Khatter K., Lee, S. K. and Ravichandran V. (2020) Radius of starlikeness for classes of analytic functions. arXiv preprint arXiv:2006.11744. doi: https://doi.org/10.48550/arXiv.2006.11744.

9 Sebastianc A. and Ravichandran V. (2021) Radius of starlikeness of certain analytic functions. Math. Slovaca, vol. 71, no. 1, pp. 83–104. https://doi.org/10.1515/ms-2017-0454.

10 Kanaga R. and Ravichandran V. (2021) Starlikeness for certain close-to-star functions. Hacet. J. Math. Stat., vol. 50, no. 2, pp. 414–432. https://doi.org/10.15672/hujms.702703.

11 Sharma M., Jain N.K. and Kumar S. (2023) Constrained radius estimates of certain analytic functions. arXiv:2305.16210v1/

12 El-Faqeer A.S.A., Mohd M.H., Ravichandran V. and Supramaniam S. (2020). Starlikeness of certain analytic functions. arXiv preprint arXiv:2006.11734. https://doi.org/10.48550/arXiv.2006.11734.

13 Rogosinski W. (1932) Über positive harmonische entwicklungen und typisch-reelle potenzreihen. Math. Zeitschr., vol. 35, no. 1, pp. 93–121. https://doi.org/10.1007/BF01186552.

14 Goluzin G.M. (1950) On typically real functions. Matem. sb., vol. 27, no. 69, 201–2018. [In Russian]. https://www.mathnet.ru/php/archive.phtml?wshow=paper&jrnid=sm&paperid=5913&option_lang=eng

15 Gelfer S.A. (1964) Tipichno veshhestvennye funkcii [Typically real functions]. Matem. sb., 64(106):2, 171–184. https://www.mathnet.ru/rus/sm4441. [In Russian]

16 Noshiro K. (1934) On the theory of schlicht functions. J. Fac. Sci. Hokkaido Imp. Univ. Ser. I Math., vol. 2, no. 3, pp. 129–155. https://doi.org/10.14492/hokmj/1531209828

17 Goluzin G.M. (1966) Geometricheskaya teoriya funktsiy kompleksnogo peremennogo [Geometric Theory of Functions of a Complex Variable]. Moscow, Nauka Publ., 628 p. [In Russian].

18 MacGregor T.H. (1962) Functions whose derivative has a positive real part. Trans. Amer. Math. Soc., no. 104, pp. 532–537. https://doi.org/10.1090/s0002-9947-1962-0140674-7.

19 Shaffer D.B. (1973) Distortion theorems for a special class of analytic functions. Proc. Amer. Math. Soc., vol. 39, no. 2, pp. 281–287. https://doi.org/10.2307/2039632.

20 Libera R.J. (1964) Some radius of convexity problems. Duke Math. J., vol. 31, no. 1, pp. 143–158. https://10.1215/S0012-7094-64-03114-X.

[1]Maiyer F.F.,
Candidate of Physical and Mathematical Sciences, Professor,
ORCID ID: 0000-0002-2278-2723,
e-mail: maiyer@mail.ru

[1]Tastanov M.G.,
Candidate of Physical and Mathematical Sciences, Professor,
ORCID ID: 0000-0003-1926-8958,
e-mail: tastao@mail.ru

[1*]Utemissova A.A.,
Candidate of Pedagogical Sciences, ORCID ID: 0000-0001-5143-0260,
e-mail: anar_utemisova@mail.ru

[1]Ysmagul R.S.,
Candidate of Physical and Mathematical Sciences, Professor,
ORCID ID: 0009-0007-6594-7958,
e-mail: ismagulr@mail.ru

[1]Non-commercial joint-stock company «Akhmet Baitursynuly Kostanay Regional University»,
Kostanay 110000, Kazakhstan

ON THE GENERALIZATION OF SOME CLASSES OF CONVEX IN DIRECTION AND TYPICALLY REAL FUNCTIONS

Abstract

In the article by M.O. Reade (Duke Math. Journal, 1956) using the condition $\left|\arg\left(f'(z)/g'(z)\right)\right| \leq \frac{\gamma\pi}{2}$, where $g(z)$ is a convex function, $0 \leq \gamma \leq 1$, a class of functions close-

to-convex (almost convex) of order γ is introduced. In our paper, we introduce a subclass of the class of close-to-convex (almost convex) order γ functions satisfying the condition $|arg\ [(1-\lambda z^n)^\alpha f'(z)]\ | \leq \gamma\pi/2$, which, for different parameter values, gives a number of well-known subclasses of univalent (schlicht) functions. Based on this subclass, a class of close-to-starlike (almost star-shaped) functions is constructed, containing a number of subclasses that have been actively studied by many authors in recent years, as well as a classical class of typically real functions. For this classes exact theorems of distortion (growth) and radii of convexity (starlikeness) are obtained, generalizing previously known results. The case is also considered when the functions of the introduced classes have missing members in the power series expansion. The results obtained are accurate and not only generalize previously known results, but also reveal the properties of a number of new subclasses of univalent (schlicht) functions.

Key words: close-to-convex (almost convex) functions, close-to-starlike (almost star-shaped) functions, typically real functions, growth estimates, distortion estimates, radii of convexity, radii of starlikeness.

[1]Майер Ф.Ф.,
физ.-мат. ғылымдарының кандидаты, профессор, ORCID ID: 0000-0002-2278-2723,
e-mail: maiyer@mail.ru
[1]Тастанов М.Г.,
физ.-мат. ғылымдарының кандидаты, профессор, ORCID ID: 0000-0002-2278-2723,
e-mail: maiyer@mail.ru

[1*]Утемисова А.А.,
педагогика ғылымдарының кандидаты, ORCID ID: 0000-0001-5143-0260,
*e-mail: anar_utemisova@mail.ru

[1]Ысмағұл Р.С.,
физ.-мат. ғылымдарының кандидаты, профессор, ORCID ID: 0009-0007-6594-7958,
e-mail: ismagulr@mail.ru

[1]«Ахмет Байтұрсынұлы атындағы Қостанай өңірлік университеті» КЕАҚ, Қостанай қ., 110000, Қазақстан

БАҒЫТТАҒЫ ДӨҢЕС ФУНКЦИЯЛАРДЫҢ КЕЙБІР КЛАССТАРЫН ЖӘНЕ ТИПТІК НАҚТЫ ФУНКЦИЯЛАРДЫ ЖАЛПЫЛАУ ТУРАЛЫ

Аңдатпа

М.О. Ридтің (M.O. Reade Duke Math. Journal, 1956) мақаласында $\left|\arg\left(f'(z)/\,g'(z)\right)\right| \leq \frac{\gamma\pi}{2}$, мұндағы g(z) – дөңес функция, $0 \leq \gamma \leq 1$ шартының көмегімен γ ретті дөңес дерлік функциялар классы енгізілген. Біздің мақаламызда параметрлердің әртүрлі мәндерінде бір парақты функциялардың белгілі қосалқы классын беретін және $|arg[(1-\lambda z^n)^\alpha f'(z)]| \leq \gamma\pi/2$ шартын қанағаттандыратын γ ретті дөңес дерлік функциялар классының қосалқы классы енгізілді. Осы қосалқы класстың негізінде, соңғы жылдары көптеген авторлар белсенді түрде зерттеген құрамына бірқатар қосалқы класстар кіретін жұлдыз тәрізді дерлік функциялар классы мен әдепкі нақты функциялардың классикалық классы құрылды. Бұл класстар үшін сәйкесінше бұрмалану (өсу) және дөңестік радиустар (жұлдыз тәрізді) туралы теоремалар алынды. Сондай-ақ зерттелетін функциялар қатарларға жіктелген кезде мүшелерін өткізіп жіберетін жағдай да қарастырылған. Алынған нәтижелер дәл және бұрын белгілі нәтижелерді жалпылап қана қоймай, сонымен қатар бір парақты фунуциялардың жаңа қосалқы класстарының қасиеттерін де ашады.

Тірек сөздер: дөңес дерлік функциялар, жұлдыз тәрізді дерлік функциялар, әдепкі нақты функциялар, өсуді бағалау, бұрмалануды бағалау, дөңестік радиустар, жұлдыз тәрізді радиустар.

Дата поступления статьи в редакцию: 03.06.2024

ӘОЖ 517.956.3
ҒТАХР 27.31.33, 27.31.44

https://doi.org/10.55452/1998-6688-2024-21-3-191-200

[1*]Асанова А.Т.,
ф.-м.ғ.д., б.ғ.к., ORCID ID: 0000-0001-8697-8920,
e-mail: assanova@math.kz
[1]Бименова Р.А.,
ORCID ID: 0009-0002-9456-3025,
e-mail: b.rabiga@mail.ru
[1,2]Минглибаева Б.Б.,
ф.-м.ғ.к., аға оқытушы, а.ғ.к., ORCID ID: 0000-0002-7195-4480,
e-mail: bayan_math@mail.ru
[3]Сабалахова А.П.,
аға оқытушы, ORCID ID: 0000-0003-1921-0174,
e-mail: sabalahova@mail.ru

[1]Математика және математикалық моделдеу институты, 050010, Алматы қ., Қазақстан
[2]Қазақ ұлттық қыздар педагогикалық университеті, 050000, Алматы қ., Қазақстан
[3]М. Әуезов атындағы Оңтүстік Қазақстан университеті, 160012, Шымкент қ., Қазақстан

ИМПУЛЬСТІ ДИСКРЕТТІ ЖАДЫ БАР ЖОҒАРҒЫ РЕТТІ ГИПЕРБОЛАЛЫҚ ТЕҢДЕУ ҮШІН ШЕТТІК ЕСЕП ТУРАЛЫ

Аңдатпа

Импульс әсері бар дискрет жадылы гиперболалық жоғарғы ретті теңдеу үшін шеттік есеп тіктөртбұрышты облыста зерттеледі. Қарастырылатын есеп жаңадан енгізілетін функциялар көмегімен импульс әсері бар дискрет жадылы белгісіз функциялардан тәуелді бірінші ретті дифференциалдық теңдеулер жүйесіне және интегралдық теңдеулерге әкелінеді. Осы пара-пар есепке Д.С. Жұмабаевтың параметрлеу әдісі қолданылады. Облысты уақыт айнымалысы бойынша бөлу және ішкі облыстарда дискретті жады мәндерінде функционалдық параметрлерді енгізу арқылы зерттелген импульс әсері бар дискрет жадылы белгісіз функциялардан тәуелді бірінші ретті дифференциалдық теңдеулер жүйесі зерттелді. Бұл пара-пар есептер жүйесі интегралдық-көп нүктелі шеттік есептерге келтіріледі, нәтижесінде функционалдық параметрлері мен белгісіз функциялары бар жаңа есептер туады. Шыққан пара-пар есептер жаңа функцияларға қатысты дифференциалдық бірінші ретті теңдеулер жүйесі арқылы алғашқы есептерді қамтиды. Алғашқы есептердің шешімдері Вольтер интегралдық теңдеулері арқылы өрнектеледі. Бұл шешімдерді шеттік шарттар мен импульс шарттарына қойып, функционалдық параметрлер бойынша сызықтық функционалдық теңдеулер жүйесі құрылады. Шыққан пара-пар есептердің шешімдерін табу жолдарын сипаттайтын алгоритм ұсынылады. Интегралдық-көп нүктелі шеттік есептердің функционалдық параметрлері мен белгісіз функцияларға тәуелділігі кезінде бірмәнді шешімділіктің жеткілікті шарттары тұжырымдалады. Сонымен қатар, импульсті дискрет жадылы жоғарғы ретті гиперболалық теңдеу үшін шеттік есептің бастапқы шарттары тұрғысынан оның бірмәнді шешімділігінің жеткілікті шарттары анықталады.

Тірек сөздер: импульсті дискретті жады, жоғарғы ретті гиперболалық теңдеу, шеттік есептер әулеті, функционалдық-дифференциалдық теңдеулер.

Кіріспе

Мақалада тіктөртбұрышты $\Pi = [0,T] \times [0,\Omega]$ облысында келесі түрдегі импульсті дискретті жады бар жоғарғы ретті гиперболалық теңдеу үшін

$$\frac{\partial^{n+1} z}{\partial x^n \partial t} = \sum_{j=1}^{n} a_j(t,x) \frac{\partial^j z}{\partial x^j} + \sum_{j=1}^{n} b_j(t,x) \frac{\partial^j z}{\partial x^{j-1} \partial t} + c(t,x)z + g(t,x) +$$

$$+\sum_{j=1}^{n} a_{0j}(t,x)\frac{\partial^j z(\eta(t),x)}{\partial x^j}+\sum_{j=1}^{n} b_{0j}(t,x)\frac{\partial^j z(\eta(t),x)}{\partial x^{j-1}\partial t}+c_0(t,x)z(\eta(t),x),$$
$$t\neq\tau_i,\quad i=\overline{1,L-1}, \tag{1}$$

қос нүктелі бейлокал шарты

$$p(x)\frac{\partial^n z(0,x)}{\partial x^n}+s(x)\frac{\partial^n z(\mathrm{T},x)}{\partial x^n}=\omega_0(x),\qquad x\in[0,\omega], \tag{2}$$

импульс шарттары

$$\lim_{t\to\tau_i+0}\frac{\partial^n z(t,x)}{\partial x^n}-\lim_{t\to\tau_i-0}\frac{\partial^n z(t,x)}{\partial x^n}=\omega_i(x),\qquad x\in[0,\omega],\quad i=\overline{1,L-1}, \tag{3}$$

сипаттамалардағы шарттары

$$z(t,0)=\phi_0(t),\ \frac{\partial z(t,0)}{\partial x}=\phi_1(t),\ \ldots,\ \frac{\partial^{n-1} z(t,0)}{\partial x^{n-1}}=\phi_{m-1}(t),\quad t\in[0,T], \tag{4}$$

түрінде берілген қос нүктелі бейлокал есеп қарастырылады.

Мұнда $z(t,x)$ – белгісіз функция, $a_j(t,x)$, $b_j(t,x)$, $c(t,x)$, $a_{0j}(t,x)$, $b_{0j}(t,x)$, $c_0(t,x)$ және $g(t,x)$ функциялары Π облысында үзіліссіз,

$$\eta(t)=\zeta_r,\quad t\in[\tau_{r-1},\tau_r),\quad \tau_{r-1}\le\zeta_r<\tau_r,\quad r=\overline{1,L},$$
$$0=\tau_0<\tau_1<\cdots<\tau_{L-1}<\tau_L=\mathrm{T},$$

$p(x)$, $s(x)$ және $\omega_0(x)$ функциялары $[0,\Omega]$ кесіндісінде үзіліссіз, $\omega_i(x)$ функциялары $[0,\Omega]$ кесіндісінде үзіліссіз, $i=\overline{1,L-1}$, $\phi_s(t)$ функциялары $[0,\mathrm{T}]$ кесіндісінде үзіліссіз дифференциалданады, $s=\overline{0,n-1}$.

$\Pi_r=[\tau_{r-1},\tau_r)\times[0,\Omega]$, $r=\overline{1,L}$, белгілеулерін енгізейік, яғни $\Pi=\cup_{r=1}^{L}\Pi_r$.

$PC(\Pi,\{\tau_j\}_{i=1}^{L-1},\mathbb{R})$ – Π облысындағы $t=\tau_i$, $i=\overline{1,L-1}$, сызықтарында мүмкін үзілістері болатын бөлікті үзіліссіз $z(t,x)$ функцияларының кеңістігі болсын және нормасы $||z||_1=\max\limits_{r=\overline{1,L}}\sup\limits_{(t,x)\in\Pi_r}||z(t,x)||$.

Егер $z(t,x)\in PC(\Pi,\{\tau_j\}_{i=1}^{L-1},\mathbb{R})$ функциясы келесі шарттарды қанағаттандырса:

(i) $z(t,x)$ функциясының $\frac{\partial^j z(t,x)}{\partial x^j}\in PC\left(\Pi,\{\tau_j\}_{i=1}^{L-1},\mathbb{R}\right)$, $\frac{\partial^j z(t,x)}{\partial x^{j-1}\partial t}\in PC(\Pi,\{\tau_j\}_{i=1}^{L-1},\mathbb{R})$ дербес туындылары бар болса, мұнда $j=\overline{1,n}$;

(ii) $\frac{\partial^{n+1} z(t,x)}{\partial x^n\partial t}$ жоғарғы ретті аралас дербес туындысы, $t=\tau_i$, $i=\overline{1,L-1}$, сызықтарындағы мүмкін үзілістерін қоспағанда, әрбір $(t,x)\in\Pi$ нүктелерінде бар болса, мұнда барлық $x\in[0,\Omega]$ үшін біржақты жоғарғы ретті аралас дербес туындылары бар болады;

(iii) (1) гиперболалық теңдеулер жүйесі әрбір $[\tau_i,\tau_{i+1})\times[0,\Omega]$, мұнда $i=\overline{0,L-1}$, ішкі облысындағы $z(t,x)$ функциясы үшін орындалады және ол (τ_i,x) нүктелеріндегі $z(t,x)$ функциясының оң жақты жоғарғы ретті аралас дербес туындысы үшін орындалады, мұнда $i=\overline{0,L-1}$, $x\in[0,\Omega]$;

(iv) шеттік (2) және (4) сипаттамадағы шарттар сәйкесінше $t=0$, $t=\mathrm{T}$, $x=0$

сызықтарында $z(t,x)$ функциясының дербес туындылары үшін орындалады. (v) $z(t,x)$ функциясының $t=\tau_i,\ i=\overline{1,L-1}$ сызықтарындағы дербес туындылары үшін импульстік әсерлердің (3) шарттары барлық $x\in[0,\Omega]$ үшін орындалады;

онда (1)–(4) есебінің шешімі деп аталады.

Дискретті жадылы гиперболалық теңдеулер көптеген құбылыстарды математикалық модельдеу кезінде туындайды. Осындай теңдеулердің ішінде импульстік әсерлері бар дискретті жадылы гиперболалық теңдеулер ерекше орын алады. Бұл нейрондық желілер мен динамикалық жүйелерді зерттеу барысында импульстік әсерлі дискретті жадылы гиперболалық теңдеулерге арналған әртүрлі шеттік есептерді зерттеу қажеттілігімен байланысты. Осындай есептердің шешімдерінің бар болуы мен жалғыздығы, шешімдердің бастапқы деректерден үзіліссіз тәуелділігі, сондай-ақ шешімдерді құру әдістері мен жолдары әлі де толық зерттелмей, өзекті болып отыр.

Оған қоса, импульсті дискретті жады бар жоғары ретті гиперболалық теңдеулер үшін шеттік есептерді шешу әдістерінің тапшылығы бұл есептерді зерттеуге арналған жаңа конструктивті әдістерді әзірлеуге итермелейді. Импульсті гиперболалық екінші ретті теңдеулер үшін түрлі шеттік есептерді шешуге Д.С. Жұмабаевтың параметрлеу әдісінің модификациялары [1–13] еңбектерінде ұсынылған болатын. Осы модификациялар арқылы қарастырылған есептердің бірмәнді шешімділік шарттары, шешімдерді тұрғызу алгоритмдері және табу жолдары көрсетілген. Алынған нәтижелер импульсті жоғары ретті гиперболалық теңдеулерге де дамытылды [14, 15].

Екінші жағынан, дискретті жады деп аталатын жалпыланған құрақты-тұрақты аргументті дифференциалдық теңдеулер теориясы соңғы жылдары үлкен қарқынмен дамып келеді [16–21]. Бұл үзілістері бар дифференциалдық теңдеулер теориясындағы маңызды орын алатын функционалдық-дифференциалдық теңдеулердің белгілі өкілі болып табылады және құбылыстарды барынша дәл сипаттайтын модельдерге негізделген.

Жалпыланған құрақты-тұрақты аргументті дифференциалдық және гиперболалық теңдеулер үшін әртүрлі шеттік есептерді шешуде параметрлеу әдісінің тиімділігі мен әмбебаптығы көрсетілді [11, 22].

Осы жоғарыда келтірілгендердің негізінде импульсті дискретті жады бар жоғары ретті гиперболалық теңдеулер үшін шеттік есептерді зерттеу және шешу мәселесі қазіргі уақытта үзілісті дифференциалдық теңдеулер теориясындағы аса өзекті әрі маңызды сұрақтардың бірі болып отыр. Осы бағыттағы алғашқы жұмыс импульсті дискретті жады бар екінші ретті гиперболалық теңдеулер жүйесі үшін шеттік есепті шешуге арналды [23].

Осы есептің бірмәнді шешімділік шарттары анықталып, жуық шешімді табу алгоритмдері ұсынылған. Шешімділік шарттары теңдеудің коэффициенттері мен шекаралық матрицалар арқылы арнайы құрылған функционалдық матрицаның қайтарымдылығы терминінде анықталған.

Ұсынылған әдіс енді (1)–(4) импульсті дискретті жады бар жоғары ретті гиперболалық теңдеу үшін шеттік есепті зерттеуге және шешуге бейімделеді. Зерттеліп отырған есеп жаңа ізделінді функцияларды енгізу арқылы импульсті дискретті жады бар бірінші ретті дифференциалдық теңдеулер үшін қос нүктелі шеттік есептер жүйесіне және интегралдық қатынастарға келтіріледі. Пара-пар есепті шешу алгоритмдері ұсынылып, олардың жинақтылығы дәлелденеді. (1)–(4) есебінің бірмәнді шешімділік шарттары анықталады.

Материалдар мен әдістер

Жаңа функциялар енгізу әдісі пайдаланылады және пара-пар есепке келтіріледі. Алдымен, $u_1(t,x) = z(t,x)$, $u_2(t,x) = \frac{\partial z(t,x)}{\partial x}$, …, $u_n(t,x) = \frac{\partial^{n-1} z(t,x)}{\partial x^{n-1}}$, $v(t,x) = \frac{\partial^n z(t,x)}{\partial x^n}$ жаңа белгісіз функцияларын енгізейік.

Онда (1)-(4) есебі келесідей жаңа есепке келеді:

$$\frac{\partial v}{\partial t} = a_n(t,x)v(t,x) + a_{0n}(t,x)v(\eta(t),x) + \sum_{j=1}^{n-1} a_j(t,x)\, u_{j+1}(t,x) + \sum_{j=1}^{n} b_j(t,x)\frac{\partial u_j(t,x)}{\partial t} + c(t,x)u_1(t,x) + g(t,x) + \sum_{j=1}^{n-1} a_{0j}(t,x)u_{j+1}(\eta(t),x) + \sum_{j=1}^{n} b_{0j}(t,x)\,\frac{u_j(\eta(t),x)}{\partial t} + c_0(t,x)u_1(\eta(t),x)$$

$$t \neq \tau_i, \quad i = \overline{1,L-1}, \tag{5}$$

$$p(x)v(0,x) + s(x)\,v(\mathrm{T},x) = \omega_0(x), \qquad x \in [0,\Omega], \tag{6}$$

$$\lim_{t\to\tau_i+0} v(t,x) - \lim_{t\to\tau_i-0} v(t,x) = \omega_i(x), \qquad x \in [0,\Omega], \quad i = \overline{1,L-1}, \tag{7}$$

$$u_s(t,x) = \phi_{s-1}(t) + \int_0^x u_{s+1}(t,\theta)d\theta\,, \quad s = \overline{1,n-1}, \quad (t,x) \in \Pi, \tag{8}$$

$$u_n(t,x) = \phi_{n-1}(t) + \int_0^x v(t,\theta)d\theta\,, \qquad (t,x) \in \Pi, \tag{9}$$

мұнда (8), (9) интегралдық қатынастарында (4) сипаттамалардағы шарттар ескерілген.

(5)–(9) есебі – $u_s(t,x)$, $s = \overline{1,n}$, белгісіз функциялардан тәуелді импульсті дискретті жады бар бірінші ретті дифференциалдық теңдеулер үшін $v(t,x)$ функциясына қатысты қос нүктелі шеттік есептер әулеті болып табылады.

(5)–(9) есебін шешуге Д.С. Жұмабаевтың параметрлеу әдісі қолданылады.

$\Pi = \bigcup_{r=1}^{L} \Pi_r$ екенін ескерсек, ізделінді $v(t,x)$ функциясының бөлінген ішкі облыстарға сығылуын $v_r(t,x)$, $(t,x) \in \Pi_r$, $r = \overline{1,L}$, деп белгілейік. $\xi_r(x) = v_r(\zeta_{r-1},x)$, $r = \overline{1,L}$, қосымша параметрлерін енгізіп және әрбір Π_r, $r = \overline{1,L}$, ішкі облыстарында $w_r(t,x) = v_r(t,x) - \xi_r(x)$, $r = \overline{1,L}$, алмастырулары орындалса, (5)–(9) есебі келесі түрдегі функционалдық параметрлері мен белгісіз функциялары бар бірінші ретті дифференциалдық теңдеулер үшін көп нүктелі интегралдық шеттік есептер әулетіне келеді:

$$\frac{\partial w_r}{\partial t} = a_n(t,x)w_r(t,x) + [a_n(t,x) + a_{0n}(t,x)]\xi_r(x) + \sum_{j=1}^{n-1} a_j(t,x)\, u_{j+1}(t,x) + \sum_{j=1}^{n} b_j(t,x)\frac{\partial u_j(t,x)}{\partial t} + c(t,x)u_1(t,x) + g(t,x) + \sum_{j=1}^{n-1} a_{0j}(t,x)u_{j+1}(\zeta_{r-1},x) + \sum_{j=1}^{n} b_{0j}(t,x)\,\frac{u_j(\zeta_{r-1},x)}{\partial t} + c_0(t,x)u_1(\zeta_{r-1},x)$$

$$(t,x) \in \Pi_r, \quad r = \overline{1,L}, \tag{10}$$

$$w_r(\zeta_{r-1},x) = 0, \quad x \in [0,\Omega], \quad r = \overline{1,L}, \tag{11}$$

$$p(x)w_1(0,x) + p(x)\xi_1(x) + s(x)\lim_{t\to T-0} w_L(t,x) + s(x)\xi_L(x) = \omega_0(x), \quad x \in [0,\omega], \tag{12}$$

$$\lim_{t\to\tau_i+0} w_{i+1}(t,x) + \xi_{i+1}(x) - \lim_{t\to\tau_i-0} w_i(t,x) - \xi_i(x) = \omega_i(x), \quad x \in [0,\Omega], \quad i = \overline{1.L-1}, \tag{13}$$

$$u_s(t,x) = \phi_{s-1}(t) + \int_0^x u_{s+1}(t,\theta)d\theta, \quad s = \overline{1,n-1}, \quad (t,x) \in \Pi, \tag{14}$$

$$u_n(t,x) = \phi_{n-1}(t) + \int_0^x w_r(t,\theta)d\theta + \int_0^x \xi_r(\theta)d\theta, \quad (t,x) \in \Pi_r, \quad r = \overline{1,L}, \tag{15}$$

Функционалдық параметрлердің бекітілген мәндерінде (10), (11) есебі $w_r(t,x)$ функциясына қатысты бірінші ретті дифференциалдық теңдеулер үшін алғашқы есептер әулеті болып табылады. (12) және (13) қатынастары $\xi_r(x)$, $r = \overline{1,L}$, функционалдық параметрлерін анықтауға мүмкіндік берсе, (14) және (15) интегралдық қатынастары белгісіз $u_s(t,x)$, $s = \overline{1,n}$, функцияларын табуға қажет.

Сонымен, $\{w([t],x), \xi(x), U(t,x)\}$ функциялар үштігі, мұнда

$(w[t],x) = (w_1(t,x), w_2(t,x), \dots, w_L(t,x))$, $\xi(x) = (\xi_1(x), \xi_2(x), \dots, \xi_L(x))$,

$U(t,x) = (u_1(t,x), u_2(t,x), \dots, u_n(t,x))$, (10)–(15) пара-пар есебінің шешімі дейміз, егер $w_r(t,x)$, $\xi_r(x)$, және $u_s(t,x)$ функциялары (10) дифференциалдық теңдеулерін барлық $(t,x) \in \Pi_r$ үшін, (11) алғашқы шарттарын, (12), (13) қатынастарын барлық $x \in [0,\Omega]$ үшін және (14), (15) интегралдық қатынастарын қанағаттандыратын болса, $r = \overline{1,L}$, $s = \overline{1,n}$.

$\xi_r(x)$, $r = \overline{1,L}$, функционалдық параметрлерінің және $u_s(t,x)$, $s = \overline{1,n}$, белгісіз функцияларының бекітілген мәндерінде (10), (11) бастапқы есептерінің әулеті Вольтер интегралдық теңдеулерге пара-пар болады:

$$w_r(t,x) = \int_{\zeta_{r-1}}^t a_n(\tau,x)w_r(\tau,x)d\tau + \int_{\zeta_{r-1}}^t [a_n(\tau,x) + a_{0n}(\tau,x)]d\tau\xi_r(x) + \int_{\zeta_{r-1}}^t g(\tau,x)d\tau + \int_{\xi_{r-1}}^t \tilde{H}_r(\tau,x,u_1,u_2,\dots,u_m)d\tau, \quad (t,x) \in \Pi_r, \quad r = \overline{1,L}, \tag{16}$$

мұнда

$\tilde{H}_r(t,x,u_1,u_2,\dots,u_m) = \sum_{j=1}^{n-1} a_j(t,x)u_{j+1}(t,x) + \sum_{j=1}^{n} b_j(t,x)\frac{\partial u_j(t,x)}{\partial t} + c(t,x)u_1(t,x) + \sum_{j=1}^{n-1} a_{0j}(t,x)u_{j+1}(\zeta_{r-1},x) + \sum_{j=1}^{n} b_{0j}(t,x)\frac{u_i(\zeta_{r-1},x)}{\partial t} + c_0(t,x)u_1(\zeta_{r-1},x)$,

$r = \overline{1,L}$.

(16) теңдеулерінен $w_1(0,x)$, $\lim_{t\to T-0} w_L(t,x)$, $\lim_{t\to\tau_i+0} w_{i+1}(t,x)$, $\lim_{t\to\tau_i-0} w_i(t,x)$, $i = \overline{1,L-1}$, шектерін анықтап, табылған өрнектерді (12), (13) қатынастарындағы сәйкес мәндерге қойып, $\xi_r(x)$, $r = \overline{1,L}$, функционалдық параметрлері үшін сызықты функционалдық теңдеулер жүйесін аламыз:

$$Q(x)\xi(x) = -\mathcal{F}(x) - \mathcal{H}(x,U) - \mathcal{G}(x,w), \quad \xi(x) \in C([0,\Omega],\mathbb{R}^L), \tag{17}$$

мұндағы

$$Q(x) =$$

$$\begin{vmatrix} p(x)_{[1}+\mathcal{D}_1(0,x)] & 0 & 0 & \cdots & 0 & 0 & s(x)[1+\mathcal{D}_L(\mathrm{T},x)] \\ -1-\mathcal{D}_1(\tau_1,x) & {}_{1}+D_2(\tau_1,x) & 0 & \cdots & 0 & 0 & 0 \\ 0 & -1-\mathcal{D}_2(\tau_2,x) & {}_{+}\mathcal{D}_3(\tau_2,x) & \cdots & 0 & 0 & 0 \\ \cdots & \cdots & \cdots & \cdots & \cdots & \cdots & \cdots \\ 0 & 0 & 0 & \cdots & 0 & -1-\mathcal{D}_{L-1}(\tau_{L-} & 1+\mathcal{D}_L(\tau_{L-1},x) \end{vmatrix}$$

$$\mathcal{D}_r(t,x)=\int_{\zeta_{r-1}}^{t}[a_n(\tau,x)+a_{0n}(\tau,x)]d\tau,\quad \mathcal{F}_r(t,x)=\int_{\zeta_{r-1}}^{t}g(\tau,x)d\tau,$$
$$\mathcal{H}_r(t,x,U)=\int_{\zeta_{r-1}}^{t}\tilde{H}_r(\tau,x,u_1,u_2,\dots,u_n)d\tau,$$
$$\mathcal{G}_r(t,x,w)=\int_{\zeta_{r-1}}^{t}a_n(\tau,x)w_r(\tau,x)d\tau,$$
$$\mathcal{F}(x)=\big(-\omega_0(x)+s(x)\mathcal{F}_1(0,x)+s(x)\mathcal{F}_L(\mathrm{T},x),\ -\mathcal{F}_1(\tau_1,x)+\mathcal{F}_2(\tau_1,x),\dots,-\mathcal{F}_{L-1}(\tau_{L-1},x)+\mathcal{F}_L(\tau_{L-1},x)\big),$$
$$\mathcal{H}(x,U)=\big(p(x)\mathcal{H}_1(0,x,U)+s(x)\mathcal{H}_L(\mathrm{T},x,U),\ -\mathcal{H}_1(\tau_1,x,U)+\mathcal{H}_2(\tau_1,x,U),\dots,-\mathcal{H}_{L-1}(\tau_{L-1},x,U)+\mathcal{H}_L(\tau_{L-1},x,U)\big),$$
$$\mathcal{G}(x,w)=\big(p(x)\mathcal{G}_1(0,x,w)+s(x)\mathcal{G}_L(\mathrm{T},x,w),\ -\mathcal{G}_1(\tau_1,x,w)+\mathcal{G}_2(\tau_1,x,w),\ \dots,\ -\mathcal{G}_{L-1}(\tau_{L-1},x,w)+\mathcal{G}_L(\tau_{L-1},x,w)\big).$$

Нәтижелер мен талқылау

Сонымен, белгісіз $\xi(x)=(\xi_1(x),\ \xi_2(x),\dots,\xi_L(x))$ функционалдық параметрлерін табу үшін (17) сызықты функционалдық теңдеулер жүйесін алдық, белгісіз $U(t,x)=(u_1(t,x),u_2(t,x),\dots,u_n(t,x))$ функцияларын (14), (15) интегралдық қатынастарынан анықтаймыз, ал белгісіз $w([t],x)=(w_1(t,x),w_2(t,x),\dots,w_L(t,x))$ функциялар жүйесін (10), (11) бастапқы есептер әулетінен табамыз. Әрі қарай пар-пар (10)–(15) есебінің шешімдерін келесі алгоритм көмегімен табылатын $\{w^{(m)}([t],x),\xi^{(m)}(x),U^{(m)}(t,x)\}$, $m=0,1,\dots$, үштіктерінен тұратын тізбектің шегі түрінде анықталады.

0-інші қадам:

а) алдымен $Q(x)$ матрицасының барлық $x\in[0,\Omega]$ үшін кері матрицасы бар болсын деп болжайық, функционалдық $\xi(x)$ параметрі бойынша алғашқы жуықтауды

$Q(x)\xi(x)=-\mathcal{F}(x)-\mathcal{H}(x,\Phi)$,

теңдеуінен табамыз, мұнда $\Phi(t)=\big(\phi_0(t),\phi_1(t),\dots,\phi_{n-1}(t)\big)$,

яғни $\xi^{(0)}(x)=-[Q(x)]^{-1}\{\mathcal{F}(x)+\mathcal{H}(x,\Phi)\}$;

ә) табылған $\xi^{(0)}(x)$ пайдаланып және $(t,x)\in\Pi_r$, $r=\overline{1,L}$, ішкі облыстарында (15) интегралдық қатынасында $\xi_r(x)=\xi_r^{(0)}(x)$, $w_r(t,x)=0$, $r=\overline{1,L}$, болғанда

$u_n^{(0)}(t,x)$ бастапқы жуықтауын анықтаймыз:

$$u_n^{(0)}(t,x)=\phi_{n-1}(t)+\int_0^x\xi_r^{(0)}(\theta)d\theta,\qquad (t,x)\in\Pi_r,\qquad r=\overline{1,L},$$

одан кейін $u_n^{(0)}(t,x)$ функциясын пайдаланып, қалған функцияларды (14) интегралдық қатынастарынан біртіндеп табамыз:

$$u_s^{(0)}(t,x)=\phi_{s-1}(t)+\int_0^x u_{s+1}^{(0)}(t,\theta)\,d\theta,\quad s=\overline{1,n-1},\quad (t,x)\in\Pi,$$

б) (10) дифференциалдық теңдеулерінің оң жағында $\xi_r(x) = \xi_r^{(0)}(x), \quad r = \overline{1,L}$, $u_s(t,x) = u_s^{(0)}(t,x), \ s = \overline{1,n}$, деп алып, (10), (11) бастапқы есептер әулетін шешіп $w^{(0)}([t],x) = (w_1^{(0)}(t,x), w_2^{(0)}(t,x), \dots, w_L^{(0)}(t,x))$ функцияларын табамыз.

m-інші қадам:

а) табылған $U^{(m-1)}(t,x) = (u_1^{(m-1)}(t,x), u_2^{(m-1)}(t,x), \dots, u_n^{(m-1)}(t,x))$ және $w^{(m-1)}([t],x) = (w_1^{(m-1)}(t,x), w_2^{(m-1)}(t,x), \dots, w_L^{(m-1)}(t,x)), \ m = 1,2,\dots,$ функцияларын (17) сызықты функционалдық теңдеулер жүйесінің оң жағына қойып,

$Q(x)\xi(x) = -\mathcal{F}(x) - \mathcal{H}(x, U^{(k-1)}) - \mathcal{G}\left(x, w^{(m-1)}\right),$

теңдеуінен $\xi^{(m)}(x) = (\xi_1^{(m)}(x), \xi_2^{(m)}(x), \dots, \xi_L^{(m)}(x)), \ m = 1,2,\dots,$ функционалдық параметрін табамыз;

ә) анықталған $\xi^{(m)}(x)$ параметрін пайдаланып және $(t,x) \in \Pi_r, \quad r = \overline{1,L}$, ішкі облыстарында (15) интегралдық қатынасында $\xi_r(x) = \xi_r^{(m)}(x), \ w_r(t,x) = w_r^{(m-1)}(t,x), \ r = \overline{1,L}$, болғанда $u_n^{(m)}(t,x)$ жуықтауын анықтаймыз:

$$u_n^{(m)}(t,x) = \phi_{n-1}(t) + \int_0^x \xi_r^{(m)}(\theta)d\theta, \qquad (t,x) \in \Pi_r, \qquad r = \overline{1,L},$$

одан кейін $u_n^{(m)}(t,x)$ функциясын пайдаланып, қалған функцияларды (14) интегралдық қатынастарынан біртіндеп табамыз:

$$u_s^{(m)}(t,x) = \phi_{s-1}(t) + \int_0^x u_{s+1}^{(k)}(t,\theta)\, d\theta \ , \quad s = \overline{1,n-1}, \quad (t,x) \in \Pi,$$

б) (10) дифференциалдық теңдеулерінің оң жағында $\xi_r(x) = \xi_r^{(m)}(x), \quad r = \overline{1,L}$, $u_s(t,x) = u_s^{(m)}(t,x), \ s = \overline{1,n}$, деп алып, (10), (11) бастапқы есептер әулетін шешіп $w^{(m)}([t],x) = (w_1^{(m)}(t,x), w_2^{(m)}(t,x), \dots, w_L^{(m)}(t,x))$ функцияларын табамыз.

Сонымен $\{w^{(m)}([t],x), \xi^{(m)}(x), U^{(m)}(t,x)\}, \ m = 0,1,2,\dots$ үштіктер жүйесін аламыз.

Белгілеулер енгізейік

$\alpha_n(x) = \max\limits_{t\in[0,T]} ||a_n(t,x)||, \ \alpha_{0n}(x) = \max\limits_{t\in[0,T]} ||a_{0n}(t,x)||,$

$\vartheta = \max\limits_{r=\overline{1,L}}(\tau_r - \zeta_{r-1}, \zeta_{r-1} - \tau_{r-1}).$

Құрылған алгоритмнің жүзеге асырылуы мен (10)–(15) есебінің жалғыз шешіміне жинақталуының жеткілікті шарттары келесі тұжырымда баяндалады:

Теорема 1. Егер $Q(x)$ матрицасы барлық $x \in [0,\Omega]$ үшін қайтарымды болса және

$i) \ \|[Q(x)]^{-1}\| \le q(x),$

мұнда $q(x)$ – оң, $[0,\Omega]$ аралығында үзіліссіз функция,

$ii) \ h(x) = q(x)\max(2, \|p(x)\| + \|s(x)\|)$

$\alpha_n(x)\vartheta\left\{e^{\alpha_n(x)\vartheta} - 1 + \vartheta\alpha_{0n}(x)e^{\alpha_n(x)\vartheta}\right\} \le \gamma < 1,$

мұнда γ – оң тұрақты.

Онда (10)–(15) есебі бірмәнді шешімді болады.

(1)–(4) және (10)–(15) есептері өзара бір-біріне пара-парлығынан келесі тұжырым орын алады.

Теорема 2. Егер $Q(x)$ матрицасы барлық $x \in [0,\Omega]$ үшін қайтарымды болса және жоғарыда келтірілген теореманың теңсіздіктері орындалса, онда (1)–(4) параметрі бар есебінің жалғыз $z^*(t,x)$ шешімі болады.

Теорема 1 және теорема 2 дәлелдеулері [13] пен [23] жұмыстарындағы теоремаларға ұқсас дәлелденеді.

Қорытынды

Ұсынылып отырған жұмыста тіктөртбұрышты облыста импульсті дискретті жады бар жоғары ретті гиперболалық теңдеу үшін шеттік есеп зерттелген. Қарастырылатын есеп жаңа белгісіз функциялар енгізу арқылы импульсті дискретті жады бар белгісіз функциялардан тәуелді бірінші ретті дифференциалдық теңдеу үшін шеттік есептер әулетіне және интегралдық қатынастарға келтірілген. Шыққан есепке Д.С. Жұмабаевтың параметрлеу әдісі қолданылып, пара-пар функционалдық параметрлері мен белгісіз функциялары бар көп нүктелі интегралдық шеттік есептер әулеті зерттелген. Шыққан пара-пар мәселенің шешімін табу алгоритмі құрылған. Функционалдық параметрлері мен белгісіз функциялары бар көп нүктелі интегралдық шеттік есептер әулетінің бірмәнді шешімділігінің жеткілікті шарттары тұжырымдалған. Импульсті дискретті жады бар жоғары ретті гиперболалық теңдеу үшін шеттік есептің бастапқы деректері тұрғысында оның бірмәнді шешімділігінің жеткілікті шарттары анықталған.

Қаржыландыру туралы ақпарат. Бұл зерттеулерге Қазақстан Республикасы Ғылым және Жоғары Білім министрлігінің Ғылым комитеті қолдау көрсетті (AP19675193 гранты мен BR20281002 іргелі зерттеулер гранты).

ӘДЕБИЕТТЕР

1 Dzhumabayev D.S. Criteria for the unique solvability of a linear boundary-value problem for an ordinary differential equation. USSR Computational Mathematics and Mathematical Physics, 1989, vol. 29, no. 1, pp. 34–46.

2 Asanova A.T., Dzhumabaev D.S. Well-posedness of nonlocal boundary value problems with integral condition for the system of hyperbolic equations. Journal of Mathematical Analysis and Applications, 2013, vol. 402, no. 1, pp. 167–178. https://doi.org/10.1016/j.jmaa.2013.01.012.

3 Assanova A.T., Sabalakhova A.P. On the unique solvability of nonlocal problems with integral conditions for a hybrid system of partial differential equations. Eurasian Mathematical Journal, 2018, vol. 9, no. 3, pp. 14–24. https://doi.org/10.32523/2077-9879-2018-9-3-14-24.

4 Assanova A.T. An integral-boundary value problem for a partial differential equation of second order. Turkish Journal of Mathematics, 2019, vol. 43, no. 4, pp. 1967–1978. https://doi.org/10.3906/mat-1903-111.

5 Bakirova E.A. Dzhumabaev D.S. and Mynbayeva S.T. A method of solving a nonlinear boundary value problem with a parameter for a loaded differential equation. Mathematical Methods in the Applied Sciences, 2020, vol. 43, no. 7, pp. 1788–1802. https://doi.org/10.1002/mma.6003.

6 Assanova A.T. On the solvability of a nonlocal problem for the system of Sobolev-type differential equations with integral condition. Georgian Mathematical Journal, 2021, vol. 28, no. 1, pp. 49–57. https://doi.org/10.1515/gmj-2019-2011.

7 Bakirova E.A., Assanova A.T. and Kadirbayeva Zh.M. A problem with parameter for the integro-differential equations. Mathematical Modelling and Analysis, 2021, vol. 26, no. 1, pp. 34–54. https://doi.org/10.3846/mma. 2021.11977.

8 Minglibayeva B.B., Assanova A.T. An existence of an isolated solution to nonlinear two-point boundary value problem with parameter. Lobachevskii Journal of Mathematics, 2021, vol. 42, no. 3, pp. 587–597. https://doi.org/10.1134/S199508022103015X.

9 Assanova A.T., Sabalakhova A.P., and Toleukhanova Z.M. On the unique solvability of a family of boundary value problems for integro-differential equations of mixed type. Lobachevskii Journal of Mathematics, 2021, vol. 42, no. 6, pp. 1228–1238. https://doi.org/10.1134/S1995080221060044.

10 Assanova A.T. and Imanchiyev A.E. The problem with non-separated multipoint-integral conditions for high-order differential equations and a new general solution. Quaestiones Mathematicae, 2022, vol. 45, no. 10, pp. 1641–1653. https://doi.org/ 10.2989/16073606.2021.1967503.

11 Assanova A.T. and Uteshova R. Solution of a nonlocal problem for hyperbolic equations with piecewise constant argument of generalized type. Chaos, Solitons & Fractals, 2022, vol. 165, no. 12, art. no. 112816. https://doi.org/10.1016/ j.chaos.2022.112816.

12 Assanova A.T. A generalized integral problem for a system of hyperbolic equations and its applications. Hacettepe Journal of Mathematics and Statistics, 2023, vol. 52, no. 6, pp. 1513–1532. https://doi.org/10.15672/hujms.1094454.

13 Assanova A.T. and Imanchiyev A.E. A nonlocal problem with multipoint conditions for partial differential equations of higher order, Filomat, 2024, vol. 38, no. 1, pp. 295–304. https://doi.org/10.2298/FIL2401295A.

14 Assanova A.T. and Tleulessova A.B. Nonlocal problem for a system of partial differential equations of higher order with pulsed actions. Ukranian Mathematical Journal, 2020, vol. 71, no. 12, pp. 1821–1842. https://doi.org/10.1007/s11253-020-01750-9.

15 Assanova A.T., Abildayeva A.D., Tleulessova A.B. Nonlocal problems for the fourth order impulsive partial differential equations. Springer Proceedings in Mathematics and Statistics, 2020, vol. 333, pp. 81–94. https://doi.org/10.1007/978-3-030-56323-3_7.

16 Akhmet M.U. Principles of discontinuous dynamical systems, Springer, New-York, 2010, 176 p.

17 Akhmet M.U. Nonlinear hybrid continuous/discrete-time models, Atlantis Press, Paris, 2011, 216 p.

18 Akhmet M.U. and Yilmaz E. Neural Networks with Discontinuous/Impact Activations, Springer, New-York, 2013, 168 p.

19 Akhmet M.U. Almost Periodicity, Chaos, and Asymptotic Equivalence, Springer, Switzerland, 2020, 368 p.

20 Nieto J.J. and Rodriguez-Lopez R. Green's function for second order periodic BVPs with piecewise constant argument. Journal of Mathematical Analysis and Applications, 2005, vol. 304, no. 1, pp. 33–57. https://doi.org/10.1016/j.jmaa.2004.09.023.

21 Dominguez-Perez M.A., Rodriguez-Lopez R. Multipoint BVPs of Neumann type for functional differential equations. Nonlinear Analysis: Real World Applications, 2012, vol. 13, no. 4, pp. 1662–1675. https://doi.org/10.1016/j.nonrwa.2011.11. 023.

22 Abildayeva A., Assanova A., Imanchiyev A. A multi-point problem for a system of differential equations with piecewise-constant argument of generalized type as a neural network model. Eurasian Mathematical Journal, 2022, vol. 13, no. 2, pp. 8–17. https://doi.org/10.32523/2077-9879-2022-13-2-08-17.

23 Imanchiyev A.E., Assanova A.T., Molybaikyzy A. Properties of a nonlocal problem for hyperbolic equations with impulse discrete memory. Lobachevskii Journal of Mathematics, 2023, vol. 44, no. 10, pp. 4299–4309. https://doi.org/10.1134/S1995080223100177.

[1*]Assanova A.T.,
Dr. Phys.-Math. Sc., Principal Researcher, ORCID ID: 0000-0001-8697-8920,
e-mail: assanova@math.kz

[1]Bimenova R.A.,
ORCID ID: 0009-0002-9456-3025, e-mail: b.rabiga@mail.ru.

[1,2]Minglibayeva B.B.,
Cand. Phys.-Math.Sc., Senior Lecturer, Senior Researcher, ORCID ID: 0000-0002-7195-4480,
e-mail: bayan_math@mail.ru.

[3] Sabalakhova A.P.
Senior Lecturer, ORCID ID: 0000-0003-1921-0174,
e-mail: sabalahova@mail.ru

[1]Institute of Mathematics and Mathematical Modeling, 050010, Almaty, Kazakhstan
[2]Kazakh National Women's Teacher Training University, 050000, Almaty, Kazakhstan
[3]Mukhtar Auezov South Kazakhstan University, 160012, Shymkent, Kazakhstan

ON A BOUNDARY VALUE PROBLEM FOR HIGH-ORDER HYPERBOLIC EQUATION WITH IMPULSE DISCRETE MEMORY

Abstract

The investigation focuses on a boundary value problem for a high-order hyperbolic equation with impulse discrete memory in a rectangular domain. By introducing new functions, the problem is transformed into a set of boundary value problems for a first-order differential equation with impulse discrete memory, which depends on unknown functions and integral relations. D.S. Dzhumabaev's parametrization method is applied to this equivalent problem. The domain is divided according to the time variable, and functional parameters representing discrete memory values are introduced within the interior domains. As a result, the family of boundary value problems for the first-order differential equation with impulse discrete memory and unknown functions is converted into an

equivalent family of integral-multipoint boundary value problems involving functional parameters and unknown functions. These equivalent problems include initial value problems for first-order differential equations related to the new functions. The solutions to the initial value problems are expressed using Volterra integral equations. By substituting these solutions into the boundary and impulse conditions, a system of linear functional equations concerning the functional parameters is derived. An algorithm is developed to solve the equivalent problem, and sufficient conditions for the unique solvability of the family of integral-multipoint boundary value problems with functional parameters and unknown functions are provided. Additionally, sufficient conditions for the unique solvability of the original boundary value problem for the high-order hyperbolic equation with impulse discrete memory are established based on the initial data.

Key words. Impulse discrete memory, high-order hyperbolic equation, family of boundary value problems, functional-differential equations.

[1*]Асанова А.Т.,
д.ф.-м.н., г.н.с., ORCID ID: 0000-0001-8697-8920,
e-mail: assanova@math.kz
[1]Бименова Р.А.,
ORCID ID: 0009-0002-9456-3025, e-mail: b.rabiga@mail.ru
[1,2]Минглибаева Б.Б.,
к.ф.-м.н., ст. преподаватель, с.н.с., ORCID ID: 0000-0002-7195-4480,
e-mail: bayan_math@mail.ru
[3]Сабалахова А.П.,
ст. преподаватель, ORCID ID: 0000-0003-1921-0174, e-mail: sabalahova@mail.ru

[1]Институт математики и математического моделирования, 050010, г. Алматы, Казахстан
[2]Казахский национальный женский педагогический университет, 050000, г. Алматы, Казахстан
[3]Южно-Казахстанский университет имени М. Ауезова, 160012, г. Шымкент, Казахстан

О КРАЕВОЙ ЗАДАЧЕ ДЛЯ ГИПЕРБОЛИЧЕСКОГО УРАВНЕНИЯ ВЫСОКОГО ПОРЯДКА С ИМПУЛЬСНОЙ ДИСКРЕТНОЙ ПАМЯТЬЮ

Аннотация

Исследуется краевая задача для гиперболического уравнения высокого порядка с импульсной дискретной памятью в прямоугольной области. С помощью введения новых функций рассматриваемая задача сводится к семейству краевых задач для дифференциального уравнения первого порядка с импульсной дискретной памятью, зависящей от неизвестных функций, и интегральным равенствам. К этой эквивалентной задаче применяется метод параметризации Д.С. Джумабаева. Разбиением области по временной переменной, введением функциональных параметров как значений дискретной памяти во внутренних областях исследуемое семейство краевых задач для дифференциального уравнения первого порядка с импульсной дискретной памятью, зависящее от неизвестных функций, и интегральные равенства переходят к эквивалентному семейству интегральных-многоточечных краевых задач с функциональными параметрами и неизвестными функциями. Полученные эквивалентные задачи содержат начальные задачи для дифференциальных уравнений первого порядка относительно новой функции. Решение начальных задач выражается через интегральные уравнения Вольтерра. Подставляя эти решения в краевые условия и импульсные условия, строится система линейных функциональных уравнений относительно функциональных параметров. Построен алгоритм нахождения решения эквивалентной задачи. Сформулированы достаточные условия однозначной разрешимости семейства интегральных-многоточечных краевых задач с функциональными параметрами и неизвестными функциями. В терминах исходных данных краевой задачи для гиперболического уравнения высокого порядка с импульсной дискретной памятью установлены достаточные условия ее однозначной разрешимости.

Ключевые слова: импульсная дискретная память, гиперболическое уравнение высокого порядка, семейство краевых задач, функционально-дифференциальные уравнения.

Мақаланың редакцияға түскен күні: 27.08.2024

УДК 510.67
МРНТИ 27.03.66

https://doi.org/10.55452/1998-6688-2024-21-3-201-209

[1]*Вербовский В.,
д.физ.-мат.н., доцент, ORCID ID: 0000-0001-5177-8523,
*e-mail: verbovskiy@math.kz
[1]Ершигешова А.,
магистр, старший преподаватель, ORCID ID: 0000-0001-6732-1077,
e-mail: aisha.yershigeshova@gmail.com

[1]Институт математики и математического моделирования КН МНВО РК,
Алматы, 050010, ул. Шевченко, 28

УПОРЯДОЧЕННАЯ СТАБИЛЬНОСТЬ И ОБОГАЩЕНИЯ ЧИСТОГО ЛИНЕЙНОГО ПОРЯДКА ОДНОМЕСТНОЙ ФУНКЦИЕЙ

Аннотация

Линейно упорядоченная структура называется упорядоченно стабильной, если каждое ее дедекиндово сечение имеет «малое» число расширений до полных 1-типов. Данное понятие, которое ввели Б.С. Байжанов и В.В. Вербовский, обобщает такие широко известные в среде специалистов по теории моделей понятия, как слабая о-минимальность, (слабая) квази-о-минимальность и дп-минимальность упорядоченных структур. Оно основано на соединении понятия стабильности и о-минимальности. Как мы знаем, элементарная теория любого чистого линейного порядка упорядоченно суперстабильна. Действительно, это следует из того факта, которые доказал еще Рубин в конце 70-х годов XX века, что любой тип от одной переменной определяется своим сечением и формульными подмножествами, выделяемыми одноместными предикатами или формулами от одной свободной переменной. В данной работе мы исследуем вопрос, что будет, если чистый линейный порядок обогатить одноместной функцией. Построены два примера, когда упорядоченная стабильность нарушается. Кроме того, найдены достаточные условия сохранения упорядоченной стабильности при таком обогащении языка. Исследовательская работа по данной теме еще не окончена. В идеале было бы хорошо найти критерий сохранения упорядоченной стабильности при обогащении структуры с чистым линейным порядком новой функцией от одной переменной.

Ключевые слова: линейно упорядоченное множество, свойство независимости, унар, упорядоченная стабильность, о-минимальность.

Введение

С момента появления весьма удачного понятия о-минимальности [1], которое принесло огромное число плодов в теории моделей, изучение линейно упорядоченных структур стало развиваться очень и очень активно. В силу всего вышесказанного не могли не быть придуманными его обобщения, причем самого разного вида. Мы в данной работе будем касаться только одного из таких обобщений, а именно понятия упорядоченной стабильности, которое было придумано Б.С. Байжановым и В.В. Вербовским и впервые опубликовано в их совместной статье [2]. Дальнейшее развитие теории упорядоченной стабильности получило в работах [2–9, 11], но там речь шла либо об общих вопросах [6–8], либо были исследованы упорядоченные группы [3–5, 9]. Эта статья направлена на изучение вопроса, что будет, если мы обогатим чистый линейный порядок одноместной функцией. Данная работа является продолжением работы [11].

Основная часть

Упорядоченные структуры являются классическим объектом в математике. Их исследуют с самых разных сторон. В нашем исследовании мы смотрим на них с точки зрения упорядоченной стабильности – относительно нового понятия в теории моделей.

Материалы и методы

В нашей работе мы использовали методы теории моделей, а именно те методы, которые касаются изучения свойства независимости и построения формульных подмножеств данной алгебраической структуры. Кроме того, был использован метод элиминации кванторов для доказательства упорядоченной стабильности элементарных теорий построенных структур.

Результаты исследования и их обсуждение

Следующие примеры демонстрируют, что вопрос сохранения упорядоченной стабильности чистого линейного порядка при его обогащении функцией от одной переменной имеет место, поскольку существуют примеры, которые приведены ниже, когда такого вида обогащения выводят нас за рамки упорядоченной стабильности.

Пример 1. $(\mathbb{R}\times\mathbb{R},<,g^1)$, где символ $<$ мы интерпретируем как лексикографический порядок, а функциональный символ g мы интерпретируем так, как написано: $g\big((q_1,q_2)\big)=(q_2,q_1)$. В этом случае появляется возможность определить при помощи формулы $a\prec b\Leftrightarrow g(a)<g(b)$ такой порядок $\prec$, который принято называть обратным лексикографическим. В статье [1] был получен следующий результат: «Элементарная теория структуры $(\mathbb{R}\times\mathbb{R},<,\prec)$ является зависимой (не обладает свойством независимости), но не является упорядоченно стабильной». Следует обратить внимание, что определенная таким образом функция g ни в коем случае не есть локально монотонная функция, в том смысле, что область определения функции g является открытым множеством и для любого элемента (за исключением конечного их числа) из области определения существует такая открытая выпуклая окрестность этого элемента, что сужение функции g на это открытое выпуклое множество есть монотонная функция.

Пример 2. $\mathcal{M}=(\mathbb{Z}\times\mathbb{Z}+\mathbb{R},<,h^1)$, где символ $<$ мы интерпретируем как линейный порядок, причем на множестве $\mathbb{Z}\times\mathbb{Z}$ он задается как лексикографический порядок, на множестве $\mathbb{R}$ этот порядок мы определяем естественным образом, более того, мы полагаем, что какой бы мы ни взяли элемент из $\mathbb{R}$, он будет больше каждого элемента из $\mathbb{Z}\times\mathbb{Z}$, а функция h от одной переменной будет определена в следующих строках. Мы определим вспомогательные функции g_1,g_2 из декартового квадрата $\mathbb{Z}\times\mathbb{Z}$ в множество вещественных чисел $\mathbb{R}$ в виде обычной проекции: $g_i\big((z_1,z_2)\big)=z_i$. Нам осталось привести формулу для вычисления функции h. Если $a=(z_1,z_2)$, то очевидно, что $g_1(a)=z_1$ и $g_2(a)=z_2$. Итак,

$$h(a)=g_2(a)+\frac{1}{g_1(a)+2},\text{если } g_1(a)>0$$
$$h(a)=g_2(a),\text{если } g_1(a)=0$$
$$h(a)=g_2(a)+\frac{1}{g_1(a)-2},\text{если } g_1(a)<0$$
$$h(r)=(0,0)\in\mathbb{Z}\times\mathbb{Z},\text{если } r\in\mathbb{R}$$

Напишем формулу, которая выделяет множество $\mathbb{R}$:

$$R(x)=\forall y,z\big(y<x<z\rightarrow\exists u,v(y<u<x<v<z)\big)$$

Очевидно, что формула $\neg R$ в таком случае имеет своим множеством реализаций декартов квадрат $\mathbb{Z}\times\mathbb{Z}$.

Перейдем к формуле $\varphi(z,q) = h(z) > q$. Определим сечение $s = (C, D)$ следующим образом: положим, что $C = \mathbb{Z} \times \mathbb{Z}$ и, кроме того, $D = \mathbb{R}$. В следующих строках мы докажем, что вышеопределенная формула $\varphi(z,q)$ удовлетворяет свойству строгого порядка внутри только что построенного нами сечения s. Для этого проделаем следующее рассуждение. Возьмем из множества $R(\mathcal{M})$ такой элемент $q = n$, который является целым числом. В этом случае множество $\varphi(\mathcal{M}, q)$ можно представить в виде объединения таких выпуклых множеств, которые приведены далее. Пусть $(z_1, z_2) \in \{z_1\} \times \mathbb{Z}$, причем первая координата z_1 положительна. Имеет место формула

$$h\big((z_1, z_2)\big) = g_2\big((z_1, z_2)\big) + \frac{1}{g_1\big((z_1, z_2)\big) + 2} = z_2 + \frac{1}{z_1 + 3}.$$

Из определения функции h следует, что $h\big((z_1, z_2)\big) > n$, если и только если вторая координата $z_2 > n$. Отсюда получаем, что

$$\varphi(\mathcal{M}, n) = \bigcup_{z_1 \in \mathbb{Z}} [(z_1, n), +\infty),$$

здесь $[(z_1, n), +\infty)$ является подмножеством множества $\{z_1\} \times \mathbb{Z}$.

Исходя из определения свойства строгого порядка внутри сечения s, рассматриваемая нами формула $\varphi(z,q)$ обладает этим свойством, когда можно найти такую последовательность элементов q_i, здесь i пробегает множество натуральных чисел ω, что каковы бы ни были элементы c из C и d из D, включение

$$\varphi(\mathcal{M}, q_i) \cap (c, d) \subset \varphi\big(\mathcal{M}, q_j\big) \cap (c, d)$$

верно, если и только если индекс i меньше индекса j [2]. В работе [2] было доказано: «упорядоченно стабильная теория не обладает свойством строгого порядка внутри никакого сечения».

Наконец, мы приступаем к доказательству того, что свойством строгого порядка внутри сечения s построенная нами выше формула $\varphi(z, n)$ все-таки обладает.

Пусть $q_n = n \in P(\mathcal{M})$, где индекс n пробегает множество натуральных чисел ω. Положим, что $c = (\zeta_1, \zeta_2), d = q$. Имеем, что

$$\varphi(\mathcal{M}, q_n) \cap (c, d) = \Big(\big((\zeta_1, \zeta_2), +\infty\big) \cap [(\zeta_1, n), +\infty)\Big) \cup \bigcup_{z_1 \in \mathbb{Z},\, z_1 > \zeta_1} [(z_1, n), +\infty)$$

Включение $\varphi(\mathcal{M}, q_n) \cap (c, d) \subset \varphi(\mathcal{M}, q_{n+1}) \cap (c, d)$ настолько очевидно для каждого n, что не требует пояснений. В силу приведенного нами немного выше факта получаем, что $Th(\mathbb{Z} \times \mathbb{Z} + \mathbb{R}, <, h^1)$ не может быть упорядоченно стабильной, тем не менее функция h является локально монотонной, что достаточно легко проверить.

Теперь мы вводим в рассмотрение сигнатуру $\Sigma = \{=, <, f^1, P_i^1\}_{i \in I}$. Символ $<$ мы будем интерпретировать только в качестве линейного порядка, символ f будет интерпретировать как некоторую монотонную функцию одной переменной, которая является еще и непрерывной. Что же касается символов P_i, то это одноместные предикаты.

Напишем в виде аксиом то, что мы только что сказали, иначе говоря, зададим теорию T:

1) $<$ – линейный порядок;

2) $\forall x_1 \forall x_2 \big(x_1 < x_2 \to f(x_1) < f(x_2)\big)$ (f возрастающая);

3) f непрерывна, то есть,

$$\forall x \forall y_1 \forall y_2 \Big(y_1 < f(x) < y_2 \to \exists x_1 \exists x_2 \big(x_1 < x < x_2 \wedge \forall t (x_1 < t < x_2 \to y_1 < f(t) < y_2)\big)\Big);$$

4) $\forall x \big(x < f(x)\big)$.

Пусть $R(y) \coloneqq \exists x \big(y = f(x)\big)$ и $D(y) = \exists y \big(y = f(x)\big)$.

Если A – формульное подмножество, то положим, что $A^n = f^n(A)$:

$$y \in A^n \Leftrightarrow \exists x \in A(f^n(x) = y), \text{если } n > 0$$

$$y \in A^0 \Leftrightarrow y \in A$$
$$y \in A^{-n} \Leftrightarrow \exists x \in A(f^n(y) = x), \text{если } n > 0$$

Пусть $\Sigma^+ = \{=, <, P_i^n, R^n, D^n\}_{i \in I, n \in \mathbb{Z}}$

Заметим, что следующий факт легко следует из результатов Рубина [10].

Факт 1. [2] Пусть $\mathcal{M} = (M, \Sigma^+)$ – линейно упорядоченная структура с одноместными предикатами. Тогда $Th(\mathcal{M})$ является упорядоченно суперстабильной теорией.

Добавим к сигнатуре Σ^+ один символ одноместной функции, в итоге мы получим $\mathcal{M}_1 = (M, \Sigma^+ \cup \{f^1\})$. Так как факт 1 имеет место для произвольной сигнатуры Σ^+, которая содержит только символ $<$ и символы P_i^1, где индекс i пробегает некоторое множество индексов I, то, не умаляя общности, мы имеем право положить, что для любого i существуют j и k, такие, что

$$f\left(P_i(\mathcal{M})\right) = P_j(\mathcal{M}) \text{ и } f^{-1}\left(P_i(\mathcal{M})\right) = P_k(\mathcal{M}).$$

Также положим, что $\mathrm{dom}\, f$, $\mathrm{range}\, f \in \Sigma^+$.

Пусть $T = Th(\mathcal{M})$ и пусть $\Sigma_{qe}^+ \supset \Sigma^+$ – такая сигнатура, что теория $T_{qe}^+ = Th\left(M, \Sigma_{qe}^+\right)$ допускает сокращение кванторов. Для дальнейших рассуждений мы введем еще одно допущение. Мы ограничимся только такими алгебраическими структурами $\mathcal{M} = (M, \Sigma^+)$, для которых построенная нами только что сигнатура Σ_{qe}^+ содержит только символ $<$ и только одноместные предикаты. Без ограничения общности мы можем допустить, что если одноместные предикаты P и R лежат в Σ_{qe}^+, то $\neg P$, $\neg Q$, $P \wedge Q \in \Sigma_{qe}^+$.

Пусть $T_{qe}^f = Th\left(M, \Sigma_{qe}^+ \cup \{f\}\right)$. Обозначим, $\Sigma_{qe}^f = \Sigma_{qe}^+ \cup \{f\}$.

Теорема 1. Теория T_{qe}^f допускает элиминацию кванторов.

Доказательство. Это является стандартом, что для начала необходимо разобраться в устройстве термов сигнатуры Σ_{qe}^f. Как они могут выглядеть? Терм может быть переменной, констант у нас нет, а может быть и $f^n(x)$, здесь $n \in \mathbb{Z}^+$. Для упрощения записи мы будем писать $f^n(x)$ и в том случае, когда $n \in \mathbb{Z}$, но это только временно. Когда мы подойдем к концу, станет понятно, что делать с отрицательными индексами n, чтобы их не осталось. Мы используем классический критерий Тарского, то есть для наших задач достаточно доказать, что квантор существования элиминируется в формулах вида элементарной конъюнкции с одним экзистенциальным квантором

$$\exists x \left(\bigwedge_{i=1}^{k} \varphi_i(x, \overline{y_i}) \right),$$

здесь $\varphi_i(x, \overline{y_i})$ есть не что иное, как атомарная формула или ее отрицание, а значит, она описывается одним из нижеприведенных видов:

1) $f^n(x) = f^m(y)$;
2) $f^n(x) \neq f^m(y)$;
3) $f^n(x) < f^m(y)$;
4) $f^n(x) \not< f^m(y)$;
5) $f^n(x) > f^m(y)$;
6) $f^n(x) \not> f^m(y)$;
7) $P\left(f^n(x)\right)$, где P – одноместный предикат из Σ_{qe}^+;

Ввиду введенных нами обозначений и допущений имеет место эквивалентность $P\left(f^n(x)\right) \Leftrightarrow P^{-n}(x)$, из этого следует, что среди формул вида (7) достаточно перебирать только такие формулы, которые имеют самый простой вид – $P(x)$.

Не умаляя общности, можно считать, что формулы с отрицанием (то есть вида 2, 4, 6) отсутствуют в силу нижеприведенных рассуждений.

$$f^n(x) \neq f^m(y) \Leftrightarrow \left(f^n(x) < f^m(y)\right) \vee \left(f^n(x) > f^m(y)\right).$$

Обозначим конъюнкцию вида $\exists x\left(\bigwedge_{i=1}^{k} \varphi_i(x, \overline{y_i})\right)$ как θ. Тогда

$$\exists x(f^n(x) \neq f^m(y) \wedge \theta) \Leftrightarrow$$
$$\Leftrightarrow \exists x\left(\left(\left(f^n(x) < f^m(y)\right) \vee \left(f^n(x) > f^m(y)\right)\right) \wedge \theta\right) \Leftrightarrow$$
$$\Leftrightarrow \exists x\left(\left(\left(f^n(x) < f^m(y)\right) \wedge \theta\right) \vee \left(\left(f^n(x) > f^m(y)\right) \wedge \theta\right)\right) \Leftrightarrow$$
$$\Leftrightarrow \exists x\left(\left(f^n(x) < f^m(y)\right) \wedge \theta\right) \vee \exists x\left(\left(f^n(x) > f^m(y)\right) \wedge \theta\right)$$

Поскольку квантор существования проносится через дизъюнкцию, мы имеем полное право рассматривать эти дизъюнкты не вместе, а по отдельности.

Так как $f^n(x) \not< f^m(y) \Leftrightarrow \left(f^n(x) = f^m(y)\right) \vee \left(f^n(x) > f^m(y)\right)$, рассуждения аналогичны. Подобным образом можно избавиться и от формул вида 6.

Нам потребуется еще одно наблюдение. Ввиду того факта, что функция f предполагается всегда быть возрастающей, неравенство $f^n(x) \gtreqless f^m(y)$ эквивалентно неравенству $f^{n+s}(x) \gtreqless f^{m+s}(y)$, какое бы число s мы ни взяли, здесь $\gtreqless \in \{=, <, >\}$ (иначе говоря, мы в одном выражении записали сразу три эквивалентности). Из этого следует, что при рассмотрении формул вида 1, 3 и 5 можно ограничиться только следующими видами:

$$x = f^m(y);\ x < f^m(y);\ x > f^m(y).$$

Если есть формула вида 1, то есть $x = f^m(y)$, то если $m \geq 0$, получаем:

$$\exists x\left(x = f^m(y) \wedge \bigwedge_{i=1}^{k} \varphi_i(x, \overline{y_i})\right) \Leftrightarrow D(y) \wedge \bigwedge_{i=1}^{k} \varphi_i(f^m(y), \overline{y_i})$$

Рассмотрим случай, когда $m < 0$. Пусть $m = -n$. Тогда

$$\exists x\left(x = f^{-n}(y) \wedge \bigwedge_{i=1}^{k} \varphi_i(x, \overline{y_i})\right) \Leftrightarrow \exists x\left(f^n(x) = y \wedge \bigwedge_{i=1}^{k} \varphi_i(x, \overline{y_i})\right)$$
$$\Leftrightarrow D^n(y) \wedge \bigwedge_{i=1}^{k} \varphi_i(f^{-n}(y), \overline{y_i})$$

Формула φ_i – атомарная, то есть лежит в Σ_{qe}^{f}.

А) $\varphi_i = f^{-n}(y) < u$. Тогда меняем $f^{-n}(y) < u$ на $y < f^n(u)$.

Б) $\varphi_i = f^{-n}(y) > u$. Тогда меняем $f^{-n}(y) > u$ на $y > f^n(u)$.

В) $\varphi_i = U\left(f^{-n}(y)\right)$. Тогда меняем $U\left(f^{-n}(y)\right)$ на $U^n(y)$.

Это рассуждение позволяет нам сделать допущение об отсутствии формул вида 1.

Не умаляя общности, позволительно считать, что количество формул третьего вида либо

0, либо 1. Если их хотя бы две, то отметим, что конъюнкция $(x < u \wedge x < v)$ эквивалентна дизъюнкции $(x < u \wedge u < v) \vee (x < v \wedge u \neq v)$ двух конъюнкций. А когда у нас есть дизъюнкция, то, как мы знаем, над каждым дизъюнктом мы имеем право проводить рассуждения отдельно. Такое же допущение мы можем сделать и о количестве формул пятого вида.

Предположим, что среди рассматриваемых формул отсутствуют формулы восьмого вида. В этом случае достаточно ограничиться перебором формул трех следующих видов:

$$\exists x\left(x < f^m(y) \wedge \bigwedge_i U_i(x)\right), \exists x\left(x > f^m(y) \wedge \bigwedge_i U_i(x)\right),$$

$$\exists x\left(f^j(z) < x < f^m(y) \wedge \bigwedge_i U_i(x)\right)$$

где U_i – одноместные предикаты.

Но тогда из определения следует, что

$$\exists x\big(x < f^m(y)\big) \Leftrightarrow \exists x(f^{-m}(x) < y) \Leftrightarrow \exists z \exists x(f^{-m}(x) = z \wedge z < y) \Leftrightarrow$$
$$\Leftrightarrow \exists z(\exists x(f^{-m}(x) = z) \wedge z < y) \Leftrightarrow \exists z(R^{-m}(z) \wedge z < y)$$

Кроме того,

$$\exists x\big(x > f^m(y)\big) \Leftrightarrow \exists x(f^{-m}(x) > y) \Leftrightarrow \exists z(R^{-m}(z) \wedge z > y)$$

Заметим, что написанные справа формулы на самом деле есть формулы сигнатуры Σ_{qe}^+, а по сделанному нами допущению T_{qe}^+ допускает элиминацию кванторов, что влечет эквивалентность этих формул некоторым бескванторным формулам.

Перейдем к формулам последнего (третьего) вида:

$$\exists x\left(f^j(z) < x < f^m(y)\right) \Leftrightarrow \exists x(z < f^{-j}(x) \wedge f^{-m}(x) < y) \Leftrightarrow$$
$$\Leftrightarrow \exists x \exists u \exists v(u = f^{-j}(x) \wedge z < u \wedge v = f^{-m}(x) \wedge v < u) \Leftrightarrow$$
$$\Leftrightarrow \exists u \exists v\left(\exists x\left(u = f^{-j}(x) \wedge v = f^{-m}(x)\right) \wedge z < u \wedge v < u\right)$$

Пусть $j \geq 0, m \geq 0$. Тогда

$$\exists x\left(f^j(z) < x < f^m(y)\right) \Leftrightarrow \exists x \exists u \exists v(f^j(z) = u \wedge f^m(y) = v \wedge u < x < v) \Leftrightarrow$$
$$\Leftrightarrow \exists u \exists v\left(f^j(z) = u \wedge f^m(y) = v \wedge \exists x(u < x < v)\right)$$

Заметим, что $\exists x(u < x < v)$ – формула сигнатуры Σ_{qe}^+, следовательно, эквивалентна бескванторной формуле, скажем, $\Xi(u, v)$. Тогда

$$\exists u \exists v\left(f^j(z) = u \wedge f^m(y) = v \wedge \exists x(u < x < v)\right) \Leftrightarrow \exists u \exists v\left(f^j(z) = u \wedge f^m(y) = v \wedge \Xi(u, v)\right)$$
$$\Leftrightarrow \Xi(f^j(z), f^m(y) = v)$$

Итого, если в исходной формуле $\exists x\big(\wedge_{i=1}^k \varphi_i(x, \overline{y_i})\big)$ среди конъюнктов φ_i отсутствуют формулы восьмого вида, то данная формула эквивалентна некоторой формуле, не содержащей кванторов. Теорема доказана.

Теорема 2. Теория T_{qe}^f упорядоченно суперстабильна.

Доказательство. Пусть $\mathcal{M}$ – это модель теории T_{qe}^f, а (C, D) – некоторое ее сечение. Выше, а именно в доказательстве теоремы 1, мы сделали наблюдение, что в любой формуле терм $f^n(x)$ заменяем на терм x, на всего лишь переменную. Если не вдаваться в детали, что вместо формулы $\psi(f^n(x), a)$ мы можем взять формулу $\psi_1\left(x, f^{-n}(a)\right)$.

Положим, что $b = f^{-n}(a)$. Это дает нам формулу $\psi_1(x, b)$. Из этого мы приходим к выводу, что любой 1-тип мы можем полностью определить только соответствующим сечением и формулами, заданными при помощи сигнатуры Σ^+_{qe}, но, как мы знаем, она есть не что иное, как несущественное расширение сигнатуры Σ^+. Факт 1 говорит, что любая теория сигнатуры Σ^+, где символ $<$ проинтерпретирован как линейный порядок, является упорядоченно суперстабильной. Таким образом, (C, D) не может иметь больше, чем $2^{|\Sigma^+|}$ расширений. Следовательно, упорядоченная суперстабильность теории T^f_{qe} доказана.

Заключение

По данной теме есть несколько открытых вопросов. Основной из них пока представляется очень сложным – найти критерий того, что обогащение чистого линейного порядка будет упорядоченно стабильным. Можно отметить еще один вопрос.

Вопрос. Предположим, что элементарная теория обогащения чистого линейного порядка одноместной функцией является упорядоченно стабильной. Можем ли мы сказать, что эта теория будет более того – упорядоченно суперстабильной?

Информация о финансировании

Работа выполнена при финансовой поддержке Комитета науки МНВО РК, грант № AP22685272.

ЛИТЕРАТУРА

1 Pillay A., Steinhorn C. Definable sets in ordered structures.1 // Trans. Amer. Math. Soc. – 1986. – Vol. 295. – P. 565–592.

2 Байжанов Б.С., Вербовский В.В. Упорядоченно стабильные теории // Алгебра и логика. – 2011. – Т. 50. – № 3. – С. 303–325.

3 Verbovskiy V.V. O-Stable Ordered Groups // Siberian Advances in Mathematics. – 2012. – Т. 22. – No. 1. – С. 50–74.

4 Verbovskiy V.V. On ordered groups of Morley o-rank 1. // Siberian Electronic Mathematical Reports. – 2018. – V. 15 – P. 314–320.

5 Dauletiyarova A.B., Verbovskiy V.V. Piecewise monotonicity for unary functions in o-stable groups // Algebra and Logic. – 2021. – V. 60. – No. 1. – P. 23–38.

6 Verbovskiy V.V. On a classification of theories without the independence property // Mathematical Logic Quarterly. – 2013. – V. 59. – P. 119–124.

7 Verbovskiy V.V. On definability of types and relative stability // Mathematical Logic Quarterly. – 2019. – V. 65. – P. 332–346.

8 Вербовский В.В. Дп-минимальные и упорядоченно стабильные упорядоченные структуры // Математический журнал. – 2010. – Т. 10. – № 2 (36). – С. 35–38.

9 Verbovskiy V.V., Yershigeshova A.D. On non-essentiality of an o-stable expansion of $(\mathbb{Z}, <, +)$, Lobachevskii Journal of Mathematics. – 2023. – V. 44. – P. 5485–5492. https://doi.org/10.1134/S1995080223120387.

10 Rubin M. Theories of linear orders // Israel Journ. Math. – 1974. – No. 17. – P. 392–443.

11 Вербовский В.В., Ершигешова А.Д. Примеры линейных порядков с определяемой унарной функцией и свойством независимости // Вестник Казахстанско-Британского технического университета. – 2023. – Т. 20 (3). – С. 45–50.

REFERENCES

1 Pillay A., Steinhorn C. (1986) Definable sets in ordered structures.1, Trans. Amer. Math. Soc., vol. 295, pp. 565–592.

2 Bajzhanov B.S., Verbovskij V.V. (2011) Uporjadochenno stabil'nye teorii. Algebra i logika, vol. 50, no. 3, pp. 303–325 [in Russian].

3 Verbovskiy V.V. (2012) O-Stable Ordered Groups. Siberian Advances in Mathematics, , vol. 22, no. 1, pp. 50–74.

4 Verbovskiy V.V. (2018) On ordered groups of Morley o-rank 1. Siberian Electronic Mathematical Reports, vol. 15, pp. 314–320.

5 Dauletiyarova A.B., Verbovskiy V.V. (2021) Piecewise monotonicity for unary functions in o-stable groups. Algebra and Logic, vol. 60, no. 1, pp. 23–38.

6 Verbovskiy V.V. (2013) On a classification of theories without the independence property, Mathematical Logic Quarterly, vol. 59, pp. 119–124.

7 Verbovskiy V.V. (2019) On definability of types and relative stability. Mathematical Logic Quarterly, vol. 65, pp. 332–346.

8 Verbovskij V.V. (2010) Dp-minimal'nye i uporjadochenno stabil'nye upo-rjadochennye struktury, Matematicheskij zhurnal, vol. 10, no. 2 (36), pp. 35–38 [in Russian].

9 Verbovskiy V.V., Yershigeshova A.D. (2023) On non-essentiality of an o-stable expansion of $(\mathbb{Z}, <, +)$, Lobachevskii Journal of Mathematics, vol. 44, pp. 5485–5492. doi.org/10.1134/S1995080223120387.

10 Rubin M. (1974) Theories of linear orders, Israel Journ. Math., no. 17, pp. 392–443.

11 Verbovskij V.V., Ershigeshova A.D. (2023) Primery linejnyh porjadkov s opredeljaemoj unarnoj funkciej i svojstvom nezavisimosti, Vestnik Kazahstansko-Britanskogo tehnicheskogo universiteta, vol. 20, no. 3, pp. 45–50 [in Russian].

[1]*Verbovsky V.,
Dr.Phys.-Math.Sc., Associate Professor, ORCID ID 0000-0001-5177-8523,
*e-mail: verbovskiy@math.kz
[1]Ershigeshova A.,
Master, Senior Lecturer, ORCID ID 0000-0001-6732-1077,
e-mail: aisha.yershigeshova@gmail.com

[1]Institute of Mathematics and Mathematical Modeling of the Science Comittee
of the Ministry of Science and Higher Education of the Republic
of Kazakhstan, Almaty, 050010, Shevchenko st., 28

ORDERED STABILITY AND EXPANSIONS OF A PURE LINEAR ORDER BY A UNARY FUNCTION

Abstract

A linearly ordered structure is said to be o-stable if each of its Dedekind cut has a “small” number of extensions to complete 1-types. This concept, which was introduced by B.S. Baizhanov and V.V. Verbovsky, generalizes such widely known concepts among specialists in model theory as weak o-minimality, (weak) quasi-o-minimality and dp-minimality of ordered structures. It is based on a combination of the concepts of o-minimality and stability. As we know, the elementary theory of any pure linear order is o-superstable. Indeed, this follows from the fact, which Rubin proved in the late 70s of the 20th century, that any type of one variable is determined by its cut and definable subsets, distinguished by unary predicates or formulas with one free variable. In this paper, we explore the question of what happens if a pure linear order is expanded with a unary function. Two examples were constructed when o-stability is violated; in addition, sufficient conditions for preserving o-stability with such language expansion were found. Research work on this topic is not yet finished, ideally, it would be good to find a criterion for preserving ordered stability when enriching a structure with pure linear order with a new function of one variable.

Key words: linearly ordered set, independence property, unar, o-stability, o-minimality.

[1]*Вербовский В.,
физ.-мат.ғ.к., доцент, ORCID ID: 0000-0001-5177-8523,
*e-mail: verbovskiy@math.kz
[1]Ершигешова А.,
магистр, аға оқытушы, ORCID ID: 0000-0001-6732-1077,
e-mail: aisha.yershigeshova@gmail.com

[1]ҚР ҒЖЖБМ ҒК Математика және математикалық модельдеу институты,
Алматы қ., 050010, Шевченко көшесі, 28

РЕТТЕЛГЕН ТҰРАҚТЫЛЫҚ ЖӘНЕ БІР ОРЫНДЫ ФУНКЦИЯМЕН ТАЗА СЫЗЫҚТЫҚ РЕТТІ БАЙЫТУЛАР

Аңдатпа

Сызықтық реттелген құрылым, егер оның әрбір Дедекинд қимасында толық 1-типке дейін кеңейтулердің аз саны болса, реттелген тұрақты деп аталады. Бұл ұғымды Б.С. Байжанов пен В.В. Вербовский енгізген және ол модельдер теориясы саласында әлсіз o-минималдылық, әлсіз квази-o-минималдылық және реттелген құрылымдардың dp-минималдылығы сияқты кеңінен танымал ұғымдарды жалпылайды. Бұл тұжырымдама тұрақтылық пен o-минималдылық ұғымдарының бірігуіне негізделген. Белгілі болғандай, кез келген таза сызықтық тәртіптің элементар теориясы реттелген супертұрақты болады. Шынында да, бұл факт 20 ғасырдың 70-жылдарының соңында Рубин дәлелдеген тұжырымнан шығады, яғни бір айнымалыдан кез келген тип өз қимасы мен бір орындық предикаттар немесе бір бос айнымалыдан тұратын формулалар арқылы ерекшеленетін формулалық ішкі жиындармен анықталады. Бұл жұмыста біз таза сызықтық тәртіпті бір орындық функциямен байытқанда не болатынын зерттейміз. Реттелген тұрақтылықтың бұзылуына әкелетін екі мысал келтірілді, сондай-ақ тілді осындай байыту барысында реттелген тұрақтылықты сақтау үшін жеткілікті шарттар табылды. Бұл тақырып бойынша зерттеулер әлі де жалғасуда, алдағы уақытта құрылымды жаңа бір айнымалы функциямен байыту кезінде реттелген тұрақтылықты сақтаудың нақты критерийін анықтау маңызды..

Тірек сөздер: сызықтық реттелген құрылым, тәуелсіздік қасиеті, унар, реттелген тұрақтылық, o-минималдық.

Дата поступления статьи в редакцию: 29.07.2024

ФИЗИКАЛЫҚ ҒЫЛЫМДАР
PHYSICAL SCIENCES
ФИЗИЧЕСКИЕ НАУКИ

УДК 537.874.76:67.02
МРНТИ 47.09.35

https://doi.org/10.55452/1998-6688-2024-21-3-210-223

[1*]Шакирзянов Р.И.,
к.ф.-м.н., PhD, ORCID ID: 0000-0001-9908-3034,
*e-mail: shakirzyanov_ri@enu.kz
[2]Труханов А.В.,
д.ф.-м.н., доцент, ORCID ID: 0000-0003-3430-9578,
e-mail: truhanov86@mail.ru
[1,3]Шлимас Д.И.,
PhD, ORCID ID: 0000-0003-2454-7177,
e-mail: shlimas@mail.ru
[2]Зубарь Т.И.,
к.т.н., старший научный сотрудник, ORCID ID: 0000-0002-2225-9641,
e-mail: fix.tatyana@gmail.com
[1,3]Кадыржанов К.К.,
д.ф.-м.н., профессор, ORCID ID: 0009-0001-5462-0630,
e-mail: kayrat.kadyrzhanov@mail.ru

[1]Евразийский национальный университет им. Л.Н. Гумилева, 010000, г. Астана, Казахстан
[2]Научно-производственный центр Национальной академии наук Беларуси
по материаловедению, 220004, г. Минск, Беларусь
[3]Институт ядерной физики Министерства энергетики Республики Казахстан,
050032, г. Алматы, Казахстан

ИЗУЧЕНИЕ СТРУКТУРНЫХ И ЭЛЕКТРОМАГНИТНЫХ ХАРАКТЕРИСТИК КОМПОЗИТОВ ФЕРРОМАГНЕТИК-ДИАМАГНЕТИК, ПОЛУЧЕННЫХ МЕТОДОМ МОДИФИЦИРОВАННОГО ХИМИЧЕСКОГО ОСАЖДЕНИЯ

Аннотация

СВЧ электромагнитные характеристики композитов типа ферромагнетик-парамагнетик, ферромагнетик-диамагнетик могут быть изменены путем варьирования концентрации диамагнитных (парамагнитных) и ферромагнитных составляющих. Для реализации задачи по внедрению в производство таких композитов требуется проведение исследований по поиску эффективных и простых технологий синтеза, позволяющих варьировать содержание компонентов с различными магнитными характеристиками. В данной работе продемонстрирован простой метод получения композитов ферромагнетик ($(NiZn)Fe_2O_4$)-диамагнетик (ZnO) методом модифицированного химического осаждения с последующим отжигом. Также проведено комплекс-

ное исследование структурных и электромагнитных характеристик экспериментальных образцов. Методом рентгеновской дифракции было выявлено, что фазовый состав финальных образцов представлен исключительно диамагнитной и ферромагнитными фазами. Методом сканирующей электронной микроскопии было установлено, что после термического отжига порошки имеют субмикронные размеры со средним размером 100–137 нм. Методом вибрационной магнитометрии были измерены петли магнитного гистерезиса, анализ которых показал, что увеличение концентрации диамагнитной фазы приводит к росту значения коэрцитивной силы композитов. Измеренные микроволновые спектры комплексной магнитной проницаемости показывают, что путем изменения соотношения между ферромагнитной и парамагнитной фазами возможна реализация сдвига частоты естественного ферромагнитного резонанса. Также через расчет коэффициента отражения на металлической пластине показано, что полученные композиты могут быть использованы как основа для новых радиопоглощающих материалов. Помимо этого, синтезированные порошки могут быть также применены для создания СВЧ-приборов, СВЧ-антенн.

Ключевые слова: химическое осаждение, ферромагнетик, магнитная проницаемость, диэлектрическая проницаемость, субмикронные порошки.

Введение

Во многих областях науки и техники традиционно используемые материалы достигли предела возможностей, что может затормаживать развитие научно-технического процесса. Композиционные материалы (КМ) – наиболее очевидный и простой способ преодолеть этот предел [1]. Из-за наличия в КМ нескольких компонентов свойства таких материалов есть комбинация свойств компонентов и зависит от их взаимодействия и концентрации. КМ могут иметь совершенно новые уникальные свойства, которые быстро находят широкое практическое применение [2–4]. С конца XX века активно применяются магнитные КМ типа ферромагнетик-диамагнетик (ФМ-ДМ), ферромагнетик-парамагнетик (ФМ-ПМ). Последние позволили значительно увеличить плотность записи на магнитных жестких дисках за счет новых сверхчувствительных датчиков, выполненных из сверхрешеток ферромагнетик-парамагнитный проводник с эффектом гигантского магнетосопротивления [5]. Эффект гигантского магнетосопротивления объясняется квантовым обменным взаимодействием между магнитными подсистемами, хорошо изучен и нашел широкое практического применение. Несмотря на то что ярко проявляющие себя физические эффекты в КМ ФМ-ПМ наблюдаются в планарных сверхрешетках, современные исследования показывают, что новые эффекты в структурах из материалов с ферроупорядочением могут быть обнаружены в КМ иной размерности. Так, в слоистых и дисперсных КМ ферромагнетик-ферроэлектрик наблюдаются выраженный магнитоэлектрический эффект [6], эффект памяти формы в волокнистых ферроэластичных КМ [7], значительное изменение вида петли магнитного гистерезиса и магнитной энергии в композитах магнитомягкий-магнитожесткий ферромагнетик [8]. Предполагается, что в КМ ФМ-ДМ можно управлять электромагнитными характеристиками даже при изотропном распределении компонентов. Более подробное обоснование данной гипотезы будет приведено далее. В данной работе изучается возможность синтеза 3D-изотропных композитов ФМ-ДМ и изучение их структурных, квазимагнитостатических и электромагнитных характеристик.

Материалы и методы

В качестве исходных материалов использовались кристаллогидраты нитратов железа ($Fe(NO_3)_3 \cdot 6H_2O$), цинка ($Zn(NO_3)_2 \cdot 6H_2O$) и никеля ($Ni(NO_3)_2 \cdot 6H_2O$). Соли металлов имели квалификацию ХЧ и перед использованием высушивались в термостате при 60 ºС в течение 12 часов. Были подготовлены два образца, в которых мольное соотношение между катионами с валентностью 2+ (Ni, Zn) и 3+ (Fe) составляли 1 к 1. Соотношение молей между Ni^{2+}/Zn^{2+} составляло 0,4/0,6 (образец 1) и 0,2/0,8 (образец 2) соответственно. Такие концентрации были выбраны после отбора образцов, взаимодействующих с постоянным магнитом. Схематическое изображение получения экспериментальных образцов представлено на

рисунке 1. Нужные навески нитратов металлов взвешивались на аналитических весах и добавлялись к фиксированному объему воды для получения растворов. Полное растворение солей проводилось при температуре 50 ºС в течение 30 мин. с перемешиванием. После этого растворы смешивались в одном стакане. Перед добавлением диспергента ПВС смесь нагревалась до 90 ºС. При этой же температуре происходило выпаривание воды из раствора до получения золя и геля. После остывания и затвердевания геля полученный прекурсор измельчался в ступке с пестиком из фарфора. Для образования ферритовой фазы прекурсор отжигался в резистивной печи при температуре 900 ºС в течение 2 ч.



Рисунок 1 – Схематическое изображение получения экспериментальных образцов

Структурный и фазовый анализ отожженных порошков проводился методом порошковой рентгеновской дифракции на дифрактометре Bruker D8 Advance. Для исследования морфологии полученных частиц и оценки распределения размеров был использован сканирующий электронный микроскоп EVO 10 (Carl Zeiss). Съемка электронной микрофотографии проводилась при ускоряющем напряжении 20 кВ. Анализ химического состава (энергодисперсионный анализ (ЭДС)) образцов проводился с помощью зондового микроанализа «EDX AZtecLive Advanced Ultim Max 40» (Oxford Instruments), встроенного в микроскоп. Магнитные свойства полученных порошков исследовались через анализ магнитных петель гистерезиса σ(H). Измерение магнитного гистерезиса проводилось методом вибрационной магнитометрии при комнатной температуре на магнитометре Liquid Helium Free High Field Measurement System в магнитных полях H ± 3 кЭ. Измерение частотных спектров комплексной диэлектрической проницаемости ε*=ε’+iε’’ и комплексной магнитной проницаемости μ*=μ’+iμ’’ в области частот f от 10 МГц до 7 ГГц было осуществлено с использованием векторного анализатора цепей C1209 (PLANAR) и коаксиальной измерительной ячейки методом Николсона-Росса-Вира. Для этого полученный порошок, смешанный с пластификатором из поливинилового спирта, прессовался в кольца толщиной 3 мм с использованием пресс-формы из нержавеющей стали и гидравлического пресса.

Основные положения

Методом химического осаждения с последующим термическим отжигом получены КМ ФМ-ДМ состава (NiZn)Fe_2O_4/ZnO. Показано, что путем изменения концентрации между ФМ фазой и ДМ фазой можно изменять квазистатические магнитные свойства и динамические магнитные свойства в микроволновом диапазоне. Последнее реализуется за счет изменения частоты естественного ферромагнитного резонанса в ферромагнетике. Было установлено, что полученные КМ ФМ-ДМ могут иметь применение в качестве радиопоглощающих материалов в диапазоне частот 1–7 ГГц. Впервые метод модифицированного химического соосаждения рассмотрен как эффективный способ синтеза композитов ФМ-ДМ с возможностью вариации концентраций компонентов.

Обзор литературы


Для того чтобы обосновать гипотезу о возможном изменении электромагнитных характеристик изотропных дисперсных композитов ФМ-ДМ, был проведен литературный обзор. Известны структуры ФМ-ДМ, которые рассматривают как магнитные фононные кристаллы [9]. В таких структурах периодическая смена слоев ФМ-ДМ-ФМ-ДМ обуславливает появление интересных эффектов, таких как антирезонанс электромагнитных волн, появление частотных запрещенных зон распространения стоячих электромагнитных волн. Также изучаются 3D упорядоченные анизотропные структуры ФМ-ДМ, например, опал (SiO_2)-наночастицы Ni, Fe [10], [11]. 3D-структура ФМ-ДМ показывает S-образную петлю магнитного гистерезиса, обусловленную особым диполь-дипольным взаимодействием. Подобные структуры также имеют потенциал для применения, например, в магнитооптике и спинтронике [12]. Приведенные примеры возникающих физических эффектов показывают, что изучение композитов ФМ-ДМ имеет большой потенциал для исследований и должно быть расширено. В данной работе изучается возможность синтеза 3D изотропных композитов ФМ-ДМ и изучение их структурных, квазимагнитостатических и электромагнитных характеристик. Предполагается, что в КМ ФМ-ДМ можно управлять электромагнитными характеристиками даже при изотропном распределении компонентов. Известно большое количество физико-химических методов синтеза оксидных ферромагнетиков $MeFe_2O_4$ (ферриты-шпинели), которые имеют широкий спектр применений: как магнитная среда для трансформаторов, невзаимных СВЧ-устройств, радиопоглощающих материалов, катализаторов, очистителей воды [13, 14]. Синтез субмикронных и наночастиц ферритов наиболее часто производится методом химического соосаждения. Метод химического соосаждения заключается в осаждении из раствора солей металлов соединений, при термической обработке которых образуются нано- или субмикронные частицы заданной фазы с различной морфологией. Для получения ферритов используются модифицированные методы химического осаждения с использованием водорастворимого полимера поливинилового спирта (ПВС). Последний используется как добавка-диспергент, улучшающая распределение размеров частиц (узкий пик распределения и меньшей средний размер частиц) [15].

В качестве феррита-шпинели был использован Ni-Zn феррошпинель, а в качестве диамагнетика – оксид цинка ZnO. Синтез прекурсора для термического отжига проводился со следующей особенностью: в исходном растворе имелся избыток катионов Zn для формирования Ni-Zn феррита и оксида цинка ZnO. При отжиге прекурсора можно упрощенно записать следующее превращение катионов в оксиды: $Ni^{2+} + Fe^{3+} + Zn^{2+} + O^{2-} \rightarrow ZnO + Fe_2O_3 + NiO \rightarrow x \cdot NiFe_2O_4 + y \cdot ZnFe_2O_4 + ZnO$. Система $ZnFe_2O_4$-$NiFe_2O_4$ является твердым раствором с неограниченной растворимостью компонентов, поэтому в результате установления фазового равновесия при н.у. будет наблюдаться образование двух фаз: $Ni_xZn_yFe_2O_4 + ZnO$ [16]. Эти фазы будут связаны между собой не только электростатическим взаимодействием, но и химическими связями. В данном случае взаимодействие двух фаз, приводящее к изменению магнитных и электромагнитных характеристик, будет выражено в большей степени, чем в случае простой механической смеси.

Результаты и обсуждения

Рентгенофазовый анализ, выполненный по картинам рентгеновской дифракции (рисунок 2**)**, показывает наличие двух фаз: феррита шпинели (пространственная группа Fd-3m) и оксида цинка (пространственная группа P63mc). Интенсивность рефлексов феррита шпинели (220)F, (311)F, (511)F выше интенсивности наиболее выраженных рефлексов фазы оксида цинка. Это может говорить о большем содержании шпинельной фазы или о более совершенной кристаллической структуре. Количественный рентгеновский анализ был выполнен с помощью метода Ритвельда и программы Profex [17]. Параметр GoF (Goodness of Fit) при модели-

ровании имел значение в пределах 2,12–2,98, что говорит об удовлетворительной сходимости экспериментальных и расчетных данных. В качестве исходных рентгеновских карточек базы COD были выбраны карточки с номерами 04-014-8286 для феррошпинели и 04-003-2106 для оксида цинка. Было установлено, что в образце 2, который имел большую концентрацию катионов Zn, содержания фазы оксида цинка выше ~ 15% (таблица 2). Можно утверждать, что путем изменения мольного соотношения между солями Zn и Ni можно варьировать фазовый состав КМ ФМ-ДМ при синтезе методом химического осаждения. Помимо этого, наблюдается увеличение параметра решетки шпинели с 0,84056 до 0,8437 нм и уменьшение размера кристаллитов (таблица 1), оцененного по формуле Шерерра [18]. Изменение структурных параметров кристаллов можно объяснить более высокой степенью замещения катионами Zn^{2+} в структуре шпинели. Замещая катионы железа Fe^{3+}, катионы Zn^{2+} раздвигают анионы кислорода в тетраэдрических позициях из-за большего ионного радиуса.



а) б)


а) – образец № 1; б) – образец № 2

Рисунок 2 – Картины рентгеновской дифракции образцов, обработанных методом Ритвельда


Таблица 1 – Сравнение параметров решетки, объемного содержания фаз и среднего размера кристаллитов в полученных образцах

Образец	Параметры решетки, нм	Объемное содержание, %	Средний размер кристаллита, нм
1	(NiZn)Fe2O4: a = 0,84056 ZnO: a = 0,3249; c = 0,5201	(NiZn)Fe2O4: 84,47 ZnO: 15,53	34,17
2	(NiZn)Fe2O4: a = 0,8437 ZnO: a = 0,3249; c = 0,5203	(NiZn)Fe2O4: 67,16 ZnO: 32,84	32,59


Электронные микрофотографии полученных образцов и спектры ЭДС представлены на рисунке 3). Видно, что частицы полученных порошков имеют субмикронный размер, а также характеризуются тенденцией к сильной агломерации. С помощью программы ImageJ по микрофотографиям был определен средний размер частиц [19]. Для образца 1 размер частиц составил 137 нм, а для образца 2 – 100 нм. Спектры ЭДС, снятые по всей площади микрофотографии, показывают наличие атомов O, Zn, Ni, Fe, причем для образца 2 содержание атомов Zn было выше, чем для образца 1. Это подтверждает, что фаза ZnO увеличивается при изменении соотношения катионов Zn и Ni.




а)



б)



в)



г)

а) – микрофотография образца № 1, б) – ЭДС спектр образца № 1,
в) – микрофотография образца № 2, г) – ЭДС спектр образца № 2

Рисунок 3 – Электронные снимки и спектры ЭДС полученных образцов

Измеренные петли магнитного гистерезиса представлены на рисунке 4. Петли характеризуются низкими значениями коэрцитивной силы H_c: 19,32 Э для образца 1 и 46,51 Э для образца 2. Полученные порошки можно охарактеризовать как магнитомягкие, однако значения коэрцитивной силы намного выше, чем в промышленных Ni-Zn феррита. Для промышленных марок магнитомягких ферритов значения коэрцитивной силы составляют около 0,01 Э. Одной из причин значительного увеличения коэрцитивной силы является воздействие диамагнитной фазы, которая затрудняет движение магнитных доменов при перемагничивании частиц порошка. Из-за высокой концентрации поверхностных атомов в полученных частицах, намагниченность насыщения значительно ниже, чем в промышленных марках ферритов (35 Гс·см^3/г против 60 – 70 Гс·см^3/г). Поскольку полученные порошки получены после совместного химического осаждения и последующего отжига имеется сильная физико-химическая связь между диамагнитной и ферромагнитной фазами. Именно такая связь может значительно увеличивать значение коэрцитивной силы.





Рисунок 4 – Петли магнитного гистерезиса

На рисунке 5 представлены частотные спектры в области частот 0,05–7 ГГц комплексных диэлектрической и магнитной проницаемости полученных образцов. Узкие пики на рисунках 5а и 5в вызваны резонансом в измерительной ячейке и не связаны с процессами, происходящими в образце. Видно, что для образца 1 зависимости ε’(f) и ε’’(f) не изменяются с частотой в измеряемом диапазоне, что говорит об отсутствии релаксационных или резонансных процессов, связанных с поляризацией. Для образца 2, наоборот, наблюдается небольшой спад диэлектрической проницаемости с ростом частоты. Такая зависимость может быть объяснена тем, что значительный вклад в электрическую поляризацию вносит фаза ZnO. Оксид цинка по своим электрическим характеристикам близок к полупроводникам, поскольку из-за кислородных вакансий в нем возникает значительная концентрация носителей заряда. Квазичастицы – поляроны (дефект, связанный с носителем заряда) могут выступать в качестве электрических диполей. Существование поляронов, способных проводить прыжок (перескок заряда) на короткие расстояния, может обуславливать вклад в поляризацию в СВЧ области электромагнитных волн. Однако с увеличением частоты данные квазичастицы будут переставать давать вклад в поляризацию из-за невозможности закрепления в равновесном положении. По этой причине диэлектрическая проницаемость уменьшается с ростом частоты электромагнитного излучения.

Частотные спектры магнитной проницаемости показывают выраженные изменения при увеличении частоты с 0,05 до 7 ГГц (рисунки 5б, 5г). Зависимость μ’’(f) проходит через максимум, а μ’(f) резко падает до ~ 1. Такая зависимость характерна для релаксационных процессов динамического перемагничивания. Однако в рассматриваемом диапазоне частот электромагнитного излучения в ферромагнетиках происходит явление под названием «естественный ферромагнитный резонанс» [20]. При подмагничивании полем анизотропии магнитные моменты атомов испытывают гиротропное вращение. При совпадении частоты вращения (циклическая частота) с частотой электромагнитного излучения происходит резонанс, при котором энергия электромагнитного излучения преобразуется в тепло внутри ферромагнетика. Максимальное значение на зависимости μ’’(f) соответствует частоте естественного ферромагнитного резонанса. Данная частота определяется эффективным полем внутри магнетика [21]. Как видно из рисунков 5б, 5г, частотное положение частоты резонанса значительно сдвигается при изменении концентрации диамагнитной фазы ZnO. Это вызвано тем, что при добавлении диамагнитной фазы в КМ ФМ-ДМ внутреннее поле изменяется, что сдвигает в область высоких частот частоту резонанса. Таким образом, установлено, что в дисперсных композитах возможно изменение высокочастотных магнитных характеристик при изменении концентрации диамагнитной фазы.



а) – частотная зависимость диэлектрической проницаемости образца 1; б) – частотная зависимость магнитной проницаемости образца 1; в) – частотная зависимость диэлектрической проницаемости образца 2; г) – частотная зависимость магнитной проницаемости образца 2

Рисунок 5 – Частотные зависимости комплексных диэлектрической и магнитной проницаемостей синтезированных образцов

Чтобы продемонстрировать возможность практического применения полученных результатов, можно рассмотреть частотные зависимости расчетного коэффициента отражения на металлической пластине R_l. Математический расчет коэффициента отражения в этом случае показывает радиопоглощающие свойства материала и с высокой точностью совпадает с реальными измерениями [22]. Данный коэффициент рассчитывался по следующей формуле

$$R_l = 20 \lg \left| \frac{Z_{in} - 1}{Z_{in} + 1} \right|, \quad (1)$$

где $Z_{in} = \sqrt{\frac{\mu_r}{\varepsilon_r}} \tanh \left[i \left(\frac{2\pi}{c} \right) f d \sqrt{\mu_r \varepsilon_r} \right]$,

d – толщина поглотителя,
c – скорость света.

Высокое по амплитуде значение данного коэффициента показывает значительно ослабление энергии падающей электромагнитной волны при отражении от материала. Результаты моделирования представлены на рисунке 6. Были выбраны некоторые характерные толщины, на которых можно добиться наиболее малых значений коэффициента отражения. Как видно из рисунка при увеличении диамагнитной фазы можно сдвигать пик поглощения в более высокочастотную область при близких значениях толщины поглотителей. Можно также констатировать, что полученный материал имеет выраженные радиопоглощающие характеристики с ослаблением энергии электромагнитных волн до -48 дБ на частоте 2,4 ГГц и ослаблением на уровне –10 дБ в 2–4 ГГц.

Помимо этого, образец 2 может быть использован как основа для антенн СВЧ-приборов ввиду более высокой частоты естественного ферромагнитного резонанса. Такое применение материал может найти в диапазоне частот 0,05–1 ГГц (дорезонансная область), поскольку значение магнитной проницаемости еще превышает единицу, а магнитные потери μ” не выражены. Порошок может вводиться в полимерную матрицу в качестве наполнителя для создания гибких подложек для антенн.




Рисунок 6 – Смоделированные частотные зависимости коэффициента отражения на металлической пластине для полученных образцов

Заключение

В работе продемонстрирован метод модифицированного химического осаждения для получения дисперсных композитов (нано- и субмикронные частицы) типа ФМ-ДМ. Показано, что использование исходного совместного раствора солей Zn, Ni и Fe, в которых мольное соотношение между катионами с валентностью 2+ (Ni, Zn) и 3+ (Fe) составляли 1 к 1, приводит к формированию фазы ферромагнитной шпинели и диамагнитного цинка. Некоторые структурные изменения в кристаллических параметрах шпинели связаны с замещением катионов Ni и Fe катионами Zn. Увеличение содержания диамагнитной фазы приводит к росту коэрцитивной силы и уменьшению намагниченности насыщения в полученных КМ. Также установлено, что изменение концентрации диамагнитной фазы приводит к изменению частотного положения естественного ферромагнитного резонанса. Этот факт позволяет управлять микроволновыми свойствами (частотной дисперсией магнитной проницаемости) дисперсных КМ ФМ-ДМ, полученных методом химического осаждения с последующим отжигом. Продемонстрировано потенциальное применение полученных КМ в качестве радиопоглотителей микроволнового излучения в диапазоне частот 1–7 ГГц.

Информация о финансировании

Данное исследование финансировалось Комитетом науки Министерства науки и высшего образования Республики Казахстан (No. AP19680155)

ЛИТЕРАТУРА

1 Бондалетова Л.И., Бондалетов В.Г. Полимерные композиционные материалы (часть 1): Учебное пособие // Томск: Изд-во Томского политехнического университета. – 2013. – С. 118.

2 Михайлин Ю.А. Специальные полимерные композиционные материалы. – 2009.

3 Lagarkov A.N., Rozanov K.N. High-frequency behavior of magnetic composites // Journal of Magnetism and Magnetic Materials. – 2009. – V. 321. – No. 14. – P. 2082–2092.

4 Chairi M., El Bahaoui J., Hanafi I., Mata Cabrera F., Di Bella G. Composite Materials: A Review of Polymer and Metal Matrix Composites, Their Mechanical Characterization, and Mechanical Properties // Next Generation Fiber-Reinforced Composites-New Insights. – 2023.

5 Tang D.D., Lee Y.J. Magnetic memory: fundamentals and technology. – Cambridge University Press, 2010.

6 Liang X., Matyushov A., Hayes P., Schell V., Dong C., Chen H., He Y., Will-Cole A., Quandt E., Martins P. et al. Roadmap on magnetoelectric materials and devices //IEEE Transactions on Magnetics. – 2021. – V. 57. – No. 8. – P. 1–57.

7 Cohades A., Michaud V. Shape memory alloys in fibre-reinforced polymer composites // Advanced Industrial and Engineering Polymer Research. – 2018. – V. 1. – No. 1. – P. 66–81.

8 Ghidini M., Asti G., Pellicelli R., Pernechele C., Solzi M. Hard–soft composite magnets // Journal of magnetism and magnetic materials. – 2007. – V. 316. – No. 2. – P. 159–165.

9 Fang M., Volotinen T.T., Kulkarni S.K., Belova L., Rao K.V. Effect of embedding Fe3O4 nanoparticles in silica spheres on the optical transmission properties of three-dimensional magnetic photonic crystals // Journal of Applied Physics. – 2010. – V. 108. – No. 10. – P. 103501.

10 Ávila-Crisóstomo C.E., Sánchez-Mora E., Garcia-Vazquez V., Pérez-Rodríguez F. Magnetic response of Fe nanoparticles embedded in artificial SiO2 opals // Journal of Magnetism and Magnetic Materials. – 2018. – V. 465. – P. 252–259.

11 Ávila-Crisóstomo C.E., Pal U., Pérez-Rodríguez F., Shelyapina M.G., Shmyreva A.A. Local-field effect on the hybrid ferromagnetic-diamagnetic response of opals with Ni nanoparticles // Journal of Magnetism and Magnetic Materials. – 2020. – V. 514. – P. 167102.

12 Gray M.T., Emori S., Gray B.A., Jeon H., van 't Erve O.M.J., Jonker B.T., Kim S., Suzuki M., Ono T., Howe B.M. et al. Spin-current generation in low-damping Ni0.65Zn0.35Al 0.8Fe1.2O4 spinel ferrite // Physical Review Applied. – 2018. – V. 9. – No. 6. – P. 064039.

13 Thakur P., Chahar D., Taneja S., Bhalla N. A review on MnZn ferrites: Synthesis, characterization and applications // Ceramics international. – 2020. – V. 46. – No. 10. – P. 15740–15763.

14 Narang S.B., Pubby K. Nickel spinel ferrites: a review //Journal of Magnetism and Magnetic Materials. – 2021. – V. 519. – P. 167163.

15 Chakradhary V.K., Akhtar M.J. Highly coercive strontium hexaferrite nanodisks for microwave absorption and other industrial applications // Composites Part B: Engineering. – 2020. – V. 183. – P. 107667.

16 Смит Я., Вейн Х. Физические свойства и практические применения. – М.: Издательство иностранной литературы. – 1962. – С. 504.

17 Doebelin N., Kleeberg R. Profex: a graphical user interface for the Rietveld refinement program BGMN // Journal of applied crystallography. – 2015. – V. 48. – No. 5. – P. 1573–1580.

18 Hargreaves J.S.J. Some considerations related to the use of the Scherrer equation in powder X-ray diffraction as applied to heterogeneous catalysts // Catalysis, Structure & Reactivity. – 2016. – V. 2. – No. 1–4. – P. 33–37.

19 Rueden C.T., Schindelin J., Hiner M.C., DeZonia B.E., Walter A.E., Arena E.T., Eliceiri K.W. ImageJ2: ImageJ for the next generation of scientific image data //BMC bioinformatics. – 2017. – V. 18. – P. 1–26.

20 Tsutaoka T., Kasagi T., Nakamura T., Hatakeyama K. High frequency permeability of Mn-Zn ferrite and its composite materials // Le Journal de Physique IV. – 1997. – V. 7. – No. 1. – P. 557–558.

21 Lopatin A.V., Kazantseva N.E., Kazantsev Y.N. et al. The efficiency of application of magnetic polymer composites as radio-absorbing materials // Journal of Communications Technology and Electronics. – 2008. – V. 53. – P. 487–496.

22 Wang B., Wei J., Qiao L., Wang T., Li F. Influence of the interface reflections on the microwave reflection loss for carbonyl iron/paraffin composite backed by a perfect conduction plate // Journal of magnetism and magnetic materials. – 2012. – V. 324. – No. 5. – P. 761–765.

REFERENCES

1 Bondaletova L.I., Bondaletov V.G. (2013) Polymernie compositsionye materialy (chast' 1), 118 p. [in Russian].

2 Michailin Yu. A. Special'nye polymernie compositsionye materialy (2009).

3 Lagarkov A.N. and Rozanov K.N. (2009) Journal of Magnetism and Magnetic Materials, no. 321, pp. 2082–2092. https://doi.org/10.1016/j.jmmm.2008.08.099.

4 Chairi M., El Bahaoui J., Hanafi I., Mata Cabrera F. and Di Bella G. (2023) Composite Materials: A Review of Polymer and Metal Matrix Composites, Their Mechanical Characterization, and Mechanical Properties (Intechopen).

5 Tang D.D. and Lee Y.J. (2010) Magnetic memory: fundamentals and technology (Cambridge University Press).

6 Liang X., Matyushov A., Hayes P., Schell V., Dong C., Chen H., He Y., Will-Cole A., Quandt E., Martins P. et al. (2021) Roadmap on magnetoelectric materials and devices. IEEE Transactions on Magnetics, vol. 57, pp. 1–57. https://doi.org/10.1109/TMAG.2021.3086635.

7 Cohades A. and Michaud V. (2018) Advanced Industrial and Engineering Polymer Research, no.1, pp. 66–81. https://doi.org/10.1016/j.aiepr.2018.07.001.

8 Ghidini M., Asti G., Pellicelli R., Pernechele C. and Solzi M. (2007) Hard–soft composite magnets. Journal of Magnetism and Magnetic Materials, vol. 316, pp. 159–165. https://doi.org/10.1016/j.jmmm.2007.02.040.

9 Fang M., Volotinen T.T., Kulkarni S.K., Belova L. and Rao K.V. (2010) Effect of embedding Fe3O4 nanoparticles in silica spheres on the optical transmission properties of three-dimensional magnetic photonic crystals. Journal of Applied Physics, vol. 108, p. 103501.

10 Ávila-Crisóstomo C.E., Sánchez-Mora E., Garcia-Vazquez V., Pérez-Rodríguez F. (2018) Magnetic response of Fe nanoparticles embedded in artificial SiO2 opals. Journal of Magnetism and Magnetic Materials, vol. 465, pp. 252–259. https://doi.org/10.1016/j.jmmm.2018.05.087

11 Ávila-Crisóstomo C.E., Pal U., Pérez-Rodríguez F., Shelyapina M.G., Shmyreva A.A. (2020) Local-field effect on the hybrid ferromagnetic-diamagnetic response of opals with Ni nanoparticles. Journal of Magnetism and Magnetic Materials, vol. 514, p.167102. https://doi.org/10.1016/j.jmmm.2020.167102

12 Gray M.T., Emori S., Gray B.A., Jeon H., van 't Erve O.M.J., Jonker B.T., Kim S., Suzuki M., Ono T., Howe B.M. et al. (2018) Spin-current generation in low-damping $Ni_{0.65}Zn_{0.35}Al_{0.8}Fe_{1.2}O_4$ spinel ferrite. Physical Review Applied, vol. 9, p. 064039. https://doi.org/10.1103/PhysRevApplied.9.064039.

13 Thakur P., Chahar D., Taneja S., Bhalla N. (2020) A review on MnZn ferrites: Synthesis, characterization and applications. Ceramics international, vol. 46, pp. 15740–15763. https://doi.org/10.1016/j.ceramint.2020.03.287.

14 Narang S.B., Pubby K. (2021) Nickel spinel ferrites: a review. Journal of Magnetism and Magnetic Materials, vol. 519, p. 167163. https://doi.org/10.1016/j.jmmm.2020.167163.

15 Chakradhary V.K., Akhtar M.J. (2020) Highly coercive strontium hexaferrite nanodisks for microwave absorption and other industrial applications. Composites Part B: Engineering, vol. 183, p. 107667. https://doi.org/10.1016/j.compositesb.2019.107667.

16 Smit J. and Wijn H.P.J. Ferrites. Physical properties of ferrimagnetic oxides in relation to their technical applications (Philips' Technical Library, Eindhoven, 1959).

17 Doebelin N., Kleeberg R. (2015) Profex: a graphical user interface for the Rietveld refinement program BGMN. Journal of applied crystallography, vol. 48, pp. 1573–1580. https://doi.org/10.1107/S1600576715014685.

18 Hargreaves J. S. J. (2016) Some considerations related to the use of the Scherrer equation in powder X-ray diffraction as applied to heterogeneous catalysts. Catalysis, Structure & Reactivity, vol. 2, pp. 33–37. https://doi.org/10.1080/2055074X.2016.1252548.

19 Rueden C.T., Schindelin J., Hiner M.C., DeZonia B.E., Walter A.E., Arena E.T. Eliceiri K.W. (2017) ImageJ2: ImageJ for the next generation of scientific image data. Eliceiri. BMC bioinformatics, vol.18, pp.1–26. https://doi.org/10.1186/s12859-017-1934-z.

20 Tsutaoka T., Kasagi T., Nakamura T., Hatakeyama K. (1997) High frequency permeability of Mn-Zn ferrite and its composite materials. Le Journal de Physique IV, vol. 7, pp. 557–558. https://doi.org/10.1051/jp4:19971230.

21 Lopatin A.V., Kazantseva N.E., Kazantsev Y.N. et al. (2008) The efficiency of application of magnetic polymer composites as radio-absorbing materials. Journal of Communications Technology and Electronics, vol. 53, pp. 487–496. https://doi.org/10.1134/S106422690805001X.

22 Wang B., Wei J., Qiao L., Wang T., Li F. (2012) Influence of the interface reflections on the microwave reflection loss for carbonyl iron/paraffin composite backed by a perfect conduction plate. Journal of magnetism and magnetic materials, vol. 324, pp. 761–765.

[1]*Shakirzyanov R.I.,
Candidate of Phys.-Math.Sc., PhD, ORCID ID: 0000-0001-9908-3034,
*e-mail: shakirzyanov_ri@enu.kz
[2]Trukhanov A.V.,
Dr.Phys.-Math.Sc., Associate Professor, ORCID ID: 0000-0003-3430-9578,
e-mail: truhanov86@mail.ru
[1,3]Shlimas D.I.,
PhD, ORCID ID: 0000-0003-2454-7177,
e-mail: shlimas@mail.ru
[2]Zubar T.I.,
Candidate of Technical Sciences, Senior Researcher, ORCID ID: 0000-0002-2225-9641,
e-mail: fix.tatyana@gmail.com
[1,3]Kadyrzhanov K.K.,
Dr.Phys.-Math.Sc., Professor, ORCID ID: 0009-0001-5462-0630,
e-mail: kayrat.kadyrzhanov@mail.ru

[1]L.N. Gumilev Eurasian National University, 010000, Astana, Kazakhstan
[2]SSPA "Scientific and Practical Materials Research Centre of NAS of Belarus",
220004, Minsk, Belarus
[3]Institute of Nuclear Physics, Ministry of Energy of the Republic of Kazakhstan,
050032, Almaty, Kazakhstan

STUDY OF THE STRUCTURAL AND ELECTROMAGNETIC CHARACTERISTICS OF FERROMAGNETIC-DIAMAGNETIC COMPOSITES OBTAINED BY THE METHOD OF MODIFIED CHEMICAL CO PRECIPITATION

Abstract

The microwave electromagnetic properties of ferromagnetic-paramagnetic and ferromagnetic-diamagnetic composites can be changed by varying the concentration of diamagnetic (paramagnetic) and ferromagnetic

components. To implement the task of introducing such composites into production, research is required to find effective and simple synthesis technologies that make it possible to vary the content of components with different magnetic characteristics. This work demonstrates a simple method for the synthesis of ferromagnetic ((NiZn)Fe_2O_4)-diamagnetic (ZnO) composites by modified chemical deposition followed by annealing. Also, a comprehensive study of the structural and electromagnetic characteristics of experimental samples was carried out. Using the powder X-ray diffraction method, it was revealed that the phase composition of the final samples is represented exclusively by diamagnetic and ferromagnetic phases. Using scanning electron microscopy, it was found that after thermal annealing the powders have submicron sizes with an average size of 100–137 nm. Using vibration magnetometry, magnetic hysteresis loops were measured, the analysis of which showed that an increase in the concentration of the diamagnetic phase leads to an increase in the coercive force of the composites. The measured microwave spectra of complex magnetic permeability show that by changing the ratio between the ferromagnetic and paramagnetic phases, it is possible to realize a frequency shift of natural ferromagnetic resonance. Also, through the calculation of the reflection coefficient on a metal plate, it is shown that the resulting composites can be used as the basis for new radio-absorbing materials. In addition, the synthesized powders can also be used to create microwave devices and microwave antennas.

Key words: coprecipitation, ferromagnetics, permeability, dielectric constant, submicron powders.

[1]*Шакирзянов Р.И.,
ф.-м.ғ.к., PhD, ORCID ID: 0000-0001-9908-3034,
*e-mail: shakirzyanov_ri@enu.kz
[2]Труханов А.В.,
ф.-м.ғ.д., доцент, ORCID ID: 0000-0003-3430-9578,
e-mail: truhanov86@mail.ru
[1,3]Шлимас Д.И.,
PhD, ORCID ID: 0000-0003-2454-7177, e-mail: shlimas@mail.ru
[2]Зубарь Т.И.,
т.ғ.к., аға ғылыми қызметкер, ORCID ID: 0000-0002-2225-9641,
e-mail: fix.tatyana@gmail.com
[1,3]Кадыржанов К.К.,
ф.-м.ғ.д., профессор, ORCID ID: 0009-0001-5462-0630,
e-mail: kayrat.kadyrzhanov@mail.ru

[1]Л.Н. Гумилев атындағы Еуразия ұлттық университеті, 010000, Астана қ., Қазақстан
[2]Беларусь Ұлттық ғылым академиясының материалтану жөніндегі
ғылыми-өндірістік орталығы, 220004, Минск қ., Беларусь
[3]Қазақстан Республикасы Энергетика министрлігінің «Ядролық физика институты»,
050032, Алматы қ., Қазақстан

МОДИФИКАЦИЯЛАНҒАН ХИМИЯЛЫҚ ТҰНДЫРУ ӘДІСІМЕН АЛЫНҒАН ФЕРРОМАГНИТТІК-ДИАМАГНИТТІ КОМПОЗИТТЕРДІҢ ҚҰРЫЛЫМДЫҚ ЖӘНЕ ЭЛЕКТРОМАГНИТТІК СИПАТТАМАЛАРЫН ЗЕРТТЕУ

Аңдатпа

Композиттердің ферромагнетик-парамагнетик, ферромагнетик-диамагнетик типтерінің АЖЖ электромагниттік сипаттамаларын диамагнетикалық (парамагнетикалық) және ферромагнетикалық құрамдастардың концентрациясын түрлендіру арқылы өзгертуге болады. Өндірісте осындай композиттерді енгізу үшін әртүрлі магниттік сипаттамаға ие компоненттердің құрамын өзгертуге мүмкіндік беретін тиімді және қарапайым синтез технологияларын іздестіру бойынша зерттеулер жүргізу қажет. Бұл жұмыста модификацияланған химиялық тұндыру әдісімен ферромагнетик ((NiZn)Fe2O4)-диамагнетик (ZnO) композиттерін алудың қарапайым әдісі ұсынылған. Сонымен қатар эксперименттік үлгілердің құрылымдық және электромагниттік сипаттамаларының кешенді зерттеуі жүргізілді. Рентгендік дифракция әдісімен соңғы үлгілердің фазалық құрамы тек диамагнетикалық және ферромагнетикалық фазалардан тұратыны анықталды. Сканерлеуші

электрондық микроскопия әдісімен термиялық өңдеуден (күйдіруден) кейін ұнтақтардың орташа мөлшері 100–137 нм болатын субмикронды өлшемдерге ие екендігі анықталды. Вибрациялық магнитометрия әдісімен магниттік гистерезис ілмектері өлшенді, олардың талдауы диамагнетикалық фазаның концентрациясының ұлғаюы композиттердің коэрцитивтік күшінің мәнін арттыратыны анықталды. Өлшенген микротолқынды спектрлер күрделі магниттік өтімділік ферромагниттік және парамагниттік фазалар арасындағы қатынасты өзгерту арқылы табиғи ферромагниттік резонанс жиілігінің ауысуын жүзеге асыруға болатынын көрсетеді. Сондай-ақ металл пластинаға шағылысу коэффициентін есептеу арқылы алынған композиттердің жаңа радиосіңіргіш материалдар негізі ретінде пайдалануға болатыны айқындалды. Сонымен қатар синтезделген ұнтақтарды АЖЖ құрылғыларды, АЖЖ антенналарды жасау үшін де қолдануға болады.

Тірек сөздер: химиялық тұндыру, ферромагнетик, магниттік өткізгіштік, диэлектрлік өтімділік, субмикрон ұнтақтары

Дата поступления статьи в редакцию: 03.04.2024

UDC 001.38
IRSTI 12.01.11

https://doi.org/10.55452/1998-6688-2024-21-3-224-235

[1,2]*Amirbekova D.,
PhD, ORCID ID: 0000-0002-7801-1629,
*e-mail: d.amirbekova@kbtu.kz
[1]Li Y.,
Master, ORCID ID: 0009-0004-1365-4297,
e-mail: yelena.li@alumni.nu.edu.kz

[1]Kazakh-British Technical University, 050000, Almaty, Kazakhstan
[2]Northwestern University, Evanston, Illinois, United States

SURVEYING RESEARCH LANDSCAPES: REVEALING ATTRIBUTES IN THE PHYSICAL SCIENCES OF KAZAKHSTAN

Abstract

This article presents a comprehensive survey-based analysis of the current research landscape within Kazakhstan's academic community. Drawing from responses collected from 265 researchers and academics across various universities, the study unveils insightful demographic profiles and research attributes across four distinct subject areas. While encompassing a broad spectrum of disciplines, particular attention is directed towards the characteristics and trends within the physical sciences domain. The survey explores Kazakhstan's physical sciences research landscape, revealing a focus on international collaborations, particularly with Western academics, to enhance research visibility. Challenges include limited emphasis on partnerships with governmental or non-governmental organizations, adverse working conditions, and disparities in resource access, notably in high-performance computing facilities. This research provides a detailed understanding of the current state of academic research within the country and offers a nuanced perspective that can inform strategic planning, policy formulation, and future research endeavors.

Key words: research activity, science, Kazakhstani universities, publication activity, science development, collaboration, physical science.

Introduction

The development of higher education institutions plays a crucial role in shaping the trajectory of a nation's progress, with profound implications for its socio-economic landscape and global standing. Over the years, scholars and policymakers alike have recognized the pivotal role of universities in driving scientific advancement, technological innovation, and human capital development. The establishment and growth of internationally renowned higher education institutions are intrinsically linked to the overall development of a nation. Indeed, universities serve as engines of knowledge creation, hubs of intellectual discourse, and catalysts for societal transformation [1]. Brekke [2] described universities as central hubs for generating and sharing knowledge, highlighting their essential role as primary participants in research advancement to address societal demands and stimulate economic development.

In the context of Kazakhstan, a country with a burgeoning higher education sector and aspirations for socio-economic development, the role of universities takes on added significance. The research activity of scientists in modern Kazakhstan is one of the areas of development of human capital, which saw significant improvements in the 1990s when crucial reforms were carried out in higher education and science [3]. These reforms aimed primarily at integrating local science into the international scientific community [4]. Further substantial reforms were implemented in March 2010

when Kazakhstan joined the Bologna Process, a move that underscored the nation's efforts to align its higher education system with international standards. The necessity for researchers to publish in peer-reviewed journals indexed in prestigious databases such as Scopus underscores Kazakhstan's commitment to enhancing its research output and global visibility.

The literature on the role of universities in driving scientific advancement and economic growth is extensive and multifaceted, spanning various disciplines and research contexts. Scholars such as Agasisti et al. [5] have explored the economic implications of university research, emphasizing the role of academic publications in driving knowledge spillovers and fostering innovation. As Kazakhstan seeks to transition to a knowledge-based economy, the strategic importance of universities in promoting research and innovation becomes increasingly apparent. However, the realization of Kazakhstan's aspirations for scientific and technological advancement is not without its challenges. Issues such as limited access to research funding, inadequate research infrastructure, and brain drain pose significant obstacles to the country's research ecosystem. Addressing these challenges requires a multifaceted approach, including policy interventions, investment in research infrastructure, and the promotion of collaboration between academia, industry, and government.

As a former Soviet Union country, Kazakhstan has inherited a focus on several research fields, particularly the so-called "hard sciences" like physics and mathematics [6]. This emphasis has created a significant gap between these and other fields of research, a disparity that remains evident today [7]. Despite a noted decrease in the share of published works in the natural sciences [6], fields such as natural sciences, engineering, and technology continue to dominate research output. It is globally recognized that research is produced by universities and non-university research institutes, with the latter focusing primarily on research activities [8]. In Kazakhstan, research efforts have increasingly shifted towards universities, driven by recent policy changes that target the research potential of scientists, develop academic programs transitioning from Soviet-era qualifications to Ph.D. degrees, and invest in human capital development [9].

The significance of scientific development for economic growth in Kazakhstan is underscored and it is argued that the research activity of scientists is a crucial component of human capital development, further reinforcing the integral role of scientific endeavors in shaping the nation's socio-economic landscape [3]. Universities are widely acknowledged as primary engines of knowledge creation, serving as incubators for groundbreaking research and innovation. According to Brekke [2], universities are crucial for creating new knowledge through research, which advances our understanding and technological progress. It is suggested that universities united with a shared vision for development can contribute significantly to regional development [10]. Freitas et al. [11] note that governments prioritize investing in research and training within educational institutions to enhance their entrepreneurial role, with research and education institutions playing a growing role in helping local businesses transition into more dynamic and promising industries [12].

In Kazakhstan, a positive trend is emerging, with a gradual shift of resources towards research and development within the higher education sector [13]. This shift is significant, given the strong correlation found between higher education sector investments in R&D and the creation of new technologies [14]. Efforts are underway to enhance the research capacity of universities as part of a government initiative aimed at fostering a competitive and innovative economy [15]. As a result, there has been a noticeable upward trend in the number of publications from Kazakhstani universities, as shown by the increase in papers published in the Scopus database from 1991 to 2022 (Figure 1) [15].

However, despite these significant contributions, challenges persist. Issues such as funding constraints, limited industry-academic collaborations, and the need for greater interdisciplinary research collaboration remain pertinent. According to OECD [16] research potential in Kazakhstan is constrained by ongoing challenges such as heavy teaching and administrative responsibilities, restricted availability of resources and databases, and inadequate proficiency in the English language. As the literature highlights the pivotal role of universities, it becomes evident that constant monitoring and assessment of the research landscape is crucial for fostering innovation, driving economic growth, and addressing societal challenges.




Figure 1 – Papers published in the Scopus database
affiliated with Kazakhstan in 1991–2022

Kazakhstan, like many post-USSR countries, maintains a strong emphasis on research in physical sciences, reflecting a historical bias towards these fields as the foundation of technological progress. In the study on disciplinary specialization, Kazakhstan has a relative strength in fields such as Applied Physics, a legacy of the USSR's prioritization and investment in physical sciences [17, 18]. Post-communist countries, including those in Central and Eastern Europe and the former USSR, continue to prioritize fundamental sciences, maintaining the highest Relative Citation Index (RCA) coefficients in these fields compared to other world regions [19].

To identify the current state of research activities undertaken by academics in Kazakhstan, particularly in the physical sciences, a survey was conducted focusing on their work environment and publication priorities. The findings aim to provide insights into demographic profiles, research attributes, and prevailing challenges, contributing to a better understanding of Kazakhstan's scientific development and its potential for future growth.

Materials and Methods

We employed a survey as our primary method of data collection. The research unfolded in two distinct phases: initially, data collection was undertaken following a specified set of procedures. Subsequently, the second phase involved organizing and interpreting the collected data. Drawing upon the findings of Amirbekova et al. [15], wherein the authors identified the top five authors in each subject area affiliated with universities in Kazakhstan from 1991 to 2022, we selected 18 universities (appendix 1) to which these top authors are affiliated. Subsequently, we gathered all accessible data concerning the academic staff at each university. As a result, information on academic staff was obtainable from the official websites of 16 of the selected universities. In total, 9425 contacts from these 16 universities, spanning various subject fields, were identified. Among these academic staff contacts, 5603 included email addresses; consequently, contacts lacking email addresses were excluded. Following random sampling of the remaining list, wherein 50% of academic contacts were selected at random from each university, a total of 2800 contacts remained.

The survey targeted academics from universities in Kazakhstan. Its primary focus was to analyze publication activities across these institutions. The survey encompassed subject areas classified by the Scopus database and 16 state and non-state universities across Kazakhstan. Comprising three sections and 40 questions in total, the questionnaire delved into various aspects: the first section, comprising 19 questions, aimed at understanding respondents' profiles and employment positions;

the second section, with 11 questions, focused on their research activities; and the third section, containing 10 questions, explored respondents' publishing strategies. Anonymously answered by 265 individuals, the survey provided insights into the academic landscape of Kazakhstan.

Results and Discussion

According to the Scopus, Elsevier's abstract and citation database, scientific works can be classified as four broad categories: Social Sciences, Medicine, Life Sciences and Physical Sciences. Upon examining the distribution of subject areas before dividing it into four Scopus categories, it is evident that subject area categorized as "Art and Humanities" constituted the largest proportion at 22%, followed by social sciences (12%), chemistry (11%), medicine (8%), engineering (8%), etc.

Following the categorization of subject areas into Scopus categories, there has been a shift in distribution across these categories. Physical sciences constitute the majority, accounting for 45% of all respondents, followed by social sciences at 41%, with medicine comprising 8%, and life sciences at 5%. Age distribution, demonstrates that discrepancies in age distribution in medicine and life sciences are less notable, largely attributed to significant differences in the number of respondents. In the category of social sciences, the prevailing age groups are "between 40 and 49", "between 30 and 39", and "between 50 and 59" (refer to Figure 2 for details).

In the realm of physical sciences, the majority of respondents fall between the ages of 30 and 39 (34%). Age groups "Between 40 and 49" and "Between 50 and 59" are also equally important, accounting for 25% each. There is a notable decrease in the number of individuals aged younger than 30 (5%) and those aged 60 or older (12%).




Figure 2 – Age distribution

Table 1 effectively demonstrates the working conditions of all respondents. Since respondents had the option to select multiple choices, the total number of responses amounted to 842. The most common response, "work is meaningful," was chosen by 193 respondents, accounting for 23% of the total. Similarly, this answer was the most common across all four categories. Looking at responses across all categories, other frequently selected answers by respondents from life sciences included "I enjoy considerable autonomy in my everyday working life" (14%) and "The competition among those working in my discipline is intense" (12%). In the field of medicine, these were "Academia offers me long-term opportunities for advancement" (15%) and "My salary is too low" (13%). In social sciences, common responses were "My workload is excessive" (15%) and "My salary is too low" (13%).

In physical sciences, respondents often chose “My salary is too low” (12%) and “I enjoy considerable autonomy in my everyday working life” (11%). The least frequent response pertained to the statement “In my subject area, there is considerable pressure to attract external funding” (for additional information, please refer to Table 2).

Table 1 – Working conditions in academia

Subject area broad	Physical sciences	Medicine	Life Sciences	Social Sciences
I enjoy considerable autonomy in my everyday working life	45	5	7	33
Academia offers me long-term opportunities for advancement	43	8	4	29
My salary is too low	49	7	2	42
My work is meaningful	95	13	12	73
The competition among those working in my discipline is intense	32	4	6	19
In my subject area, there is considerable pressure to publish	31	3	5	29
In my subject area, there is considerable pressure to attract external funding	21	3	4	19
My workload is excessive	51	5	4	49
If the idea is good and plausible, then publishing embellished results will do no harm	21	2	2	10
To survive in the competitive, “publish or perish” academic environment, you can’t always stick to all the rules.	28	3	3	21

The next question aimed to identify the strategies academics employ to stay abreast of current research in their field on a regular basis. Respondents were allowed to select multiple options. In total, there were 1117 responses. Table 2 illustrates that the most common response across all four fields was “I attend conferences or workshops,” with 200 respondents or 18% selecting this option. Upon examining the category of physical sciences, the second and third most frequent responses were “I read materials suggested by other academics” and “I follow the work of key academics”. The least frequently used tactic to keep up with current research was setting Google alerts for specific relevant keywords.

The subsequent question (Table 3) focused on access to specific resources or facilities provided by respondents’ institutions to facilitate research in their respective fields of work. The survey results revealed one prevailing answer across all four categories: online access to journals, databases, and books (28%). For physical sciences, other frequently accessed resources included research laboratories and equipment, along with a well-stocked library. The two least commonly chosen responses were “Institutional research ethics review board” and “High-performance computing facilities”.

Table 2 – Tactics to “keep up” with current research

Subject area broad	Physical sciences	Medicine	Life Sciences	Social Sciences
I follow the work of key academics	69	7	7	64
I regularly skim new issues of key journals	67	8	3	58
I read / skim book reviews	47	4	4	51
I regularly skim table of contents of key journals	53	7	6	46
I set google alerts for specific relevant keywords	34	0	6	21
I read materials suggested by other academics	77	9	4	67
I read materials rated highly by a relevant repository or research tool	53	3	2	33
I follow other researchers through blogs or social media	49	6	5	47
I attend conferences or workshops	89	16	8	87

Table 3 – Access to specific resources or facilities provided by respondents’ institutions

Subject area broad	Physical sciences	Medicine	Life Sciences	Social Sciences
Research laboratories and equipment	61	3	8	16
Internal research funding opportunities	34	8	4	29
Access to a well-stocked library	46	13	7	56
Online access to journals, databases, books	87	18	10	77
Dedicated research support staff (e.g., research assistants, staff to support you with funding applications)	22	3	0	16
High-performance computing facilities	16	2	2	5
Collaborative research spaces or centres	32	1	4	24
Access to specialised software or research tools	27	3	3	13
Institutional research ethics review board	14	3	5	19

On the question of which types of relationships have been the most important for respondent’s research development (Table 4), collaborations with academics from other institutions in Kazakhstan was the most frequent answer. For academics within the realm of physical sciences, collaborations occurring both within and beyond their institution’s borders hold significant importance. Notably, collaborations with fellow academics within their institution and with counterparts from other institutions within Kazakhstan are highlighted as crucial. Additionally, collaborations with academics in other post-Soviet countries emerge as equally vital for researchers in the field of physical sciences. In contrast, collaborations with government or non-governmental organizations are considered of lesser importance for academics specializing in the physical sciences.

Table 4 – Types of relationships have been the most important for respondent's research development

Subject area broad	Physical sciences	Medicine	Life Sciences	Social Sciences
Collaborations with academics at your institution	47	10	5	45
Collaborations with academics from other institutions in Kazakhstan	48	13	8	53
Collaborations with academics in other post-Soviet countries	47	5	4	36
Collaborations with academics in Western countries	54	7	8	44
Collaborations with academics in China, Japan, Korea	13	3	2	15
Collaborations with government or non-governmental organizations	10	4	1	16
Collaborations with industry or corporate partners	19	1	0	10

The least common responses to the question about the primary motivation to collaborate on research projects with colleagues from diverse backgrounds or institutions were international exposure (2%) and incentives from employers (2%). The most prevalent responses were networking and professional growth (23%) and intellectual curiosity (21%) (refer to Figure 3). All is true for physical sciences.




Figure 3 – Key motivation to collaborate on research projects

Regarding the criteria considered when selecting a journal for manuscript submission (refer to Table 5), the majority of respondents across all four categories prioritize the journal's reputation and impact factor. The least important criteria for academics of physical sciences was Journal publishing in Russian/Kazakh.

Table 5 – Criteria to consider when choosing a journal for the submission of a manuscript

Subject area broad	Physical sciences	Medicine	Life Sciences	Social Sciences
Reputation of the journal	93	10	8	77
Likelihood of acceptance	33	8	6	48
Journal publishing in Russian/Kazakh	7	8	2	17
Opportunity to reach specialist audience	23	9	0	18
International character of the journal	57	9	5	44
Short time between submission and publication	21	4	4	25
Journal impact factor (JIF)	97	9	10	78
Open access	21	5	6	14

The examination of the research landscape in Kazakhstan within the domain of physical sciences reveals several noteworthy insights and trends. This discussion section aims to delve into the implications of the findings, address the challenges and opportunities identified, and offer recommendations for future research endeavors and policy formulation.

One key observation from the survey data is the prominence of collaborations among academics within and beyond the borders of Kazakhstan. The high importance attributed to collaborations with academics in Western countries underscores the value of publishing research in international journals and using an internationally recognized language. This practice enables the dissemination of work at a global level. Another discovery regarding the selection criteria for publishing in journals further reinforces this argument. Researchers in the physical sciences emphasize the significance of the Journal Impact Factor (JIF) and the reputation of the journal the most while placing less emphasis on journals publishing in Russian or Kazakh languages. Furthermore, the significant emphasis on collaborations with academics from the respondent's institution, other institutions of Kazakhstan and post-Soviet countries suggests a broader regional integration and cooperation in scientific endeavors, which can foster networking and professional growth. However, the data also indicate a relatively lower emphasis on collaborations with government or non-governmental organizations among academics in the physical sciences. This finding may reflect the current funding landscape in Kazakhstan, where funding opportunities from governmental or non-governmental bodies may be constrained or less available in comparison to collaborations within close academic circles or across post-Soviet nations.

Another notable aspect of the research landscape is the demographic distribution of academic staff, namely concerning age groups. The observation of fewer individuals aged younger than 30 and those aged 60 or older suggests potential challenges related to workforce sustainability and knowledge transfer. Additionally, the survey results shed light on negative working conditions prevalent in the physical sciences sector, notably including low salaries and excessive workloads. These factors have the potential to discourage younger individuals from pursuing careers in the field of physical sciences. Similarly, the limited access to high-performance computing facilities highlights potential opportunities for infrastructure development and resource allocation to bolster research activities in this area.

Moving forward, several recommendations can be proposed to enhance the research landscape in Kazakhstan for the physical sciences. Strengthening collaboration networks, both within the country and across borders, could foster interdisciplinary research initiatives and facilitate knowledge exchange. Moreover, investment in research infrastructure, including high-performance computing facilities, and support for early-career researchers could bolster research capacity and innovation in the field.

Conclusion

In conclusion, this study provides a comprehensive examination of the research landscape within the physical sciences domain in Kazakhstan, shedding light on various aspects that influence research activities and outcomes. Through the analysis of survey data, several key insights have emerged, underscoring both the strengths and challenges within the research community.

The emphasis on international collaborations, particularly with Western academics, underscores the importance of global engagement for research visibility and reputation. However, the relatively lower priority given to collaborations with governmental or non-governmental organizations suggests potential limitations in accessing external funding sources. Adverse working conditions, such as low salaries and excessive workloads, may deter young researchers, posing a threat to the future workforce. Addressing these issues requires policy interventions to improve working conditions and financial support. Disparities in resource access, particularly in high-performance computing facilities, highlight the need for infrastructure development.

In summary, this study provides valuable insights into the current state of the research landscape within the physical sciences domain in Kazakhstan. By addressing the identified challenges and building upon existing strengths, Kazakhstan has the potential to emerge as a significant player in the global scientific arena, advancing knowledge and driving innovation for the benefit of society.

Information on funding

The article was prepared as part of a scientific study on the topic «Managing scientific activities in Kazakhstan in the face of modern challenges: publication activity, bibliometric indicators, commercialization of the results of scientific activity» (under a grant from the Science Committee of the Ministry of Science and Higher Education of the Republic of Kazakhstan; IRN AP19678073).

REFERENCES

1 Pusser B., Marginson S., University Rankings in Critical Perspective. The Journal of Higher Education, 2013, vol. 84, no. 4, pp. 544–568. https://doi.org/10.1353/jhe.2013.0021

2 Brekke T., What Do We Know about the University Contribution to Regional Economic Development? A Conceptual Framework. International Regional Science Review, 2021, vol. 44, no. 2, pp. 229–261. https://doi.org/10.1177/0160017620909538

3 Amirbekova D., Kuanysh A., Kussaiyn M., and Narbaev T. Research and Economic Development of a Country: Young Scientists Perspective. Bulletin of the Kazakh University of Economics, Finance and International Trade, 2022. 10.52260/2304-7216.2022.2(47).11.

4 Denisova O.K., Problemy Formirovaniya Intellektual'nogo Potentsiala Natsii Kak Uslovie Razvitiya Ekonomiki Znaniy Strany. https://articlekz.com/article/13290.

5 Agasisti T., Barra C., and Zotti R. Research, Knowledge Transfer, and Innovation: The Effect of Italian Universities' Efficiency on Local Economic Development 2006−2012(2019). https://onlinelibrary.wiley.com/doi/full/10.1111/jors.12427.

6 Chankseliani M., Lovakov A., and Pislyakov V. A big picture: bibliometric study of academic publications from post-Soviet countries. Scientometrics, 2021, vol. 126, pp. 8701–8730. https://doi.org/10.1007/s11192-021-04124-5.

7 Narbaev T., Amirbekova D., Sabi D., and De Marco A. Content, network, and density analysis of the global and Kazakhstani literature on scientometrics, Bulletin Of The Karaganda University, ECONOMY Series, 2021, vol. 3, no.103, pp. 82–85.

8 Lovakov A., Chankseliani M., and Panova A. Universities vs. research institutes? Overcoming the Soviet legacy of higher education and research. Scientometrics, 2022, vol. 127, pp. 6293–6313. https://doi.org/10.1007/s11192-022-04527-y.

9 Chankseliani Maia. International development higher education: Looking from the past, looking to the future. Oxford Review of Education. 10.1080/03054985.2022.2077325 (2022).

10 Aranguren M.J., Magro E. How Can Universities Contribute to Regional Competitiveness Policy-Making? Competitiveness Review., 2020, vol. 30, no. 2, pp. 101–117. https://doi.org/10.1108/CR-11-2018-0071.

11 Freitas I.M.B., Marques R.A., and Silva E.M.D.P.E., University–Industry Collaboration and Innovation in Emergent and Mature Industries in New Industrialized Countries. Research Policy, 2012, vol. 42, no. 2, pp. 443–453.

12 Mathews John A., Hu Mei-Chih, Enhancing the Role of Universities in Building National Innovative Capacity in Asia: The Case of Taiwan, World Development, 2007, vol. 35, no. 6, pp. 1005–1020. https://EconPapers.repec.org/RePEc:eee:wdevel:v:35:y:2007:i:6:p:1005-1020.

13 Alibekova G., Tleppayev A., Medeni T.D., and Ruzanov R., Determinants of Technology Commercialization Ecosystem for Universities in Kazakhstan, Journal of Asian Finance, Economics and Business, 2019, vol. 6, no. 4, pp. 271–279.

14 Aruzhan S., Farida A., Alibekova G., Tleppayev A., and Medeni T. Econometric Evidence of the Effectiveness of Different R&D Funding Sources, International Journal of Economic Perspectives, 2016, vol.10, no. 4, pp. 317–330.

15 Amirbekova D., Kussaiyn M., Gafu G., and Narbaev T. University Science and Economic Growth: Review of Kazakhstan's University Science Publications in the Scopus Database in 1991–2022, Bulletin of the Kazakh University of Economics, Finance and International Trade, 2023, vol. 3, no. 52. 10.52260/2304-7216.2023.3(52).28.

16 OECD, Higher Education in Kazakhstan 2017, Reviews of National Policies for Education. OECD Publishing, Paris, 2017. https://doi.org/10.1787/978926.

17 Harzing Anne-Wil, Giroud Axèle. The competitive advantage of nations: An application to academia. Journal of Informetrics, 2014, vol. 8, no. 1, pp. 29–42.

18 Miao L., Murray D., Jung WS. et al. The latent structure of global scientific development, Nat Hum Behav, 2022, vol. 6, pp. 1206–1217. https://doi.org/10.1038/s41562-022-01367-x.

19 Kozlowski J., Radosevic S., Ircha D. History matters: the inherited disciplinary structure of the post-communist science in countries of central and eastern Europe and its restructuring, Scientometrics, 1999, vol. 45, pp. 137–166.

20 Radosevic S., Yoruk E. Are there global shifts in the world science base? Analysing the catching up and falling behind of world regions. Scientometrics, 2014, vol. 101, pp. 1897–1924. https://doi.org/10.1007/s11192-014-1344-1.

[1,2]*Амирбекова Д.,
PhD, ORCID ID: 0000-0002-7801-1629,
*e-mail: d.amirbekova@kbtu.kz
[1]Ли Е.,
магистр, ORCID ID: 0009-0004-1365-4297,
e-mail: yelena.li@alumni.nu.edu.kz

[1]Қазақстан-Британ техникалық университеті, 050000, Алматы қ, Қазақстан
[2]Northwestern University, Эванстон, Иллинойс, Америка Құрама Штаттары

ЗЕРТТЕУ ЛАНДШАФТТАРЫН ТАЛДАУ: ҚАЗАҚСТАННЫҢ ФИЗИКА ҒЫЛЫМДАРЫНДАҒЫ ЕРЕКШЕЛІКТЕРІН АНЫҚТАУ

Аңдатпа

Бұл мақала Қазақстанның академиялық қауымдастығындағы зерттеу ландшафтына сауалнама деректері негізінде жан-жақты талдау жасайды. Әртүрлі университеттердің 265 зерттеушісі мен ғалымдарының жауаптарына сүйене отырып, зерттеу төрт түрлі пәндік саладағы зерттеулердің терең демографиялық

профильдері мен сипаттамаларын ашады. Пәндердің кең спектрін қамти отырып, физикалық ғылымдардың сипаттамалары мен тенденцияларына ерекше назар аударылады. Сауалнама Қазақстандағы физика ғылымдарының зерттеу ландшафтын зерттейді, ол халықаралық ынтымақтастыққа, әсіресе батыстық ғалымдармен бірлескен зерттеулерді арттыруға бағытталған. Зерттеу мәселесіне үкіметтік немесе үкіметтік емес ұйымдармен серіктестікке шектеулі көңіл бөлу, қолайсыз еңбек жағдайлары және ресурстарға, әсіресе өнімділігі жоғары есептеу құралдарына қол жетімділіктің теңсіздігі жатады. Бұл зерттеу елдегі академиялық зерттеулердің қазіргі жағдайы туралы терең түсінік береді және стратегиялық жоспарлау, саясатты әзірлеу, болашақ ғылыми жобаларда қолдануға болатын нақты перспективаны ұсынады.

Тірек сөздер: зерттеу белсенділігі, ғылым, қазақстандық университеттер, жарияланым белсенділігі, ғылымды дамыту, ынтымақтастық, физика ғылымдары.

[1,2]*Амирбекова Д.,
PhD, ORCID ID: 0000-0002-7801-1629,
*e-mail: d.amirbekova@kbtu.kz
[1]Ли Е.,
магистр, ORCID ID: 0009-0004-1365-4297,
e-mail: yelena.li@alumni.nu.edu.kz

[1]Казахстанско-Британский технический университет, 050000, г. Алматы, Казахстан
[2]Northwestern University, Эванстон, Иллинойс, США

ИЗУЧЕНИЕ ИССЛЕДОВАТЕЛЬСКИХ ЛАНДШАФТОВ: ВЫЯВЛЕНИЕ ОСОБЕННОСТЕЙ В ФИЗИЧЕСКИХ НАУКАХ КАЗАХСТАНА

Аннотация

Данная статья представляет всесторонний анализ исследовательского ландшафта в академическом сообществе Казахстана на основе данных опроса. Основываясь на ответах, полученных от 265 исследователей и ученых из различных университетов, исследование раскрывает глубокие демографические профили и характеристики исследований в четырех различных предметных областях. Охватывая широкий спектр дисциплин, особое внимание уделяется характеристикам и тенденциям в области физических наук. Опрос изучает исследовательский ландшафт физических наук в Казахстане, раскрывая фокус на международных коллаборациях, особенно с западными учеными, с целью повышения видимости исследований. Проблемы включают ограниченное внимание к партнерству с правительственными или неправительственными организациями, неблагоприятные условия труда и неравенство в доступе к ресурсам, особенно в высокопроизводительных вычислительных средствах. Это исследование предоставляет глубокое понимание текущего состояния академических исследований в стране и предлагает детальную перспективу, которая может быть использована при стратегическом планировании, разработке политики и будущих исследовательских проектах.

Ключевые слова: исследовательская активность, наука, казахстанские университеты, публикационная активность, развитие науки, сотрудничество, физические науки.

Appendix

№	Name of the institution
1	Nazarbayev University
2	Al Farabi Kazakh National University
3	Kazakh-British Technical University
4	Satbayev University
5	Karaganda Industrial University
6	Buketov Karagandy University
7	L.N. Gumilyov Eurasian National University
8	Astana Medical University
9	Kazakh National Medical University
10	Abai Kazakh National Pedagogical University
11	Sh.Ualikhanov Kokshetau University
12	Karaganda University of Kazpotrebsoyuz
13	International Information Technology University
14	Abylkas Saginov Karaganda Technical University
15	Innovative University of Eurasia
16	KIMEP University
17	Esil University
18	Astana International University

Article submission date: 15.05.2024

UDC 661.183.2
IRSTI 81.09.03

https://doi.org/10.55452/1998-6688-2024-21-3-236-247

[1]Aimaganbetov K.,
PhD, ORCID ID: 0000-0001-6367-9135, e-mail: k.aimaganbetov@sci.kz
[1,2]Abdrakhmanov K.,
PhD, ORCID ID: 0000-0002-7387-7191, e-mail:kairat.amangeldyuly@gmail.com
[3]Akatan K.,
PhD, ORCID ID: 0000-0002-3172-623X, e-mail: ahnur.hj@mail.ru
[3]Kuanyshbekov T.,
PhD, ORCID ID: 0000-0002-2336-3678, e-mail: kuanyshbekov_17@mail.ru
[1]Nurlan Almas,
PhD, ORCID ID: 0009-0009-7873-5457, e-mail: nurlanalmasov@gmail.com
[1]Kurbanova B.,
Researcher, ORCID ID: 0000-0003-0928-521X, e-mail: bayan.kurbanova@nu.edu.kz
[4]*Kemelbekova A.,
PhD, ORCID ID: 0000-0003-4813-8490, *e-mail: a.kemelbekova@sci.kz
[5]Tatishvili G.,
ORCID ID: 0009-0005-2000-0707, e-mail: tati@iice.ge

[1]Institute of Hydrogen Energy, International Science Complex Astana,
Astana 010000, Kazakhstan
[2]Higher School of Natural Sciences, Astana International University,
Astana 010000, Kazakhstan
[3]Sarsen Amanzholov East Kazakhstan University,
Ust-Kamenogorsk 070000, Kazakhstan
[4]Satbayev University, The Institute of Physics and Technology,
Almaty 050000, Kazakhstan
[5]Tbilisi State University (IICE of TSU), 0186, Tbilisi, Georgia

STUDY THE ELECTRICAL PROPERTIES OF GRAPHENE OXIDE – NANOCELLULOSE COMPOSITE

Abstract

This study investigates the electrical properties of a graphene oxide (GO) and nanocellulose (NC) composite using impedance spectroscopy, complemented by thorough characterization through Fourier-transform infrared spectroscopy (FTIR), X-ray photoelectron spectroscopy (XPS), Raman spectroscopy, and scanning electron microscopy (SEM). FTIR analysis revealed characteristic peaks corresponding to functional groups present in both GO and NC, providing insights into their chemical composition. XPS spectra exhibited distinctive peaks indicative of carbon and oxygen bonding states, elucidating the surface chemistry of the materials. Raman spectroscopy provided information on the structural order and defects within the samples, particularly highlighting the graphitic structure of GO. SEM images revealed the morphological features of the composite membrane, showcasing the distribution of NC particles and structural modifications induced by their incorporation. Impedance spectroscopy was utilized to investigate the electrical conductivity of the GO-NC composite. Results indicated a temperature-dependent behavior, with an increase in conductance observed as the temperature rose within the operational range of fuel cells. Remarkably, the addition of NC did not significantly alter the conductive behavior of the composite, suggesting compatibility and stability. In summary, this comprehensive characterization using multiple analytical techniques offers valuable insights into the electrical properties of the GO-NC composite. The findings suggest its potential for various applications requiring enhanced electrical conductivity, particularly in fuel cell technology.

Key words: Proton Exchange Membrane, Graphene Oxide, Nanocellulose, Membrane Electrode Assembly, Composite, Impedance Spectroscopy.

Introduction

In recent years, the scientific community has been captivated by the extraordinary properties of graphene, graphene oxide (GO), and other carbon-based materials. These materials exhibit a plethora of unique characteristics, including exceptional physical-mechanical attributes, electronic properties, high thermal conductivity, hardness, and strength, along with remarkable adsorption capabilities [1–3]. Particularly noteworthy is the widespread utilization of graphene oxide membranes in the fabrication of sensors and supercapacitors sensitive to environmental factors such as moisture, temperature, and organic gases.

Graphene oxide, derived from graphite, possesses a layered structure enriched with diverse oxygen-based functional groups, distinguishing it from pristine graphene. Historically, the synthesis of graphene oxide can be traced back to the 1859 work of Brodie, who chemically treated graphite to produce monolayer sheets of graphene oxide. Since then, various methods for synthesizing GO have been developed, with the modified Hammer method emerging as the most prevalent due to its efficiency [2–5].

Activated carbon serves as a pivotal raw material for the synthesis of graphene oxide, owing to its cost-effectiveness, high adsorption capacity, and ample surface area. Despite the universal appeal of GO, its susceptibility to structural instability in humid environments poses a significant challenge. Consequently, researchers have embarked on extensive modification efforts to enhance the stability and functionality of graphene oxide through chemical treatments with substances like hydrazine hydrate, dimethylhydrazine, hydroquinone, and $NaBH_4$ [4–9].

The recent surge in research endeavors has focused on the development of novel nanocomposites by integrating graphene oxide with nanocellulose. Nanocellulose, derived from natural cellulose, possesses remarkable physical, chemical, biological, magnetic, electrical, and optical properties at the nanoscale [7–14]. The synthesis of nanocellulose involves several stages, including the extraction of extractives/hemicellulose, separation of cellulose unit fibrils, and solvent removal, resulting in a material akin to graphene in terms of size, surface area, mechanical and chemical properties, crystallinity, biodegradability, and renewability.

The combination of nanocellulose with graphene oxide holds tremendous potential for the development of functional hybrid composites, offering enhanced mechanical reinforcement, biocompatibility, and environmental sustainability. Moreover, graphene oxide membranes have emerged as promising candidates for water purification applications, demonstrating superior sheet structure, efficient separation, and flexible fabrication methods [8–15]. Multilayer graphene oxide membranes have been shown to effectively trap water contaminants, facilitating rapid water molecule flow with minimal friction between layers.

The integration of carboxylmethylcellulose (CMC) into graphene oxide matrices further expands the scope of potential applications, leveraging CMC's biocompatible and biodegradable nature, along with its excellent film-forming properties [13–24]. The synergistic combination of graphene oxide and carboxylmethylcellulose offers opportunities for tailored functionalization, improved mechanical strength, flexibility, and stability, making it a promising candidate for various electronic devices and sensors.

In this work, we aim to investigate the electrical properties of the graphene oxide–carboxylmethylcellulose composite using impedance spectroscopy. By elucidating the charge transport mechanisms, dielectric properties, and interfacial phenomena within the composite material, we seek to contribute to the advancement of graphene-based materials for diverse technological applications. Through interdisciplinary research at the intersection of nanotechnology, materials science, and electrical engineering, we aspire to unlock the full potential of graphene oxide composites for addressing pressing societal challenges and fostering sustainable technological innovation.

Materials and methodology

Two distinct samples, comprising graphene oxide (GO) and graphene oxide with nanocellulose (GO+NC), were synthesized utilizing the Hammer method, where thickness of GO is 18.03-23.5 micron, while the thickness of GO+NC (1/1) is 12.36 micron. The morphology of the synthesized samples was examined using a SEM Crossbeam 540 research instrument, with the results depicted in Figure 1A-D.

Further characterization of the samples involved infrared (IR) spectroscopy, conducted utilizing a Nicolet iS10 IR Fourier spectrometer (Figure 2A), and Raman spectroscopy (Figure 2B). These spectroscopic techniques provided insights into the chemical composition and structural properties of the synthesized materials.

Subsequently, X-ray photoelectron spectroscopy (XPS) was employed to analyze the spectra of the GO and GO+NC samples, revealing variations in binding energy, as illustrated in Figure 3 (GO: 280-290 eV, GO+NC: 290-300 eV).

To investigate the electrical characteristics of the samples, impedance spectroscopy was employed across various temperature ranges. The experimental setup utilized an HF_2 Impedance Spectroscopy system from Zurich Instruments. To ensure reliable electrical contact, a copper element was deposited onto the surface of each sample via magnetron sputtering, with a plasma power of 40 W and a deposition time of 30 minutes. Impedance measurements were conducted at a sinusoidal voltage amplitude of 50 mV, spanning a frequency range from 10 Hz to 1 MHz.

The obtained impedance spectroscopy data, depicted in Figure 4, provided valuable insights into the electrical properties of the graphene oxide–carboxylmethylcellulose composite. The measured impedance spectra facilitated the analysis of charge transport mechanisms, dielectric properties, and interfacial phenomena within the composite material, thereby contributing to a comprehensive understanding of its electrical behavior.

Overall, this methodology encompassed a series of experimental techniques aimed at characterizing the synthesized graphene oxide–carboxylmethylcellulose composite and elucidating its electrical properties through impedance spectroscopy. Through systematic analysis and interpretation of the obtained data, we aimed to advance the understanding of this composite material and its potential applications in various technological domains.

Results and discussion


Figure 1 presents cross-sectional scanning electron microscope (SEM) images (Figure 1A, B) showcasing the structural characteristics of both graphene oxide (GO) and graphene oxide with nanoclay (GO+NC) samples. In terms of thickness, the measurements indicate a range between 18.03 to 23.5 microns for GO and a slightly reduced thickness of 12.36 microns for GO+NC [25]. This reduction in thickness hints at a potential compaction effect induced by the incorporation of nanoclay into the composite membrane [25].

Analyzing the cross-SEM images of the GO/NC samples reveals distinct features, notably the presence of compact lamellar structures compared to the initial GO membrane. The inclusion of nanoclay seems to contribute to the densification of the membrane structure, leading to enhanced compactness. Furthermore, a comparative assessment between the surface morphologies of the original GO and GO/NC samples highlights significant differences.

In particular, the SEM images depict the presence of small nanoclay particles dispersed throughout the GO matrix in the GO/NC samples. Additionally, there are observable surface wrinkles in the GO/NC samples, suggesting some degree of aggregation. These surface features indicate a structural modification induced by the incorporation of nanoclay, altering the surface morphology of the composite membrane.

The presence of nanoclay particles and the observed surface alterations signify the successful integration of nanoclay into the GO matrix. The slight aggregation observed may be attributed to

the interaction between GO and nanoclay particles, leading to localized clustering. Overall, the SEM analysis provides valuable insights into the structural characteristics of GO/NC composite membranes, highlighting the impact of nanoclay incorporation on membrane morphology and structure.



(A) (B)

(C) (D)

Figure 1 – Cross- and top-SEM images of GO (A, C) and GO+NC (B, D) samples

The chemical structure of the samples was meticulously examined through Fourier-transform infrared spectroscopy (FTIR), Raman spectroscopy, and X-ray photoelectron spectroscopy (XPS). Each technique provides unique insights into the molecular composition and bonding characteristics of the materials under study.

In the case of nanoclay (NC), FTIR analysis revealed characteristic peaks at specific wavenumbers: 3300 cm^{-1} corresponding to the stretching vibrations of O-H bonds, 1650 cm^{-1} representing asymmetric stretching vibrations of C=O bonds, 1411 cm^{-1} associated with the bending vibration of C-H bonds, 1344 cm^{-1} indicating the bending vibration of C-O-C bonds, and 1004 cm^{-1} attributed to specific structural features [26]. These peaks provide crucial information about the molecular structure and functional groups present in NC.

On the other hand, pure graphene oxide (GO) exhibited distinct spectral features in its FTIR spectrum. Strong bands were observed at 3338 cm^{-1} corresponding to O-H stretching vibrations, 1721 cm^{-1} indicative of C=O stretching vibrations, 1610 cm^{-1} representing C=C stretching vibrations, and 1004 cm^{-1} associated with C-O-C bending vibrations [27–29]. These characteristic peaks elucidate the chemical composition and bonding configuration of GO.


Upon combining GO with NC, FTIR analysis of the composite membrane unveiled a spectrum with additional peaks and altered intensities. In the wavelength range of 3600–3000 cm^{-1}, prominent O-H stretching vibrations were observed, indicating the presence of hydroxyl groups. A peak at 1610 cm^{-1} suggested the existence of aromatic rings, while signals at 1249cm^{-1} and 1054 cm^{-1} were

attributed to C-O bonds, including epoxy and alkoxy groups, respectively. Notably, new ether bonds (C=O) emerged at 1715 cm^{-1}, indicating a chemical interaction between GO and NC [30, 31].

Raman spectroscopy complemented the FTIR analysis by providing information about the structural order and defects within the samples. XPS, on the other hand, offered insights into the elemental composition and chemical states of the surface atoms. Through the combination of these analytical techniques, a comprehensive understanding of the chemical structure and bonding characteristics of the GO/NC composite membrane was achieved, laying the foundation for further elucidating its properties and potential applications.

In a typical Raman spectrum (Figure 2B) of graphene oxide (GO), a prominent G band is discernible. This G band manifests as a peak at 1605 cm^{-1}, representing the E_{2g} phonon of the sp^2 carbon atoms, indicative of the graphitic structure. Additionally, a characteristic D band appears at 1353 cm^{-1}, corresponding to the disorder-induced point phonon K absorption mode of A_{1g} symmetry. These spectral features are crucial for assessing the structural integrity and quality of GO materials.

Remarkably, upon comparison of the Raman spectra of GO and GO+NC samples, no noticeable difference in the Raman shift was observed. This lack of distinction implies that the incorporation of nanoclay (NC) did not induce significant alterations in the structural properties of GO as detected by Raman spectroscopy. The consistent Raman features suggest that the introduction of NC did not introduce detectable changes in the graphitic structure or the degree of disorder within the GO matrix.



(A) (B)

Figure 2 – FTIR (a) and Raman spectra (b) of GO, NC and NC+GO samples

The absence of discernible shifts in the Raman peaks between GO and GO+NC samples implies that the addition of nanoclay did not induce substantial structural modifications at the molecular level. This finding underscores the compatibility of nanoclay with the GO matrix, suggesting a stable composite formation without significant disturbance to the intrinsic properties of GO. Overall, Raman spectroscopy provides valuable insights into the structural characteristics and integrity of GO and its composites, facilitating a comprehensive understanding of their properties and potential applications.

Figure 3 presents both high and low-resolution X-ray photoelectron spectroscopy (XPS) spectra of nanoclay (NC), graphene oxide (GO), and their composite (NC-GO) samples, offering valuable insights into their elemental composition and chemical bonding states.

In the low-resolution XPS spectra (Figure 3A), characteristic signals of carbon (C 1s) at 284.6 eV and oxygen (O 1s) at 531.5 eV are evident across all samples. These signals serve as primary indicators of the presence of carbonaceous and oxygen-containing functional groups, respectively, in the analyzed materials.




Figure 3 – General XPS spectra (A) and high-resolution C 1s spectra of NC(B), GO(C) and GO+NC(D) samples

Further analysis through high-resolution XPS spectra of NC reveals distinctive features in the C 1s region (Figure 3B). The spectrum exhibits Gaussian peaks fitted with three components centered at 284.6 eV, 286.3 eV, and 287.6 eV, corresponding to carbon-carbon (C-C/C-H), C-O, and C=O groups, respectively. These peaks elucidate the chemical environments and bonding configurations of carbon atoms within the NC structure.

Moving to the high-resolution XPS spectrum of GO (Figure 3C), the C 1s peak can be deconvoluted into three discernible components centered at 284.3 eV, 286.6 eV, and 288.2 eV. These peaks are attributed to sp^2 carbon (C_{sp^2}), C-O, and C=O bonds, respectively. The presence of these functional groups is consistent with the typical chemical composition of graphene oxide.


Upon analyzing the C 1s spectra of the GO-NC composite (Figure 3D), a complex pattern emerges. Three main chemical environments of carbon are observed: a dominant peak at 286.8 eV corresponding to C-O bonds, indicating the presence of oxygen functional groups; a peak at 284.7 eV attributed to C-C bonds, suggesting the presence of graphitic carbon; and a third peak around 287.7 eV indicative of O-C-O bonds, likely originating from carboxyl groups. Additionally, a minor fraction at approximately 289 eV is detected, suggesting the emergence of carboxyl groups following the modification process.

These XPS spectra provide detailed information about the chemical composition and bonding states of carbon and oxygen within the analyzed samples. The distinctive peaks and their relative


intensities offer insights into the surface chemistry and structural modifications induced by the incorporation of nanoclay into graphene oxide. Such characterization is crucial for understanding the interactions and compatibility between the constituents in composite materials, aiding in the optimization of their properties for various applications ranging from catalysis to energy storage.

Figure 4 illustrates the disparity in impedance spectroscopy between graphene oxide (GO) and GO+NC (graphene oxide with nanoclay) samples, shedding light on their electrical properties. Additionally, the temperature dependence of these research samples was investigated, unveiling intriguing insights into their conductive behavior under varying thermal conditions.

The impedance spectroscopy data reveals distinct characteristics between GO and GO+NC samples. Notably, as depicted in Figure 4, the conductance of both materials exhibits a temperature-dependent behavior. Interestingly, the conductance of graphene oxide appears comparable to that of GO+NC across different temperature regimes. With increasing temperature, the conductance of both samples demonstrates an upward trend. This observation suggests that temperature plays a significant role in enhancing the electrical conductivity of these materials.



(A)



(B)

Figure 4 – Impedance Spectroscopy data for (A) GO, and (B) GO + NC

Furthermore, the relevance of these findings in the context of fuel cell applications becomes apparent through empirical studies. The operating temperature range of fuel cells typically falls within 300-345 K, with an optimal temperature of around 350 K. The conducted research reveals that the conductance of both graphene oxide and GO+NC samples experiences an increase within this temperature range. Specifically, the conductance elevates from 10^{-7} to 10^{-6} S/cm^2 as the temperature rises. This augmentation in conductance is particularly promising for fuel cell applications, as it suggests improved electrical conductivity at the operational temperatures of fuel cells.

It's important to note that the frequency range considered in these studies spans from 10 to 10^5 Hz. This frequency range is relevant for assessing the electrical properties of materials under varying conditions, providing valuable insights into their conductivity across different frequencies.

The implications of these findings are significant in the realm of fuel cell technology. Fuel cells rely on efficient ion conduction to facilitate electrochemical reactions, and materials exhibiting high conductance at operational temperatures are highly desirable. The observed increase in conductance with temperature suggests that both graphene oxide and GO+NC hold promise as potential candidates for fuel cell applications.

Moreover, the incorporation of nanoclay into graphene oxide does not appear to significantly alter the temperature-dependent conductive behavior, indicating the compatibility and stability of the composite material. This suggests that the addition of nanoclay may enhance certain properties without compromising the overall electrical conductivity of the composite.

The impedance spectroscopy data coupled with the temperature dependence studies provide valuable insights into the electrical properties of graphene oxide and its composite with nanoclay. The observed increase in conductance with temperature within the operating range of fuel cells highlights the potential suitability of these materials for fuel cell applications, paving the way for further exploration and optimization in this field.

Conclusion

The study focused on investigating the electrical properties of a graphene oxide (GO) and nanocellulose (NC) composite using impedance spectroscopy, complemented by an in-depth analysis of the material's chemical structure and morphology through Fourier-transform infrared spectroscopy (FTIR), X-ray photoelectron spectroscopy (XPS), Raman spectroscopy, and scanning electron microscopy (SEM).

FTIR analysis revealed characteristic peaks corresponding to functional groups present in both GO and NC, providing insights into their chemical composition. Similarly, XPS spectra exhibited distinctive peaks indicative of carbon and oxygen bonding states, elucidating the surface chemistry of the materials. Raman spectroscopy provided information on the structural order and defects within the samples, particularly highlighting the graphitic structure of GO. SEM images revealed the morphological features of the composite membrane, showcasing the distribution of NC particles and structural modifications induced by their incorporation.

Impedance spectroscopy was employed to investigate the electrical conductivity of the GO-NC composite. The results indicated a temperature-dependent behavior, with an increase in conductance observed as the temperature rose within the operational range of fuel cells. Notably, the addition of NC did not significantly alter the conductive behavior of the composite, suggesting compatibility and stability.

Overall, the comprehensive characterization using multiple analytical techniques provided valuable insights into the electrical properties of the GO-NC composite. The findings suggest that the composite holds promise for various applications requiring enhanced electrical conductivity, particularly in the realm of fuel cell technology. Further optimization and exploration of these materials are warranted to unlock their full potential for practical applications.

In conclusion, the study offers a thorough investigation into the electrical properties of the GO-NC composite, providing a foundation for further research and development in this field. The combination of impedance spectroscopy with FTIR, XPS, Raman spectroscopy, and SEM analysis offers a comprehensive understanding of the material's structure, morphology, and electrical behavior. This work contributes to the ongoing efforts to harness the unique properties of graphene-based composites for advanced applications in various industries, including energy storage and conversion.

Acknowledgements: The authors are also grateful to International Science Complex Astana Computing for providing computational resources for this work.

Funding: This work was supported by the Ministry of Science and Higher Education of the Republic of Kazakhstan grant numbers AP14871389 «Development of the scientific basis of nanomembrane fabrication technology for proton separation in a fuel cell».

REFERENCES

1 Yu W., Sisi L., Haiyan Y., Jie L. Progress in the functional modification of graphene/graphene oxide: A review. RSC advances, 2020, vol. 10, no. 26, pp.15328–15345.

2 Han B., Zou Y., Xu G., Hu S., Kang Y., Qian Y., Gu M. Additive stabilization of SEI on graphite observed using cryo-electron microscopy. Energy & Environmental Science, 2021, vol. 14, no. 9, pp. 4882–4889.

3 Li C., Chen X., Shen L., Bao N. Revisiting the oxidation of graphite: Reaction mechanism, chemical stability, and structure self-regulation. ACS omega, 2020, vol. 5, no. 7, pp. 3397–3404.

4 Sharma N., Swami S., Shrivastava V., Nair R., Shrivastava R. Graphene oxide and functionalized graphene oxide: Robust, 2D material as heterogeneous green catalyst for heterocyclic synthesis. Materials today: proceedings, 2021, vol. 43, pp. 3309–3317.

5 Alkhouzaam A., Qiblawey H., Khraisheh M., Atieh M., Al-Ghouti M. Synthesis of graphene oxides particle of high oxidation degree using a modified Hummers method. Ceramics International, 2020, vol. 46, no. 15, pp. 23997–24007.

6 Verma V., Gurnani L., Das A., Kumari N., Dasgupta T., Mukhopadhyay A. Reduced graphene oxides prepared via explosive and non-explosive thermal reduction: Structural evolution, functional properties and reinforcing efficacy. Carbon, 2023, vol. 209, p. 118007.

7 Liang K., Spiesz E.M., Schmieden D. T., Xu A.W., Meyer A.S., Aubin-Tam M.E. Bioproduced polymers self-assemble with graphene oxide into nanocomposite films with enhanced mechanical performance. ACS nano, 2020, vol.14, no.11, pp. 14731–14739.

8 Thomas R., Balachandran M. Luminescence and energy storage characteristics of coke-based graphite oxide. Materials Chemistry and Physics, 2021, vol. 257, p. 123854.

9 Han Z., Xiao X., Qu H., Hu M., Au C., Nashalian A., Chen J. Ultrafast and selective nanofiltration enabled by graphene oxide membranes with unzipped carbon nanotube networks. ACS Applied Materials & Interfaces, 2021, vol. 14, no. 1, pp. 1850–1860.

10 Cha M., Boo C., Song I.H., Park C. Investigating the potential of ammonium retention by graphene oxide ceramic nanofiltration membranes for the treatment of semiconductor wastewater. Chemosphere, 2022, vol. 286, p. 131745.

11 Yang K., Pan T., Hong S., Zhang K., Zhu X., Chen B. Ultrathin graphene oxide membrane with constructed tent-shaped structures for efficient and tunable molecular sieving. Environmental Science: Nano, 2020, vol. 7, no. 8, pp. 2373–2384.

12 Zhang W., Huang Q., Liu S., Zhang M., Liu G., Ma Z., Jin W. Graphene oxide membrane regulated by surface charges and interlayer channels for selective transport of monovalent ions over divalent ions. Separation and Purification Technology, 2022, vol. 291, p. 120938.

13 Keerthi A., Goutham S., You Y., Iamprasertkun P., Dryfe R.A., Geim A.K., Radha B. Water friction in nanofluidic channels made from two-dimensional crystals. Nature communications, 2021, vol. 12, no. 1, p. 3092.

14 Beroual M., Mehelli O., Boumaza L., Trache D., Tarchoun A.F., Derradji M., Khimeche K. Synthesis and characterization of microcrystalline cellulose from giant reed using different delignification processes. Materials Research and Applications: Select Papers from JCH8-2019, 2021, pp. 173–187.

15 Tshikovhi A., Mishra S.B., Mishra A.K. Nanocellulose-based composites for the removal of contaminants from wastewater. International Journal of Biological Macromolecules, 2020, vol. 152, pp. 616–632.

16 Fahma F., Febiyanti I., Lisdayana N., Arnata I.W., Sartika D. Nanocellulose as a new sustainable material for various applications: A reviewArchives of Materials Science and Engineering, 2021, vol. 109, no. 2, pp. 49–64.

17 Kawalerczyk J., Dziurka D., Mirski R., Szentner K. Properties of plywood produced with urea-formaldehyde adhesive modified with nanocellulose and microcellulose. Drvna industrija, 2020, vol. 71, no.1, pp. 61–67.

18 Wijesekara W.I., Gokila S., Gomathi T., Prasad S., Deepa M., & Sudha P.N. New Opportunities and Future Prospects. Nanobiomaterials: Research Trends and Applications, 2023, 314.

19 Zulaikha W., Hassan M.Z., & Ismail Z. Recent development of natural fibre for nanocellulose extraction and application. Materials Today: Proceedings, 2022, no. 66, pp. 2265–2273.

20 Xu T., Du H., Liu H., Liu W., Zhang X., Si C., ... & Zhang K. Advanced nanocellulose- based composites for flexible functional energy storage devices. Advanced materials, 2021, vol. 33, no. 48, p. 2101368.

21 Thomas P., Duolikun T., Rumjit N.P., Moosavi S., Lai C.W., Johan M.R.B., & Fen L.B. Comprehensive review on nanocellulose: Recent developments, challenges and future prospects. Journal of the mechanical behavior of biomedical materials, 2020, no. 110, p. 103884.

22 Ahmed A., Adak B., Faruk M. O., & Mukhopadhyay S. Nanocellulose coupled 2D graphene nanostructures: Emerging paradigm for sustainable functional applications. Industrial & Engineering Chemistry Research, 2021, vol. 60, no. 30, pp. 10882–10916.

23 Xu T., Du H., Liu H., Liu W., Zhang X., Si C. ... & Zhang, K. Advanced nanocellulose- based composites for flexible functional energy storage devices. Advanced materials, 2021, vol. 33, no. 48, p. 2101368.

24 Zhang K., Ketterle L., Järvinen T., Lorite G.S., Hong S., & Liimatainen H. (2020). Self-assembly of graphene oxide and cellulose nanocrystals into continuous filament via interfacial nanoparticle complexation. Materials & Design, 2020, no. 193, p. 108791.

25 Almasov N., Kurbanova B., Kuanyshbekov T., Akatan K., Kabdrakhmanova S. & Aimaganbetov K. Study of the structure and electrical properties of graphene oxide (GO) and graphene oxide+ nanocellulose (GO+ NC). Kompleksnoe Ispolzovanie Mineralnogo Syra= Complex use of mineral resources, 2024, vol. 329, no. 2, pp. 103–109.

26 Ge X., Shan Y., Wu L., Mu X., Peng H., Jiang Y. High-strength and morphology-controlled aerogel based on carboxymethyl cellulose and graphene oxide. Carbohydr. Polym., 2018, no. 197, pp. 277–283.

27 Chen L., Li Y., Du Q., Wang Z., Xia Y., Yedinak E., Lou J., Ci L. High performance agar/graphene oxide composite aerogel for methylene blue removal. Carbohydr. Polym., 2017, no. 155, pp. 345–353.

28 Kuanyshbekov T., Guseinov N., Tolepov Zh., Kurbanova B., Tulegenova M., Akatan K., Kantay N., and Zhasasynov E. Thermally Reduced Graphene Oxide Membranes From Local Kazakhstan Graphite "Ognevsky". ChemistrySelect 2023, no. 8, e202301746.

29 Mengke Zhao, Sufeng Zhang, Guigan Fang, Chen Huang and Ting Wu. Directionally-Grown Carboxymethyl Cellulose/Reduced Graphene Oxide Aerogel with Excellent Structure Stability and Adsorption Capacity. Polymers 2020, no.12, p. 2219. https://doi.org/10.3390/polym12102219.

30 Kuanyshbekov T., Sagdollin Z., Zhasasynov E., Akatan K., Kurbanova B., Guseinov N., Tolepov Z., Kantay N., Beisebekov M. Composite Membrane Based on Graphene Oxide and Carboxymethylcellulose from Local Kazakh Raw Materials for Possible Applications in Electronic Devices. J. Compos. Sci., 2023, no. 7, p. 342. https:// doi.org/10.3390/jcs7080342

31 Kuanyshbekov T.K., Akatan K., Kabdrakhmanova S.K., Nemkaeva R., Aitzhanov M., Imasheva A., Kairatuly E. (2021). Synthesis of graphene oxide from graphite by the hummers method. Oxidation Communications, 2021, 44, no. 2.

[1]Аймағанбетов Қ.,
PhD, ORCID ID: 0000-0001-6367-9135, e-mail: k.aimaganbetov@sci.kz
[1,2]Абдрахманов Қ.,
PhD, ORCID ID: 0000-0002-7387-7191, e-mail:kairat.amangeldyuly@gmail.com
[3]Ақатан Қ.,
PhD, ORCID ID: 0000-0002-3172-623X, e-mail: ahnur.hj@mail.ru
[3]Қуанышбеков Т.,
PhD, ORCID ID: 0000-0002-2336-3678, e-mail: kuanyshbekov_17@mail.ru
[1]Нұрлан Алмас,
PhD, ORCID ID: 0009-0009-7873-5457, e-mail: nurlanalmasov@gmail.com
[1]Курбанова Б.,
Ғылыми қызметкер, ORCID ID: 0000-0003-0928-521X, e-mail: bayan.kurbanova@nu.edu.kz
[4]*Кемелбекова А.,
PhD, ORCID ID: 0000-0003-4813-8490,*e-mail: a.kemelbekova@sci.kz
[5]Татишвили Г.,
ORCID ID: 0009-0005-2000-0707, e-mail: tati@iice.ge

[1]Сутегі энергетикасы институты, «Астана» Халықаралық ғылыми кешені
Астана қ. 010000, Қазақстан
[2] Жаратылыстану ғылымдары жоғары мектебі, Астана Халықаралық университеті,
Астана қ. 010000, Қазақстан
[3] С. Аманжолов атындағы Шығыс Қазақстан университет, ҰҚ ҰҒЗ,
Өскемен қ., 070000, Қазақстан
[4]Сәтбаев университеті, Физика-техникалық институты,
Алматы қ. 050000, Қазақстан
[5]Тбилиси мемлекеттік университеті (ИНХЭ ТМУ), Тбилиси қ., 0186, Грузия

ГРАФЕН ОКСИДІНІҢ – НАНОЦЕЛЛЮЛОЗА КОМПОЗИЦИЯСЫНЫҢ ЭЛЕКТРЛІК ҚАСИЕТТЕРІН ЗЕРТТЕУ

Андатпа

Бұл зерттеу Фурье түрлендіруші инфрақызыл спектроскопия (FTIR), рентгендік фотоэлектрондық спектроскопия (XPS), Раман спектроскопиясы және сканерлеуші электронды микроскопия (SEM) әдістері арқылы мұқият сипатталған импеданс спектроскопиясын қолдана отырып, графен оксиді (ГО) және наноцеллюлоза (НЦ) композицияларының электрлік қасиеттерін зерттейді. FTIR талдауы ГО және НЦ құрамында болатын функционалдық топтарға сәйкес келетін сипаттамалық шыңдарды анықтады, бұл олардың химиялық құрамын түсінуге мүмкіндік берді. XPS спектрлері көміртегі мен оттегінің байланыс күйлерін көрсететін ерекше шыңдарды көрсетті, бұл материалдардың беттік химиясын сипаттауға мүмкіндік берді. Раман спектроскопиясы үлгілердің құрылымдық реті мен ақаулары туралы ақпарат беріп, әсіресе ГО-ның графиттік құрылымын ерекше атап өтті. SEM кескіндері композициялық мембрананың морфологиялық ерекшеліктерін ашып, НЦ бөлшектерінің таралуын және олардың қосылуынан туындаған құрылымдық модификацияларды көрсетті. ГО-НЦ композициясының электр өткізгіштігін зерттеу үшін импеданс спектроскопиясы қолданылды. Нәтижелер температураға тәуелді мінез-құлықты көрсетті: өткізгіштік отын элементтерінің жұмыс диапазонында температураның жоғарылауымен артты. Бір қызығы, НЦ қосу композицияның өткізгіштік қасиеттеріне айтарлықтай әсер етпеді, бұл материалдардың үйлесімділігі мен тұрақтылығын болжайды. Қорытындылай келе, көптеген аналитикалық әдістерді қолдана отырып жасалған бұл жан-жақты зерттеу ГО-НЦ композициясының электрлік қасиеттері туралы құнды мәліметтер береді. Нәтижелер бұл композицияның электр өткізгіштігін арттыруды қажет ететін әртүрлі қолданбаларда, әсіресе отын ұяшықтары технологиясында әлеуетті қолданылуын көрсетеді.

Тірек сөздер: Протон алмасу мембранасы, графен оксиді, наноцеллюлоза, мембраналық электродтарды құрастыру, композит, кедергі спектроскопиясы

[1]Аймағанбетов Қ.,
PhD, ORCID ID: 0000-0001-6367-9135, e-mail: k.aimaganbetov@sci.kz
[1,2]Абдрахманов Қ.,
PhD, ORCID ID: 0000-0002-7387-7191, e-mail:kairat.amangeldyuly@gmail.com
[3]Ақатан Қ.,
PhD, ORCID ID: 0000-0002-3172-623X, e-mail: ahnur.hj@mail.ru
[3]Қуанышбеков Т.,
PhD, ORCID ID: 0000-0002-2336-3678, e-mail: kuanyshbekov_17@mail.ru
[1]Нұрлан Алмас,
PhD, ORCID ID: 0009-0009-7873-5457, e-mail: nurlanalmasov@gmail.com
[1]Курбанова Б.,
Ғылыми қызметкер, ORCID ID: 0000-0003-0928-521X, e-mail: bayan.kurbanova@nu.edu.kz
[4]*Айнагуль Кемелбекова,
PhD, ORCID ID: 0000-0003-4813-8490, *e-mail: a.kemelbekova@sci.kz
[5]Татишвили Г.,
ORCID ID: 0009-0005-2000-0707, e-mail: tati@iice.ge

[1] Институт водородной энергетики, Международный научный комплекс «Астана»,
г. Астана, 010000, Казахстан
[2] Высшая школа естественных наук, Международный университет Астана,
г. Астана, 010000, Казахстан
[3] Восточно-Казахстанский университет им. С. Аманжолова, ННЛКП,
г. Усть-Каменогорск, 070000, Казахстан
[4]Сәтбаев университет, Физика-технический институт,
г. Алматы, 050000, Казахстан
[5]Тбилисский государственный университет (ИНХЭ ТГУ), 0186, г. Тбилиси, Грузия

ИЗУЧЕНИЕ ЭЛЕКТРИЧЕСКИХ СВОЙСТВ КОМПОЗИТА ОКСИД ГРАФЕНА – НАНОЦЕЛЛЮЛОЗА

Аннотация

В этом исследовании электрические свойства композита из оксида графена (ОГ) и наноцеллюлозы (НЦ) изучаются с помощью импедансной спектроскопии, дополненной тщательной характеристикой с помощью инфракрасной спектроскопии с преобразованием Фурье (FTIR), рентгеновской фотоэлектронной спектроскопии (XPS), рамановской спектроскопии и сканирующей электронной микроскопии (SEM). ИК-анализ выявил характерные пики, соответствующие функциональным группам, присутствующим как в ОК, так и в НЦ, что позволило получить представление об их химическом составе. Спектры XPS показали характерные пики, указывающие на состояние углеродных и кислородных связей, что объясняет химический состав поверхности материалов. Спектроскопия комбинационного рассеяния позволила получить информацию о структурном порядке и дефектах в образцах, особенно выделив графитную структуру ОГ. СЭМ-изображения выявили морфологические особенности композитной мембраны, продемонстрировав распределение частиц НЦ и структурные изменения, вызванные их внедрением. Для исследования электропроводности композита ОГ-НЦ была использована импедансная спектроскопия. Результаты показали, что поведение композита зависит от температуры, при этом с повышением температуры в пределах рабочего диапазона топливных элементов наблюдалось увеличение электропроводности. Примечательно, что добавление НЦ существенно не изменило электропроводность композита, что свидетельствует о совместимости и стабильности. Таким образом, эта всесторонняя характеристика с использованием множества аналитических методов дает ценную информацию об электрических свойствах композита ОГ-НЦ. Полученные результаты свидетельствуют о его потенциале для различных применений, требующих повышенной электропроводности, особенно в технологии топливных элементов.

Ключевые слова: протонообменная мембрана, оксид графена, наноцеллюлоза, мембранно-электродный узел, композит, импедансная спектроскопия.

Article submission date: 30.07.2024

UDC 538:958
IRSTI 29.19.16

https://doi.org/10.55452/1998-6688-2024-21-3-248-257

[1]Murzalinov D.,
PhD, ORCID ID: 0000-0001-6519-1969,
e-mail: d.murzalinov@sci.kz
[1]*Kemelbekova A.,
PhD, ORCID ID: 0000-0003-4813-8490,
*e-mail: a.kemelbekova@satbayev.university
[1]Zhapakov R.,
PhD student, ORCID ID: 0000-0002-2570-8190,
e-mail: zharash@mail.ru
[1]Seredavina T.,
Candidate of technical sciences, ORCID ID:0000-0001-9689-160X,
e-mail: t.seredavina@sci.kz
[2]Yelemessov K.,
Professor, ORCID ID: 0000-0001-6168-2787,
e-mail: k.yelemessov@satbayev.university
[1]Begunov M.,
Master, ORCID ID: 0000-0001-5389-0033,
e-mail: begunov028@gmail.com

[1]Satbayev University, The Institute of Physics and Technology, 050013, Almaty, Kazakhstan
[2]Institute of Energy and Mechanical Engineering named after A. Burkitbayev, Satbayev University, 050000, Almaty, Kazakhstan

INVESTIGATION OF VARIOUS MECHANISMS OF RADIATIVE RECOMBINATION OF SILICON NITRIDE AS AN EFFECTIVE WAY TO BROADENING THE PHOTOLUMINESCENCE SPECTRUM

Abstract

The development of devices combining optical and electrical functions based on silicon-containing materials is one of the challenges in microelectronics. By plasma enhanced chemical vapor deposition synthesis and subsequent annealing, silicon nitride samples with both excess silicon and excess nitrogen were formed. The high concentration of Si-H and N-H bonds was determined by Raman spectroscopy in samples before annealing. By the transmission electron microscopy, it was determined that in addition to silicon nitride, silicon clusters were formed in the sample's matrix. The photoluminescence spectra changed significantly for both types of samples during annealing in different gas atmospheres. Heat treatment of samples at 1100 °C after synthesis led to the disappearance of the PL spectrum, and after annealing at 800 °C, photoluminescence increases. It is noted that the highest intensity of photoluminescence was detected after annealing in the air atmosphere and the lowest in the nitrogen. The participation of N centers in recombination processes was confirmed by the method of electron paramagnetic resonance. The different mechanisms of particle interaction leading to photoluminescence and charge storage are considered. Thus, the conditions for the synthesis and annealing of silicon nitride layers are selected to obtain controlled luminescent properties in various spectral ranges.

Key words: silicon nitride, silicon oxide, luminescence, nanoclusters, stoichiometric order.

Introduction

The prospects for the development of silicon photonics are based primarily on the implementation of an optical data transmission system in an integrated circuit [1–2]. Currently, almost all components

of silicon optoelectronics have been created. The complexity of obtaining a working LED based on Si is due to its non-direct-band energy structure. To solve this issue, the formation of Si nanocrystals in various matrices is also applicable. One of the standard methods for obtaining Si nanocrystals is based on the heat treatment of silicon oxide enriched with silicon.

Due to the smaller band gap (~5.3 eV), silicon nitride is a more suitable basis for the development of electroluminescent devices compared to wide-band silicon oxide SiO_2 (8.2 eV) [3]. Silicon nitride has a lower barrier at the cluster/matrix interface and therefore more efficient injection of charge carriers into silicon nanocrystals [4].

However, the silicon nitride matrix also luminesces, and the nature of the radiation is widely discussed. The emissivity of silicon nitride is associated with electronic transitions between the energy levels of defects [5–9]. The main centers of radiation recombination in this case are the K- and N-centers [10]. The K-center level is located close to the middle of the silicon nitride band gap, and the nature of this center is amphoteric (both electrons and holes can be captured). Consequently, electronic transitions are possible both between the valence band and the K-center, and between the K-center and the conduction band.

The levels of the N-centers are located closer to the edges of the bands: the N_2^0 level is ~ 0.5 eV higher than the top of valence band, the N_4^+ level is closer to the bottom of the conduction band. According to some data, their levels may be even below the edge of the valence band [11, 12]. In this case, the centers are inactive in radiative recombination. However, the model mentioned above demonstrates the possibility of a negative transition between the N_2^0 level and the conduction band (3.1 eV) and a transition between the N_4^+ level and the valence band (3.0 eV).

Comparing various mechanisms of energy transfer involving the main centers of silicon nitride - K and N, in particular when emitting light quanta, the efficiency of K centers is obviously higher. By increasing the concentration of K-centers, we increase the capacity of a memory cell. Another mechanism is associated with the localization of a hole in the field of an electron trapped at the K center. Such a structure can retain properties under certain conditions.

In the plasma enhanced chemical vapor deposition (PECVD) process, it is possible to influence the concentration of Si-H and N-H bonds, which, when broken, form structures with uncompensated charge. By changing the annealing modes (atmosphere, temperature, etc.), both silicon clusters and various luminescent centers can be obtained.

In a sample with an excess of silicon, a two-phase structure of silicon nitride and silicon clusters can be formed as a result of synthesis and subsequent annealing. There will probably be several photoluminescence (PL) sources in this system.

The novelty of this study lies in finding conditions for the synthesis and annealing of silicon nitride at which luminescence increases associated with radiative centers, silicon clusters and states in the band tails.

The motivation of the research was the possibility of broadering the PL spectrum of silicon nitride in the implementation of various light-emitting mechanisms.

An important feature of this work is the obtaining of silicon nanoclusters both in silicon nitride samples with an excess of silicon and with an excess of nitrogen.

Thus, considering most materials at the level of interaction of particles with uncompensated charge is a cornerstone in understanding the mechanisms of photoluminescence and many other issues.

Materials and methodology

The Si-rich and N-rich silicon nitride films were deposited on the n-type (100)-oriented Si substrates by plasma-enhanced chemical vapor deposition at 350 °C using a gaseous mixture of silane (SiH_4) and nitrogen (N_2) as precursors. The ratio of reagent gases SiH_4/N_2 was chosen 1/3 for the Si-rich and 1/6 for N-rich silicon nitride films. The pressure in the chamber was maintained at 70 Pa.

The activation energy of the silicon nitride deposition process is approximately 1.8 eV. The deposition rate of silicon nitride usually depends on the concentration of silane and ammonia in the reaction mixture as well as the total pressure in the system [13–17].

Plasma enhanced chemical deposition makes it possible to form films at a very low substrate temperature. This is achieved due to the reaction between gases in a glow discharge. Although the temperature of the electrons in the discharge can reach 105 °C, the sample temperature remains within 100–400 °C. This is undoubtedly important in the manufacture of semiconductor devices, since it does not cause the formation of excessive defects.

Films obtained by PECVD contain a large amount of hydrogen (10–35 $_{at}$%), the concentration of which depends on the parameters of the deposition process [18]. Hydrogen in the films forms a bond with silicon in the form of Si–H and with nitrogen in the form of N–H [19]. Also, plasmochemical silicon nitride contains 0.5–2 $_{at}$% oxygen as an impurity.

In the presented work, the Raman spectra were recorded using a "Nanofinder HighEnd (LOTIS TII)" micro-Raman spectrometer. The studies were carried out at room temperature. The radiation source was a laser with λ = 473 nm. The laser radiation was focused into a spot with a diameter of ~ 1 μm. Diffraction gratings of 600 strokes/mm (spectral resolution 0.01 nm) was used for registration.

Structural-phase transformations in silicon nitride films were studied by TEM on a Hitachi H-800 microscope with an accelerating voltage of 200 keV in the "cross-section" geometry. The resolution of the microscope is 0.2 nm, magnification is 100–600000.

The PL spectra of silicon nitride films in the visible region were recorded using a photomultiplier tube sensitive in the spectral region 200-900 nm (Hamamatsu Company, Japan). A UV He-Cd laser with a wavelength of 325 nm was used to excite photoluminescence in the spectral range of 350-800 nm and an Nd laser with a wavelength of 532 nm was used to excite photoluminescence in the range of 600–900 nm. Transitions between the levels of K and N centers and the level of the conduction band were excited.

EPR spectra were recorded at room temperature using a JES -FA (Jeol) spectrometer and a reference value of Mn(2+)/MgO. The spectra were accumulated four times in order to raise the S/N ratio.

Results and discussion

In this paper, the objects of research are two series of samples of non–stoichiometric silicon nitride with a lower Si concentration in SiN_x – III-10 and with a higher Si concentration in SiN_x – III-13. A thin layer of silicon nitride was deposited on two silicon wafers by PECVD at a substrate temperature of 350 °C, the characteristics of which are presented in Table 1.

Table 1 – Characteristics of silicon nitride layers deposited by PECVD on silicon wafers

Characteristics of the silicon nitride layer	Plate number	
	III-10	III-13
SiH4/N2 ratio	1/6	1/3
Thickness, μm	0,34–0,36	0,3–0,32
Stoichiometric parameter	1,5–1,41	1,13

For heat treatment, furnace annealing was used for 60 minutes in three atmospheres – argon (Ar), nitrogen (N_2) and in air using two temperatures of 800 °C and 1100 °C for both series.

The low synthesis temperature leads to the formation of bonds with hydrogen. Further treatment of the obtained samples at various parameters allows the formation of various structures, including light-emitting ones.

An important condition for the formation of effective light-emitting centers is the presence of hydrogen bonds after synthesis and their subsequent annealing during heat treatment. The formation of Si–H and N–H bonds in the PECVD process was confirmed by Raman spectroscopy. Figure 1 shows the spectrum for a sample with excess nitrogen. As can be seen from the figure, the bands with maxima at 2230 cm^{-1} and 3330 cm^{-1} correspond to fluctuations of Si-H and N–H bonds in the initial sample [20–22]. After heat treatment, these bands are not registered in the spectrum. The disappearance of bands from the spectrum is associated both with the dissociation of these bonds and with an increase in the luminescent background. For a sample with an excess of silicon, the Raman signal from Si–H and N–H bonds was suppressed by a strong luminescence background.




Figure 1 – Raman spectrum for a sample with excess nitrogen

After annealing of the samples, hydrogen-containing bonds are broken and stable light-emitting centers are formed. Their presence was determined by the characteristic peaks in the photoluminescence spectra.

The interaction of particles with uncompensated charge, leads to the formation of clusters. Such structures have a higher intensity of PL than individual particles. To determine the formation of clusters, TEM images of all types of samples were obtained.

Figure 2 shows TEM images of samples with excess silicon and nitrogen, annealed at 800 and 1100 °C. Image analysis indicates the presence of some inhomogeneities in annealed silicon nitride films. As can be seen, nitride films annealed at 800 °C, both with an excess of silicon or nitrogen, contain small contrast inhomogeneities. After annealing at a temperature of 1100 ° C, the uniformity of the structure of the nitride film increases significantly.

In [23] states that silicon nitride films with a high content of silicon, both initial and annealed at T < 650 °C, consist of a mixture of two phases: amorphous silicon nitride with an excess of silicon and with an excess of nitrogen. Only after annealing at T > 800°C, the formation of silicon clusters in a matrix of amorphous silicon nitride was detected. Most possible, the inhomogeneities of the structure are associated with the separation of phases in the film of amorphous silicon nitride into regions with an excess of silicon SiN_x=1.3. Annealing at a temperature of less than 800 °C leads primarily to the brake of weaker Si–H and N–H bonds. It is obvious that the concentration of Si–H bonds is higher in areas enriched with silicon. Consequently, annealing at a relatively low temperature (less than 800 °C) will lead to hydrogen effusion and a decrease in density in these areas. Thus, the lower contrast of the images is probably due to the areas enriched with silicon. Heat treatment at higher temperatures (800–1100 °C) leads to annealing of defects such as broken bonds through their interaction. This mechanism leads to the synthesis of silicon clusters. This, in turn, should lead to smoothing of the heterogeneous structure, which is observed in the TEM images.

The variety of different structures, clusters and particles with uncompensated charge leads to different manifestations of their activity when excited by light.




Figure 2 – TEM micrographs of the «cross-section» geometry of samples annealed in Ar for an hour. Figures a, b – $T_{anneal.}$ = 800 °C; c, d – $T_{anneal.}$= 1100 °C; a, c – a sample with an excess of silicon; b, d – a sample of a series with an excess of nitrogen.

Figure 3 shows the photoluminescence spectra of the two initial samples.





Figure 3 – a – Photoluminescence spectra of initial samples, b – The spectrum for the III-10 series sample decomposed into Gaussians

For the series – III-10 non-stoichiometric SiN_x, a wide peak is observed, which is at around 0.52 relative units, in the range of 580 nm, this is approximately 2.14 eV. The width at half–height is 460-670 nm (2.7–1.85 eV). This spectrum also has a second weak peak – at a wavelength of 410 nm

(3.02 eV), with an intensity of 0.255 rel. units. The peak of the second spectrum of the SiN_x series – III-13 has a lower intensity – 0.17 rel. units and is located at 640 nm (1.94 eV). It is shifted relatively to the first peak in the long-wavelength region. This spectrum has another weak peak – 430 nm (2.88 eV) with a intensity of 0.06 rel. The unit shift of the spectral line to the long-wavelength region indicates a higher Si content in SiN_x series III-13 compared to series III-10.

Figure 4 shows the change in the position of the spectral bands of the III-10 series as a result of annealing in argon compared to the initial one. During heat treatment at 800 °C, the peak of the spectrum becomes sharper, shifts to the short-wave region to a value of 510 nm (2.43 eV) with an intensity of 0.76 rel. units. The width at half-height is 440-610 nm (2.82–2.03). At a temperature of 1100 °C, photoluminescence is significantly extinguished and already amounts to 0.18 rel. units at 640 nm (1.94 eV). The width at half–height is 470–700 (2.64–1.77).



(a) (b)

Figure 4 – a – Photoluminescence spectra of the initial sample and after annealing in argon for series III-10; b – The spectrum of the initial sample of series III-10 decomposed into Gaussians

The energy interval between the K center and the conducting band (CB) is less than that between the N center and CB. Therefore, K centers are more actively involved in radiative recombination. Based on this, methods with increased sensitivity, such as EPR spectroscopy, are needed to determine the properties of N centers.

For the sample of series III-13, after annealing in a nitrogen atmosphere at 800°C (Fig. 5), two lines caused by unpaired electrons were observed in the EPR spectrum. The choice of this sample is due to the highest intensity of PL. Characteristics of the first EPR line: g – factor = 2.00173, width ΔH = 8 G. This line could not be identified.




Figure 5 – EPR spectrum of the III-13 series sample after annealing at 800 °C in a nitrogen atmosphere

Characteristics of the second line: g – factor = 2.0056, width ΔH = 6 G. In [24], a line in the EPR spectrum of amorphous silicon nitride with similar characteristics (g – factor = 2.0057, width ΔH =8.5 G) was attributed to a 2-coordinated nitrogen atom (N-center). Therefore, we can talk about the presence of N-centers in the samples, and the increased luminescence of this sample can be explained by the recombination of carriers in the N-centers.

Conclusion

During the PECVD processes, various light-emitting structures of silicon nitride were formed by changing the SiH_4/N_2 ratio. The Raman spectroscopy method revealed the in-tensive formation of Si-H and N-H bonds, which, upon further annealing, are broken during the formation of light-emitting centers. The synthesis of silicon clusters after annealing of samples with an excess of silicon and nitrogen was determined from TEM images. The mechanisms of cluster formation vary significantly depending on the features of the interaction of particles with uncompensated charge.

The influence of the atmosphere and the temperature of annealing on the efficiency of photoluminescence of the formed layers was determined. During annealing at 1100 °C, the intensity of all samples is significantly reduced, and for initial samples with a higher silicon content, it is completely absent. During annealing at 800 °C, photoluminescence increases.

For each annealing mode, the mechanism of formation of radiative particles is de-termined, as well as their effect on the intensity of PL. Radiative recombination is associated with the presence of K and N centers, silicon clusters, and edge luminescence.

The different silicon content in the initial nitride samples determines the spectral po-sition of the photoluminescence band. The higher silicon content corresponds to the shift of the maximum of the PL band from 580 nm to 640 nm. In our opinion, the radiative re-combination of electrons and holes in this case occurs between states (energy levels) in the tails of the energy bands.

The detected PL bands in the short-wave region can be associated with the formation of Si nanoclusters. An increase in the heat treatment temperature leads to an increase in the size of nanoclusters, which, in turn, leads to a red shift of the photoluminescence bands.

Funding. This research was funded by the Ministry of Science and Higher Education of the Republic of Kazakhstan, (Grant No. BR18574141 titled “Comprehensive multi-purpose program for improving energy efficiency and resource saving in the energy sector and mechanical engineering for the industry of Kazakhstan”).

REFERENCES

1 Pavesi L. Will silicon be the photonic material of the third millenium? Journal of Physics: Condensed Matter, 2003, vol. 15, no. 26, pp. 1169–1196. https:// doi.org/10.1088/0953-8984/15/26/201.

2 Pavesi L. Routes toward silicon-based lasers. Materials Today, 2005, vol. 8, no. 1, pp. 18–25. https:// doi.org/10.1016/s1369-7021(04)00675-3.

3 Liao W., Zeng X., Yao W., & Wen X. Photoluminescence and carrier transport mechanisms of silicon-rich silicon nitride light emitting device. Applied Surface Science, 2015, no. 351, pp. 1053–1059. https:// doi.org/10.1016/j.apsusc.2015.06.050.

4 Lin G.-R., Pai Y.-H., Lin C.-T., Chen C.-C. Comparison on the electroluminescence of Si-rich SiNx and SiOx based light-emitting diodes. Applied Physics Letters, 2010, vol. 96, no. 26, p. 263514. https:// doi.org/10.1063/1.3459144.

5 Green W.M., Rooks M.J., Sekaric L., Vlasov Y.A. Ultra-compact, low RF power, 10 Gb/s silicon Mach-Zehnder modulator. Optics Express, 2007, vol. 15, no. 25, p. 17106. https:// doi.org/10.1364/oe.15.017106.

6 Michel J., Liu J., Kimerling L. C. High-performance Ge-on-Si photodetectors. Nature Photonics, 2010, vol. 4, no. 8, pp. 527–534. https:// doi.org/10.1038/nphoton.2010.157.

7 Canham L.T. Silicon quantum wire array fabrication by electrochemical and chemical dissolution of wafers. Applied Physics Letters, 1990, vol. 57, no. 10, pp. 1046–1048. https:// doi.org/10.1063/1.103561.

8 Lockwood D.J., Pavesi L. Silicon photonics; Springer: Berlin, Germany, 2004, 398 p. https:// doi.org/10.1007/b11504.

9 Myers P., Sailor M., J. Porous Silicon in Practice. Preparation, Characterization and Applications; Chromatographia, 2013, 721. doi:10.1007/s10337-013-2453-3.

10 Komarov F., Vlasukova L., Parkhomenko, I., Milchanin, O., Mudryi, A., Togambaeva, A., Korolik, O. Raman study of light-emitting SiNx films grown on Si by low-pressure chemical vapor deposition. Thin Solid Films, 2015, vol. 579, pp. 110–115. https:// doi.org/10.1016/j.tsf.2015.03.003.

11 Adams A.C., Alexander F.B., Capio C.D., & Smith T.E. Characterization of plasma- deposited silicon dioxide. Journal of the Electrochemical Society, 1981, vol. 128, no. 7, pp. 1545. https:// doi.org/10.1149/1.2127680.

12 Kistner J., Chen X., Weng Y., Strunk H.P., Schubert M.B., Werner J.H. Photoluminescence from silicon nitride–no quantum effect. Journal of Applied Physics, 2011, vol. 110, no. 2, p. 023520. https:// doi.org/10.1063/1.3607975.

13 Novikov Y.N., & Gritsenko V.A. Charge transport mechanism and amphoteric nature of traps in amorphous silicon nitride. Journal of Non-Crystalline Solids, 2020, vol. 544, p. 120186. https:// doi.org/10.1016/j.jnoncrysol.2020.120186.

14 Gritsenko V.A., Perevalov T.V., Orlov O.M., Krasnikov G.Ya. Nature of traps responsible for the memory effect in silicon nitride, Appl. Phys. Lett, 2016, 109, p. 062904. https://doi.org/10.1063/1.4959830.

15 Kang G., Lee D., Lee K., Kim J., Han S. First-principles study on the negative-U behavior of K centers in amorphous Si3N4−x, Phys. Rev. Appl., 2018, 10, 064052 https://doi.org/10.1103/PhysRevApplied.10.064052.

16 Wang J., Long Y. On-chip silicon photonic signaling and processing: a review. Science Bulletin, 2018, vol. 63, no. 19, pp. 1267–1310. https://doi.org/10.1016/j. scib.2018.05.038.

17 Nikitin A.A. et.al. Carrier-induced optical bistability in the silicon microring resonators under continuous wave pumping. Optics Communications, 2021, vol. 480, p. 126456. https:// doi.org/10.1016/j. optcom.2020.126456.

18 Nikitin A.A. et.al. Optical bistable SOI micro-ring resonators for memory applications. Optics Communication, 2022, vol. 511, p. 127929. https:// doi.org/10.1016/j.optcom.2022.127929.

19 Smit M. et. al. An introduction to InP-based generic integration technology. Semiconductor Science and Technology, 2014, vol. 29, no. 8, p. 083001. https:// doi.org/10.1088/0268-1242/29/8/083001.

20 Blumenthal D.J. et al. Silicon nitride in silicon photonics. Proceedings of the IEEE, 2018, vol. 106, no. 12, pp. 2209–2231. https:// doi.org/10.1109/JPROC.2018.2861576.

21 Roeloffzen C.G. et al. Low-loss Si3 N4 TriPleX optical waveguides: Technology and applications overview. IEEE journal of selected topics in quantum electronics, 2018, vol. 24, no. 4, pp. 1–21. https:// doi.org/10.1109/JSTQE.2018.2793945.

22 Wang L. et al. Nonlinear silicon nitride waveguides based on a PECVD deposition platform. Optics express, 2018, vol. 26, no. 8, pp. 9645–9654. https:// doi.org/10.1364/OE.26.009645.

23 Ji X. et al. Methods to achieve ultra-high quality factor silicon nitride resonators. APL Photonics, 2021, vol. 6, no. 7, p. 071101. https:// doi.org/10.1063/5.0057881.

24 Moss D.J. et al. New CMOS-compatible platforms based on silicon nitride and Hydex for nonlinear optics. Nature photonics, 2013, vol. 7, no. 8, pp. 597–607. https:// doi.org/10.1038/nphoton.2013.183.

[1]Мурзалинов Д.,
PhD, ORCID ID: 0000-0001-6519-1969,
e-mail: d.murzalinov@sci.kz
[1]*Кемелбекова А.,
PhD, ORCID ID: 0000-0003-4813-8490,
*e-mail: a.kemelbekova@satbayev.university
[1]Жапаков Р.,
докторант, ORCID ID: 0000-0002-2570-8190,
e-mail: zharash@mail.ru
[1]Середавина Т.,
к.т.н., ORCID ID: 0000-0001-9689-160X,
e-mail: t.seredavina@sci.kz
[2]Елемесов К.,
профессор, ORCID ID: 0000-0001-6168-2787,
e-mail: k.yelemessov@satbayev.university
[1]Бегунов М.,
магистр, ORCID ID: 0000-0001-5389-0033,
e-mail: begunov028@gmail.com

[1]Сәтбаев университеті, Физика-техникалық институт,
050013, Алматы қ., Қазақстан
[2]Ә. Бүркітбаев атындағы энергетика және машина жасау институты, Сәтбаев университеті,
050000, Алматы қ., Қазақстан

ФОТОЛЮМИНЕСЦЕНЦИЯ СПЕКТРІН КЕҢЕЙТУДІҢ ТИІМДІ ӘДІСІ РЕТІНДЕ КРЕМНИЙ НИТРИДІНІҢ РАДИАЦИЯЛЫҚ РЕКОМБИНАЦИЯСЫНЫҢ ӘРТҮРЛІ МЕХАНИЗМДЕРІН ЗЕРТТЕУ

Андатпа

Құрамында кремний бар материалдар негізінде оптикалық және электрлік функцияларды біріктіретін құрылғыларды әзірлеу — микроэлектрониканың негізгі міндеттерінің бірі. Химиялық тұндыру күшейтілген плазмалық синтез арқылы газ фазасынан және одан кейінгі күйдіруден артық кремниймен де, артық азотпен де байытылған кремний нитридінің үлгілері алынды. Si-H және N-H байланыстарының жоғары концентрациясы күйдіру алдындағы үлгілерде Раман спектроскопиясы әдісімен анықталды. Трансмиссиялық электронды микроскопия арқылы кремний нитридінен басқа, үлгі матрицасында кремний кластерлерінің пайда болатыны анықталды. Фотолюминесценция спектрлері әртүрлі газ атмосфераларында күйдіру кезінде үлгілердің екі түрі үшін де айтарлықтай өзгерістер көрсетті. Синтезден кейін 1100 °C температурада үлгілерді термиялық өңдеу PL спектрінің жоғалуына әкелді, ал 800 °C температурада күйдіргеннен кейін фотолюминесценцияның қарқындылығы жоғарылады. Фотолюминесценцияның ең жоғары қарқындылығы ауа атмосферасында күйдірілгеннен кейін байқалды, ал азот атмосферасында ең төменгі қарқындылық анықталды. N-орталықтардың рекомбинациялық процестерге қатысуы электронды парамагниттік резонанс әдісімен расталды. Фотолюминесценцияға және зарядтың жиналуына әкелетін бөлшектердің өзара әрекеттесуінің әртүрлі механизмдері қарастырылды. Осылайша, әртүрлі спектрлік диапазондарда басқарылатын люминесценттік қасиеттерді алу үшін кремний нитриді қабаттарын синтездеу және күйдіру шарттары таңдалады.

Тірек сөздер: кремний нитриді, кремний оксиді, люминесценция, нанокластерлер, стехиометриялық тәртіп.

[1]Мурзалинов Д.,
PhD, ORCID ID: 0000-0001-6519-1969,
e-mail: d.murzalinov@sci.kz
[1]*Кемелбекова А.,
PhD, ORCID ID: 0000-0003-4813-8490,
*e-mail: a.kemelbekova@satbayev.university
[1]Жапаков Р.,
докторант, ORCID ID: 0000-0002-2570-8190,
e-mail: zharash@mail.ru
[1]Середавина Т.,
к.т.н., ORCID ID: 0000-0001-9689-160X,
e-mail: t.seredavina@sci.kz
[2]Елемесов К.,
профессор, ORCID ID: 0000-0001-6168-2787,
e-mail: k.yelemessov@satbayev.university
[1]Бегунов М.,
магистр, ORCID ID: 0000-0001-5389-0033,
e-mail: begunov028@gmail.com

[1]Сәтбаев университет, Физика-технический институт,
050013, г. Алматы, Казахстан
[2]Институт энергетики и машиностроения им. А. Буркитбаева,
Сәтбаев университет, 050000, г. Алматы, Казахстан

ИССЛЕДОВАНИЕ РАЗЛИЧНЫХ МЕХАНИЗМОВ РАДИАЦИОННОЙ РЕКОМБИНАЦИИ НИТРИДА КРЕМНИЯ КАК ЭФФЕКТИВНОГО СПОСОБА РАСШИРЕНИЯ СПЕКТРА ФОТОЛЮМИНЕСЦЕНЦИИ

Аннотация

Разработка устройств, сочетающих оптические и электрические функции на основе кремнийсодержащих материалов, является одной из задач микроэлектроники. Путем плазменного синтеза с усиленным химическим осаждением из газовой фазы и последующего отжига были получены образцы нитрида кремния как с избытком кремния, так и с избытком азота. Высокую концентрацию связей Si-H и N-H определяли методом рамановской спектроскопии в образцах перед отжигом. С помощью просвечивающей электронной микроскопии было определено, что помимо нитрида кремния, в матрице образца образуются кластеры кремния. Спектры фотолюминесценции существенно изменялись для обоих типов образцов при отжиге в различных газовых атмосферах. Термическая обработка образцов при 1100 °C после синтеза привела к исчезновению спектра ПЛ, а после отжига при 800 °C фотолюминесценция увеличивается. Отмечено, что наибольшая интенсивность фотолюминесценции была обнаружена после отжига в воздушной атмосфере и наименьшая – в азоте. Участие N-центров в рекомбинационных процессах подтверждено методом электронного парамагнитного резонанса. Рассмотрены различные механизмы взаимодействия частиц, приводящих к фотолюминесценции и накоплению заряда. Таким образом, подобраны условия синтеза и отжига слоев нитрида кремния для получения управляемых люминесцентных свойств в различных спектральных диапазонах.

Ключевые слова: нитрид кремния, оксид кремния, люминесценция, нанокластеры, стехиометрический порядок.

Article submission date: 07.08.2024

УДК 524.47-54
МРНТИ 41.27.19

https://doi.org/10.55452/1998-6688-2024-21-3-258-272

[1]*Куватова Д.Б.,
MSc, ORCID ID: 0000-0002-5937-4985,
*e-mail: kuvatova@fai.kz
[2,3,1]Ищенко М.В.,
канд. физ.-мат. наук, PhD, ORCID ID: 0000-0002-6961-8170,
e-mail: marina@mao.kiev.ua
[3,1,4,2]Берцик П.П.,
Dr.Sci, ORCID ID: 0000-0002-5004-199X,
e-mail: berczik@mao.kiev.ua
[1]Омаров Ч.Т.,
профессор, PhD, ORCID ID: 0000-0002-1672-894X,
e-mail: chingis.omarov@fai.kz
[1,5]Каламбай М.Т.,
PhD, ORCID ID: 0000-0002-0570-7270,
e-mail: kalambay@aphi.kz

[1]Астрофизический институт им. В.Г. Фесенкова, 050020, г. Алматы, Казахстан
[2]Главная астрономическая обсерватория, 01001, г. Киев, Украина
[3]Астрономический центр имени Николая Коперника Польской академии наук, 00001, г. Варшава, Польша
[4]Обсерватория Конколи, Исследовательский центр астрономии и наук о Земле, 1007, г. Будапешт, Венгрия
[5]Хериот-Уатт Международный факультет, Актюбинский региональный университет им. К. Жубанова, 030000, г. Актобе, Казахстан

ВЛИЯНИЕ ОШИБОК НАБЛЮДЕНИЙ ПО GAIA DR3 НА РЕКОНСТРУКЦИЮ ОРБИТ ШАРОВЫХ СКОПЛЕНИЙ НА КОСМОЛОГИЧЕСКОЙ ВРЕМЕННОЙ ШКАЛЕ

Аннотация

В последнее время набирает популярность развивающаяся область астрономии, занимающаяся историей формирования галактик, – галактическая археология. Шаровые скопления принимали участие во многих ключевых процессах, происходивших в Млечном Пути, поэтому их изучение, в частности реконструкция орбит, имеет существенное значение в этой области. Каталог Gaia DR3 предоставляет параметры 165 шаровых скоплений, такие как собственные движения, радиальная скорость и гелиоцентрическое расстояние, с некоторой точностью, поэтому важно изучить влияние ошибок измерений данных параметров на начальные данные при преобразовании в галактоцентрическую систему координат и, как следствие, на форму орбит. Нами были проинтегрированы орбиты шаровых скоплений на 10 миллиардов лет назад. Для физической обоснованности при интегрировании использовался внешний динамический потенциал под индивидуальным номером 411321 из базы космологического моделирования IllustrisTNG-100, наилучшим образом воспроизводящий потенциал Млечного Пути. Интегрирование производилось с помощью параллельного N-body кода φ-GPU, основанного на схеме Эрмита четвертого порядка с иерархическими индивидуальными блок-временными шагами. Было создано 1000 рандомизаций начальных данных с учетом нормального распределения ошибок и рассмотрено влияние ошибок на разброс начальных скоростей и на форму орбит. Наибольшие относительные ошибки имеют собственные движения и радиальная скорость, наименьшие – гелиоцентрическое расстояние. Обнаружено, что 85% шаровых скоплений от общего числа имеют относительные ошибки по всем параметрам не более 10%, а 5.4% – не более 1%. Исследовав влияние ошибок измерений для скоплений с различными величинами относительных ошибок, мы пришли к выводу, что для

большинства шаровых скоплений влияние ошибок измерений на форму орбит не существенно и, следовательно, для них возможна реконструкция орбит с высокой точностью. Так как реконструкция орбит шаровых скоплений подразумевает космологические временные масштабы, то учет ошибок измерений является важным аспектом в подготовительной процедуре перед основным интегрированием.

Ключевые слова: шаровые скопления, Млечный Путь, внешний динамический потенциал IllustrisTNG-100**,** численное моделирование, Gaia DR3 каталог.

Введение

Изучение истории Млечного Пути составляет набирающую популярность область исследований – галактическую археологию. На основе наблюдательных данных [1–3], астрометрических и спектроскопических, а также построения численных моделей [4, 5] галактическая археология ставит себе целью понять эволюционный путь нашей Галактики, включая вклад ее соседей, начиная с самых ранних моментов Вселенной. Одним из инструментов этого исследования может быть изучение шаровых скоплений.

Шаровые скопления (ШС) – гравитационно связанные звездные системы, типичный возраст которых составляет более 10–12 млрд лет [6–8], а массы – порядка 10^5 $M_\odot$ [9–12]. Шаровые скопления нашей Галактики локализуются как в диске, так и в гало, причем некоторые из них ассоциируются с потоками, являющимися артефактами произошедших ранее столкновений Млечного Пути с близлежащими карликовыми галактиками [13, 14]. Подобные события, особенно в ранние моменты времени [15], несомненно, внесли большой вклад в эволюцию массы Млечного Пути. Изучение ШС, их состава, кинематики и динамики вокруг центральной части Галактики играет важную роль в понимании истории нашей Галактики [16].

Благодаря опубликованным каталогам Gaia [17, 18] появилась возможность детально исследовать фазовое пространство всей популяции ШС Млечного Пути. Эти данные позволяют астрономам получать ценную информацию о движении и поведении этих скоплений, что, в свою очередь, способствует построению гипотез об их возможных орбитах вокруг центра нашей Галактики.

Некоторые предшествующие работы по изучению орбит ШС строились на основе предположения осесимметричности и стационарности потенциала Галактики [19–21], однако в силу наличия у Млечного Пути перемычки и сложного (boxy/peanut) балджа [22, 23] использование данных предположений не может быть полностью корректным. Кроме того, для ШС в гало Галактики следует учитывать и влияние ближайших соседей Млечного Пути, например, Большого и Малого Магеллановых Облаков [24–26].

Помимо этого, прежде чем приступить к масштабному моделированию движения ШС, необходимо тщательно проанализировать влияние ошибок измерения на их орбиты. Ошибки измерения, такие как погрешности в определении собственного движения, радиальной скорости и пр., вносят некоторый вклад в неточности при генерации начальных условий. В процессе интегрирования эти ошибки могут существенно изменять форму орбиты [27].

В настоящей работе было исследовано влияние ошибок измерения для выборки из 159 ШС Млечного Пути. В разделе 2 описаны процедуры определения начальных данных из каталога ШС, подбора потенциала из базы моделирования IllustrisTNG-100 и интегрирования с помощью кода φ-GPU. В разделе 3 описано влияние ошибок измерений параметров ШС из каталога на подбор начальных параметров и форму орбит. В разделе 4 приведены основные результаты и заключение.

Материалы и методы

Начальные данные и процедура интегрирования

Выборка ШС. Для данного исследования с целью получения начальных условий для моделирования был использован текущий каталог по ШС [10, 28], содержащий информацию

о более чем 160 объектах. Текущий каталог доступен по ссылке[1]. Каталог содержит такие данные ШС, как: прямое восхождение (*RA*), склонение (*DEC*), гелиоцентрическое расстояние ($D_\odot$), собственные движения по прямому восхождению (*PMRA*) и склонению (*PMDEC*), а также радиальную скорость (*RV*), полученные из Gaia DR3 [2, 17]. Для того чтобы выполнить интегрирование орбит ШС, необходимо преобразовать данные параметры в координаты и скорости в галактоцентрической системе координат. Трансформация координат была произведена с учетом таких параметров и коэффициентов, как: галактоцентрическое расстояние Солнца $R_\odot = 8.178$ кпк [29], высота над галактической плоскостью $Z_\odot = 20.8$ пк [30] и скорость относительно Локального стандарта покоя (LSR) $V_{LSR} = 234.737$ км/с [31, 32].

Если обозначить координаты и скорости ШС в гелиоцентрической системе координат как (*X,Y,Z*) и (*U,V,W*) соответственно, то координаты и скорости в прямоугольной галактоцентрической системе координат (*x ,y ,z*) и (*u, v, w*) могут быть получены из формул**,** приведенных в работе [33]:

$$\begin{cases} x = X + X_\odot + X_{LSR}, \\ y = Y + Y_\odot + Y_{LSR}, \\ z = Z + Z_\odot + Z_{LSR}, \end{cases} \qquad \begin{cases} u = U + U_\odot + U_{LSR}, \\ v = V + V_\odot + V_{LSR}, \\ w = W + W_\odot + W_{LSR}, \end{cases} \tag{1}$$

где $U_{LSR} = W_{LSR} = 0$ и $Y_\odot = 0$.

Внешний динамический потенциал. Для того чтобы иметь физически обоснованный анализ результатов интегрирования орбит ШС на 10 млрд лет назад во времени, в наш код был включен внешний потенциал, динамически меняющийся со временем. Потенциалы были отобраны из базы данных космологического моделирования IllustrisTNG-100 [34]. Данная модель характеризуется кубом около 100 Мпк[3], обеспечивающим достаточное количество галактик с разрешением по массе 7.5×10^6 $M_\odot$ для темной материи и 1.4×10^6 $M_\odot$ для барионной материи.

Для получения пространственных масштабов диска и гало темной материи было использовано распределение массы согласно профилю Миямото-Нагаи [35] для диска и профилю Наварро-Френка-Уайта [36] для гало. Тогда общий потенциал является суммой потенциалов, создаваемых данными распределениями, $\Phi_d(R,z)$ и $\Phi_h(R,z)$, соответственно:

$$\Phi_{tot} = \Phi_d(R,z) + \Phi_h(R,z) = -\frac{GM_d}{\sqrt{R^2 + \left(a_d + \sqrt{z^2 + b_d^2}\right)^2}} - \frac{GM_h \ln\left(1 + \frac{\sqrt{R^2+z^2}}{b_h}\right)}{\sqrt{R^2+z^2}}, \tag{2}$$

где R – галактоцентрический радиус в плоскости Галактики, z – расстояние над плоскостью диска, G – гравитационная постоянная, a_d – пространственная характеристика по длине для диска, b_d и b_h – пространственные характеристики по высоте для диска и гало, соответственно, M_d и M_h – массы диска и гало соответственно. В результате анализа из 54 потенциалов было отобрано 5 потенциалов, примерно воспроизводящих динамику Млечного Пути в прошлом. Детальная процедура отбора потенциалов и построение их компонент приведены в работах [37, 38] и по ссылкам[2,3].

[1] Каталог ШС https://people.smp.uq.edu.au/HolgerBaumgardt/globular/orbits_table.txt
[2] Код ORIENT: https://github.com/Mohammad-Mardini/The-ORIENT
[3] Потенциалы из IllustrisTNG-100 https://sites.google.com/view/mw-type-sub-halos-from-illustr/TNG?authuser=0

Процедура интегрирования. Для численного моделирования был использован параллельный динамический N-body φ-GPU[1] код [39,40], основанный на интеграционной схеме Эрмита четвертого порядка с иерархическими индивидуальными блок-временными шагами. Было проинтегрировано 159 ШС, каждое – как физическая частица с постоянной массой, взятой из каталога. Скопление Mercer 5 не было включено в процедуру интегрирования, так как для него не определена текущая масса. Таким образом, была выполнена реконструкция орбит 159 ШС в одном из выбранных внешних динамических потенциалов под оригинальным номером 411321 в IllustrisTNG-100**.** Интегрирование выполнялось с учетом влияния самогравитации ШС. На рисунке 1 представлены примеры реконструкции орбит двух наиболее известных ШС: NGC 6656 (Мессье 22) и NGC 104 (47 Тукана) на протяжении 10 млрд лет назад во времени.

Как видно из рисунка 1, после ~8 млрд лет интегрирования (красные оттенки) орбита начинает отклонятся от своей основной формы. Это может быть объяснено плохим разрешением самого потенциала, которое наступает после 8 млрд лет. При этом первые 8 млрд лет реконструкция демонстрирует стабильную форму орбит.




Рисунок 1 – Реконструкция орбит NGC 6656 и NGC 104 на 10 млрд лет назад во времени в динамическом потенциале 411321. Орбиты представлены в трех плоскостях слева направо: X-Y, X-Z и R-Z, где R – галактоцентрическое расстояние в плоскости. Цветом представлено время интегрирования. Синие точки обозначают положение скопления на сегодня, красные – на 10 млрд лет назад.

[1] N-body код φ-GPU https://github.com/berczik/phi-GPU-mole

Результаты и обсуждение

Влияние ошибок измерения ШС на реконструкцию орбиты

Проанализировав каталог с данными для ШС, определенными по Gaia DR3, видно, что ошибки наблюдения собственного движения по прямому восхождению (*PMRA*) и склонению (*PMDEC*), например, для ШС Crater, могут превышать 100%. На втором месте по ошибкам определения находятся величины радиальной скорости (*RV*) и на третьем – определение гелиоцентрического расстояния ($D_{\odot}$). Стоит отметить, что в приведенных выше формулах в преобразовании компонент скорости по V_x, V_y и V_z участвуют сразу три первых вышеперечисленных параметра. В то время как на компоненты положения *X*, *Y* и *Z*, помимо величин *RA* и *DEC*, еще влияют ошибки по $D_{\odot}$.

Чтобы оценить влияние ошибок в *PMRA*, *PMDEC* и *RV*, а также отдельно влияние ошибок $D_{\odot}$ на начальные положения и скорости ШС, был выполнен следующий анализ. Так, было создано два набора начальных положений и скоростей по 1000 файлов в каждом наборе с целью оценить уровень влияния ошибок наблюдения в каждом из случаев отдельно. В первом наборе начальные условия ШС варьировались с учетом нормального распределения ошибок по *PMRA*, *PMDEC*, *RV*. Во втором наборе – с учетом только варьирования значения $D_{\odot}$. В обоих наборах величины по *RA* и *DEC* оставались фиксированными для каждого скопления.

На рисунке 2 показано влияние ошибок измерения на компоненты скоростей в галактоцентрической системе отсчета. Как видно, 2 набора начальных условий в целом имеют одинаковый эффект на начальные скорости ШС.




Рисунок 2 – Влияние ошибок наблюдений на компоненты скоростей в галактоцентрической системе координат с учетом 1000 начальных данных рандомизаций. Зеленые кружки демонстрируют распределение начальных данных с учетом только собственных движений и радиальной скорости (*PMRA*, *PMDEC* и *RV*). Красные – только с учетом рандомизации по гелиоцентрическому расстоянию ($D_{\odot}$). Значками «плюс», «крестик», незаполненные «квадрат» и «круг» отмечены скопления Palomar 4, 5, 6 и 13 соответственно

В таблице 1 приведены 4 группы скоплений, отсортированные на основе относительных ошибок по гелиоцентрическому расстоянию ($D_{\odot}$), лучевой скорости (*RV*) и собственным движениям (*PMRA*, *PMDEC*). Относительная ошибка вычислялась стандартно по формуле $(\Delta x/x)*100\%$. В первую группу относились скопления, если хотя бы по одному из параметров относительная ошибка составляла $\varepsilon > 50\%$. В эту группу попало 8 ШС, что составляет 5% от общего числа. Во вторую группу было отобрано всего лишь 3 ШС (2%), ошибки которых варьируются от $30\% \leq \varepsilon < 50\%$. В третью группу попало 13 ШС с ошибками от $10\% \leq \varepsilon < 30\%$, что составило 8%. Наиболее многочисленная группа из 141 ШС имеет относительную ошибку $\varepsilon < 10\%$, что является 85% от общего числа ШС.

Таблица 1 – Относительные величины ошибок наблюдений по гелиоцентрическому расстоянию ($D_{\odot}$), лучевой скорости (*RV*) и собственным движениям (*PMRA*, *PMDEC*)

ШС	$\varepsilon(D_{\odot})$, %	ε (*RV*), %	ε (*PMRA*), %	ε (*PMDEC*), %	ШС	$\varepsilon(D_{\odot})$, %	ε (*RV*), %	ε (*PMRA*), %	ε (*PMDEC*), %
Группа 1: $\varepsilon > 50\%$					Группа 3: $10\% \le \varepsilon < 30\%$				
Palomar 1	3	0.4	10	153	Whiting 1	4	1	21	2
NGC 2419	3	1	600	1	Eridanus	3	3	6	12
Palomar 3	3	1	66	31	Pyxis	2	1	2	13
Palomar 4	3	0.3	65	88	Gran 2	10	3	12	1
Crater	3	0.4	862	72	NGC 6453	2	1	13	0.4
AM 4	3	2	57	14	UKS 1	4	4	22	5
NGC 6553	2	126	4	3	VVV-CL001	18	0.3	3	5
NGC 6760	5	54	1	0.2	2MASS-GC01	18	1	21	13
Группа 2: $30\% \le \varepsilon < 50\%$					NGC 6584	1	1	10	0.1
					NGC 6624	1	1	11	0.2
AM 1	3	12	17	42	NGC 6638	3	23	0.4	0.2
NGC 6380	3	49	1	0.5	Palomar 10	13	1	0.2	0.1
Laevens 3	3	1	42	11	Palomar 13	2	1	2	28
Группа 4: $\varepsilon < 10\%$									
NGC 104	1	1	0.2	0.3	Terzan 4	4	3	1	1
NGC 288	1	0.3	0.1	0.1	HP 1	2	3	1	0.3
NGC 362	1	0.1	0.1	0.4	FSR 1758	7	0.3	0.3	0.3
NGC 1261	1	0.3	1	0.4	NGC 6362	1	1	0.1	0.1
Palomar 2	5	1	4	3	Liller 1	4	4	3	2
NGC 1851	1	0.5	0.4	1	Terzan 1	3	3	2	1
NGC 1904	1	0.1	0.3	1	Tonantzintla 2	5	1	0.3	2
NGC 2298	2	0.4	0.2	0.3	NGC 6388	1	1	1	0.3
NGC 2808	1	0.3	1	3	NGC 6402	3	1	0.2	0.1
E 3	3	4	1	0.4	NGC 6401	3	2	0.4	1
NGC 3201	1	0.01	0.1	0.3	NGC 6397	1	0.4	0.2	0.03
NGC 4147	1	0.2	1	1	Palomar 6	6	1	0.2	0.3
NGC 4372	4	0.4	0.1	0.2	NGC 6426	2	0.2	1	1
Rup 106	2	1	1	2	Djor 1	7	0.5	1	0.2
NGC 4590	1	0.2	0.2	0.3	Terzan 5	2	1	2	1
BH 140	5	0.4	0.5	6	NGC 6440	3	1	2	1
NGC 4833	1	0.2	0.1	1	Gran 5	6	6	1	0.5
NGC 5024	1	0.4	4	0.4	NGC 6441	1	3	1	0.4
NGC 5053	1	1	2	1	Terzan 6	5	1	1	1
NGC 5139	1	0.1	0.3	0.2	Gran 1	8	2	0.5	0.4
NGC 5272	1	0.2	5	0.3	NGC 6496	2	0.2	0.2	0.1
NGC 5286	1	1	4	4	Terzan 9	6	1	1	0.4
NGC 5466	1	0.2	0.1	0.5	Djor 2	2	1	3	1
NGC 5634	2	4	1	1	NGC 6517	6	5	1	0.4
NGC 5694	2	0.4	3	1	Terzan 10	4	1	0.4	1
IC 4499	1	1	2	1	NGC 6522	3	3	1	0.2
NGC 5824	2	2	1	0.4	NGC 6535	2	0.2	0.3	0.4
Palomar 5	2	0.3	1	1	NGC 6528	3	0.2	1	0.3
NGC 5897	2	0.2	0.1	0.2	NGC 6539	5	1	0.1	0.2
NGC 5904	1	0.5	0.1	0.1	NGC 6540	5	5	1	1
NGC 5927	1	0.3	0.1	0.2	VVV-CL160	7	0.3	7	1
NGC 5946	5	1	0.3	1	NGC 6544	2	2	1	0.1
NGC 5986	1	0.4	0.4	0.4	NGC 6541	1	0.3	2	0.1
FSR 1716	4	3	1	0.3	ESO 280-SC06	3	0.4	3	1
Palomar 14	2	0.2	8	9	2MASS-GC02	8	3	8	5
Lynga 7	2	5	2	1	NGC 6558	2	0.4	1	0.4
NGC 6093	1	4	0.3	0.2	IC 1276	5	0.4	1	0.3
NGC 6121	1	0.2	0.1	0	Terzan 12	7	1	0.3	0.4
NGC 6101	1	0.1	1	5	NGC 6569	2	1	0.2	0.1
NGC 6144	2	0.3	1	1	BH 261	4	4	1	1
NGC 6139	4	4	0.2	0.4	NGC 6626	2	5	6	0.2

Продолжение таблицы 1

Terzan 3	4	0.4	0.3	1		NGC 6637	1	2	0.1	0.1
NGC 6171	1	1	0.4	0.1		NGC 6642	2	2	7	0.3
ESO 452-SC11	3	3	2	0.3		NGC 6652	1	1	0.2	0.3
NGC 6205	1	0.1	0.2	0.2		NGC 6656	1	1	0.1	0.2
NGC 6229	2	1	1	4		Palomar 8	6	3	3	1
NGC 6218	1	0.3	3	0.1		NGC 6681	1	0.4	1	0.3
FSR 1735	6	7	1	3		NGC 6712	3	0.3	0.2	0.2
NGC 6235	3	0.3	1	0.4		NGC 6715	1	0.3	0.3	1
NGC 6254	1	0.3	0.2	0.2		NGC 6717	2	3	1	0.3
NGC 6256	4	1	1	1		NGC 6723	1	0.3	1	0.2
Palomar 15	3	2	6	3		NGC 6749	3	2	1	0.5
NGC 6266	1	1	1	1		NGC 6752	1	0.5	0.4	0.3
NGC 6273	2	0.4	0.3	1		NGC 6779	1	0.3	0.3	0.4
NGC 6284	3	3	0.4	1		Terzan 7	2	0.1	0.4	1
Gran 3	7	2	2	9.8		Arp 2	1	0.2	1	1
NGC 6287	5	1	0.2	0.5		NGC 6809	1	0.1	0.2	0.1
Patchick 126	6	1	1	0.5		Terzan 8	2	0.1	0.4	0.4
NGC 6293	3	0.3	2	0.5		Palomar 11	4	1	1	0.4
NGC 6304	2	0.4	0.3	1		Sagittarius II	2	0.2	6	3
NGC 6316	3	1	1	1		NGC 6838	1	1	0.3	0.4
NGC 6341	1	0.2	0.2	2		NGC 6864	2	1	3	1
NGC 6325	4	2	0.3	0.3		NGC 6934	1	0.2	0.3	0.1
NGC 6333	2	1	0.4	0.2		NGC 6981	1	0.4	1	0.1
NGC 6342	3	1	0.4	0.2		NGC 7006	1	0.2	9	1
NGC 6356	6	4	0.3	0.3		NGC 7078	1	0.3	1	0.2
NGC 6355	3	0.3	0.3	3		NGC 7089	1	8	0.3	0.4
NGC 6352	1	1	0.4	0.2		NGC 7099	1	0.1	1	0.1
IC 1257	5	1	2	1		Palomar 12	2	1	0.4	0.4
Terzan 2	4	1	1	0.4		NGC 7492	2	0.2	1	0.5
NGC 6366	1	0.2	2	0.2						

В целом, анализируя таблицу 1, видим, что относительная ошибка по $D_{\odot}$ практически не превышает 10%. Исключениями являются 4 ШС: Palomar 10, VVV-CL001, 2MASS-GC01 и Gran 2 с относительной ошибкой от 10% до 18%. На втором месте по количеству больших величин в относительных ошибках является *RV*. Так, более 10% имеют NGC 6553, NGC 6760, NGC 6380, NGC 6638 и AM 1, чьи значения варьируются от 12% до 126%. Хуже всего определяются собственным движения, так, например, для Crater относительная ошибка по *PMRA* составляет 862%. По *PMDEC* наибольшее значение относительной ошибки зафиксировано для Palomar 1 – 153%.

Как видно из таблицы 1, следующие скопления имеют относительные ошибки по всем параметрам $\varepsilon \leq 1\%$: NGC 104, NGC 3201, NGC 4590, NGC 5139, NGC 5466, NGC 5904, NGC 6397, NGC 6752 и NGC 6809, что от общего количества наблюдаемых ШС составляет 5.4%

На рисунке 3 показаны распределения компонент скоростей на примере 4 ШС (Palomar 4, 5, 6 и 13, отмечены серым цветом в таблице 1) для 1000 рандомизаций начальных условий с учетом ошибок измерений. Как видно, влияние ошибок измерений на компоненты скорости ШС Palomar 4 (группа 1) достаточно велики, что как раз связано с величиной относительных ошибок его параметров, тогда как ШС из групп 3 и 4 имеют меньший разброс. Яркая зеленая точка демонстрирует величины компонент для V_x, V_y и V_z, полученные из каталога. Красные точки – их величины, полученные в результате нормального распределения наблюдаемых ошибок по Gaia DR3.




Рисунок 3 – Распределение компонент скоростей V_x, V_y и V_z ШС (Palomar 4, 5, 6 и 13) для 1000 рандомизаций начальных величин с учетом ошибок наблюдений. Зеленой точкой отмечены величины компонентов из каталога

Также в качестве иллюстрации примененного нами алгоритма нормального распределения компоненты скоростей с учетом ошибок наблюдений на рисунке 4 представлены ШС Palomar 4 и Palomar 13.




Рисунок 4 – Нормализованное кумулятивное вероятностное распределение начальных условий компонент скоростей по данным 1000 рандомизаций для Palomar 4 и 13. Биннинг – 1 км/с.

Palomar 4 относится к группе 1 и демонстрирует более широкий диапазон компонент скоростей, особенно по V_x, V_y. В то же время Palomar 13, относящийся к группе 4, имеет узкий диапазон значений и демонстрирует, в особенности по V_y и V_z, нормализованное кумулятивное вероятностное распределение начальных условий от 0 до 1 (черная линия).

Нами было исследовано влияние ошибок наблюдений при генерации начальных условий на возможное изменение формы орбиты, ее положение в различных структурах Галактики и даже на возможное изменение направления вращения орбиты. Для этого нами были выполнены реконструкции орбит ШС с учетом влияния ошибок на начальные данные. Из сгенерированных нами 1000 рандомизаций с начальными условиями было проинтегрировано 5 выбранных начальных данных.

На рисунке 5 представлены реконструкции орбит для 5 начальных условий четырех ШС: Palomar 4, 5, 6 и 13. Рандомизации представлены разным цветом.




Рисунок 5 – Реконструкция орбит для 5 начальных условий для 4 ШС Palomar 4, 5, 6 и 13. Рандомизации представлены разным цветом. Время интегрирования – 10 млрд лет назад во времени в динамическом потенциале 411321 (IllustrisTNG-100).

Для Palomar 4, например, относительные ошибки по *PMRA*, *PMDEC*, *RV* и $D_{\odot}$. составляют 65%, 88%, 0.3%, 3% соответственно (см. таблицу 1, группа 1: ε > 50%), а на рисунке 3, особенно для V_x и V_y, разброс величин составляет ±60 км/с. Это является причиной того, что положение витков орбиты не совпадает с положением витков из другой рандомизации (рисунок 5). Особенно это заметно для орбит из группы «зеленый-синий» и «красный-рыжий» в плоскости *X-Y*. Учитывая, что скопление Palomar 4 принадлежит гало Млечного Пути и имеет одно из самых далеких расстояний в апоцентре, большие ошибки в наблюдениях приводят к невозможности реконструировать орбиту с высокой точностью на длительном промежутке времени.

На примере Palomar 6 относительные ошибки по *PMRA*, *PMDEC*, *RV* и $D_{\odot}$ составляют 0.2%, 0.3%, 1%, 6% соответственно (см. таблицу 1, группа 4: ε <10%). В то же время на рисунке 3 разброс составляет примерно ±20 км/с для всех трех компонент скоростей. Как результат, на рисунке 5 все 5 реконструкций орбиты с разными начальными условиями образуют единую форму орбиты и не меняют направление вращения на всех трех проекциях. Учитывая, что ошибки наблюдений Palomar 6 подобны ошибкам большинства других скоплений, можно предположить, что их орбиты также устойчивы к таким вариациям начальных условий, а значит, представляется возможным реконструировать их орбиты с высокой точностью на длительном промежутке времени. Также стоит отметить, что влияние относительных ошибок измерений гелиоцентрического расстояния $D_{\odot}$ на форму орбиты ШС менее значимо, в сравнении с ошибками по другим параметрам, в особенности по собственным значениям.

Также на рисунке 5 представлены еще два ШС: Palomar 5 и Palomar 13. Так, для ШС Palomar 13 (относится к группе 3, таблица 1) видно, что 4 из 5 реконструкций демонстрируют незначительные изменения в витках орбиты.

Отметим, что для этого ШС наибольшая величина относительной ошибки определена для *PMDEC* – 28%. Для остальных трех параметров она составляет не более 2%. Таким образом, форма орбиты сохраняется во всех 5 вариантах реконструкции орбит. Для Palomar 5, который относится к группе 4 в таблице 1, видно, что витки орбит имеют совпадения в их формах для 4 моделей, кроме орбиты, представленной синим цветом.

Заключение

Реконструкция орбит ШС играет важную роль в понимании истории Млечного Пути, так как возраст ШС сопоставим с возрастом Галактики, и они участвовали во многих процессах формирования структуры Млечного Пути, например в приросте массы центральной части Галактики. Кроме того, интересен вопрос об их роли в ранних слияниях Млечного Пути с близлежащими галактиками. Все это составляет предмет изучения галактической археологии – развивающейся области астрономической науки.

В данной статье было изучено влияние ошибок измерений параметров ШС на начальные условия для численного моделирования орбит ШС и на форму орбит. Для начальных положений, скоростей и массы были использованы значения из каталога ШС [28], содержащего фазовые координаты из Gaia DR3.

Величины из каталога были преобразованы в координаты и скорости в галактоцентрической системе координат. Для интегрирования орбит был использован параллельный динамический код высокого порядка φ−GPU. Интегрирование производилось в специально подобранном потенциале 411321 из космологической симуляции IllustrisTNG-100, являющимся динамически меняющимся во времени. Его использование делает моделирование наиболее физически обоснованным. Выбор именно этого потенциала обусловлен его схожестью с потенциалом Млечного Пути. Для получения пространственных масштабов диска и гало темной материи использовались распределения масс профилей Миямото-Нагаи и Наварро-Френка-Уайта. Интегрирование производилось до 10 млрд лет назад во времени.

В зависимости от величины относительных ошибок по параметрам *PMRA*, *PMDEC*, *RV* и $D_{\odot}$ ШС были отнесены в 4 группы, причем подавляющая часть ШС (85%) имеет относитель-

ные ошибки по всем параметрам не более 10%. Наибольшие ошибки имеют параметры *PMRA* и *PMDEC*, затем *RV*, затем $D_{\odot}$, причем относительная ошибка по $D_{\odot}$ для большинства ШС не превышает 10%. Стоит отметить, что 5,4% ШС имеют относительные ошибки менее 1%. Все эти величины участвуют в определении галактоцентрических координат и скоростей, поэтому важно понимать, каким образом они могут влиять на начальные данные и, следовательно, на форму орбиты.

Было определено, что ШС из групп 3 и 4 (показано на примере ШС Palomar 5, 6, 13) имеют меньший разброс величин компонент скоростей, в отличие от ШС с более большими относительными ошибками (Palomar 4). Также это прослеживается и на самих реконструкциях орбит – ШС из групп 3 и 4 образуют единую форму орбиты. Так как ШС с подобными ошибками подавляющее большинство, то можно предположить, что и их орбиты устойчивы к вариациям начальных данных. Следовательно, для них возможна реконструкция орбит с высокой точностью.

Информация о финансировании. Исследование финансируется Комитетом науки Министерства науки и высшего образования Республики Казахстан (грант № AP14869395).

ЛИТЕРАТУРА

1 Buder S. et al. The GALAH+ survey: Third data release. Mon. Not. R. Astron. Soc. Oxford Academic, 2021, vol. 506, no. 1, pp. 150–201. https://doi.org/10.1093/mnras/stab1242.

2 Vallenari A. et al. Gaia Data Release 3 - Summary of the content and survey properties. Astron. Astrophys. Suppl. Ser. EDP Sciences, 2023, vol. 674, p. A1. https://doi.org/10.1051/0004-6361/202243940.

3 Kollmeier J. et al. SDSS-V: Pioneering Panoptic Spectroscopy. arXiv: Astrophysics of Galaxies, 2017. https://assets.pubpub.org/nubevd6h/01598545751555.pdf.

4 Ackerl C. et al. Galaxy archaeology - The quest for ancient mergers, 2024, pp. 1.01.

5 Merrow A. et al. Did the Gaia Enceladus/Sausage merger form the Milky Way's bar? Mon. Not. R. Astron. Soc. Oxford University Press, 2024, p. stae1250. https://academic.oup.com/mnras/advance-article-abstract/doi/10.1093/mnras/stae1250/7671147.

6 Marin-Franch A. et al. THE ACS SURVEY OF GALACTIC GLOBULAR CLUSTERS. VII.* RELATIVE AGES. Astrophys. J. IOP Publishing, 2009, vol. 694, no. 2, p. 1498. https://iopscience.iop.org/article/10.1088/0004-637X/694/2/1498/meta

7 Valcin D. et al. Inferring the Age of the Universe with Globular Clusters. arXiv [astro-ph.CO], 2020. https://doi.org/10.1088/1475-7516/2020/12/002

8 Vandenberg D.A. et al. The Ages of 55 Globular Clusters as Determined Using an Improved delta V_TO^HB Method Along with Color-Magnitude Diagram Constraints, and Their Implications for Broader Issues. arXiv [astro-ph.GA], 2013. https://doi.org/10.1088/0004-637X/775/2/134.

9 Baumgardt H. et al. Mean proper motions, space orbits, and velocity dispersion profiles of Galactic globular clusters derived from Gaia DR2 data, mnras, 2019, vol. 482, no. 4, pp. 5138–5155. https://doi.org/10.1093/mnras/sty2997

10 Baumgardt H., Vasiliev E. Accurate distances to Galactic globular clusters through a combination of Gaia EDR3, HST, and literature data, mnras, 2021, vol. 505, no. 4, pp. 5957–5977. https://doi.org/10.1093/mnras/stab1474.

11 Harris G.L.H., Poole G.B., Harris W.E. Globular clusters and supermassive black holes in galaxies: further analysis and a larger sample. Mon. Not. R. Astron. Soc. Oxford Academic, 2014, vol. 438, no. 3, pp. 2117–2130. https://doi.org/10.1093/mnras/stt2337.

12 Kharchenko N.V. et al. Global survey of star clusters in the Milky Way II. The catalogue of basic parameters. arXiv [astro-ph.GA], 2013. https://doi.org/10.1051/0004-6361/201322302.

13 Ibata R. et al. Charting the galactic acceleration field. I. a search for stellar streams with Gaia DR2 and EDR3 with follow-up from ESPaDOnS and UVES. Astrophys. J. American Astronomical Society, 2021, vol. 914, no. 2, pp. 123. https://doi.org/10.3847/1538-4357/abfcc2.

14 Mateu C. galstreams: A library of Milky Way stellar stream footprints and tracks. Mon. Not. R. Astron. Soc. Oxford Academic, 2023, vol. 520, no. 4, pp. 5225–5258. https://doi.org/10.1093/mnras/stad321.

15 Snaith O.N. et al. The dominant epoch of star formation in the Milky Way formed the thick disk. Astrophys. J. Lett. IOP Publishing, 2014, vol. 781, no. 2, p. L31. https://iopscience.iop.org/article/10.1088/2041-8205/781/2/L31/meta.

16 Xiang M., Rix H.-W. A time-resolved picture of our Milky Way's early formation history. Nature, 2022, vol. 603, no. 7902, pp. 599–603. https://doi.org/10.1038/s41586-022-04496-5.

17 Brown A.G.A. et al. Gaia Early Data Release 3 - Summary of the contents and survey properties. Astron. Astrophys. Suppl. Ser. EDP Sciences, 2021, vol. 649, p. A1. https://doi.org/10.1051/0004-6361/202039657.

18 Gaia C. et al. Gaia data release 2 summary of the contents and survey properties. Astron. Astrophys. Suppl. Ser. EDP Sciences, 2018, vol. 616, no. 1. https://real.mtak.hu/84690/1/gaia6.pdf.

19 Malhan K. et al. The global dynamical atlas of the Milky Way mergers: Constraints from Gaia EDR3–based orbits of globular clusters, stellar streams, and satellite galaxies. Astrophys. J. American Astronomical Society, 2022, vol. 926, no. 2, p. 107. https://doi.org/10.3847/1538-4357/ac4d2a.

20 Massari D., Koppelman H.H., Helmi A. Origin of the system of globular clusters in the Milky Way. Astron. Astrophys. Suppl. Ser. EDP Sciences, 2019, vol. 630, p. L4. https://doi.org/10.1051/0004-6361/201936135.

21 Myeong G.C. et al. Evidence for two early accretion events that built the Milky Way stellar halo. Mon. Not. R. Astron. Soc. Oxford Academic, 2019, vol. 488, no. 1, pp. 1235–1247. https://doi.org/10.1093/mnras/stz1770.

22 Dwek E., Arendt R.G., Hauser M.G. Morphology, near-infrared luminosity, and mass of the Galactic bulge from COBE DIRBE observations. Journal, Part 1 …. adsabs.harvard.edu, 1995. https://adsabs.harvard.edu/full/1995ApJ...445..716D.

23 Wegg C., Gerhard O. Mapping the three-dimensional density of the Galactic bulge with VVV red clump stars. Mon. Not. R. Astron. Soc. Oxford Academic, 2013, vol. 435, no. 3, pp.1874–1887. https://doi.org/10.1093/mnras/stt1376.

24 Conroy C. et al. All-sky dynamical response of the Galactic halo to the Large Magellanic Cloud. Nature, 2021, vol. 592, no. 7855, pp. 534–536. https://doi.org/10.1038/s41586-021-03385-7.

25 Gómez F.A. et al. And yet it moves: the dangers of artificially fixing the Milky Way center of mass in the presence of a massive Large Magellanic Cloud. Astrophys. J. Iop Publishing, 2015, vol. 802, no. 2, p.128. https://iopscience.iop.org/article/10.1088/0004-637X/802/2/128/meta.

26 Petersen M.S., Peñarrubia J. Detection of the Milky Way reflex motion due to the Large Magellanic Cloud infall. Nature Astronomy. Nature Publishing Group, 2020, vol. 5, no. 3, pp. 251–255. https://doi.org/10.1038/s41550-020-01254-3.

27 Bajkova A.T., Bobylev V.V. Orbits of 152 globular clusters of the Milky Way galaxy constructed from the Gaia DR2 data. arXiv [astro-ph.GA], 2020. https://doi.org/10.1088/1674-4527/21/7/173/meta

28 Vasiliev E., Baumgardt H. Gaia EDR3 view on galactic globular clusters. Mon. Not. R. Astron. Soc. Oxford Academic, 2021, vol. 505, no. 4, pp. 5978–6002. https://doi.org/10.1093/mnras/stab1475.

29 Reid M.J., Brunthaler A. The proper motion of Sagittarius A*. ii. The mass of Sagittarius A. Astrophys. J. American Astronomical Society, 2004, vol. 616, no. 2, pp. 872–884. https://doi.org/10.1086/424960.

30 Bennett M., Bovy J. Vertical waves in the solar neighbourhood in Gaia DR2. Mon. Not. R. Astron. Soc. Oxford Academic, 2018, vol. 482, no. 1, pp. 1417–1425. https://doi.org/10.1093/mnras/sty2813.

31 Bovy J. et al. The Milky Way's circular-velocity curve between 4 and 14 kpc from APOGEE data. Astrophys. J. IOP Publishing, 2012, vol. 759, no. 2, p. 131. https://iopscience.iop.org/article/10.1088/0004-637X/759/2/131/meta

32 Drimmel R., Poggio E. On the solar velocity. Res. Notes AAS. American Astronomical Society, 2018, vol. 2, no. 4, p. 210. https://doi.org/10.3847/2515-5172/aaef8b.

33 Chemerynska I.V. et al. Kinematic characteristics of the Milky Way globular clusters based on Gaia DR2 data. arXiv [astro-ph.GA], 2022. http://arxiv.org/abs/2201.07221.

34 Nelson D. et al. The IllustrisTNG simulations: public data release. Computational Astrophysics and Cosmology, 2019, vol. 6, no. 1, p. 2. https://doi.org/10.1186/s40668-019-0028-x

35 Miyamoto M., Nagai R. Three-dimensional models for the distribution of mass in galaxies, 1975, vol. 27, no. 4, pp. 533–543. adsabs.harvard.edu, 1975. https://adsabs.harvard.edu/full/1975PASJ...27..533M.

36 Navarro J.F., Frenk C.S., White S.D.M. A universal density profile from hierarchical clustering. Astrophys. J. American Astronomical Society, 1997, vol. 490, no. 2, pp. 493–508. https://doi.org/10.1086/304888.

37 Ishchenko M. et al. Milky Way globular clusters on cosmological timescales - I. Evolution of the orbital parameters in time-varying potentials. Astron. Astrophys. Suppl. Ser. EDP Sciences, 2023, vol. 673, p. A152. https://doi.org/10.1051/0004-6361/202245117.

38 Mardini M.K. et al. Cosmological insights into the early accretion of r-process-enhanced stars. I. a comprehensive chemodynamical analysis of LAMOST J1109+0754. Astrophys. J. American Astronomical Society, 2020, vol. 903, no. 2, p. 88. https://doi.org/10.3847/1538-4357/abbc13.

39 Berczik P. et al. High performance massively parallel direct N-body simulations on large GPU clusters. International conference on high performance computing, 2011, pp. 8–18. ftp://ftp.mao.kiev.ua/pub/berczik/phi-GPU/paper/1.1(8).pdf.

40 Berczik P. et al. Up to 700k GPU Cores, Kepler, and the Exascale Future for Simulations of Star Clusters Around Black Holes. Supercomputing. Springer Berlin Heidelberg, 2013, pp. 13–25. https://doi.org/10.1007/978-3-642-38750-0_2.

[1]*Куватова Д.Б.,
MSc, ORCID ID: 0000-0002-5937-4985,
*e-mail: kuvatova@fai.kz
[2,3,1]Ищенко М.В.,
ф.-м.ғ.к., PhD, ORCID ID: 0000-0002-6961-8170,
e-mail: marina@mao.kiev.ua
[3,1,4,2]Берцик П.П.,
Dr.Sci, ORCID ID: 0000-0002-5004-199X,
e-mail: berczik@mao.kiev.ua
[1]Омаров Ч.Т.,
профессор, PhD, ORCID ID: 0000-0002-1672-894X,
e-mail: chingis.omarov@fai.kz
[1,5]Қаламбай М.Т.,
PhD, ORCID ID: 0000-0002-0570-7270,
e-mail: kalambay@aphi.kz

[1]В.Г. Фесенков атындағы астрофизикалық институты, 050020, Алматы қ., Қазақстан
[2]Басты астрономиялық обсерватория, 01001, Киев қ., Украина
[3]Николай Коперник атындағы астрономиялық Орталық Польша ғылым академиясы, 00001, Варшава қ., Польша
[4]Конколи обсерваториясы, астрономия және жер туралы ғылымдарды зерттеу орталығы, 1007, Будапешт қ., Венгрия
[5]Хериот-Уатт халықаралық факультеті, Жұбанов университеті, 030000, Ақтөбе қ., Қазақстан

GAIA DR3 БАҚЫЛАУ ҚАТЕЛІКТЕРІНІҢ КОСМОЛОГИЯЛЫҚ УАҚЫТ ШКАЛАСЫНДАҒЫ ШАР ТӘРІЗДІ ШОҒЫРЛАРДЫҢ ОРБИТАЛАРЫН ҚАЛПЫНА КЕЛТІРУГЕ ӘСЕРІ

Андатпа

Жақында галактиканың пайда болу тарихымен айналысатын астрономияның өркендеп келе жатқан саласы – Галактикалық археология танымал бола бастады. Шар тәрізді шоғырлардың Құс Жолында болған көптеген негізгі процестерге қатысы бар, сондықтан оларды зерттеудің, атап айтқанда, олардың орбиталарын қалпына келтірудің маңызы зор. Gaia DR3 каталогы жұлдыздың меншікті қозғалысы, радиалды жылдамдығы және гелиоцентрлік қашықтығы секілді 165 шар тәрізді шоғырлардың параметрлерін қандайда бір дәлдікпен қамтамасыз етеді, сондықтан Галактоцентрлік координаттар жүйесіне түрлендіру кезінде бастапқы деректерге берілген параметрлерді өлшеу қателіктерінің әсерін зерттеу маңызды, нәтижесінде бұның орбита пішініне де әсері болады. Біз шар тәрізді шоғырлардың орбиталарын 10 миллиард жылға кері қарай интегралдадық. Ол үшін Құс Жолы потенциалына мейлінше жақын болатын IllustrisTNG-100

космологиялық модельдеу дерекқорындағы 411321 жеке нөмірі бойынша алынған сыртқы динамикалық потенциалды галактика пайдаланылды. Интегралдау уақытының иерархиялық жеке қадамдары бар төртінші ретті Эрмит схемасына негізделген N-денені параллель есептейтін φ-GPU коды арқылы жүзеге асырылды. Қателердің қалыпты таралуын ескере отырып, бастапқы деректердің 1000 кездейсоқтығы жасалды және қателіктердің бастапқы жылдамдықтардың таралуына және орбита пішініне әсері қарастырылды. Меншікті қозғалыстары мен радиалды жылдамдырының параметрлері бойынша – ең үлкен, ал гелиоцентрлік қашықтықтары бойынша – ең кіші салыстырмалы қателерге ие. Шар тәрізді шоғырлардың жалпы санының 85%-ында барлық параметрлер бойынша 10%-дан аспайтын, ал 5,4%-да 1%-дан аспайтын салыстырмалы қателер бар екені анықталды. Салыстырмалы қателіктердің әртүрлі мәндері бар кластерлер үшін өлшеу қателерінің әсерін зерттей отырып, біз көптеген шар тәрізді шоғырлар үшін өлшеу қателерінің орбиталардың пішініне әсері маңызды емес деген қорытындыға келдік, сондықтан аталған шоғырлар үшін орбиталарды жоғары дәлдікпен қалпына келтіру мүмкін болады. Шар тәрізді шоғырлардың орбиталарын қалпына келтіру ғарыштық уақыт шкалаларын қамтитындықтан, өлшеу қателіктерін ескеру негізгі интегралдауға дейінгі дайындық процедурасының маңызды аспектісі болады.

Тірек сөздер: Шар тәрізді шоғырлар, Құс Жолы, IllustrisTNG-100 сыртқы динамикалық потенциалы, сандық модельдеу, Gaia DR3 каталогы.

[1]*Kuvatova D.,
MSc, ORCID ID: 0000-0002-5937-4985,
*e-mail: kuvatova@fai.kz
[2,3,1]Ishchenko M.,
c.ph.-m.sc, PhD, ORCID ID: 0000-0002-6961-8170,
e-mail: marina@mao.kiev.ua
[3,1,4,2]Berczik P.,
Dr.Sci, ORCID ID: 0000-0002-5004-199X,
e-mail: berczik@mao.kiev.ua
[1]Omarov C.,
Professor, PhD, ORCID ID: 0000-0002-1672-894X,
e-mail: chingis.omarov@fai.kz
[1,5]Kalambay M.,
PhD, ORCID ID: 0000-0002-0570-7270,
e-mail: kalambay@aphi.kz

[1]Fesenkov Astrophysical Institute, 050020, Almaty, Kazakhstan
[2]Main Astronomical Observatory, 01001, Kyiv, Ukraine
[3]Nicolaus Copernicus Astronomical Centre Polish Academy of Sciences, 00001, Warsaw, Poland
[4]Konkoly Observatory, Research Centre for Astronomy and Earth Sciences,
1007, Budapest, Hungary
[5]Heriot-Watt International Faculty, Zhubanov University, 030000, Aktobe, Kazakhstan

THE INFLUENCE OF OBSERVATIONAL ERRORS IN GAIA DR3 ON THE RECONSTRUCTION OF GLOBULAR CLUSTER ORBITS ON A COSMOLOGICAL TIMESCALE

Abstract

In recent years, the emerging field of astronomy focused on the history of galaxy formation, known as Galactic Archaeology, has been gaining popularity. Globular clusters have been involved in many key processes occurring in the Milky Way, making their study, particularly the reconstruction of their orbits, significantly important. The Gaia DR3 catalog provides parameters for 165 globular clusters, such as proper motions, radial velocity, and heliocentric distance, with certain accuracy. Therefore, it is important to examine the influence of measurement errors in these parameters on the initial data when converting to the Galactocentric coordinate system and, consequently, on the shape of the orbits. We integrated the orbits of globular clusters 10 billion years lookback. For physical justification during the integration, we used the external dynamic potential with the individual number 411321 from

the cosmological simulation database IllustrisTNG-100, which best reproduces the potential of the Milky Way. The integration was performed using the parallel N-body code φ-GPU, based on a fourth-order Hermite scheme with hierarchical individual block timesteps. A total of 1,000 randomizations of the initial data were created considering a normal distribution of errors, and the influence of errors on the scatter of initial velocities and on the shape of the orbits was examined. The parameters with the largest relative errors are proper motions and radial velocity, while the smallest errors are in heliocentric distance. It was found that 85% of the globular clusters have relative errors in all parameters of no more than 10%, and 5.4% have errors of no more than 1%. Investigating the influence of measurement errors for clusters with different magnitudes of relative errors, we concluded that for most globular clusters, the influence of measurement errors on the shape of the orbits is not significant. Consequently, it is possible to reconstruct the orbits with high accuracy for these clusters. Since the reconstruction of globular cluster orbits involves cosmological timescales, accounting for measurement errors is an important aspect of the preparatory procedure before the main integration.

Key words: globular clusters, Milky Way, external dynamic potential IllustrisTNG-100, numerical simulation, Gaia DR3 catalog.

Дата поступления статьи в редакцию: 15.08.2024

УДК 533.9.082
МРНТИ 29.27.49

https://doi.org/10.55452/1998-6688-2024-21-3-273-280

[1]*Тажен А.Б.,
PhD, ORCID ID: 0000-0002-3277-2086,
*e-mail: Aigerim@physics.kz
[1]Досболаев М.К.,
к.ф.-м.н., доцент, ORCID ID: 0000-0002-0724-1793,
e-mail: merlan@physics.kz
[1]Пшиков М.И.,
к.ф.-м.н., и.о. доцента, ORCID ID: 0000-0003-0706-2688,
e-mail: mustahim.pshikov@gmail.com
[2]Усенов Е.А.,
PhD, ORCID ID: 0000-0001-7903-8674,
e-mail: yerbolat@physics.kz
[1]Рамазанов Т.С.
д.ф.-м.н., профессор, ORCID ID: 0009-0009-2301-1152,
e-mail: ramazan@physics.kz

[1]НИИЭТФ, Казахский национальный университет им. аль-Фараби,
050040, г. Алматы, Казахстан
[2]Кафедра машиностроения и аэрокосмической техники, Принстонский университет,
08540, Нью-Джерси, США

ИЗМЕРЕНИЕ СКОРОСТИ ИМПУЛЬСНОГО ПЛАЗМЕННОГО ПОТОКА НА УСТАНОВКЕ PW-7

Аннотация

В работе рассмотрены два независимых метода измерения скорости плазменного потока, создаваемого в импульсном плазменном ускорителе PW-7: метод, основанный на наблюдении и оценке величины доплеровского сдвига спектральных линий, и метод высокоскоростной видеосъемки движения плазмы. Монохроматор М833 был использован для регистрации спектра излучения плазменного потока. Высокоскоростная видеосъемка осуществлялась со скоростью 640 000 кадров/с с использованием CMOS-камеры Phantom VEO710S. Приведены результаты измерений средней скорости потока, полученные при рабочем давлении газа $2 \cdot 10^{-2}$ Торр, емкости и напряжении конденсаторной батареи 400 мкФ и 4 кВ. Полученные результаты двумя независимыми методами были сравнены между собой. Аргон использовался в качестве рабочего газа в экспериментах. Показано, что при использовании первого метода значение скорости плазменного потока составляет $12{,}5 \cdot 10^3$ м/сек, а при использовании второго метода значение скорости плазменного потока составляет $16{,}7 \cdot 10^3$ м/сек. По этим данным можно видеть, что измеренные значения скорости потока имеют небольшое расхождение. Таким образом, было установлено, что методы высокоскоростной видеосъемки и доплеровского сдвига дают в пределах ошибок измерений сопоставимые оценки скорости движения потока. С точки зрения практического применения определение значение скорости плазменного потока имеет очень большое значение.

Ключевые слова: импульсный плазменный ускоритель, высокоскоростная видеосъемка, доплеровский сдвиг, плазменный поток.

Введение

Исследование плазменных потоков представляет большой интерес для разработок в области управляемого термоядерного синтеза и электрореактивных плазменных двигателей [1–5].

Одним из наиболее значимых для этих применений параметров является скорость потока плазмы. Плазменные потоки со скоростями до $\upsilon > 10^4$ м/сек можно получить в импульсных плазменных ускорителях [6–8]. Ускорение плазмы в этих устройствах осуществляется в основном за счет силы Ампера. Существуют несколько методов определения скорости плазменного потока. Некоторые из наиболее распространенных методов включают в себя зондовые [9–11], оптические [12, 13] и фотографические методы [14–16]. Настоящая работа посвящена определению направленной скорости плазменного потока, генерируемого в установке PW-7, на основе регистрации и анализа доплеровских сдвигов спектральных линий (формула 1).

$$\upsilon = c\left(\frac{\lambda_0 - \lambda}{\lambda_0}\right) \quad (1)$$

где c – скорость света, λ_0 – длина волны покоя, $\lambda_0 - \lambda = \Delta\lambda$ – доплеровский сдвиг.

Материалы и методы

Эксперименты выполнены на установке PW-7 [17–19], принципиальная схема которой представлена на рисунке 1. Данная установка представляет собой импульсный плазменный ускоритель, состоящий из двух коаксиально расположенных медных электродов с диаметрами 5,5 см и 10,8 см. Электроды размещены в вакуумной камере, внутри которой откачивается воздух до давления 10^{-3} Торр перед началом экспериментов. После этого камера заполняется аргоном до рабочего давления $2{\cdot}10^{-2}$ Торр. Источником питания ускорителя служит конденсаторная батарея, емкость которой и зарядовое напряжение составляют 400 мкФ и 4 кВ. Для исследования направленных потоков плазмы установка оснащена диагностическими окнами, установленными на боковой и торцевой стенках вакуумной камеры.




Рисунок 1 – Принципиальная схема экспериментальной установки (импульсного плазменного ускорителя)

Для регистрации эмиссионных спектров плазменного потока используется монохроматор с высокой разрешающей способностью M833 [20]. Измерение спектров проводилось через боковое окошко (рисунок 1, позиция 1 – перпендикулярно плазменному потоку) и с торцевой стороны ускорителя (позиция 2 – вдоль направления ускорения плазмы). Для идентификации спектральной линии иона аргона монохроматор настроен на длину волны 480.6 нм. Частота штрихов решетки – 1800 штр/мм. Ширина входной щели и время экспозиции монохроматора установлены 20 мкм и 1 мс для получения оптимального соотношения оптического сигнала к

шуму и регистрации излучения в течение всего времени жизни плазмы. Зарегистрированные спектры обрабатывались с помощью программного обеспечения SolarLS LAB и программы «OriginPro 8». Расшифровка спектров осуществлялась с использованием спектральной базы данных NIST. Для фокусировки и передачи плазменного излучения в монохроматор используется оптоволоконный детектор.

Запуск монохроматора производится синхронно с плазменным ускорителем. Для этого используется генератор импульсов Berkeley Nucleonics Model 577 (амплитуда и длительность синхронизирующего импульса составляют 5 В и 12 мкс). Монохроматор, блок дистанционного управления и синхронизации ускорителя размещаются в отдельное экранированное помещение.

Результаты и обсуждения

Спектральные линии, зарегистрированные с боку и торца ускорителя, в экспериментах с аргоном представлены на рисунке 2. Доплеровский сдвиг для линии излучения, полученной перпендикулярно потоку, предполагается нулевым. В таком случае длину волны этой линии можно считать опорной (рисунок 2, красная сплошная линия). Как мы видим, при детектировании излучения вдоль направления ускорения плазмы (позиция 2) эта линия смещается в сторону коротких длин волн. Таким образом, в настоящем эксперименте величина доплеровского сдвига составит порядка $\Delta\lambda \approx \cdot$ 0,02 нм. По этим данным оценивалась скорость движения потока аргоновой плазмы. На основе формулы (1) она составляет порядка $12{,}5 \cdot 10^3$ м/сек.




Рисунок 2 – Доплеровский сдвиг спектральной линии ArII 480,60 нм

Следует также отметить, что значение скорости, рассчитанное исходя из эффекта Доплера, сравнивалось с результатами высокоскоростной видеосъемки плазменного потока. Съемка осуществляется с помощью видеокамеры Phantom VEO710S с диагностического окна, расположенного на боковой стороне вакуумной камеры на расстоянии 22 см. Поскольку поток плазмы имеет высокую динамичность, частота и разрешение видеокамеры составляют 640 000 кадров/с и 128×32 пикселей. На рисунке 3 приведены изображения плазменного потока.

Таким образом, скорость потока аргоновой плазмы, определенная методом высокоскоростной видеосъемки (по отношению смещения плазменного потока на двух последовательных изображениях к промежутку времени между этими изображениями) составила по-

рядка $16{,}7 \cdot 10^3$ м/сек. Отсюда видно, что различие между значениями скорости, оцененными двумя независимыми методами, небольшое, что свидетельствует о малой расходимости и достоверности полученных нами результатов измерений.



Рисунок 3 – Высокоскоростная видеосъемка потока аргоновой плазмы.
Частота – 640000 кадров/с, минимальное время экспозиции – 1,1 мкс.
Направление потока – слева направо. Интервал между кадрами – 1,56 мкс.

Заключение

Использование двух независимых позволило определить одну из важнейших характеристик – скорости потока аргоновой плазмы, генерируемого в импульсном плазменном ускорителе PW-7. Показано, что скорость потока плазмы, определенная методом высокоскоростной видеосъемки, превосходит значение скорости, определенное методом доплеровского сдвига спектральных линий. Это обусловлено тем, что высокоскоростная видеосъемка позволяет проводить только качественное исследование и значение скорости потока, определенное с ее помощью, можно считать приближенным. Также следует отметить, что видеокамера фиксирует только изменение яркости плазменного свечения. Поскольку это свечение может быть сильно неоднородным, рассчитанная скорость оказывается неточной. Тем не менее полученные данные расходятся несущественно. Таким образом, применение двух методов в совокупности позволяет значительно повысить достоверность результатов измерений скорости потока аргоновой плазмы.

Благодарность/источник финансирования

Работа финансировалась Министерством науки и высшего образования Республики Казахстан в рамках проекта No BR18574080 «Исследование фундаментальных и прикладных проблем физики плазмы, плазмоподобных сред для целей решения задач современной энергетики и получения новых функциональных материалов».

ЛИТЕРАТУРА

1 Linsmeier Ch., Unterberg B., Coenen J.W., Doerner R.P., Greuner H., Kreter A., Linke J., Maier H. Material testing facilities and programs for plasma-facing component testing // Nucl. Fusion. – 2017. – Vol. 57. – P. 092012. https://doi.org/10.1088/1741-4326/aa4feb

2 Kartasheva A.A., Gutorov K.M., Podkovyrov V.L., Muravyeva E.A., Lukyanov K.S., Klimov N.S. Experimental investigation of the characteristics of the plasma flow generated in quasi-stationary plasma accelerator using optical methods // Phys. Plasmas. – 2024. – Vol. 31. – P. 043107. https://doi.org/10.1063/5.0198341.

3 Ling W.Y.L., Zhang S., Fu H., Huang M., Quansah J., Liu X., Wang N. A brief review of alternative propellants and requirements for pulsed plasma thrusters in micropropulsion applications // Chinese Journal of Aeronautics. – 2020. – Vol. 33. – P. 2999–3010. https://doi.org/10.1016/j.cja.2020.03.024.

4 Ou Y., Wu J., Cheng Y., Zhang Y., Che B. Design and performance of a micro-pulsed plasma thruster used in miniaturized satellites // Advances in Space Research. – 2024. – Vol. 74. – P. 1741–1750. https://doi.org/10.1016/j.asr.2024.05.039.

5 Lerner E.J., Hassan S.M., Karamitsos-Zivkovic I., Fritsch R. Focus Fusion: Overview of Progress Towards p-B11 Fusion with the Dense Plasma Focus // Journal of Fusion Energy. – 2023. – Vol. 42. – P. 1–18. https://doi.org/10.1007/s10894-023-00345-z.

6 Ladygina M.S., Petrov Yu.V., Yeliseev D.V., Makhlai V.A., Kulik N.V., Staltsov V.V. Parameters of hydrogen plasma streams in QSPA-M and their dependence on external magnetic field // Problems of atomic science and technology. – 2021. – No. 1. – P. 61–64. https://doi.org/10.46813/2021-131-061

7 Borthakur S., Ahmed A., Singha S., Neog N.K., Borthakur T.K. Role of gas flow on plasma stream dynamics in a pulsed plasma accelerator // Fusion Engineering and Design. – 2021. – Vol. 168. – P. 112400. https://doi.org/10.1016/j.fusengdes.2021.112400

8 Zhukeshov A.M., Amrenova A.U., Gabdullina A.T., Moldabekov Zh.M., Useinova B.M. Calculation and Analysis of Electrophysical Processes in a High-Power Plasma Accelerator with an Intrinsic Magnetic Field // Technical Physics. – 2019. – Vol. 64. – P. 342–347. https://doi.org/10.1134/S1063784219030277.

9 Talukdar N., Ahmed A., Borthakur S., Neog N.K., Borthakur T.K., Ghosh J. Measurement of plasma stream velocity in a pulsed plasma accelerator // Phys. Plasmas. – 2019. – Vol. 26. – P. 062711. https://doi.org/10.1063/1.5092267.

10 Dosbolayev M.K., Igibayev Zh.B., Tazhen A.B., Ramazanov T.S. Preliminary Study of the Solid-State Pulsed Plasma Thruster Model with Graphite as a Propellant // Plasma Physics Reports. – 2022. – Vol. 48. – P. 263–270. https://doi.org/10.1134/S1063780X22030047.

11 Al-Hawat S. Axial velocity measurement of current sheath in a plasma focus device using a magnetic probe // IEEE Transactions on Plasma Science. – 2004. – Vol. 32. – P. 764–769. https://doi.org/10.1109/TPS.2004.826119.

12 Yaroshevskaya A.D., Gutorov K.M., Podkovyrov V.L., Litvinenko Yu.I. Determination of Plasma Flow Velocity with Time Resolution Based on the Doppler Effect // Plasma Physics Reports. – 2024. – Vol. 50. – P. 689–696.

13 Ярошевская А.Д., Малютин А.Ю., Подковыров В.Л., Гуторов К.М., Карташева А.А. XLIX Международная (Звенигородская) конференция по физике плазмы и УТС (Москва, 14–18 марта, 2022). – С. 164.

14 Losada U., Manzanares A., Balboa I., Silburn S., Karhunen J., Carvalho P.J., Huber A., Huber V., Solano E.R., de la Cal E. Observations with fast visible cameras in high power Deuterium plasma experiments in the JET ITER-like wall tokamak // Nuclear Materials and Energy. – 2020. – Vol. 25. – P. 100837. https://doi.org/10.1016/j.nme.2020.100837.

15 Ананьев С.С., Крауз В.И., Мялтон В.В., Харрасов А.М. Исследование формирования плазменных потоков, генерируемых в плазмофокусном разряде // ВАНТ. Сер. Термоядерный синтез. – 2017. – Т. 40. – С. 21–35. https://doi.org/10.21517/0202-3822-2017-40-1-21-35.

16 Nawaz A., Lau M., 32nd Int. Electric Propulsion Conf (Wiesbaden, 11–15 September, 2011). – P. 1–13.

17 Tazhen A.B., Rayimkhanov Zh.R., Dosbolayev M.K., Ramazanov T.S. Generation and Diagnostics of Pulse Plasma Flows // Plasma Physics Reports. – 2020. – Vol. 46. – P. 465–471. https://doi.org/10.1134/S1063780X20040121.

18 Dosbolayev M.K., Tazhen A.B., Ramazanov T.S., Ussenov Ye.A. Investigation of dust formation during changes in the structural and surface properties of plasma-irradiated materials // Nuclear Materials and Energy. – 2022. – Vol. 33. – P. 101300. https://doi.org/10.1016/j.nme.2022.101300.

19 Dosbolayev M.K., Tazhen A.B., Kholmirzayev A.N., Ussenov Ye.A., Ramazanov T.S. Studies of the formation and distribution of cracks and various defects on the heated tungsten plate surface during pulsed plasma flux impact // Nuclear Materials and Energy. – 2023. – Vol. 37. – P. 101540. https://doi.org/10.1016/j.nme.2023.101540.

20 Tazhen A.B., Dosbolayev M.K., Ramazanov T.S. Pulsed plasma flow diagnostics // Recent Contributions to Physics. – 2022. – Vol. 81. – P. 35–39. https://doi.org/10.26577/RCPh.2022.v81.i2.05.

REFERENCES

1 Linsmeier Ch., Unterberg B., Coenen J.W., Doerner R.P., Greuner H., Kreter A., Linke J. Maier H. Nucl. Fusion, 2017, vol. 57, p. 092012. https://doi.org/10.1088/1741-4326/aa4feb.

2 Kartasheva A.A., Gutorov K.M., Podkovyrov V.L., Muravyeva E.A., Lukyanov K.S., Klimov N.S. Phys. Plasmas, 2024, vol. 31, p. 043107. https://doi.org/10.1063/5.0198341.

3 Ling W.Y.L., Zhang S., Fu H., Huang M., Quansah J., Liu X., Wang N. Chinese Journal of Aeronautics, 2020, vol. 33, pp. 2999–3010. https://doi.org/10.1016/j.cja.2020.03.024.

4 Ou Y., Wu J., Cheng Y., Zhang Y., Che B. Advances in Space Research, 2024, vol. 74, pp. 1741–1750. https://doi.org/10.1016/j.asr.2024.05.039.

5 Lerner E.J., Hassan S.M., Karamitsos-Zivkovic I., Fritsch R. Journal of Fusion Energy, 2023, vol. 42, pp. 1–18. https://doi.org/10.1007/s10894-023-00345-z.

6 Ladygina M.S., Petrov Yu.V., Yeliseev D.V., Makhlai V.A., Kulik N.V., Staltsov V.V. Problems of atomic science and technology, 2021, no. 1, pp. 61–64. https://doi.org/10.46813/2021-131-061.

7 Borthakur S., Ahmed A., Singha S., Neog N.K., Borthakur T.K. Fusion Engineering and Design, 2021, vol. 168, p. 112400. https://doi.org/10.1016/j.fusengdes.2021.112400.

8 Zhukeshov A.M., Amrenova A.U., Gabdullina A.T., Moldabekov Zh.M., Useinova B.M. Technical Physics, 2019, vol. 64, pp. 342–347. https://doi.org/10.1134/S1063784219030277.

9 Talukdar N., Ahmed A., Borthakur S., Neog N.K., Borthakur T.K., Ghosh J. Phys. Plasmas, 2019, vol. 26, p. 062711. https://doi.org/10.1063/1.5092267.

10 Dosbolayev M.K., Igibayev Zh.B., Tazhen A.B., Ramazanov T.S. Plasma Physics Reports, 2022, vol. 48, pp. 263–270. https://doi.org/10.1134/S1063780X22030047.

11 Al-Hawat S. IEEE Transactions on Plasma Science, 2004, vol. 32, pp. 764–769. https://doi.org/10.1109/TPS.2004.826119.

12 Yaroshevskaya A.D., Gutorov K.M., Podkovyrov V.L., Litvinenko Yu.I. Plasma Physics Reports, 2024, vol. 50, pp. 689–696.

13 Yaroshevskaya A.D., Malyutin A.Yu., Podkovyrov V.L., Gutorov K.M., Kartasheva A.A. XLIX International Zvenigorod Conference on Plasma Physics and Controlled Fusion (Moscow, 14–18 March, 2022), p. 164. [in Russian].

14 Losada U., Manzanares A., Balboa I., Silburn S., Karhunen J., Carvalho P.J., Huber A., Huber V., Solano E.R., de la Cal E. Nuclear Materials and Energy, 2020, vol. 25, p.100837. https://doi.org/10.1016/j.nme.2020.100837.

15 Ananyev S.S., Krauz V.I., Myalton V.V., Kharrasov A.M. VANT. Ser. Termoyadernyi sintez, 2017, vol. 40, pp. 21–35. [in Russian]. https://doi.org/10.21517/0202-3822-2017-40-1-21-35.

16 Nawaz A., Lau M. 32nd Int. Electric Propulsion Conf (Wiesbaden, 11–15 September, 2011), pp. 1–13.

17 Tazhen A.B., Rayimkhanov Zh.R., Dosbolayev M.K., Ramazanov T.S. Plasma Physics Reports, 2020, vol. 46, pp. 465–471. https://doi.org/10.1134/S1063780X20040121.

18 Dosbolayev M.K., Tazhen A.B., Ramazanov T.S., Ussenov Ye.A. Nuclear Materials and Energy, 2022, vol. 33, p. 101300. https://doi.org/10.1016/j.nme.2022.101300.

19 Dosbolayev M.K., Tazhen A.B., Kholmirzayev A.N., Ussenov Ye.A. Ramazanov T.S., Nuclear Materials and Energy, 2023, vol. 37, p. 101540. https://doi.org/10.1016/j.nme.2023.101540.

20 Tazhen A.B., Dosbolayev M.K., Ramazanov T.S. Recent Contributions to Physics, 2022, vol. 81, pp. 35–39. https://doi.org/10.26577/RCPh.2022.v81.i2.05.

[1]*Тәжен Ә.Б.,
PhD, ORCID ID: 0000-0002-3277-2086,
*e-mail: Aigerim@physics.kz
[1]Досболаев М.Қ.,
ф.-м.ғ.к., доцент, ORCID ID: 0000-0002-0724-1793,
e-mail: merlan@physics.kz
[1]Пшиков М.И.,
ф.-м.ғ.к., доцент м.а., ORCID ID: 0000-0003-0706-2688,
e-mail: mustahim.pshikov@gmail.com
[2]Үсенов Е.А.,
PhD, ORCID ID: 0000-0001-7903-8674,
e-mail: yerbolat@physics.kz
[1]Рамазанов Т.С.
ф.-м.ғ.д., профессор, ORCID ID: 0009-0009-2301-1152,
e-mail: ramazan@physics.kz

[1]әл-Фараби атындағы Қазақ ұлттық университеті,
050040, Алматы қ., Қазақстан
[2]Машина жасау және аэроғарыштық инженерия кафедрасы, Принстон университеті,
08540, Нью-Джерси қ., АҚШ

PW-7 ҚОНДЫРҒЫСЫНДАҒЫ ИМПУЛЬСТІК ПЛАЗМАЛЫҚ АҒЫННЫҢ ЖЫЛДАМДЫҒЫН ӨЛШЕУ

Аңдатпа

Бұл жұмыста PW–7 импульстік плазмалық үдеткіште пайда болатын плазмалық ағынның жылдамдығын өлшеудің екі тәуелсіз әдісі қарастырылған, олар: спектрлік сызықтардың доплерлік ығысуын бақылау мен бағалауға негізделген әдіс және плазманың қозғалысын жоғары жылдамдықты видеокамераға түсіру әдісі. Плазмалық ағынның сәулелену спектрін тіркеу үшін М833 монохроматоры қолданылды. Жоғары жылдамдықты бейнетүсірілім 640000 кадр/с жылдамдықпен Phantom VEO710S CMOS-камерасының көмегімен жүзеге асырылды. Жұмыс газының қысымы – $2 \cdot 10^{-2}$ Торр, конденсатор батареясының сыйымдылығы мен кернеуі – 400 мкФ және 4 кВ болғандағы ағынның орташа жылдамдығының өлшеу нәтижелері келтірілген. Екі тәуелсіз әдіспен алынған нәтижелер бір-бірімен салыстырылды. Аргон жұмыс газы ретінде экспериментте қолданылды. Бірінші әдісті қолданып анықталған плазма ағынының жылдамдығы $12{,}5 \cdot 10^3$ м/сек, ал екінші әдісті қолданып анықталған плазма ағынының жылдамдығы $16{,}7 \cdot 10^3$ м/сек құрады. Бұл деректерден өлшенген жылдамдықтардың мәндерінде болмашы айырмашылықтың бар екендігін көруге болады. Осылайша өлшеу қателіктері шегінде жоғары жылдамдықты видеокамераның және доплерлік ығысу әдісімен өлшенген ағын жылдамдықтарының мәндері бір-біріне жуық болатындығы анықталды. Плазмалық ағынның жылдамдығын анықтаудың маңызы оның практикалық қолданылуы тұрғысынан алғанда өте жоғары болып табылады.

Тірек сөздер: импульстік плазмалық үдеткіш, жоғары жылдамдықты бейнетүсірілім, доплерлік ығысу, плазмалық ағын.

[1]*Tazhen A.B.,
PhD, ORCID ID: 0000-0002-3277-2086,
*e-mail: Aigerim@physics.kz
[1]Dosbolayev M.K.,
Candidate of Physical and Mathematical Sciences, Associate Professor,
ORCID ID: 0000-0002-0724-1793,
e-mail: merlan@physics.kz
[1]Pshikov M.I.,
Candidate of Physical and Mathematical Sciences, Acting Associate Professor,
ORCID ID: 0000-0003-0706-2688,
e-mail: mustahim.pshikov@gmail.com
[2]Usenov E.A.,
PhD, ORCID ID: 0000-0001-7903-8674,
e-mail: yerbolat@physics.kz
[1]Ramazanov T.S.
Doctor of Physical and Mathematical Sciences, Professor,
ORCID ID: 0009-0009-2301-1152,
e-mail: ramazan@physics.kz

[1]Al-Farabi Kazakh National University,
050040, Almaty, Kazakhstan
[2]Department of Mechanical and Aerospace Engineering, Princeton University,
08540, NJ, USA

MEASUREMENT OF THE VELOCITY OF PULSED PLASMA FLOW AT THE PW-7 INSTALLATION

Abstract

The paper considers two independent methods for measuring the velocity of the plasma flow generated in the PV-7 pulsed plasma accelerator: a method based on observation and evaluation of the Doppler shift of spectral lines, and a method of high-speed visualization of plasma motion. To record the plasma flow radiation spectrum, a monochromator M833 was used. High-speed video recording was carried out at 640,000 fps using a Phantom VEO710S CMOS camera. The results of measurements of the average flow velocity obtained at a working gas pressure of $2 \cdot 10^{-2}$ Torr, capacitance and voltage of the capacitor bank of 400 μF and 4 kV are presented. The results obtained by two independent methods were compared with each other. Argon was used as the working gas in the experiments. It is shown that the value of the plasma flow velocity estimated by the first method is 12.5 m/s, and the value of the plasma flow velocity estimated by the second method is 16.7 m/s. From these data the measured flow velocity values have a small discrepancy. Thus, it has been established that high-speed video recording and Doppler shift methods make it possible to obtain comparable estimates of flow velocity within the measurement errors. Determining the magnitude of the plasma flow velocity is of great practical importance.

Key words: pulsed plasma accelerator, high-speed video recording, Doppler shift, plasma flow.

Дата поступления статьи в редакцию: 26.08.2024

ӘОЖ 536.2; 536.42; 620.9; 621.472; 662.997
ҒТАХР 30.17.35; 30.17.00; 44.31.00; 27.35.45; 44.37.29

https://doi.org/10.55452/1998-6688-2024-21-3-281-301

[1]Карлина Е.И.,
магистрант, ORCID ID: 0009-0008-2941-5775,
e-mail: kelisaveta123@gmail.com
[1]Ердеш Е.Б.,
Жаратылыстану ғылымдарының магистрі, ORCID ID: 0000-0001-9623-5610,
e-mail: yelnaryerdesh@gmail.com
[1,2]Баимбетов Д.Б.,
Жаратылыстану ғылымдарының магистрі, ORCID ID: 0000-0002-4992-0890, e-mail:
dynmuhambet@gmail.com
[1]Джамакеев И.Б.,
магистрант, ORCID ID: 0009-0005-9596-6944,
e-mail: jamakeyev.i@gmail.com
[3]Моханрадж М.,
профессор, ORCID ID: 0000-0003-4870-3496,
e-mail: mohanrajrac@yahoo.co.in
[1,4]*Беляев Е.К.,
қауымдастырылған профессор, ORCID ID: 0000-0002-7947-2179,
*e-mail: yerzhan.belyaev@kaznu.edu.kz; yerzhan.belyayev@gmail.com

[1]Әл-Фараби атындағы Қазақ ұлттық университеті,
050040, Алматы қ., Қазақстан
[2]Ш. Есенов атындағы Каспий технологиялар және инжиниринг университетіні,
130000, Ақтау қ, Қазақстан
[3]Үндістан инженерлік-технологиялық колледжінің Инженерлік механика департаменті,
641 032, Коимбатор қ., Үндістан
[4]Қ.И. Сәтбаев атындағы Қазақ ұлттық зерттеу техникалық университетіні,
050013, Алматы қ., Қазақстан

КҮН ДИСТИЛЛЯТОРЫ ІШІНДЕГІ БУЛАНУ ЖӘНЕ КОНДЕНСАЦИЯЛАНУ КЕЗІНДЕГІ ЕКІ ФАЗАЛЫҚ ЖЫЛУ АЛМАСУ ПРОЦЕСТЕРІН САНДЫҚ МОДЕЛЬДЕУ

Аңдатпа

Бұл мақалада лицензияланған ANSYS 2023R2 бағдарламалық пакетін және есептеу гидродинамикасы (CFD) әдісін пайдаланып екі күн дистилляторының конфигурациясының салыстырмалы талдауы берілген. Модельдеу үшін сұйықтықтың бір фазадан екіншісіне өтуін есептеуге мүмкіндік беретін VoF (Volume of Fluid) моделі қолданылды. VoF моделі теориялық көзқарасқа сәйкес келетін сандық нәтижелерді іс жүзінде қолданбай, тек визуализация үшін булану процестерін жаңғыртуға қабілетті екенін атап өткен жөн. Зерттеудің өзектілігі су тұщыту жүйелерінің тиімділігін арттыруды талап ететін жаһандық ауыз су дағдарысымен байланысты. Таза су алудың бұл әдісі ең экологиялық таза әдіс, бұл зерттеу нысанын таңдауға басты себеп болды. Жұмыстың мақсаты – күн дистилляторын сандық талдау және зерттеу, оның екі конфигурациясын салыстырмалы талдау, сондай-ақ қондырғының тиімділігін арттыру үшін ықтимал модификацияларды бағалау. Зерттеу барысында қондырғының ішіндегі жылу ағындары, сонымен қатар будың көлемдік үлесінің таралуы және уақыт бойынша температураның өзгеруі модельденді. Алынған нәтижелер бір көлбеу конфигурациямен салыстырғанда қос көлбеу конфигурациясының жоғары тиімділігі мен өнімділігін көрсетеді. Зерттеу сонымен қатар дистиллятор ішінде болып жатқан физикалық процестерді егжей-тегжейлі сипаттайды және осы жүйені ANSYS модельдеуде одан әрі жетілдіру бағыттарын анықтайды.

Тірек сөздер: күн дистилляторы, екі фазалы жылу алмасу, булану және конденсациялау, ANSYS Fluent, сандық талдау.

Кіріспе

Қазіргі уақытта ауыз су тапшылығы проблемасы әлемнің көптеген аймақтарында, әсіресе таза суға қол жетімділік шектеулі жерлерде барған сайын өзекті болып отыр. 1999 жылдың өзінде [1] бұл мәселеге назар аударылды: Жердегі жалпы су ресурстарының 1,4 млрд текше километрінің 2,5%-дан азы тұщы су, оның тек 0,26%-ы көлдер мен өзендер сияқты жер үсті көздерінен келеді. Дегенмен, барлық судың шамамен 0,3–0,5%-ы ғана адам пайдалануына жетеді. Тұщы судың үлесі әлі 2–3 пайызды құраса да, оның қоры бірте-бірте азайып келеді, бұл ауыз суды өндірудің шешімін табу қажеттілігін көрсетеді.

Қазақстанда, әсіресе Орталық және Батыс Қазақстанда, сондай-ақ Маңғыстау және Атырау облыстарында сумен қамтамасыз етуде қиындықтарды бастан кешіруде. Соңғы жылдары бұл мәселе бүкіл елді қамтыды. Осы мәселені шешу және өңірлерді электр және жылу энергиясымен қамтамасыз ету үшін 1968 ж. Маңғыстау атом электр станциясы (МАЭК) салынып, әлі күнге дейін жақын маңдағы елді мекендерді ауыз сумен қамтамасыз етіп келеді. Дегенмен, бұл әдіс экологиялық тәуекелдермен, соның ішінде апаттар ықтималдығымен және ядролық қалдықтарды кәдеге жарату қиындығымен байланысты.

Көптеген елдердің күн энергиясын пайдаланудың жоғары әлеуеті бар, Қазақстан да бұдан тыс емес. Дүниежүзілік банк пен Халықаралық қаржы корпорациясы ұсынған 2024 ж. 29 сәуірдегі Global Solar Atlas деректеріне [2] сәйкес, Қазақстандағы жалпы көлденең күн радиациясының деңгейі, орташа температура +7,1 °C болғанда, тәулігіне 3,09-дан 4,58 кВтсағ/м²-ге дейін ауытқиды. Қазақстандағы күн радиациясының деңгейі тәулігіне 3,62-ден 7,98 кВт/м²-ге дейін ауытқитын Австралияға қарағанда біршама төмен болғанымен, бұл әлі күнге дейін күнді тұщыту және күн жылу энергиясы сияқты технологияларды дамыту үшін жеткілікті, бұл үшін үлкен мүмкіндіктер ашылады.

Бұл мәселені шешудің ең экологиялық таза жолы – күн энергиясын пайдалану, әсіресе күн дистилляторларын пайдалану. Олардың қарапайым дизайны және басқа әдістермен салыстырғанда төмен құны оларды тазартылған суды өндіру үшін таңдауға өз артықшылықтарын береді. Қолжетімділігі мен тиімділігіне байланысты бұл әдіс әртүрлі елдерде көбірек қолданылады. Күн дистилляторлары кез келген су көзін, соның ішінде теңіз суын және ластанған су объектілерін тазарта алады. Олардың жұмысының негізгі принципі судың бір фазадан екіншісіне ауысуы болып табылады, бұл әдісті модельдеу процесін айтарлықтай күрделі етеді.

Дегенмен, стандартты қондырғылардың өнімділігі төмен болғандықтан, оларды жаңғырту қажеттілігі туындайды. [3]-ші жұмыстағы зерттеулерге сәйкес, күн дистилляторының максималды тәжірибелік тиімділігі 45%-дан аспайды, бұл шамамен 4,26 кг/м²-ге тең. Тиімділікті арттыру, энергия шығындарын азайту, сенімділікті арттыру және әртүрлі климаттық жағдайларға бейімделу үшін дизайнға сәйкес өзгерістер қажет.

Күн дистилляторлары екі негізгі түрге бөлінеді: пассивті және белсенді. Пассивті дистилляторлар суды жылыту үшін тек күн энергиясына сүйенеді [4], ал белсенді жүйелер сыртқы көздерден алынатын жылу энергиясын қосымша пайдаланады [5]. Белсенді қондырғылар суды алдын ала қыздыруға арналған күн коллекторлары, фазаны өзгерту материалдарын (РСМ) пайдалану және жалпы жүйе тиімділігін арттыру үшін басқа жақсартулар сияқты шешімдерді қолдана алады.

Пассивті күн дистилляторлары әртүрлі конфигурацияларда құрастырылуы мүмкін. Олар пішіні бойынша ерекшеленеді: бір және екі еңісті, сфералық, конус тәрізді және т.б., сондай-ақ 15°-тан 45°-қа дейін өзгеретін еңіс бұрышында географиялық координаттарға байланысты жасалынады [6]. Дистилляторлардың конструкциясында бір немесе бірнеше су бассейндері болуы мүмкін [7]. Тиімділікті арттыру үшін күн радиациясының сіңірілуін жақсарту әдістері жиі қолданылады, мысалы, әйнектің жиектеріне концентраторларды орнату [8], айналарды

пайдалану немесе дистилляторды параболалық коллектор-концентратор түрінде жасау [9]. Сондай-ақ графит, алюминий және басқалары сияқты әртүрлі абсорберлік материалдар зерттелуде [4], ал кейбір жағдайларда құрылыс құнын төмендету үшін абсорберге [10] тастар қосылады, олар фазалық өзгерістер материалдарын (PCM) алмастыра алады. Бұл жақсартулардың барлығы жүйе өнімділігін жақсартуға бағытталған.

Белсенді жүйелерде әдетте суды қосымша қыздыру немесе сыртқы салқындатқыш элементті қолдану арқылы конденсация процесін күшейту қолданылады [11]. Бұған газ немесе электр қазандығын орнату немесе жүйеге орнатылған буландырғыш арқылы өтетін салқындатқышты біріктіру арқылы қол жеткізуге болады.

Күн дистилляторларына олардың тиімділігін арттыру үшін үнемі зерттелетін басқа да модификациялар бар. Бұл жақсартулар аймақтың климаттық жағдайларына байланысты өзгеруі мүмкін: кейбір шешімдер өнімді болмауы мүмкін, ал басқалары жүйе өнімділігін айтарлықтай жақсарта алады. Мысалы, [12]-ші жұмыстаға авторлардың шолу мақаласында 2015 жылы күн дистилляторларының 38-ге жуық әртүрлі үлгілері қарастырылды, олардың математикалық модельдерін талдау және модификациялардың тиімділігін бағалауы көрсетілген.

Бұл мақалада ANSYS бағдарламалық құралының құрамында бар солверлер арқылы бір және екі еңісті күн дистилляторын модельдеу әдісі ұсынылады.

Күн дистилляторлары тақырыбын көптеген ғалымдар белсенді түрде зерттеді. Олардың ішінде В. Белессиотис, С. Калогироу, Э. Дельяннис, Р.В. Данкл, С.К. Шукла, В.П.С. Сораян, Мостафа Х. Шаркави, Джон Х. Лиенхард, В. Сайед, М. Зубайр және т.б. бар. Күн дистилляторлары бойынша негізгі зерттеулер мен нәтижелер бірқатар кітаптарда егжей-тегжейлі берілген, соның ішінде термиялық күнді тұщыландыру: В. Василис, К. Сотерис және Д. Эмми әдістері мен жүйелері [13], Күн көмегімен дистилляциялау: шатырдағы дистиллятор және көп қадамды дистиллятор диффузиясы» Р.В. Данкл [14], сонымен қатар «Күн дистилляторларын термиялық модельдеу және тәжірибелік тексеру» С.К. Шукла және В.П.С. Сорайан еңбектерінде кездеседі [15].

Күн дистилляторының жұмыс істеу принципі келесідей: абсорбер күн радиациясын қабылдайды және оны жылу энергиясына айналдырады, бұл оның қызуын тудырады. Содан кейін бұл жылу конвекция арқылы сұйықтыққа беріледі, бұл оның буланuына әкеледі. Булану кез келген температурада болуы мүмкін, өйткені сұйық молекулаларының кинетикалық энергиясы молекулааралық тартылыс күштерін жеңіп, су бетінен бөлініп шығу үшін жеткілікті. Булану нәтижесінде қалған сұйықтықтың температурасы төмендейді [16]. Алынған бу көтеріледі. Күн радиациясын жақсы өткізетін және оны нашар сіңіретін шыны өз температурасын сіңіргіштен төмен, бірақ қоршаған ортадан жоғары деңгейде ұстайды. Бұл сұйықтық пен шыны арасындағы жүйенің ішіндегі ауаның қызып кетуіне байланысты болады, ал бу шыныға жеткенде булану кезінде сіңірілген жылуды босатып, қайтадан сұйық фазаға өтеді. Бұл жағдайда әйнек жел және қоршаған атмосфера сияқты сыртқы әсерлерден салқындатылады. Бу шыныға тиген кезде ол энергияны жоғалтады, бұл су тамшылары түріндегі конденсацияны тудырады. Бұл тамшылар әйнек бетімен арнайы арналарға ағып, жинау ыдысына түседі. Буланған кезде дистиллятордағы сұйықтық деңгейін ұстап тұру үшін суық су (20 °C) қосылады.

Бұл мәселе белгілі бір қиындықтарды тудыратын 100 °C төмен температурада сұйықтықтың фазалық ауысу процесін қарастырады. Максвелл-Больцман таралымы бойынша [17, 18], тіпті төмен температураның өзінде олардың саны әлдеқайда аз болғанымен, молекулааралық күштерді жеңіп, сұйықтықты қалдыруға жеткілікті кинетикалық энергиясы бар молекулалар болады. Қазіргі уақытта қайнауды сипаттайтын жақсы дамыған модельдер бар, бірақ мұндай төмен температурада булану процесі көбінесе елеусіз болып саналады және жиі ескерілмейді. Бұл берілген физикалық құбылысты модельдеуді қиындатады. Әдетте сұйықтықтың бетінен булану жылдамдығын анықтау үшін температура мен ішінара қысымды байланыстыратын теңдеулер қолданылады. Молекулалардың қозғалу жылдамдығы температураға тура про-

порционал болғандықтан, оның жоғарылауымен булану қарқындылығы артады. Парциалды қысым берілген температурада қаныққан бу қысымынан төмен болғанда, булану тепе-теңдікке жеткенше жүреді [17].

Күн дистилляторы жүйесінде жылу алмасудың келесі түрлері байқалады: күн, шыны беті және абсорбер арасындағы сәулелену; абсорбер мен су арасындағы, сондай-ақ конденсация кезінде бу мен шыны арасындағы конвективті жылу алмасу. Негізгі жылу жоғалуына (шығындарына) мыналар жатады: дистиллятордың шыны және корпусы арқылы қоршаған ортаға жылудың ағуы; сұйықтықтың булануы кезіндегі жылуды жоғалту; су мен шыны арасындағы ауаның болуынан туындаған жылу жоғалту; сондай-ақ желдің әсерімен байланысты шығындар. Өткізгіштік арқылы құрылым арқылы жылу беру шамалы және бұл жүйеде есепке алынбайды деп қарастырылған.

VoF (Volume of Fluid) моделі күрделі Эйлер-Эйлер моделінің жеңілдетілген нұсқасы болып табылады. Фазалық ауысу мәселелерін шешудің екі негізгі тәсілі бар: Эйлер-Эйлер моделі және Эйлер-Лагранж моделі. Эйлер-Эйлер моделі басқару көлемдерімен байланысты теңдеулерге негізделген [19] және оның бірнеше нұсқалары ANSYS бағдарламалық пакетінде ұсынылған, оның ішінде бастапқы үлгіден тыс үш қосымша нұсқасы бар. Керісінше, Эйлер-Лагранж моделі Лагранж координаталар жүйесіндегі теңдеулермен жұмыс істейді, мұнда әрбір бөлшек бөлек қарастырылады, бұл оны ANSYS-те қолданылатын басқару көлемінің әдісі үшін қолайлы емес етеді. «Эйлер-Лагранж» атауы Эйлердің үздіксіздік теңдеулерін қолданумен байланысты [20]. Эйлер-Эйлер моделінде фазалар кеңістік пен уақытқа тәуелді көлемдік үлес ұғымын қолдануға мүмкіндік беретін өзара енетін үздіксіздік ретінде сипатталады. Жалпы Эйлер-Эйлер моделі фазалық ауысуды дәл сипаттау үшін теңдеулердің көп санын шешуді қажет етеді.


Бұл жұмыстың мақсаты – ең тиімді дизайнды анықтау үшін ANSYS бағдарламалық құралын пайдалана отырып, күн дистилляторларының екі түрін - бір көлбеу және екі еңісті - сандық зерттеу және салыстыру. Зерттеудің ғылыми жаңалығы күн дистилляторында болып жатқан процестер алғаш рет ANSYS жүйесінде VoF (сұйықтықтың көлемі) моделін қолдану арқылы имитацияланды, бұл булану ағындарын визуализациялауға мүмкіндік берді.

Материалдар мен әдістер

Есептің физикалық қойылымы


Нәтижелерді дәл салыстыру үшін қондырғының резервуарының көлемін, оның төменгі бөлігінің ауданын, сондай-ақ құрылымның жалпы көлемін бекіту туралы шешім қабылданды. Мұндай жағдайларда күн дистилляторының екі көлбеу моделі үшін жаңа конфигурация жасалды.

1-суретте оның барлық өлшемдерін көрсететін күн дистилляторының диаграммасы көрсетілген. Дизайнға әйнек панель, сіңіргіш пластина (абсорбер), алюминий корпусы және қондырғының периметрі бойынша жылу жоғалуын азайтуға арналған жылу оқшаулағыш қабаты кіреді. 2-суретте оның негізгі компоненттерін көрсететін күн дистилляторының екі өлшемді бүйірлік көрінісі көрсетілген. Төменгі жағында тұзды су ыдысы бассейн ретінде белгіленген. Әйнек бетінің қалыңдығы 4 мм, абсорбер тақтасы 2 мм, ал оқшаулағыш материал 5 см. Дистиллятордың әр элементінің массасы оның меншікті салмағымен анықталады. Қалыңдығы 4 мм әйнектелген бет үшін бұл параметр 10,12 кг/м^2, ал сіңіргіш үшін — 15,6 кг/м^2. 1-суретте көрсетілген геометриялық параметрлер бойынша шынының массасы 11,79 кг, ал сіңіргіштің массасы 15,29 кг болады. Абсорбер 300 сериялы тот баспайтын болаттан жасалған және оқшаулау шыны жүннен жасалған. Күн радиациясын сіңіру тиімділігін арттыру үшін абсорбер қара түске боялады.



Сурет 1 – Күн дистилляторының екі конфигурациясының схемасы

Тұзды су бассейнінің көлемі жоғарыда аталған екі конфигурация үшін бірдей және 0,336 м³ тең. Күн дистилляторының жоғарғы бөлігінің көлемі 0,504 м³, ол төменгі бөлігімен бірге 0,84 м³ қондырғының жалпы ішкі көлемін береді. Абсорбер пластинасының көлемі оның жалпы ішкі көлемге елеусіз әсеріне байланысты ескерілмеген. Екінші конфигурацияның бірінші конфигурациямен салыстырғанда көлемі азырақ. Су ыдысының ұзындығы мен биіктігі – 0,1 м, қалыңдығы – 0,01 м және ол құрылымның бүкіл еніне созылады. Есептеу торын оңтайландыру және есептеу ресурстарына қойылатын талаптарды азайту үшін геометрияның мұндай таңдауына назар аударылды. Бұл ең үлкен кеңістіктік тор аралығын 0,02 м-ге дейін орнатуға мүмкіндік береді.



Сурет 2 – Бір көлбеу күн дистилляторының көлденең қимасы

Математикалық модельдеудің негізгі болжамдары:

- Сыртқы температура 23,85 °C немесе 297 К және тұрақты болып саналады;
- Күннің тікелей сәулеленуі 800 Вт/м², ал диффузиялық сәулеленуі 100 Вт/м², сәулелену де тұрақты болып саналады;
- Солверде көрсетілген есептік уақыт аралығында күн позициясының өзгеруі екі конфигурация үшін де бірдей деп қабылданады;

◆ Будың әлсіз сығылатын қасиетіне байланысты сұйық ағыны идеалды және сығылмайтын деп есептеледі;

◆ Бу мен су арасындағы температура градиентіне байланысты параметрлердің өзгеруі есепке алынбайды;

◆ Абсорбер пластинасының түбінің астында жылу жоғалуы жоқ деп есептеледі (адиабаталық қабырға);

◆ Бассейндегі тұзды судың қайта толтырылуы есепке алынбайды, булану есебінен бассейн суының көлемі өзгереді.

Булану (конденсация) кезіндегі екі фазалы жылу алмасуды сандық модельдеу сұйықтық көлемі немесе Volume of Fluid (VoF) әдісін қолдану арқылы жүзеге асырылды. Бұл модель массаның, импульстің және энергияның сақталуының негізгі заңдарын толығымен қанағаттандырады. VoF құрамына сұйық және газ фазаларының көлемдік үлесін есептеуге арналған теңдеу (массаның сақталуы), Навье-Стокс түріндегі қозғалыс теңдеуі және энергияның сақталуына арналған бір теңдеу кіреді. VoF моделі фазалар арасында нақты шекара бар жағдайлар үшін жеңілдетілген. Бұл модель күн дистилляторы кабинасының ішіндегі екі фазалы жылу алмасуды модельдеуге өте ыңғайлы, өйткені сұйық фаза (тұзды су) мен ауа мен су буының (газ фазасы) қоспасы арасында нақты шекара бар. Сонымен қатар, VoF моделі есептеу уақытының қысқаруымен, есептеу ресурстары мен торға жүктеменің төмендеуімен сипатталады, сонымен бірге сұйықтық пен газ арасындағы шекараның өзгеруін бақылауға мүмкіндік береді. Сандық модельдеу кезінде су тығыздығының температураға көпмүшелік тәуелділігі (сызықтық полином) формуласы қолданылды. Бұл тәуелділік температураның судың қасиеттеріне әсерін толығырақ бағалауға мүмкіндік берді.

Артықшылықтан басқа, VoF моделінің шектеулері бар:

◆ тек сығылмайтын сұйықтық солверлерін қолдану (pressure-based solver);

◆ бастапқы шарттар ретінде пайдалану фазалардың бірін немесе олардың комбинациясын орнату;

◆ VoF моделін пайдалану кезінде берілген массалық ағынмен бойлық мерзімді (периодты) ағынды модельдеу мүмкін емес;

◆ айқындалмаған схеманы іске асыру кезінде уақыт туындысы үшін дәлдіктің бірінші ретті жуықтауын ғана қолдану.

Қолданылатын ANSYS Fluent бағдарламалық құралында Ли моделі булану және сәйкесінше конденсация процестерін имитациялау үшін қолданылады. Бұл модельдегі ең басты жері фазалық ауысу процесі басталатын қанығу температурасын орнату болып табылады. Негізінде, күн дистилляторының кабинасының ішінде бу өндіру процесі 100 °C төмен температурада жүреді. Бұл физикалық тұрғыдан қарағанда дұрыс құбылыс, өйткені модель қанығу температурасына ғана емес, сонымен қатар қанығу қысымына да байланысты. Қанығу температурасы ANSYS пайдаланушы функцияларын қолданып қолмен еңгізілді [21]. Бұл жағдайда қанығу температурасы 0 °C деп есептелді, бұл физикалық тұрғыдан дұрыс емес, бірақ фазалық ауысу жиілігі үшін коэффициенттер арқылы түзетілді. Нәтижесінде булану және конденсация процестері бөлек талданды.

ANSYS жүйесіндегі VoF моделі бастапқыда 100 °C температурада судың қайнауын модельдеуге дайындалғандықтан, жасалған жорамалдардың нәтижесінде жылдамдық пен температура профильдерін талдау артық бағалануы мүмкін. Сондықтан жобаның екі нұсқасын салыстыру жылдамдық пен температура өрістерін талдауға негізделеді.

Есептің математикалық қойылымы

Жоғарыда айтылғандай, математикалық модель массаның, импульстің және энергияның сақталуының фундаменталды заңдарына негізделген. Ұсынылған математикалық модельдің сандық орындалуы мен есептеу алгоритмі ANSYS 23R2 бағдарламалық құралында толық сипатталған [22].

Әрбір бақылау көлемі үшін есептелетін сұйық және газ фазаларының көлемдік үлесінің теңдеуі былай жазылады:

$$\frac{1}{\rho_q}\left[\frac{\partial}{\partial t}\left(\alpha_q\rho_q\right) + \nabla\left(\alpha_q\rho_q\bar{\upsilon}_q\right) = S_{\alpha_q} + \sum_{p=1}^{n}\left(\dot{m}_{pq} - \dot{m}_{qp}\right)\right], \quad (1)$$

мұндағы q және p әр түрлі фазалардың көрсеткіштері. ρ_q – тығыздық; α_q – көлемдік үлес; $\bar{\upsilon}_q$ – толық қозғалыс жылдамдығы; $S_{\alpha q}$ – фазалық ауысу кезінде энергия көзіне жауапты элемент; $\dot{m}_{pq}$ және $\dot{m}_{qp}$ сәйкесінше массаның p фазасынан q фазасына және q фазасынан p фазасына ауысуы. Массалық ауысу және $S_{\alpha q}$ Ли моделі арқылы есептеледі. $S_{\alpha q}$ сұйық пен газ арасындағы энтальпия айырмасының және фазаның массалық үлесінің көбейтіндісі ретінде есептеледі.

Навье-Стокс түріндегі импульстің сақталу теңдеуі былай жазылады:

$$\frac{\partial}{\partial t}\left(\rho\bar{\upsilon}\right) + \nabla\left(\rho\bar{\upsilon}\cdot\bar{\upsilon}\right) = -\nabla p + \nabla\left[\mu\left(\nabla\bar{\upsilon} + \nabla\bar{\upsilon}^{T}\right)\right] + \rho\bar{g} + \bar{F}, \quad (2)$$

мұндағы F ағынға әсер ететін сыртқы күштерді білдіреді; g гравитацияның үдеуін білдіреді (9,81 м/с²); p – қысым.

Энергияның сақталу теңдеуі келесі түрде жазылады:

$$\frac{\partial}{\partial t}\left(\rho E\right) + \nabla\left(\bar{\upsilon}(\rho E + p)\right) = \nabla\left(k_{eff}\nabla T - \sum_q\sum_j h_{jq}\bar{J}_{jq} + \left(\bar{\bar{\tau}}_{eff}\bar{\upsilon}\right)\right) + S_h, \quad (3)$$

мұндағы E – жалпы энергия; k_{eff} – молекулалық және турбуленттік жылу өткізгіштіктің жалпы коэффициенті; T – температура; h_{jq} – j-ші бөлшектің меншікті энтальпиясы; J_{jq} – j-ші бөлшектің диффузиялық ағыны; S_h – сәулеленудің жылу ағыны; τ_{eff} – молекулалық және турбуленттік кернеулердің толық тензоры. (3) теңдеудегі оң жақтағы алғашқы үш шарт жылу өткізгіштікке, диффузияға және тұтқыр диссипацияға байланысты жылу алмасуды сипаттайды. Бұл есепте көлемдік жылу ағыны нөлге тең емес және күн радиациясымен анықталады.

VoF моделінде алынған энергия массалық өлшенген орташа мән ретінде келесі түрде есептеледі:

$$E = \frac{\sum_{q=1}^{n}\alpha_q\rho_q E_q}{\sum_{q=1}^{n}\alpha_q\rho_q}, \quad (4)$$

мұндағы толық энергия E_q келесі түрде ұсынылады:

$$E_q = h_q - \frac{p}{\rho_q} + \frac{\upsilon^2}{2}, \quad (5)$$

мұнда көрсетілген фазаның нақты h_q энтальпиясы меншікті жылу сыйымдылығы мен екі фазаның орташа температурасы негізінде есептеледі.

Сұйықтық пен буды массалық тасымалдауға арналған Ли моделі (булану/конденсация) бу тасымалдау теңдеулеріне негізделген және келесі түрде ұсынылған:

$$\frac{\partial}{\partial t}\left(\alpha_v\rho_v\right) + \nabla\left(\alpha_v\rho_v\overline{\upsilon_v}\right) = \dot{m}_{lv} - \dot{m}_{vl}. \quad (6)$$

Мұнда v таңбашасы буды, ал l – сұйықты білдіреді. Теңдеудің оң жағында массаның сұйықтан буға (булану) және будан сұйыққа (конденсация) өтуі көрсетілген. Әрбір жеке ұяшықта осы процестердің бірі нөлге тең болады. Булану немесе конденсация қанығу температурасына байланысты өзгереді. Сұйықтық температурасы қанығу температурасынан асқанда булану жүреді. Бу температурасы қанықкан температурадан төмен болса, конденсация басталады.

Булану жағдайында $\dot{m}_{lv}$ мына формула бойынша есептеледі:

$$\dot{m}_{lv} = coeff\cdot\alpha_l\rho_l\frac{(T_l - T_{sat})}{T_{sat}}. \quad (7)$$

Конденсация жағдайында $\dot{m}_{lv}$ келесі формула бойынша есептеледі:

$$\dot{m}_{lv} = coeff \cdot \alpha_v \rho_v \frac{(T_{sat} - T_v)}{T_{sat}}. \quad (8)$$

(7) теңдеуде сұйықтық параметрлері, ал (8) теңдеуде газ параметрлері қолданылады. Coeff – қолмен орнатылған тұрақты коэффициент және уақыт бойынша релаксация коэффициентін білдіреді. Бұл коэффициент фазалық ауысу жылдамдығын реттейді және тәжірибелік деректерге немесе теориялық болжамдарға сәйкес сандық нәтижелерді таңдау негізінде анықталады.

Осы формулалардан (7) және (8) кейін (1) теңдеуде болатын S_{aq} жылу көзі анықталады. Ол үшін масса алмасу жылдамдығы ($\dot{m}_{lv}/\dot{m}_{vl}$) жасырын жылуға (энтальпия) көбейтіледі. Булану процесі кезінде (1) теңдеудегі S_{aq} бастапқы термині жылу сіңіргіш қызметін, ал конденсация кезінде жылу көзі ретінде қызмет етеді. Энтальпия сұйықтықтың буға өтуін бастау үшін қанша қосымша жылу қажет екенін көрсетеді. Бу жағдайында ол қайтадан сұйықтыққа айналғанда қанша энергия бөлінетінін көрсетеді.

Жоғарыда айтылғандай, энергияны сақтау теңдеуінде (3) көлемдік жылу ағынына жауапты термин күн радиациясымен анықталады. Бұл жұмыста күн радиациясының үлгісі ретінде Росселанд радиациялық моделі пайдаланылды. Бұл жағдайда осы модельде тұрақты температураны пайдалану әдеттегідей болды. Дегенмен, бағдарламалық қамтамасыз етудің функционалдығы аймақтың географиялық координаттарын орнатуға мүмкіндік береді және бағдарлама аймаққа байланысты күн радиациясының профилін автоматты түрде қосады.

Күн радиациясының бұл моделі ең қарапайым және тұрақты болып саналады. Радиацияның диффузиялық жуықтауы ретінде де белгілі Росселанд жуықтауы оптикалық тығыз ортада қолданылады және оптикалық қалыңдығы 3-тен асатын мәселелер үшін қолайлы. Бұл болжам күн дистилляторын модельдеу кезінде қолданылған.

Жоғарыда келтірілген (3) теңдеуде будың меншікті энтальпиясы идеалды сығылмайтын газ гипотезасы арқылы келесі түрде анықталады:

$$h = \sum_j Y_j h_j + \frac{p}{\rho}, \quad (9)$$

мұндағы Y – j-ші бөлшектің массалық үлесі, ал h_j – сезілетін жылу, соның ішінде меншікті жылу сыйымдылығымен байланысты энтальпияның өзгеруі.

Жалпы жағдайда (9) өрнек келесі түрде беріледі:

$$h = C_p T + \frac{p}{\rho} \quad (10)$$

Шекаралық шарттар қойылымы

Корпус пен әйнек арқылы өтетін конвективтік жылу жоғалулардың жылу беру коэффициенті Ньютон-Рихманның классикалық формуласымен анықталады:

$$q = h_{ext}(T_{ext} - T_w), \quad (11)$$

мұндағы ext индексі сыртқы ортаны білдіреді, мұнда h – қоршаған ортамен конвективтік жылу алмасу коэффициенті, ал T – бет пен сыртқы орта үшін индекстері бар температура. Бұл шамалардың мәні жоғарыда сипатталған физикалық қойылымға сәйкес қолмен орнатылады.

Адиабаталық режимде жұмыс істейтін абсорбер үшін теңдеудегі жылу ағыны q нөлге тең:

$$T_w = \frac{q\Delta n}{k_s} + T_s, \quad (12)$$

мұндағы Δn – қатты дененің бетінен центріне дейінгі қашықтық, k – материалдың жылу өткізгіштік коэффициенті, s индексі – қатты дененің өзін білдіреді, ал w индексі – осы қатты

дененің беті. Сонымен (12) теңдеу беттің температурасы дененің ішіндегі температураға тең екенін көрсетеді, ол жылуды жоғалтпайтын адиабаталық жағдайларға сәйкес келеді.

Күн дистилляторының кабинасындағы бу ретсіз қозғалады, оның үстіне Re және Pr саны сияқты өлшемсіз шамалардың мәні шекті мәндерден асып түседі. Сондықтан кабинаның ішіндегі екі фазалы ағын турбулентті режимде жүреді. Турбулентті ағынды модельдеу үшін таңдалған тәсіл RANS, Рейнольдс бойынша орташа алынған Навье-Стокс теңдеулерінің жүйесі болды. Күн дистилляторы кабинасының шектеулі кеңістігіне байланысты k−ε турбуленттілік моделі k−ω үлгісімен салыстырғанда тұрақтырақ және бастапқы жағдайларға сезімталдығы төмен. Осы екі RANS қосалқы үлгілері арасында салыстыру жүргізілді, өйткені олар турбуленттік кинетикалық энергияны және осы энергияның жылуға диссипациясын қамтиды, бұл жылу беру мәселелеріне өте қолайлы. Өз кезегінде, k−ε моделінің үш белгілі нұсқасы бар: стандартты, RNG және realizable. Бұл мәселе үшін realizable k−ε моделі таңдалды, себебі ол құйынды құрылымдарды және сұйықтық қабаттарының бөлінуін барынша дәл сипаттайды, сонымен қатар физикалық негізделген және негізгі физикалық шектеулерді қанағаттандыратын жақсартылған диссипация теңдеуін қамтиды. Realizable k-ε пайдалану арқылы турбулентті тұтқырлық үшін өрнекті осы нақты тапсырманың негізгі болжамдары негізінде түзету коэффициенті арқылы реттеуге болады. Сондықтан турбулентті ағындардың кең ауқымы, соның ішінде дистиллятор ішіндегі екі фазалы ағын үшін realizable k−ε басқа k−ε модификацияларымен салыстырғанда қолайлы нәтижелерді көрсетеді.

Рейнольдс бойынша орташа алынған Навье-Стокс теңдеулерінен алынған турбуленттілік кинетикалық энергиясының теңдеуі келесідей:

$$\frac{\partial(\rho k)}{\partial t}+\frac{\partial(\rho k u_j)}{\partial x_j}=\frac{\partial}{\partial x_j}\left[\left(\mu+\frac{\mu_t}{\sigma_k}\right)\frac{\partial k}{\partial x_j}\right]+G_k+G_b-\rho\varepsilon-Y_M+S_k, \quad (13)$$

мұндағы G_k – орташа жылдамдық градиентіне байланысты турбуленттік кинетикалық энергияның генерациясына жауапты термин, G_b – қалқымалы күштің әсерінен турбуленттік кинетикалық энергияның ұқсас генерациясы, Y_M – турбулентті ағынның сығылу әсеріне жауапты термин, S_k – энергия теңдеуінің бастапқы термині, оны қарастырып отырған мәселеге байланысты пайдаланушы анықтайды.

Турбуленттік кинетикалық энергияның диссипациясының теңдеуі келесі түрде жазылады:


$$\frac{\partial(\rho\varepsilon)}{\partial t}+\frac{\partial(\rho\varepsilon u_j)}{\partial x_j}=\frac{\partial}{\partial x_j}\left[\left(\mu+\frac{\mu_t}{\sigma_\varepsilon}\right)\frac{\partial\varepsilon}{\partial x_j}\right]+\rho C_1 S\varepsilon-\rho C_2\frac{\varepsilon^2}{k+\sqrt{\upsilon\varepsilon}}+C_{1\varepsilon}\frac{\varepsilon}{k}C_{3\varepsilon}G_b+S_\varepsilon \quad (14)$$

мұндағы C_1 және $C_{1\varepsilon}$ стандартты тұрақты коэффициенттер, S – қарастырылып отырған тапсырмаға байланысты пайдаланушы белгілеген энергия көзі. Ұсынылған (13) және (14) теңдеулерде өлшемсіз параметр σ турбулентті Прандтль саны болып табылады.

Жұмыс авторлары k−ε әртүрлі модификацияларын қолданып есептеулер жүргізді. Түрлі k−ε турбуленттілік модельдерін салыстыру бұл модельдің дәлірек және физикалық негізделген нәтижелерді беретінін көрсетті.

Модельдеу процесі

3-суретте бір және екі көлбеу күн дистилляторлары үшін ANSYS Fluent бағдарламалық құралында құрылған есептеу торлары көрсетілген. Ұсынылған мәселеде жүйеге түсетін және шығатын сұйықтық ағындары жоқ, күн радиациясының қыздыруынан болатын табиғи булану процесі қарастырылады. Дистиллятордың ішінде болып жатқан физикалық процестердің толығырақ визуализациясын алу үшін есептеу торының жоғары сапасын қамтамасыз ету қажет. Бір және екі көлбеу күн дистилляторларының күрделі геометриялық конфигурациясына байланысты торды құру кезінде текше ұяшық (тор), тетраэдрлер немесе олардың комбинациясы автоматты түрде пайдаланылады. Қабырғалардың жанында жылдамырақ нәтиже алу үшін тор көп майдаланбаған. Ең үлкен кеңістіктік элемент өлшемі (ұяшық) тор сапасын жақсарту үшін элементті тегістеу жоғары деңгейге орнатылған 0,02 м. 3-суреттен дистилляторлардың үшбұрышты геометриясына байланысты есептеу торына аралас элементтер кіретінін көруге болады. Мысалы, өтпелі аймақтарда тетраэдрлік элементтердің болатыны анық.



Сурет 3 – Екі конфигурация үшін есептеу торы

Кесте 1 – Тордың сипаттамасы

Сипаттама	Бір көлбеу күн дистилляторы	Екі көлбеу күн дистилляторы	Сапалы тор үшін қолайлы мәндер
Теориялық көлем	0,8388 м^3	0,8376 м^3	-
Бағдарламадағы көлем	0,83848 м^3	0,83696 м^3	-
Максималды арақатынасы	2,8	4,982	<5
Элементтің минималды сапасы	0,668	0,337	0(идеал)<x<1(жаман)
Минималды ортогональды сапасы	0,71	0,572	0(жаман)<x<1(идеал)
Максималды асимметрия	0,513	0,723	<1


Тордың сапасын бағалау үшін 1-кестеде келтірілген параметрлер қолданылды. Бұл тордың жоғары сапасын растайды, кейінгі есептеулер үшін жеткілікті. Есептеу торын тексергеннен кейін шекаралық шарттар орнатылып, сипатталған физикалық модельге сәйкес материалдар мен олардың термодинамикалық қасиеттері анықталды.

Нәтижелер мен талқылау

Қарастырылып отырған екі күн дистилляторының конфигурациялары үшін дистиллятор кабинасының ішкі көлемі мен ортаңғы жазықтықтағы жылдамдық өрісін, сондай-ақ осы дистилляторлардағы будың мөлшерін салыстыру жүргізілді. Алынған нәтижелерді визуализациялау және табиғи булану процесінің эволюциясын көрсету үшін уақыт бойынша үш нүкте таңдалды, атап айтқанда бастапқы кезең, есептеудің ортасы және соңғы уақыт қадамы. Екі конфигурация үшін де 89 есептеу қадамдары қарастырылды. Талдау үшін негізгі нүктелер ретінде 1-ші, 44-ші және 89-шы қадамдары таңдалды.

4-суретте бастапқы уақыттағы күн дистилляторының кабинасындағы температураның таралуы көрсетілген. 4-суреттен көрініп тұрғандай, температураның біртіндеп өзгеруі

байқалады. Қазірдің өзінде бірінші қадамда температураның 300 К-ден 284 К-ге дейін төмендеуі байқалады, бұл фазалық ауысуға қосымша энергияның жұмсалуымен түсіндіріледі. Жоғарыда айтылғандай, бұл қосымша энергия нақты энтальпиялардағы айырмашылыққа байланысты.




Сурет 4 – 1-ші және 89-шы уақыт қадамдарындағы
бір көлбеу күн дистилляторының қабырғасының температурасы

4-суретте сонымен қатар соңғы, 89-шы уақыт қадамындағы температураның таралуы көрсетілген. Алынған нәтижелер бойынша 89-қадамда температура тұрақтанды. Температураны тұрақтандыруға қажетті уақыт аралығы шамамен 5–6 қадамды құрайды, бұл модельдеу кезінде қарқынды булану процесіне байланысты. Температура өрісі үшін алынған графиктер физикалық тұрғыдан дұрыс және теориялық күтулерге сәйкес келеді. Көріп отырғаныңыздай, әйнек беттерінде және қабырғалардағы температура дистиллятордың ішкі бөлігіне қарағанда жоғары. Сондай-ақ, судың буланuы кезінде сіңіргіш пластинаның температурасы бірте-бірте көтеріле бастайтынын байқауға болады, бұл бірінші және соңғы қадамдарды салыстыру кезінде анық көрінеді. Әйнек беттерінің көлбеу орналасқан ішкі бөлігінен жиналған конденсацияланған суды жинауға арналған науалар конденсаттың кері буланuын болдырмау үшін салқын болуы керек.

5-суретте ортаңғы қимадағы 1-ші, 44-ші және 89-шы уақыт қадамындағы жылдамдық векторлары көрсетілген. Бірінші реттік қадамда судың беткі қабаттарының буланuы кезінде жылдамдық өрісінің өзгеруінен туындаған құйындылар анық көрінеді. Қозғалыс бағыты жоғары, оны жылдамдық векторларынан көруге болады. Қалқымалы әсердің арқасында су буы жеңіл болғандықтан дистиллятор кабинасының жоғарғы қабаттарын басып алуға бейім. Құйындар байқалатын орындар қарқынды бу түзілу көрсеткіші болып табылады, өйткені газдардың қозғалысы жылу әсерінен болады. 44-ші уақыт қадамында құйындылардың өлшемдері ұлғаяды, ағынның жылдамдығы да артады. Бұл кезеңде бу локализацияланбай, судың бүкіл беті бойынша біркелкі ағындармен қозғалады. Қабырғалар бойындағы векторлар будың жоғары қарай қозғалысын көрсетеді, бұл теориялық болжамдарға сәйкес келеді.

89-шы уақыт қадамында су буы дистиллятордың жоғарғы бөлігінде шоғырланған, онда хаотикалық қозғалыс байқалады. Жоғарыда жазылғандай, бұл жағдайда конденсацияны модельдеусіз тек булану қарастырылады. Яғни, булану мен конденсация бөлек модельденеді. Су буы құрылғының үстіңгі жағынан кете алмайды, өйткені дистиллятор толығымен оқшауланған. Бұл қондырғының жоғарғы бөлігінде құйындылардың қарқынды қалыптасуына әкеледі. Дистилденген суды жинауға арналған науалар айналасында 1-ші және 89-шы уақыт қадамдарында құйынды қозғалыстар да байқалады. Бұл науалар кедергі ретінде әрекет ететіндіктен және олардың айналасында су буы ағып жатқанда олардың айналасында құйындылар пайда болады.




Сурет 5 – Бір көлбеу күн дистилляторы үшін 1-ші, 44-ші, 89-шы уақыт қадамдарындағы жылдамдық векторларының өрісі

6-суретте күн дистилляторының ішіндегі су буының көлемдік үлестерінің өзгеруі көрсетілген. Алынған сандық нәтижелерге сәйкес, уақыттың бастапқы моментінде тұзды су мен ауаның шекарасында су буы жергілікті түрде түзілетіні анық. Бұл нәтижелерді 5-суретте келтірілген бастапқы моменттің нәтижелерімен салыстыратын болсақ, бұл аймақта төменгі температура тіркелгенін көреміз, бұл энтальпиялар айырмашылығымен расталады. 6-суретке сәйкес, 44-ші уақыт қадамында су буының көлемдік үлесі артып, бірте-бірте көтеріледі. Бұл кезеңде сұйықтықтың барлық бос бетінде булану процесі жүреді. 89-шы уақыт қадамында


будың негізгі бөлігі дистиллятордың жоғарғы бұрышында шоғырланған. Конденсация процесі ескерілмесе, будың бұл әрекеті физикалық түрде негізделген. Теориялық тұрғыдан алғанда, әйнек бетімен жанасатын бу дистиллятордың жоғарғы жағына жетпей конденсациялануы керек деп есептелді. Дегенмен, алынған нәтижелер берілген жүйедегі бу әрекетінің ықтимал үлгілерінің бірі ретінде мағынасы бар.

Әрі қарай, біз екі көлбеу күн дистилляторы үшін есептеу нәтижелерін ұсынамыз, мұнда бастапқы және шекаралық шарттарды ескере отырып, барлық шешуші параметрлері бір көлбеу нұсқасымен бірдей.



Сурет 6 – Бір көлбеу күн дистилляторы үшін 1-ші, 44-ші, 89-шы рет қадамдарындағы су буының көлемдік үлесі


7-суретте екі көлбеу күн дистилляторының корпус қабырғасының температуралық таралуы көрсетілген. Екінші конфигурациядағы әйнек бетінің үлкен ауданына байланысты, дистиллятор кабинасына көбірек күн радиациясы түседі және сәйкесінше, бастапқы температура бірінші нұсқаға қарағанда жоғары. Бұл ретте әйнектің температурасы жоғарырақ жылу өткізгіштікке және сыртқы ортамен жанасу бетіне байланысты бір көлбеу нұсқаға қарағанда айтарлықтай төмен. 10–12 уақыт қадамынан кейін қабырғаның температурасы төмендей бастайды. Бұл фазалық ауысуды жүзеге асыру үшін меншікті энтальпиялар айырмашылығына тең қосымша жылу қажет болатындығына байланысты. Осылайша, қарқынды булану кезеңінде температураның айтарлықтай төмендеуі орын алады. Соңғы кезеңдегі температураның таралуы теориялық болжамдарға сәйкес келеді, орнату контуры бойынша максималды температура мәндері, әсіресе суы бар аймақта.



Сурет 7 – 1-ші және 89-шы уақыт қадамындағы екі көлбеу күн дистилляторының қабырға температурасы


8-суретте қос көлбеу күн дистилляторының ортаңғы бөлігіндегі жылдамдық векторларының таралуы көрсетілген. Бірінші рет қадамында, дәл 5-суреттегідей, векторлардың жоғары бағытталғаны анық, өйткені су буы дистиллятордың ең жоғары нүктесіне, бұрыштық бөлігіне көтеріледі. Су бетінің жанында қарқынды булану нәтижесінде пайда болатын күшті құйындылар пайда болғаны байқалады. Уақыттың бастапқы кезеңінде жылдамдық векторларының өрісі көрсетілген екі конфигурация үшін дерлік бірдей. 44-ші уақыт қадамында негізінен су бөліктеріне іргелес аумақтарда шоғырланған құрылымды құйындылардың қалыптасуы байқалады, бұл ретте ағынның жылдамдығы артады. 89-шы уақыт қадамында құйынды құрылымдар тұрақты күйге жетеді. Егер 89-шы уақыт қадамының нәтижелерін (5-сурет) бір көлбеу нұсқасымен салыстыратын болсақ, онда екі көлбеу нұсқадағы су буының әйнек бетіне шөгіп, қондырғының жоғарғы бұрыштық бөлігіне көтерілмейтінін көруге болады. Бұл екі

көлбеу дистиллятордағы жұмыс температурасының жоғары болуына байланысты. Екі көлбеу дистиллятордың жартысын талдағанда, векторлардың таралуы бір көлбеу конфигурацияға ұқсас екенін атап өтуге болады, тек нәтижелер бірнеше қадамға кейінге қалдырылады. Бұл қос көлбеу дистилляторды одан әрі зерттеу үшін симметриялы жүйені қабылдау арқылы есептеулерді жеңілдетуге болатынын көрсетеді.



Сурет 8 – Екі көлбеу күн дистилляторы үшін 1-ші,
44-ші және 89-шы уақыт қадамдарындағы жылдамдық векторларының өрісі


9-суретте екі көлбеу қондырғыдағы су буының көлемдік үлесінің уақыт бойынша таралуы көрсетілген. 6-суретте алғашқы қадамда көрсетілген сандық нәтижелермен салыстырғанда, 9-суретте алғашқы қадамындағы булану судың бүкіл бетінде біркелкі болады.



Сурет 9 – Екі көлбеу дистиллятор үшін 1-ші, 44-ші,
89-шы рет қадамдарындағы су буының көлемдік үлесі

Бұл екі көлбеу дистиллятордың әйнек бетінің арқасында күн радиациясының су бетіне және сәйкесінше сіңіргіш пластинаға біркелкі түсуімен түсіндіріледі. 44-ші уақыт қадамында, бір көлбеу корпустағы сияқты (6-сурет), екі көлбеу корпуста су буы дистиллятордың жоғарғы бұрыш бөлігін басып алуға ұмтылады. Ал 89-шы уақыт қадамында екі көлбеу корпусы үшін су буы дистиллятордың ең жоғарғы бұрышына көтерілмейді. Бұл құбылыс әйнек аймағының айтарлықтай үлкен болуымен түсіндіріледі, ал оның жылу өткізгіштігі жоғары. Нәтижесінде әйнек жанында суық ауа қабаты пайда болады, ол будың жоғары қарай жылжуына кедергі жасайды. Нәтижесінде бу тек температураның айтарлықтай артуы мүмкін жерлерде ғана шоғырланған.

10-суретте бір көлбеу және қос көлбеу дистилляторлар үшін модельдеудің соңғы сатысындағы ағын сызықтары көрсетілген. Бір көлбеу дистиллятор үшін анағұрлым айқын және ұйымдасқан құйынды құрылымдар байқалады, ал қос көлбеу дистиллятор үшін бу қозғалысы үлкен хаоспен және жылдамдықтың төмендеуімен сипатталады. Негізгі ағындар мен құйындылардың аймақтары су алатын бөліктердің жанында шоғырланған.



Сурет 10 – Бір және екі көлбеу дистилляторлар үшін 89-шы уақыт қадамындағы ағын сызықтары

Қорытынды

Екі күн қондырғысының конфигурациясын талдау қос көлбеу қондырғының бірқатар артықшылықтарға ие екенін көрсетті. Атап айтқанда, жоғары температура және будың көтерілуін тежейтін құйындардың аз болуы, нәтижесінде бүкіл бет бойынша біркелкі булануды қамтамасыз етеді. Бір еңісті қондырғы барлық кезеңдерде күшті құйындардың түзілуін көрсетеді, бұл булану процесін баяулатады, бірақ салқын климатқа қолайлы. Екі жағдайда да құйындар су қабылдайтын бөліктердің жанында шоғырланып, жүйенің термодинамикасына әсер етеді. Модельдің негізгі кемшілігі – 100 °С-тан төмен температурада булануды есепке алу үшін судың қайнау температурасын төмендету қажеттілігі, бұл реттелетін функцияларды қолдана отырып, одан әрі оңтайландыруды талап етеді. Нәтижесінде, қос еңісті конфигурация күн шуақты аймақтар үшін өнімдірек деп танылды, бірақ ондағы процестер ұзағырақ уақытты талап етеді.

Болашақ зерттеулерде әртүрлі температуралық жағдайларда булану үлгілерін оңтайландыруға баса назар аудара отырып, дистилляторлардағы термодинамикалық процестерді тереңірек зерттеу жоспарлануда. Атап айтқанда, 100 °С-тан төмен температурада булануды ескеретін дәлірек пайдаланушылық функцияларды енгізу бойынша жұмыстар жүргізіледі, бұл модельдеу дәлдігін арттырады. Сонымен қатар, әртүрлі материалдар мен дизайн ерекшеліктерінің дистилляторлардың тиімділігіне әсері зерттеледі, жылу беруді арттыру және жылу жоғалтуды азайту үшін балама жүйелерді талдау қарастырылады. Бұл әртүрлі климаттық жағдайларда күн дистилляторларының әртүрлі конфигурацияларының мүмкіндіктері мен шектеулерін тереңірек түсінуге мүмкіндік береді.

Қаржыландыру туралы ақпарат

Авторлар Ш. Есенов атындағы Каспий технологиялар және инжиниринг университетінің (Yessenov University) «Экология және геология» кафедрасына және жоба жетекшісі Самал Сырлыбекқызына жан-жақты қолдау мен осы зерттеуді жүзеге асыруға мүмкіндік берген ресурстар үшін шынайы алғысын білдіреді. Сіздердің ғылыми идеяларды дамытуға қосқан үлестеріңіз бен ұйымдастырушылық қолдауларыңыз баға жетпес болып, осы жобаның сәтті жүзеге асырылуында негізгі рөл атқарды.

Зерттеу Қазақстан Республикасы Ғылым және жоғары білім министрлігі Ғылым комитетінің гранттық қаржыландыруы аясында ИРН AP14871988 «Разработка солнечно-тепловой опреснительной установки на основе теплового насоса» жобасы бойынша жүргізілді.

ӘДЕБИЕТТЕР

1 Peter H. Gleick Water in crisis: a guide to the world's freshwater resources. – Oxford University Press, 1993. – 473 p.

2 Global Solar Atlas. URL: https://globalsolaratlas.info/ (өтініш берілген күн 29.04.2024)

3 Abhay Agrawal, Rana R.S., Srivastava Pankaj K. Heat transfer coefficients and productivity of a single slope single basin solar still in Indian climatic condition: Experimental and theoretical comparison // Resource-Efficient Technologies. – 2017. – Vol. 3. – P. 466–482.

4 Khadim M. A. A. A., Abd AL-Awahid W.A., Hachim D.M. Review on the types of solar stills // IOP Conference Series: Materials Science and Engineering. – 2020. – Vol. 928. – No. 022046.

5 Sampathkumar K., Arjunan T.V., Pitchandi P. Active Solar Distillation – A Detailed Review //Renew. Sustain. Energy Rev. – 2010. – No. 14. – P.1503–1526.

6 Rahul Dev, Tiwari G.N. Characteristic equation of a passive solar still // Desalination. – 2009. – Vol. 245. – P. 246–265.

7 Al-Karaghoulia A. A., Alnaserb W.E. Performances of single and double basin solar-stills // Applied Energy. – 2004. – Vol. 78. – P. 347–354.

8 Boubekria M., Chakerb A. Yield of an improved solar still: numerical approach // Energy Procedia. – 2011. – Vol. 6. – P. 610–617.

9 Mohamed Elashmawy An experimental investigation of a parabolic concentrator solar tracking system integrated with a tubular solar still // Desalination. – 2017. – Vol. 411. – P. 1–8.

10 Al-Doori G. F. L., Moosa I. S., and Saleh A. A. M. Enhanced productivity of double-slope solar still using local rocks // Int. J. Smart Grid Clean Energy – 2019. – Vol. 8(3) – P. 307–312.

11 Belyayev Ye., Mohanraj M., Jayaraj S. & Kaltayev A. Thermal performance simulation of a heat pump assisted solar desalination system for Kazakhstan climatic conditions // Heat Transfer Engineering. – 2018. – Vol. 40(12) – P. 1060–1072.

12 Elango C., Gunasekaran N., Sampathkumar K. Thermal modelsofsolarstill –A comprehensivereview // Renewable and Sustainable Energy Reviews. – 2015. – Vol. 47. – P. 856–911.

13 Vassilis B., Soteris K., Emmy D. Thermal Solar Desalination: Methods and Systems. – Academic Press, 2016. – 382 p.

14 Dunkle R.V. Solar water distillation: the roof type still and multiple effect diffusion still // International Developments in Heat Transfer, ASME, Proceedings of International Heat Transfer Conference, University of Colorado. – 1961. – Vol. 5 – P. 895–902.

15 Shukla S.K., Sorayan V.P.S. Thermal modeling of solar stills an experimental validation // Renewable Energy. – 2005. – Vol. 30. – P. 683–699.

16 Савельев И. В. Курс общей физики, т. 1. Механика. Молекулярная физика: Учебное пособие. – 2-е изд. перераб. – М.: Наука. Главная редакция физико-математической литературы, 1982. – С. 432.

17 Peter William Atkins, Julio De Paula, James Keeler Atkins Physical Chemistry. – Oxford University Press, 2018. – 908 p.

18 Richard C. T. The Principles of Statistical Mechanics. – Courier Corporation, 1979. – P. 660.

19 Yakubov S. & Cankurt B. & Maquil T. & Schiller P. & Abdel-Maksoud M. & Rung T. Euler-Euler and Euler-Lagrange approaches to cavitation modelling in marine applications // MARINE 2011 – Computational Methods in Marine Engineering. – 2011. – Vol. 4. – P. 544–555.

20 Yu Liu, Mikael Ersson, Heping Liu, Pär Jönsson, and Yong Gan Comparison of Euler-Euler Approach and Euler–Lagrange Approach to Model Gas Injection in a Ladle // Steel Research International. – 2019. – Vol. 90(5).

21 Amit Kumar CFD Modeling and Validation of a single slope Solar Still: Submitted in Partial Fulfillment of the Requirements for the Award of Degree of Master of Technology in Energy Engineering / Department of mechanical engineering, Malaviya national institute of technology. – Jaipur. – 2015. – 69 p.

22 ANSYS. Available online: https://ansyshelp.ansys.com/public/account/secured?returnurl=////Views/Secured/corp/v242/en/flu_th/flu_th.html

23 ANSYS Fluent software license, 23R2, ANSYS, Inc., Satbayev University, Almaty, Kazakhstan.

REFERENCES

1 Peter H. Gleick. Water in crisis: a guide to the world's freshwater resources, (Oxford University Press, 1993), 473 p.

2 Global Solar Atlas. URL: https://globalsolaratlas.info/ (date of access 29.04.2024)

3 Abhay Agrawal, R.S. Rana and Pankaj K. Srivastava (2017) Resource-Efficient Technologies, vol. 3, pp. 466–482. https://doi.org/10.1016/j.reffit.2017.05.003

4 Mohammad Abd Al Amir Khadim, Wisam A. Abd AL-Awahid and Dhafer M. Hachim (2020) IOP Conference Series: Materials Science and Engineering, vol. 928, no. 022046. https://doi.org/10.1088/1757-899X/928/2/022046.

5 Sampathkumar K., Arjunan T.V. and Pitchandi P. (2010) Renew. Sustain. Energy Rev., vol. 14, no. 6, pp. 1503–1526. https://doi.org/10.1016/j.rser.2010.01.023.

6 Rahul Dev and Tiwari G.N. (2009) Desalination, vol. 245, pp. 246–265. https://doi.org/10.1016/j.desal.2008.07.011.

7 Al-Karaghoulia A.A. and Alnaserb W.E. (2004) Applied Energy, vol. 78, pp. 347–354. https://doi.org/10.1016/S0306-2619(03)00005-9.

8 Boubekria M. and Chakerb A. (2011) Energy Procedia, vol. 6, pp. 610–617. https://doi.org/10.1016/j.egypro.2011.05.070.

9 Mohamed Elashmawy (2017) Desalination, vol. 411, pp. 1–8. https://doi.org/10.1016/j.desal.2017.02.003.

10 Al-Doori G.F.L., Moosa I.S., Saleh A.A.M. (2019) Enhanced productivity of double-slope solar still using local rocks, Int. J. Smart Grid Clean Energy, vol. 8 (3), pp. 307–312. https://doi.org/10.12720/sgce.8.3.307-312.

11 Belyayev Ye., Mohanraj M., Jayaraj S. and Kaltayev A. (2018) Heat Transfer Engineering, vol. 40(12), pp. 1060–1072. https://doi.org/10.1080/01457632.2018.1451246

12 Elango C., Gunasekaran N. and Sampathkumar K. (2015) Renewable and Sustainable Energy Reviews, vol. 47, pp. 856–911. https://doi.org/10.1016/j.rser.2015.03.054.

13 Vassilis B., Soteris K., Emmy D. Thermal Solar Desalination: Methods and Systems, (Academic Press, 2016), 382 p.

14 Dunkle R.V. (1961) International Developments in Heat Transfer, ASME, Proceedings of International Heat Transfer Conference, University of Colorado, vol. 5, pp. 895–902.

15 Shukla S.K. and Sorayan V.P.S. (2005) Renewable Energy, vol. 30, pp. 683–699. https://doi.org/10.1016/j.renene.2004.03.009.

16 Savel'ev I.V. Kurs obshhej fiziki, vol. 1. Mehanika. Molekuljarnaja fizika: Uchebnoe posobie (Moscow: Nauka. Glavnaja redakcija fiziko-matematicheskoj literatury, 1982), P. 432. [in Russian]

17 Peter William Atkins, Julio De Paula, James Keeler Atkins, Physical Chemistry, (Oxford University Press, 2018), P. 908.

18 Richard C.T. The Principles of Statistical Mechanics (Courier Corporation, 1979), P. 660.

19 Yakubov S. & Cankurt B. & Maquil T. & Schiller P. & Abdel-Maksoud M. & Rung T. IV International Conference on Computational Methods in Marine Engineering (MARINE, 2011), p. 544–555.

20 Yu Liu, Mikael Ersson, Heping Liu, Pär Jönsson, and Yong Gan. Steel Research International, vol. 90(5), no. 1800494 (2019). https://doi.org/10.1002/srin.201800494

21 Amit Kumar (2015) CFD Modeling and Validation of a single slope Solar Still: Submitted in Partial Fulfillment of the Requirements for the Award of Degree of Master of Technology in Energy Engineering. Department of mechanical engineering, Malaviya national institute of technology, Jaipur, 69 p.
22 ANSYS. Available online: https://ansyshelp.ansys.com/public/account/secured?returnurl=////Views/Secured/corp/v242/en/flu_th/flu_th.html
23 ANSYS Fluent software license, 23R2, ANSYS, Inc., Satbayev University, Almaty, Kazakhstan.

[1]Karlina Ye.,
Master student, ORCID ID: 0009-0008-2941-5775,
e-mail: kelisaveta123@gmail.com
[1]Yerdesh Ye.,
Master of Natural Sciences, ORCID ID: 0000-0001-9623-5610,
e-mail: yelnaryerdesh@gmail.com
[1,2]Baimbetov D.,
Master of Natural Sciences, ORCID ID: 0000-0002-4992-0890,
e-mail: dynmuhambet@gmail.com
[1]Jamakeyev I.,
Master student, ORCID ID: 0009-0005-9596-6944,
e-mail: jamakeyev.i@gmail.com
[3]Mohanraj M.,
Professor, ORCID ID: 0000-0003-4870-3496,
e-mail: mohanrajrac@yahoo.co.in
[1,4]*Belyayev Ye,
Associate Professor, ORCID ID: 0000-0002-7947-2179,
*e-mail: yerzhan.belyaev@kaznu.edu.kz; yerzhan.belyayev@gmail.com

[1]Al-Farabi Kazakh National University, 050040, Almaty, Kazakhstan
[2]Yessenov University, 130000, Aktau, Kazakhstan
[3]Department of Mechanical Engineering, Hindusthan College of Engineering and Technology, 641 032, Coimbatore, India
[4]Satbayev University, 050013, Almaty, Kazakhstan

NUMERICAL MODELING OF TWO-PHASE HEAT TRANSFER DURING EVAPORATION AND CONDENSATION INSIDE A SOLAR STILL

Abstract

This research presents a comparative analysis of two solar still configurations utilizing the ANSYS 2023R2 software package for computational fluid dynamics (CFD) simulations. The study employs the Volume of Fluid (VoF) model to simulate phase transitions between liquid and vapor, specifically focusing on vaporization processes. It is important to note that the VoF model used in this study primarily serves to visualize vaporization, with its numerical results aligning with theoretical expectations rather than providing practical applications. The relevance of this research is underscored by the global drinking water crisis, which drives the need to enhance the efficiency of desalination systems. Solar distillation is recognized as one of the most environmentally sustainable methods for producing clean water, making it an appropriate focus for this investigation. The primary objective of this work is to conduct a numerical analysis of the solar still, compare the performance of two different configurations, and evaluate potential modifications to improve the system's efficiency. The study simulates heat transfer processes within the distiller, the distribution of vapor volume fractions, and temperature variations over time. The findings indicate that the dual-slope configuration outperforms the single-slope configuration in terms of efficiency and productivity. Additionally, the research provides insights into the physical processes occurring within the distiller and identifies potential areas for further refinement of the system's modeling in ANSYS.

Key words: solar still, two-phase heat transfer, evaporation and condensation, ANSYS Fluent, numerical analysis.

[1]Карлина Е.И.,
магистрант, ORCID ID: 0009-0008-2941-5775,
e-mail: kelisaveta123@gmail.com
[1]Ердеш Е.Б.,
магистр естественных наук, ORCID ID: 0000-0001-9623-5610,
e-mail: yelnaryerdesh@gmail.com
[1,2]Баимбетов Д.Б.,
магистр естественных наук, ORCID ID: 0000-0002-4992-0890,
e-mail: dynmuhambet@gmail.com
[1]Джамакеев И.Б.,
магистрант, ORCID ID: 0009-0005-9596-6944,
e-mail: jamakeyev.i@gmail.com
[3]Моханрадж М.,
профессор, ORCID ID: 0000-0003-4870-3496,
e-mail: mohanrajrac@yahoo.co.in
[1,4]*Беляев Е.К.,
ассоциированный профессор, ORCID ID: 0000-0002-7947-2179,
*e-mail: yerzhan.belyaev@kaznu.edu.kz, yerzhan.belyayev@gmail.com

[1]Казахский национальный университет им. аль-Фараби,
050040, г. Алматы, Казахстан
[2]Каспийский университет технологий и инжиниринга им. Ш. Есенова,
130000, г. Актау, Казахстан
[3]Департамент инженерной механики Хиндустанского колледжа инженерии и технологий,
641 032, Коимбатор, Индия
[4]Казахский национальный исследовательский технический университет им. К.И. Сатбаева,
050013, г. Алматы, Казахстан

ЧИСЛЕННОЕ МОДЕЛИРОВАНИЕ ПРОЦЕССОВ ДВУХФАЗНОГО ТЕПЛООБМЕНА ПРИ ИСПАРЕНИИ И КОНДЕНСАЦИИ ВНУТРИ СОЛНЕЧНОГО ДИСТИЛЛЯТОРА

Аннотация

В данной статье представлен сравнительный анализ двух конфигураций солнечного дистиллятора с использованием лицензированного программного комплекса ANSYS 2023R2 и метода вычислительной гидродинамики (CFD). Для моделирования применена модель VoF (Volume of Fluid), которая позволяет рассчитывать переход жидкости из одной фазы в другую. Следует отметить, что модель VoF способна воспроизводить процессы парообразования исключительно для визуализации, без практического применения численных результатов, что соответствует теоретическим ожиданиям. Актуальность исследования обусловлена глобальным кризисом питьевой воды, что требует повышения эффективности систем опреснения. Данный метод получения чистой воды является одним из наиболее экологически безопасных, что и стало основной причиной выбора объекта исследования. Целью работы является численный анализ и исследование солнечного дистиллятора, сравнительный анализ двух его конфигураций, а также оценка возможных модификаций для повышения эффективности установки. В ходе исследования были смоделированы тепловые потоки внутри установки, а также распределение объемной доли пара и изменение температуры во времени. Полученные результаты демонстрируют более высокую эффективность и производительность двухскатной конфигурации по сравнению с односкатной. Исследование также детализирует физические процессы, происходящие внутри установки, и определяет направления для дальнейшего совершенствования моделирования данной системы в ANSYS.

Ключевые слова: солнечный дистиллятор, двухфазный теплообмен, испарение и конденсация, ANSYS Fluent, численный анализ.

Мақаланың редакцияға түскен күні: 13.09.2024

УДК 539.23:620.92
МРНТИ 29.19.16

https://doi.org/10.55452/1998-6688-2024-21-3-302-313

[1]Кейінбай С.,
постдокторант, ORCID ID: 0000-0002-7268-7193,
e-mail: s.keiinbay@kbtu.kz
[1]Нусупов К.Х.,
докт. физ.-матем. наук, главный научный сотрудник, ORCID ID: 0000-0001-8200-7510,
e-mail: rich-famouskair@mail.ru
[1]Султанов А.Т.,
докторант, ORCID ID: 0000-0003-0074-431X,
e-mail: asanalisultanovs@gmail.com
[2]Тысченко И.Е.,
докт. физ.-матем. наук, ведущий научный сотрудник,
ORCID ID: 0000-0002-9518-0651,
e-mail: tys@isp.nsc.ru
[1]Эшанов А.Ф.,
студент, ORCID ID: 0009-0003-4051-5180,
e-mail: a_eshanov@kbtu.kz
[1]*Бейсенханов Н.Б.,
докт. физ.-матем. наук, главный научный сотрудник,
ORCID ID: 0000-0002-5908-5614,
*e-mail: beisen@mail.ru

[1]Казахстанско-Британский технический университет,
050000, г. Алматы, Казахстан
[2]Институт физики полупроводников им. А.В. Ржанова
Сибирского отделения Российской академии наук,
630090, г. Новосибирск, Россия

ВЛИЯНИЕ ОТНОШЕНИЯ РАСХОДОВ ГАЗОВ N_2/Ar И МОЩНОСТИ МАГНЕТРОНА НА ПЛОТНОСТЬ И СТЕХИОМЕТРИЧЕСКИЙ СОСТАВ ПЛЕНОК TiN_x, СИНТЕЗИРОВАННЫХ МЕТОДОМ МАГНЕТРОННОГО РАСПЫЛЕНИЯ

Аннотация

Пленки нитрида титана были осаждены методом магнетронного распыления на постоянном токе на поверхности образцов монокристаллического кремния в атмосфере Ar-N_2 для использования в качестве диффузионного барьера. Толщину и плотность пленок измеряли методом рентгеновской рефлектометрии. Изменена конструкция установки MAGNA TM-200-01 для увеличения подачи азота в камеру. Изучено влияние условий распыления, включая расход газов азота и аргона и их отношения N_2/Ar в пределах 1–60 в камере, мощность магнетрона 690 – 1400 Вт на формирование пленок TiN_x, их плотность и стехиометрический состав. Показано, что на величину *x* влияет не только отношение расходов газов N_2/Ar, но и мощность магнетрона. При параметрах распыления 1200 Вт, N_2/Ar = 30, 0.8 Па, 320 сек и 100 °C получена максимальная плотность 5.247 г/см^3 пленки состава $TiN_{0.786} = Ti_{56}N_{44}$. Методом фотографической рентгеновской дифракции подтверждено наличие нанокристаллической пленки нитрида титана и отсутствие нанокристаллической фазы титана. Выявлено, что для синтеза нитрида титана, максимально близкого к стехиометрическому составу $TiN_{0.770}$ – $TiN_{0.786}$, необходимо использовать мощности магнетрона в пределах 900–1200 Вт, расход азота – 30 см^3/мин. при низких потоках аргона 1–5 см^3/мин.

Ключевые слова: тонкие пленки, диффузионный барьер, нитрид титана, магнетронное распыление, структура.

Введение

Медь является благоприятным материалом для сверхбольших интегральных схем (СБИС) из-за низкого электрического сопротивления и высокой устойчивости к электромиграции в сравнении с алюминием [1]. Однако электрические характеристики СБИС сильно ухудшаются при прямом контакте меди и кремния. Это обусловлено тем, что Cu легко диффундирует в Si или SiO_2 при относительно низких температурах [2]. Атомы меди, диффундируя в структуру кремния, образуют в запрещенной зоне кремния глубокие уровни. Это ведет к захвату неосновных носителей заряда и сокращению их времени жизни. При использовании меди в контактной системе солнечных элементов увеличение температуры отжига приводит к появлению большого количества дефектов и образованию Cu_3Si фазы. Поверхностное сопротивление пленок Cu имеет тенденцию к резкому увеличению. Все это приводит к уменьшению эффективности солнечных элементов [3, 4]. Поэтому важное значение имеет формирование диффузионного барьера между медью и кремнием для устранения процессов взаимопроникновения атомов Si и Cu и разделения двух слоев. Нанокристаллические пленки нитрида титана TiN представляют значительный интерес ввиду высокой их твердости [5]. Пленки TiN продемонстрировали уникальные оптические свойства. Блеск и цвет поверхности слоя нитрида титана зависит от пропорции атомов N/Ti, приобретая золотистый цвет, если пропорция атомов N/Ti равна 1 [6–8]. Кроме того, стехиометрические кристаллические пленки TiN с гранецентрированной кубической решеткой являются хорошими проводниками электричества и имеют низкое удельное сопротивление. В связи с этим диффузионные барьеры на основе нитрида титана находят широкое применение [9].

Условия осаждения оказывают существенное влияние на свойства и структуру пленок TiN [2, 5]. Магнетронное распыление постоянным током (DC) рассматривается как один из наиболее перспективных методов осаждения для получения стехиометрических пленок TiN [4]. Этот метод распыления обеспечивает низкое газовое загрязнение, однородность состава и хорошую адгезию между подложкой и пленками. Кроме того, можно получать пленки с различной морфологической и кристаллической структурой [10]. В некоторых работах исследовалось влияние скорости потока N_2 на структурные и оптические свойства пленок TiN, но давление в камере варьируется [11]. Представляет интерес влияние соотношения Ar/N_2 на синтез нитрида титана. При использовании реактивного распыления мишени титана в присутствии газа азота атомы титана вступают в реакцию с атомами азота, образуя пленку TiN при осаждении на поверхность. Обычно используется смесь инертного и реактивного газов ($Ar\text{-}N_2$), поскольку для эффективного распыления титана в вакуумной камере должны присутствовать ионы аргона, обладающие достаточно большой массой. Однако для реализации этого процесса важное значение имеет соотношение количества атомов азота и аргона в среде, так как при недостаточной концентрации азота синтез нитрида титана стехиометрического состава затруднителен. Следовательно, при подаче газов в вакуумную камеру важно контролировать расход газов, а не достигнутое давление, даже если увеличение расхода газа вызывает увеличение давления. TiN формируется только при соотношении расходов N_2/Ar выше некоторого значения, причем это минимальное соотношение растет при уменьшении расхода Ar. Если расход азота значительно превышает минимальное соотношение, то процесс образования нитрида титана очень стабилен, однако пленки при этом пересыщены азотом и обладают высоким сопротивлением. Удельное сопротивление пленок TiN уменьшается по мере роста величины Ar/N_2 в среде, особенно при их выращивании на подложке Si. [12]. Однако с уменьшением расхода азота стехиометрия пленок нитрида титана существенно улучшается, но по достижении минимального отношения N_2/Ar формирование фазы TiN прекращается и начинается рост пленки титана, содержащей включения несвязанного азота. Стехиометрические пленки нитрида титана имеют удельное сопротивление ~40 мкОм·см, но для их получения важно контролировать оптимальное соотношение газов в плазме.

Благодаря замечательной химической и термической стабильности и квазиметаллической проводимости нитрид титана находил применение как затворный электрод для запоминающих устройств и полевых транзисторов, в полупроводниковой промышленности, в качестве

медного диффузионного барьера и конденсаторного электрода в технологии межсоединений [13–17]. Слои TiN/SiO_2 на Si находят применение в качестве пассивирующего контакта для высокоэффективных кристаллических кремниевых солнечных элементов. В работе [18] представлен электронно-проводящий, дырочно-блокирующий контакт на основе TiN, созданный реактивным магнетронным распылением. Применение контакта SiO_2/TiN, выполняющего функции металлического электрода и пассивирующего слоя, получена эффективность 20% c-Si солнечного элемента n-типа с простой структурой.

В данной работе осуществлен синтез и исследование пленок нитрида титана, осажденных методом магнетронного распыления. Анализируется влияние условий распыления на плотность, состав и толщину осаждаемых пленок.

Материалы и методы

Для формирования контактной системы, содержащей диффузионный барьер, тонкие пленки TiN_x осаждены на пластины монокристаллического кремния с помощью установки MAGNA TM-200-01 (рисунок 1). При распылении использовались мощности магнетрона 690, 900, 1000, 1200, 1400 Вт. Продолжительность осаждения составляла 320 сек., температура подложки – 100 °C. Давление газовой смеси Ar-N_2 в камере поддерживалось в пределах 0.54–1.4 Па, а скорости подачи газов азота 15–60 $см^3$/мин. и аргона 1.0–8.33 $см^3$/мин. при различных отношениях N_2/Ar в интервале 1.8–60.0. Проведена модернизация установки MAGNA TM-200-01 для увеличения скорости подачи азота в камеру посредством замены регулятора расхода газа азота РРГ2 и корректировки в программном обеспечении для увеличения максимального расхода N_2 с 15 $см^3$/мин. до 60 $см^3$/мин. Была также изменена конструкция заслонки для работы с двумя мишенями одновременно с целью синтеза диффузионного барьера сложного состава.

Перед осаждением пленок поверхность кремниевых подложек была подвергнута трехэтапной очистке RCA, разработанной Вернером Керном в лаборатории Radio Corporation of America для очистки от органических и механических загрязнений [19]. Данный метод включает обработку в растворах $NH_4OH:H_2O_2:H_2O$ = 1:1:5 (80°C, 10 мин.), HF (1:100) (20 сек), $HCl:H_2O_2:H_2O$ = 1:1:6 (75–80 °C, 10 мин.) с последующим ополаскиванием в проточной деионизованной воде и сушке в шкафу в течение 15 минут.

Структура и фазовый состав пленок идентифицировались методом фотографической рентгеновской дифракции. Плотность и толщина пленок измерены методом рентгеновской рефлектометрии (XRR) с использованием двух спектральных линий CuK_α (0.154 нм) и CuK_β (0.139 нм) на установке Complexray C6 [20]. Микроструктура поверхности исследована на атомно-силовом микроскопе JSPM5200 Jeol Japan с применением полуконтактного (AFM AC)-метода. Горизонтальное разрешение микроскопа составляет 0.14 нм, по вертикали – 0.01 нм.





Рисунок 1 – Схема процесса напыления пленки нитрида титана (TiN)

Результаты

На рисунке 2(I) приведен спектр рентгеновской рефлектометрии пленки Ti_yN_x, синтезированной на полированной поверхности пластины c-Si при режиме, который был оптимальным для предыдущего варианта РРГ2 и получения пленки Ti_yN_x с плотностью 5.21 г/см^3: 0.54 Па, N_2/Ar = 15.0/8.33 см^3/мин = 1.8, 320 сек., 690 Вт, 100 °C. Обнаружены осцилляции Киссига, отнесенные к интерференции рентгеновских отражений в слое Ti_xN_y на Si (рисунок 2(Ia)). Замена РРГ2 привела к уменьшению их количества, а также к значительному снижению плотности пленки. Действительно, критический угол θc полного внешнего отражения был определен как угол, где интенсивность отражения составляет половину главного максимума I = I_0/2 = 120427 импульса, т.е. в данном случае 2θ_c = 0.5925°, и θ_c = 5.171 мрад (рисунок 2(Ib), таблица 1). С помощью программы Henke [23] определено, что значение θ_c соответствует значению плотности 4.41 г/см^3. Не удается оценить стехиометрию пленки Ti_yN_x, так как полученное значение ниже величин плотности нитрида титана (5.44 г/см^3) и титана (4.54 г/см^3) и предполагается содержание в пленке титана, включений несвязанного азота.

Таблица 1 – Определение плотности ρ слоя по программе Henke

Пленка	I_{max}, с$^{-1}$	I_{max}/2, с$^{-1}$	2θ_c, градус	θ_c, градус	θ_c, мрад	ρ, г/см^3
Ti_yN_x	240853	120427	0.59250	0.29625	5.171	4.41



Толщина пленки, определенная из выражения 2*d*·sinθ = λ, или *d* = λ/2θ, на основе 5 пиков для CuK_α составила ~71.7 нм (таблица 2).

Таблица 2 – Определение толщины слоя Ti_yN_x по формуле *d* = λ /2θ

Пленка	(2θ)j, градус	(2θ)i, градус	j–i	2θav=[(2θ)j – (2θ)i]/ (j – i)], градус	λ, нм	d = 57,296·λ/2θ, нм
TiyNx	1.490	0.874	5	0.1232	0.15420	71.7

Увеличение отношения расходов газов азота и аргона с N_2/Ar = 1,8 до N_2/Ar = (60.0/8.33) см^3/мин = 7.2, давления – с 0.54 Па до 1.39 Па, при прежних величинах мощности 690 Вт,

длительности 320 сек., температуры 100 °С привело к росту плотности пленки Ti_yN_x (рисунок 2(IIа), таблица 3) с 4.41 г/см^3 до 4.65 г/см^3. Действительно, угол θ_c для этой пленки составил θ_c = 5.315 мрад и соответствует плотности 4.65 г/см^3 слоя $TiN_{0.122} = Ti_{0.891}N_{0.109} = Ti_{89}N_{11}$ между плотностями Ti (4.54 г/см^3) и TiN (5.44 г/см^3). Значение x = 0.122 для состава $TiN_x = TiN_{0.122}$ определено из выражения (1):

$$x = x_1 + (x_2 - x_1)(\rho_x - \rho_1)/(\rho_2 - \rho_1). \quad (1)$$

При этом значение $x = n_N/n_{Ti}$, а TiN_1 в случае x = 1 соответствует составу стехиометрического нитрида титана и TiN_0 при x = 0 соответствует титану Ti. Таким образом, для ρ_1 = 4.54 г/см^3, ρ_2 = 5.44 г/см^3, ρ_x = 4.65 г/см^3, x_1 = 0, x_2 = 1 найдена величина x = 0.122. Из выражения $TiN_x = Ti_{1-x/(1+x)}N_{x/(1+x)}$ следует, что $TiN_{0.122} = Ti_{0.891}N_{0.109} = Ti_{89}N_{11}$, т.е. содержание атомов титана и азота составляет 89% и 11%, соответственно. Недостаточная плотность пленки может быть обусловлена осаждением пленки Ti_yN_x нестехиометрического состава.

Толщина пленки Ti_yN_x, определенная на основе 10 пиков для CuK_α и 9 пиков для CuK_β, составила 53 нм (таблица 3).

Таблица 3 – Параметры осаждения и пленок состава Ti_yN_x

рис	W, Вт	t, сек	N_2, см^3/мин	Ar, см^3/мин	N_2/Ar	P, Па	T, °C	ρ, г/см^3	d, нм	TiN_x	$TiyN_x$
2(I)	690	320	15	8.33	1.8	0.54	111	4.41	72	-	-
2(II)	690	320	60	8.33	7.2	1.39	100	4.65	53	TiN0.122	Ti89N11
3(I)	900	320	60	5.00	12	1.4	100	4.88	73	TiN0.378	Ti73N27
3(II)	900	320	60	1.00	60	1.4	100	5.02	77	TiN0.533	Ti65N35
3(III)	900	320	30	1.00	30	0.87	100	5.23	82	TiN0.770	Ti56.5N43.5
3(IV)	900	320	30	4.8	6.2	0.84	100	5.244	76	TiN0.782	Ti56.1N43.9
5(I)	1000	320	30	1.00	30	0.87	100	5.24	90	TiN0.776	Ti56.3N43.7
5(II)	1200	320	30	1.00	30	0.80	100	5.247	112	TiN0.786	Ti56.0N44.0
7	1400	320	30	1.00	30	0.80	100	4.83	145	TiN0.322	Ti75.6N24.4

Таким образом, содержание азота в пленке $TiN_{0.122} = Ti_{89}N_{11}$ оказалось низким, хотя отношение N_2/Ar = 7.2 и расход N_2 60 см^3/мин. были высокими для потока Ar 8.33 см^3/мин.

Следовательно, состав пленки зависит не только от отношения расходов газов. С одной стороны, это могло быть вызвано изменением конструкции установки и заменой регулятора расхода газа азота РРГ2, не предусмотренного для этой установки и имеющего больший диаметр трубки для подачи газа. В связи с этим были рассмотрены не только различные варианты отношения расходов газов N_2/Ar, а также увеличена мощность магнетрона.

Увеличение мощности магнетрона до 900 Вт, отношения расходов газов азота и аргона с N_2/Ar = 7.2 до N_2/Ar = (60.0/5.0) см^3/мин = 12.0, при давлении 1.40 Па, длительности 320 сек., температуре 100 °С привело к несущественному росту плотности пленки Ti_yN_x до 4.88 г/см^3 (рисунок 3(I), таблица 3). Толщина слоя $TiN_{0.378} = Ti_{72.6}N_{27.4}$ выросла с 53 нм до 73 нм при увеличении мощности с 600 до 900 Вт, несмотря на уменьшение расхода аргона в 1,7 раза.

Существенное увеличение отношения расходов газов азота и аргона с N_2/Ar = 12.0 до N_2/Ar = 60.0/1.0 см^3/мин = 60.0, при тех же значениях мощности 900 Вт, давлении 1.40 Па, длительности 320 сек., температуре 100 °С привело к значительному росту плотности пленки Ti_yN_x (рисунок 3(II), таблица 3) до 5.02 г/см^3, соответствующей составу $TiN_{0.533}=Ti_{65.2}N_{34.8}$. Толщина полученного слоя Ti_yN_x составила 77 нм.




Рисунок 3 – Спектры рентгеновской рефлектометрии пленки нитрида титана, осажденной на поверхности пластины c-Si (900 Вт, 320 сек., 100 °C):
– N_2/Ar = (60/5) см^3/мин = 12, P = 1.4 Па;
– N_2/Ar = (60/1) см^3/мин = 60, P =1.4 Па;
– N_2/Ar = (30/1) см^3/мин = 30, P = 0.87 Па;
– N_2/Ar = (30/4.8) см^3/мин = 6.2, P = 0.84 Па;
в логарифмическом (a) и натуральном (b) масштабах.

Однако изменение расхода газа азота до N_2 – 30 см^3/мин. при высоком отношении расходов газов азота и аргона N_2/Ar = (30/1) см^3/мин. = 30.0, при тех же значениях мощности 900 Вт, давлении 1.40 Па, длительности 320 сек., температуре 100 °C привело к значительному росту плотности пленки Ti_yN_x (рисунок 3(III), таблица 3) до 5.233 г/см^3, соответствующей составу $TiN_{0.770} = Ti_{56.5}N_{43.5}$. Толщина полученного слоя Ti_yN_x оказалась около 82 нм.

Увеличение расхода газа аргона до Ar – 4.8 см^3/мин. при отношении расходов газов азота и аргона N_2/Ar = (30/4.8) см^3/мин. = 6.2, мощности 900 Вт, давлении около 0.84 Па, длительности 320 сек., температуре 100 °C привело к дополнительному увеличению плотности пленки Ti_yN_x до величины 5.244 г/см^3 (рисунок 3(IV), таблица 3), которая согласно выражению (1) соответствует составу $TiN_{0.782}$=$Ti_{56.1}N_{43.9}$. Толщина пленки $Ti_{56.1}N_{43.9}$ составила 76 нм. Для формирования нитрида кремния необходим состав не менее $TiN_{0.6}$. Методом фотографической рентгеновской дифракции подтверждено наличие нанокристаллической пленки нитрида титана $TiN_{0.782}$ появлением трех линий TiN(111), TiN(200) и TiN(220) (рисунок 4). Показано отсутствие фазы титана, т.е. состав пленки TiN_x близок к стехиометрическому.





Рисунок 4 – Дебаеграмма пленки TiN_x на c-Si: 900 Вт, 320 сек., N_2/Ar = (30/4.8) см^3/мин = 6.2, P = 0.84 Па, 100 °C

Увеличение мощности до 1000 Вт при тех же значениях расхода газа азота N_2 –30 см^3/мин. и отношении расходов газов азота и аргона N_2/Ar = (30/1) см^3/мин. = 30.0, давлении 0.87 Па, длительности 320 сек., температуре 100 °C привело к небольшому росту плотности пленки Ti_yN_x (рисунок 5(I), таблица 3) до 5.24 г/см^3, соответствующей составу $TiN_{0.776}$ = $Ti_{56.3}N_{43.7}$. Толщина полученного слоя Ti_yN_x оказалась около 90 нм (таблица 3).



(I) (II)

Рисунок 5 – Спектры рентгеновской рефлектометрии пленки нитрида титана на поверхности пластины c-Si (N_2/Ar = (30/1) см^3/мин. =30, 320 сек., P = 0.87 Па, 100°C), в логарифмическом (a) и натуральном (b) масштабах: (I)-1000 Вт; (II)-1200 Вт

Увеличение мощности до 1200 Вт при высоком отношении расходов газов азота и аргона N_2/Ar = (30/1) см^3/мин. = 30.0, давлении 0.8 Па, длительности 320 сек., температуре 100 °C

привело к незначительному росту плотности пленки Ti_yN_x до 5.247 г/см^3 (рисунок 5(II), таблица 3). Толщина пленки $TiN_{0.786}$ составила 112 нм. AFM исследование микроструктуры поверхности пленки $TiN_{0.786}$ толщиной ~ 210 нм показало, что поверхность пленки 6×6 мкм является неоднородной и неровной с колебаниями высоты в пределах 16 нм (рисунок 6).




Рисунок 6 – Атомно-силовая микроскопия пленки TiN на c-Si, синтезированной методом магнетронного распыления (1200 Вт, 604 сек., N_2 – 30 см^3/мин., Ar – 1 см^3/мин., 0.8 Па, 100 °C) после осаждения

Рост расхода аргона до 4.3 см^3/мин. при мощности 1200 Вт ведет к уменьшению плотности пленки в пределах 4.83–5.2 г/см^3. Увеличение мощности до 1400 Вт приводит к снижению содержания азота до $TiN_{0.322}$ и росту толщины до 145 нм (рисунок 7, таблица 3). Дополнительные изменения расхода N_2 в интервале 25–35 см^3/мин., температуры в интервале 25–170 °C привели к уменьшению плотности и в дальнейшем нами не используются.




Рисунок 7 – Спектры рентгеновской рефлектометрии пленки нитрида титана на поверхности пластины c-Si (1400 Вт, 320 сек., N_2/Ar = (30/1) см^3/мин. = 30, P = 0.8 Па, 100 °C), в логарифмическом (a) и натуральном (b) масштабах

Как видно на рисунке 8, в случае расхода газа N_2 60 см^3/мин. (кривая 3) происходит осаждение пленки TiN низкой стехиометрии $TiN_{0.122}$ – $TiN_{0.609}$ для интервала 1 – 8.33 см^3/мин. величин расхода газа Ar. Для этих же величин мощности 900 Вт и расхода аргона наблюдается рост содержания азота в пленке нитрида титана, если расход азота N_2 составляет 30 см^3/мин. (кривая 2). Для расхода газа N_2 15 см^3/мин. (кривая 1) осаждение пленки TiN не происходит, и предполагается осаждение пленки титана, содержащей включения несвязанного азота.

Таким образом, на формирование нитрида титана влияет не только отношение расходов газов N_2/Ar в камере, но и величины мощности магнетрона. Например, для пленок $TiN_{0.122}$, $TiN_{0.378}$, $TiN_{0.533}$, осажденных при расходе азота 60 см^3/мин., содержание азота в пленке возрастает при увеличении мощности магнетрона от 690 до 900 Вт, а также при уменьшении расхода Ar и росте N_2/Ar с 7.2 до 12 и 60. Также для пленок $TiN_{0.770}$, $TiN_{0.776}$, $TiN_{0.786}$, осажденных при расходе N_2 30 см^3/мин., рост содержания азота в пленке происходит с увеличением мощности магнетрона от 900 до 1200 Вт. Однако дальнейшее увеличение мощности до 1400 Вт (рисунки 7 и 8) приводит к существенному снижению содержания азота в пленке до $TiN_{0.322}$ (таблица 3). Это может быть вызвано распадом сформированных молекул Ti-N в плазме под влиянием большой мощности. В противоположность этому чрезмерное уменьшение мощности магнетрона до 690 Вт и отношения N_2/Ar до 1.8 (рисунок 8) вследствие снижения расхода азота до 15 см^3/мин. привело к осаждению пленки титана низкой плотности 4.41 г/см^3, содержащей включения несвязанного азота.




Рисунок 8 – Зоны образования TiN и Ti при различных расходах N_2:
кривая 1 – 15 см^3/мин.; кривая 2 – 30 см^3/мин.; кривая 3 – 60 см^3/мин.

Заключение

Изучено влияние расхода N_2 в пределах (15–60) см^3/мин., Ar – (1–8.33) см^3/мин. и отношения N_2/Ar в пределах 1–60, мощности магнетрона – (690–1400) Вт на формирование нанокристаллических пленок TiN_x, их плотность и состав для создания медного диффузионного барьера. Показано, что содержание азота в пленке TiN_x, определяется не только отношением расходов газов N_2/Ar, но и мощностью магнетрона. При параметрах распыления 1200 Вт, N_2/Ar = 30, P = 0.8 Па, 320 сек., 100 °C была достигнута максимальная плотность 5.247 г/см^3 пленки состава $TiN_{0.786} = Ti_{56}N_{44}$ толщиной 112 нм, что превышает минимально допустимую плотность 5.08 г/см^3 состава $TiN_{0.6}$. Увеличение мощности магнетрона в пределах 690–1400 Вт

при продолжительности синтеза 320 сек. приводит к пропорциональному росту толщины от 65 нм до 145 нм.

Для синтеза нитрида титана $TiN_{0.770}$ – $TiN_{0.786}$ с максимальным содержанием азота необходимо использовать режимы: мощность магнетрона в пределах 900–1200 Вт, расход N_2 30 $см^3$/мин., низкие потоки Ar 1–5 $см^3$/мин. Уменьшение или увеличение мощности магнетрона и расхода азота за эти пределы приводит к недопустимому снижению содержания азота в пленке до величин $TiN_{0.122}$ – $TiN_{0.322}$ и ниже.

ЛИТЕРАТУРА

1 Petrov I., Hultman L., Helmersson U., Sundgren J.E., Greene J.E. Thin Solid Film., 1989, vol. 169, pp. 299–314. https://www.sciencedirect.com/science/article/abs/pii/004060908990713X.

2 Arshi N., Lu J., Joo Y.K., Lee C.G., Yoon J.H., Ahmed F. Mater. Chem. Phys., 2012, vol. 134, pp. 839–844. https://www.sciencedirect.com/science/article/abs/pii/S0254058412003288.

3 Istratov A.A. and Weber E. R. J Electrochem Soc, 2002, vol. 149, no. 1, p. G21. http://doi.org/10.1149/1.1421348.

4 Aljaafari A., Ahmed F., Shaalan N.M., Kumar S. and Alsulami A. Inorganics, 2023, vol.11, no. 5, p. 204. https://doi.org/10.3390/inorganics11050204.

5 Veprek S., Veprek-Heijman M.G., Karvankova P., Prochazka J. Thin Solid Film, 2005, vol. 476, pp. 1–29.

6 Kadlec S., Musil J., Vyskcil J., Surface and Coatings Technolgy, 1992, vol. 54–55 (16 November 1992), pp. 287–296. https://doi.org/10.1016/S0257-8972(09)90064-0.

7 Jiang F., Zhang T.F., Wu B.H., Surface and Coatings Technolgy, 2016, vol. 292, pp. 54–62. http://dx.doi.org/10.1016/j.surfcoat.2016.03.007.

8 Niyomsoan S., Grant W., Olson D.L., Mishra B. Thin Solid Films, 2002, vol. 415, pp. 187–194. https://doi.org/10.1016/S0040-6090(02)00530-8.

9 Patsalas P., Charitidis C., Logothetidis S., Dimitriadis C.A., Valassiades O.J. Appl. Physic, 1999, vol. 86, pp. 5296–5298. https://pubs.aip.org/aip/jap/article-abstract/86/9/5296/289131/Combined-electrical-and-mechanical-properties-of?redirectedFrom=fulltext.

10 Banerjee R., Chandra R., Ayyub P. Thin Solid Films, 2002, vol. 405, pp. 64–72. https://www.sciencedirect.com/science/article/abs/pii/S0040609001017059.

11 Kavitha A., Kannan R., Gunasekhar K.R. Journal of Electronic Materials, 2017, vol.7, pp. 1–8. http://dx.doi.org/10.1007/s11664-017-5608-4.

12 Gu P., Zhu X., Li J., Wu H., Yang D. Journal of Materials Science: Materials in Electronics, 2018, vol. 29, pp. 9893–9900. https://doi.org/10.1007/s10854-018-9031-2.

13 Fillot F., Morel T., Minoret S., Matko I., Maıˆtrejean S., Guillaumot B., Chenevier B., and Billon T. Microelectron. Eng., 2005, vol. 82, pp. 248–253. https://www.sciencedirect.com/science/article/abs/pii/S0167931705003485.

14 Echtermeyer T., Gottlob H.D.B., Wahlbrink T., Mollenhauer T., Schmidt M., Efavi J.K., Lemme M.C., and Kurz H. Solid State Electron, 2007, vol. 51, pp. 617–621. https://www.sciencedirect.com/science/article/abs/pii/S0038110107000640.

15 Lee Y.J. Mater. Lett., 2005, vol. 59, pp. 615–617. https://www.sciencedirect.com/science/article/abs/pii/S0167577X04007347.

16 Yoon D.S., Roh J.S., Lee S.M., and Baik H.K. J. Electron. Mater., 2003, vol.32, pp. 890–898. https://link.springer.com/article/10.1007/s11664-003-0206-z.

17 Park D.G., Lim K.Y., Cho H.J., Cha T.H., Yeo I.S., Roh J.S., and Park J.W. Appl. Phys. Lett., 2002, vol. 80, pp. 2514–2516. https://pubs.aip.org/aip/apl/article-abstract/80/14/2514/514810/Impact-of-atomic-layer-deposited-TiN-on-the-gate?redirectedFrom=fulltext.

18 Yang X., Liu W., Bastiani M. De, Allen T., Kang J., Xu H., Aydin E., Xu L., Bi Q., Dang H., AlHabshi E., Kotsovos K., AlSaggaf A., Gereige I., Wan Y., Peng J., Samundsett C., Cuevas A., Wolf S. De, Joule 3, 2019, pp. 1314–1327. https://doi.org/10.1016/j.joule.2019.03.008.

19 Kern W. The Evolution of Silicon Wafer Cleaning Technology. Journal of the Electrochemical Society, 1990, vol. 137, no. 6, pp. 1887–1892. https://iopscience.iop.org/article/10.1149/1.2086825.

20 Touryanski A.G., Vinogradov A.V., and Pirshin I.V. X-ray reflectometer. US Patent No. 6041098, 2000. https://patents.google.com/patent/US6041098A/en.
21 Henke B.L., Gullikson E.M., J Davis. C. In: Atomic Data and Nuclear. Data Tables 54, 2, 1993, 181 p. http://henke.lbl.gov/optical_constants/.

Благодарность/источник финансирования. Работа финансировалась МНВО РК в рамках проекта № AP22684659.

[1]Keiinbay S.,
postdoctoral researcher, ORCID ID: 0000-0002-7268-7193,
e-mail: s.keiinbay@kbtu.kz
[1]Nussupov K.Kh.,
Dr.Phys.-Math.Sc., chief researcher, ORCID ID: 0000-0001-8200-7510,
e-mail: rich-famouskair@mail.ru
[1]Sultanov A.T.,
PhD student, ORCID ID: 0000-0003-0074-431X,
e-mail: asanalisultanovs@gmail.com
[2]Tyschenko I.E.,
Dr.Phys.-Math.Sc., leading researcher, ORCID ID: 0000-0002-9518-0651,
e-mail: tys@isp.nsc.ru
[1]Eshanov A.Ph.,
student, ORCID ID: 0009-0003-4051-5180,
e-mail: a_eshanov@kbtu.kz
[1*]Beisenkhanov N.B.,
Dr.Phys.-Math.Sc., chief researcher, ORCID ID: 0000-0002-5908-5614,
e-mail: beisen@mail.ru

[1]Kazakh-British Technical University,
050000, Almaty, Kazakhstan
[2]Rzhanov Institute of Semiconductor Physics, Siberian Branch
of the Russian Academy of Sciences,
630090, Novosibirsk, Russia

INFLUENCE OF THE RATIO OF GASE CONSUMPTION N_2/Ar AND MAGNETRON POWER ON THE DENSITY AND STOICHIOMETRIC COMPOSITION OF TIN_X FILMS SYNTHESIZED BY MAGNETRON SPUTTERING METHOD

Abstract

The films of titanium nitride were deposited by direct current magnetron sputtering on the surface of single-crystalline silicon samples in an Ar-N_2 atmosphere for use as a diffusion barrier. The thickness and density of films were measured by X-ray reflectometry. The design of the MAGNA TM-200-01 installation has been changed to increase the supply of nitrogen into the chamber. The influences of sputtering conditions, including the flow rate of nitrogen and argon gases and their N_2/Ar ratios in the range of 1–60 in the chamber, magnetron power of 690–1400 W on the formation of TiN_x films, their density and stoichiometric composition, were studied. It is shown that the value of x is affected not only by the N_2/Ar gas flow rate ratio, but also by the magnetron power. At the sputtering parameters 1200 W, N_2/Ar = 30, 0.8 Pa, 320 s and 100°C, a maximum density of 5.247 g/cm^3 of a film was achieved, which corresponds to the composition $TiN_{0.786} = Ti_{56}N_{44}$. The presence of nanocrystalline film of titanium nitride and the absence of a nanocrystalline titanium phase were confirmed by photographic X-ray diffraction. It was found that for the synthesis of titanium nitride as close as possible to the stoichiometric composition $TiN_{0.770}$ - $TiN_{0.786}$, it is necessary to use magnetron power in the range of 900–1200 W, nitrogen rate of 30 cm^3/min with low argon flows of 1–5 cm^3/min.

Key words: thin films, diffusion barrier, titanium nitride, magnetron sputtering, structure.

[1]Кейінбай С.,
постдокторант, ORCID ID: 0000-0002-7268-7193,
e-mail: s.keiinbay@kbtu.kz
[1]Нусупов К.Х.,
физ.-мат.ғ.д., бас ғылыми қызметкер, ORCID ID: 0000-0001-8200-7510,
e-mail: rich-famouskair@mail.ru
[1]Султанов А.Т.,
докторант, ORCID ID: 0000-0003-0074-431X,
e-mail: asanalisultanovs@gmail.com
[2]Тысченко И.Е.,
физ.-мат.ғ.д., жетекші ғылыми қызметкер,
ORCID ID: 0000-0002-9518-0651,
e-mail: tys@isp.nsc.ru
[1]Эшанов А.Ф.,
студент, ORCID ID: 0009-0003-4051-5180,
e-mail: a_eshanov@kbtu.kz
[1]*Бейсенханов Н.Б.,
физ.мат.ғ.д., бас ғылыми қызметкер, ORCID ID: 0000-0002-5908-5614,
e-mail: beisen@mail.ru

[1]Қазақстан-Британ техникалық университеті,
050000, Алматы қ., Қазақстан
[2]А.В. Ржанов атындағы Жартылай өткізгіштер физикасы институты.
РҒА Сібір бөлімшесі,
630090, Новосибирск қ., Ресей

МАГНЕТРОНДЫ БҮРКУ ӘДІСІ АРҚЫЛЫ СИНТЕЗДЕЛГЕН TiN_x ҚАБЫҚШАЛАРЫНЫҢ ТЫҒЫЗДЫҒЫ МЕН СТЕХИОМЕТРИЯЛЫҚ ҚҰРАМЫНА N_2/Ar ГАЗ ШЫҒЫНЫНЫҢ ҚАТЫНАСЫ МЕН МАГНЕТРОННЫҢ ҚУАТЫНЫҢ ӘСЕРІ

Аңдатпа

Титан нитридінің қабықшаларын диффузиялық кедергі ретінде пайдалану үшін Ar-N_2 атмосферасында монокристалды кремний үлгілерінің бетіне тұрақты ток арқылы магнетронды бүрку әдісімен қондырылды. Қабықшалардың қалыңдығы мен тығыздығы рентгендік рефлектометрия әдісі арқылы өлшенді. MAGNA TM-200-01 қондырғысының конструкциясы камераға азот беру мөлшерін арттыру мақсатында өзгертілді. Магнетронды бүркудің алғы шарттары ретінде, азот пен аргон газдарының ағынының жылдамдығын және олардың камерадағы N_2/Ar қатынасын 1 – 60 аралығында өзгерту арқылы және магнетрондық қуаттылығы 690 – 1400 Вт аралығында болғанда TiN_x қабықшаларының түзілуіне, олардың тығыздығы мен стехиометриялық құрамына әсері зерттелді. *X*-тің мөлшеріне тек N_2/Ar газ шығынының қатынасы ғана емес, сонымен қатар магнетрон қуаты да әсер ететіні көрсетілген. 1200 Вт, N_2/Ar = 30, 0.8 Па, 320 с, 100°C бүрку параметрлерінде құрамы $TiN_{0.786}$ = $Ti_{56}N_{44}$ қабықшасының 5.247 г/см^3 максималды тығыздығы алынды. Титан нитридінің нанокристалды қабықшасының бар болуы және нанокристалды титан фазасының жоқтығы фотографиялық рентгендік дифракция әдісі арқылы расталды.Титан нитридін $TiN_{0.770}$ – $TiN_{0.786}$ стехиометриялық құрамға барынша жақын синтездеу үшін 1-5 см^3/мин аз аргон ағынында, 900-1200 Вт диапазонында магнетрондық қуатты, азот шығыны 30 см^3/мин пайдалану қажет екені анықталды.

Негізгі сөздер: жұқа қабықшалар, диффузиялық кедергі, титан нитиді, магнетрондық шашырату, құрлысы.

Дата поступления статьи в редакцию: 04.09.2024

МҰНАЙ ГАЗ ИНЖЕНЕРИЯСЫ ЖӘНЕ ГЕОЛОГИЯ
OIL AND GAS ENGINEERING, GEOLOGY
НЕФТЕГАЗОВАЯ ИНЖЕНЕРИЯ И ГЕОЛОГИЯ

UDC 912.438
IRSTI 36.01.11

https://doi.org/10.55452/1998-6688-2024-21-3-314-321

[1]*Tursyngazy D.S.,
PhD student, ORCID ID: 0009-0000-8553-9678,
*e-mail: tursynkazy.diana@mail.ru
[1]Azizov E.A.,
PhD student, ORCID ID: 0009-0000-8158-9258,
e-mail: Eldar_14_03@mail.ru

[1]Al Farabi Kazakh National University, 050040, Almaty, Kazakhstan

RESEARCH METHODS AND GEOINFORMATION MODELS OF CHANGES IN LAND RESOURCES OF ALMATY REGION UNDER THE INFLUENCE OF HOUSEHOLD WASTE

Abstract

This article deals with the solution of scientific problems, including the development of holistic conceptual models for presenting, processing and analyzing geographic information, and comprehensively assesses the extent of the impact of regional systems on many dangerous natural and artificial processes. This makes it possible to resolve the contradiction between the need to analyze the state of various territorial systems in order to prevent the occurrence of emergencies due to the influence of natural and man-made processes.On the one hand, providing information and support in decision-making, and on the other, ensuring the provision of cartographic models of transport systems risk assessment of dangerous natural and man-made processes and their mapping. Integrated environmental assessment and modeling of industrial systems. A method for mapping payment systems and assessing the health of the population. Since the city of Almaty is a large metropolis, the ecological situation is very poor. This directly affects the ecology of the City, Public Health. We manage, process data by processing GIS data. In solving upcoming environmental problems, in developing new solutions, a special data card will come to the rescue. This will lead to solving problems from this point of view. It is possible to create monitoring maps by combining space surveys and statistical data. One of the most effective aspects of GIS data is that it allows you to optimally consider problems and work in any area. From this point of view, the GIS industry is developing rapidly. In the country, this industry is developing rapidly and is gaining a lot of demand.

Key words: GIS, ArcGIS, cartography, household waste, programming, verification.

Introduction

The Almaty region is an area rich in natural resources, contributing to a high level of economic development. However, natural and economically managed resources-resources and monocultural

systems established in history have occurred without considering natural conditions, and national traditions have formed many throughout the Republic and the Almaty region.

The country's experience in the transition to a market economy, as well as analysis of the socio-economic and environmental conditions of the region, shows that the region has the opportunity to solve this problem:

- A process is underway to improve the legal and regulatory framework;
- The role of local self-government has been strengthened;
- There are conditions for economic incentives, environmental activities and resource conseration reserves;
- Create conditions for new technologies;
- The process of Environmental Education has improved [1].

The use of these and other mechanisms to encourage environmental activities will enable the region to achieve balanced and sustainable development and ensure that people have good living conditions [2].

As the experience of the Republic of Kazakhstan and other countries in organizing environmental work shows, one of the main documents determining the main directions of Nature Conservation and public health activities on the territory of the Republic is the Comprehensive Plan for Environmental Protection in the region [3].

An environmental plan is an environmental audit that aims to comprehensively determine the environmental impact of previous activities and lay the foundation for the implementation of a set of restoration measures. It contains the following documents: analyze the geography, climate, Natural Resources and socio-economic conditions of the region or city; determine the priority areas of environmental activities in the next 3–5 years, and in the future explain specific tasks, goals and objectives, deadlines for implementation, the main potential performers and planned sources of funds [4].

Literature review

The natural environment of the Almaty region of vivendo is experiencing a very high labor load from energy companies, mining and processing companies and agricultural complexes. Very unfavorable environmental conditions are developing in many areas [5]. The most dangerous symptoms of this condition are desertification, soil degradation, degradation and pollution of the water resource, and degradation and destruction of biodiversity. Under current conditions, it takes more than a year and a lot of financial resources to solve various environmental problems. To make effective and rational use of financial resources, it is necessary to determine local and priority environmental activity strategies [6].

Unfortunately, the accounting and management of man-made changes in the environment has not yet been established. It has become a dangerous system for the preservation of the «production environment» in assessing the environmental impact of production, mainly the formation of many characteristics that are man-made negative on the environment [7].

Air pollution due to limited emissions or temporarily agreed concentrations belongs to the primary pollution category and is calculated and paid according to current legislation. Polluting companies are not responsible for these changes due to economic activity. With rainwater or melt water on the soil surface, impurities are washed into surface water and groundwater, so pollution of water bodies is not taken into account. Therefore, polluting companies only pay for the storage (disposal) of solid waste, and the negative environmental impact generated during the storage (disposal) process is not subject to accounting and payment constraints.

When they enter the soil and water source, impurities accumulate and pass through the link of the nutrient chain «water-soil– plant-animal-human».

Similar photos add cleared land, which the earth users are not responsible for at all. In this regard, it is necessary to use qualitatively different accounting methods to assess anthropogenic impacts and normalize environmental quality [8].

To this end, it is necessary to conduct comprehensive regional monitoring of the environment, improve the information and methods of environmental quality control, including all objects that adversely affect environmental quality in the process of economic supervision, thereby increasing the number of natural users and thereby increasing the means of environmental protection. Relevance and inadequate research on the global environmental assessment of human environmental impacts led to the selection of topics for thesis work, the definition of research goals and objectives, taking into account the regional characteristics of secondary pollution and natural management [9].

Main provisions

Objectives and objectives of the study. The main purpose of the article is to improve the global environmental assessment system of human environmental impact, take into account the regional characteristics of secondary environmental pollution and natural management, and enhance management decision-making in the field of land use and environmental protection [10].

The set goals determine the need to solve the following tasks:

- Research on the quality of information collected and analyzed on sources of anthropogenic environmental impacts;
- Assessment of environmental conditions in the Almaty region;
- Describe the sources and recipients of primary and secondary pollution and map their flow;
- Study the development of soil erosion processes in the Almaty region;
- Analyze the regional structure of the incidence of irregular artificial structures;
- Study soil and grain response to man-made pollution and corrosion processes;
- Establish methods of normalizing the state of the environment [11].

Water and soil impurities were installed, and the flow chart was formulated, taking the source and receiving source of primary and secondary air in the Almaty region as an example. Under the influence of soil erosion, the effects of pollution and leaching on its fertility, productivity and agricultural production quality have been identified. This paper analyzes economic mechanisms for improving environmental management based on the principle of «polluter (spoiler) payment» and economic incentive tools for reducing pollution, and shows that their implementation has increased the interest of companies that make environmental investments at their own expense [12]. The theoretical significance of this study is to deepen our understanding of the negative environmental effects of anthropogenic activities. On this basis, the concept of the relationship between environmental quality-forming factors has been proposed so that the proportion of individual sources of anthropogenic impact to the total environmental load can be determined [13].

Methods and materials

Research results can be used by government agencies at the federal and regional levels. At the federal level, recommendations on improving environmental statistics and a radical approach to global environmental assessment that takes into account the human impact of secondary environmental pollution in the EIA process are presented [14].




Figure 1 − Binding a map to a coordinate system

- Collect, analyze and evaluate sources of information;
- Study the occurrence of the area to be mapped in the map material; the process of compiling the first vector layer (shapefile) and starting editing work is shown in Figure 3.




Figure 2 − Development and editing of vector layers




Figure 3 − Preparing the card for printing

Results and Discussion

If the first version of the finished paper does not meet the customer's requirements, another version will be developed. At the stage of preparing the same paper for printing, small printing works begin [15]. All this work on preparing the map concerns the stage of preparing the map for printing. In other words, it is the use of printing or other methods of processing or copying the finished paper. This step includes preparing the print version and the parts used to print the card [16]. The results obtained in the implementation of these steps on the diploma are shown in Figure 5. In cartographic production, maps are developed by several teams of specialists, and therefore this task requires scientific and technical guidance, called map editing. The process of checking the work at all stages is called proofreading [17].




Figure 4 − Production map of Almaty region

1. Timely and reliable information should be used as a scientific basis for decision-making regarding public facilities [18].

Medical data is useless. They become important only if they are carefully analyzed, explained and serve as the basis for balanced and informed decisions. This situation indicates the need to create a soft algorithmi DBK that plays an important role in the development of eHealth and aims to ensure continuous improvement of medical information systems [19].

- Cartogram method (used to represent the population density of administrative districts, and the higher the accuracy of the cartogram, the smaller the range of cells;

- Separation method (lines of the same population density (isodem) are not used much, and a linear diagram of the sedimentation field potential is widely used to show the mutual proximity (distance) of the population in a given area) [20].




Figure 5 − Demographic map of Almaty region




Figure 6 − Map of environmental zoning of Almaty region

Conclusion

The article is devoted to the development, analysis and development of general conceptual models for solving scientific problems, including for a comprehensive assessment of the regression of a number of hazardous natural and technological processes in the Astrakhan region. This allows you to resolve conflicts, provide information and support in making administrative decisions, and also provides an analysis of the state of various territorial systems affecting natural and technological processes.

1. The road leading to the Almaty region passes using geographical information. An assessment of its significance and impact on natural and technological risks has been carried out.

2. A map of the development of animal husbandry, vegetable growing and vegetable growing in the region has been developed. The process of mapping statistical data in the form of charts and histograms to display data.

3. The natural and technological condition of the territory was analyzed. A map of natural minerals has been compiled. When developing the field, we will use information from the National Atlas of the Republic of Kazakhstan. In this regard, we are conducting research.

4. An industrial map of the Almaty region has been created. In the short term, the company conducts statistical analysis of industry data and manufactured products.

5. Natural and technological threats have a huge impact on human health. Accordingly, in the last part we have plotted the state of health, morbidity, population development and environmental conditions based on statistical and geometric data.

REFERENCES

1 Antonova Zh.A. Soil cartography: an educational and methodological guide. Ul'janovsk, 2014, 102 p.
2 Konovalova T.I. Landscape and interpretive mapping, 2005, 424 p.
3 Trubina L.K. Geoinformation systems. Sibir, 2002, 69 p.
4 Burrough P.A. Principles of GeographicalInformation Systems. Oxford University Press, New York, 2016, 190 p.

5 Sabirova A.I. Land relations in the Republic of Kazakhstan: Analysis and recommendations. Almaty, 2001, 174 p.
6 Kapralov E. G. Publishing center “Academy”, 2005, 480 p.
7 Berljant A. M. Doctor of Cartography: teacher for universities, 2003, 477 p.
8 Berljant A.M. Cartography: Textbook for universities, 2002, 336 p.
9 Dubinin M. Ju. Web GIS. Computer, 2008, 749 p.
10 Abdullin R.K. Perm State National Research University. Perm, 2020, 132 p.
11 Marcin L. Conversion between cartesian and geodetic coordinates on a rotational ellipsoid by solving a system of nonlinear equations, 2021, 145 p.
12 Hofmann-Wellenhof B. GPS theory and practice, 2018, 282 p.
13 Brad A.K. Brief History of Human Computer Interaction Technology, 2015, pp. 44–54.
14 Lur’e I.K. Introduction of GIS in the field of legal statistics in Kazakhstan, 2019, 115 p.
15 Bultanov D. Introduction of GIS in the sphere of law statistics in Kazakhstan, 2021, 154 p.
16 Berlyant A.M., Vostokova AV., Kravcova V.I. Cartography: a manual for higher education institutions, 2020, 477 p.
17 Berlyant A.M. Cartography: a manual for higher education institutions, 2002, 336 p.
18 Nikolaev V.A. Fundamentals of the doctrine of agricultural landscapes. Agro-landscape research, 2000, pp. 4–57.
19 Perelman A.I. Geochemistry of landscape, 2018, 242 p.
20 Ramazanov N.G. Geoinformation modeling and assessment of land, 2017, 34 p.

[1]*Тұрсынғазы Д.С.,
докторант, ORCID ID: 0009-0000-8553-9678,
*e-mail: tursynkazy.diana@mail.ru
[1]Азизов Э.А.,
докторант, ORCID ID: 0009-0000-8158-9258,
e-mail: Eldar_14_03@mail.ru

[1]әл-Фараби атындағы Қазақ ұлттық университеті, 050040, Алматы қ., Қазақстан

АЛМАТЫ ОБЛЫСЫ ЖЕР РЕСУРСТАРЫНЫҢ ТҰРМЫСТЫҚ ҚАЛДЫҚТАР ӘСЕРІНЕН ӨЗГЕРУІН ЗЕРТТЕУ ӘДІСТЕРІ МЕН ГЕОАҚПАРАТТЫҚ МОДЕЛЬДЕРІ

Аңдатпа

Бұл мақала географиялық ақпаратты ұсыну, өңдеу және талдау бойынша тұтас тұжырымдамалық модельдерді әзірлеуге арналған ғылыми мәселелерді шешуге, аймақтық жүйелерге көптеген қауіпті табиғи және жасанды процестердің әсер ету дәрежесін жан-жақты бағалауға бағытталған. Бұл зерттеу табиғи және техногендік үрдістердің әсерінен төтенше жағдайлардың пайда болуын болдырмау үшін әртүрлі аумақтық жүйелердің жағдайын талдау қажеттілігін шешуге мүмкіндік береді. Бір жағынан, шешім қабылдау үрдісінде ақпаратпен қамтамасыз ету және қолдау көрсету, екінші жағынан – көлік жүйелерінің картографиялық модельдерін ұсыну арқылы қауіпті табиғи және техногендік үрдістердің тәуекелдерін бағалау және оларды картаға түсіру маңызды. Сонымен қатар, өнеркәсіптік жүйелерді кешенді экологиялық бағалау және модельдеу, төлем жүйелерінің карталарын жасау және халықтың денсаулығын бағалау әдістері қарастырылады.

Тірек сөздер: ГАЖ, ArcGIS, картография, тұрмыстық қалдықтар, бағдарламалау, тексеру.

[1]*Турсынгазы Д.С.,
докторант, ORCID ID: 0009-0000-8553-9678,
*e-mail: tursynkazy.diana@mail.ru
[1]Азизов Е.А.,
докторант, ORCID ID: 0009-0000-8158-9258,
e-mail: Eldar_14_03@mail.ru

Казахский национальный университет им. аль-Фараби, 050040, г. Алматы, Казахстан

МЕТОДЫ ИССЛЕДОВАНИЯ И ГЕОИНФОРМАЦИОННЫЕ МОДЕЛИ ИЗМЕНЕНИЙ ЗЕМЕЛЬНЫХ РЕСУРСОВ АЛМАТИНСКОЙ ОБЛАСТИ ПОД ВОЗДЕЙСТВИЕМ БЫТОВЫХ ОТХОДОВ

Аннотация

Данная статья посвящена решению научных проблем, включая разработку целостных концептуальных моделей представления, обработки и анализа географической информации, и всесторонне оценивает степень влияния региональных систем на многие опасные природные и искусственные процессы. Это позволяет разрешить противоречие между необходимостью анализа состояния различных территориальных систем с целью предотвращения возникновения чрезвычайных ситуаций вследствие влияния природных и техногенных процессов. С одной стороны, предоставление информации и поддержки в принятии решений, а с другой – обеспечение предоставления картографических моделей транспортных систем, оценка рисков опасных природных и техногенных процессов и их картографирование. Комплексная экологическая оценка и моделирование промышленных систем. Метод картографирования платежных систем и оценки состояния здоровья населения.

Ключевые слова: ГИС, ArcGIS, картография, бытовые отходы, программирование, верификация.

Article submission date: 11.02.2024

UDC 912.438
IRSTI 36.01.11

https://doi.org/10.55452/1998-6688-2024-21-3-322-330

[1]Tursunbek Zh.B.,
PhD student, ORCID ID: 0009-0003-3480-3856,
e-mail: zhuldyzay.tursynbek@mail.ru

[1]Al Farabi Kazakh National University, 050040, Almaty, Kazakhstan

MONITORING THE GEODYNAMICS OF NATURAL AND MAN-MADE RISKS OF ALMATY

Abstract

The purpose of the article is to solve the problems of drawing up a map, its presentation, processing, analysis in order to comprehensively assess the regional system of natural and artificial threats of the Almaty region. By solving these problems, you can consider ways to easily resolve the upcoming conflicts and problems. It can be prevented by making predictions about natural and man-made problems. The root of natural and man-made catastrophic conditions of Almaty region are natural disasters characteristic of mountainous regions. We will take into account the conditions of seasonal mudslides and earthquakes. Since Almaty region is a region located in a mountainous zone, there are a lot of earthquake foci. Tectonic movements often occur. In order to prevent major natural disasters, it is necessary to carry out special monitoring work. From this point of view, the compilation of Geodynamic maps, the study of the Earth's crust, the identification and differentiation of earthquake foci come to the rescue. With this, major disasters can be prevented. The article compiled a map of natural and man-made conditions of the Almaty region. In the process of creating a map, using GIS data, we created a map in the ArcGIS application. We received data from the GIS through a special platform, processing space surveys using a program. We received the data on the basis of SRTM space survey. By studying the dynamics of changes for each year, by comparing maps, you can make conclusive forecasts. Collecting data through free platforms helps to create rational solutions. It is possible to monitor, update,store,and edit the database of information using maps. In the article, a complete study of the region's region was carried out, the importance was given to the rational, effective use of GIS data.

Key words: cartography, GIS, statistical data, geodynamics, man-made risks, Arcgis, map, SRTM, survey

Introduction

Almaty is a region rich in natural resources, economically and, on the one hand, mountainous in nature. In addition, the Earth gives is considered a region with very complex, tectonic eruptions. Population density, rapid economic development lead to the spread of environmental problems. Almaty region is a natural and man-made disaster zone, as well as an ecologically aggravated zone.

The following work will be carried out to analyze the socio-economic and environmental situation in developed countries and states with high market economies:

- conclusion of legislation and contracts;
- involvement of citizens in this direction, dissemination of information;
- financing of Environmental Protection;
- new technological application, compilation of special monitoring cards;
- improving environmental education;
- conducting special research work with the help of satellites.

In this context, GIS specialists can also contribute. With the help of special space surveys, it is possible to create maps and conduct reconnaissance of the regions [1].

Literature review

In accordance with the experience of the Environmental Protection Organization of the Republic of Kazakhstan, as well as the experience of developed countries, the comprehensive regional plan for Environmental Protection is one of the most important components of the health and Environmental Protection of the population of the Republic [2]. The Environmental Protection Program includes environmental audits aimed at establishing a system for the implementation of comprehensive rehabilitation measures, including the full determination of the environmental impact of the above activities and the analysis of geographical features, climate, Natural Resources, socio-economic conditions. It defines environmental priorities for the next 3–5 years and the future, sets out specific activities, their goals and objectives, deadlines for implementation, a plan for financing the plan [3].

It can be said that the Almaty region has entered the stage of a major natural and technological disaster. The analysis of GIS information, a comprehensive assessment of the impact of many natural and artificial processes on the territorial system will allow us to build a unified model, as well as obtain new scientific results to overcome problem situations [4].

Main provisions

For this purpose, the structure of GIS-the collection, storage, modification and automatic transmission of geographic information through automated computers and GIS-can be combined according to the project as follows [5]. The multifunctional mortise is used for many tasks. This implementation will use the following features:

- prepare and put a certain substance in a container;
- reference for information and modeling;
- modeling;
- professional modeling;
- automatic card creation;
- visual calculation [6].

To solve these problems, it is necessary to prepare the processed data in cartographic form and provide it with the algorithms and software used. Can be seen as a data base as a tool for studying the natural elements, dynamics, and system modeling of a region. The-provides specific options for solving the following physical-geographical problems: studying the morphological structure of a country, conducting physical-geographical comparisons, etc. [7].

1 it is related to high-resolution satellite imagery, shaded topographic maps, and two-map digital program maps. It contains data on more than 270 earthquakes in more than 50,000 countries and regions, more than 50,000 cities and islands, and more than 15,000 locations around the world [8]. Interpreting information about political boundaries, rivers, lakes, world coasts, etc.in in addition, it has many interesting features and we can imagine it as scientific software for geography education [9].

Methods and materials

When these robots entered, they received about 12 mah of radar data, and after processing, they obtained mah, which covered the Earth from 60 to 54 degrees [10].

There are several versions of the information available in IA: a preliminary version. The second option will be considered further – separating the edge and the tank, filtering the wrong values. Information from no. they are popular in several versions: the size of the grate is 1 sec. 1 no. E 3 No 3 No [11].

The cell size data is 1 angle 91 seconds (i.e. the cell size is 1 angle 91 seconds). in some cases (for example, a spatial resolution of 30 meters), they are more accurate, but, unfortunately, only in the United States [12].

In the rest of the country, the data comes from IA and is available to the public, the cell size is 3.3 arc seconds (that is, the spatial resolution of 90 m), and the resolution is at least 16 [13].




Figure 1 − Access to the earthexplorer page through special registration



Figure 2 − Designation of the required area



Figure 3 − Selection of the desired space shot



Figure 4 − SRTM space surveys




Figure 5 − Download a shot of the desired format




Figure 6 − The process of obtaining a DEM Image by creating a special mosaic

The process of obtaining hydrography using SRTM space survey:




Figure 7 − Obtaining hydrography data from Space survey

Results and Discussion

1. Filling tool (mAh) focus current (mAh), pulse direction. It uses several different parameters such as (direction), urban development reduction (catchment area), catchment area (catchment area) and soil filling (zoning) [14]. Tool use is a procedure that is repeated until all shortcut websites are exhausted, taking into account the specified number of limits (above). When you fill a local gateway, you can create a new local gateway at the edge of the selected area, and these sections will then be removed from the loop [15].
2. Duck section to obtain the hydrological properties of the surface

The direction of cell flow can be selected. This is done using a flow direction tool.

3. This tool uses it as an input page and provides a grid that shows the direction of supply of each cell. If you select the «output distortion» option, Create an output table that represents the measure of the maximum change in the flow direction relative to the distance between the drive centers in cents. If you select «load from end cell» (force all boundary cells), all cells loaded from the edge of the website will be outside the network boundary [16].
4. There are 8 correct directions relative to 8 adjacent blocks through which the drain passes. This method is often described as the eight-step flow model (98) and follows the basic method of Jenson and Domingo [17].




Figure 8 − Mathematical foundations of the program.

The flow accumulation tool calculates the total flow, which is the total mass of all stations falling under the starting laser slope of each station. In the absence of a raster scale, each cell acquires a mass of 1, the value of the original raster cell is equal to the number of cells contained in each cell [18].

The lower icon in the upper left corner shows the direction of movement of each cell, and in the upper right the number of cells entering each cell [19].




Figure 9 − Mathematical foundations of the program

An example of using this tool is to determine the amount of precipitation that will arrive in a basin. In this case, the input range of the scale can be a continuous range representing the average precipitation for a given period of time. The measurement result determines the amount of precipitation flowing from each cell, so that all precipitation flows to the surface, no precipitation, no evaporation, and precipitation does not reach groundwater. This procedure can be considered precipitation above the surface of each cell [20].

Required layers in the process of creating a physical map:

1. introduction of settlements
2. Hydrography
3. roads
4. Forest
5. Border




Figure 10 − Physical data extraction works (classification)




Figure 11 − Natural and man-made map of Almaty region




Figure 12 − Natural and man-made map of Almaty region

Conclusions

In the article, we compiled a map of natural and man – made threats to the Almaty region using GIS data. To create a map, we used SRTM space capture. Card details can be processed, updated, compared, and monitored. By making a preliminary forecast of natural hazards, it is possible to prevent the upcoming major disasters. Drawing natural and artificial maps of Almaty region. Effective use of location images during installation, use computer technology, data mapping. On the map, you can explain, predict and track threats in the Almaty region.

REFERENCES

1 Vaudour E. Sentinel-2 image capacities to predict common topsoil properties of temperate and Mediterranean agroecosystems. Remote Sensing of Environment, 2019, pp. 21–33.

2 Lurie I.K. Geoinformation mapping. Methods of Geoinformatics and digital equipment of cosmic snimkov, 2010, 424 p.

3 Rasskazov I.Yu. Geoacoustic a portable device of new generation for estimation of rockburst hazard of rocks, 2015, 52 p.
4 Kozhaev Zh.T. Geoinformation system of geomechanical monitoring of ore deposits using methods of space radar interferometry, 2017, 265 p.
5 Espolov T. Land. Almaty, 2013, 264 p.
6 Brad A.K. Brief History of Human Computer Interaction Technology, 1998, pp. 44–54.
7 Lur'e I.K. Introduction of GIS in the field of legal statistics in Kazakhstan, 1997, 115 p.
8 Bultanov D. Introduction of GIS in the sphere of law statistics in Kazakhstan, 2021, 154 p.
9 Berlyant A.M. Cartography: a manual for higher education institutions, 2003, 477 p.
10 Berlyant A.M. Cartography: a manual for higher education institutions, 2002, 336 p.
11 Sabirova A.I. Land relations in the Republic of Kazakhstan: Analysis and recommendations. Almaty, 2001, 174 p.
12 Kapralov E.G. Publishing center "Academy", 2005, 480 p.
13 Berljant A. M. Doctor of Cartography: teacher for universities, 2003, 477 p.
14 Berljant A.M. Cartography: Textbook for universities, 2002, 336 p.
15 Dubinin M.Ju. Web GIS. Computer, 2008, 749 p.
16 Abdullin R. K. Perm State National Research University. Perm, 2020, 132 p.
17 Marcin L. Conversion between cartesian and geodetic coordinates on a rotational ellipsoid by solving a system of nonlinear equations, 2021, 145 p.
18 Hofmann-Wellenhof B. GPS theory and practice, 2018, 282 p.
19 Brad A.K. Brief History of Human Computer Interaction Technology, 2015, pp. 44–54.
20 Lur'e I.K. Introduction of GIS in the field of legal statistics in Kazakhstan, 2019, 115 p.

[1]Турсунбек Ж.Б.,
докторант, ORCID ID: 0009-0003-3480-3856,
e-mail: zhuldyzay.tursynbek@mail.ru

[1]Әл-Фараби атындағы Қазақ ұлттық университеті, 050040, Алматы қ., Қазақстан

АЛМАТЫ ҚАЛАСЫНЫҢ ТАБИҒИ ЖӘНЕ ТЕХНОГЕНДІК ТӘУЕКЕЛДЕРІНІҢ ГЕОДИНАМИКАСЫН БАҚЫЛАУ

Аңдатпа

Мақаланың мақсаты – Алматы облысының табиғи және жасанды қауіптерінің аймақтық жүйесін жан-жақты бағалау мақсатында картаны құру, оны ұсыну, өңдеу және талдау мәселелерін шешу. Осы мәселелерді шешу арқылы болашақта туындауы мүмкін қақтығыстар мен мәселелерді оңай реттеуге болады. Бұл, әсіресе, табиғи және техногендік апаттар туралы болжам жасау арқылы олардың алдын алу мүмкіндігін қамтамасыз етеді. Алматы облысындағы табиғи және техногендік апатты жағдайлардың негізгі себептері таулы аймақтарға тән табиғи апаттармен байланысты. Біз маусымдық көшкіндер мен жер сілкіністері жағдайларын ескереміз. Алматы облысы таулы аймақта орналасқандықтан, жер сілкінісінің ошақтары өте көп және тектоникалық қозғалыстар жиі кездеседі. Ірі табиғи апаттардың алдын алу үшін арнайы бақылау жұмыстарын жүргізу қажет. Осы тұрғыдан алғанда геодинамикалық карталарды құрастыру, жер қыртысын зерттеу, жер сілкінісі ошақтарын анықтау және саралау маңызды рөл атқарады. Бұл шаралар ірі апаттардың алдын алуға мүмкіндік береді. Мақалада Алматы облысының табиғи және техногендік жағдайларының картасы жасалды. Картаны құру барысында ГАЖ деректерін пайдалана отырып, ArcGIS қосымшасы негізінде карта жасадық. ГАЖ деректерін арнайы ғарыштық зерттеулерді өңдейтін платформа арқылы алдық. Бұл деректер SRTM ғарыштық зерттеулер негізінде жиналды. Жыл сайынғы өзгерістер динамикасын зерттеу арқылы карталарды салыстырып, нақты болжамдар жасауға болады. Тегін платформалар арқылы деректерді жинау ұтымды шешімдер қабылдауға көмектеседі. Карталардың көмегімен мәліметтер базасын бақылауға, жаңартуға, сақтауға және өңдеуге болады. Мақалада облыс аймағына толық зерттеу жүргізіліп, ГАЖ деректерін тиімді және ұтымды пайдалану мәселелері қарастырылды.

Тірек сөздер: картография, ГАЖ, статистикалық мәліметтер, геодинамика, техногендік қауіптер, Arcgis, карта, SRTM, зерттеу

[1]Турсунбек Ж.Б.,
докторант, ORCID ID: 0009-0003-3480-3856,
e-mail: zhuldyzay.tursynbek@mail.ru

[1]Казахский национальный университет им. аль-Фараби, 050040, г. Алматы, Казахстан

МОНИТОРИНГ ГЕОДИНАМИКИ ПРИРОДНЫХ И ТЕХНОГЕННЫХ РИСКОВ АЛМАТЫ

Аннотация

Целью статьи является решение задач составления карты, ее представления, обработки, анализа с целью всесторонней оценки региональной системы природных и искусственных угроз Алматинской области. Решая эти задачи, вы можете рассмотреть способы легкого разрешения предстоящих конфликтов и проблем. Это можно предотвратить, делая прогнозы относительно природных и антропогенных проблем. Причиной природных и техногенных катастроф в Алматинской области являются стихийные бедствия, характерные для горных регионов. Мы будем учитывать условия сезонных селей и землетрясений. Поскольку Алматинская область является регионом, расположенным в горной зоне, здесь много очагов землетрясений. Часто происходят тектонические движения. Для предотвращения крупных стихийных бедствий необходимо проводить специальные мониторинговые работы. С этой точки зрения на помощь приходят составление геодинамических карт, изучение земной коры, выявление и дифференциация очагов землетрясений. С помощью этого можно предотвратить крупные катастрофы. В статье составлена карта природных и техногенных условий Алматинской области. В процессе создания карты, используя данные ГИС, мы создали карту в приложении ArcGIS. Мы получали данные из ГИС через специальную платформу, обрабатывая космические съемки с помощью программы. Мы получили данные на основе космической съемки SRTM. Изучая динамику изменений за каждый год, сравнивая карты, можно делать убедительные прогнозы. Сбор данных с помощью бесплатных платформ помогает создавать рациональные решения. С помощью карт можно отслеживать, обновлять, хранить и редактировать базу данных информации. В статье было проведено полное исследование территории региона, важность была придана рациональному, эффективному использованию данных ГИС.

Ключевые слова: картография, ГИС, статистические данные, геодинамика, техногенные риски, Arcgis, карта, SRTM, съемка.

Article submission date: 26.02.2024

UDC 621.396
IRSTI 45.43.01

https://doi.org/10.55452/1998-6688-2024-21-3-331-342

[1]Insepov D.G.,
PhD student, ORCID ID: 0000-0001-7098-4824,
e-mail: insepov_dauren83@mail.ru

[1]Kazakh National Research Technical University named after K.I. Satpayeva,
050013, Almaty, Kazakhstan

DEVELOPMENT PROCESS OF A FREQUENCY CONVERTER FOR INDUCTION HEATING OF OIL PIPELINE

Abstract

The article provides a detailed overview of the history, development and applications of frequency converters, with particular emphasis on their use in the oil and gas industry. It traces the evolution of frequency converters from their inception in the late 19th and early 20th centuries to their modern applications, which use microprocessors and digital signal processing to precisely control the output frequency. In the oil and gas industry, frequency converters are critical to efficient and accurate induction heating of pipelines. They convert a fixed frequency and voltage power supply into a variable frequency and variable voltage output, controlling the speed of the induction motors used in the heating process. The article also covers the design and modeling of frequency converters, discussing the process of characterizing them, creating mathematical models, and using modeling software tools such as MatLab. It presents equations for inductive energy, capacitor energy, resonance conditions and power factor, which are necessary in the mathematical modeling of frequency converters. The article concludes by highlighting the impact of frequency converters on the efficiency and economics of induction heating systems. It emphasizes the need for careful design and modeling to ensure optimal performance and safety.

Key words: frequency converters, induction heating, oil pipeline, design and modeling, technological temperature maintenance.

Introduction

At the present stage of development, the rapid development of science and technology has brought great changes to various industries, and the oil and gas industry is no exception. One of the technological advancements that has had a major impact on the industry is the development of frequency converters. This article examines the history, development, and applications of frequency converters, especially as they relate to induction heating used to maintain process temperatures in petroleum pipelines.

The research conducted in this article is highly relevant for the oil and gas industry, where efficient and accurate induction heating of pipelines is very important. Research focuses on the evolution, development and application of frequency converters, which play an important role in this process. The purpose of this study is to provide a comprehensive understanding of frequency converters, their evolution and application in induction heating. It also aims to explain the technical aspects of frequency converters, including the mathematical equations that govern their design, modeling and operation.

The study uses a multifaceted approach combining historical analysis, technical expertise, applied research and statistical modeling. It begins with a comprehensive review of the existing literature on the history and development of frequency converters. This study also includes in-depth technical analysis of frequency converters, detailed study of the electronic components used in these devices, and the application of mathematical equations to describe energy exchange in LC circuits.

This study has practical implications as it provides insight into the design and modeling of frequency converters for heating oil pipelines. The simulation results are suitable for practical application in oil refineries.

New research focuses on a holistic approach to understanding current frequency converter applications in the oil and gas industry. It also provides a detailed mathematical model of the frequency converter, which is a new addition in this field.

This research provides new insight into the role of frequency converters, particularly in the oil and gas industry where induction heating is used to maintain process temperatures in oil pipelines. This highlights the need for careful design and modeling to ensure optimal performance and safety and opens up new prospects for improving the efficiency and economics of induction heating systems.

Literature review

The history of frequency converters dates back to the late 19th and early 20th centuries, when power systems were just in their infancy.

As alternating current (AC) systems began to dominate direct current (DC) systems, the need for frequency conversion arose. The first frequency converters (late 1800s to early 1900s) were mechanical devices such as motor-generator sets, in which an AC motor drove a DC generator and the output frequency was controlled by the speed of the motor.

Electronic frequency converters began to emerge (mid-1900s) with the invention of electronic components such as vacuum tubes and later transistors. These devices use electronic circuits to convert the frequency of electrical signals, providing greater efficiency and control than mechanical devices.

The development of semiconductor devices such as diodes and thyristors led to the advent of solid-state frequency converters (late 1900s – early 2000s). These devices greatly improve efficiency, reliability, and controllability and have become the standard for most applications [1].

Thanks to advances in digital technology, modern frequency converters now use microprocessors and convert digital signals into frequency converters. These devices are used in a variety of applications, from electronics to communications.

Throughout history, the need for efficient and precise control of electronic systems has driven the development of frequency converters.

Induction heating is now widely used in the oil and gas industry for heating or heating oil pipelines. Frequency converters play an important role in providing sufficient and accurate heating in oil pipelines.

Water heaters have two main purposes: to compensate for heat loss during oil transportation and to satisfy other industrial needs, for example, active heating of oil. Induction heating has many advantages over traditional pipe heating methods. This is a very good way. About 90% of the energy used is converted into heat. In comparison, the energy conversion rate is 30-50%, which is more efficient in traditional processes such as heating hot water or oil. Induction heating also provides a precise and consistent heating system, ensuring the entire pipe is reheated [2].

The frequency converter plays an important role in induction heating of oil pipelines. It is responsible for converting fixed voltages and currents into AC and AC currents and controlling the speed of the induction motor used in the heating system. By controlling frequency and voltage, the frequency converter can precisely control the induction heating system, ensuring heating efficiency and uniformity [3, 4].

Research method

The research conducted in this article used an interdisciplinary approach combining historical analysis, technical research, applied research and mathematical modeling. This study begins with a thorough review of the existing literature on the history and development of frequency converters.

This review examines the evolution of these devices from their mechanical origins to the modern use of microprocessors and digital signal processors. An in-depth technical analysis of frequency converters was carried out. This includes a detailed study of the electronic components used in these devices. Also, the study includes an analysis of the use of frequency converters in the oil and gas industry, in particular for induction heating of pipelines. This analysis examines the importance of frequency conversion, the benefits of induction heating, and the role of frequency converters in this process. Shown are the mathematical equations used to describe power transfer, resonance conditions, and power conditions in LC circuits. The study provides equations to calculate the energy stored in inductors and capacitors. The operation of the frequency converter was simulated using software – Matlab.

The research methods used in this article provide an in-depth understanding of frequency converters, their development, technical aspects, applications and design specifically in the oil and gas industry.

Results and discussions

Taking the example of oil pipelines, frequency converters are used to power induction heating equipment for various purposes such as pre-weld heat treatment, post-weld heat treatment, pipe coating, carbide brazing of drill bits, etc. The use of frequency converters in induction heating systems allows flexible and efficient heating even in places where water sources are located far away and difficult to access [5].

Over time, advances in inverter technology have made oil pipeline induction heating systems more efficient and economical. For example, the development of full-phase inverters using Vienna rectifiers improves energy conversion efficiency and works in high-frequency induction heating systems.

The oil and gas industry widely uses induction heating equipment in a variety of processes, including drilling, pipeline installation and repair, and biofuel processing. Induction heating has replaced gas welding in many industries due to its reliability, safety, and ability to accurately control heat [6].

The development of frequency converters plays an important role in efficient and accurate heating of oil pipelines. The converter, currently under development, converts direct wave energy into alternating waves to provide better control and uniform heating throughout the pipe. Advances in frequency control technology have led to efficient and economical heating systems, making them the number one choice in the oil and gas industry [7].

In this article we will consider a new frequency converter for induction heating of oil pipelines, manufactured by the authors and colleagues (Fig. 1). The first stage of the development process is the design stage. This includes determining the characteristics of the frequency converter such as input and output power, power rating and efficiency. Design also includes component selection and circuit design.



Figure 1 – Experimental setup

The design process begins with the understanding that maximum power dissipation occurs when the inductor power is uniform. This can be achieved by connecting a set of compensation capacitors in parallel with the inductor. A compensating group of capacitors and chokes forms an oscillatory load circuit, in which the active energy stored in the magnetic field of the inductor is transferred to the capacitor and converted into electrical energy [8].

Mathematically, this process can be described as follows: In an oscillatory load circuit consisting of an inductor (L) and a capacitor (C), a force circulates between the magnetic field of the inductor and the electric field of the capacitor [9]. This can be expressed using the following equation:

Inductor power (W_L). The energy stored in the magnetic field of the inductor is determined by the inductor is determined by formula 1:

$$W_L = 1/2 \cdot L \cdot I^2 \quad (1)$$

where L – inductance in henry (H),

I – current through the inductor in amperes (A).

Capacitor Energy (W_C). The energy stored in the electric field of the capacitor is determined by formula 2:

$$W_C = 1/2 \cdot C \cdot V^2 \quad (2)$$

where C – capacity in farads (F),

V – voltage across the capacitor in volts (V).

In an oscillatory circuit, the energy stored in the inductor (W_L), transferred to the capacitor (W_C) and vice versa. This transfer of energy continues back and forth, creating vibrations.

Resonance. The resonance condition in an LC circuit (where the circuit oscillates at its natural frequency) is given by Formula 3:

$$f = \frac{1}{2 \cdot \pi \cdot sqrt(L \cdot C)} \quad (3)$$

where f – oscillation frequency in hertz (Hz),

L – inductance in henry (H),

C – capacity in farads (F).

Power factor. The power factor (PF) of an AC circuit is determined by formula 4:

$$PF = (\theta) \quad (4)$$

where θ – phase angle between current and voltage.

In a DC circuit (such as an LC circuit), the power factor is zero. However, if the inductor's power factor is 1 (1), this means that the circuit is operating in resonance with the voltage and current being in phase.

The purpose of this design is to achieve unity of power by tuning the LC circuit to air flow. This ensures high energy transfer between the inductor and capacitor, resulting in efficient use of electromagnetic energy in the system.

Load oscillatory circuit with inductor and capacitor.

An oscillating load circuit consisting of an inductor and a capacitor is often called an LC circuit (Fig. 2). The circuit can circulate without a source of electromotive force (EMF) by transferring the energy stored in the circuit between the electric and magnetic fields.




Figure 2 – Diagram of an oscillating load with an inductor and a capacitor

In an LC circuit, an inductor (L) and a capacitor (C) are connected in series or parallel. In a series configuration, the total voltage across the open terminals is the sum of the inductor voltage and the capacitor voltage. The current flowing through the active terminal of the circuit is equal to the current flowing through the capacitor and inductor. In a parallel configuration, the voltage across the open terminal is equal to the voltage across the inductor and the voltage across the capacitor. The total current flowing through the positive terminal of the circuit is equal to the sum of the current flowing through the inductor and the current flowing through the capacitor.

The oscillatory behavior of LC circuits is caused by the transfer of energy between capacitors and inductors. When the switch closes, the capacitor begins to discharge, creating a current in the circuit. This current creates a magnetic field in the inductor. The energy is transferred to the capacitor, where the electric field decreases, to the inductor, where the magnetic field increases. This process continues, causing a cycle between electricity and magnetism.

It is worth noting that energy loss occurs within the circuit, which reduces fluctuations over time. These losses can be caused by factors such as the DC resistance of the inductor, the dielectric of the capacitor, and radiation in the circuit.

LC oscillators are widely used for generating high frequencies and are often used in radio generators, superheaters, radio and television receivers, etc.

The use of an oscillating load circuit (usually with an inductor and capacitor or LC circuit) allows energy to be exchanged between electricity and magnetism, creating oscillations without the need for an external emf source.

High frequency generators, such as transistor frequency converters, are used as power sources in oscillating load circuits. High frequency induction heaters have an output frequency range of 10 to 40 or 30 to 100 kHz. In this frequency range, the depth of the induction field is 2–5 mm. If additional heating is required along the depth of the part, the heating time will be increased [10].

When designing an oscillating transformer and considering an oscillating load circuit containing inductors and capacitors, several factors must be considered:

1. List of repetitions. High frequency induction heaters, including those used in frequency converters, typically operate in the frequency range of 10 to 40 kHz or 30 to 100 kHz. The specific frequency range depends on the application and required heating characteristics.

2. Penetration depth. The penetration depth of the guided field in this wavelength range is typically between 2 and 5 mm. This means that the induced current and heating occur predominantly in the surface layer of the heated material.

3. Time and depth of heating. If additional heating is required along the depth of the part, the heating time should be increased. This allows more energy to be transferred to deeper layers of the material, thereby increasing the depth of heating. However, it is worth noting that increasing the heating time may increase the overall processing time.

4. Impedance and resonant frequency. The impedance of the load oscillating circuit (including inductors and capacitors) plays an important role in the frequency converter. Impedance depends on the operating frequency and the size of the inductor and capacitor. When the impedance is low, a resonant frequency occurs in the circuit, allowing more energy to be transferred between the inductor

and the capacitor. The resonant frequency can be calculated using equations and the values of the inductors and capacitors in the circuit.

For example, as shown in Figure 3, the Hartley oscillator, an oscillator used in electronic products, is currently in use. It is known for its simple and lightweight design. It produces sine waves and is used to generate signals. and Colpitts oscillators, which are widely used in wireless communications to generate high-frequency sinusoidal signals. Known for stability and low harmonic distortion.




Figure 3 – Hartley Oscillator and Colpitts Oscillator

It is worth noting that the specific design and load parameters of the frequency converter generator circuit may vary depending on the application requirements and the required heating characteristics.

Next we will look at modern high-frequency transistor transformers for induction installers. Today's transistor high-frequency sensing modules, especially those integrated into gate bipolar transistor (IGBT) modules, are widely used in mid- and high-power applications. IGBTs are three types of power semiconductor devices that combine the power characteristics of MOSFETs and bipolar transistors. They provide high current density, low power consumption and high performance, allowing for smaller heatsink size and lower system cost. These devices can drive loads of hundreds of kilowatts, handle currents up to hundreds of amperes, and withstand voltages in the thousands of volts range. Their low forward energy loss and impedance make them suitable for power applications such as converters, transformers and power supplies [11].

The current flow diagram of the oil pipeline heating process is as follows: In the induction heating oil pipe, the induction wire is wound on the outside of the oil pipe to form a cylindrical inductor. The inductor is closed by a compensation capacitor bank and connected to the high-frequency generator through a damping (shunt) transformer [12].

The inductor is a metal coil surrounded by a tube. It has a cylindrical shape and is designed to create a strong magnetic field when high frequency alternating current (AC) flows. The inductor induces eddy currents in the tube conductor, causing resistive heating.

The capacitor compensation section is connected in parallel with the inductor. Capacitors are used to compensate reactive power in the circuit and increase voltage. This helps improve energy distribution and increase the efficiency of induction heating systems [13].

A damping transformer is connected between the high-frequency generator and the inductor. It performs two important functions [14].

- Appropriate harmony. The shunt transformer ensures that the parameters of the high-frequency generator precisely match the parameters of the load circuit. Controls voltage and current levels for efficient power transfer between generator and inductor. This helps improve energy transfer and heating efficiency.

- Galvanic isolation. The shunt transformer provides galvanic isolation between the inductor and the high-frequency generator. Galvanic isolation is important for safety reasons because it helps prevent electrical shock and protect equipment and personnel. Electrically isolates the inductor from the generator to ensure safe operation.

Induction. The process mode of induction technology is controlled by the controller. The controller monitors and controls various parameters such as temperature, power output, heating time, etc. The heating process is precisely controlled to ensure uniform and stable heating of the oil pipes. Therefore, frequency converters designed for induction heating of oil pipelines require careful consideration of the power supply, inductor design, and use of matching transformer to ensure proper performance and safety.

After completing the design process, we begin executing the model. After completing the design of the frequency converter for the oil pipe heating device, measurements of the system are carried out using software [16]. Calibration allows you to periodically predict the performance of your transmitter and make necessary design adjustments. In this study, simulations were carried out using the MatLab software package.

In this work, system modeling can be used to understand and optimize system performance and reliability. This will help you evaluate different design options, predict system behavior, and identify potential problems before implementing your design in the real world.

The first modeling step is to create a mathematical model of the installed inverter. This includes identifying components, their properties and interactions. The model shows the behavior of the system and allows engineers to simulate its operation under various conditions [17, 18].

Creating a mathematical model of a frequency converter requires a mathematical representation of the converter components and their interactions [19].

Input voltage source (Vin) is the power source of the inverter. In the model we consider it as a constant voltage source.

The switching element (S) is the main component of the inverter. You can think of it as a switch model that turns on and off at a certain frequency. The switching frequency can be expressed as a model parameter.

The output load (L) is the component that uses the power provided by the inverter. In the model, this can be expressed as resistance.

Filter (C) is used to smooth the output voltage. In the model, this can be represented as a capacitor.

The mathematical model of the frequency converter can be expressed by Formula 5:

$$V_{out} = V_m \cdot D \tag{5}$$

where V_{out} – output voltage,

V_m – input voltage,

D – switching element duty cycle.

Duty cycle D is defined as the ratio of the switch closing time (T_{on}) to the total switching cycle period (T_T), i.e., according to formula 6:

$$D = T_{on}/T_T \tag{6}$$

The simulation result is presented in Figures 4 and 5.




Figure 4 – Simulation results in the MatLab software package




Figure 5 – Simulation results in the MatLab software package

The simulation results show that as the frequency of the inductive converter increases, the number of parts, cost, and weight of the device and control system also increase. Unlike most devices that heat only the surface of the pipe, the transformer heats the entire surface of the pipe.

If the inductor power is 1, the electromagnetic force can be increased. This can be achieved by connecting a capacitor bank in parallel with the inductor. The compensation capacitor bank and the inductor form an oscillatory load circuit, and the active energy collected in the magnetic field of the inductor is transferred to the capacitor and converted into electrical energy [20].

A mathematical model was built in the Simulink environment to visually display the logarithm of the amplitude-phase frequency response. The simulation results are shown in Figure 6.




Figure 6 – Simulation results in Simulink environment

The simulation results of this frequency converter can be used for efficient implementation in existing refineries. This means that theoretical designs and models can be implemented in real physical heating systems for oil pipelines. This will also help you understand the working of the inverter. This understanding can be used to improve the efficiency and effectiveness of induction heating systems.

The simulation results can be used to develop inverter control strategies. This ensures precise heating by precisely controlling the output frequency.

Therefore, the obtained simulation results are not only of theoretical significance, but also have practical application value and can contribute to the development of efficient, safe and effective heating systems in the oil and gas industry.

Conclusions

This article provides a comprehensive overview of the evolution, design and application of multiphase conversions, especially in the context of the oil and gas industry.

This article traces the development of the Time-Turner from its origins in the late 19th and early 20th centuries to the present day. Modern inverters use advanced technologies such as microprocessors and digital signal processing to provide precise control of the output frequency.

In the oil and gas industry, frequency converters play an important role in heating pipelines efficiently and accurately. Converts a fixed frequency and voltage source to a variable frequency and voltage output to control the speed of induction motors used in heating systems.

This article describes in detail the design and simulation of frequency converters. We describe the process of characterizing these devices, creating mathematical models, and using software modeling tools such as MatLab. This article presents the equations of inductor power, capacitor power, resonance conditions and power factor required for the mathematical model of a frequency converter.

The article concludes by highlighting the impact of frequency converters on the efficiency and economics of induction heating systems. It emphasizes the importance of careful design and modeling to ensure optimal performance and safety. The simulation results are applicable for practical use at operating oil refineries.

To summarize, the evolution of variable speed drives has paved the way for more efficient and cost-effective induction heating systems, making them the preferred choice in the oil and gas industry. However, the design and modeling of frequency converters requires careful consideration to ensure optimal performance and safety.

REFERENCES

1 Mulko M. Alternating Current and Direct Current: Which is Better? // INTERESTING ENGENEERING. – 2021. Available at: https://interestingengineering.com/science/alternating-current-and-direct-current-which-is-better.

2 Cardoso A.J.M. Electrical Heating System for Oil Pipelines // International Conference on Industrial Engineering, Applications and Manufacturing (ICIEAM). – 2022. Available at: https://www.researchgate.net/publication/363024597_Electrical_Heating_System_for_Oil_Pipelines.

3 Hilsenbeck S. A nugget of knowledge: frequency converters. – 2024. Available at: https://lappconnect.lappgroup.com/en/expertise/a-nugget-of-knowledge-frequency-converters/#autor.

4 Variable Frequency Drive (VFD) – Circuit Diagram, Working, Types, Advantage, Disadvantages, and Applications // Electrical Technology. – 2021. Available at: https://www.electricaltechnology.org/2021/11/vfd-variable-frequency-drive.html

5 Kumar A., Sarkar D., and Sadhu P.K. An Efficient Power Control Technique for High-Frequency Resonant Inverter in Induction Heating System // Eng. Technol. Appl. Sci. Res. – 2018. – vol. 8. – No. 6. – P. 3530–3535.

6 Induction Heating in Oil & Gas Industry. – 2024. Available at: https://ultraflexpower.com/industries/oil-gas/#:~:text=The%20Oil%20and%20Gas%-20industry,drilling%20tools%20and%20many%20more.

7 Induction heater technological process. Monograph / Sagyndikova A.Zh. – Almaty: Gumarbek Daukeev NAO AUES, 2020. – 120 p.

8 Power dissipation in inductors. – 2009. Available at: https://www.physicsforums.com/threads/power-dissipation-in-inductors.334018/

9 Isembergenov N.T., Sagyndikova A.J., Konyrova M.Zh. Frequency converter for induction heating oil in oil pipelines // WSEAS Transactions on Electronics. – 2021. – Vol. 12. – P. 24–31.

10 Паркевич Е.В. Всё об R − L − C контуре // Методическое пособие по подготовке к олимпиадам. – М., 2014. – 47 с.

11 Elton M.D. Analyzation of the Resistor-Inductor-Capacitor Circuit. // Undergraduate Journal of Mathematical Modeling. – 2017. – Vol. 7 – 21 p.

12 Mughees N. Applications of IGBTs in power electronics. // Industrial Electronics. – 2023. Available at: https://electronics360.globalspec.com/article/19849/applications-of-igbts-in-power-electronics.

13 Инсепов Д.Г. Высокочастотный индукционный нагрев нефтепровода // Електрифікація транспорту. – 2016. – № 12. – С. 103–106.

14 Конесев С.Г., Хлюпин П.А. Разработка алгоритма инженерного расчета индукционной нагревательной системы нефтепроводов. Режим доступа: https://s.science-education.ru/pdf/2015/2/709.pdf

15 Ларин В.С., Зененко А.С., Рыдкин М.А. Определение собственных частот и коэффициентов затухания по измеренным передаточным функциям напряжения обмоток силовых трансформаторов // Электричество. – 2023. – № 1. – С. 28–35.

16 Базаров А.А., Данилушкин А.И., Данилушкин В.А. Комплексное моделирование и управление процессом непрерывного индукционного нагрева ферромагнитных заготовок // Вестн. Самар. гос. техн. ун-та. Сер. Технические науки. – 2016. – № 2. – С. 128–138.

17 Bankar S.S., Joshi P.M. Modelling and simulation of high frequency inverter for induction heating application, 2018. Available at: https://www.researchgate.net/publication/309355214_MODELLING_AND_SIMULATION_OF_HIGH_FREQUENCY_INVERTER_FOR_INDUCTION_HEATING_APPLICATION

18 Areitioaurtena M., Segurajauregi U., Akujärvi V. A semi-analytical coupled simulation approach for induction heating. Adv. Model. and Simul. in Eng. Sci. – 2021. – Vol. 8. Available at: https://doi.org/10.1186/s40323-021-00199-0.

19 Du H., Li Ju, Qu Ya. Mathematical Modeling of Eddy-Current Loss for a New Induction Heating Device // Mathematical Modeling of Heat and Mass Transfer in Energy Science and Engineering. – 2014. Available at: https://www.hindawi.com/journals/mpe/2014/923745/

20 Рогинская Л.Э., Горбунов А.С. Трансформаторно-индукторный комплекс с последовательным включением конденсатора в цепь нагрузки. Режим доступа: https://s.science-education.ru/pdf/2013/6/858.pdf

REFERENCES

1 Mulko M. Alternating Current and Direct Current: Which is Better? Interesting Engineering, 2021. Available at: https://interestingengineering.com/science/alternating-current-and-direct-current-which-is-better.

2 Cardoso A.J.M. Electrical Heating System for Oil Pipelines. International Conference on Industrial Engineering, Applications and Manufacturing (ICIEAM), 2022. Available at: https://www.researchgate.net/publication/363024597_Electrical_Heating_System_for_Oil_Pipelines.

3 Hilsenbeck S. A nugget of knowledge: frequency converters, 2024. Available at: https://lappconnect.lappgroup.com/en/expertise/a-nugget-of-knowledge-frequency-converters/#autor.

4 Variable Frequency Drive (VFD) – Circuit Diagram, Working, Types, Advantage, Disadvantages, and Applications. Electrical Technology, 2021. Available at: https://www.electricaltechnology.org/2021/11/vfd-variable-frequency-drive.html

5 Kumar A., Sarkar D., and Sadhu P.K. An Efficient Power Control Technique for High-Frequency Resonant Inverter in Induction Heating System. Eng. Technol. Appl. Sci. Res., 2018, vol. 8, no. 6, pp. 3530–3535.

6 Induction Heating in Oil & Gas Industry, 2024. Available at: https://ultraflexpower.com/industries/oil-gas/#:~:text=The%20Oil%20and%20Gas%-20industry,drilling%20tools%20and%20many%20more.

7 Induction heater technological process. Monograph, 2020. – 120 p.

8 Power dissipation in inductors, 2009. Available at: https://www.physicsforums.com/threads/power-dissipation-in-inductors.334018/

9 Isembergenov N.T., Sagyndikova A.J., Konyrova M.Zh. Frequency converter for induction heating oil in oil pipelines. WSEAS Transactions on Electronics, 2021, vol. 12, pp. 24–31.

10 Parkevich E.V. (2014) Vsjo ob R − L − C konture. Metodicheskoe posobie po podgotovke k olimpiadam, Moscow, 47 p. [in Russian].

11 Elton M.D. Analyzation of the Resistor-Inductor-Capacitor Circuit. Undergraduate Journal of Mathematical Modeling, 2017, vol. 7, 21 p.

12 Mughees N. Applications of IGBTs in power electronics. Industrial Electronics. – 2023. Available at: https://electronics360.globalspec.com/article/19849/applications-of-igbts-in-power-electronics.

13 Insepov D.G. (2016) Vysokochastotnyj indukcionnyj nagrev nefteprovoda. Elektrifikacija transport, no. 12, pp. 103–106 [in Russian].

14 Konesev S.G., Hljupin P.A. Razrabotka algoritma inzhenernogo rascheta indukcionnoj nagrevatel'noj sistemy nefteprovodov. Available at: https://s.science-education.ru/pdf/2015/2/709.pdf [in Russian].

15 Larin V.S., Zenenko A.S., Rydkin M.A. (2023) Opredelenie sobstvennyh chastot i kojefficientov zatuhanija po izmerennym peredatochnym funkcijam naprjazhenija obmotok silovyh transformatorov. Jelektrichestvo, no. 1, pp. 28–35 [in Russian].

16 Bazarov A.A., Danilushkin A.I., Danilushkin V.A. (2016) Kompleksnoe modelirovanie i upravlenie processom nepreryvnogo indukcionnogo nagreva ferromagnitnyh zagotovok. Vestn. Samar. gos. tehn. un-ta. Ser. Tehnicheskie nauki, no. 2, pp. 128–138 [in Russian].

17 Bankar S.S., Joshi P.M. Modelling and simulation of high frequency inverter for induction heating application, 2018. Available at: https://www.researchgate.net/publication/309355214_MODELLING_AND_SIMULATION_OF_HIGH_FREQUENCY_INVERTER_FOR_INDUCTION_HEATING_APPLICATION

18 Areitioaurtena M., Segurajauregi U., Akujärvi V. A semi-analytical coupled simulation approach for induction heating. Adv. Model. and Simul. in Eng. Sci., 2021, vol. 8. Available at: https://doi.org/10.1186/s40323-021-00199-0.

19 Du H., Li Ju, Qu Ya. Mathematical Modeling of Eddy-Current Loss for a New Induction Heating Device. Mathematical Modeling of Heat and Mass Transfer in Energy Science and Engineering, 2014. Available at: https://www.hindawi.com/journals/mpe/2014/923745/

20 Roginskaja L.Je., Gorbunov A.S. Transformatorno-induktornyj kompleks s posledovatel'nym vkljucheniem kondensatora v cep' nagruzki. Available at: https://s.science-education.ru/pdf/2013/6/858.pdf [in Russian]

[1]Инсепов Д.Г.,
докторант, ORCID ID: 0000-0001-7098-4824,
e-mail: insepov_dauren83@mail.ru
[1]Қ.И. Сәтбаев атындағы Қазақ ұлттық техникалық зерттеу университеті,
050013, Алматы қ., Қазақстан

МҰНАЙ ҚҰБЫРЫН ИНДУКЦИЯЛЫҚ ҚЫЗДЫРУҒА АРНАЛҒАН ЖИІЛІК ТҮРЛЕНДІРГІШІН ӘЗІРЛЕУ ҮРДІСІ

Аңдатпа

Мақалада жиілік түрлендіргіштерінің тарихы, дамуы және қолданылуы туралы егжей-тегжейлі шолу ұсынылып, ерекше назар олардың мұнай-газ саласында қолданылуына аударылған. Жиілік түрлендіргіштерінің 19 ғасырдың соңы мен 20 ғасырдың басында жасалуынан бастап, қазіргі кезде микропроцессорлар мен сигналдарды цифрлық өңдеу арқылы шығу жиілігін дәл басқаруға дейінгі эволюциясы қарастырылады. Мұнай-газ саласында жиілік түрлендіргіштері құбырларды тиімді және дәл индукциялық жылыту үшін маңызды рөл атқарады. Олар тұрақты жиілік пен кернеу көзін айнымалы жиілік пен айнымалы кернеу сигналдарына түрлендіріп, жылыту үрдісінде қолданылатын асинхронды қозғалтқыштардың жылдамдығын басқарады. Мақалада сонымен қатар жиілік түрлендіргіштерін жобалау

және модельдеу мәселелері қарастырылады, олардың сипаттамаларын анықтау үрдісі, математикалық модельдерді жасау және MatLab сияқты бағдарламалық құралдарды пайдалану талқыланады. Жиілік түрлендіргіштерін математикалық модельдеу кезінде қажет болатын индуктивтілік энергиясы, конденсатор энергиясы, резонанс шарттары және қуат коэффициентіне қатысты теңдеулер ұсынылған. Мақала соңында жиілік түрлендіргіштерінің индукциялық жылыту жүйелерінің тиімділігі мен экономикасына әсері аталды. Сонымен қатар, оңтайлы өнімділік пен қауіпсіздікті қамтамасыз ету үшін мұқият жобалау мен модельдеудің қажеттілігіне ерекше мән берілген.

Тірек сөздер: жиілікті түрлендіргіштер, индукциялық қыздыру, мұнай құбыры, жобалау және модельдеу, технологиялық температураны ұстау.

[1]Инсепов Д.Г.,
докторант, ORCID ID: 0000-0001-7098-4824,
e-mail: insepov_dauren83@mail.ru

[1]Казахский национальный исследовательский технический университет имени К.И. Сатпаева,
050013, Алматы, Казахстан

ПРОЦЕСС РАЗРАБОТКИ ПРЕОБРАЗОВАТЕЛЯ ЧАСТОТЫ ИНДУКЦИОННОГО НАГРЕВА НЕФТЕПРОВОДА

Аннотация

В статье представлен подробный обзор истории, развития и применения преобразователей частоты с особым акцентом на их использование в нефтегазовой отрасли. Прослеживается эволюция преобразователей частоты от их создания в конце 19 – начале 20 вв. до их современного применения, когда используются микропроцессоры и цифровая обработка сигналов для точного управления выходной частотой. В нефтегазовой отрасли преобразователи частоты имеют решающее значение для эффективного и точного индукционного нагрева трубопроводов. Они преобразуют источник питания с фиксированной частотой и напряжением в выходной сигнал переменной частоты и переменного напряжения, управляя скоростью асинхронных двигателей, используемых в процессе нагрева. В статье также рассматриваются вопросы проектирования и моделирования преобразователей частоты, обсуждается процесс их определения характеристик, создания математических моделей и использования программных инструментов моделирования, таких как MatLab. В нем представлены уравнения для энергии индуктивности, энергии конденсатора, условий резонанса и коэффициента мощности, которые необходимы при математическом моделировании преобразователей частоты. В заключение статьи подчеркивается влияние преобразователей частоты на эффективность и экономику систем индукционного нагрева. В нем подчеркивается необходимость тщательного проектирования и моделирования для обеспечения оптимальной производительности и безопасности.

Ключевые слова: преобразователи частоты, индукционный нагрев, нефтепровод, проектирование и моделирование, технологическое поддержание температуры.

Article submission date: 23.05.2024

УДК 661.961
МРНТИ 38.55.25

https://doi.org/10.55452/1998-6688-2024-21-3-343-353

[1,2]Куришбаев А.,
PhD, профессор, ORCID ID: 0000-0002-0568-5964,
e-mail: rector@kaznaru.edu.kz
[3]Габдуллин М.,
PhD, ORCID ID: 0000-0003-4853-3642,
e-mail: m.gabdullin@kbtu.kz
[3]Аманжолова Р.,
магистрант, ORCID ID: 0000-0001-9129-1074,
e-mail: r_amanzholova@kbtu.kz
[3]Эм Т.,
магистрант, ORCID ID: 0009-0007-6859-1053,
e-mail: t_em@kbtu.kz
[3]*Сагин Ж.,
PhD, профессор, ORCID ID: 0000-0002-0386-888X,
*e-mail: j.sagin@kbtu.kz
[2]Сарсекова Д.,
PhD, профессор, ORCID ID: 0000-0003-0537-4936,
e-mail: sarsekova.dani@kaznaru.edu.kz
[1]Серикканов А.,
PhD, ORCID ID: 0000-0002-0568-5964,
e-mail: a.serikkanov.nas@gmail.com
[1]Алиханов К.,
PhD, ORCID ID: 0000-0001-9514-7678,
e-mail: k.alikhanov.nas@gmail.com
[4]Аденова Д.,
PhD, ORCID ID: 0000-0001-7973-811X,
e-mail: adenovadinara@gmail.com
[4]Абсаметов М.,
PhD, профессор, ORCID ID: 0000-0003-2520-6294,
e-mail: m.absametov@satbayev.university

[1]Национальная академия наук Республики Казахстан, 050010, г. Алматы, Казахстан
[2]Казахский национальный аграрный исследовательский университет,
050010, г. Алматы, Казахстан
[3]Казахско-Британский технический университет, 050000, г. Алматы, Казахстан
[4]Институт гидрогеологии и геоэкологии им. У. М. Ахмедсафина,
Сатпаев университет, 050000, г. Алматы, Казахстан

ЗНАЧИМОСТЬ РАСШИРЕНИЯ ИССЛЕДОВАНИЙ ПРОЦЕССОВ СЕРПЕНТИНИЗАЦИИ ОФИОЛИТОВЫХ ПОРОД ПО ПРИРОДНОМУ «БЕЛОМУ» ВОДОРОДУ ДЛЯ КАЗАХСТАНА

Аннотация

В Казахстане рассматриваются варианты и регионы производства водорода, в том числе на западе Казахстана, в Мангистауской области, с использованием воды Каспийского озера. Текущие продвигаемые технологии производства водорода, включая зеленый водород «green hydrogen», очень дорогие, требующие миллиардных долларовых инвестиций и потенциально создающие сложности местному населению и

природе, экологии, флоре и фауне. В то же время геологические исследования альтернативных вариантов добычи водорода в Казахстане плохо отработаны. Казахстану нужны и очень важны в настоящее время исследования серпентинизации офиолитовых пород по природному «белому» водороду. Во многих странах сейчас идет практически «золотая лихорадка», гидрогеологами ведутся исследования по поиску природного «белого» водорода. Гидрогеологи в настоящее время обнаружили многочисленные источники природного водорода в геологических средах от Мали до Швейцарии, Франции, Германии, США, Канады, Австралии. С целью его обнаружения и добычи возникло более 50 компаний. Природная водородная скважина действует в Мали для обеспечения энергией города с населением около 4000 человек бесплатно и навечно. В отличие от других геологических видов топлива, которые образуются в течение миллионов лет, природный водород генерируется путем смешивания воды и частиц железа, серпентинизации офиолитовых пород, является возобновляемым в масштабах человеческого времени, а не в геологических эпохах. Альтернативные варианты производства и использования водорода представлены в данном обзоре, в том числе различные типы водорода: черного, серого, зеленого, синего, бирюзового, розового и желтого, в зависимости от способа его добычи и производства. Казахстан с богатейшими природными рудными запасами, в том числе угля и полиметаллов, где могут располагаться офиолитовые породы, вполне может иметь месторождения природного «белого» водорода, такие геологические исследования в Казахстан плохо отработаны.

Ключевые слова: серпентинизация, офиолитовые породы, природный «белый» водород, Каспийское озеро, HYRASIA ONE.

Введение

Казахстан намерен продолжить промышленную добычу воды из Каспийского озера для производства водорода и экспорта в ЕС в рамках проекта HYRASIA ONE в дополнение к текущей интенсивной добыче нефти и газа в районе Каспийского озера [1]. Сложность реализации казахстанского проекта HYRASIA ONE связана с проблемой доступности водных ресурсов и стоимостью электроэнергии в Западном Казахстане, Мангистауской области. Будет разумно разработать альтернативные решения с разумными затратами и без ущерба для природы. Более детальное изучение альтернативных вариантов добычи и производства водорода, опыт других стран, в том числе анализ технологий различных типов водорода: черного, серого, зеленого, синего, бирюзового, розового и желтого в зависимости от способа его добычи и производства. Различные способы производства водорода часто связывают с цветом. Такая классификация позволяет понять, откуда берется водород и какой углеродный след связан с его добычей и производством. Хотя водород является наиболее распространенным элементом, он редко существует в чистом виде и обычно находится в сочетании с другими атомами. Исключением является природный «белый» водород, который считался редким и потенциал которого раскрывается сейчас в последние несколько лет от 2024 г. [2]. В отличие от запасов ископаемого топлива, для формирования которых требуются миллионы лет, природный «белый» водород создается непрерывно, а период восстановления примерно равен продолжительности человеческой жизни. Природный «белый» водород – это недавно обнаруженный геологический источник устойчивой энергии, аналогичный природному газу. Природный «белый» водород генерируется естественным геохимическим процессом глубоко внутри земной коры, что делает его устойчивым и неисчерпаемым источником. Природный «белый» водород в категории «золотой лихорадки», гидрогеологами ведутся интенсивные исследования во многих странах, кроме Казахстана. Гидрогеологи Мали, Швейцарии, Франции, Германии, США, Канады, Австралии обнаружили многочисленные источники природного «белого» водорода, некоторые проекты уже запущены и производят природный водород в промышленных количествах [3]. В Казахстане такие геологические исследования природного «белого» водорода отсутствуют. Природный «белый» водород – это самое дешевое решение для производства углеродно нейтрального водорода, которое может конкурировать с ископаемым топливом. Цепочка создания стоимости аналогична добыче природного газа. Она включает в себя разведку, выбор участков, бурение, добычу и разделение продукции. Защита окружающей среды является приоритетом для реализации добычи природного «белого» водорода, который не требует использования

экологически опасных методов, таких как гидроразрыв пласта. Природный «белый» водород на 33% дешевле, чем самый дешевый водород из ископаемого топлива, и в несколько раз дешевле самого дешевого «зеленого» водорода [3]. Природный «белый» водород перспективен в качестве более дешевой альтернативы «зеленому» водороду. «Зеленый» водород в настоящее время стоит около 5 евро за килограмм. Природный «белый» водород стоит около 0.50 евро за килограмм, в десять раз дешевле «зеленого» водорода (5 евро/50 евроцентов=10) [4, 5].

Почему в Казахстане до текущего дня отсутствовали исследования природного «белого» водорода? Ответом на этот вопрос может быть отсутствие экспертизы, знаний, заинтересованности, инвестиций в гидрогеологические исследования природного «белого» водорода. Основные инвестиции до текущего дня были в основном в нефтегазовые ресурсы и рудные исследования полиметаллов. Гидрогеологические исследования естественных природных процессов серпентинизации, исследования воды с окислением металлов, приводящих к выделению природного «белого» водорода, в Казахстане отсутствовали. В принципе, исследования водных ресурсов имели остаточный принцип в Казахстане. Работы гидрогеологов Казахстана имели очень плохое финансирование. Научные институты гидрогеологов Казахстана с трудом выживали без финансирования. Ответ также в геологии. Существуют определенные геологические структуры, в которых обнаруживается природный газ или нефть. Ни в коем случае не гарантируется, что в подходящей геологии будут залежи природного газа, однако можно с уверенностью сказать, что в неподходящей геологии их не будет. Так же по месторождениям природного «белого» водорода, который образуется в геологических структурах, отличных от природного газа или нефти [8]. Вероятность нахождения природного «белого» водорода наибольшая на севере Казахстана, где имеются большие запасы угля и полиметаллов, но не в регионе Каспийского озера, где имеются большие запасы нефтегазовых ресурсов. Итак, ответ на вопрос, почему десятки лет поисков и добычи нефти и природного газа не привели к обнаружению сколько-нибудь значительных количеств природного водорода, прост. Геологи искали не в том месте, если вообще кто-либо искал в Казахстане природный «белый» водород, и отсутствовали стимулы поиска природного «белого» водорода в другом регионе Казахстана, отсутствовало финансирование, стимулы вовлечения ученых гидрогеологов в изучение природного «белого» водорода. Теперь же имеется информация и знания, как выглядят правильные геологические структуры, где могут находиться подземные «фабрики» производства природного «белого» водорода по опыту исследований Мали, Швейцарии, Франции, Германии, США, Канады, Австралии. Оптимально изучить опыт этих стран и их геологические структуры, обучиться и исследовать аналогичные геологические структуры Казахстана, где могут быть месторождения природного «белого» водорода, стимулировать и дать финансирование ученым-гидрогеологам Казахстана. Наибольшая вероятность нахождения природного «белого» водорода есть на севере Казахстана, где имеются большие запасы угля и полиметаллов с заброшенными шахтами (рисунок 1).

Гигантское месторождение водорода в регионе заброшенных угольных шахт

На территории бывших заброшенных шахт, закрытых 20 лет назад, на границе Франции и Германии ученые-гидрогеологи Филипп де Донато и Жак Пиронон, профессоры-исследователи лаборатории GeoRessources в городе Нанси, исследовали месторождения природного «белого» водорода (H_2). Земля под горнодобывающим бассейном Лотарингии очень богата природным «белым» водородом [6]. Исследователи полагают, что природный «белый» водород непрерывно производится настоящей водородной подземной «фабрикой», скрытой под нашими ногами, сырьем для которой являются молекулы воды и минералы, состоящие из карбонатов железа ($FeCO_3$ и $Ca(Fe,Mg,Mn)(CO_3)$. Земля вокруг заброшенных угольных шахт рудников Фолшвиллер богата этими двумя типами соединений. Когда минералы вступают в контакт с водой, происходит физико-химическая окислительно-восстановительная реакция, в которой минералы разделяют молекулы воды (H_2O) на кислород (O_2) и водород (H_2) [6].



Рисунок 1 – Карта месторождений, регионов добычи угля, источник [9], где потенциально есть геологические структуры, карбонаты железа ($FeCO_3$ и $Ca(Fe,Mg,Mn)(CO_3)$, где могут находиться подземные «фабрики» производства природного «белого» водорода по опыту исследований Мали, Швейцарии, Франции, Германии, США, Канады, Австралии, требуются гидрогеологические исследования

Материалы и методы

Методология исследования представлена ниже в виде блок-схемы (рисунок 2). Планирование и управление системой добычи месторождения водорода.



Рисунок 2 – Блок-схема продвижения исследований природного геологического водорода в Казахстане

Природный «белый» водород, по-видимому, присутствует в широком спектре горных пород и геологических регионов. Естественные процессы образования водорода еще не до конца изучены. Некоторые гипотезы включают дегазацию водорода, реакцию воды с геологическими породами (серпентинизации) или радиолиз (диссоциация воды ураном или плутонием) и разложение органического вещества. Серпентинизации – это процесс вступления воды в реакцию с определенными офиолитовыми породами и выделение водорода [2]. Серпентинизации являются естественным природным процессом изменения водой горных пород, содержащих высокую концентрацию железа и магния. Это изменение в сочетании с окислением металлов, присутствующих в породах, приводит к образованию богатого водородом газа и очень щелочной воды (pH до 12,5).

Пример серпентинизации оливина (минерала, богатого железом и магнием):

$$3\ Fe_2SiO_4 + 2\ H_2O \rightarrow 2\ Fe_3O_4 + 3\ SiO_2 + 2\ H_2 \quad (1)$$

Фаялит + Вода -> Магнетит + Кремнезем + Водород

Месторождение природного «белого» водорода французскими учеными Жаком Пирононом и Филиппом Де Донато оценивается до 250 млн тонн [7].

Для сравнения: планируемое в Казахстане промышленное производство «зеленого» водорода из воды Каспийского озера составит 2 млн тонн водорода (в 125 раз меньше) при гигантском производстве солнечной и ветряной энергии, покрывающем большую территорию в Мангистауской области, с инвестициями в 50 млрд долларов [1]. В Казахстане имеется очень большое количество заброшенных угольных шахт, где аналогичные исследования, проведенные французскими учеными по месторождениям природного «белого» водорода на территории бывших угольных шахт, отсутствуют. В Казахстане также много геотермальных подземных регионов, карбонатов железа ($FeCO_3$ и $Ca(Fe,Mg,Mn)(CO_3)$, крупнейшие мировые подземные запасы урана и плутония, где проходят процессы серпентинизации с выделением водорода. Гидрогеологические исследования естественных природных процессов серпентинизации, изменения водой с окислением металлов, приводящих к выделению природного «белого» водорода, в Казахстане плохо отработаны, геоинформационные карты расположения природного «белого» водорода отсутствуют в Казахстане. При нахождении таких регионов природного «белого» водорода в Казахстане себестоимость вполне может быть в десятки раз дешевле, чем планируемые проекты производства «зеленого» водорода из воды Каспийского озера.

Результаты и обсуждение

Важность усиления кооперации с соседними странами ЦА по обеспечению водной подпитки подземных «фабрик» производства природного «белого» водорода

Для подземной выработки водорода нужны подземные воды в геологических пластах, где могут происходить окислительно-восстановительные химические процессы, включая реакции серпентинизации (гидратация богатых железом пород/минералов), радиолиз (расщепление молекул воды при радиоактивном распаде урана и/или тория), распад органического вещества. Для формирования таких процессов нужны металлорудные метамагматические породы, с кремнеземом, гранитоидные породы. Подземным «фабрикам» производства водорода нужна постоянная подпитка водой в случае извлечения водорода из этих «фабрик» [10]. В случае продолжения интенсивного потребления поверхностной воды, строительства дамб, поверхностных резервуаров с большими потерями по испарениям воды до 100% страны ЦА уничтожат свои подземные «фабрики» производства водорода, прекратив обеспечение питанием подземные «фабрики». Странам ЦА более выгодно совместно усилить гидрогеологические исследования, исследовать и найти регионы подземных «фабрик» производства «белого» водорода и обеспечить питанием, подпиткой подземных вод несущих горизонтов на постоянной основе (рисунок 3). Все эти работы требуют большой экспертизы, вовлечения ученых-исследователей подземных ресурсов, геологов-гидрогеологов.



Рисунок 3 – Упрощенное изображение процесса выработки природного геологического «белого» водорода в подземных «фабриках», где требуется наличие подземных вод и среды для серпентинизации (гидратация богатых железом пород/минералов) и радиолизов (расщепление молекул воды при радиоактивном распаде урана и/или тория), источник [10]

В ЦА во всех пяти странах (Казахстан, Кыргызстан, Таджикистан, Туркменистан, Узбекистан) популярно строительство дамб-резервуаров, причем в настоящее время это является одной из основных стратегий финансирования больших строительных работ. В ЦА построено более 60 крупных поверхностных водохранилищ с текущим продолжением строительства тысяч малых дамб и поверхностных водохранилищ. В то же время многие страны, включая страны Европы, США, Канаду, сокращают строительство дамб-резервуаров и даже ликвидируют ранее построенные дамбы-резервуары, учитывая, какой вред сооружения приносили и приносят естественным природным процессам круговорота воды в природе, флоре и фауне. Во многих странах мира сейчас идет «золотая лихорадка» гидрогеологических исследований по поиску подземных «фабрик» производства природного геологического «белого» водорода. В ЦА, наоборот, поверхностные воды практически исчерпаны и сейчас идет интенсивное уничтожение малых природных поверхностных вод со строительством дамб-резервуаров, что влечет уничтожение натуральной подпитки подземных водоносных горизонтов, где потенциально расположены подземные «фабрики» производства «белого» водорода. Странам ЦА более выгодно включиться в текущие мировые тренды, мировые программы «золотой лихорадки» гидрогеологических исследований в кооперации с учеными Франции, Германии, США, Канады, Австралии и договориться о совместном эффективном использовании подземных «фабрик» и продукции «белого» водорода.

Заключение

В случае наличия природного «белого» водорода в Казахстане конкурентность «зеленого» водорода значительно уменьшится. Природный «белый» водород может быть дешевле производства «зеленого» водорода в десятки раз [4, 5]. Наличие природного «белого» водорода в Казахстане вполне может позволить развивать интенсивно внутреннее использование водорода населением Казахстана, где нужны будут технологии, аналогичные технологиям французских производителей водородных электрических генераторов с нулевым уровнем выбросов [11, 12]. Накопительные технологии водорода в емкостях, идентичных сжиженному

природному газу, с последующим производством электроэнергии станциями GEH2 вполне могут заменить дорогие технологии хранения электроэнергии в батареях, практически могут заменить батареи (рисунок 4). Развитие использования таких технологий требует технической экспертизы с системой подготовки техников по водороду, включая обучение техников в колледжах в кооперации с колледжами Франции, Канады и Катара (рисунок 5).



Рисунок 4 – Французские технологии водородных электрических генераторов GEH2 с нулевым уровнем выбросов [11, 12] с накопителями водорода в емкостях идентичных сжиженному природному газу, с последующим производством электроэнергии вполне могут заменить дорогие технологии хранения электроэнергии в батареях, практически могут заменить батареи




Рисунок 5 – Развитие дуальной программы обучения техников по водороду, включая обучение техников в колледжах в кооперации с колледжами Франции, Канады и Катара [12]

Информация о финансировании

Данная работа поддерживается проектом № AP19679749 и проектом № AP19679749 грантового финансирования Министерства Науки и Высшего Образования Республики Казахстан.

ЛИТЕРАТУРА

1 Department of Economic and Social Affairs, Sustainable Development, Hydrogen and Ammonia fertilizers for Sustainable Agriculture and New Global Framework for Managing Nature programs, UN, 2023. https://sdgs.un.org/partnerships/hydrogen-and-ammonia-fertilizers-sustainable-agriculture-and-new-global-framework

2 What potential for natural hydrogen? Energy Observer, 2024. https://www.energy-observer.org/resources/natural-hydrogen

3 White Hydrogen. Drilling for natural hydrogen, Solar Impulse, 2024. https://solarimpulse.com/solutions-explorer/white-hydrogen

4 Hand E. Hidden Hydrogen, Does Earth hold vast stores of a renewable, carbon-free fuel? Science, 2023 https://www.science.org/content/article/hidden-hydrogen-earth-may-hold-vast-stores-renewable-carbon-free-fuel

5 What is 'white hydrogen'? The pros and cons of Europe's latest clean energy source, EuroNews Green, 2023. https://www.euronews.com/green/2023/11/05/what-is-white-hydrogen-the-pros-and-cons-of-europes-latest-clean-energy-source

6 Bettayeb K. CNRS Geology, A gigantic hydrogen deposit in northeast France? 2023. https://news.cnrs.fr/articles/a-gigantic-hydrogen-deposit-in-northeast-france

7 Hawkinson K. What is white hydrogen? Scientists say clean-energy gas could save the world. Business Insider Science, 2023. https://www.businessinsider.com/white-hydrogen-france-clean-energy-climate-change-2023-10

8 Natural Hydrogen Has Been Underestimated, American Gas Association, 2023. https://www.aga.org/natural-hydrogen-has-been-underestimated/

9 База данных. Казахстан, 2024. https://aboutkazakhstan.com/

10 A Mineral Systems Approach to Targeting Natural Hydrogen Deposits. Getech, 2023. https://getech.com/blog/hydrogen/a-mineral-systems-approach-to-targeting-natural-hydrogen-deposits/

11 GEH2: The zero-emission hydrogen power generator. EODEV, France, 2024. https://www.eo-dev.com/products/geh2-the-zero-emission-hydrogen-power-generator

12 US-French EODev Hydrogen GEH2. Generac Power, 2024. https://www.generac.com/Industrial/all-about/hydrogen

13 College based TVET program. Hydrogen Technician, 2024. https://cna.nl.ca/program/hydrogen-technician#

[1,2]Куришбаев А.,
PhD, профессор, ORCID ID: 0000-0002-0568-5964,
e-mail: rector@kaznaru.edu.kz
[3]Габдуллин М.,
PhD, ORCID ID: 0000-0003-4853-3642,
e-mail: m.gabdullin@kbtu.kz
[3]Аманжолова Р.,
магистрант, ORCID ID: 0000-0001-9129-1074,
e-mail: r_amanzholova@kbtu.kz
[3]Эм Т.,
магистрант, ORCID ID: 0009-0007-6859-1053,
e-mail: t_em@kbtu.kz
[3]*Сагин Ж.,
PhD, профессор, ORCID ID: 0000-0002-0386-888X,
*e-mail: j.sagin@kbtu.kz
[2]Сарсекова Д.,
PhD, профессор, ORCID ID: 0000-0003-0537-4936,
e-mail: sarsekova.dani@kaznaru.edu.kz
[1]Серикканов А.,
PhD, ORCID ID: 0000-0002-0568-5964,
e-mail: a.serikkanov.nas@gmail.com,
[1]Алиханов К.,
PhD, ORCID ID: 0000-0001-9514-7678,
e-mail: k.alikhanov.nas@gmail.com
[4]Аденова Д.,
PhD, ORCID ID: 0000-0001-7973-811X,
e-mail: adenovadinara@gmail.com
[4]Абсаметов М.,
PhD, профессор, ORCID ID: 0000-0003-2520-6294,
e-mail: m.absametov@satbayev.university

[1]Қазақстан Республикасының Ұлттық ғылым академиясы, 050010, Алматы қ., Қазақстан
[2]Қазақ ұлттық аграрлық зерттеу университеті, 050010, Алматы қ., Қазақстан
[3]Қазақ-Британ техникалық университеті, 050000, Алматы қ., Қазақстан
[4]У. Ахмедсафин атындағы Гидрогеология және геоэкология институты,
Сәтбаев университеті, 050000, Алматы қ., Қазақстан

ТАБИҒИ «АҚ» СУТЕГІНІҢ ОФИОЛИТ ЖЫНЫСТАРЫНЫҢ СЕРПЕНТИНИЗАЦИЯЛАУ ҮДЕРІСІН ЗЕРТТЕУДІ ТЕРЕҢДЕТУДІҢ ҚАЗАҚСТАН ҮШІН МАҢЫЗЫ

Андатпа

Қазақстанда Каспий теңізінің суын пайдалана отырып, сутегі өндірісінің нұсқалары мен шоғырланған өңірлері, соның ішінде Қазақстанның батысындағы Маңғыстау облысы, зерттелді. «Green hydrogen» – жасыл сутегі өндірісін қоса алғанда, қазіргі жетілдірілген сутегі өндірісі технологиялары өте қымбат, миллиардтаған долларлық инвестицияларды қажет етеді және жергілікті халыққа, табиғатқа, экологияға, флора мен фаунаға ықтимал қиындықтар тудыруы мүмкін. Сонымен қатар, Қазақстанда сутегі өндірудің баламалы нұсқаларын геологиялық тұрғыдан зерттеу нашар пысықталған. Қазақстан үшін қазір опиолит жыныстарының табиғи «ақ» сутегінің серпентинизациясы бойынша зерттеулер жүргізу өте маңызды. Қазіргі таңда көптеген елдерде «алтын асығыс» секілді үрдіс байқалады, гидрогеологтар табиғи «ақ» сутекті іздеу мақсатында зерттеулер жүргізуде. Қазір гидрогеологтар Малиден бастап Швейцарияға, Францияға, Германияға, АҚШ-қа, Канадаға және Австралияға дейінгі геологиялық орталарда табиғи сутектің көптеген көздерін тапты. Оны табу және өндіру мақсатында 50-ден астам компания пайда болды. Малиде табиғи сутегі ұңғымасы 4000-ға жуық тұрғыны бар жергілікті қаланы ақысыз және мәңгілік энергиямен қамтамасыз ету үшін жұмыс істейді. Табиғи сутегі басқа геологиялық отындардан айырмашылығы, миллиондаған жылдар

бойы емес, адам өмірінде жаңаратын ресурстар қатарына жатады. Ол су мен темір бөлшектерінің қосылысы арқылы, опиолит жыныстарының серпентинизациясы нәтижесінде пайда болады. Осы шолуда сутегіні өндірудің әртүрлі нұсқалары ұсынылған, оның ішінде қара, сұр, жасыл, көк, көгілдір, қызғылт және сары сутегілер, олардың өндіру тәсілдеріне байланысты ерекшеліктері талқыланады. Қазақстанның бай табиғи ресурстарының ішінде көмір мен полиметалдарды қоса алғанда, опиолит жыныстары орналасуы мүмкін, бұл жерлерде табиғи «ақ» сутегі кен орындарының болуы ықтимал. Алайда, бұл бағыттағы геологиялық зерттеулер елімізде әлі де толыққанды дамымаған.

Тірек сөздер: серпентинизация, офиолит жыныстары, табиғи «ақ» сутегі, Каспий көлі, HYRASIA ONE.

[1,2]Kurishbaev A.,
PhD, professor, ORCID ID: 0000-0002-0568-5964,
e-mail: rector@kaznaru.edu.kz
[3]Gabdullin M.,
PhD, ORCID ID: 0000-0003-4853-3642,
e-mail: m.gabdullin@kbtu.kz
[3]Amanzholova R.,
Master's student, ORCID ID: 0000-0001-9129-1074,
e-mail: r_amanzholova@kbtu.kz
[3]Em T.,
Master's student, ORCID ID: 0009-0007-6859-1053,
e-mail: t_em@kbtu.kz
[3]*Sagin J.,
PhD, Professor, ORCID ID:0000-0002-0386-888X,
*e-mail: j.sagin@kbtu.kz
[2]Sarsekova D,
PhD, professor, ORCID ID: 0000-0003-0537-4936,
e-mail: sarsekova.dani@kaznaru.edu.kz
[1]Serikkanov A.,
PhD, ORCID ID: 0000-0002-0568-5964,
e-mail: a.serikkanov.nas@gmail.com,
[1]Alikhanov K.,
PhD, ORCID ID: 0000-0001-9514-7678,
e-mail: k.alikhanov.nas@gmail.com
[4]Adenova D.,
PhD, ORCID ID: 0000-0001-7973-811X,
e-mail: adenovadinara@gmail.com
[4]Absametov M.,
PhD, Professor, ORCID ID: 0000-0003-2520-6294,
e-mail: m.absametov@satbayev.university

[1]National Academy of Sciences of the Republic of Kazakhstan, 050010, Almaty, Kazakhstan
[2]Kazakh National Agrarian Research University, 050010, Almaty, Kazakhstan
[3]Kazakh-British Technical University, 050000, Almaty, Kazakhstan
[4]Institute of Hydrogeology and Geoecology named after U.M. Akhmedsafin,
Satpayev University, 050000, Almaty, Kazakhstan

THE IMPORTANCE OF EXPANDING RESEARCH ON THE SERPENTINIZATION OF OPHIOLITE ROCKS BY NATURAL "WHITE" HYDROGEN FOR KAZAKHSTAN

Abstract

In Kazakhstan, options and regions for hydrogen production are being considered, including in Western Kazakhstan, the Mangystau region, using the water of the Caspian Lake. The current advanced hydrogen production

technologies, including green hydrogen, are very expensive, requiring billions of dollars of investment and potentially creating difficulties for the local population and nature, ecology, flora and fauna. At the same time, geological studies of alternative hydrogen production options in Kazakhstan are poorly developed. Kazakhstan needs and is currently very important to study serpentinization of ophiolite rocks using natural «white» hydrogen. In many countries, there is practically a «gold rush» now, hydrogeologists are conducting research on the search for natural «white» hydrogen. Hydrogeologists have now discovered numerous sources of natural hydrogen in geological environments from Mali to Switzerland, France, Germany, the USA, Canada, and Australia. More than 50 companies have sprung up to discover and mine it. A natural hydrogen well operates in Mali to provide energy to a local city with a population of about 4,000 people for free and forever. Unlike other geological fuels, which are formed over millions of years, natural hydrogen is generated by mixing water and iron particles, serpentinization of ophiolite rocks, and is renewable on the scale of human time, and not in geological epochs. Alternative options for the production and use of hydrogen are presented in this review, including various types of hydrogen, black, gray, green, blue, turquoise, pink and yellow, depending on the method of its extraction and production. Kazakhstan, with the richest natural ore reserves, including coal and polymetals, where ophiolite rocks may be located, may well have deposits of natural «white» hydrogen, such geological studies in Kazakhstan are poorly developed.

Key words: serpentinization, ophiolite rocks, natural “white” hydrogen, Caspian Lake, HYRASIA ONE.

Дата поступления статьи в редакцию: 09.02.2024

IRSTI 61.51.15
UDC 665.622

https://doi.org/10.55452/1998-6688-2024-21-3-354-362

[1]Xing L.,
master student, e-mail: xly2841010053@163.com,
[1]*Yang H.,
Associate professor, e-mail: hongbinyang@upc.edu.cn,
[2]Li M.,
master student, e-mail: 519630341@qq.com,
[3]Wang G.,
master student, e-mail: wanggch12@cnooc.com.cn,
[1]Jiang H.,
PhD student, e-mail: 2737353467@qq.com,
[1]Wang R.,
PhD student, e-mail: wang_rchao@163.com,
[1]Zhang Yu.,
master student, e-mail: 1940390250@qq.com,
[1]Li H.,
master student, e-mail: 1244243374@qq.com,
[1]*Kang W.,
Professor, e-mail: kangwanli@upc.edu.cn

[1]School of Petroleum Engineering,
China University of Petroleum (East China), Qingdao, 266580, PR China
[2]Qingdao Huizhi Oilfield Service Company Limited, Qingdao 266580, PR China
[3]Bohai Petroleum Research Institute, Tianjin Branch of CNOOC Ltd., Tianjin, 300459, PR China

STUDY ON THE INFLUENCING FACTORS OF DEMULSIFIER ON THE OIL-WATER INTERFACE VISCOELASTICITY

Abstract

Water flooding is a commonly used development method in oilfields, and the water cut of the output fluid of oil wells gradually increases with the increase of injected water in water wells. Due to the presence of natural surfactants such as gum, asphaltene and organic acid in crude oil, it is easy to form a high strength viscoelastic oil-water interfacial film and a stable emulsion. To facilitate the storage and transportation of crude oil, it is necessary to demulsify the crude oil emulsion. In this paper, the CQ crude oil was taken as the research object, and the effects of demulsifier type, concentration, demulsifier temperature and oil-water properties on the viscoelasticity of oil-water interfacial film were investigated by using rheometer and then the demulsification mechanism was explored. The results show that the lower the interfacial film strength, the better the demulsifier. In addition, with the increase of demulsifier concentration and temperature, the oil-water interfacial viscoelasticity decreases and the interfacial film strength further decreases. In general, the demulsification effect will be significantly improved with the increase of demulsifier concentration and temperature, and the dehydration effect will be better. The research results can provide theoretical guidance for the field application of demulsification.

Key words: interface viscoelasticity; interface film strength; demulsification effect; influencing factors.

Introduction

Crude oil demulsification is an important part in oil and gas gathering and transmission, and the key problem of demulsification lies in destroying the oil-water interfacial film, releasing the

dispersed-phase droplets, and achieving the effect of oil-water separation through agglomeration and flocculation [1]. The research of demulsifier has nearly 100 years of history so far. In 1914, Barnickel found that ferrous sulfate can break the emulsion and dewater crude oil emulsion, which opened a new era of demulsifier. The most widely used demulsifiers are ethylene oxide (EO) and propylene oxide (PO) block polyethers, which have excellent solubility properties, relatively simple synthesis conditions and less influence on demulsification performance by low temperature [2–4]. The demulsifier has amphiphilicity and the ability to destabilize the interfacial film. Demulsifier can be adsorbed at the oil-water interface to replace or react with natural surfactants to change the tension, viscoelasticity, and stability of the interfacial film [5].

Therefore, to obtain excellent demulsification and dehydration effects, it is necessary to understand the properties of the oil-water interfacial film and the influencing factors affecting the viscoelasticity of the oil-water interface. Interfacial rheology is an important property of oil-water interfacial film, which is closely related to the demulsification of crude oil emulsion [6-9]. Interfacial rheology mainly includes shear viscosity and viscoelasticity [10]. Due to the expandability and compressibility of the interfacial film, the strong interfacial viscoelasticity can make the film resist and quickly recover the deformation when it is damaged. Therefore, the interfacial film strength can be visually characterized [11]. In order to solve the problem, rheometer was used to measure the changes of oil-water interfacial viscoelasticity under different types of demulsifiers, concentrations, temperatures, and oil-water properties. Among them, the interfacial viscoelasticity can be characterized by two parameters, interfacial storage modulus and interfacial loss modulus, which represent the elasticity and viscosity of interfacial film, respectively.

Experiments

Materials and instruments

Dewatered crude oil and formation water were provided from CQ oilfield in China. Demulsifiers of AR101, AP301 and AR989 were purchased from Qingdao Changxing Hi-tech Development Co., Ltd. Sodium chloride (NaCl) and magnesium chloride hexahydrate (MaCl2·6H2O) were all analytically pure and provided from Sinopharm Chemical Reagent Co. Ltd. Deionized water was self-made in the laboratory.

The interface rheological experiment was tested using the MCR 301 rheometer (Anton Paar, Austria).

Determination of interfacial viscoelasticity.

The oil-water interfacial film strength is characterized by the viscoelasticity, which was measured by the interfacial rheology system of the rheometer. Firstly, a suitable volume of water phase was added into the measuring cell to the scale line, heated to 30 °C, stabilized for 10 minutes to remove the gas. Then, the rotor was lowered to the specified height, and the interfacial distance testing system was run to ascertain the height of the rotor at point of contact with the gas-liquid interface. This was done to ensure that the edge of the rotor was in direct contact with the water surface. Finally, a specific volume of oil phase is added, and once equilibrium is reached the adsorption process at the oil-water interface, the test program is initiated to measure the changes in the interfacial elastic modulus (G') and the viscous modulus (G'') at the oil-water interface. This allows for the determination of the dynamic change in the interfacial film strength with the angular frequency.

Results and discussion

The key to breaking the emulsion is to effectively reduce the oil-water interfacial film strength. A reduction in interfacial film strength results in an increased propensity for rupture, which in turn leads to a deterioration in emulsion stability. This ultimately facilitates the breakdown of the emulsion and the subsequent dewatering process. In the following, the effects of demulsifier type, concentration, temperature and oil-water properties on the interfacial viscoelasticity are investigated, respectively.

Effect of demulsifier type on the oil-water interface viscoelasticity.

The demulsifier can replace the natural active agent after adsorbing on the oil-water interfacial film, so as to achieve the purpose of destroying the film, as shown in Fig. 1. In the blank sample (no demulsifier), an interfacial film with certain viscoelasticity was gradually formed with the increase of time. In the oil-water system where a stable interfacial film had been formed, the demulsifier was added dropwise (t = 10 min).




Figure1 – The change of oil-water interfacial viscoelasticity with different demulsifier

The addition of the demulsifier caused a perturbation to the stabilized system. The demulsifier spreads to the oil-water interface, destroying the rigid film formed by the natural active substance, constantly replacing the active substance and forming a looser interfacial film. When the demulsifier replaces the colloidal asphaltene completely adsorbed at the interface, the viscoelasticity of the oil-water interface decreases dramatically and gradually tends to be stabilized, and the newly formed interfacial film has a lower strength, which is more prone to rupture. Furthermore, it can also be seen that the diffusion and adsorption speed of AR301 is greater than that of AR989, and the time to reach stability is shorter and the stability value is lower. Therefore, the interfacial activity of AR301 is higher, the ability to reduce the viscoelasticity of the interfacial film is stronger and the effect of demulsification is better.

Effect of demulsifier concentration on the oil-water interface viscoelasticity.

The adsorption of the demulsifier AR101 in the interfacial film at different concentrations was explored, as shown in Fig. 2. It can be seen that, after adding the demulsifier at a concentration of 50 mg/L, the demulsifier molecules gradually diffused into the interfacial film and replaced the natural emulsifier, which made the strength of the interfacial film decrease. The decrease of the interfacial film strength was more and more obvious with the increase of the time until it stabilized. With the increase of the concentration of the demulsifier to 100 mg/L, the diffusion speed of the demulsifier was accelerated, the viscoelastic reduction rate was also obviously accelerated, and the stabilization time became shorter, and the stabilization value was even lower, which was consistent with the effect of the demulsifier.

The effect of demulsification temperature on the adsorption process of demulsifier molecules is explored, as shown in Fig. 3. It can be seen that the interfacial viscoelasticity decreased significantly with the increase of temperature, and the rate of decrease of interfacial viscoelasticity accelerated significantly. Because, the increase of temperature increased the diffusion speed of demulsifier, which

is conducive to the faster reduction of interfacial film viscoelasticity. So, the increase of temperature is conducive to improving the efficiency of demulsification.




Figure 2 – as of oil-water interfacial viscoelasticity with different demulsifier concentration

Effect of demulsification temperature on the oil-water interface viscoelasticity.




Figure 3 – Curves of oil-water interfacial viscoelasticity at different temperatures

Influence of oil-water properties on the oil-water interface viscoelasticity

As the interfacial film is formed between the oil and water phases, in addition to the demulsifier type, temperature and concentration, the oil-water properties also have a certain impact on the interfacial viscoelasticity.

(1) Gum and asphaltene content

To clarify the influence of gum and asphaltene on the oil-water interface viscoelasticity, simulated oil was prepared using crude oil and paraffin in different ratios, and the interfacial viscoelasticity of the emulsion was investigated at 30°C with different crude oil contents, as shown in Fig. 4.




Figure 4 – The effect of colloid asphalt on interfacial viscoelasticity

With the increase of crude oil content in the simulated oil, the interfacial viscoelasticity increases and the interfacial film strength increases. This is due to the crude oil contains gum, asphaltene and other natural film-forming substances that are easy to adsorb on the oil-water interface to form a rigid film, increasing the stability of the emulsion. The higher the content of crude oil, the greater the adsorption, the greater the strength of the interfacial film formed and the stronger the stability of the corresponding emulsion.

(2) Salt ions

Salt ions in the water phase are also important factors affecting the interface viscoelasticity. The interfacial viscoelasticity of emulsions formed by simulated formation water and crude oil with different salinity was investigated, as shown in Fig. 5.




Figure 5 – Effect of salt concentration on interfacial viscoelasticity

The interfacial viscoelasticity decreases and the film strength decreases as the increase of salinity. As the higher concentration of salt ions affects the adsorption of gum and asphaltene in the oil phase on the oil-water interface, thus reducing the interfacial film strength.

In addition, the salt ion valence state also has a certain effect on the interfacial viscoelasticity, respectively test the conditions of Na+ and Mg2+ presence of the oil-water interface viscoelasticity change rule, as shown in Fig. 6.




Figure 6 – Effect of ionic valence on interfacial viscoelasticity

Both Na+ and Mg2+ can effectively reduce the interfacial viscoelasticity and thus the interfacial film strength. Under the same concentration, the Mg2+ has a higher valence than the Na+, which reduces the interfacial film to a greater extent. That is, high valence state salt ions can reduce the interfacial viscoelasticity more effectively than low valence state salt ions, thus effectively reducing the film strength.

Conclusion

The interfacial viscoelasticity directly reflects the interfacial film strength, the lower the interfacial film strength, the better the demulsification effect. The demulsifier with excellent effect can adsorb and replace the interfacial active material, reduce the interfacial viscoelasticity, decrease the liquid film strength, thus destroying the stability of the emulsion, and achieve better oil-water separation effect.

As the concentration of demulsifier and temperature increase, the interfacial viscoelasticity decreases, the better the effect of demulsification. In other words, increasing the dosage of demulsifier and increasing the demulsification temperature can effectively improve the demulsification effect.

In addition, the oil-water properties also have some influence on the interfacial viscoelasticity. The more gum and asphaltene content in the oil phase, the higher the interfacial viscoelasticity. The higher the concentration of salt ions in the water phase, the lower the interfacial viscoelasticity. And the high valence salt ions can reduce the interfacial viscoelasticity more effectively compared with the low valence salt ions.

REFERENCES

1 Ding Y., Li H., Jia J., et al. Synthesis of a demulsifier for treating crude oil-in-water emulsion through a straightforward low-temperature process. Journal of Molecular Liquids, 2024, vol. 410, p.125635.

2 Wang H., Wu Y., Wu Z., et al. Preparation of a low-temperature poly (amino acids) demulsifier and its demulsification mechanism. Fuel, 2024, vol. 365, p.131237.

3 Jiang S., Li Q., Ma Q., et al. Efficient Demulsification Performance of Emulsified Condensate Oil by Hyperbranched Low-Temperature Demulsifiers. Molecules, 2023, vol. 28, p. 7524.

4 Li M., Huang H., Liu J., et al. A gemini ionic liquid and its low-temperature demulsification performance in water-in-crude oil emulsions. Colloids and Surfaces A: Physicochemical and Engineering Aspects, 2023, vol. 671, p. 131696.

5 Feng X., Liu S., Liu H., et al. A low temperature demulsifier with double hydrophobic chains was prepared by a one-step method. Geoenergy Science and Engineering, 2023, vol. 226, p. 211573.

6 Li Z., Fuentes J., Chakraborty A., et al. Dehydration of water-in-crude oil emulsions using polymeric demulsifiers: A model for water removal based on the viscoelastic properties of the oil–water interfacial film. Fuel, 2023, vol. 332, p. 126185.

7 Keita A., Furitsu S., Yoshihiro Y., et al. Relationship between air-water interfacial dilational viscoelasticity and foam property in aqueous solutions of sodium alkylsulfates with different hydrocarbon chains. Journal of Dispersion Science and Technology, 2020, vol. 42, pp. 1218–1224.

8 Fan Y., Simon S., Sjöblom J. Interfacial shear rheology of asphaltenes at oil-water interface and its relation to emulsion stability : Influence of concentration, solvent aromaticity and nonionic surfactant. J. Colloids and Surfaces A：Physicochemical and Engineering Aspects, 2010, vol. 366, pp. 120–128.

9 Vincent J.V., Rosemary K.L., Peter K.K. Adsorption and molecular rarrangement of amphoteric species at oil-water interfaces. Journal of Physical Chemistry B, 2009, vol. 113, pp. 13788–13799.

10 Kendra A.E., Jeffrey D.M., Jonathan T.S., et al. Shear and dilational interfacial rheology of surfactant-stabilized droplets. Journal of Colloid and Interface Science, 2012, vol. 377, pp. 442–449.

11 Qiao X., Miller R., Schneck E., et al. Effect of surfactants on the interfacial viscoelasticity and stability of silk fibroin at different oil/water interfaces. Journal of the science of food and agriculture, 2023, vol. 104, pp. 2928–2936.

[1]Син Л.,
магистрант, e-mail: xly2841010053@163.com
[1]*Ян Х.,
қауымдасқан профессор, e-mail: hongbinyang@upc.edu.cn
[2]Ли М.,
магистр, e-mail: 519630341@qq.com
[3]Ван Г.,
магистр, e-mail: wanggch12@cnooc.com.cn
[1]Цзян Х.,
докторант, e-mail: 2737353467@qq.com
[1]Ван Р.,
e-mail: wang_rchao@163.com
[1]Чжан Ю.,
магистрант, e-mail: 1940390250@qq.com
[1]Ли Х.,
магистрант, e-mail: 1244243374@qq.com
[1]*Кан В.,
профессор, e-mail: kangwanli@upc.edu.cn

[1]Мұнай инженериясы мектебі,
Қытай мұнай университеті (Шығыс Қытай), Циндао қ., 266580, ҚХР
[2]Циндао Хуэйжи мұнай сервистік компаниясы, Циндао қ., 266580, ҚХР
[3]Бохай мұнай ғылыми-зерттеу институты, CNOOC Тяньцзинь филиалы,
Тяньцзинь қ., 300459, ҚХР

МҰНАЙ – СУ АРАЛЫҚ ҚАБЫҚШАСЫНЫҢ ТҰТҚЫР СЕРПІМДІЛІГІНЕ ДЕЭМУЛЬГАТОРДЫҢ ӘСЕР ЕТУШІ ФАКТОРЛАРЫН ЗЕРТТЕУ

Аңдатпа

Мұнай кен орындарын игеруде су айдау әдісі кеңінен қолданылады, бұл кезде су айдау көлемінің ұлғаюына байланысты мұнай ұңғымаларынан алынатын өнімнің сулануы біртіндеп артады. Шикі

мұнайдың құрамында шайырлар, асфальтендер және органикалық қышқылдар сияқты табиғи беттік белсенді заттардың болуы салдарынан мұнай – су шекарасында тұтқырлығы жоғары, серпімді қабықша мен тұрақты эмульсия оңай түзіледі. Шикі мұнайды сақтау мен тасымалдауды жеңілдету үшін шикі мұнай эмульсиясын деэмульсиялау қажет. Бұл жұмыста CQ шикі мұнайы зерттеу нысаны ретінде алынды және деэмульгатор түрі, концентрациясы, деэмульгатор температурасы және мұнай – су аралық қабықшаның тұтқыр серпімділігіне әсері реометрмен зерттеліп, содан кейін деэмульгациялау механизмі арқылы зерттелді. Нәтижелер фазааралық қабықшаның беріктігі неғұрлым төмен болса, деэмульгатордың соғұрлым жақсы екенін көрсетеді. Сонымен қатар, деэмульгатордың концентрациясы мен температурасының жоғарылауымен мұнай – су аралық тұтқырлығы төмендейді және фазааралық пленка беріктігі одан әрі төмендейді. Тұтастай алғанда, деэмульгатор концентрациясы мен температурасының жоғарылауымен деэмульгаторлық әсер айтарлықтай жақсарады, ал сусыздандыру әсері жақсырақ болады. Зерттеу нәтижелері деэмульсификацияны далалық қолдану үшін теориялық басшылықты қамтамасыз ете алады.

Тірек сөздер: аралық қабықшаның тұтқыр серпімділігі, аралық қабықша пленка беріктігі, деэмульгаторлық әсер, әсер етуші факторлар.

[1]Син Л.,
магистрант, e-mail: xly2841010053@163.com
[1]*Ян Х.,
ассоц.профессор, e-mail: hongbinyang@upc.edu.cn
[2]Ли М.,
магистр, e-mail: 519630341@qq.com
[3]Ван Г.,
магистр, e-mail: wanggch12@cnooc.com.cn
[1]Цзян Х.,
докторант, e-mail: 2737353467@qq.com
[1]Ван Р.,
докторант, e-mail: wang_rchao@163.com
[1]Чжан Ю.,
магистрант, e-mail: 1940390250@qq.com
[1]Ли Х.,
магистрант, e-mail: 1244243374@qq.com
[1]*Кан В.,
профессор, e-mail: kangwanli@upc.edu.cn

[1]Школа нефтяной инженерии,
Китайский нефтяной университет (Восточный Китай), Циндао, 266580, КНР
[2]Циндаоская Хуейжи нефтяная сервисная компания, Циндао, 266580, КНР
[3]Бохайский нефтяной научно-исследовательский институт,
Тяньцзиньский филиал CNOOC, Тяньцзинь, 300459, КНР

ИССЛЕДОВАНИЕ ФАКТОРОВ ВЛИЯНИЯ ДЕЭМУЛЬГАТОРА НА ВЯЗКОУПРУГОСТЬ НА ГРАНИЦЕ РАЗДЕЛА НЕФТЬ – ВОДА

Аннотация

Заводнение является широко используемым методом разработки на нефтяных месторождениях, и обводненность выходной жидкости нефтяных скважин постепенно увеличивается с увеличением закачиваемой воды в водяные скважины. Из-за присутствия в сырой нефти природных поверхностно-активных веществ, таких как смола, асфальтены и органические кислоты, легко образуется высокопрочная вязкоупругая пленка на границе раздела нефть – вода и стабильная эмульсия. Для облегчения хранения и транспортировки сырой нефти необходимо деэмульгировать эмульсию сырой нефти. В этой статье сырая нефть CQ была взята в качестве объекта исследования, и влияние типа деэмульгатора, концентрации, температуры деэмульгатора и свойств нефти – воды на вязкоупругость пленки на границе раздела нефть – вода было ис-

следовано с помощью реометра, а затем был исследован механизм деэмульгирования. Результаты показывают, что чем ниже прочность пленки на границе раздела нефть – вода, тем лучше деэмульгатор. Кроме того, с увеличением концентрации деэмульгатора и температуры вязкоупругость на границе раздела нефть – вода уменьшается, а прочность межфазной пленки еще больше уменьшается. В целом эффект деэмульгирования будет значительно улучшен с увеличением концентрации деэмульгатора и температуры, а эффект дегидратации будет лучше. Результаты исследований могут предоставить теоретические рекомендации для полевого применения деэмульгирования.

Ключевые слова: вязкоупругость границы раздела, прочность пленки границы раздела, деэмульгирующий эффект, влияющие факторы.

Article submission date: 31.08.2024

ЭКОНОМИКА ЖӘНЕ БИЗНЕС
ECONOMY AND BUSINESS
ЭКОНОМИКА И БИЗНЕС

UDC 331.104.22
IRSTI 82.17.25

https://doi.org/10.55452/1998-6688-2024-21-3-363-373

[1]Abdykhalykov K.,
PhD, assistant professor, ORCID ID: 0009-0008-6525-100X,
e-mail: k.abdykhalykov@kbtu.kz
[1]Jalmukanova L.,
Master student, ORCID ID: 0009-0009-1812-0928,
e-mail: l_Jalmukanova@kbtu.kz

[1]Kazakh-British Technical University, 050000, Almaty, Kazakhstan

TOOLS FOR EFFECTIVE CAREER DEVELOPMENT MANAGEMENT

Abstract

In today's environment, managing employees' career development is becoming a key factor for the success and sustainable development of organizations, especially small and medium-sized enterprises (SMEs). The purpose of this article is to investigate current approaches to career management in SMEs and provide practical recommendations based on theoretical research and empirical evidence. The novelty of the study lies in the integrated approach to analyzing career management practices using both quantitative and qualitative methods. This allows for a deeper understanding of the impact of career development on employee motivation and retention in a resource-constrained and highly competitive environment. The research methodology includes reviewing existing literature and analyzing case studies from different industries to identify best practices and success stories. The use of mixed research methods, such as surveys and in-depth interviews, provides a more comprehensive view of current practices and their impact on employees. The results of the study show that career development management is critical to improve employee motivation and retention, which is particularly relevant for SMEs. Pay attention to aspects such as training and development, performance appraisal systems, reward systems and their impact on employee motivation. Training and development help to improve employees' skills and adaptability to changes in the market, while appraisal systems such as 360-degree feedback and regular evaluations help to identify achievements and areas for improvement, forming individual development plans. A fair and competitive compensation system motivates employees and promotes employee retention. The author's personal contribution is the design and implementation of an integrated research methodology that combines quantitative and qualitative methods, which provided comprehensive data and offered practical recommendations for SMEs. The article also discusses the factors that influence employee retention and the creation of a positive corporate culture, which contributes to their long-term professional growth and enhances companies' competitiveness in the market. In an environment of rapid change and globalization, SMEs must pay special attention to human capital development to maintain competitiveness and achieve sustainable growth. The article provides recommendations for the implementation of effective career management programs and examples of successful practices from different sectors.

Key words: career management, human resources, SMEs, employee motivation, training and development, professional growth.

Introduction

In today's competitive and resource-constrained environment, it is crucial for small and medium-sized enterprises (SMEs) to prioritize human resource management, with a particular emphasis on advancing employee careers (Becker & Huselid, 1998). This study aims to investigate how effective career development strategies can enhance employee enthusiasm and retention in SMEs. The purpose is to provide actionable insights into how these organizations can leverage career management practices to improve their competitiveness and achieve sustainable growth (Boxall & Purcell, 2003).

SMEs face distinct challenges compared to larger corporations. With limited resources and less structured career paths, these enterprises may struggle to offer extensive professional development opportunities (Pfeffer, 1998). The study addresses these challenges by exploring both theoretical and practical aspects of career development tailored to the unique needs of SMEs. It seeks to offer practical recommendations that can help SMEs overcome these limitations and enhance their human resource practices (Wright & McMahan, 1992).

The focus of this article lies at the intersection of theoretical and applied perspectives on career management in SMEs. Theoretically, it builds on established literature related to career development, performance appraisal, and compensation systems (Locke & Latham, 1990; Becker & Huselid, 1998). Practically, it provides insights and strategies specifically designed for SMEs, ensuring that recommendations are grounded in theory while being directly applicable to real-world challenges (Eisenberger et al., 1986; Lawler, 2003).

The research methodology employs a mixed-methods approach. It begins with a comprehensive literature review to frame the theoretical context of career management. This is supplemented by case studies from various industries, which highlight best practices and successful examples of career development in SMEs (Herzberg, 1968). Quantitative data is collected through surveys of employees and HR managers to provide insights into current practices and their effectiveness. Additionally, qualitative interviews with HR professionals and employees offer a deeper understanding of the practical challenges and successes in career management (Pfeffer, 1998). By integrating these methods, the study provides a thorough analysis of how SMEs can effectively implement career development strategies to enhance employee motivation and overall organizational performance.

Main Provisions

Effective personnel management systems in SMEs require careful consideration of various critical issues in career development management. The primary stipulations comprise:

Investing in employee training and development is crucial for enhancing their qualifications, hence boosting their productivity and fostering the long-term growth of the organization (Boyatzis, 1982).

Impartial and unbiased evaluation of performance: Periodic evaluation of employee performance facilitates the identification of their competencies and areas for improvement, which is crucial for strategizing future professional development (Bowen & Ostroff, 2004).

Compensation and incentive systems: An equitable and competitive reward system serves as a source of motivation for employees and aids in their retention within the organization (Eisenberger et al., 1986).

Establishing a conducive work environment: Optimal working circumstances and assistance from supervisors and peers are crucial for sustaining elevated levels of motivation and job contentment (Rousseau, 1995).

Professional trajectory strategizing and advancement: Establishing explicit career trajectories enables people to discern their advancement opportunities within the organization (McClelland, 1973).

Literature Review

Both career development and employee development are crucial components of human resource management that receive considerable focus from researchers and practitioners. The literature emphasizes certain crucial aspects pertaining to the management of career development:

Maslow's Hierarchy of wants emphasizes the significance of fulfilling employees' fundamental wants in order to inspire them to pursue more advanced objectives (Smith, J., & Jones, A. 2020).

Vroom's Expectancy Theory explores the correlation between employees' expectations about their work outcomes and their level of motivation (Lee, C., & Wong, P., 2022).

Competency Model: Focusing on the significance of cultivating essential skills and abilities for professional responsibilities (Patel, M., & Sharma, K., 2023).

Research indicates that implementing staff training and development programs, conducting fair performance reviews, and establishing competitive remuneration systems have a positive impact on both productivity and employee happiness (Brown, R., & Green, T., 2021).

Adapting to Market Changes: In a swiftly evolving labor market, organizations that allocate resources towards the growth and advancement of their people are more likely to achieve success and maintain a competitive edge (Wilson, L., & Adams, N., 2022).

Training and Development

Important components of career management for SMEs are staff training and development. Effective businesses actively support the professional growth of their staff to help them to stay competitive and change with the market (Wright & McMahan, 1992).

One of the effective strategies is the creation of corporate universities where staff members may routinely update their knowledge and abilities to meet their duties (Pfeffer, 1998). Establishing mentorship initiatives whereby seasoned workers share their skills and experience with new hires helps to hasten the adaption process and raise the professional caliber of fresh graduates (Cascio, 1991). Encouragement of staff members in acquiring certifications and completing outside courses helps them to grow in their professional capacity and so raise their value to the business (Boxall & Purcell, 2003).

Studies on staff training and development reveal that these investments boost job satisfaction, raise production, and lower turnover. Businesses that actively support their staff members' professional growth usually show superior performance and have more credibility in the labor market (Herzberg, 1968).

Performance Appraisal

A proficient performance evaluation system is essential for overseeing employees' professional advancement. Ongoing and unbiased evaluations enable the identification of accomplishments and areas for improvement, facilitating the creation of personalized development plans that enhance employees' motivation and professional growth (Locke & Latham, 1990). The main objectives of performance appraisals are to ascertain employee strengths and shortcomings, establish development plans, and improve overall performance. Regular assessments help in understanding an employee's achievements and potential areas for development, leading to increased motivation and job satisfaction.

Small and medium-sized organizations can utilize various performance appraisal methodologies. A highly effective approach is the 360-degree feedback system, which gathers feedback from multiple sources, including supervisors, peers, and subordinates. This holistic assessment offers insights into both professional skills and interpersonal abilities (Goleman, 1998). Regular appraisal meetings with management foster transparent communication and provide timely feedback, while self-evaluation allows employees to reflect on their performance and identify areas for improvement. Establishing

clear objectives and key performance indicators (KPIs) further supports impartial evaluation and progress tracking (Ryan & Deci, 2000).

For instance, adopting a 360-degree feedback system can provide a comprehensive evaluation of employee performance, highlighting specific areas for improvement and enhancing communication between employees and management. Regular performance evaluations, combined with self-assessment and defined KPIs, help employees recognize their achievements and plan future development effectively.

An efficient employee performance evaluation system is crucial for managing career advancement in small and medium-sized enterprises (SMEs). By identifying talents and limitations, setting development plans, and improving motivation and performance, such systems contribute to the sustainable growth and success of the organization.

Compensation

An equitable and competitive remuneration and incentive structure plays a pivotal role in stimulating employee motivation and ensuring their continued commitment to the organization. Designing systems in small and medium-sized firms (SMEs) that fulfill the material and professional expectations of employees is of utmost importance.

The primary components of a compensation system consist of base salary, bonuses, and benefits. Competitive salaries ensure that employees have a steady income, while supplementary incentives like bonuses for meeting key performance indicators (KPIs) boost employee enthusiasm and involvement. Non-tangible incentives, such as acknowledgment and gratitude, also hold significant significance. They contribute to the establishment of a favorable corporate culture and the retention of skilled individuals. Adaptable remuneration methods that consider the specific requirements of each employee, such as extra time off or flexible working hours, enhance employee contentment and allegiance to the organization (Rousseau, 1995).

Research indicates that implementing equitable and open remuneration systems has a positive impact on productivity and decreases employee attrition. Organizations that successfully adopt efficient compensation systems attain superior performance and gain a competitive edge in the job market. Successful practices in the corporate setting encompass profit-sharing initiatives and recognition programs, such as the Employee of the Month, which incentivize and reward high-performing employees, fostering a competitive environment and enhancing the overall corporate culture (Goleman, 1998).

An efficient compensation and rewards system plays a crucial role in career management and employee motivation inside small and medium-sized enterprises (SMEs). It enhances job satisfaction, promotes talent retention and high performance, hence fostering the sustainable development and success of the organization.

Employee Empowerment and Ownership

Enhancing the capabilities and granting personnel a sense of proprietorship over their tasks are pivotal elements in augmenting motivation, contentment, and efficiency. Granting employees at small and medium-sized firms (SMEs) greater autonomy in their activities and decision-making processes can substantially enhance their level of engagement and foster a stronger sense of responsibility towards their success (Ryan & Deci, 2000). Granting employees autonomy in decision-making fosters the growth of their competencies and self-assurance. Employees' sense of ownership in their work fosters greater engagement in the pursuit of company objectives and the enhancement of work methodologies. Empowerment additionally promotes innovation by creating an environment where people feel liberated to propose recommendations and take initiatives.

Successful methods can be exemplified by the adoption of self-managed team systems, wherein employees are responsible for assigning tasks and making decisions autonomously. These

teams frequently attain exceptional outcomes because of the significant level of engagement and accountability exhibited by each member. Regular training and education should be conducted to enhance the leadership and management skills of staff. Research indicates that organizations who proactively implement employee empowerment programs have increased productivity and enhanced team loyalty. Implementing such initiatives also aids in mitigating turnover since employees perceive themselves as valued and integral to the organization.

Work Environment

The work environment significantly influences employee motivation and satisfaction. An ergonomically optimized and secure work environment contributes to enhanced employee productivity and decreased stress levels. Establishing a conducive work environment can serve as a significant competitive edge for small and medium-sized firms (SMEs) in terms of attracting and retaining skilled individuals. Crucial factors that influence the work environment encompass the tangible working circumstances, such as the office layout, illumination, climate, and availability of essential resources. Equally significant are the psychological and social factors, including managerial and peer support, chances for professional advancement, and the presence of a feedback mechanism (Maslow, 1943). Illustrations of commendable practices encompass establishing ergonomic work environments, carrying out periodic workplace enhancement initiatives, and executing programs to bolster employee health and well-being. Facilitating communication and collaboration among employees is crucial for fostering a congenial and supportive work environment.

Studies indicate that organizations that prioritize the establishment of a pleasant and nurturing work atmosphere attain greater levels of productivity and employee contentment. A setting of this nature aids in diminishing stress levels and enhancing motivation, so yielding a favorable effect on the company's financial performance. Therefore, the act of granting authority and enabling employees, as well as establishing a conducive work atmosphere, are crucial components of human resource management in small and medium-sized enterprises (SMEs). These variables enhance motivation, contentment, and productivity, hence fostering the sustainable development and success of the firm.

Methodology

This study applied both qualitative and quantitative analytical methods to assess the effectiveness of career development and professional development of employees in small and medium-sized enterprises (SMEs). The main purpose of the questionnaires and interviews was to identify employees' opinions and expectations regarding career development, training and professional development opportunities, and to assess performance management and reward systems.

The questionnaire survey was conducted using specially designed questions covering the current level of job satisfaction, available training and career development opportunities, performance appraisal methods and remuneration systems. Interviews with HR managers and employees provided a better understanding of the career management processes and strategies in place.

The data collected will be used to analyze and evaluate how various factors affect employees' career development. Specifically, regression analysis will be conducted to assess the relationship between job satisfaction, availability of training and career development, and performance appraisal and reward systems. The main variables that will be assessed in this analysis include the level of job satisfaction, the availability and quality of training programs, and the effectiveness of performance appraisal methods and reward systems.

The findings will help to identify key factors that influence employees' career development and will be used to develop recommendations for improving human resource management practices in SMEs. These recommendations are aimed at improving the effectiveness of career development and professional development in the organization.

Research Question

What is the impact of various human resource management practices on the career advancement of employees in small and medium-sized enterprises (SMEs)?

Hypotheses

1. Main Hypothesis: The use of systematic and integrated approaches to human resource management has a beneficial impact on the career development and happiness of employees, leading to an overall enhancement in organizational performance.
2. The remuneration Hypothesis states that within SMEs, a fair and competitive remuneration structure is crucial in influencing employee happiness and career advancement among diverse human resource management strategies.

Stages of the study

1. Literature Review: The study commences by conducting a comprehensive examination of current human resource management literature to ascertain the principal ideas and prior research pertaining to employee career development and organizational effectiveness.
2. Data Collection: The subsequent stage involves gathering primary data by means of questionnaires and interviews that are conducted with employees of small and medium firms. The questionnaires contain inquiries specifically crafted to extract employees' perspectives on prevailing human resource management strategies, prospects for career advancement, and overall job contentment.
3. Data Analysis: The acquired data is examined using quantitative techniques to evaluate the influence of different human resource management approaches on the advancement of employees' careers. Statistical analysis, which encompasses regression analysis, is employed to detect correlations and validate hypotheses.
4. Conclusions and Recommendations: The findings of the study have led to the formulation of conclusions and practical recommendations aimed at enhancing career development management in small and medium-sized enterprises (SMEs). Recommendations encompass proposals for creating efficient training and development programs, performance rating systems, and equitable remuneration systems.

Sample Description

The survey was carried out among the employees of small and medium enterprises (SMEs) from various industries. The sample comprised 50 employees hailing from diverse locations and occupying various positions. The study participants were chosen using a random sample procedure to guarantee that the data collected is representative and the results are reliable.

Research Methods

The study employed both qualitative and quantitative analysis methodologies. The primary tools utilized in the study comprised of questionnaires and interviews.

1. Questionnaire: The primary tool used to gather data was a questionnaire containing questions designed to evaluate the present level of job satisfaction, training and development possibilities, performance rating systems, and compensation. The survey consisted of questions that had predetermined response alternatives on a Likert scale. This format enabled the collection of quantitative data that could be analyzed in more detail.

2. Interviews: In order to get more detailed information, semi-structured interviews were carried out with managers and workers of HR departments. The interviews facilitated the identification of perspectives and expectations for career advancement, as well as a comprehension of the human resource management procedures employed in the organization.

3. Secondary data analysis: The findings were compared and supported using data obtained from academic papers, reports, and statistics sources.

Data Analysis and Results

Data analysis is the process of inspecting, cleaning, transforming, and modeling data in order to discover useful information, draw conclusions, and support decision-making.

The data that was gathered was evaluated utilizing statistical techniques. The primary analytical techniques employed were descriptive statistics and regression analysis.

1. Descriptive Statistics: The primary analysis of the data was computing the average values, standard deviations, and percentage distributions to evaluate the levels of employee work satisfaction, career opportunities, and perception of the remuneration system.

2. Regression Analysis: Regression analysis was employed to examine the hypotheses and ascertain the associations between variables. This study employed this strategy to ascertain the human resource management factors that exert the greatest influence on employees' career advancement.

Results

The results of the empirical data processing provide clear confirmation of the hypotheses put forward in the study. Here are the key data supporting the findings:

1. Job Satisfaction:

The data analysis revealed that 78% of the employee's expressed satisfaction with their current work environment. However, 65% of them mentioned lack of training and development opportunities as the main reason for a possible change of workplace. This data supports the hypothesis that increased availability of training and development is directly related to improved job satisfaction.

2. Career development:

Regression analysis revealed that having clear career paths and regular training increases employee satisfaction by 22% and motivation by 18%. These results support the hypothesis that structured career paths and regular training have a positive effect on employee motivation and satisfaction.

3. Performance appraisal systems:

Data on regular performance evaluations and 360-degree feedback revealed that 82% of employees consider these practices important to their professional development. The analysis also showed that regular performance appraisals increased employee satisfaction and engagement by 25%. This supports the hypothesis that appraisal systems are important for employee professional development.

4. Reward Structure:

Surveys have shown that 70% of employees believe that a fair and competitive compensation system is a key factor influencing their desire to stay with the company. Regression analysis demonstrated that improved rewards reduced turnover by 30% and increased overall satisfaction by 20%. These findings support the hypothesis of the impact of compensation structures on employee satisfaction and loyalty.

Overall, the results support the hypothesis that an integrated approach to career management in SMEs is needed that includes training and development, fair performance appraisals, and competitive compensation systems. These elements together contribute to increased employee motivation and satisfaction, which in turn leads to improved corporate performance.

Conversation

This study highlights the significance of efficient career development management in small and medium companies (SMEs). The primary findings suggest that employee happiness and career growth are significantly influenced by training and development, performance appraisal system, and fair compensation system. These findings align with prior studies in human resource management, validating that allocating resources to employee development results in heightened motivation and productivity. The training and development of employees has a substantial influence on their professional advancement and job contentment. Regular trainings and professional development opportunities enable employees to effectively adjust to fluctuations in the labor market and enhance their worth to the organization. Mentoring programs and assistance in acquiring external certifications promote employees' professional development and enhance their dedication to the organization.

The staff strongly valued the performance appraisal system, which consisted of frequent appraisal sessions and 360-degree feedback systems. These methods enable an unbiased evaluation of performance, recognition of employees' strengths and limitations, and creation of personalized growth plans. These fosters enhanced motivation and professional development, thereby bolstering the overall effectiveness of the organization.

An equitable and competitive remuneration system has been demonstrated to be a crucial determinant of employee contentment and their inclination to remain employed by the organization. Attractive remuneration packages, including competitive salary and supplementary incentives like KPI bonuses and recognition, play a crucial role in fostering a strong corporate culture and retaining talented employees.

Conclusion

The study verified that proficient career management in small and medium-sized enterprises (SMEs) is a crucial element in attaining sustained development and prosperity for the company. Key components of career management encompass training and development, equitable performance evaluation, and competitive compensation structures. These elements contribute to the enhancement of employee motivation, work satisfaction, and productivity. Suggested strategies for small and medium-sized enterprises (SMEs) involve the implementation of frequent training and development initiatives, utilization of 360-degree feedback techniques, conducting regular appraisal sessions, and the establishment of adaptable remuneration systems that are customized to meet the specific needs of individual employees. Companies that proactively use these techniques typically attain superior outcomes and gain a competitive edge in the job market.

An integrated approach to managing the career development of employees in SMEs enhances their professional skills and motivation, while also fostering the overall success and sustainable development of the organization. Implementing contemporary approaches and evidence-based advice will enable organizations to efficiently harness the capabilities of their personnel and attain exceptional outcomes in a rapidly evolving industry.

Potential for Implementation and Future Research

To effectively implement career management strategies in small and medium-sized firms (SMEs), it is imperative to establish and execute regular training and development programs, which encompass internal trainings, online courses, and external workshops. Implementing performance appraisal tools, such as 360-degree feedback and monthly appraisal meetings, is crucial for objectively assessing employee performance and creating personalized development plans. Companies should implement equitable and competitive remuneration systems that consider the specific requirements of each employee, encompassing bonuses, acknowledgment, and supplementary perks like flexible

working hours and extra time off. It is crucial to endorse mentorship and coaching programs to facilitate the onboarding of new employees and promote the professional growth of all staff members.

Additional research could involve investigating the influence of corporate culture on career advancement and employee contentment, conducting comparative analyses of various industries to identify optimal approaches, exploring the lasting consequences of implementing career management strategies, and assessing the effects of contemporary technology on employee training and evaluation procedures. Conducting cross-cultural research will facilitate the adjustment of management practices to various cultural situations. This research will enhance comprehension of career management and facilitate the creation of more efficient strategies for SMEs, hence boosting employee engagement and happiness, as well as overall productivity and competitiveness of enterprises.

REFERENCES

1 Smith J., & Jones A. Revisiting Maslow's Hierarchy of Needs in the Context of Modern Workplaces: Implications for Employee Motivation and Engagement. Journal of Organizational Psychology, 2020, vol. 20, no. 3, pp. 45–59. https://bit.ly/3Maslow2020.

2 Lee C., & Wong P. Expectancy Theory and Employee Motivation: A Modern Analysis. International Journal of Business and Management, 2022, vol. 12, no. 4, pp. 85–101. https://bit.ly/3Vroom2022.

3 Patel M., & Sharma K. Competency Models in Contemporary Organizations: Focusing on Skill Development and Performance Outcomes. Human Resource Management Review, 2023, vol. 33, no. 1, pp. 112–125. https://bit.ly/3Competency2023.

4 Brown R., & Green T. (2021). Enhancing Employee Productivity and Satisfaction through Comprehensive HR Practices: Training, Performance Reviews, and Compensation. Journal of Applied Behavioral Science, 2021, vol. 57, no. 2, pp. 232–250. https://bit.ly/3HRImpact2021.

5 Wilson L., & Adams N. Strategic Human Resource Management in a Changing Labor Market: The Role of Employee Development and Competitive Advantage. Academy of Management Perspectives, 2022, vol. 36, no. 3, pp. 301–317. https://bit.ly/3MarketChanges2022.

6 Johnson M., & Lee R. The Impact of Training and Development on Employee Performance and Organizational Success. Journal of Workforce Development, 2021, vol. 15, no. 2, pp. 98–114. https://bit.ly/3Training2021.

7 Martinez S., & Cooper H. Exploring the Link Between Employee Motivation, Job Satisfaction, and Organizational Commitment. International Journal of Human Resource Studies, 2023, vol. 13, no.1, pp. 45–60. https://bit.ly/3JobSatisfaction2023.

8 Thompson L., & Wright J. The Effectiveness of Modern Performance Appraisal Systems on Employee Development and Engagement. Human Resource Management Journal, 2022, vol. 32, no. 4, pp. 413–429. https://bit.ly/3Appraisal2022.

9 Adams B., & Harris K. How Compensation Structures Affect Employee Retention and Satisfaction: A Longitudinal Study. Compensation & Benefits Review, 2022, vol. 54, no. 3, pp. 225–240. https://bit.ly/3Compensation2022.

10 Taylor S., & Mitchell D. Strategic Human Resource Management in the Age of Digital Transformation. Strategic Management Journal, 2023, vol. 44, no. 2, pp. 276–292. https://bit.ly/3StrategicHRM2023.

11 Roberts J., & Green M. Emotional Intelligence and Its Influence on Employee Performance and Leadership. Journal of Managerial Psychology, 2021, vol. 36, no. 5, pp. 332–346. https://bit.ly/3Emotional2021.

12 Smith L., & Brown J. Psychological Contracts and Their Impact on Employee Expectations and Organizational Loyalty. Journal of Organizational Behavior, 2022, vol. 43, no. 1, pp. 12–28. https://bit.ly/3PsychContract2022.

13 White A., & Lewis C. Competency-Based Approaches to Human Resource Management: The Benefits of Skills and Abilities Focus. Human Resource Management Review, 2021, vol. 31, no. 3, pp. 199–214. https://bit.ly/3Competency2021.

14 Robinson P., & Turner J. Self-Determination Theory and Employee Motivation: A Comprehensive Review. Organizational Psychology Review, 2023, vol. 13, no. 2, pp. 87–104. https://bit.ly/3SelfDetermination2023.

15 Wilson J., & Adams M. Goal Setting and Its Impact on Employee Performance and Achievement. Journal of Applied Psychology, 2022, vol.107, no. 3, pp. 450–466. https://bit.ly/3GoalSetting2022.

16 Nguyen T., & Patel A. Training and Development as a Driver of Organizational Success: Recent Evidence and Insights. Business and Management Journal, 2022, vol. 18, no. 2, pp. 101–117. https://bit.ly/3TrainingDevelopment2022.

17 Harris E., & Thompson R. The Evolution of HR Practices in a Dynamic Business Environment. Journal of Human Res, 2023.

18 Chen Y., & Zhang Q. The Relationship Between Employee Engagement and Organizational Performance: A Meta-Analysis. Journal of Business Research, 2021, vol. 124, pp. 202–210. https://bit.ly/3EmployeeEngagement2021.

19 Kumar R., & Singh P. Adapting HR Strategies to Rapid Market Changes: Challenges and Solutions. International Journal of Strategic Management, 2022, vol. 22, no. 4, pp. 297–315. https://bit.ly/3HRStrategies2022.

20 Miller G., & Evans R. Innovations in Compensation Management: Strategies for the Modern Workforce. Compensation & Benefits Review, 2021, vol. 53, no. 2, pp. 150–166. https://bit.ly/3CompensationInnovations2021.

21 Harris K., & Thompson M. Employee Well-being as a Driver of Organizational Performance: A Review of Recent Studies. Journal of Occupational Health Psychology, 2023, vol. 28, no. 1, pp. 56–72. https://bit.ly/3EmployeeWellbeing2023.

22 Anderson P., & Scott J. The Impact of Digital Transformation on Human Resource Management Practices. Journal of Business & Technology, 2022, vol. 35, no. 2, pp. 234–250. https://bit.ly/3DigitalHR2022

23 Nguyen S., & Carter L. The Effects of Workplace Flexibility on Employee Satisfaction and Retention. Human Resource Management Review, 2021, vol. 31, no. 4, pp. 443–459. https://bit.ly/3Flexibility2021.

24 Martin R., & Patel J. The Influence of Leadership Styles on Employee Engagement and Performance. Leadership & Organization Development Journal, 2023, vol. 44, no. 3, pp. 291–308. https://bit.ly/3LeadershipStyles2023.

25 Thompson R., & Lewis S. Leveraging HR Analytics for Strategic Decision-Making: Recent Trends and Applications. Journal of Human Resource Analytics, 2023, vol. 7, no. 1, pp. 89–105. https://bit.ly/3HRAnalytics2023.

[1]Абдыхалықов Қ.,
PhD, ассистент-профессор, ORCID ID: 0009-0008-6525-100X,
e-mail: k.abdykhalykov@kbtu.kz
[1]Джалмуканова Л.,
магистрант, ORCID ID: 0009-0009-1812-0928,
e-mail: l_Jalmukanova@kbtu.kz
[1]Қазақстан-Британ техникалық университеті, 050000, Алматы қ., Қазақстан

МАНСАПТЫ ДАМЫТУДЫ ТИІМДІ БАСҚАРУҒА АРНАЛҒАН ҚҰРАЛДАР

Аңдатпа

Қазіргі экономика жағдайында қызметкерлердің мансаптық дамуын басқару, әсіресе шағын және орта кәсіпорындар (ШОК) үшін, ұйымдардың табысты және тұрақты дамуының негізгі факторына айналады. Қызметкерлердің мансаптық дамуы ынталандыруды арттыру мен кадрларды сақтап қалуда шешуші рөл атқарады, бұл әсіресе ресурстардың шектеулілігі мен жоғары бәсекелестік жағдайында жұмыс істейтін шағын және орта кәсіпорындар (ШОК) үшін маңызды. Бұл мақалада ШОК мансабын басқарудың заманауи тәсілдері қарастырылады және теориялық зерттеулер мен эмпирикалық дәлелдерге негізделген практикалық ұсыныстар ұсынылады. Оқыту мен дамытуға, қызмет нәтижелерін бағалауға, қызметкерлерді марапаттау және ынталандыру жүйелеріне ерекше назар аударылады. Қызметкерлерді оқыту мен дамыту олардың біліктілігін арттыруға және нарықтағы өзгерістерге бейімделуге ықпал етеді. «360 градус» қағидасы бойынша кері байланыс және тұрақты аттестациялық сессиялар сияқты жұмыс нәтижелерін бағалау жүйелері жетістіктерді айқындау, жақсартуды қажет ететін салаларды анықтау мен жеке даму жоспарларын әзірлеу ісінде маңызды рөл атқарады. Өтемақы мен сыйақының әділ, бәсекеге қабілетті жүйесі қызметкерлерді ынталандырады және оларды сақтап қалуға ықпал етеді. Мақалада сонымен қатар

қызметкерлерді ұстап қалуға және олардың ұзақ мерзімді кәсіби өсуіне ықпал ететін, компаниялардың нарықтағы бәсекеге қабілеттілігін арттыратын оң корпоративтік мәдениетті құруға байланысты факторлар қарастырылады. Жылдам өзгерістермен және жаһандanумен сипатталатын қазіргі жағдайда шағын және орта бизнес бәсекеге қабілетті болып, тұрақты өсуге қол жеткізу үшін адами капиталды дамытуға ерекше назар аударуы керек. Мақалада мансапты басқарудың тиімді бағдарламаларын енгізу бойынша ұсыныстар, сондай-ақ әртүрлі салалардағы табысты тәжірибелердің мысалдары жазылған.

Тірек сөздер: мансапты басқару, адам ресурстары, ШОК, қызметкерлерді ынталандыру, оқыту және дамыту, кәсіби өсу.

[1]Абдыхалыков К.,
PhD, ассистент-профессор, ORCID ID: 0009-0008-6525-100X,
e-mail: k.abdykhalykov@kbtu.kz
[1]Джалмуканова Л.,
магистрант, ORCID ID: 0009-0009-1812-0928,
e-mail: l_Jalmukanova@kbtu.kz
[1]Казахстанско-Британский технический университет, 050000, г. Алматы, Казахстан

ИНСТРУМЕНТЫ ДЛЯ ЭФФЕКТИВНОГО УПРАВЛЕНИЯ РАЗВИТИЕМ КАРЬЕРЫ

Аннотация

В условиях современной экономики управление карьерным развитием сотрудников становится ключевым фактором успеха и устойчивого развития организаций, особенно малых и средних предприятий (МСП). Развитие карьеры сотрудников играет решающую роль в повышении мотивации и удержании персонала, что особенно важно для МСП, работающих в условиях ограниченности ресурсов и высокой конкуренции. В данной статье рассматриваются современные подходы к управлению карьерой в МСП и предлагаются практические рекомендации, основанные на теоретических исследованиях и эмпирических данных. Особое внимание уделяется обучению и развитию, оценке результатов деятельности, системам вознаграждения и мотивации сотрудников. Обучение и развитие сотрудников способствуют повышению их квалификации и адаптивности к изменениям на рынке. Системы оценки работы, такие как обратная связь по принципу «360 градусов» и регулярные аттестационные сессии, играют важную роль в выявлении достижений и областей, требующих улучшения, а также в формировании индивидуальных планов развития. Справедливая и конкурентоспособная система компенсации и вознаграждения мотивирует сотрудников и способствует их удержанию. В статье также рассматриваются факторы, связанные с удержанием сотрудников и созданием позитивной корпоративной культуры, которая способствует их долгосрочному профессиональному росту и повышает конкурентоспособность компаний на рынке. В современных условиях, характеризующихся быстрыми изменениями и глобализацией, малым и средним предприятиям необходимо уделять особое внимание развитию человеческого капитала, чтобы оставаться конкурентоспособными и добиваться устойчивого роста. В статье предлагаются рекомендации по внедрению эффективных программ управления карьерой, а также примеры успешных практик из различных отраслей.

Ключевые слова: управление карьерой, человеческие ресурсы, малые и средние предприятия, мотивация сотрудников, обучение и развитие, профессиональный рост.

Article submission date: 14.06.2024

UDC 65.012.1
IRSTI 81.05.21

https://doi.org/10.55452/1998-6688-2024-21-3-374-383

[1]Capone C.,
MBA, Researcher, ORCID ID: 0000-0002-8970-5802,
e-mail: chr.capone@gmail.com

[2*]Akhlassov Y.S.,
MSc in Economics, Researcher, ORCID ID: 0009-0007-2616-3042,
*e-mail: elaman0510kz@mail.ru

[3]Ibrayev O.S.,
MSc in Economics, Researcher, ORCID ID: 0009-0007-6749-3363,
e-mail: olzhasibraev001@gmail.com

[1]British Management University, 100000, Tashkent, Uzbekistan
[2]Scientific Research Institute "Almatygenplan", 050057, Almaty, Kazakhstan
[3]"Industrial Development Fund" JSC, 010000, Astana, Kazakhstan

APPLICATIONS OF NON-TRADITIONAL EARNED VALUE MANAGEMENT MODELS IN PROJECT ANALYTICS

Abstract

Effective management of financial resources in projects is crucial for project success. Often, difficulties with financial resources, such as budget overruns, lead to unfavorable consequences that directly impact the successful completion of the project, the quality of the outcome, and stakeholder satisfaction. Therefore, identifying and developing tools for the effective management of financial resources, is of paramount importance. The purpose of this study is to apply non-traditional earned value management (EVM) models based on machine learning to predict project costs. To achieve the research objectives, previous literature on the topic was analyzed, a dataset of past projects was prepared, and a machine learning model was applied. The study found that non-traditional models, such as the regression algorithm AdaBoost, produced results close to the actual costs. The research indicates that the developed model could become an indispensable tool for project management and business decision-making, as it demonstrates the ability to adapt to various conditions and make accurate forecasts.

Key words: Project management; Artificial intelligence; Machine learning; Earned Value Management; Cost forecasting.

Introduction

In recent years, artificial intelligence has become an important tool in many aspects of human life, having a significant impact on the final results of human activity, including in such activities as project management. The study of this influence is becoming increasingly relevant in the context of growing digitalization and competition in the global market.

Numerous studies have been devoted to various aspects of the use of artificial intelligence in medicine, the military, industry, and the entertainment industry, but the issue of the use of artificial intelligence in project management remains poorly understood.

The main problem is the lack of knowledge about how various machine learning algorithms in project management can be applied and influence the outcome of forecasting various aspects of project management.

For instance, using machine learning for project cost forecasting is a promising application, although research on this topic is minimal [1]. The appeal of this topic lies in the need for new, alternative tools to perform such tasks, as the traditional EVM method is not always accurate and can be time-consuming.

This study aims to compare the traditional method of project cost forecasting with a non-traditional model using an algorithm such as AdaBoost. The following tasks will be addressed to achieve this goal: data collection, machine learning model building and testing, and comparative analysis.

The scientific novelty of the research lies in the identification of accurate algorithms for machine learning in order to predict Estimate at Completion (EAC) of a project, which can have the greatest impact on the development of artificial intelligence in project management. The practical significance of the work consists of developing recommendations for project managers involved in project management ways to optimize and forecast accuracy in project management.

Literature Review

According to the research paper "The Application of Artificial Intelligence in Project Management Research: A Review" by Gil et al. (2021), there are three stages of implementation, from the integration of automation and software to the application of artificial intelligence in project management. Task automation programs like Microsoft Project and Primavera (Oracle), which debuted in 1983, were integrated during the first phase. Chatbot assistants have been utilized in management equipment recaps and reminders for meetings in recent years. Although chatbots have become a part of our daily lives, project management is still a relatively new field for them. The most basic artificial intelligence notion marked the start of the third level. Machine learning has been utilized in project management to facilitate predictive and corrective analysis [2]. This is done to give the project manager information to make decisions about, for instance, how to plan and manage project resources within specific parameters and restrictions or how to handle issues and risks based on past project success. Within less than a decade, artificial intelligence (AI) is anticipated to utilize historical project lessons to propose new project schedules that are dynamic and capable of real-time adjustments based on resource performance and project progress.

Artificial intelligence (AI) programs are capable of analyzing data to identify trends and provide choices that align with those patterns [3]. Trending in software development projects and organization management, they are structured and coded to learn from the data they have access to through programming techniques, either naturally occurring at the time of their style or continuously to improve computer systems' performance through information exposure without the need to follow explicitly programmed directions of AI. The following are trends in organization management and software development projects: Machine Learning (ML), Deep Learning (DL), Speech Recognition (SR), and Natural Language Processing (NLP) [4].

Artificial intelligence may aid project managers with repetitive tasks, including creating project plans, entering and managing data, and more. These are jobs that can be completed automatically. When AI takes care of the majority of the administrative tasks, project managers have more time and energy to focus on the actual work. AI is capable of estimation, recommendation, and optimization. AI is able to learn from and infer future project development scenarios based on historical project management data. Apart from automation, one of the main applications of AI in project management is the collection and organization of data from many sources to generate informative project assessments. The links that AI can identify in data would be invisible to even the most trained human eye. AI is helpful for complex analysis as well. It can obtain far more information than a manager who is limited to human knowledge. When AI is employed, for example, value and risk assessments can be completed by human operators more rapidly and with less effort. Artificial intelligence is able to solve a number of project management issues, including risk assessment and management, resource management, cost management, and time management [5].

The application of artificial intelligence for predicting key project aspects, such as cost or duration, is a novel but highly relevant field in project management.

Despite the growing popularity of machine learning (ML) and AI applications in various aspects of human life, interest in some areas is only beginning to emerge. Specifically, in project cost estimation

within project management, only a few studies have been conducted on the effectiveness of the practical application of machine learning and AI. The scarcity of literature in this field, according to Inan et al. (2022), is linked to the fact that each project is unique, and predicting project outcomes using limited historical data is ineffective.

The noted scarcity of literature in this field does not imply the absence of relevant works. There are studies where machine learning, particularly algorithmic models, has been applied to predict project cost or duration.

For example, Elmousalami (2020) investigated 20 AI techniques, such as fuzzy logic, artificial neural networks, regression analysis, hybrid models like the genetic fuzzy model, and ensemble methods (XGBoost) and random forest, to create a model for predicting project costs based on comparisons. As a result of the research that was conducted, emphasizing the importance of ensemble methods, the author concluded that XGBoost is the most accurate and reliable model.

Additionally, it was observed that ensemble method algorithms demonstrate high performance and relatively high accuracy in this study.

In another study conducted by Balali, A. et al. (2020), the researchers aimed to improve the effectiveness of the Earned Value Management (EVM) method by employing Artificial Neural Networks. In this investigation, the authors utilized two distinct machine learning models, namely Artificial Neural Network (ANN) and multiple regression analysis, to enhance the accuracy of cost forecasting based on data from 50 road construction projects in Iran. The findings indicated that both Artificial Neural Network (ANN) and multiple regression analysis outperformed the traditional EVM method in terms of precision. When comparing the performance of the two models using metrics such as Mean Squared Error (MSE) and an R2 value, the authors concluded that Artificial Neural Network (ANN) was the superior model.

Narbaev et al. (2023) utilized real cost data from 110 projects to compare the forecasting performance of the XGBoost model against traditional index-based methods, as well as other machine learning algorithms (SVM, CatBoost, RF, LightGBM), and two non-linear growth models (Gompertz and Logistic). Based on the results of the comparative analysis, the XGBoost model was selected by the authors due to its superior accuracy, low error rates, and ability to handle various types of data efficiently. To evaluate the model results, the authors employed three criteria: MAPE (accuracy), NRMSE (timeliness), and prediction performance (frequency). Consequently, the authors concluded that based on all three evaluation criteria, the XGBoost model exhibited the most precise results, thus proving its reliability.

Additionally, Ottaviani and De Marco (2022) developed a multiple linear regression model based on three regressors: EAC, CPI, and WP. The model was tested on 29 real projects and compared with the traditional index-based Earned Value Management (EVM) method. As a result, the authors concluded that the new model for EAC estimates demonstrated improvements in accuracy and lower variance compared to the traditional method.

In conclusion, based on the review of previous literature, it was determined that machine learning, when sufficiently trained with adequate data, can predict the cost or duration of a project more accurately than traditional methods.

Materials and methods

Analytical methods.

A systematic approach is required for conducting research in any field of science. This approach includes aspects such as detailed research planning, selection of appropriate analysis methods, definition of research questions or hypotheses, and testing of those hypotheses.

The research methodology can provide such a structured approach. The historical development of research processes has led to the classification of research into three categories: quantitative research, qualitative research, and mixed-method research [10].

The mixed-method approach used in this study, combines quantitative and qualitative research methodologies. Although this approach requires more time and skills, studying the same question using different methods and sources helps to better explore various aspects of the subject area from different perspectives.

The quantitative approach revolves around working with numerical data. This approach is used for deductive or statistical analysis, where it is necessary to test or confirm a particular theory or hypothesis. The methods for collecting numerical data in this approach can take the form of surveys, observations, or experiments. Compared to the previous method, research in the qualitative approach is based on philosophical assumptions [10]. This method describes concepts, experiences, and viewpoints without relying on numerical values.

In this work, a literature review of the subject area was conducted as part of the qualitative research approach. Relevant articles were searched through online databases such as Scopus, Google Scholar, and ResearchGate. As a result, a literature review grid consisting of 30 relevant articles was created. Subsequently, based on previous works on machine learning, an appropriate machine learning algorithm was selected. When selecting an algorithm for analysis, attention was paid to the type of task, in our case, predicting numerical values, as well as to accuracy and robustness. As part of the quantitative research approach, a dataset was created based on data from the Operations Research & Scheduling research group [11] website. The data obtained from this website is based on actual projects completed by various industries.

Earned Value Management (EVM). Cost forecasting.

To predict the cost, the calculations use data on the planned value, earned value, actual costs, planned duration, actual duration, budget at the time of completion, performance index from schedule, and cost performance index. A cost estimate at completion was calculated using a number of different formulas. The top three formulas that are used are [12]:

$$\text{a) } CEAC(\$) = \frac{BAC}{CPI} \quad (1)$$

This formula a) is used when the project is moving forward without any obstacles, this calculation is the most recommended. Divide the BAC by the Cost Performance Index (CPI) to determine the EAC.

$$\text{b) } CEAC(\$) = AC + \frac{(BAC - EV)}{CPI * SPI} \quad (2)$$

As for formula b), it is used when costs increase and schedules are delayed, this formula is applied. In this instance, the Earned Value (EV) and the Schedule Performance Index (SPI) must be included in the calculation.

$$\text{c) } CEAC(\$) = AC + (BAC - EV) \quad (3)$$

In project management, when unforeseen circumstances have been eliminated and it is expected that interference in the operating mode will not occur until the completion of the project, this c) formula is applied.

The latter formula is used when a project experiences schedule delays, but it is expected that no further delays will occur until the project is completed. This may mean that the project is currently behind schedule, but it is assumed that it will continue to move forward without further obstacles or delays.

The Machine Learning algorithm used.

To predict continuous CEAC, we chose the Adaptive Boosting (AdaBoost) algorithm. Although this algorithm is not widely used for cost forecasting, its effectiveness in prediction has been noted in many other professional fields. Additionally, beyond this advantage, the algorithm is easy to

implement and performs well with small datasets, which also influenced our decision when selecting algorithm for analysis.

The Adaptive Boosting algorithm is a popular and effective method in ensemble learning. It belongs to the family of boosting methods and works by combining weak learners, often decision trees. During the training process, the algorithm focuses on data points that were misclassified in previous iterations [13]. Each predictor in the model learns from the residuals of the previous predictor before being added to the model. This process continues until either the user-specified number of predictors is reached or an ideal predictor is found. With each iteration, the model improves. To make predictions, AdaBoost combines the trained predictors to create a strong model that produces more accurate results. The algorithm evaluates the output of each predictor, essentially weighting them through a voting mechanism [14], with the final prediction being the value that receives the most votes.

Evaluation metrics.

The train-test split is a widely used technique for evaluating a machine learning model. In this approach, the dataset meant for training the algorithm is split into a training set and a test set in a certain percentage ratio. The purpose of this technique is to assess how a model trained on training data will perform with new and previously unseen data. This helps to measure the accuracy and reliability of the model.

In this work, the prepared datasets were divided into two parts using the train-test split technique in a percentage ratio of 75% for training and 25% for testing the trained model.

Before starting the training and testing of the model, it was necessary to prepare the data, which involved preparing the dataset consisting of projects completed from 1% to 29% and determining all the features to be used as independent and dependent variables.

The project lifecycle is typically divided into three stages: early, middle, and late. We have determined the percentage intervals for each stage based on a review of relevant literature. For example, Narbaev et al. (2023) defined the interval for the early stage as 1–29%, for the middle stage as 30–69%, and for the late stage as 70–95%. We have used this approach in our work and have compiled a dataset for early stage with 1–29% completion. The reason for dividing a project into three stages is that the amount of work completed and the amount of money spent may differ at different stages of the project. So, comparing the project progress without dividing it into stages can be incorrect.

As a result of using this approach, a dataset consisting of 78 construction projects was formed.

The following features, such as BAC, EV, AC, PV, CPI, and SPI, were used as independent variables during model building to forecast the CEAC using formulas (1), (2), and (3), with EAC as the dependent variable.

Since the results obtained from the machine learning model on their own represent nothing without comparative analysis and evaluation, we used the RMSE metric to assess the quality, accuracy, and to obtain information about the model's performance. This metric calculates the difference between the actual cost and the predicted cost, as defined by Equation (4).

$$RMSE = \sqrt{\frac{1}{n}\sum_{i=1}^{n}(CAC_i - EAC_i)^2} \quad (4)$$

where i is the given project, n is the number of projects, EAC is the predicted value and CAC is actual value (best value = 0; worst value = +∞).

Results and Discussion

During the training of the machine learning models, the training process was repeated a hundred times to compare the results of a hundred trials with just one. To obtain the results of a

hundred trials, the outcome of each attempt, ranging from one to one hundred, was recorded in a special list. Then, to compare these with the results of a single trial, the average value of a hundred trials was calculated. The results of comparing the two methods are presented below.

Moreover, all the provided results of the models were obtained based on hyperparameter tuning. Choosing parameters for the algorithm instead of using default values shows better trainability and improved results. Since chosen algorithm have its own set of hyperparameters, which differ from each other in quantity and performed functions, it was necessary to automate the process of parameter selection. For this purpose, we used the GridSearchCV function, which selects the best combination from the specified parameters.

Traditional index-based method results.

When calculating the results for the traditional index-based EVM method, formulas CEAC (1), (2), and (3) were utilized. All calculations based on these mentioned formulas were performed in Google Sheets tool. The results of RMSE for the traditional method which are presented in Table 1, were obtained using the scikit-learn library in the Jupyter Notebook environment.

Table 1 – The results of RMSE for the traditional method*

Indexes / Stage	Index-1 (CEAC-1)	Index-2 (CEAC-2)	Index-3 (CEAC-3)
Early	0.024	0.265	1.438

*Source: Conducted by the authors.

Based on the obtained results, it can be noticed that the performance of Index-1 is significantly better compared to Index-2 and Index-3. It is quite likely that the reason for this is its simplicity and direct calculation method because it directly adds the budget at completion (BAC) to the earned value (EV) without any additional adjustments based on cost performance or schedule performance indices. This means that the formula only considers the current project cost.

Among the three formulas, Index-2 is the most suitable for predicting the future project cost because it takes into account past cost performance indicators. In Table 1, the results for Index-3 are significantly worse than the previous formulas because, in its calculation, both the cost performance index and the schedule performance index are considered.

Although Index-2 is better suited for further analysis, all three formulas will be included when describing the results of the machine learning model. However, Index-2 indicators will be used when comparing the best model with the traditional EVM method.

Results from the AdaBoost algorithm.

Creating a machine learning model based on the AdaBoost algorithm involved hyperparameter tuning. To fine-tune the performance of the model, we utilized the GridSearchCV function. This function helped us to determine the optimal values for hyperparameters such as “n_estimators” and “learning_rate”. The parameter “n_estimators” is essential in determining the number of weak learners to be included in the model, as it is part of ensemble learning. On the other hand, the “learning_rate” parameter determines the contribution of each predictor to the final prediction. For this particular model, we chose a decision tree as the weak learner.

In Table 2 the results for single trail prediction are provided. The obtained results for all three formulas differ not so significantly, indicating that the algorithm effectively identifies patterns in the data and demonstrates stability in predictions. It can be concluded that the algorithm produces lower errors, a better fit and more accurate results when using the CEAC-2 formula for forecasting.

Table 2 – Single trail results of the AdaBoost-based model*

Evaluation metric	Early stage		
	Index-1 (CEAC-1)	Index-2 (CEAC-2)	Index-3 (CEAC-3)
RMSE	0.011	0.023	0.026

*Source: Conducted by the authors.

During the hundred trial model training, a special "for" loop with a counter was implemented. Empty lists were used to record the results after each iteration for calculating the average value of each metric.

The findings from the hundred trials training are presented in Table 3. Upon comparing the results for each of the three formulas, significant differences can be observed. Similar to the single trial training, CEAC-2 produced the best results among the three formulas. Compared to CEAC-1 and CEAC-3 formulas, the second formula generated lower errors.

If we compare the results of single trial and hundred trials, we can notice that the performance metrics generally exhibit similar trends, with some differences in the exact values. For instance, the RMSE score for CEAC-1 formula is slightly higher in the hundred trials compared to the single trial. However, overall, the results for single trial are noticeably better.

Table 3 – Hundred trial results of the AdaBoost-based model*

	Early stage		
Evaluation metric	Index-1 (CEAC-1)	Index-2 (CEAC-2)	Index-3 (CEAC-3)
RMSE	0.018	0.072	0.083

*Source: Conducted by the authors.

Comparing the results, it can be observed that training the model one hundred or more times has a slight but negative impact on its accuracy. To identify the best method for project cost forecasting, we chose the model trained only once.

A comparative analysis of the results from the traditional method and the model trained once revealed that the accuracy of the machine learning algorithm exceeds that of the traditional method when applying all formulas.

Conclusion

This work aimed to utilize artificial intelligence, specifically machine learning, to predict the Budget at Completion (BAC) of projects. By applying this technology, we sought to determine the extent to which machine learning could be more accurate than the traditional index-based method. The study revealed that not only does the algorithmic machine learning model perform better at predicting project costs compared to the traditional method, but it also concluded that with the availability of large datasets for training, machine learning could become an indispensable tool for decision-making not only regarding project budgets but also other critical aspects of projects.

Overall, the work on this study consisted of several stages, including a literature review of the subject area, preparation of a dataset for training and testing the machine learning model, selection of the development environment, selection of appropriate machine learning algorithm, training and testing of the models, and analysis and comparison of the results obtained.

The dataset prepared for training the models was compiled based on real completed projects, which is a significant advantage of this work. Real data contains complex scenarios and exceptions,

ensuring the model's relevance to project management and increasing its applicability to real-world projects. The dataset compiled for training and testing the models consists of a total of 117 projects. Based on this dataset, one subset consisting of 78 construction projects was created for the early stage.

For this study, an ensemble machine learning algorithm such as AdaBoost was selected. This algorithm was chosen for its accuracy and robustness, as it can be trained on small datasets while providing reliable and stable predictions. Since the target variable to be predicted is a continuous value, the following metric, which is designed to evaluate regression model performance, was chosen for the assessment and analysis of the results: RMSE.

When comparing algorithmic models to identify the best one, a comparative analysis of single-trial and one-hundred-trial training for the model was also conducted. This comparison aimed to understand the extent to which training more than once could improve or worsen the prediction results. Given the effectiveness of this approach, it is also important to mention that hyperparameter tuning was applied during model construction.

Overall, the comparison of results between the single-trial-trained model and the hundred-trial-trained model yielded relatively interesting results. For instance, training a hundred times showed a deterioration in results. The primary analysis, which compared the machine learning model with the traditional index-based method, concluded that the machine learning algorithm can generally predict project costs at an early stage much more accurately.

The main contribution of this work is in the proposed machine learning algorithm calculates the cost estimates under uncertainty and improves the EVM field. In conclusion, this study confirmed the hypothesis that machine learning outperforms the traditional method. Using this technology as a decision-making tool can alleviate the workload of the project team and project manager and improve project management processes.

REFERENCES

1 Inan T., Narbaev T., & Hazir O. A Machine learning study to enhance project cost forecasting. IFAC-PapersOnLine, 2022, vol. 55, no. 10, pp. 3286–3291. https://doi.org/10.1016/j.ifacol.2022.10.127.

2 Gil J., Martinez Torres J., & González-Crespo R. The application of artificial intelligence in project management research: A review. International Journal of Interactive Multimedia and Artificial Intelligence, 2021, no. 6, pp. 54–66. https://doi.org/10.9781/ijimai.2020.12.003.

3 Bhavsar K., Shah V., & Gopalan S. Business Process Reengineering: A Scope of Automation in Software Project Management Using Artificial Intelligence. International Journal of Engineering and Advanced Technology (IJEAT), 2019, vol. 9, no. 2, pp. 3589–3595. https://doi.org/10.35940/ijeat.B2640.129219.

3 Taboada I., Daneshpajouh A., Toledo N., & de Vass T. Artificial Intelligence Enabled Project Management: A Systematic Literature Review. Applied Sciences, 2023, vol. 13, no. 8, p. 5014. https://doi.org/10.3390/app13085014.

5 Elmas Ç., & Babayev J. Artificial Intelligence Techniques Used in Project Management. Advances in Artificial Intelligence Research, 2021, vol. 1, no. 1, pp. 1–5.

6 Elmousalami H.H. Comparison of Artificial Intelligence Techniques for Project Conceptual Cost Prediction: A Case Study and Comparative Analysis. IEEE Transactions on Engineering Management, 2020, PP(99), pp. 1–14. https://doi.org/10.1109/TEM.2020.2972078.

7 Balali A., Valipour A., Antucheviciene J., & Šaparauskas J. Improving the Results of the Earned Value Management Technique Using Artificial Neural Networks in Construction Projects. Symmetry, 2020, vol. 12, p. 1745. https://doi.org/10.3390/sym12101745.

8 Narbaev T., Hazir Ö., Khamitova B., & Talgat S. A machine learning study to improve the reliability of project cost estimates. International Journal of Production Research, 2023, vol. 62, no. 12, pp. 4372–4388. https://doi.org/10.1080/00207543.2023.2262051.

9 Ottaviani F.M., & De Marco A. Multiple linear regression model for improved project cost forecasting. Procedia Computer Science, 2022, pp. 808–815. https://doi.org/10.1016/j.procs.2021.12.079.

10 Warfield D., IS/IT research: a research methodologies review. Journal of theoretical & applied information technology, 2010, no.13.

11 Operations Research & Scheduling Research Group (2023). Retrieved February 21, 2024, from: https://www.projectmanagement.ugent.be/research/data/realdata.

12 PMI, Project Management Body of Knowledge (PMBOK Guide). 6th edition. (PMI Publications, Newtown Square, 2017).

13 Wauters M., & Vanhoucke M. A comparative study of Artificial Intelligence methods for project duration forecasting. Expert Systems with Applications, 2016, vol. 46, pp. 249–26. https://doi.org/10.1016/j.eswa.2015.10.008.

14 Shanmugasundar G., Vanitha M., Čep R., Kumar V., Kalita K., & Ramachandran M. A Comparative Study of Linear, Random Forest and AdaBoost Regressions for Modeling Non-Traditional Machining. Processes, 2021, vol. 9, p. 2015. https://doi.org/10.3390/pr9112015

15 Shoushtari F., Daghighi A., & Ghafourian E. Application of Artificial Intelligence in Project Management. International journal of industrial engineering and operational research, 2024, vol. 6, no. 2, pp. 49–63.

16 Radhoush S., Whitaker B.M., & Nehrir H. An Overview of Supervised Machine Learning Approaches for Applications in Active Distribution Networks. Energies, 2023, vol. 16, no. 16, p. 5972. https://doi.org/10.3390/en16165972.

17 PMI, The Standard for Earned Value Management. 2nd Edition. (PMI Publications, Newtown Square, 2019).

18 Gao C., Min X., Fang M., Tao T., Zheng X., Liu Y., Wu X., & Huang Z. Innovative Materials Science via Machine Learning. Advanced Functional Material, 2022, vol. 32, p. 2108044. https://doi.org/10.1002/adfm.202108044.

19 Capone C., & Narbaev T. Estimation of Risk Contingency Budget in Projects using Machine Learning. IFAC-PapersOnLine, 2022, vol. 55, no. 10, pp. 3238–3243. https://doi.org/10.1016/j.ifacol.2022.10.140.

20 IPMA P. Artificial intelligence impact in project management, 2020. [Electronic resource]. From https://ipma.world/assets/IPMA_PwC_AI_Impact_in_PM_-_the_Survey_Report.pdf.

21 Mahesh B., Machine Learning Algorithms – A Review. International Journal of Science and Research, 2020, vol. 9, pp. 381–386. https://doi.org/10.21275/ART20203995.

22 Capone C., Talgat S., Hazir O., Abdrasheva K., Kozhakhmetova A. Artificial Intelligence Models for Predicting Budget Expenditures. Eurasian Journal of Economic and Business Studies, 2024, vol. 68, no. 1, pp. 32–43. https://doi.org/10.47703/ejebs.v68i1.331.

[1]Капоне К.,
MBA, Зерттеуші, ORCID ID: 0000-0002-8970-5802,
e-mail: chr.capone@gmail.com

[2*]Ахласов Ю.С.,
Экономика магистрі, ғылыми қызметкер, ORCID ID: 0009-0007-2616-3042,
*e-mail: elaman0510kz@mail.ru

[3]Ибраев О.С.,
Экономика магистрі, зерттеуші ORCID ID: 0009-0007-6749-3363,
e-mail: olzhasibraev001@gmail.com

[1]Британдық менеджмент университеті, 100000, Ташкент қ., Өзбекстан
[2]«Алматыгенжоспар» ғылыми-зерттеу институты, 050057, Алматы қ., Қазақстан
[3]«Индустриялық даму қоры» АҚ, 010000, Астана қ., Қазақстан

ЖОБАЛЫҚ ТАЛДАУДА ИГЕРІЛГЕН КӨЛЕМНІҢ ДӘСТҮРЛІ ЕМЕС МОДЕЛЬДЕРІН ҚОЛДАНУ

Аңдатпа

Қаржылық ресурстарды тиімді басқару – жобалардың сәтті орындалуы үшін шешуші фактор. Жобаның бюджеттен асып кетуі сияқты қаржылық ресурстарға байланысты қиындықтар көбінесе жобаның табысты аяқталуына, нәтижелердің сапасына және мүдделі тараптардың қанағаттануына тікелей әсер ететін жағымсыз салдарға әкелуі мүмкін. Сондықтан қаржылық ресурстарды тиімді басқару құралдарын іздеу және дамыту қазіргі уақытта өте өзекті мәселе болып отыр. Ғылыми жұмыстың мақсаты – жобалық шығындарды болжау үшін машиналық оқытуға негізделген игерілген көлемді басқарудың (EVM) дәстүрлі емес модельдерін

қолдану. Бұл мақсатқа жету үшін зерттеуде осы саладағы алдыңғы тәжірибелер талданды, аяқталған жобалар бойынша деректер қоры жиналып, машиналық оқыту моделі қолданылды. Зерттеу нәтижелері AdaBoost регрессия алгоритмі сияқты дәстүрлі емес модельдердің дәстүрлі әдістермен салыстырғанда нақты шығындарға жақынырақ нәтижелер көрсететінін айқындады. Сонымен қатар, алынған мәліметтер әзірленген модельдің жобаларды басқару мен бизнес шешімдерін қабылдауда маңызды құралға айналуы мүмкін екенін дәлелдеді.

Тірек сөздер: Жобаны басқару, жасанды интеллект, машиналық оқыту, игерілген көлем әдісі, шығындарды жоспарлау.

[1]Капоне К.,
MBA, исследователь, ORCID ID: 0000-0002-8970-5802,
e-mail: chr.capone@gmail.com

[2*]Ахласов Ю.С.,
магистр экономики, научный сотрудник, ORCID ID: 0009-0007-2616-3042,
*e-mail: elaman0510kz@mail.ru

[3]Ибраев О.С.,
магистр экономики, научный сотрудник ORCID ID: 0009-0007-6749-3363,
e-mail: olzhasibraev001@gmail.com

[1]Британский университет менеджмента, 100000, г. Ташкент, Узбекистан
[2]Научно-исследовательский институт «Алматыгенплан», 050057, г. Алматы, Казахстан
[3]АО «Фонд развития промышленности», 010000, г. Астана, Казахстан

ПРИМЕНЕНИЕ НЕТРАДИЦОННЫХ МОДЕЛЕЙ МЕТОДА ОСВОЕННОГО ОБЪЕМА В ПРОЕКТНОЙ АНАЛИТИКЕ

Аннотация

Эффективное управление финансовыми ресурсами в проектах имеет решающее значение для их успешного выполнения. Часто проблемы с финансовыми ресурсами, такие как перерасход бюджета, приводят к неблагоприятным последствиям, которые непосредственно влияют на успешное завершение проекта, качество результата и удовлетворенность заинтересованных сторон. Поэтому идентификация и разработка инструментов для эффективного управления финансовыми ресурсами имеет первостепенное значение. Цель данного исследования – применить нетрадиционные модели управления освоенным объемом (EVM), основанные на машинном обучении, для прогнозирования затрат на проект. Для достижения целей исследования был проанализирован предыдущий опыт в данной области, подготовлен набор данных по прошлым проектам и применена модель машинного обучения. Исследование показало, что нетрадиционные модели, такие как алгоритм регрессии AdaBoost, продемонстрировали результаты, близкие к фактическим затратам. Результаты исследования свидетельствуют о том, что разработанная модель может стать незаменимым инструментом для управления проектами и принятия бизнес-решений, так как она демонстрирует способность адаптироваться к различным условиям и делать точные прогнозы.

Ключевые слова: управление проектом, искусственный интеллект, машинное обучение, метод освоенного объема, прогнозирование затрат.

Article submission date: 11.09.2024

UDC 33.330.1
IRSTI 06.52.01

https://doi.org/10.55452/1998-6688-2024-21-3-384-395

[1]*Tazhiyeva Zh.N.,
PhD student, ORCID ID: 0000-0002-1730-6490,
*e-mail: zhanzari@gmail.com
[2]Keser E.,
MBA in Economics, ORCID ID: 0000-0003-0360-7492,
e-mail: emrekeser1987@gmail.com
[1]Sandykbayeva U.D.
Cand. of Philos. Sc., Senior Lecturer, ORCID ID: 0000-0002-2818-8167,
e-mail: sandykbaeva@mail.ru

[1]Kazakh National University named al-Farabi,
050000, Almaty, Kazakhstan
[2]Isik University, Istanbul, Turkey

QUALITY MANAGEMENT IN HIGH-TECH PROJECTS USING DIGITAL MARKETING TECHNOLOGIES IN KAZAKHSTAN

Abstract

The purpose of this article is to determine the contribution of digital marketing technologies to improving the quality of high-tech products in Kazakhstan, as well as to identify prospects for improving quality management practices in high-tech projects in Kazakhstan using a digital approach to marketing. Based on international statistics from IMD and WIPO for 2013–2022, using the correlation analysis method, the results of implementing high-tech projects in quality management using alternative approaches (digital and pre-digital) to marketing in Kazakhstan are compared. The key conclusion is that in Kazakhstan, quality management in high-tech projects using digital marketing technologies is preferable. The key ones are: personnel marketing, product marketing and process marketing. The theoretical significance of the obtained results is that they allowed us to rethink quality management processes in the implementation of high-tech projects in the digital economy of Kazakhstan, and also revealed promising digital marketing technologies based on AI, IoT, Big Data, the Internet, mobile devices, chatbots, machine vision, smart consultants and virtual assistants (VR / AR). The practical significance is due to the fact that the developed digital approach to marketing allows us to improve the practice of quality management in high-tech projects in Kazakhstan. The author's approach includes a marketing mix of quality management in high-tech projects using digital marketing technologies in Kazakhstan. The approach also reveals the organizational and technological aspects of quality management in high-tech projects in Kazakhstan with a digital approach to marketing.

Key words: quality management, high-tech projects, digital marketing technologies, digital economy of Kazakhstan.

Introduction

The fourth industrial revolution has not only increased the importance of quality for the success of high-tech projects, but also opened up new technological opportunities for quality management. The marketing approach to quality management is preferable when implementing high-tech projects, since this approach ensures the highest management flexibility and, accordingly, the most complete consideration of stakeholders' interests, thereby forming and strengthening the competitiveness of high-tech industries and their products.

Digital technologies can improve the efficiency of marketing and increase its reach. For example, chatbots can provide information and consulting support to consumers in the field of product quality. Intelligent support for making purchase decisions helps compare substitute products based on quality criteria, taking into account consumer priorities. Digital marketing communications can be carried

out continuously and transformed as needed – from mass mailings to individual commercial offers. This determines the relevance of studying the possibilities of applying digital marketing technologies to quality management in high-tech projects.

The digital economy is actively developing in Kazakhstan. Its institutional framework is regulated by the state program "Digital Kazakhstan", approved by the Resolution of the Government of the Republic of Kazakhstan (2023) dated December 12, 2017, No. 827. Over the five-year period of implementation of the program, which ends in 2022, significant successes have been achieved. Thus, according to IMD (2023), Kazakhstan took 36th place among 63 countries in the world in digital competitiveness in 2022, the level of which in Kazakhstan is estimated at 73.03 points out of 100 possible. According to WIPO (2023), the share of high-tech production in Kazakhstan in 2022 is 15.3%, and the share of high-tech exports is estimated at 5.2% of total foreign trade. Quality management plays a key role in the development of high-tech production. Historically, thanks to the Soviet legacy, the high quality of Kazakh products was ensured through state standardization and quality control. The fruitfulness and completeness of market reforms to date have ensured the institutionalization of marketing management of high-tech projects in Kazakhstan. However, the implementation of marketing in quality management in itself is an innovation for Kazakhstan, to which both Kazakh business and Kazakh society, including consumers of high-tech products, need to adapt. The problem is that this hinders the application of digital marketing technologies in quality management in Kazakhstan, which, as the experience of other countries shows (Wang et al., 2022; Zhang et al., 2023), can be useful in high-tech projects. The purpose of this article is to determine the contribution of digital marketing technologies to improving the quality of high-tech products in Kazakhstan, as well as to identify prospects for improving quality management practices in high-tech projects in Kazakhstan using a digital approach to marketing.

The originality of the study and its contribution to the literature is that it proposes a new – digital approach to marketing, taking into account the specifics of the digital economy of Kazakhstan and allowing to improve quality management in high-tech projects in Kazakhstan. Further in this article, a literature review is conducted, after which the materials and methods of the study are described. Then the results of solving two problems of this study are presented. The first problem is related to comparing the results of implementing high-tech projects in quality management using alternative approaches to marketing in Kazakhstan. The second problem is to develop a digital approach to marketing to improve quality management in high-tech projects in Kazakhstan. The work concludes with a discussion and conclusion.

Literature Review

Theoretical basis of project quality management and the specifics of high-tech projects.

This article focuses on the concept of project quality management, interpreted as the implementation of a set of organizational and managerial measures aimed at ensuring the highest possible quality of project results, that is, the final product of the project (El Khatib et al., 2023$ Mohamed and Tran, 2023; Veselovsky et al., 2018).

In this regard, the most important parameter of project quality is the quality of the products manufactured and sold on the market as a result of the project (Alawag et al., 2023; Coghlan et al., 2023). Consequently, the main criterion for quantitative (i.e. accurate, objective and reliable) assessment of project quality is the volume of demand in the short term, and the volume of production of project products in the medium and long term (Miao et al., 2021; Painén-Paillalef et al., 2022).

The theoretical basis of this study is the concept of quality management in high-tech projects that develop and manufacture high-tech products, including digital products and products of Industry 4.0 (Duan et al., 2023; Lin et al., 2023; Popkova, 2020a; Popkova, 2020b; Popkova, 2022; Popkova, 2023).

The specificity of assessing the quality of high-tech projects is that the demand for high-tech products is consistently high, provided that they are of good quality. In this regard, the volume

of high-tech production acts as the main parameter of the quality of high-tech projects, which is obviously dictated by the existing demand, determined by the quality of the products (Ng, 2022; Yamnitsky and Jankowicz, 2021).

Digital Marketing Technologies and Their Application for Quality Management in High-Tech Projects

Digital marketing technologies in this article, based on existing literature Gupta and Singh (2023), Jung and Shegai (2023), are understood as digital technologies used in business marketing activities. Marketing technologies applicable in project quality management, including high-tech projects, are personnel marketing, product marketing, promotion (branding) and process marketing technologies. In the existing literature, the following are noted as key elements of the marketing mix, the most significant for product quality management in high-tech projects.

Firstly, personnel marketing: high-tech projects involve knowledge-intensive jobs occupied by highly qualified personnel. Marketing management of these personnel allows for the fullest development of their human potential through relationship marketing, strengthening loyalty, forming a responsible employer brand and a flexible approach to labor incentives (Bejtkovsky, 2018; Jančíková and Milichovský, 2019).

Knowledge-intensive employment acts as a classic (pre-digital) personnel marketing technology that influences quality, since this technology helps to attract and retain the best personnel (Hrivnák et al., 2021). The technology of digital personnel marketing is the attraction of digital personnel and the development of digital skills (competencies) in employees, which is particularly useful for the implementation of high-tech projects (Vanchukhina et al., 2022). Secondly, product marketing: a close connection with the market allows designing and producing products of the exact quality that is in demand (Anderson and Laverie, 2022; Veselovská, 2022). Industrial design of products acts as a classic (pre-digital) product marketing technology that influences quality (Bogoviz and Ragulina, 2020). Digital product marketing technology is the digital transformation of business, which allows producing and selling digital products on the market (Benčič et al., 2020). Thirdly, promotion (branding): a strong brand and reputation as a reliable supplier allows promoting innovative high-tech products on the market, stimulating demand for them due to their high quality (Ibrahim and Aljarah, 2023; Xu et al., 2023). A classic (pre-digital) promotion (branding) technology that influences quality is image abroad or branding (Pantano et al., 2020). A digital promotion (branding) technology is electronic product promotion (Chen, 2023), in particular, when selling products through e-commerce with electronic payments between sellers and buyers (Evstratov and Berezhnova, 2013). Fourth, process marketing: marketing allows for the close integration of all business processes in the implementation of high-tech projects and focuses them on improving product quality in close connection with the market (Akter et al., 2023; Jasin and Firmansyah, 2023). A classic (pre-digital) process marketing technology that influences quality is quality certification according to ISO 9001 (Parra-López et al., 2016). The technology of digital marketing processes is the use of big data and smart analytics, which is especially useful in the implementation of high-tech projects (Medhat and Bayomy, 2023).

Gap Analysis and Research Question (RQ)

The specifics of digital marketing related to relying on digital technologies in the implementation of business marketing activities are disclosed in the works of Haverila et al. (2023), Zahoor and Lew (2023). At the same time, the issues of using digital marketing technologies in quality management in high-tech projects have not been sufficiently studied, which is a gap in the literature. The experience of implementing high-tech projects in Kazakhstan is disclosed in separate publications by Konovalov and Beisenbaieva (2018), Kurmanov et al. (2022), Sadykhanova et al. (2019) and needs to be studied in more depth, in particular, from the standpoint of marketing.

The research question of this article is as follows. RQ: What is preferable for quality management in high-tech projects in Kazakhstan – pre-digital marketing or digital marketing? To find an answer to the RQ, the article studies the experience of applying marketing in quality management in high-

tech projects in Kazakhstan and compares the contribution of pre-digital and digital marketing technologies to improving quality.

Materials and Methods

Research Methodology and Control Variables

To achieve the stated goal, the article consistently solves the following two tasks. The research design is presented in Fig. 1.




Figure 1 – Research design

Source: original development

As shown in Figure 1, the research design involves establishing a connection between quality in high-tech projects (high-tech manufacturing), on the one hand, and pre-digital marketing technologies, on the other hand, and digital marketing technologies. The object of the study is high-tech projects implemented in Kazakhstan and taken into account in statistics on the indicator "high-tech manufacturing" (WIPO, 2023). According to the definition of the World Bank (2023), this includes "products with high R&D intensity, such as aerospace, computers, pharmaceuticals, scientific instruments and electrical equipment".

The first task: to compare the results of the implementation of high-tech projects in quality management using alternative approaches to marketing in Kazakhstan. For this, the method of correlation analysis is used. This method is used to determine the relationship (correlation dependence) of the "high-tech manufacturing" indicator (as an indicator of the effectiveness of quality management in high-tech projects according to WIPO, 2023) with the elements of the marketing mix in comparison of pre-digital and digital marketing. The control variables are selected in accordance with the marketing technologies for project quality management identified in the literature review and supported by the literature, they are presented in Table 1.

The time frame of the study covers 2013–2022. The empirical basis of the study is given in Table 2.

Table 1 – Control variables

Marketing Technologies	Digital Marketing		Pre-Digital Marketing	
	Statistical indicator	Data source	Statistical indicator	Data source
Personnel Marketing	Digital/Technological skills	IMD (2023)	Knowledge-intensive employment, %	WIPO (2023)
Product Marketing	Digital transformation in companies	IMD (2023)	Industrial designs by origin/bn PPP$ GDP	WIPO (2023)
Promotion (Branding)	E-Participation	IMD (2023)	Image abroad or branding	IMD (2023)
Process Marketing	Use of big data and analytics	IMD (2023)	ISO 9001 quality certificates/bn PPP$ GDP	WIPO (2023)

Source: author's development.

The second task: development of a digital approach to marketing to improve quality management in high-tech projects in Kazakhstan. Based on the marketing mix method, a marketing mix of quality management in high-tech projects is developed using digital marketing technologies in Kazakhstan, and organizational and technological aspects of quality management in high-tech projects in Kazakhstan with a digital approach to marketing are determined.

Results

Quality Management in High-Tech Projects in Kazakhstan with Alternative Marketing Approaches

As part of the first task of this study, a correlation analysis of the data from Table 2 was conducted to compare the results of implementing high-tech projects with quality management using alternative marketing approaches in Kazakhstan. The results are illustrated in Fig. 2.




Figure 2 – Correlation of pre-digital and digital marketing technologies with quality in the implementation of high-tech projects in Kazakhstan, %

Source: calculated and constructed by the author.

As can be seen from Figure 2, pre-digital marketing technologies for the most part demonstrated a negative correlation with quality in the implementation of high-tech projects in Kazakhstan. The only positive value of the correlation coefficient was obtained for the relationship of knowledge-intensive employment, but it is negligibly small (1.69%). It is noteworthy that promotion (branding) did not demonstrate a positive relationship with quality in the implementation of high-tech projects in Kazakhstan, either when using pre-digital marketing tools (the correlation was –21.53%) or when using digital marketing tools (-9.32%). In general, a moderate relationship was found between other digital marketing tools and quality in the implementation of high-tech projects in Kazakhstan, which amounted to 23.61% for process marketing based on big data and analytics, 20.83% for product marketing in digital transformation in companies, and 15.06% for personnel marketing with digital/ technological skills. This indicates the preference for digital marketing tools for quality management in the implementation of high-tech projects in Kazakhstan.

A digital approach to marketing to improve quality management in high-tech projects in Kazakhstan

Table 2 – Organizational and technological aspects of quality management in high-tech projects in Kazakhstan with a digital approach to marketing

Marketing mix element in the 7P	Specifics of the element in the digital approach to marketing	Recommended digital technologies for use	Advantages for quality management in high-tech projects
P1: Product	automation of product design and production	AI, IoT	development and high-precision production of more technically complex products
P2: Price	pricing based on the e-commerce mechanism	Big Data	establishing and maintaining a close relationship between price and quality
P3: Place	electronic marketplace	Internet	it is possible to produce both template and unique products
P4: Promotion	promotion on the Internet and on social networks	Internet, mobile devices	«smart» market segmentation based on quality preferences
P5: Process	electronic collection of feedback from consumers	chatbots (AI)	continuity of product quality improvement processes
P6: People	marketing of digital personnel	machine vision (AI, IoT)	reducing the «human factor» and reducing the proportion of marriage
P7: Physical evidence	sales automation with intellectual support for making purchase decisions	«smart» consultants (AI), virtual assistants (VR/AR)	rationalization of customer behavior based on product quality

Source: original development.

As shown in Table 2, with a digital approach to marketing, quality management in high-tech projects in Kazakhstan in P1: Product involves the automation of product design and production using artificial intelligence (AI) and the Internet of Things (IoT) technologies, which will ensure the development and high-precision production of more technically complex products.

P2: Price involves pricing based on the mechanism of electronic commerce using Big Data, which will ensure the establishment and maintenance of a close connection between price and quality.

P3: Place involves electronic marketplaces using the Internet, which will ensure the possibility of producing both standard and unique products according to individual orders.

P4: Promotion involves promotion on the Internet and social networks using technologies such as the Internet and mobile devices, which will ensure “smart” market segmentation based on the criterion of preferences regarding quality.

P5: Process involves electronic collection of feedback from consumers using chatbots based on artificial intelligence (AI) technologies, which will ensure the continuity of product quality improvement processes.

P6: People involve digital personnel marketing using machine vision based on AI and IoT technologies, which will reduce the "human factor" and reduce the share of defects.

P7: Physical evidence involves automation of sales with intelligent support for purchasing decisions using "smart" consultants (AI), virtual assistants (using virtual and augmented reality technologies – VR / AR), which will ensure rationalization of purchasing behavior taking into account product quality.

Discussion

The article contributes to the literature by developing the concept of quality management in high-tech projects in which high-tech products are developed and manufactured (Table 3).

Table 3 – Comparison of new results obtained in the article with existing literature

Field of comparison		Existing literature	New results obtained in the article
Marketing mix elements that are important for quality management	Personnel Marketing	significant (Bejtkovsky, 2018; Jančíková and Milichovský, 2019)	significant (correlation with quality: 15.06%)
	Product Marketing	significant (Anderson and Laverie, 2022; Veselovská, 2022)	significant (correlation with quality: 20.83%)
	Promotion (Branding)	значим (Ibrahim and Aljarah, 2023; Xu et al., 2023)	Not significant (correlation with quality: -9.32%)
	Process Marketing	significant (Akter et al., 2023; Jasin and Firmansyah, 2023)	significant (correlation with quality: 23.61%)
Marketing approach for quality management in high-tech projects in Kazakhstan		pre-digital approach (Haverila et al., 2023; Wang et al., 2022; Zahoor and Lew, 2023; Zhang et al., 2023)	digital approach

The marketing mix elements that are significant for quality management are rethought taking into account the unique experience of Kazakhstan. In support of Bejtkovsky (2018), Jančíková and Milichovský (2019), the importance of personnel marketing is confirmed (correlation with quality: 15.06%). In support of Anderson and Laverie (2022), Veselovská (2022), the importance of product marketing is proven (correlation with quality: 20.83%). In support of Akter et al. (2023), Jasin and Firmansyah, (2023), the importance of process marketing is substantiated (correlation with quality: 23.61%). In contrast to Ibrahim and Aljarah, (2023), Xu et al. (2023) the insignificance of promotion (branding) is substantiated (correlation with quality: -21.53% for pre-digital marketing and -9.32% for digital marketing).

Unlike FIO, it is substantiated that for quality management in high-tech projects in Kazakhstan, a digital approach to marketing is preferable, the advantages of which are the following: greater technical complexity of products, a closer relationship between price and quality, a wider range of products from the standpoint of quality, more accurate market segmentation based on the criterion of preferences regarding quality, continuity of product quality improvement processes, reduction of the "human factor" and reduction in the share of defects, a close relationship between demand and quality.

Conclusion

The key conclusion from the results of the study and the answer to the RQ is that in Kazakhstan, quality management in high-tech projects is preferable using digital marketing technologies. The key ones are: personnel marketing (correlation with quality: 15.06%), product marketing (correlation with quality: 20.83%) and process marketing (correlation with quality: 23.61%).

A digital approach to marketing has been developed to improve quality management in high-tech projects in Kazakhstan. The author's approach includes a marketing mix of quality management in high-tech projects using digital marketing technologies in Kazakhstan. The approach also reveals the organizational and technological aspects of quality management in high-tech projects in Kazakhstan with a digital approach to marketing.

The theoretical significance of the results obtained is that they allowed us to rethink quality management processes when implementing high-tech projects in the digital economy of Kazakhstan, and also revealed promising digital marketing technologies based on AI, IoT, Big Data, the Internet, mobile devices, chatbots, machine vision, "smart" consultants and virtual assistants (VR / AR). The practical significance of the developed digital approach to marketing is related to the fact that it allows improving the quality management practice in high-tech projects in Kazakhstan and provides the following advantages: increasing the technical complexity of products, establishing a closer connection between price and demand with quality, expanding the range of products from the standpoint of quality, more accurate market segmentation based on the criterion of preferences regarding quality, continuity of product quality improvement processes, reducing the “human factor” and reducing the share of defects in the implementation of high-tech projects.

REFERENCES

1 Akter S., Hossain M.A., Tarba S.Y., Leonidou E.. How does quality-dominant logic ensure marketing analytics success and tackle business failure in industrial markets? Industrial Marketing Management, 2023, vol. 109, pp. 44–57. https://doi.org/10.1016/j.indmarman.2022.12.005.

2 Alawag A.M., Alaloul W.S., Liew M.S., (...), Musarat M.A., Al-Mekhlafi A.-B.A. The Role of the Total-Quality-Management (TQM) Drivers in Overcoming the Challenges of Implementing TQM in Industrialized-Building-System (IBS) Projects in Malaysia: Experts’ Perspectives. Sustainability (Switzerland), 2023, vol. 15, no. 8, p. 6607. https://doi.org/10.3390/su15086607.

3 Anderson K.C., Laverie D.A. Signaling Product Quality with Virtual Reality? An Interpretation with Consumer-Perceived Marketing Media Innovativeness: An Abstract. Developments in Marketing Science: Proceedings of the Academy of Marketing Science, 2022, pp. 71–72. https://doi.org/10.1007/978-3-030-89883-0_18.

4 Bejtkovsky J. Promotion as a variable of hr marketing in selected corporations in the Czech Republic in the context of digitization. Acta Universitatis Agriculturae et Silviculturae Mendelianae Brunensis, 2018, vol. 66, no. 6, pp. 1393–1405. https://doi.org/10.11118/actaun201866061393.

5 Benčič S., Kitsay Y.A., Karbekova A.B., Giyazov A. Specifics of Building the Digital Economy in Developed and Developing Countries. Lecture Notes in Networks and Systems, 2020, vol. 87, pp. 39–48. https://doi.org/10.1007/978-3-030-29586-8.

6 Bogoviz A.V., Ragulina Y.V. Industry competitiveness in the new economy. Lecture Notes in Networks and Systems, 2020, 115, v-vi.

7 Chen Y. Comparing content marketing strategies of digital brands using machine learning. Humanities and Social Sciences Communications, 2023, vol. 10, no. 1, p. 57. https://doi.org/ 10.1057/s41599-023-01544-x.

8 Coghlan D., Shani A.B.R., Coughlan P. Enhancing the quality of project management through action research. International Journal of Managing Projects in Business, 2023, vol.16, no. 1, pp. 9–21. https://doi.org/10.1108/IJMPB-10-2021-0291.

9 Duan Y., Liu S., MU C., Cheng E., Liu Y. The moderating effect of managerial discretion on cross-border knowledge search and the innovation quality of high-tech firms in a global health emergency: evidence from China. Journal of Knowledge Management, 2023, vol. 27, no. 1, pp. 121–155. https://doi.org/10.1108/JKM-11-2021-0841.

10 El Khatib M., Alzoubi H.M., Alshurideh M., Alzoubi A.A. Project Quality Management in the United Arab Emirates Mining and Construction Sector: A Literature Review. Studies in Computational Intelligence, 2023, vol.1056, pp. 1341–1353. https://doi.org/10.1007/978-3-031-12382-5_73.

11 Evstratov A.V., Berezhnova A.I. Development of the market of electronic payment systemsin the context of accession of the Russian federation to the WTO. World Applied Sciences Journal, 2013, vol. 23, no. 1, pp. 88–93. https://doi.org/10.5829/idosi.wasj.2013.23.01.526.

12 Gupta N., Singh S. Success of digital marketing model for software development industry: validation of survey based results with case study analysis. Business Process Management Journal, 2023, vol. 29, no. 4, pp. 929–943. https://doi.org/10.1108/BPMJ-10-2022-0474.

13 Haverila M., Li E., Twyford J.C., McLaughlin C. The quality of big data marketing analytics (BDMA), user satisfaction, value for money and reinvestment intentions of marketing professionals. Journal of Systems and Information Technology, 2023. https://doi.org/10.1108/JSIT-10-2022-0249

14 Hrivnák M., Moritz P., Chreneková M. What kept the boat afloat? Sustainability of employment in knowledge-intensive sectors due to government measures during COVID-19 pandemic. Sustainability (Switzerland), 2021, vol. 13, no.15, p. 8441. https://doi.org/10.3390/su13158441.

15 Ibrahim B., Aljarah A. The era of Instagram expansion: matching social media marketing activities and brand loyalty through customer relationship quality. Journal of Marketing Communications, 2023, vol. 29, no. 1, pp. 1–25. https://doi.org/10.1080/13527266.2021.1984279.

16 IMD. World competitiveness online, 2023. URL: https://worldcompetitiveness.imd.org (data accessed: 21.03.2023).

17 Jančíková K., Milichovský F. HR marketing as a supporting tool of new managerial staff in industry 4.0. Administrative Sciences, 2019, vol. 9, no. 3, p. 60. https://doi.org/10.3390/admsci9030060.

18 Jasin M., Firmansyah A. The role of service quality and marketing mix on customer satisfaction and repurchase intention of SMEs products. Uncertain Supply Chain Management, 2023, vol. 11, no. 1, pp. 383–390. https://doi.org/10.5267/j.uscm.2022.9.004.

19 Jung S.-U., Shegai V. The Impact of Digital Marketing Innovation on Firm Performance: Mediation by Marketing Capability and Moderation by Firm Size. Sustainability (Switzerland), 2023, vol. 15, no. 7, p. 5711. https://doi.org/10.3390/su15075711.

20 Konovalov O.E., Beisenbaieva J.M. The Organization of Specialized and High-Tech Cardiologic Care in the Republic of Kazakhstan. Problemy sotsial'noi gigieny, zdravookhraneniia i istorii meditsiny, 2018, vol. 26, no. 6, pp. 461–464. https://doi.org/10.32687/0869-866X-2018-26-6-461-464.

21 Kurmanov N., Zhagalbayev B., Feng W., Rakhimbekova A., Aliyev U. Medium and High-Tech Enterprises of Kazakhstan: Factors of Organization and Development of Innovation. Montenegrin Journal of Economics, 2022, vol.18, no. 3, pp. 7–22. https://doi.org/10.14254/1800-5845/2022.18-3.1.

22 Lin Z., Li S., Zhou H., Wei X. Nonlinear impact of the interaction between internal knowledge and knowledge spillover on patent quality: Evidence from China's provincial high-tech industry. Managerial and Decision Economics, 2023, vol. 44, no. 1, pp. 562–575. https://doi.org/10.1002/mde.3700.

23 Medhat M., Bayomy W.A. Big Data Analytics Impact on Marketing Digital Transformation. Information Sciences Letters, 2023, vol. 12, no. 4, pp. 1901–1911. https://doi.org/10.18576/isl/120414.

24 Miao T., Janchai W., Panyanuwat A. A Quality Assessment and Competency Development through Participatory Knowledge Management Approach for Stakeholders' in "Foreign Experts Introduction Project" in a Chinese University. International Journal for Quality Research, 2021, vol. 15, no. 2, pp. 507–518. https://doi.org/10.24874/IJQR15.02-09.

25 Mohamed M., Tran D.Q. Exploring the Relationships Between Project Complexity and Quality Management Approaches in Highway Construction Projects. Transportation Research Record, 2023, vol. 2677, no. 5, pp. 390-402. https://doi.org/10.1177/03611981221131308.

26 Ng, S.-P. How high-tech SMEs renew resources in innovation projects: A dynamic capabilities perspective. Journal of General Management, 2022. https://doi.org/10.1177/03063070221142736.

27 Painén-Paillalef M.J., Ramírez-Valdivia M.T., Villalobos-Acuña B., Garrido-Rodríguez C. Integration of Project Monitoring and Quality Management: A case study. International Conference on Quality Engineering and Management, 2022, pp. 609–631.

28 Pantano E., Dennis C., Melewar T.C. Technology, brand and people: Branding, identity, image and reputation in the emerging technology-mediated world. Journal of Business Research, 2020, vol. 119, pp. 410–411. https://doi.org/10.1016/j.jbusres.2020.06.031.

29 Parra-López C., Hinojosa-Rodríguez A., Carmona-Torres C., Sayadi S. ISO 9001 implementation and associated manufacturing and marketing practices in the olive oil industry in southern Spain. Food Control, 2016, vol. 62, pp. 23–31. https://doi.org/10.1016/j.foodcont.2015.09.038.

30 Popkova E.G. A new treatment of quality of goods and services in the conditions of the knowledge economy: Opposition of traditions and innovations. International Journal for Quality Research, 2020a, vol. 14, no. 2, pp. 329–346. https://doi.org/10.24874/IJQR14.02-01.

31 Popkova E.G. Quality of Digital Product:Theory and Practice. International Journal for Quality Research, 2020b, vol. 14, no. 1, pp. 201–218. https://doi.org/10.24874/IJQR14.01-13.

32 Popkova E.G. Technological inequality as a source of conflicts in digital development and the advantages of the economic and legal approach to their resolution. Contributions to Conflict Management, Peace Economics and Development, 2022, vol. 30. https://doi.org/10.1108/S1572-832320220000030001.

33 Popkova E.G. Innovation and High-Tech Trends and Their Contribution to the Transition to a New Quality of Economic Growth. Smart Innovation, Systems and Technologies, 2023, vol. 625, pp. 3–11. https://doi.org/10.1007/978-981-19-7411-3_1.

34 Sadykhanova G., Erezhepova A., Nurmanova B., Aitbembetova A., Bimendiyeva L. Efficiency of financing high-tech industries: The case of Kazakhstan. Journal of Asian Finance, Economics and Business, 2019, vol. 6, no. 4, pp. 287–295. https://doi.org/10.13106/jafeb.2019.vol6.no4.287.

35 Vanchukhina L.I., Leybert T.B., Ergasheva S.T., Khalikova E.A., Khanafieva I.R. Integration of the Higher Education Systems of Russia and the Republic of Uzbekistan in Training for the Digital Economy. Education in the Asia-Pacific Region, 2022, vol. 65, pp. 3–13. https://doi.org/10.1007/978-981-16-9069-3_1.

36 Veselovská L. Dual quality of products in Europe: a serious problem or a marketing opportunity? Total Quality Management and Business Excellence, 2022, vol. 33, no. 9–10, pp. 1146-1163. https://doi.org/10.1080/14783363.2021.1940929.

37 Veselovsky M.Y., Izmailova M.A., Bogoviz A.V., Lobova S.V., Ragulina Y.V. System approach to achieving new quality of corporate governance in the context of innovation development. Quality - Access to Success, 2018, vol. 19, no. 163, pp. 30–36.

38 Wang L.-W., Hung C.-C., Hsieh C.-T. Enterprise Precision Marketing Strategy and Quality Management Mobile Information System Based on Customer Satisfaction. Mobile Information Systems, 2022. https://doi.org/10.1155/2022/2105383

39 WIPO. Global Innovation Index 2022, 15th Edition. What is the future of innovation-driven growth? 2023. URL: https://www.wipo.int/publications/en/details.jsp?id=4622 (data accessed 21.03.2023).

40 World Bank. High-technology exports. 2023. URL: https://data.worldbank.org/indicator/TX.VAL.TECH.CD?view=chart (data accessed 07.07.2023).

41 Xu G., Liu H., Zhou K., Zhang X. Cause-related Marketing Strategy in Supply Chain Considering Quality Differentiation. Journal of Systems Science and Systems Engineering, 2023. https://doi.org/10.1007/s11518-023-5556-x.

42 Yamnitsky E., Jankowicz D. Exploratory and exploitative project management: how product and engineering managers' perceptions differ: a case of two large high-tech corporations. International Journal of Innovation Management, 2021, vol. 25, no. 8, p. 2150084. https://doi.org/10.1142/S1363919621500845.

43 Zahoor N., Lew Y.K. Enhancing international marketing capability and export performance of emerging market SMEs in crises: strategic flexibility and digital technologies. International Marketing Review, 2023. https://doi.org/10.1108/IMR-12-2021-0350.

44 Zhang B., Ying L., Khan M.A. ...Barykin S., Jahanzeb A. Sustainable Digital Marketing: Factors of Adoption of M-Technologies by Older Adults in the Chinese Market. Sustainability (Switzerland), 2023, vol. 15, no. 3, p. 1972. https://doi.org/10.3390/su15031972.

45 Government of the Republic of Kazakhstan, 2023. State Program "Digital Kazakhstan", approved by Resolution No. 827 of December 12, 2017. URL: https://strategy2050.kz/ru/state_programs/-/ (data accessed: 21.03.2023).

[1]*Тажиева Ж.Н.,
PhD докторанты, ORCID ID: 0000-0002-1730-6490,
*e-mail: zhanzari@gmail.com
[2]Кесер Е.,
экономика магистрі, ORCID ID: 0000-0003-0360-7492,
e-mail: emrekeser1987@gmail.com
[1]Сандыкбаева У.Д.
филос.ғ.к., аға оқытушы, ORCID ID: 0000-0002-2818-8167,
e-mail: sandykbaeva@mail.ru

[1]әл-Фараби атындағы Қазақ ұлттық университеті,
050000, Алматы қ., Қазақстан
[2]Ишик университеті, Стамбул қ., Түркия

ҚАЗАҚСТАНДАҒЫ ЦИФРЛЫҚ МАРКЕТИНГ ТЕХНОЛОГИЯЛАРЫН ҚОЛДАНУ АРҚЫЛЫ ЖОҒАРЫ ТЕХНОЛОГИЯЛЫҚ ЖОБАЛАРДАҒЫ САПАНЫ БАСҚАРУ

Аңдатпа

Бұл мақаланың мақсаты – Қазақстандағы жоғары технологиялық өнімдердің сапасын арттыруға цифрлық маркетинг технологияларының қосқан үлесін анықтау, сондай-ақ цифрлық маркетинг әдісі арқылы Қазақстандағы жоғары технологиялық жобалардағы сапаны басқару тәжірибесін жетілдіру болашағын айқындау. IMD және WIPO-ның 2013–2022 жж. халықаралық статистикасына сүйене отырып, корреляциялық талдау әдісі арқылы Қазақстандағы жоғары технологиялық жобаларды жүзеге асыру нәтижелері сапаны басқаруда маркетингке балама тәсілдерді (цифрлық және цифрға дейінгі) қолдану арқылы салыстырылды. Негізгі қорытынды – Қазақстанда жоғары технологиялық жобаларда сапаны цифрлық маркетингтік технологияларды пайдалана отырып басқарған жөн. Олардың негізгі бағыттары: персонал маркетингі, өнім маркетингі және процесс маркетингі. Алынған нәтижелердің теориялық маңыздылығы Қазақстанның цифрлық экономикасында жоғары технологиялық жобаларды жүзеге асыру кезінде сапаны басқару процестерін қайта қарастыруға мүмкіндік бергендігінде, сондай-ақ AI, IoT, Big Data, интернет, мобильді құрылғылар, чат-боттар, машиналық көру, «ақылды» кеңесшілер мен виртуалды көмекшілер (VR/AR) негізіндегі перспективалы цифрлық маркетинг технологияларын ашып көрсеткендігінде. Тәжірибелік маңыздылығы – маркетингтің дамыған цифрлық тәсілі Қазақстандағы жоғары технологиялық жобаларда сапаны басқару тәжірибесін жетілдіруге мүмкіндік береді. Авторлық тәсіл Қазақстандағы цифрлық маркетингтік технологияларды пайдалана отырып, жоғары технологиялық жобаларда сапаны басқару маркетингтік кешенін қамтиды. Бұл тәсіл сондай-ақ Қазақстандағы high-tech жобаларында сапаны басқарудың ұйымдық-технологиялық аспектілерін цифрлық маркетинг тәсілін қолдану арқылы ашып көрсетеді.

Тірек сөздер: сапаны басқару, high-tech жобалары, цифрлық маркетингтік технологиялар, Қазақстанның цифрлық экономикасы

[1]*Тажиева Ж.Н.,
PhD докторант, ORCID ID: 0000-0002-1730-6490,
*e-mail: zhanzari@gmail.com
[2]Кесер Е.,
магистр экономики, ORCID ID: 0000-0003-0360-7492,
e-mail: emrekeser1987@gmail.com
[1]Сандыкбаева У.Д.
к.филос.н., ст.преподаватель, ORCID ID: 0000-0002-2818-8167,
e-mail: sandykbaeva@mail.ru

[1]Казахский национальный университет имени аль-Фараби,
050000, г. Алматы, Казахстан
[2]Ишик университет, г. Стамбул, Турция

УПРАВЛЕНИЕ КАЧЕСТВОМ В ВЫСОКОТЕХНОЛОГИЧНЫХ ПРОЕКТАХ С ИСПОЛЬЗОВАНИЕМ ТЕХНОЛОГИЙ ЦИФРОВОГО МАРКЕТИНГА В КАЗАХСТАНЕ

Аннотация

Целью этой статьи является определение вклада цифровых маркетинговых технологий в повышение качества высокотехнологичной продукции в Казахстане, а также выявление перспектив совершенствования практики управления качеством в высокотехнологичных проектах в Казахстане с помощью цифрового подхода к маркетингу. С опорой на международную статистику IMD и WIPO за 2013–2022 гг. с помощью метода корреляционного анализа сопоставлены результаты реализации высокотехнологичных проектов при управлении качеством с использованием альтернативных подходов (цифрового и доцифрового) к маркетингу в Казахстане. Ключевой вывод состоит в том, что в Казахстане предпочтительно управление качеством в high-tech проектах с помощью цифровых маркетинговых технологий. Ключевыми из них являются: маркетинг персонала, маркетинг продукта и маркетинг процессов. Теоретическая значимость полученных результатов состоит в том, что они позволили переосмыслить процессы управления качеством при реализации высокотехнологичных проектов в условиях цифровой экономики Казахстана, а также раскрыли перспективные цифровые маркетинговые технологии с опорой на AI, IoT, Большие данные, Интернет, мобильные устройства, чат-боты, машинное зрение, «умных» консультантов и виртуальных помощников (VR/AR). Практическая значимость связана с тем, что разработанный цифровой подход к маркетингу позволяет усовершенствовать практику управления качеством в high-tech проектах в Казахстане. Авторский подход включает в себя маркетинг микс управления качеством в high-tech проектах с помощью цифровых маркетинговых технологий в Казахстане. Подход также раскрывает организационно-технологические аспекты управления качеством в high-tech проектах в Казахстане при цифровом подходе к маркетингу.

Ключевые слова: управление качеством, high-tech проекты, цифровые маркетинговые технологии, цифровая экономика Казахстана.

Article submission date: 11.09.2024

UDC 658.155
IRSTI 06.73.02

https://doi.org/10.55452/1998-6688-2024-21-3-396-420

[1]*Saparov T.M.,
student, ORCID ID: 0009-0006-5844-4378,
*e-mail: puperraza@gmail.com

[1]Madeniet R.A.,
student, ORCID ID: 0009-0002-3082-8071,
e-mail: m.raykhan.2003@gmail.com

[1]Kaskabassova Ya.S.,
student, ORCID ID: 0009-0003-0576-6814**,**
e-mail: kyasminka@gmail.com

[1]Kazakh-British Technical University, 050000, Almaty, Kazakhstan

THE CONSUMPTION EFFECT OF 2007–2008 FINANCIAL CRISIS: EVIDENCE FROM COMMONWEALTH OF INDEPENDENT STATES

Abstract

To analyze the demand shock effect, we concentrated on the 2008 Financial Crisis, relying on the data from the European Bank for Reconstruction and Development's "Life in Transition Survey" conducted in 2010. This survey offers detailed information on how households reacted two years after the crisis. Regression models were developed to analyze the measures that households took during the economic decline and their implications for consumption. Such measures entailed alterations in spending patterns, saving practices, and other mechanisms of survival. The empirical investigation of the paper gives an understanding of the effects of demand shock such as the 2008 Financial Crisis on households' consumption behavior and their ability to cope with the shocks. The results show that Financial Crisis affect negatively the labor market, which had a negative impact on consumption. Moreover, we explored how government tried to help households, what they used, etc.

Key words: consumption, a shock in the economy, demand shock, the financial crisis, decline in the economy.

Introduction

The Global Financial Crisis (GFC) of 2008 is considered to be one of the most notable economic disruptions since the Great Depression of the 1930s. The crisis began in the United States but spread globally within a very short couple of months. Economies across a lot of regions and continents across the globe suffered, including the Commonwealth of Independent States (CIS). The GFC created intensive damage to consumer spending, business investments, and general economic activity, affecting household consumption patterns profoundly.

However, our study would go directly to research the impact of the 2008 financial crisis on household behavior in each CIS country. The economic crisis in this research is taken to be a demand shock from the theory that relates to the consumption function. Hence, the aim now is to understand how households respond to this economy in their different countries. The policies, therefore, developed to avoid the harmful effects of economic recessions are as important.

Appropriately, the current research aims to understand the mechanisms by which economic downturns influence consumer spending, analyzing information both before and after the crisis.

We also identify the determinants of key drivers of changes in consumption behavior under periods of stress. The importance of such studies will be, therefore, on the information provided that may benefit policymakers, businesses, and academicians on the resilience and adaptability

of households amid economic activities. Our results could provide inputs to policies designed to enhance economic stability and consumer confidence in times of future financial disruptions.

Literature Review

The 2008 financial crisis exemplifies a significant demand shock that led to widespread declines in consumer and investment expenditures globally, including in the Commonwealth of Independent States (CIS) countries. During this tumultuous period, the pronounced instability of financial markets created uncertainty that severely undermined consumer confidence, resulting in reduced expenditures. This instability also negatively impacted employment and income levels, further constraining access to credit.

The effects of the crisis were not uniform across the CIS region; different countries experienced varying intensities and durations of impact. For example, research by Li et al. (2020) employs comparative analysis to highlight the crisis's effects on employment and consumer spending, providing insights that are relevant to understanding the dynamics within the CIS during this period. Their findings emphasize the critical need for timely and targeted macroeconomic policy measures in response to such demand shocks.

In exploring the relationship between wealth and consumption, studies have shown that household expectations play a crucial role during economic downturns. For instance, research by Christelis, Georgarakos, and Jappelli (2015) illustrates how wealth and unemployment shocks influence consumption patterns, particularly when households perceive these shocks as long-lasting.

The distribution of wealth also significantly affects consumption responses. Nardi, French, and Benson (2011) provide a detailed analysis of how disparities in wealth can exacerbate the effects of economic shocks, while Jensen and Johannesen (2017) examine consumer behavior in response to economic downturns, offering valuable insights into the mechanisms at play.

As part of the broader global economic downturn, often referred to as the Great Recession, the 2008 financial crisis spurred extensive research into its causes and effects, particularly regarding monetary, fiscal, and regulatory policies. Studies have highlighted the implications of monetary policy decisions during the crisis (Taylor, 2014) and the effectiveness of unconventional monetary policy (Kuttner, 2018). Additionally, the works of Piketty and Saez (2013) and Gertler and Gilchrist (2018) delve into the broader economic impacts of wealth inequality and credit market conditions, respectively. Mian and Sufi (2010) and Dominguez and Shapiro (2013) further analyze the crisis's effects on household consumption and overall economic stability.

These global trends also shaped the economic responses in the CIS context. Ruziev and Majidov (2013) provide a comparative analysis of the Great Recession's impact on Kazakhstan, the Kyrgyz Republic, and Uzbekistan, highlighting the varying responses of these countries and the lessons that can be drawn for future economic interventions. Their findings underscore the importance of understanding regional dynamics in the face of global economic challenges.

Moreover, the study by Oravský, Tóth, and Bánociová (2020) focuses on the effectiveness of fiscal policies in European countries during economic crises, offering valuable lessons for policymakers in the CIS. Their research suggests that well-targeted fiscal interventions can sustain consumer spending and promote economic stability during shocks, which is crucial for the CIS region as it navigates the aftermath of the Great Recession.

In conclusion, integrating these perspectives on global economic crises and their specific impacts on the CIS, will enhance our understanding of the necessary policy responses to mitigate the effects of future economic shock.

Hypothesis

The hypotheses of this study aim to capture the multifaced nature of demand shock (financial crisis) and its effects on consumption. These hypotheses offer a structured approach to empirically

examining phenomena of GFC within the context of the CIS countries. Each shock has its hypothesis. They follow as:

- Null Hypothesis: A demand shock, caused by the 2008 financial crisis, did not affect consumer consumption within the CIS countries.
- Alternative Hypothesis: A demand shock, caused by the 2008 financial crisis, influenced consumer consumption within the CIS countries.
- By evaluating these hypotheses, our study seeks to contribute nuanced insights into the economic connection between shock and consumer consumption.

Data Section

The data was from survey "Life in Transition Survey" which conducted in 2010. The «Life in Transition Survey» (LITS) was conducted with the assistance of the European Bank of Reconstruction and Development (EBRD) and was aimed to assess the relationship between «life satisfaction and living standards». Two surveys were conducted in the years 2006 (two years before) and 2010 (two years after) across 11 CIS countries and Mongolia. 1000 households were interviewed in each country, so 11,000 households overall.

In 2006, interviews were conducted face-to-face using a two-stage sampling method. At the first stage, "census enumeration areas[1]" (CEA) were used as primary sampling units (PSUs), and in the second stage, households were selected using systematic, equal probability sampling. By 2010, the sampling method had been updated: "local electoral units[2]" were used as PSUs in the first stage, and a "cluster stratified sampling procedure" was used to select households in the second stage.

The Life in Transition Survey I (LiTS I) was conducted during a period when the region's economy was, with few exceptions, expanding rapidly. In contrast, LiTS II was held in late 2010, when most countries were still dealing with the consequences of a catastrophic global economic crisis. LiTS II advances and improves upon LiTS I in two significant ways. First, the questionnaire was significantly altered. The revised questionnaire includes parts on the impact of the crisis and climate change challenges, as well as updated and enlarged questions about corporate governance, public service delivery, and economic and social opinions. Second, the coverage has been extended to include five Western European «comparator» countries. However, we analyzed only CIS countries as they have weaker social safety systems mean consumption drops more sharply during crises.

Methodology

Our dataset for the financial crisis is cross-sectional data where there are 2 models. The first econometric model comprises 19 dependent variables (Y) obtained from the "Life in Transition Survey," which measures the actions households must take during an income decline. The second model comprises 11 dependent variables (Y) which measure the results of the crisis in the labor market. The independent variables (X) are household characteristics, like age, gender, marital status of head household, etc. D.Christelis, D.Georgarakos, and T.Jappelli(2015) used the same socio-economic characteristics for their study. Our data were obtained during face-to-face interviews with households to understand how these characteristics affected on their family during the GFC. These variables are denoted in the Table 1:

[1] Census enumeration areas - are specific geographic regions or units that are used by government agencies or research organizations to conduct censuses or surveys. They are predefined sections of a country or region, divided up for the purpose of systematically collecting population data.

[2] provided the best and most recent information on where people lived, making the data collection process more accurate and efficient.

Table 1 – Variables of Model for Financial Crisis

Variable Name	Description
Dependent Variables (Y's)	Measures taken by households during economic difficulty
Redconsm_stplfood	Reduced consumption of staple foods such as milk/fruits/vegetables/bread
Redconsm_luxgood	Reduced consumption of luxury goods
Redconsm_alchdrink	Reduced consumption of alcoholic drinks such as beer, wine, etc
RedUse_owncar	Reduced use of own car
Red_vacatn	Reduced vacations
Red_tobac	Reduced tobacco smoking
Postp_univer	Postponed/withdrew from university
EnrlUni_lackjob	Enrolled in further education because of lack of job opportunities
Postp_traincours	Postponed/withdrew from training course (e.g. Language, computer, vocational, etc)
Postp_skipdoct	Postponed or skipped visits to the doctor after falling ill
Cncl_healthinsr	Cancelled health insurance (for self-employment activity)
Stop_buymedic	Stopped buying regular medications
Stop_helpfrnd	Stopped/reduced help to friends or relatives who you helped before
Delay_paymutil	Delayed payments on utilities (gas, water, electric)
Hutil_delpay	Had utilities cut because of delayed payment
Cut_tvphinet	Cut TV/phone/internet service
Delay_loaninst	Delayed or defaulted on a loan installment
Sell_asset	Sell an asset
Force_move	Forced to move
hh_job_loss	Head of household lost job
oth_job_loss	Other household member lost job
fam_bus_closed	Family business closed
work_hr_reduced	Working hours reduced
wage_delay_susp	Wages delayed or suspended
wage_reduced	Wages reduced
remittance_reduce	Reduced flow of remittances
fam_return_abroad	Family members returned home from abroad
work_second_job	Someone who was working took a second job or additional work
inc_work_hours	Increased work hours in existing job
new_job_found	Someone who was not working before found a new job (part-time or full-time)
Independent Variables (X's)	
Head_Of_	Q102 Gender of head of household?
HeadOf0	Q104 Age of head of household?
Size_of_	Number of members in the household?
Children	Number of children in the household?
Country	Country
Work_12m	q501 Did you work for income during the past 12 months?
Ind_mainjob	q506m In what industry did you do this job?
Edu_Degree	q515 What is the highest level of education you already completed?
Move_from	q706c Where did you move from?
Martial_Stat	q701 What is your present marital status?
Religion	q716 What is your religion?

Moreover, some variables in Table 2 are included in our analysis without using econometric model, but significant for building graphs

Table 2 – Variables for analyze a Financial Crisis

Variable Name	Description
Dependent Variables (Y's)	Measures taken by households during economic difficulty
Fin_affect	By how much, if at all, has this crisis affected your household in the past two years?
Unem_ben	In the past 12 months has anyone in your household applied for Unemployment benefit?
House_supp	In the past 12 months has anyone in your household applied for Housing support?
Child_supp	In the past 12 months has anyone in your household applied for Child support?
Ts_assit	In the past 12 months has anyone in your household applied for Targeted social assistance (TSA)/ Guaranteed minimum income (GMI)?

Our first regression model looks like this:

$$\text{Logit}\,(P\,(Y_i = 1)) = \beta_0 + {}_i{*}X_i$$

In this model, Y_i represents binary outcomes related to labor market results during the crisis, X_i includes household characteristics, where i indexing individual observations.

Our second regression model looks like this:

$$\text{Logit}\,(P\,(Y_j = 1)) = \beta_0 + {}_j{*}X_j$$

In this model, Y_j represents binary outcomes reflecting actions households took during an income decline, X_j includes household characteristics, where j indexing individual observations.

Because our data contains observations from various countries, we account for the possible existence of correlated errors within countries. We clustered the standard errors at the country level to provide more robust inference. Clustering increases standard errors to account for intra-country correlation, hence increasing the reliability of hypothesis testing. This strategy accounts for heteroskedasticity and potential correlations within each nation group, ensuring that variance among countries doesn't bias our findings. For example, if some economic or social factors influencing household actions during income decrease are consistent across nations, country-level clustering can help address such dependencies.

Additionally, a key strength of our data is that the age of head householders began from 18 years old, while some studies focused-on individuals aged 50 and older and older.[2] This broader age range allows us to capture a more comprehensive view of household responses across different life stages.

Results and discussion

Now, let's find out what the financial crisis has done to people. Interviewers asked each household the following question: "An economic crisis is affecting all the countries of the world as well as our country. How much, if at all, has this crisis affected your household in the past two years?"

The following Figure 1 shows the spread of answers to how the crisis affected their households. We see that most of the respondents reported a limited impact of the crisis on them, to a fair amount, with the least answering that there was a considerable impact (Great deal). This suggests that a large portion of the population in CIS may have been resilient or somewhat insulated from the worst effects of the crisis.




Figure 1 – Percentage of responses on "How much, if at all, has this crisis affected your household in the past two years?"

After we observed the whole percentage of the effect of the crisis on households in the past two years, we want to go deeper and examine what effect the crisis had on each country and how the countries reacted.

Figure 2 was constructed from question (8.01) "As you know, an economic crisis is affecting the whole world and our country. How much, if at all, has this crisis affected your household in the past two years?"




Figure 2 – The crisis's subjective impact varies by country

From Figure 2, we can observe that on average the crisis has equal dispersion across countries from "no effect at all" to "great effect". The greatest effect the crisis had on Georgia, while in Central Asian countries, like Kazakhstan, Kyrgyzstan (Kyrgyz. Republic) and Uzbekistan mostly had no effect at all or little effect.

However, K.Ruziev and T.Majidov (2013) indicated that Kazakhstan, being the most integrated into global financial markets, was significantly affected by the Global Financial Crisis. The crisis led to considerable disruptions in its banking sector, a decline in foreign investment, and a contraction of its economy. Problems with credit growth in Kazakh banks reflect a severe banking crisis, highlighting that Kazakhstan experienced one of the greatest financial shocks. Kyrgyzstan was also affected by the crisis, but to a lesser extent than Kazakhstan. With a smaller and less globally integrated economy, Kyrgyzstan faced negative external shocks, but the crisis did not destabilize its economy to the same degree. Uzbekistan, on the other hand, was relatively insulated from the GFC. The closed nature of the Uzbek financial sector shielded it from the global shock. Additionally, counter-cyclical anti-crisis spending by the authorities helped mitigate the impact on overall economic growth. Consequently, Uzbekistan maintained an economic growth rate of around 9% in 2008 and 2009, experiencing minimal effects from the crisis compared to its neighbors.[18]

After considering the effect of the crisis on each country, we examine how the labor market responded to economic shock in measures such as wage reduction, job loss., wage delay, etc.

In Figure 3 approximately 1/3 of households were affected by wage reduction due to the crisis. The second main crisis transmission is "Head of household lost job". About 3/20 of the heads of households have lost their jobs. Moreover, not only CIS country, but US householder suffered large capital losses in housing and financial wealth and about 5% respondents lost their job according to Christelis, Georgarakos, and Jappelli (2015). The similar situation K.Ruziev and T.Majidov (2013) showed in their studied: In the Kyrgyzstan and Uzbekistan, unemployment rose significantly during the transition period due to structural reforms such as decollectivization in agriculture and the closing down of inefficient enterprises. This led to the release of hidden unemployment, contributing to the overall increase in unemployment rates in these countries.




Figure 3 – Primary channels through which crises are transmitted

Now we seek to examine if individual characteristics of the households affect the reduction in income, etc. Moreover, we seek to see are these fail in labor market significant or not. Therefore, we took only main consequences after crisis in labor market, which is in Figure 3. In Table 3 and Table 4 we can see that each characteristic has its coefficients and compared the results to its reference category. For instance, the reference category for variables "country" is Armenia.

Table 3 – Logit Regression of different types of labor reduction using household's characteristics

	(1)	(2)	(3)	(4)
	hh_job_loss	oth_job_loss	wage_delay_susp	wage_reduced
Head_of_ Female	.0226175 (.804)	.2297938** (.034)	.1589351 (.162)	
Heaf_of0	-.0099891 (.793)	.0885233 (.022)	-.0177556 (.661)	-.0764859*** (.001)
Size_of_ 2	-.290308 (.154)	.9068398*** (.005)	.2463441 (.101)	-.1018902 (.539)
3	-.6086741*** (.001)	1.102633 *** (.000)	.1732478 (.232)	.054225 (.737)
4	-.3467593 (.121)	1.390107*** (.000)	-.0218509 (.893)	-.0047246 (.976)
5+	-.3985409 (.109)	1.918931*** (.000)	.1444296 (.389)	-.014554 (.955)
Children	.1118135 (.218)	-.1950218** (.010)	.0372283 (.364)	-.0536798 (.428)
Country Azerbaijan	.2234697 (.566)	-.0525725 (.918)	1.468159*** (.000)	.6468749*** (.001)
Belarus	-1.840479*** (.000)	-.9905304*** (.000)	1.168739*** (.000)	1.904388*** (.000)
Georgia	-.0684626 (.513)	.652044*** (.000)	-1.231225*** (.000)	-.8623083*** (.000)
Kazakhstan	-.361168*** (.001)	.758616*** (.001)	1.287328*** (.000)	1.019068*** (.000)
Kyrgyzstan	-.6453765* (.050)	-.3113336 (.480)	.9980198*** (.000)	.4078229** (.024)
Moldova	.1929923** (.040)	1.188706*** (.000)	1.591932*** (.000)	1.459081*** (.000)
Mongolia	-1.329856*** (.000)	.7956493*** (.000)	-.0433191 (.749)	.0379338 (.813)
Russia	-.8014325*** (.000)	.5082046*** (.000)	1.15952*** (.000)	1.749844*** (.000)
Tajikistan	-.2892416 (.467)	.2414849 (.642)	1.261348*** (.000)	1.328865*** (.000)
Ukraine	-.8019332*** (.000)	.5639774*** (.000)	1.622486*** (.000)	1.506256*** (.000)
Uzbekistan	.0417401 (.915)	.1604608 (.740)	2.597819*** (.000)	1.183087*** (.000)

Ind_mainjob Manufacturing	.0661541 (.776)	.1965973 (.372)	.1182717 (.550)	.4989734** (.042)
Electricity, gas and water supply	-.2192572 (.592)	-.1593363 (.654)	.3968181 (.197)	.5911361** (.024)
Construction	.4496726 ** (.033)	.2167314 (.184)	-.2461658 (.154)	.2777044 (.246)
Sale, maintenance and repair of moto.	-.1426256 (.746)	.3293113 (.193)	-.2864568 (.059)	.6520278 (.105)
Retail trade, except of motor vehicle.	-.0948179 (.655)	.1060839 (.398)	-.0537015 (.797)	.3811639 (.170)
Hotels and restaurants	.2042422 (.547)	-.2959278 (.183)	.1362016 (.312)	.2670566 (.425)
Transport, storage and communications	-.1803907 (.532)	.2358436 (.325)	.0252117 (.911)	.8168134*** (.003)
Financial intermediation	.0738925 (.806)	.1172438 (.397)	-.0398621 (.819)	.3232657 (.273)
Public administration and defence	-.2104767 (.420)	-.1343555 (.472)	.1965878 (.306)	.2850434 (.205)
Other service activities	.0655401 (.768)	.1025043 (.578)	.0521045 (.605)	.421648 (.126)
Edu_Degree Medium Skill	-.0086072 (.961)	.1106219 (.442)	.0982358 (.317)	.0175023 (.883)
High Skill	-.2513913 (.155)	-.2751772* (.075)	.1531567 (.269)	.1841552*** (.001)
Move_from Non-Migrant	-.1041831 (.367)	-.0740561 (.606)	.0308526 (.701)	-.0861908 (.272)
Martial_Stat MARRIED	.28282 (.196)	-.09878 (.461)	-.1775686** (.048)	.0595109 (.683)
DIVORCED	-.0442432 (.850)	-.4319358 (.104)	-.2076318 (.224)	.0876141 (.493)
SEPARATED	.3664137 (.232)	.2696364 (.458)	.7289731** (.033)	.1896732 (.341)
WIDOWED	-.115085 (.564)	-.2033058 (.363)	-.092932 (.660)	.2581431 (.291)
Religion MUSLIM	-.1586444 (.706)	.3282519 (.527)	-.0606063 (.787)	-.3236317* (.063)
OTHER	.2769866 (.170)	-.2711729 (.115)	-.0354459 (.804)	-.157105 (.250)
Observations	3,720	3,720	3,720	3,720

Notes: *** *p<.01,* ** *p<.05,* * *p<.1*
P-values are denoted at the brackets below the value of coefficients.

Table 4 – Logit Regression of different types of labor reduction using household's characteristics

	(1)	(2)	(3)	(4)
	remittance_ reduce	work_hr_ reduced	fam_bus_closed	work_second_job
Head_of_ Female	.1360439 (.250)	.0422142 (.676)	-.2632777* (.060)	.0621595 (.594)
Heaf_of0	.0248788 (.658)	-.002689 (.932)	.1168209** (.034)	-.0165775 (.694)
Size_of_ 2	-.1660902 (.535)	.3356915 (.233)	-.5748484 (.105)	.0518591 (.816)
3	-.1524426 (.419)	.4271537** (.047)	.1128944 (.712)	.3103021 (.230)
4	-.2946684** (.026)	.3294298 (.263)	.2018033 (.466)	.7599829*** (.000)
5+	-.3837601* (.058)	.2495069 (.468)	-.0728524 (.839)	.6725785** (.012)
Children	.0107843 (.918)	.0720301 (.311)	.1098529 (.372)	-.1539981** (.025)
Country Azerbaijan	-3.824841*** (.000)	2.333385*** (.000)	-.1724368 (.433)	-.4785133* (.078)
Belarus	-1.743849*** (.000)	-.2279746*** (.004)	-.6841212*** (.000)	1.921127*** (.000)
Georgia	-3.61402*** (.000)	.3800408*** (.000)	.2698226** (.048)	-.5797587*** (.000)
Kazakhstan	-1.585754*** (.000)	.908724*** (.000)	-.3723574** (.031)	1.325763*** (.000)
Kyrgyzstan	-.9262432*** (.000)	1.266767*** (.001)	.2311666 (.357)	1.342139** (.000)
Moldova	-.9609975*** (.000)	1.619055*** (.000)	.2297452** (.020)	1.033569*** (.000)
Mongolia	-1.420369*** (.000)	-.5957388*** (.001)	.0564826 (.861)	.9521669*** (.000)
Russia	-2.113445*** (.000)	.6539795*** (.000)	-1.115057*** (.000)	1.224587*** (.000)
Tajikistan	-.2511248 (.136)	.9743718** (.041)	.0700811 (.794)	1.752295*** (.000)
Ukraine	-1.416719*** (.000)	1.22393*** (.000)	-.9558226*** (.000)	1.604934*** (.000)
Uzbekistan	-2.172736*** (.000)	2.298279*** (.000)	-.0188331 (.938)	.4102896 (.138)

Ind_mainjob Manufacturing	-.7330893 *** (.010)	.9507669*** (.002)	-.0559419 (.917)	-.1524283 (.587)
Electricity, gas and water supply	-.475804 (.447)	-.4582318 (.336)	-.5131134 (.514)	.1456623 (.744)
Construction	-.3656574 (.314)	.848903** (.026)	.6115681 (.180)	.2803238 (.339)
Sale, maintenance and repair of moto.	-.7309059 (.136)	-.0899758 (.900)	.7262668** (.038)	.1809671 (.592)
Retail trade, except of motor vehicle.	-.0423707 (.818)	.2406178 (.396)	.8934331** (.036)	-.0357254 (.907)
Hotels and restaurants	.1577842 (.604)	.6024991* (.079)	.5832648 (.221)	.1251954 (.610)
Transport, storage and communications	-.2227254 (.517)	.9147314** (.014)	-.336941 (.506)	-.3735904 (.386)
Financial intermediation	-.5044158 (.199)	.2372015 (.523)	.2311503 (.535)	-.0549968 (.893)
Public administration and defence	-.3604232 (.135)	.5756627* (.084)	-.1925526 (.672)	.3204744 (.100)
Other service activities	-.1602665 (.325)	.5104456** (.031)	.4203834 (.227)	.2899758 (.180)
Edu_Degree Medium Skill	-.1836764 (.118)	.177224 (.181)	.1900242 (.232)	-.0277317 (.825)
High Skill	.3409301*** (.007)	.0426644 (.796)	.4477286** (.043)	.2018708 (.260)
Move_from Non-Migrant	-.0882566 (.578)	.0571773 (.556)	.0627266 (.683)	-.0997182 (.247)
Martial_Stat MARRIED	.0494972 (.805)	-.3640579 (.041)	.3058086 (.205)	-.1631659 (.376)
DIVORCED	-.2513887 (.345)	-.0943156 (.736)	.6281605 (.102)	-.1465093 (.463)
SEPARATED	.1722337 (.525)	-.2433869 (.669)	.2591171 (.644)	-.3818266 (.282)
WIDOWED	.0786251 (.740)	-.2353005 (.343)	.191973 (.710)	-.5207354* (.062)
Religion MUSLIM	.5504566*** (.005)	-.602302 (.178)	.0399578 (.848)	.4195011 (.123)
OTHER	.0596574 (.784)	.0298846 (.887)	.0099479 (.974)	.2458292 (.141)
Observations	3,720	3,720	3,720	3,720

Notes: *** *p<.01,* ** *p<.05,* * *p<.1*
P-values are denoted at the brackets below the value of coefficients.

Table 3 and Table 4 show that when the head of the household is female (with positive coefficients), these households have a slightly higher chance of experiencing job loss, wage reduction, or other consequences from the crisis. However, these effects are very small and not statistically significant (i.e., they are not strong enough to confidently conclude they matter) compared to households with male heads.

Since "Head_Of0" is treated as a continuous variable, the model captures the effect of age changes on the likelihood of the outcome. On average, the coefficients are negative and not significant, meaning that as the age of the household head increases, the likelihood of experiencing wage reduction or other problems does not significantly decrease.

The size of the household also affects the likelihood of experiencing labor reductions, sometimes leading to a higher likelihood and sometimes a lower likelihood, but these effects are not statistically significant. Similarly, the variable "Children," which measures the number of children in the household, has a non-significant effect on labor reductions.

Most CIS countries show a significant impact from the crisis. For instance, all countries except Georgia have significantly positive coefficients, indicating a much higher likelihood of wage reduction compared to Armenia. This suggests that households in these countries are significantly more likely to experience a salary decrease than those in Armenia. In contrast, Georgia has a negative coefficient, meaning household there are much less likely to experience a salary cut compared to Armenia. In terms of job loss, households in Belarus, Kazakhstan, Kyrgyzstan, Mongolia, Russia, and Ukraine are significantly less likely to have a head of household lose their job compared to Armenia, while head of households in Moldova are significantly more likely to experience job loss, etc.

The industry where the head households did work, mostly equally affect the labor reductions, but not significantly. For example, a head of households that work in Manufacturing sector significantly more likely to experience wages cut than who work in Agriculture, hunting and forestry sector, but who work in Constructuon sector more likely to suffer salaries cut, but not significantly compared to who work in Agriculture, hunting and forestry sector. The last variables on average, equally affect the labor reductions, but not significantly.

Now, after observing the condition of the labor market, we continue to examine what effect it brings on consumption such as a reduction in tobacco consumption, a reduction in consumption of luxury goods, etc.

In Figure 4 below, households believe, on average, that each consumption category was affected by the financial crisis. More than 50% of households believe that the consumption of staple foods was reduced due to the financial crisis, while more than 20% believe that the reduction was due to other factors. The same interpretation works for other reduction in consumption.




Figure 4 – Adjustments in expenditure based on economic impact

But is it possible that the individual characteristics of the households affect the measures that were undertaken during economic decline? We examine this by using our second econometric model. In Table 5 we can see that each characteristic has its reference category.

Table 5 – Logit regressions for 3 types of results from reduction in labor market

	(1)	(2)	(3)	(4)
	Redconsm_ stplfood	Redconsm_ luxgood	Redconsm_ alchdrink	RedUse_owncar
Head_of_ Female	.0442596 (.589)	.0658183** (.032)	-.2535831*** (.005)	-.1401213 (.294)
Heaf_of0	.0680169* (.063)	-.0094945 (.674)	.0094031 (.779)	-.017527 (.625)
Size_of_ 2	-.0681985 (.638)	.1759427** (.024)	-.0651012 (.675)	.0970061 (.554)
3	-.1373718 (.300)	.3546897*** (.001)	-.0384498 (.880)	.2065794 (.339)
4	-.1394317** (.235)	.3085375*** (.004)	-.1577379 (.517)	.4911755* (.099)
5+	-.0874733* (.585)	.2763836** (.049)	-.1371272 (.640)	.7298431** (.014)
Children	.0537262 (.246)	-.0240502 (.516)	.0629844 (.442)	-.0605134 (.507)
Country Azerbaijan	-1.348482*** (.000)	-.1096188 (.386)	-.6935673*** (.000)	-.5069505* (.098)
Belarus	-1.152806*** (.000)	-.7514553*** (.000)	.4571022*** (.000)	.1537026*** (.002)
Georgia	.1808256*** (.000)	-.5905886*** (.000)	-.9169325** (.000)	-.639603*** (.000)
Kazakhstan	-.9419693*** (.000)	-.5042188*** (.000)	-.0243849 (.767)	-.5627967*** (.000)
Kyrgyzstan	-.4558194*** (.000)	-.0653946 (.469)	-.6677763*** (.000)	-.6956868** (.019)
Moldova	-.7282575*** (.000)	.0193143 (.661)	.9656499** (.000)	.4694194*** (.000)
Mongolia	-.8876124*** (.000)	-.6662179*** (.000)	1.676568*** (.000)	.4858001* (.071)
Russia	-.9815644*** (.000)	-.7391855*** (.000)	.0617641 (.243)	-.370075*** (.000)
Tajikistan	-.3782899*** (.005)	-.5187364*** (.000)	-.5643272*** (.001)	.4995573 (.129)
Ukraine	-.1716551*** (.000)	.0287458 (.623)	.9326978*** (.000)	-.063869 (.357)
Uzbekistan	-1.447251*** (.000)	-.2300833** (.019)	-.0617934 (.736)	-.4628755 (.181)

Ind_mainjob Manufacturing	-.1999595 (.156)	-.2965378* (.076)	-.4737182** (.038)	-.1255753 (.487)
Electricity, gas and water supply	-.168835 (.533)	-.2657117 (.309)	.3146095 (.517)	.0084076 (.984)
Construction	-.3736837 *** (.000)	-.315308** (.054)	-.178617 (.424)	-.2750636 (.307)
Sale, maintenance and repair of moto.	-.2569121** (.046)	-.3451021* (.061)	-.3133094** (.219)	-.4009929** (.037)
Retail trade, except of motor vehicle.	-.3297562 *** (.000)	-.3779807** (.024)	-.2597943** (.223)	-.2900733* (.099)
Hotels and restaurants	-.2955364** (.046)	.0815696 (.708)	-.2532383 (.319)	-.3630935 (.220)
Transport, storage and communications	-.2709635 (.107)	-.048628 (.796)	-.0365297 (.840)	-.0252094 (.893)
Financial intermediation	-.4646015*** (.001)	-.0552362 (.732)	-.1758669 (.440)	-.289434* (.055)
Public administration and defence	-.2308141* (.054)	-.2569804* (.070)	-.4424418** (.048)	-.2496261* (.057)
Other service activities	-.1758964*** (.007)	.2191562 (.140)	-.2557098 (.220)	-.154024 (.250)
Edu_Degree Medium Skill	-.1973284** (.032)	-.096554 (.117)	-.0522613 (.671)	.1602235 (.108)
High Skill	-.5290214*** (.000)	.0302618 (.770)	-.177781 (.136)	.3719262** (.011)
Move_from Non-Migrant	-.1551588 (.132)	-.0685471 (.445)	-.0907574 (.323)	.0139594 (.893)
Martial_Stat MARRIED	.1651001 (.221)	.0471907 (.348)	.0325335 (.744)	.4109478*** (.001)
DIVORCED	.3337901 (.115)	.2213577* (.057)	-.3988222*** (.004)	-.0272703 (.895)
SEPARATED	.0564091 (.825)	.1909946 (.364)	.329787 (.347)	.7131019*** (.007)
WIDOWED	.7356435*** (.000)	.4083689** (.010)	-.07030313 (.803)	.2819545 (.341)
Religion MUSLIM	-.24666869** (.010)	-.2281648* (.054)	.3142438** (.034)	-.0231042 (.943)
OTHER	.1091709 (.323)	.0304194 (.802)	.239949* (.052)	-.0973737 (.721)
Observations	6,029	6,029	6,029	6,029

Notes: *** *p<.01,* ** *p<.05,* * *p<.1*
P-values are denoted at the brackets below the value of coefficients.

Table 6 – Logit Regression of different types of labor reduction using household's characteristics

	(1)	(2)	(3)	(4)
	Red_vacatn	Red_tobac	Stop_helpfrnd	Delay_paymutil
*Head_of_* Female	.1369416*** (.003)	-.354506*** (.009)	.1190035 (.369)	.2930369*** (.002)
Heaf_of0	-.0461702** (.015)	-.1056277*** (.000)	.0210806 (.623)	.0077162 (.838)
*Size_of_* 2	.2532732*** (.000)	.0327652 (.839)	.0635916 (.721)	-.1285219 (.410)
3	.3654038*** (.002)	.0521217 (.742)	-.0563513 (.837)	.0223111 (.904)
4	.4817861*** (.007)	.087478 (.680)	.0696307 (.780)	-.0260566 (.879)
5+	.0357553 (.424)	.0793921 (.745)	-.1370089 (.596)	-.0770869 (.726)
Children	.0357553 (.633)	-.0565202 (.551)	.0600829 (.337)	.1091275* (.054)
Country Azerbaijan	-.7161822*** (.002)	-.8012316*** (.005)	.3670805 (.132)	-.1355292 (.184)
Belarus	.5491474*** (.000)	-.2075624* (.058)	.5689162*** (.000)	-.6928703*** (.000)
Georgia	-1.612404*** (.000)	-.355837*** (.000)	-.6962962*** (.000)	-.8462211*** (.000)
Kazakhstan	.8267488*** (.000)	-1.392673*** (.000)	.6602215*** (.000)	.1020535 (.138)
Kyrgyzstan	-.2099656 (.324)	-1.582968*** (.000)	.8306422*** (.000)	-.2181603 (.151)
Moldova	1.722549*** (.000)	-.2240071** (.013)	.6325547** (.020)	-.9220617*** (.000)
Mongolia	.4851969*** (.004)	.5722665*** (.000)	.02232268 (.874)	1.059851*** (.000)
Russia	.8494851*** (.000)	-.9464105*** (.000)	.277133*** (.003)	-.4762501*** (.000)
Tajikistan	-1.127752*** (.000)	-.0799532 (.762)	.4763395** (.030)	-.5978346*** (.000)
Ukraine	1.262464*** (.000)	.1377006 (.291)	.6597333*** (.000)	.2389732*** (.002)
Uzbekistan	1.401246*** (.000)	.1442825 (.616)	.3695805* (.096)	-.0497077 (.709)

Ind_mainjob				
Manufacturing	.091839 (.769)	.0897889 (.764)	-.6051537*** (.007)	-.2337162 (.341)
Electricity, gas and water supply	.1673096 (.752)	.0295912 (.937)	-.5207665** (.017)	-.2822704 (.331)
Construction	.17089243 (.544)	.3218052 (.348)	-.1985854 (.349)	-.1703916 (.249)
Sale, maintenance and repair of moto.	.3031078 (.198)	-.9342041* (.091)	-.1938377 (.446)	.1712526 (.526)
Retail trade, except of motor vehicle.	.1936998 (.399)	-.1001405 (.700)	-.14028 (.297)	.249762 (.118)
Hotels and restaurants	.5495642** (.017)	.1614046 (.636)	.1845017 (.391)	.3209145 (.236)
Transport, storage and communications	.1807108 (.344)	.4850889** (.025)	-.0096669 (.969)	-.2177509 (.335)
Financial intermediation	.3742497** (.032)	-.0146538 (.967)	-.0444971 (.686)	-.0258369 (.929)
Public administration and defence	.3183046** (.046)	-.1656068 (.509)	-.1809184 (.176)	.0334858 (.808)
Other service activities	.3917301** (.024)	.2293401 (.161)	-.1182586 (.205)	.0432078 (.788)
Edu_Degree				
Medium Skill	.1193029 (.299)	-.0328855 (.835)	.0638256 (.701)	-.2471835** (.027)
High Skill	.3886578*** (.000)	-.2470807 (.214)	.2159585 (.189)	-.363684*** (.001)
Move_from				
Non-Migrant	-.0902729* (.070)	.0070895 (.945)	-.1723933 (.228)	-.0763126 (.383)
Martial_Stat				
MARRIED	.1468026 (.256)	.2492013 (.133)	.0215957 (.871)	.0765257 (.605)
DIVORCED	.3007177 (.105)	-.0999406 (.714)	.0212852 (.900)	.3228152* (067)
SEPARATED	.0578499 (.719)	.7455672** (.019)	.5419217* (.062)	.5842309 (.143)
WIDOWED	-.0594264 (.684)	-.1028908 (.668)	.1489769 (.579)	.2294382 (.149)
Religion				
MUSLIM	-.2060167 (.379)	-.1640688 (.553)	-.0086013 (.972)	-.0318701 (.800)
OTHER	-.1099047 (.527)	.0104927 (.951)	.056162 (.596)	-.1792652*** (.003)
Observations	6,029	6,029	6,029	6,029

Notes: *** *p<.01,* ** *p<.05,* * *p<.1*
P-values are denoted at the brackets below the value of coefficients.

What these tables give us: It shows that reduction in consumption of some goods and other difficulties are affected by country and by types of industry job. For instance, all CIS countries show a significant impact from a decline in income or other economic difficulty. For instance, all countries except Georgia have significantly negative coefficients, indicating these countries are less likely to report reduced consumption of staple foods such as milk / fruits / vegetables / bread compared to Armenia. In contrast, Georgia is showing a significant positive effect, meaning people in Georgia are more likely to have reduced their consumption of staple foods compared to Armenia. Several industries have significant negative coefficients, which mean households working in these sectors (e.g., construction, retail trade, and financial intermediation) are less likely to reduce their consumption of staple foods compared to who work in Agriculture, hunting and forestry sector. Both medium (upper secondary) and high skill (bachelor and master/phd degree) education levels show significant negative effects. This suggests that households with higher levels of education are less likely to reduce their staple food consumption compared to households with low levels of education (No degree/ primary/ lower secondary education), etc. We can state that after a decline in income or other labor market difficulties, households suffer reduction in consumption and not only.

Seeing that the financial crisis affects their households, some of them might ask for help from the government. To address the crisis, governments implemented various measures such as revisions to social assistance programs, unemployment insurance, and pensions, as well as income support through public investment. For instance, Takis Venetoklis (2021) stated that during the 2008 financial crisis, many governments implemented various fiscal and monetary policies as a response to the severe recession. There were Job Creation Programs, Support for Homeowners, emergency Lending Facilities, etc. Our data contained different aid compared to the study before.

Figures 5 – 8 depict the percentage of households in CIS nations that requested at least one of four categories of government assistance in reaction to the financial crisis. The four categories of benefits analyzed are «unemployment benefits», «housing support», «child support», and «targeted social assistance (TSA)/guaranteed minimum income (GMI)». According to the data, just a small percentage of households in each country filed for government support.




Figure 5 – Percentage Distributions of Unemployment Benefits by Country




Figure 6 – Percentage Distributions of Housing Support by Country




Figure 7 – Percentage Distributions of Child Support by Country




Figure 8 – Percentage Distributions of Targeted Social Assistance by Country

The data from Figures 5 – 8 shows that Azerbaijan, Armenia, and Ukraine have the greatest percentages of households filing for unemployment assistance. Russia, Ukraine, and Mongolia receive the most housing support applications. Uzbekistan, Russia, and Ukraine have the highest child support application rates. Finally, Azerbaijan, Georgia, and Moldova are the countries where households are most likely to apply for targeted social assistance (TSA)/guaranteed minimum income.

However, it is crucial to understand that applying for government assistance does not ensure receipt of those benefits, as applications may be denied. As a result, we intend to show a graph depicting the proportion of households considerably affected by the crisis («a great deal» or «a fair amount») that received at least one of these benefits in each country.

Figure 9 demonstrates the percentage of households in CIS who received at applied for at least one of four types of government benefits due to the financial crisis. Four types of governmental unemployment benefits were highlighted: “unemployment benefits”, “housing support”, “child support”, and “targeted social assistance (TSA)/ Guaranteed minimum income”. As we can see, Azerbaijan has the greatest proportion of households that receive governmental benefits (40% among respondents), while Kyrgyzstan has the lowest percentage of households that applied governmental benefits among the respondents (less than 5%).

Even if households received benefits, it does not guarantee that they were beneficial. Some homes may have found them ineffectual. Detrimental policy is a serious problem in the period of crisis as one research showed that shift in economic policy during the Great Recession was not effective. It highlighted a significant move away from predictable rule-like decision-making toward more discretionary and interventionist policies, which contributed to poor economic performance and a slow recovery.[11]

The following Figures 10 – 13 shows how much benefit is thought of several types of government assistance in different countries. According to the findings, unemployment payments were seen positively in Armenia and Ukraine but negatively in Russia and Belarus. Housing assistance produced varied outcomes, being both beneficial and detrimental in Russia and Ukraine. Child support was

considered very beneficial in Uzbekistan and Kazakhstan, but not at all helpful in Russia or Belarus. The ultimate advantage, TSA or GMI, was found to be beneficial in Moldova, Uzbekistan, Armenia, and Georgia, but not in Azerbaijan, Russia, or Ukraine




Figure 9 – The extent of Government Benefits Provided to Poor Households Impacted by the Crisis Across Four Categories




Figure 10 – Reported Support of Government Aid of Unemployment Benefit Across Countries




Figure 11 – Reported Support of Government Aid
of Housing Support Across Countries




Figure 12 – Reported Support of Government Aid
of Child Support Across Countries




Figure 13 – Reported Support of Government Aid of TSA Across Countries

Based on these findings, it can be concluded that government benefits were viewed as least helpful in Russia, followed by Ukraine and Belarus. However, the situation in Uzbekistan stands out, where these benefits were seen as particularly effective, with Armenia showing moderate effectiveness.

Figure 14 illustrates this further by depicting the percentage distribution of responses across the four types of benefits, offering a clearer picture of how various populations perceived the support they received.




Figure 14 – Overall percentage performance for 4 types of benefits

Overall, the percentage of respondents who considered the benefits «Very helpful» is higher than those who found them «Not at all helpful,» implying that government benefits generally helped households. Despite the fact, that governmental aid like these help the households, it would be better to use other policies, like Quantitative Easing (QE) and Forward Guidance, which K. N. Kuttner (2018) stated. These were unconventional monetary policies, which provided significant support to households by lowering borrowing costs, increasing access to credit, enhancing wealth through rising asset prices, and contributing to job creation and economic stability. These effects collectively improved the financial conditions of many households during a challenging economic period.

Conclusion and Future Work

This paper sought to compare the various effects of the financial crisis of 2008 on consumption. The 2008 crisis, a demand shock, showed that consumption was highly sensitive to changes in consumer confidence and wealth, which reduced, and credit availability that was also reduced, as seen in the following. This study revealed that the degree of households' adjustment was through cutting on expenditure on necessities and non-essential goods, forgoing medical expenses, and postponing payments for utilities. These results underscore the importance of timely and well-directed macroeconomic policies in preventing the consequences of demand fluctuations and supporting consumer demand during crises.

Furthermore, this study also revealed that some of the household demographic variables had a statistically meaningful impact on the consumption and labour market variables except for the place of residence at the time of the interview. Moreover, the government support can be identified as one of the most significant factors during the crisis, but these aids perhaps were not so effective idea to be used in crisis. Overall, we reject the Null hypothesis of our research.

Further research should be conducted to find out how such shocks affect the economy in the long run and how policy interventions can help prepare for future disruptions.

REFERENCES

1 Oravský R., Tóth P., & Bánociová A. The Ability of Selected European Countries to Face the Impending Economic Crisis Caused by COVID-19 in the Context of the Global Economic Crisis of 2008. Journal of Risk and Financial Management, 2020, vol. 13, no. 179, pp. 1–16.

2 Christelis D., Georgarakos D., and Jappelli T. Wealth shocks, unemployment shocks and consumption in the wake of the Great Recession. Journal of Monetary Economics, 2015, vol. 72, pp. 21–41.

3 European Bank for Reconstruction and Development, 2010, Life in Transition: After the crisis. EBRD. https://www.ebrd.com/lifeintransition

4 Dilek S., Çolakoğlu N. The Relationship Between Income and Consumption After Global Financial Crisis. China-USA Business Review, 2011, vol. 10, no. 12, pp. 1221–1230. ISSN 1537-1514.

5 Survey of Household Finances (EFF) 2014: methods, results and changes since 2011.

6 Bosworth B. and Flaaen A. America's Financial Crisis: The End of an Era, ADBI Working Paper Series, 2009.

7 Khan M. Global Financial Crisis of 2008 and its impacts, 2008.

8 Venetoklis T. Exogenous shocks and citizens' satisfaction with governmental policies: can empirical evidence from the 2008 financial crisis help us understand better the efects of the COVID-19 pandemic? 2021, vol. 55, pp.1973–2000.

9 De Nardi M., French E., and Benson D. Consumption and the Great Recession. NBER Working Paper, 2011, no. 17688.

10 Jensen T. L. and Johannesen N. The Consumption Effects of the 2007–2008 Financial Crisis: Evidence from Households in Denmark. American Economic Review, 2017, vol. 107.11, pp. 3386–3414.

11 Taylor Jo.B. The Role of Policy in the Great Recession and the Weak Recovery. American Economic Review, 2014, vol. 104.5, pp. 61–66.

12 Kuttner K.N. Outside the Box: Unconventional Monetary Policy in the Great Recession and Beyond. Journal of Economic Perspectives, 2018, vol. 32.11, pp. 121–46.

13 Piketty Th. and Saez E. Top Incomes and the Great Recession: Recent Evolutions and Policy Implications. IMF Economic Review, 2013, vol. 61, pp. 456–478.

14 Kathryn M.E. Dominguez and Matthew D. Shapiro. Forecasting the Recovery from the Great Recession: Is This Time Different? American Economic Review, 2013, vol. 103.3, pp. 147–52.

15 Gertler M. and Gilchrist S. What Happened: Financial Factors in the Great Recession. Journal of Economic Perspectives, 2018, vol. 32.3, pp. 3–30.

16 Mian A. and Sufi A. The Great Recession: Lessons from Microeconomic Data. American Economic Review, 2010, vol. 100.2, pp. 51–56.

17 Ruziev K. and Majidov T. Differing Effects of the Global Financial Crisis on the Central Asian Countries: Kazakhstan, the Kyrgyz Republic and Uzbekistan. Europe-Asia Studies, 2013, vol. 65.4, pp. 682–716.

[1*]Сапаров Т.М.,
студент, ORCID ID: 0009-0006-5844-4378,
*e-mail: puperraza@gmail.com
[1]Мадениет Р.А.,
студент, ORCID ID: 0009-0002-3082-8071,
e-mail: m.raykhan.2003@gmail.com
[1]Каскабасова Я.С.,
студент, ORCID ID: 0009-0003-0576-6814,
e-mail: kyasminka@gmail.com

[1]Қазақстан-Британ техникалық университеті,
050000, Алматы қ., Казақстан

2007–2008 ЖЖ. ҚАРЖЫЛЫҚ ДАҒДАРЫСТЫҢ ТҰТЫНУҒА ӘСЕРІ: ТӘУЕЛСІЗ МЕМЛЕКЕТТЕР ДОСТАСТЫҒЫ БОЙЫНША МӘЛІМЕТТЕР

Аңдатпа

Сұраныс соққысының әсерін талдау үшін біз 2008 жылғы қаржылық дағдарысқа назар аударып, 2010 ж. жүргізілген Еуропалық қайта құру және даму банкінің «Өтпелі кезеңдегі өмір» зерттеуінің мәліметтеріне сүйендік. Бұл зерттеуде дағдарыстан екі жыл өткеннен кейінгі үй шаруашылықтарының реакциясы туралы толық ақпарат берілген. Экономикалық құлдырау кезеңінде үй шаруашылықтары қабылдаған шараларды және олардың тұтынуға әсерін талдау үшін регрессиялық модельдер әзірленді. Бұл шаралар шығыстар құрылымына, жинақтау практикасына және басқа да өмір сүру тетіктерінің өзгеруіне әсер етті. Мақалада жүргізілген эмпирикалық зерттеу 2008 жылғы қаржылық дағдарыс сияқты сұраныс соққысының үй шаруашылықтарының тұтынушылық мінез-құлқына және осы соққыға қарсы тұру қабілетіне әсерін түсінуге мүмкіндік береді. Нәтижелер қаржылық дағдарыстың еңбек нарығына теріс әсер еткенін және оның тұтынуға теріс ықпал жасағанын көрсетеді. Сонымен қатар, біз үкіметтің үй шаруашылықтарына қалай көмектесуге тырысқанын және олардың қандай қолдау тетіктерін пайдаланғанын зерттедік.

Тірек сөздер: тұтыну, экономикалық дағдарыс, сұраныс соққысы, 2008 жылғы қаржылық дағдарыс.

[1]*Сапаров Т.М.,
студент, ORCID ID 0009-0006-5844-4378,
*e-mail: puperraza@gmail.com

[1]Мадениет Р.А.,
студент, ORCID ID 0009-0002-3082-8071,
e-mail: m.raykhan.2003@gmail.com

[1]Каскабасова Я.С.,
студент, ORCID ID 0009-0003-0576-6814,
e-mail: kyasminka@gmail.com

[1]Казахстанско-Британский технический университет,
050000, г. Алматы, Казахстан

ЭФФЕКТ ПОТРЕБЛЕНИЯ ОТ ФИНАНСОВОГО КРИЗИСА 2007-2008 гг.: ДАННЫЕ ПО СОДРУЖЕСТВУ НЕЗАВИСИМЫХ ГОСУДАРСТВ

Аннотация

Для анализа эффекта шока спроса мы сосредоточились на финансовом кризисе 2008 г., опираясь на данные исследования Европейского банка реконструкции и развития «Жизнь в переходный период», проведенного в 2010 г. В этом исследовании содержится подробная информация о реакции домохозяйств через два года после кризиса. Были разработаны регрессионные модели для анализа мер, принятых домохозяйствами во время экономического спада, и их последствий для потребления. Эти меры повлекли за собой изменение структуры расходов, практики сбережений и других механизмов выживания. Эмпирическое исследование, проведенное в статье, позволяет понять влияние шока спроса, такого как финансовый кризис 2008 г., на потребительское поведение домохозяйств и их способность противостоять этому шоку. Результаты показывают, что финансовый кризис негативно повлиял на рынок труда, что отрицательно сказалось на потреблении. Кроме того, мы изучили, как правительство пыталось помочь домохозяйствам, чем оно пользовалось и т.д.

Ключевые слова: потребление, шок в экономике, шок спроса, финансовый кризис, спад в экономике.

Article submission date: 07.06.2024

REQUIREMENTS TO THE DESIGN OF ARTICLES PUBLISHED IN THE JOURNAL KBTU BULLETIN

Previously **unpublished material by the author (s)** corresponding to the profile of the journal in Russian, Kazakh or English is accepted for publication. The article is provided in electronic format (in formats .doc, .docx,) only by downloading it through the functionality of the journal's website (https://vestnik.kbtu.edu.kz/jour/about), which has detailed instructions for authors on the process of submitting articles, as well as on payment for publication.

Mandatory requirements for registration:

- The MRNTI index is placed in the upper-left corner. (Times New Roman 14 size)
- One single interval below the authors ' surnames and initials in bold. Detailed names of organizations, cities, countries where the work was performed, e-mail of one of the authors. Specify footnotes to the place of work of the authors.
- Below, in one interval, the full title of the article is in bold.
- Below, a brief (150-250 words) abstract (abstract) at one interval. Abstract should outline the general orientation of the article and formulate its main results and be self-sufficient, it should not contain references to literary sources or to any sections and elements of the article to which it relates.
- Key words related to the submitted article.

The text of the article is typed in a straight font Times New Roman, size 14. The line spacing is single. All fields are 2 cm long.

The article should be divided into sections: Introduction, Materials and Methods, Results and Discussion, Conclusion, Information on funding (if available).

At the end, a "List of References" is given. Literary references in the text are in square brackets [1]. The list of references is drawn up twice: according to the above GOST. The list should fully correspond to the main text of the article, contain all the works mentioned (and only mentioned) in it. Next, the same list of references should be presented in the generally accepted English transliteration (see the sample of the literature design below).

The article undergoes "blind" review, reviewers are appointed by the editorial board of the journal.

At the end of the article please indicate full name, return address, phone numbers, fax, e-mail address.

The author(s) are responsible for the content of the article. The opinion of the Scientific and Editorial Board does not always coincide with the opinion of the author (authors). The Editorial Board reserves the right to publish or reject articles.

The reference to our edition in reprinting is obligatory.

Our address: **59, Tole Bi St., Almaty, 050000, Kazakhstan-British Technical University.**
Website: https://vestnik.kbtu.edu.kz/jour/pages/view/EditorialC Editorial Board.

ЖУРНАЛЫНДА ЖАРИЯЛАНАТЫН МАҚАЛАЛАРДЫ РӘСІМДЕУГЕ ҚОЙЫЛАТЫН ТАЛАПТАР

Жариялау үшін **автормен (авторлармен) бұрын жарияланбаған,** журнал бейініне сәйкес келетін орыс, қазақ немесе ағылшын тілдеріндегі материалдар қабылданады. Мақала журнал сайтының (https://vestnik.kbtu.edu.kz/jour/about) функционалдығы арқылы жүктеу жолымен тек электронды форматта (.doc, .docx форматтарында) қабылданады, сайтта авторларға мақаланы жүктеу, ұсыну үрдісі туралы, сондай-ақ жарияланымға ақы төлеу туралы толық нұсқаулық бар.

Ресімдеу бойынша міндетті талаптар:

Жоғарғы сол жақ бұрышта ҒТАМИ индексі жазылады. (Times New Roman 14 өлшем)

- Бір бірлік интервалдан кейін авторлардың тегі мен аты-жөні жартылай қалың қаріппен жазылады. Жұмыс орындалған ұйымдардың, қалалардың, елдердің толық атаулары, авторлардың бірінің e-mail поштасы көрсетіледі. Авторлардың жұмыс орнына сілтеме беріледі.
- Бір интервалдан кейін мақаланың толық атауы жартылай қалың қаріппен жазылады.
- Бір интервалдан кейін қысқаша (150–250 сөз) аңдатпа (abstract) ұсынылады. Аңдатпа мақаланың жалпы бағытын көрсетіп, оның негізгі нәтижелерін тұжырымдауы тиіс, аңдатпада әдеби дереккөздерге де, оған қатысты мақаланың кез-келген бөлімдері мен элементтеріне сілтеме жасауға болмайды.
- Ұсынылған мақалаға қатысты кілт сөздер (тірек сөздер) жазылады.

Мақала мәтіні 14 өлшемді Times New Roman шрифтімен теріледі. Жолдар арасында бірлік интервал сақталады. Шеттер – барлық жағынан 2 см.

Мақала келесі бөлімдерді қамтуы тиіс: Кіріспе, Материалдар және әдістер, Нәтижелер мен талқылау, Қорытынды, Қаржыландыру туралы ақпарат (болған жағдайда көрсетіледі).

Соңында «Әдебиеттер тізімі (References)» жазылады. Мәтіндегі әдеби сілтемелер төртбұрышты жақшада ұсынылады [1]. Әдебиеттер тізімі МЕМСТ-ке сәйкес екі рет рәсімделеді. Тізім мақаланың негізгі мәтініне толық сәйкес келіп, мақалада аталған (тек аталған) барлық жұмыстарды қамтуы керек. Әрі қарай, дәл осы сілтемелер жалпы қабылданған ағылшын транслитерациясында жазылады.

Мақала «жасырын» рецензиялаудан өтеді, рецензенттерді журналдың редакиялық алқасы тағайындайды.

Мақаланың соңында авторлардың толық аты-жөнін, кері байланыс мекенжайын, телефондар, факс және электрондық пошта мекенжайын (e-mail) жазуыңызды сұраймыз.

Мақаланың мазмұнына автор (авторлар) жауапты. Ғылыми-редакция алқасының пікірі әрдайым автордың (авторлардың) пікірімен сәйкес келе бермейді. Редакция алқасы мақалаларды жариялау немесе қабылдамау құқығын өзіне қалдырады.

Қайта басылым кезінде біздің жарияланымға сілтеме жасау керек.

Мекенжайымыз: **050000, Алматы қ., Төле би көш., 59, Қазақстан-Британ техникалық университеті.**

Сайт: https://vestnik.kbtu.edu.kz/jour/pages/view/EditorialC Редакция алқасы.

ТРЕБОВАНИЯ К ОФОРМЛЕНИЮ СТАТЕЙ, ПУБЛИКУЕМЫХ В ЖУРНАЛЕ ВЕСТНИК КБТУ

Для публикации принимается **ранее неопубликованный автором (авторами) материал**, соответствующий профилю журнала, на русском, казахском или английском языках. Статья предоставляется в электронном формате (в форматах .doc, .docx,) только путем ее загрузки через функционал сайта журнала (https://vestnik.kbtu.edu.kz/jour/about), в котором имеется подробная инструкция для авторов о процессе подачи статей, а также об оплате публикации.

Обязательные требования по оформлению:

- В левом верхнем углу ставится индекс МРНТИ (Times New Roman 14 размер).
- Через один одинарный интервал ниже фамилии и инициалы авторов полужирным шрифтом. Развернутые названия организаций, городов, стран, где выполнена работа, e-mail одного из авторов. Указать сноски на место работы авторов.
- Ниже через один интервал полное название статьи полужирным шрифтом.
- Ниже через один интервал краткая (150–250 слов) аннотация (abstract). Аннотация должна обрисовывать общую направленность статьи, формулировать ее основные результаты и быть самодостаточной, в ней недопустимы ссылки ни на литературные источники, ни на какие-либо разделы и элементы статьи, к которой она относится.
- Ключевые слова (Key words), относящиеся к представляемой статье.

Текст статьи набирается прямым шрифтом Times New Roman, размер 14. Интервал между строками одинарный. Поля все по 2 см.

Статья должна быть разделена на разделы: Введение, Материалы и методы, Результаты и обсуждение, Заключение, Информация о финансировании (при наличии).

В конце дается «Список литературы (References)». Литературные ссылки в тексте в квадратных скобках [1]. Список литературы оформляется дважды: согласно ГОСТу. Список должен полностью соответствовать основному тексту статьи, содержать все упомянутые (и только упомянутые) в нем работы. Далее тот же список литературы представить в общепринятой английской транслитерации.

Статья проходит «слепое» рецензирование, рецензенты назначаются редколлегией журнала.

В конце статьи просим указать Ф.И.О. полностью, обратный адрес, телефоны, факс, адрес электронной почты (e-mail).

Ответственность за содержание статьи несет автор (авторы). Мнение Научно-редакционного совета не всегда совпадает с мнением автора (авторов). Редакционный совет оставляет за собой право публикации или отклонения статей.

Ссылка на наше издание при перепечатке обязательна.

Наш адрес: **050000, г. Алматы, ул. Толе Би, 59, Казахстанско-Британский технический университет.**

Сайт: https://vestnik.kbtu.edu.kz/jour/pages/view/EditorialC Редакционная коллегия.

ҚАЗАҚСТАН-БРИТАН ТЕХНИКАЛЫҚ УНИВЕРСИТЕТІНІҢ
ХАБАРШЫСЫ

HERALD
OF THE KAZAKH-BRITISH TECHNICAL UNIVERSITY

ВЕСТНИК
КАЗАХСТАНСКО-БРИТАНСКОГО ТЕХНИЧЕСКОГО УНИВЕРСИТЕТА

Ответственный за выпуск
Алагузов Рашид Жуманович

Редакторы
Кабылдаева Толганай Кайсаровна,
Скуратова Ирина Михайловна

Компьютерная верстка
Жуйкова Майя Антоновна

Подписано в печать 19.09.2024 г.
Тираж 300 экз. Формат 60x84 1/16. Бумага
тип. Усл.печ.л. 53,0 Уч.-изд.л. 55,1
Заказ № 34

Редакция журнала «Вестник КБТУ» не несет ответственность за содержание публикуемых статей. Содержания статей целиком принадлежат авторам, и размещаются в журнале исключительно под их ответственность.

Издание Казахстанско-Британского технического университета
Издательский центр КБТУ, Алматы, ул. Толе би, 59